

Safety Data Sheet

Product identifier used on the label: MAG 1 UNIV 2-CYCLE 12/8OZ

Product Code: MAG60138

Revision Date: 04-06-2021

Replaces: 03-08-2021

1. Identification

Product identifier used on the label: MAG 1 UNIV 2-CYCLE 12/8OZ

Product Code: MAG60138

Other means of identification:

Synonyms: No data available

Recommended use of the chemical and restrictions on use:

Recommended use: Two Cycle Engine Oil

Restrictions on use: Uses other than those described above

Name, address, and telephone number Warren Distribution, Inc.

of the chemical manufacturer, 950 S. 10th St., Suite 300

importer, or other responsible party: Omaha, NE 68108-3296

Phone number: +01 (800) 825-1235 +01 (402) 341-9397

E-mail address: sds@wd-wpp.com

Emergency phone number: CHEMTREC: +1 (800) 424-9300 International: +01 (703) 527-3887

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

**GHS Hazard
Symbols:**



GHS Classification:

Germ Cell Mutagenicity Category 1B

Carcinogenicity Category 1A

Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure
Category 1

Signal Word:

Danger

Hazard Statements:

May cause genetic defects; May cause cancer.; Causes damage to organs
through prolonged or repeated exposure

Precautionary Statements:

Prevention:

Obtain special instructions before use. Do not handle until all safety
precautions have been read and understood. Do not breathe

Safety Data Sheet

Product identifier used on the label: MAG 1 UNIV 2-CYCLE 12/8OZ

Product Code: MAG60138

Revision Date: 04-06-2021

Replaces: 03-08-2021

dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

Response:

If exposed or concerned: Get medical advice/attention. Get medical advice/attention if you feel unwell.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazards not otherwise classified:

No data available

3. Composition/information on ingredients

| Chemical Name | Common name and synonyms | CAS # | % |
|---|--------------------------|------------|---------|
| Petroleum distillates, hydrotreated heavy paraffinic | No data available | 64742-54-7 | 65 - 85 |
| Distillates, petroleum, straight-run middle | No data available | 64741-44-2 | 5 - 10 |
| Distillates, petroleum, hydrodesulfurized middle | No data available | 64742-80-9 | 5 - 10 |
| Distillates, petroleum, hydrodesulfurized light catalytic cracked | No data available | 68333-25-5 | 5 - 10 |
| Kerosene | No data available | 8008-20-6 | 5 - 10 |
| Residual oils (petroleum), solvent dewaxed | No data available | 64742-62-7 | 5 - 10 |
| Kerosine, petroleum, hydrodesulfurized | No data available | 64742-81-0 | 1 - 5 |
| Light hydrocracked distillate | No data available | 64741-77-1 | 1 - 5 |
| Distillates, petroleum, solvent-dewaxed heavy paraffinic | No data available | 64742-65-0 | 0.1 - 1 |
| Naphthalene | No data available | 91-20-3 | 0.1 - 1 |

One or more hazardous ingredient(s) is claimed as a trade secret under the OSHA Hazard Communication Standard. The hazards of this (these) ingredient(s) are given on this SDS.

4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin

Safety Data Sheet

Product identifier used on the label: MAG 1 UNIV 2-CYCLE 12/8OZ

Product Code: MAG60138

Revision Date: 04-06-2021

Replaces: 03-08-2021

and eye contact, and ingestion:

Inhalation:

Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately.

Eye Contact:

Flush immediately with large amounts of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Get medical attention if irritation results. Thermal burns require immediate medical attention.

Skin Contact:

Remove contaminated clothing immediately. Wash area of contact thoroughly with soap and water. Get medical attention if irritation persists. High pressure skin injections are serious medical emergencies. Get immediate medical attention. Thermal burns require immediate medical attention.

Ingestion:

Seek medical attention immediately or call the Poison control center. Do not induce vomiting. If patient is fully conscious, give up to two glasses of water. Provide medical care provider with this SDS.

Most important symptoms/effects, acute and delayed:

Causes damage to organs through prolonged or repeated exposure.

Indication of immediate medical attention and special treatment needed, if necessary:

Get medical advice/attention if you feel unwell. If exposed or concerned: Get medical advice/attention.

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media:

Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do not direct a stream of water into the hot burning liquid.

Unsuitable extinguishing media:

No data available

Specific hazards arising from the chemical:

Material may be ignited only if preheated to temperatures above the high flash point, for example in a fire.

Hazardous combustion products:

Carbon dioxide, Carbon monoxide

Special protective equipment and precautions for fire-fighters:

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Use methods for the surrounding fire.

Safety Data Sheet

Product identifier used on the label: MAG 1 UNIV 2-CYCLE 12/8OZ

Product Code: MAG60138

Revision Date: 04-06-2021

Replaces: 03-08-2021

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

No health effects expected from the clean up of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section 8 of this SDS.

Methods and materials for containment and cleaning up:

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material. Gather and store in a sealed container pending a waste disposal evaluation.

7. Handling and storage

Precautions for safe handling:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Conditions for safe storage, including any incompatibilities:

Safe storage conditions:

Store locked up.

Materials to Avoid/Chemical Incompatibility:

Strong oxidizing agents

8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

| Chemical component | OSHA PEL | ACGIH TLV | ACGIH STEL | IDLH |
|--|-------------------------|--|---------------------------|-------------------|
| Petroleum distillates, hydrotreated heavy paraffinic | 5 mg/m ³ TWA | 5 mg/m ³ TWA | 10 mg/m ³ STEL | No data available |
| Kerosene | No PEL | 200 mg/m ³ TWA (application restricted to conditions in which there are negligible aerosol exposures, total hydrocarbon vapor, listed under | No STEL | No data available |

Safety Data Sheet

Product identifier used on the label: MAG 1 UNIV 2-CYCLE 12/80Z

Product Code: MAG60138

Revision Date: 04-06-2021

Replaces: 03-08-2021

| | | | | |
|--|--------------------------------------|--|---------------------------|-------------------|
| | | Kerosene/Jet fuels) | | |
| Kerosine, petroleum, hydrodesulfurized | No PEL | 200 mg/m ³ TWA (application restricted to conditions in which there are negligible aerosol exposures, total hydrocarbon vapor, listed under Kerosene/Jet fuels) | No STEL | No data available |
| Distillates, petroleum, solvent-dewaxed heavy paraffinic | 5 mg/m ³ TWA | 5 mg/m ³ TWA | 10 mg/m ³ STEL | No data available |
| Naphthalene | 10 ppm TWA; 50 mg/m ³ TWA | 10 ppm TWA | No STEL | 250 ppm IDLH |

Appropriate engineering controls:

Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.

Individual protection measures, such as personal protective equipment:

Respiratory Protection:

Do not breathe dust/fume/gas/mist/vapors/spray.

Respirator Type(s):

If airborne concentrations are above the applicable exposure limits, use NIOSH/MSHA approved respiratory protection. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

Eye protection:

Wear safety glasses when handling this product if there is a likelihood of contact with eyes.

Skin protection:

Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

Gloves:

Neoprene, Nitrile

General hygiene conditions:

Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

9. Physical and chemical properties

Safety Data Sheet

Product identifier used on the label: MAG 1 UNIV 2-CYCLE 12/8OZ

Product Code: MAG60138

Revision Date: 04-06-2021

Replaces: 03-08-2021

Appearance (physical state, color etc.):

| | |
|---|-------------------|
| Physical state: | Liquid |
| Color: | Blue |
| Odor: | Mild |
| Odor Threshold: | Not determined |
| pH: | No data available |
| Melting point/freezing point: | |
| Melting Point: | No data available |
| Freezing point: | No data available |
| Initial boiling point and boiling range (°C): | No data available |
| Flash Point (°C): | 218 |
| Evaporation Rate: | No data available |
| Flammability (solid, gas): | No data available |
| Upper/lower flammability or explosive limits: | |
| Upper flammability or explosive limits: | Not established |
| Lower flammability or explosive limits: | Not established |
| Vapor pressure: | > 3 MMHG |
| Vapor density: | 4.42 |
| Relative density: | 0.87 |
| Solubility(ies): | Negligible; 0-1% |
| Partition coefficient: n-octanol/water: | 3.3 |
| Auto-ignition temperature: | No data available |
| Decomposition Temperature: | Not determined |
| Viscosity: | 51.58 |

10. Stability and reactivity

| | |
|-------------------------------------|---|
| Reactivity: | There are no known reactivity hazards associated with this product. |
| Chemical stability: | Stable under normal conditions. |
| Possibility of hazardous reactions: | None expected under standard conditions of storage. |

Safety Data Sheet

Product identifier used on the label: MAG 1 UNIV 2-CYCLE 12/8OZ

Product Code: MAG60138

Revision Date: 04-06-2021

Replaces: 03-08-2021

Conditions to avoid (e.g., static discharge, shock, or vibration):

Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition.
Moisture (will lead to product performance degradation).

Incompatible materials:

Strong oxidizing agents

Hazardous decomposition products:

No data available

11. Toxicological information

Description of the various toxicological (health) effects and the available data used to identify those effects:

Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact):

Inhalation, Ingestion, Skin contact, Eye contact

Symptoms related to the physical, chemical and toxicological characteristics:

Causes damage to organs through prolonged or repeated exposure.

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Ingestion:

No hazard in normal industrial use. Estimated to be > 5.0 g/kg.

Skin Contact:

This material is likely to be moderately irritating to skin based on animal data. Contact may result in defatting, redness, itching, inflammation, cracking, and possible secondary infection. High pressure skin injections are Serious Medical Emergencies. Injury may not appear serious at first; within a few hours, tissue will become swollen, discolored and extremely painful (see Notes to Doctor). Contact with heated material may cause thermal burns.

Absorption:

Estimated to be > 5.0 g/kg; practically non-toxic

Inhalation:

No hazard in normal industrial use. Likely to be practically non-toxic based on animal data.

Eye Contact:

This material is estimated to be non-irritating eyes (Draize score <15 [rabbits]). Exposure to vapors, fumes or mists may cause irritation contact with heated material may cause thermal burns.

Sensitization:

Non-hazardous under Respiratory Sensitization category. No data available to indicate product or components may be a skin sensitizer.

Mutagenicity:

No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

Carcinogenicity:

Contains a substance that is a probable cancer hazard based on animal

Safety Data Sheet

Product identifier used on the label: MAG 1 UNIV 2-CYCLE 12/8OZ

Product Code: MAG60138

Revision Date: 04-06-2021

Replaces: 03-08-2021

Reproductive toxicity

studies using doses likely to be encountered in the workplace.

STOT-single exposure:

Not known or reported to cause reproductive or developmental toxicity.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Classification has been based on toxicological information of the components in Section 3.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Other information:

None known.

Numerical measures of toxicity (such as acute toxicity estimates):

| Chemical Name | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|---|-----------------------------|---------------------------------|---------------------------------------|
| Naphthalene | Oral LD50 Rat 490 mg/kg | Dermal LD50 Rabbit 1120 mg/kg | Inhalation LC50 (1h) Rat > 340 MG/M3 |
| Distillates, petroleum, solvent-dewaxed heavy paraffinic | Oral LD50 Rat > 15000 mg/kg | Dermal LD50 Rabbit > 5000 mg/kg | Inhalation LC50 (4h) Rat > 2400 MG/M3 |
| Light hydrocracked distillate | Oral LD50 Rat 3200 mg/kg | Dermal LD50 Rabbit > 2000 mg/kg | Inhalation LC50 (4h) Rat 4.65 mg/L |
| Kerosine, petroleum, hydrodesulfurized | Oral LD50 Rat > 5000 mg/kg | Dermal LD50 Rabbit > 2000 mg/kg | Inhalation LC50 (4h) Rat > 5200 MG/M3 |
| Residual oils (petroleum), solvent dewaxed | Oral LD50 Rat > 5000 mg/kg | Dermal LD50 Rabbit > 2000 mg/kg | Inhalation LC50 (4h) Rat 2.18 mg/L |
| Kerosene | Oral LD50 Rat > 5000 mg/kg | Dermal LD50 Rabbit > 2000 mg/kg | Inhalation LC50 (4h) Rat > 5.28 mg/L |
| Distillates, petroleum, straight-run middle | Oral LD50 Rat > 5000 mg/kg | Dermal LD50 Rabbit > 2000 mg/kg | Inhalation LC50 (4h) Rat 1.78 mg/L |
| Distillates, petroleum, hydrodesulfurized middle | Oral LD50 Rat > 5000 mg/kg | Dermal LD50 Rabbit > 2000 mg/kg | Inhalation LC50 (4h) Rat 4.6 mg/L |
| Distillates, petroleum, hydrodesulfurized light catalytic cracked | Oral LD50 Rat 3200 mg/kg | Dermal LD50 Rabbit > 2000 mg/kg | Inhalation LC50 (4h) Rat 4.65 mg/L |
| Petroleum distillates, hydrotreated heavy paraffinic | Oral LD50 Rat > 15000 mg/kg | Dermal LD50 Rabbit > 5000 mg/kg | |

Is the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA:

| Chemical Name | OSHA Carcinogen | IARC Carcinogen | NTP Carcinogen |
|---------------|-----------------|-----------------|----------------|
| Naphthalene | Y | Y | Y |

Safety Data Sheet

Product identifier used on the label: MAG 1 UNIV 2-CYCLE 12/8OZ

Product Code: MAG60138

Revision Date: 04-06-2021

Replaces: 03-08-2021

12. Ecological information

Ecotoxicity (aquatic and terrestrial, where available):

Moderate ecological hazard. This product may be dangerous to plants and/or wildlife.

Ecological Toxicity Data:

| Chemical Name | CAS # | Aquatic EC50 Crustacea | Aquatic ERC50 Algae | Aquatic LC50 Fish |
|---|------------|--------------------------------------|---------------------|---|
| Naphthalene | 91-20-3 | EC50 (48h) Daphnia magna 2.16 mg/L | No data available | LC50 (96h) Rainbow Trout 1.6 mg/L |
| Distillates, petroleum, solvent-dewaxed heavy paraffinic | 64742-65-0 | EC50 (48h) Daphnia magna > 1000 mg/L | No data available | LC50 (96h) Rainbow Trout > 5000 mg/L |
| Light hydrocracked distillate | 64741-77-1 | No data available | No data available | LC50 (96h) BRACHYDANIO RERIO 7.3 mg/L |
| Kerosine, petroleum, hydrodesulfurized | 64742-81-0 | EC50 (48h) 4720 mg/L | No data available | LC50 (96h) 45 mg/L |
| Residual oils (petroleum), solvent dewaxed | 64742-62-7 | EC50 (48h) Daphnia magna > 1000 mg/L | No data available | LC50 (96h) Rainbow Trout > 5000 mg/L |
| Distillates, petroleum, hydrodesulfurized light catalytic cracked | 68333-25-5 | No data available | No data available | LC50 (96h) BRACHYDANIO RERIO 7.3 mg/L |
| Distillates, petroleum, hydrodesulfurized middle | 64742-80-9 | No data available | No data available | LC50 (96h) Pimephales promelas (Fathead Minnow) 35 mg/L |
| Petroleum distillates, hydrotreated heavy paraffinic | 64742-54-7 | EC50 (48h) Daphnia magna > 1000 mg/L | No data available | LC50 (96h) Rainbow Trout > 5000 mg/L |

Persistence and degradability:

Biodegrades slowly.

Bioaccumulative potential:

Bioconcentration may occur.

Mobility in soil:

This material is expected to have essentially no mobility in soil. It absorbs strongly to most soil types.

Other adverse effects (such as hazardous to the ozone layer):

None known.

Safety Data Sheet

Product identifier used on the label: MAG 1 UNIV 2-CYCLE 12/8OZ

Product Code: MAG60138

Revision Date: 04-06-2021

Replaces: 03-08-2021

13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging:

Dispose of contents and container in accordance with local/regional/national/international regulations.

Contaminated packaging:

Recycle containers whenever possible.

14. Transport information

Carriage of dangerous goods by road (DOT), rail or inland waterways:

DOT Basic Description:

Not regulated for road transport

International carriage of dangerous goods by sea (IMDG/IMO):

UN number:

Not regulated by IMDG

UN Proper shipping name:

Not applicable

Transport hazard class(es):

Not applicable

Packing group, if applicable:

Not applicable

International carriage of dangerous goods by air (IATA):

UN number:

Not regulated by IATA

UN Proper shipping name:

Not applicable

Transport hazard class(es):

Not applicable

Packing group, if applicable:

Not applicable

Environmental hazards (e.g., Marine pollutant (Yes/No)):

None.

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):

No data available

Special precautions which a user needs to be aware of or needs to comply with in connection with transport or conveyance either within or outside their premises:

No data available

Safety Data Sheet

Product identifier used on the label: MAG 1 UNIV 2-CYCLE 12/8OZ

Product Code: MAG60138

Revision Date: 04-06-2021

Replaces: 03-08-2021

15. Regulatory information

Safety, health and environmental regulations specific for the product in question:

TSCA Status:

All components of this material are on the Active US TSCA Inventory or are exempt.

Regulated Components:

| Chemical Name | CAS # | CERCLA | Sara EHS | Sara 313 | U.S. HAP |
|---|------------|--------|----------|----------|----------|
| Petroleum distillates, hydrotreated heavy paraffinic | 64742-54-7 | N | N | N | N |
| Distillates, petroleum, straight-run middle | 64741-44-2 | N | N | N | N |
| Distillates, petroleum, hydrodesulfurized light catalytic cracked | 68333-25-5 | N | N | N | N |
| Distillates, petroleum, hydrodesulfurized middle | 64742-80-9 | N | N | N | N |
| Kerosene | 8008-20-6 | N | N | N | N |
| Residual oils (petroleum), solvent dewaxed | 64742-62-7 | N | N | N | N |
| Kerosine, petroleum, hydrodesulfurized | 64742-81-0 | N | N | N | N |
| Light hydrocracked distillate | 64741-77-1 | N | N | N | N |
| Distillates, petroleum, solvent-dewaxed heavy paraffinic | 64742-65-0 | N | N | N | N |
| Naphthalene | 91-20-3 | Y | N | Y | Y |

| Chemical Name | CAS # | California Prop 65 - Cancer | California Prop 65 - Dev. Toxicity | California Prop 65 - Reprod fem | California Prop 65 - Reprod male |
|---|------------|-----------------------------|------------------------------------|---------------------------------|----------------------------------|
| Petroleum distillates, hydrotreated heavy | 64742-54-7 | N | N | N | N |

Safety Data Sheet

Product identifier used on the label: MAG 1 UNIV 2-CYCLE 12/8OZ

Product Code: MAG60138

Revision Date: 04-06-2021

Replaces: 03-08-2021

| | | | | | |
|--|------------|---|---|---|---|
| paraffinic | | | | | |
| Distillates, petroleum, straight- run middle | 64741-44-2 | N | N | N | N |
| Distillates, petroleum, hydrodesulfurized light catalytic cracked | 68333-25-5 | N | N | N | N |
| Distillates, petroleum, hydrodesulfurized middle | 64742-80-9 | N | N | N | N |
| Kerosene | 8008-20-6 | N | N | N | N |
| Residual oils (petroleum), solvent dewaxed | 64742-62-7 | N | N | N | N |
| Kerosine, petroleum, hydrodesulfurized | 64742-81-0 | N | N | N | N |
| Light hydrocracked distillate | 64741-77-1 | N | N | N | N |
| Distillates, petroleum, solvent- dewaxed heavy paraffinic | 64742-65-0 | N | N | N | N |
| Naphthalene | 91-20-3 | Y | N | N | N |

| Chemical Name | CAS # | Massachusetts RTK List | New Jersey RTK List | Pennsylvania RTK List | Rhode Island RTK List | Minnesota Hazardous Substance List |
|--|------------|---------------------------|------------------------|--------------------------|-----------------------------|---|
| Petroleum distillates, hydrotreated heavy paraffinic | 64742-54-7 | N | N | N | N | N |
| Distillates, petroleum, straight- run middle | 64741-44-2 | N | N | N | N | N |
| Distillates, petroleum, hydrodesulfurized light catalytic cracked | 68333-25-5 | N | N | N | N | N |

Safety Data Sheet

Product identifier used on the label: MAG 1 UNIV 2-CYCLE 12/8OZ

Product Code: MAG60138

Revision Date: 04-06-2021

Replaces: 03-08-2021

| | | | | | | |
|--|------------|---|---|---|---|---|
| Distillates, petroleum, hydrodesulfurized middle | 64742-80-9 | N | N | N | N | N |
| Kerosene | 8008-20-6 | Y | Y | Y | N | N |
| Residual oils (petroleum), solvent dewaxed | 64742-62-7 | N | N | N | N | N |
| Kerosine, petroleum, hydrodesulfurized | 64742-81-0 | N | N | N | N | N |
| Light hydrocracked distillate | 64741-77-1 | N | N | N | N | N |
| Distillates, petroleum, solvent-dewaxed heavy paraffinic | 64742-65-0 | N | N | N | N | N |
| Naphthalene | 91-20-3 | Y | Y | Y | N | Y |

16. Other information, including date of preparation or last revision.

SDS Prepared by: CDURSTON

Revision Date: 04-06-2021

Revision Number: 30

Reason for revision: Activated by Document Formulation Generation

References: No data available

Other Info: No data available

Disclaimer: This safety data sheet and the information it contains is offered to you in good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct, but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either expressed or implied.