

acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

SECTION 1: Identification

1.1 Product identifier

Trade name STP Super Concentrated Fuel Injector Cleaner -

bottle

Alternative number(s) 071153172418, 071153175631, 071153785779,

071153785755, 071153785946, 067788171117,

067788171193

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses General use

1.3 Details of the supplier of the safety data sheet

Energizer Manufacturing, Inc. 25225 Detroit Rd. Westlake OH 44145 United States

Telephone: 800-383-7323; 314-985-2000 (USA / CANADA)

Website: http://data.energizer.com

Energizer Trading Ltd.

Sword House, Totteridge Road, High Wycombe, HP13 6DG, UK

Telephone: +44(0)8000353376

e-mail: ConsumerServiceEU@energizer.com

1.4 Emergency telephone number

Emergency information service 1-314-985-1511 Int'l: 1-800-526-4727

This number is only available during the following

office hours: Mon-Fri 09:00 AM - 05:00 PM

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard state- ment
A.1I	acute toxicity (inhal.)	3	Acute Tox. 3	H331
A.5	germ cell mutagenicity	1B	Muta. 1B	H340
A.6	carcinogenicity	1A	Carc. 1A	H350
A.7	reproductive toxicity	2	Repr. 2	H361d

United States: en Page: 1 / 37



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Revision: 2021-01-05 Version number: 10.0 Replaces version of: 2020-12-10 (9)

Section	Hazard class	Category	Hazard class and category	Hazard state- ment
A.10	aspiration hazard	1	Asp. Tox. 1	H304
B.6	flammable liquid	3	Flam. Liq. 3	H226

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects The product is combustible and can be ignited by potential ignition sources.

2.2 **Label elements**

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS02, GHS06, GHS08







- Hazard statements

H226 Flammable liquid and vapor.

May be fatal if swallowed and enters airways. H304

H331 Toxic if inhaled.

H340 May cause genetic defects.

H350 May cause cancer.

H361d Suspected of damaging the unborn child.

- Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing mist/vapors.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/eye protection/face protection. P301+P310 If swallowed: Immediately call a poison center/doctor.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P311 Call a poison center/doctor.

Specific treatment (see on this label). P321

Do NOT induce vomiting. P331

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

United States: en Page: 2 / 37



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

- Precautionary statements

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with national regulations.

2.2.1.7 - Hazardous ingredients for labelling

Distillates (petroleum), hydrodesulfurized middle, Kerosene, toluene, benzene

2.3 Other hazards

Hazards not otherwise classified

May be harmful in contact with skin (GHS category 5: acutely toxic - dermal).

Toxic to aquatic life with long lasting effects (GHS category 2: aquatic toxicity - acute and/or chronic).

SECTION 3: Composition/information on ingredients

3.1 Substances


Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Straight-run Kerosene	CAS No 64741-44-2	10-<25	Acute Tox. 4 / H332 Flam. Liq. 3 / H226	♦ (!>
Distillates (petroleum), hy- drodesulfurized middle	CAS No 64742-80-9	10-<25	Acute Tox. 4 / H332 Carc. 1B / H350 Flam. Liq. 3 / H226	
Distillates (petroleum), hy- drodesulfurized light cata- lytic cracked	CAS No 68333-25-5	10 - < 25	Acute Tox. 4 / H332 Carc. 1B / H350 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	
Kerosene	CAS No 8008-20-6	10-<25	Acute Tox. 3 / H331 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	
Kerosine (petroleum), hy- drodesulfurized	CAS No 64742-81-0	5-<10	Acute Tox. 3 / H331 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	
Distillates (petroleum), light hydrocracked	CAS No 64741-77-1	1-<5	Acute Tox. 3 / H331 Carc. 2 / H351 Flam. Liq. 3 / H226	

United States: en Page: 3 / 37





STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Solvent naphtha (petro- leum), light arom.	CAS No 64742-95-6	1-<5	Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Flam. Liq. 1 / H224	
1,2,4 trimethlybenzene	CAS No 95-63-6	1-<5	Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	
benzene	CAS No 71-43-2	<1	Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Muta. 1B / H340 Carc. 1A / H350 STOT RE 1 / H372 Asp. Tox. 1 / H304 Flam. Liq. 2 / H225	
ethylbenzene	CAS No 100-41-4	<1	Acute Tox. 4 / H332 Carc. 2 / H351 STOT RE 2 / H373 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	(3) (1) (3)
cumene	CAS No 98-82-8	<1	Carc. 2 / H351 STOT SE 3 / H335 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	(3) (1) (3)
naphthalene	CAS No 91-20-3	<1	Acute Tox. 4 / H302 Acute Tox. 1 / H330 Carc. 2 / H351 STOT SE 2 / H371 STOT RE 2 / H373	
2-ethylhexan-1-ol	CAS No 104-76-7	<1	Acute Tox. 2 / H330 Flam. Liq. 4 / H227	
toluene	CAS No 108-88-3	<1	Acute Tox. 1 / H330 Skin Irrit. 2 / H315 Repr. 2 / H361d STOT SE 3 / H336 STOT RE 2 / H373 Asp. Tox. 1 / H304 Flam. Liq. 2 / H225	

For full text of abbreviations: see SECTION 16.

United States: en Page: 4 / 37



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

United States: en Page: 5 / 37



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

United States: en Page: 6 / 37

Energizer.

Holdings, Inc.

acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Keep any substance that emits harmful vapors or gases in a place that allows these to be permanently extracted. Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m³]	Nota tion	Sourc e
US	hydrocarbon mixture (RCP method)		TLV		100		200				AC- GIH® 2016
US	ethylbenzene	100-41-4	PEL (CA)	5	22	30	130				Cal/ OSHA PEL
US	ethylbenzene	100-41-4	REL	100 (10 h)	435 (10 h)	125	545				NIOSH REL
US	ethylbenzene	100-41-4	TLV®	20							AC- GIH® 2019

United States: en Page: 7 / 37



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m³]	Nota tion	Sourc e
US	ethylbenzene	100-41-4	PEL	100	435						29 CFR 1910.1 000
US	toluene	108-88-3	REL	100 (10 h)	375 (10 h)	150	560				NIOSH REL
US	toluene	108-88-3	TLV®	20							AC- GIH® 2019
US	toluene	108-88-3	PEL	200		500 (10 min)		300			29 CFR 1910.1 000
US	toluene (toluol)	108-88-3	PEL (CA)	10	37	150	560	500			Cal/ OSHA PEL
US	Kerosine - unspe- cified	64742- 81-0	TLV®		200					vap, Hy- Carb	AC- GIH® 2019
US	benzene	71-43-2	PEL (CA)	1		5					Cal/ OSHA PEL
US	benzene	71-43-2	TLV®	0.5		2.5					AC- GIH® 2019
US	benzene	71-43-2	PEL	1		5					29 CFR 1910.1 000
US	benzene	71-43-2	REL	0.1 (10 h)		1				аррх- А	NIOSH REL
US	benzene	71-43-2	PEL	10		50 (10 min)		25		us- pel- z2a	29 CFR 1910.1 000
US	Kerosine (petro- leum)	8008-20- 6	REL		100 (10 h)						NIOSH REL
US	Kerosine (petro- leum) (jet fuels, JP 5)	8008-20- 6	TLV®		200					vap, Hy- Carb	AC- GIH® 2019
US	naphthalene	91-20-3	PEL (CA)	0.1	0.5						Cal/ OSHA PEL

United States: en Page: 8 / 37



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m³]	Nota tion	Sourc e
US	naphthalene	91-20-3	REL	10 (10 h)	50 (10 h)	15	75				NIOSH REL
US	naphthalene	91-20-3	TLV®	10							AC- GIH® 2019
US	naphthalene	91-20-3	PEL	10	50						29 CFR 1910.1 000
US	1,2,4-trimethyl- benzene	95-63-6	REL	25 (10 h)	125 (10 h)						NIOSH REL
US	C9-C15 aromatics	95-63-6	TLV®		100						AC- GIH® 2019
US	cumene	98-82-8	REL	50 (10 h)	245 (10 h)						NIOSH REL
US	cumene	98-82-8	TLV®	50							AC- GIH® 2019
US	cumene	98-82-8	PEL	50	245						29 CFR 1910.1 000
US	cumene (isopro- pylbenzene)	98-82-8	PEL (CA)	50	245						Cal/ OSHA PEL

Notation

NIOSH Potential Occupational Carcinogen (Appendix A) аррх-А

Ceiling-C ceiling value is a limit value above which exposure should not occur

HyCarb calculated as hydrocarbons

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period SŤEL

(unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours timeweighted average (unless otherwise specified

us-pel-z2a This standard applies to the industry segments exempt from the 1 ppm 8-hour TWA and 5 ppm STEL of the benzene standard

at 1910.1028.

vap as vapors

United States: en Page: 9 / 37



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

Biological limit values

Country	Name of agent	Parameter	Nota- tion	Identifier	Value	Source
US	ethylbenzene	mandelic acid, benzoyl- formic acid	crea	BEI®	0.15 g/g	ACGIH® 2019
US	toluene	toluene		BEI®	0.02 mg/l	ACGIH® 2019
US	toluene	toluene		BEI®	0.03 mg/l	ACGIH® 2019
US	toluene	o-cresol	hydr, crea	BEI®	0.3 mg/g	ACGIH® 2019
US	benzene	S-phenylmercapturic acid	crea	BEI®	25 μg/g	ACGIH® 2019
US	benzene	trans,trans-muconic acid	crea	BEI®	500 μg/g	ACGIH® 2019

Notation

crea creatinine hydr hydrolysis

Relevant DNELs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Protection goal, route of expos- ure	Used in	Exposure time
Straight-run Ker- osene	64741-44-2	DNEL	16.4 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
Straight-run Ker- osene	64741-44-2	DNEL	1,501 mg/ m³	human, inhalatory	worker (industry)	acute - systemic ef- fects
Straight-run Ker- osene	64741-44-2	DNEL	2.91 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Distillates (petro- leum), hydrodesul- furized light catalyt- ic cracked	68333-25-5	DNEL	27.3 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Distillates (petro- leum), hydrodesul- furized light catalyt- ic cracked	68333-25-5	DNEL	2,230 mg/ m ³	human, inhalatory	worker (industry)	acute - systemic ef- fects
Distillates (petro- leum), hydrodesul- furized light catalyt- ic cracked	68333-25-5	DNEL	2.4 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

United States: en Page: 10 / 37

acc. to 29 CFR 1910.1200 App D



STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

Relevant DNELs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Protection goal, route of expos- ure	Used in	Exposure time
Distillates (petro- leum), light hydro- cracked	64741-77-1	DNEL	68.34 mg/ m³	human, inhalatory	worker (industry)	chronic - systemic effects
Distillates (petro- leum), light hydro- cracked	64741-77-1	DNEL	4,288 mg/ m³	human, inhalatory	worker (industry)	acute - systemic ef- fects
Distillates (petro- leum), light hydro- cracked	64741-77-1	DNEL	2.91 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
1,2,4 trimethlyben- zene	95-63-6	DNEL	100 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
1,2,4 trimethlyben- zene	95-63-6	DNEL	100 mg/m ³	human, inhalatory	worker (industry)	acute - systemic ef- fects
1,2,4 trimethlyben- zene	95-63-6	DNEL	100 mg/m ³	human, inhalatory	worker (industry)	chronic - local ef- fects
1,2,4 trimethlyben- zene	95-63-6	DNEL	100 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
1,2,4 trimethlyben- zene	95-63-6	DNEL	16,171 mg/ kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
naphthalene	91-20-3	DNEL	25 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
naphthalene	91-20-3	DNEL	25 mg/m³	human, inhalatory	worker (industry)	chronic - local ef- fects
naphthalene	91-20-3	DNEL	3.57 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
cumene	98-82-8	DNEL	100 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
cumene	98-82-8	DNEL	250 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
cumene	98-82-8	DNEL	15.4 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
2-ethylhexan-1-ol	104-76-7	DNEL	12.8 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2-ethylhexan-1-ol	104-76-7	DNEL	53.2 mg/m³	human, inhalatory	worker (industry)	chronic - local ef- fects
2-ethylhexan-1-ol	104-76-7	DNEL	53.2 mg/m³	human, inhalatory	worker (industry)	acute - local effects

United States: en Page: 11 / 37



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)


Relevant DNELs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Protection goal, route of expos- ure	Used in	Exposure time
2-ethylhexan-1-ol	104-76-7	DNEL	23 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
toluene	108-88-3	DNEL	192 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
toluene	108-88-3	DNEL	384 mg/m³	human, inhalatory	worker (industry)	acute - systemic ef- fects
toluene	108-88-3	DNEL	192 mg/m³	human, inhalatory	worker (industry)	chronic - local ef- fects
toluene	108-88-3	DNEL	384 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
toluene	108-88-3	DNEL	384 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
ethylbenzene	100-41-4	DNEL	77 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
ethylbenzene	100-41-4	DNEL	293 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
ethylbenzene	100-41-4	DNEL	180 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time
1,2,4 trimethlyben- zene	95-63-6	PNEC	0.12 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)
1,2,4 trimethlyben- zene	95-63-6	PNEC	0.12 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)
1,2,4 trimethlyben- zene	95-63-6	PNEC	2.41 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
1,2,4 trimethlyben- zene	95-63-6	PNEC	13.56 ^{mg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
1,2,4 trimethlyben- zene	95-63-6	PNEC	13.56 ^{mg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)
1,2,4 trimethlyben- zene	95-63-6	PNEC	2.34 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
cumene	98-82-8	PNEC	0.035 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)

United States: en Page: 12 / 37





STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

Relevant PNECs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time
cumene	98-82-8	PNEC	0.004 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)
cumene	98-82-8	PNEC	200 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
cumene	98-82-8	PNEC	3.22 ^{mg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
cumene	98-82-8	PNEC	0.322 ^{mg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)
cumene	98-82-8	PNEC	0.624 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
2-ethylhexan-1-ol	104-76-7	PNEC	0.017 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)
2-ethylhexan-1-ol	104-76-7	PNEC	0.002 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)
2-ethylhexan-1-ol	104-76-7	PNEC	10 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
2-ethylhexan-1-ol	104-76-7	PNEC	0.284 ^{mg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
2-ethylhexan-1-ol	104-76-7	PNEC	0.028 ^{mg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)
2-ethylhexan-1-ol	104-76-7	PNEC	0.047 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
toluene	108-88-3	PNEC	0.68 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)
toluene	108-88-3	PNEC	0.68 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)
toluene	108-88-3	PNEC	13.61 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
toluene	108-88-3	PNEC	16.39 ^{mg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
toluene	108-88-3	PNEC	16.39 ^{mg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)
toluene	108-88-3	PNEC	2.89 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
benzene	71-43-2	PNEC	1.9 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)

United States: en Page: 13 / 37



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

Relevant PNECs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time
benzene	71-43-2	PNEC	1.9 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)
benzene	71-43-2	PNEC	39 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
benzene	71-43-2	PNEC	33 ^{mg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
benzene	71-43-2	PNEC	33 ^{mg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)
benzene	71-43-2	PNEC	4.8 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
ethylbenzene	100-41-4	PNEC	0.1 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)
ethylbenzene	100-41-4	PNEC	0.01 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)
ethylbenzene	100-41-4	PNEC	9.6 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
ethylbenzene	100-41-4	PNEC	13.7 ^{mg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
ethylbenzene	100-41-4	PNEC	1.37 ^{mg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)
ethylbenzene	100-41-4	PNEC	2.68 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

United States: en Page: 14 / 37



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	various
Odor	characteristic

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	≥-20 °C at 101.3 kPa
Flash point	44 °C
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)

Explosive limits

- Lower explosion limit (LEL)	1.4 vol%
- Upper explosion limit (UEL)	7.6 vol%

United States: en Page: 15 / 37

Energizer.

acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

Vapor pressure	≤240 kPa at 37.8 °C
Density	not determined
Vapor density	this information is not available
Relative density	Information on this property is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available	
Auto-ignition temperature	220 °C (auto-ignition temperature (liquids and gases))	
Viscosity	not determined	
Explosive properties	none	
Oxidizing properties	none	

9.2 Other information

Temperature class (USA, acc. to NEC 500)	T2D (maximum permissible surface temperature on the equip-	
	ment: 215°C)	

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

United States: en Page: 16 / 37



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Toxic if inhaled.

GHS of the United Nations, annex 4: May be harmful in contact with skin.

- Acute toxicity estimate (ATE)

Inhalation: gas 4,031 ppmV/_{4h} Inhalation: vapor 7.458 mg/₁/₄h

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
Straight-run Kerosene	64741-44-2	inhalation: vapor	11 ^{mg} / _l /4h
Straight-run Kerosene	64741-44-2	64741-44-2 inhalation: dust/mist	
Distillates (petroleum), hydrodesulfurized middle	64742-80-9	inhalation: vapor	11 ^{mg} / _l /4h
Distillates (petroleum), hydrodesulfurized middle	64742-80-9 inhalation: dust/mist		4.6 ^{mg} / _l /4h
Kerosene	8008-20-6	inhalation: vapor	5.28 ^{mg} / _l /4h
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	inhalation: vapor	11 ^{mg} / _l /4h
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	inhalation: dust/mist	4.65 ^{mg} / _l /4h
Kerosine (petroleum), hydrodesulfurized	64742-81-0	inhalation: vapor	5.28 ^{mg} / _l /4h

United States: en Page: 17 / 37



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Revision: 2021-01-05 Version number: 10.0 Replaces version of: 2020-12-10 (9)

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
Distillates (petroleum), light hydrocracked	64741-77-1 inhalation: vapor		3.6 ^{mg} / _l /4h
1,2,4 trimethlybenzene	95-63-6	inhalation: vapor	11 ^{mg} / _l /4h
naphthalene	91-20-3	oral	710 ^{mg} / _{kg}
naphthalene	91-20-3	inhalation: vapor	0.4 ^{mg} / _l /4h
naphthalene	91-20-3	inhalation: dust/mist	0.005 ^{mg} / _l /4h
2-ethylhexan-1-ol	104-76-7	inhalation: vapor	0.89 ^{mg} / _l /4h
toluene	108-88-3	inhalation: gas	7.6 ^{ppmV} / _{4h}
ethylbenzene	100-41-4	inhalation: vapor	11 ^{mg} / _l /4h

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

May cause genetic defects.

Carcinogenicity

May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
benzene	71-43-2	1	
ethylbenzene	100-41-4	2B	
cumene	98-82-8	2B	
naphthalene	91-20-3	2B	
toluene	108-88-3	3	

Legend

Carcinogenic to humans

2B 3 Possibly carcinogenic to humans

Not classifiable as to carcinogenicity in humans

United States: en Page: 18 / 37



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

National Toxicology Program (United States): Report on Carcinogens

Name of substance	CAS No	Classification	Number
benzene	71-43-2	Known to be a hu- man carcinogen	1st Report on Carcinogens
cumene	98-82-8	Reasonably anticip- ated to be a human carcinogen	13th Report on Carcinogens
naphthalene	91-20-3	Reasonably anticip- ated to be a human carcinogen	11th Report on Carcinogens

29 CFR 1910/1915/1926 Occupational Safety and Health Standards: Toxic and Hazardous Substances (carcinogens)

Name of substance	CAS No	Type of registration
benzene	71-43-2	GI §1910.1028, SE §1915.1028, CI §1926.1128

Legend

 CI §1926.1128
 Construction Industry (29 CFR 1926.1128)§us_oshacarc_1_2017

 GI §1910.1028
 General Industry (29 CFR 1910.1028)§us_oshacarc_1_2017

 SE §1915.1028
 Shipyard Employment (29 CFR 1915.1028)§us_oshacarc_1_2017

Reproductive toxicity

Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Straight-run Kerosene	64741-44-2	LL50	>100 ^{mg} / _l	fish	24 h

United States: en Page: 19 / 37





STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Straight-run Kerosene	64741-44-2	EL50	>1,000 ^{mg} / _l	aquatic invertebrates	24 h
Distillates (petroleum), hydrodesulfurized middle	64742-80-9	LL50	>100 ^{mg} / _l	fish	24 h
Distillates (petroleum), hydrodesulfurized middle	64742-80-9	EL50	>1,000 ^{mg} /	aquatic invertebrates	24 h
Kerosene	8008-20-6	LL50	5 ^{mg} / _l	fish	96 h
Kerosene	8008-20-6	EL50	1.4 ^{mg} / _l	aquatic invertebrates	48 h
Kerosene	8008-20-6	LOEL	1 ^{mg} / _l	algae	72 h
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	LL50	>0.3 ^{mg} / _I	fish	96 h
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	LC50	>0.21 ^{mg} / _l	fish	96 h
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	EL50	0.32 ^{mg} / _l	aquatic invertebrates	48 h
Kerosine (petroleum), hydrodesulfurized	64742-81-0	LL50	5 ^{mg} / _l	fish	96 h
Kerosine (petroleum), hydrodesulfurized	64742-81-0	EL50	1.4 ^{mg} / _l	aquatic invertebrates	48 h
Kerosine (petroleum), hydrodesulfurized	64742-81-0	LOEL	1 ^{mg} / _l	algae	72 h
Distillates (petroleum), light hydrocracked	64741-77-1	LL50	>100 ^{mg} / _l	fish	24 h
Distillates (petroleum), light hydrocracked	64741-77-1	EL50	180 ^{mg} / _l	aquatic invertebrates	24 h
Solvent naphtha (petro- leum), light arom.	64742-95-6	LL50	8.2 ^{mg} / _l	fish	96 h
Solvent naphtha (petro- leum), light arom.	64742-95-6	EL50	4.5 ^{mg} / _l	aquatic invertebrates	48 h
1,2,4 trimethlybenzene	95-63-6	LC50	7.72 ^{mg} / _l	fish	96 h
1,2,4 trimethlybenzene	95-63-6	EC50	2.356 ^{mg} / _l	algae	96 h

United States: en Page: 20 / 37

acc. to 29 CFR 1910.1200 App D



STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
naphthalene	91-20-3	LC50	1.6 ^{mg} / _l	fish	96 h
naphthalene	91-20-3	EC50	2.16 ^{mg} / _l	aquatic invertebrates	48 h
cumene	98-82-8	LC50	4.7 ^{mg} / _I	fish	96 h
cumene	98-82-8	EC50	2.14 ^{mg} / _l	aquatic invertebrates	48 h
cumene	98-82-8	ErC50	2.01 ^{mg} / _l	algae	72 h
cumene	98-82-8	NOEC	<2.9 ^{mg} / _l	fish	96 h
cumene	98-82-8	growth (EbCx) 10%	1.3 ^{mg} / _l	aquatic invertebrates	48 h
cumene	98-82-8	growth rate (ErCx) 10%	1.35 ^{mg} / _l	algae	72 h
2-ethylhexan-1-ol	104-76-7	LC50	17.1 ^{mg} / _l	fish	96 h
2-ethylhexan-1-ol	104-76-7	EC50	39 ^{mg} / _l	aquatic invertebrates	48 h
2-ethylhexan-1-ol	104-76-7	ErC50	16.6 ^{mg} / _l	algae	72 h
2-ethylhexan-1-ol	104-76-7	NOEC	14 ^{mg} / _l	fish	96 h
2-ethylhexan-1-ol	104-76-7	growth (EbCx) 10%	3.2 ^{mg} / _l	algae	72 h
2-ethylhexan-1-ol	104-76-7	growth rate (ErCx) 10%	5.3 ^{mg} / _l	algae	72 h
toluene	108-88-3	LC50	5.5 ^{mg} / _l	fish	96 h
toluene	108-88-3	EC50	84 ^{mg} / _l	microorganisms	24 h
benzene	71-43-2	LC50	5.3 ^{mg} / _l	fish	96 h
benzene	71-43-2	EC50	10 ^{mg} / _l	aquatic invertebrates	24 h
benzene	71-43-2	ErC50	100 ^{mg} / _l	algae	72 h
benzene	71-43-2	growth (EbCx) 10%	10 ^{mg} / _l	algae	72 h
benzene	71-43-2	growth rate (ErCx) 10%	34 ^{mg} / _l	algae	72 h
ethylbenzene	100-41-4	LC50	7 ^{mg} / _l	fish	24 h
ethylbenzene	100-41-4	EC50	2.4 ^{mg} / _l	aquatic invertebrates	48 h

United States: en Page: 21 / 37

acc. to 29 CFR 1910.1200 App D



STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
ethylbenzene	100-41-4	NOEC	3.3 ^{mg} / _l	fish	96 h

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Straight-run Kerosene	64741-44-2	EL50	>1,000 ^{mg} / _l	microorganisms	40 h
Distillates (petroleum), hydrodesulfurized middle	64742-80-9	EL50	>1,000 ^{mg} / _l	microorganisms	40 h
Kerosene	8008-20-6	EL50	0.89 ^{mg} / _l	aquatic invertebrates	21 d
Kerosene	8008-20-6	LOEL	1.2 ^{mg} / _l	aquatic invertebrates	21 d
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	EL50	0.22 ^{mg} / _l	aquatic invertebrates	21 d
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	EC50	0.17 ^{mg} / _l	aquatic invertebrates	21 d
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	NOEC	0.038 ^{mg} / _l	aquatic invertebrates	21 d
Kerosine (petroleum), hydrodesulfurized	64742-81-0	EL50	0.89 ^{mg} / _l	aquatic invertebrates	21 d
Kerosine (petroleum), hydrodesulfurized	64742-81-0	LOEL	1.2 ^{mg} / _l	aquatic invertebrates	21 d
Distillates (petroleum), light hydrocracked	64741-77-1	EL50	>1,000 ^{mg} / _l	microorganisms	40 h
Solvent naphtha (petro- leum), light arom.	64742-95-6	EL50	10 ^{mg} / _l	fish	21 d
Solvent naphtha (petro- leum), light arom.	64742-95-6	EC50	15.41 ^{mg} / _l	microorganisms	40 h
naphthalene	91-20-3	EC50	2.96 ^{mg} / _l	algae	4 h
naphthalene	91-20-3	NOEC	0.37 ^{mg} / _l	fish	40 d
naphthalene	91-20-3	LOEC	0.38 ^{mg} / _l	fish	40 d
cumene	98-82-8	EC50	1.5 ^{mg} / _l	aquatic invertebrates	21 d

United States: en Page: 22 / 37



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
cumene	98-82-8	LC50	>3 ^{mg} / _l	aquatic invertebrates	21 d
cumene	98-82-8	NOEC	0.38 ^{mg} / _l	fish	28 d
cumene	98-82-8	growth (EbCx) 10%	0.6 ^{mg} / _l	aquatic invertebrates	21 d
toluene	108-88-3	LC50	3.78 ^{mg} / _l	aquatic invertebrates	2 d
toluene	108-88-3	EC50	3.23 ^{mg} / _l	aquatic invertebrates	7 d
toluene	108-88-3	LOEC	2.77 ^{mg} / _l	fish	40 d
toluene	108-88-3	NOEC	1.39 ^{mg} / _l	fish	40 d
benzene	71-43-2	LOEC	1.6 ^{mg} / _l	fish	32 d
ethylbenzene	100-41-4	LC50	3.6 ^{mg} / _l	aquatic invertebrates	7 d
ethylbenzene	100-41-4	LOEL	1.7 ^{mg} / _l	aquatic invertebrates	7 d
ethylbenzene	100-41-4	NOEC	0.96 ^{mg} / _l	aquatic invertebrates	7 d
ethylbenzene	100-41-4	LOEC	1.7 ^{mg} / _l	aquatic invertebrates	7 d

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

United States: en Page: 23 / 37



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 L	JN I	num	ber
--------	------	-----	-----

DOT	1268
IMDG-Code	1268
ICAO-TI	1268

14.2 UN proper shipping name

DOT	Petroleum distillates, n.o.s.
IMDG-Code	PETROLEUM DISTILLATES, N.O.S.
ICAO-TI	Petroleum distillates, n.o.s.

14.3 Transport hazard class(es)

DOT	3
IMDG-Code	3
ICAO-TI	3

14.4 Packing group

DOT	III
IMDG-Code	III
ICAO-TI	III

14.5 Environmental hazards hazardous to the aquatic environment

Environmentally hazardous substance (aquatic

environment)

United States: en Page: 24 / 37

Kerosene



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration UN1268, Petroleum distillates, n.o.s., (contains:

Straight-run Kerosene, Distillates (petroleum), hydrodesulfurized middle), 3, III, environmentally

hazardous

Reportable quantity (RQ) 5,303 lbs (2,408 kg) (benzene) (naphthalene)

Danger label(s) 3, fish and tree





Environmental hazards Yes (hazardous to the aquatic environment)

Special provisions (SP) 144, B1, IB3, T4, TP1, TP29

ERG No 128

International Maritime Dangerous Goods Code (IMDG) - Additional information

Particulars in the shipper's declaration UN1268, PETROLEUM DISTILLATES, N.O.S., (con-

tains: Straight-run Kerosene, Distillates

(petroleum), hydrodesulfurized middle), 3, III, 44°C

c.c., MARINE POLLUTANT

Marine pollutant yes (P) (hazardous to the aquatic environment) (Kerosene)

Danger label(s) 3, fish and tree





Special provisions (SP) 223, 955

Excepted quantities (EQ) E1

Limited quantities (LQ) 5 L

EmS F-E, S-E

Stowage category A

United States: en Page: 25 / 37



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Particulars in the shipper's declaration UN1268, Petroleum distillates, n.o.s., (contains:

Straight-run Kerosene, Distillates (petroleum), hy-

drodesulfurized middle), 3, III

Environmental hazards yes (hazardous to the aquatic environment)

Danger label(s) 3



Special provisions (SP)

Excepted quantities (EQ)

Limited quantities (LQ)

A3

E1

10 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) all ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings

Name of substance	CAS No	Remarks	Effective date
benzene	71-43-2		1987-01-01
ethylbenzene	100-41-4		1987-01-01
cumene	98-82-8		1987-01-01
1,2,4 trimethlybenzene	95-63-6		1987-01-01
naphthalene	91-20-3		1987-01-01
toluene	108-88-3		1987-01-01

United States: en Page: 26 / 37



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
benzene	71-43-2	a	1 2 3 4	10 (4,54)
benzene				
ethylbenzene	100-41-4		1 2 3	1000 (454)
cumene	98-82-8		3 4	5000 (2270)
naphthalene	91-20-3		1 2 3 4	100 (45,4)
toluene	108-88-3		1 2 3 4	1000 (454)

Legend

- "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act
- "2" indicates that the source is section 307(a) of the Clean Water Act
- 2 "3" indicates that the source is section 112 of the Clean Air Act
- "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA) 4
- Benzene was already a CERCLA hazardous substance prior to the CAA Amendments of 1990 and received an adjusted 10-pound RQ based on potential carcinogenicity in an August 14, 1989, final rule (54 FR 33418). The CAA Amendments specify that "benzene (including benzene from gasoline)" is a hazardous air pollutant and, thus, a CERCLA hazardous substance.

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	Name acc. to inventory	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Thres hold	De Minimis Concentra- tion Threshold
Propylbenzene	Cumene	98-82-8				0.1 %
benzene	Benzene	71-43-2				1.0 %
ethylbenzene	Ethylbenzene	100-41-4				0.1 %

United States: en Page: 27 / 37

Energizer.

Holdings Inc.

acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

Name of substance	Name acc. to inventory	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Thres hold	De Minimis Concentra- tion Threshold
cumene	Cumene	98-82-8				0.1 %
1,2,4 trimethlybenzene	1,2,4-Trimethylbenzene	95-63-6				1.0 %
xylene	Xylene (mixed isomers)	1330-20-7				1.0 %
naphthalene	Naphthalene	91-20-3				0.1 %
toluene	Toluene	108-88-3				1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	Name acc. to inventory	CAS No	References	Remarks
benzene	Benzene	71-43-2	A, N, O, R, T, *	
1,2,4 trimethlybenzene	Trimethylbenzene	25551-13-7	A	

Legend

- Substances which are regulated by OSHA as carcinogens; have been categorized by the ACGIH as either "human carcinogens" or "suspect of carcinogenic potential for man"; have been evaluated by the International Agency for Research on Cancer (IARC) and found to be carcinogens or potential carcinogens; or have been listed as a carcinogen or potential carcinogen in the Annual Report on Carcinogens published by the National Toxicology Program (NTP).
- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH

 National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards,"
- N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer
- Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division
- R International Agency for Research on Cancer (IARC) Monographs on the Evaluation of the Carcinogenic Risks to Humans; Overall Evaluations of Carcinogenicity: An Updating of IARC Monographs Volumes 1 to 42, Supplement 7 (1987). Available from: WHO Publications Centre USA
- T National Toxicology Program (NTP) "Fifth Annual Report on Carcinogens," 1989 (NTP 89-239). Order information: (919) 541-3992

- Hazardous Substance List (NJ-RTK)

Name of substance	Name acc. to inventory	CAS No	Remarks	Classifications
Propylbenzene	propylbenzene (benzene, pro- pyl-)	103-65-1		F3
1,2,3-Trimethylbenzene	TRIMETHYL BENZENE (mixed isomers) (BENZENE, TRIMETHYL-)	25551-13-7		F2
benzene	benzene	71-43-2		CA MU F3
ethylbenzene	ethylbenzene (benzene, ethyl-)	100-41-4		CA F3

United States: en Page: 28 / 37



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Revision: 2021-01-05 Version number: 10.0 Replaces version of: 2020-12-10 (9)

Name of substance	Name acc. to inventory	CAS No	Remarks	Classifications
cumene	cumene	98-82-8		F3 R1
Kerosene	Kerosine (petroleum)	8008-20-6		F2
1,2,4 trimethlybenzene	pseudocumene	95-63-6		F2
xylene	xylene, mixture of isomers (benzene, dimethyl-)	1330-20-7		F3
naphthalene	naphthalene	91-20-3		CA F2
1,3,5-trimethylbenzene	TRIMETHYL BENZENE (mixed isomers) (BENZENE, TRIMETHYL-)	25551-13-7		F2
toluene	toluene (benzene, methyl-) (tolu- ol)	108-88-3		TE F3

Legend

CA

Carcinogenic Flammable - Second Degree Flammable - Third Degree F2 F3

MU

Mutagenic Reactive - First Degree R1

TE Teratogenic

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name of substance	Name acc. to inventory	CAS No	Classification
benzene	BENZENE	71-43-2	E, S
ethylbenzene	BENZENE, ETHYL-	100-41-4	Е
cumene	BENZENE, (1-METHYLETHYL)-	98-82-8	E
Kerosene	KEROSINE (PETROLEUM)	8008-20-6	
1,2,4 trimethlybenzene	PSEUDOCUMENE	95-63-6	Е
xylene	BENZENE, DIMETHYL-	1330-20-7	E
naphthalene	NAPHTHALENE	91-20-3	Е
toluene	BENZENE, METHYL-	108-88-3	Е

Legend

Environmental hazard Special hazardous substance

United States: en Page: 29 / 37



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

- Hazardous Substance List (RI-RTK)

Name of substance	Name acc. to inventory	CAS No	References
Propylbenzene	cumene	98-82-8	T, F
1,2,3-Trimethylbenzene	Trimethyl benzene	25551-13-7	Т
benzene	benzene	71-43-2	T, F, C
ethylbenzene	Ethyl benzene	100-41-4	T, F
cumene	cumene	98-82-8	T, F
Kerosene	Kerosene	8008-20-6	F
1,2,4 trimethlybenzene	Trimethyl benzene	25551-13-7	Т
xylene	Dimethylbenzene	1330-20-7	T, F
naphthalene	naphthalene	91-20-3	T, F
1,3,5-trimethylbenzene	Trimethyl benzene	25551-13-7	Т
toluene	Methylbenzene	108-88-3	Т, F

Legend

C Carcinogenicity (IARC)
F Flammability (NFPA®)
T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals

Name acc. to inventory	CAS No	Remarks	Type of the toxicity
benzene	71-43-2		cancer
benzene	71-43-2		developmental, male
ethylbenzene	100-41-4		cancer
cumene	98-82-8		cancer
naphthalene	91-20-3		cancer
toluene	108-88-3		developmental

Industry or sector specific available guidance(s)

NPCA-HMIS® III

 $\label{thm:max-equation} \textit{Hazardous Materials Identification System}. \ \textit{American Coatings Association}.$

United States: en Page: 30 / 37



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	1	irritation or minor reversible injury possible
Flammability	2	material that must be moderately heated or exposed to relatively high ambient tem- peratures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient tem- peratures before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
AU	AICS	all ingredients are listed
CA	DSL	all ingredients are listed
CA	NDSL	not all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed

United States: en Page: 31 / 37



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

Country	Inventory	Status
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	not all ingredients are listed
US	TSCA	all ingredients are listed

Legend

AICS Australian Inventory of Chemical Substances CICR Chemical Inventory and Control Regulation

CSCL-ENCS List of Existing and New Chemical Substances (CSCL-ENCS)

DSL

ECSI

Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China **IECSC**

INSQ

National Inventory of Chemical Substances
Inventory of Existing and New Chemical Substances (ISHA-ENCS) ISHA-ENCS

Korea Existing Chemicals Inventory Non-domestic Substances List (NDSL) KECI NDSL NZIoC New Zealand Inventory of Chemicals

PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)

REACH Reg. REACH registered substances

Taiwan Chemical Substance Inventory TCSI

TSCA Toxic Substance Control Act

Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.3	Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.		yes
12.7	Other adverse effects	Other adverse effects: Data are not available.	yes
14.1	UN number: 1268	UN number	yes
14.1		DOT: 1268	yes
14.1		IMDG-Code: 1268	yes
14.1		ICAO-TI: 1268	yes

United States: en Page: 32 / 37



STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
14.2	UN proper shipping name: Petroleum distillates, n.o.s.	UN proper shipping name	yes
14.2		DOT: Petroleum distillates, n.o.s.	yes
14.2		IMDG-Code: PETROLEUM DISTILLATES, N.O.S.	yes
14.2		ICAO-TI: Petroleum distillates, n.o.s.	yes
14.3	Class: 3 (flammable liquids)		yes
14.3		DOT: 3	yes
14.3		IMDG-Code: 3	yes
14.3		ICAO-TI: 3	yes
14.4	Packing group: III (substance presenting low danger)	Packing group	yes
14.4		DOT: III	yes
14.4		IMDG-Code: III	yes
14.4		ICAO-TI: III	yes
14.7	Index number: 1268		yes
14.7	Proper shipping name: Petroleum distillates, n.o.s.		yes
14.7	Particulars in the shipper's declaration: UN1268, Petroleum distillates, n.o.s., 3, III, envir- onmentally hazardous	Particulars in the shipper's declaration: UN1268, Petroleum distillates, n.o.s., (contains: Straight-run Kerosene, Distillates (petroleum), hy- drodesulfurized middle), 3, III, environmentally hazardous	yes
14.7	Class: 3		yes
14.7	Packing group: III		yes
14.7	UN number: 1268		yes

United States: en Page: 33 / 37



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
14.7	Proper shipping name: PETROLEUM DISTILLATES, N.O.S.		yes
14.7	Class: 3		yes
14.7	Packing group: III		yes
14.7	Marine pollutant: yes (P) (hazardous to the aquatic environment)	Marine pollutant: yes (P) (hazardous to the aquatic environment) (Kerosene)	yes
14.7	UN number: 1268		yes
14.7	Proper shipping name: Petroleum distillates, n.o.s.		yes
14.7	Class: 3		yes
14.7	Packing group: III		yes
14.7	Particulars in the shipper's declaration: UN1268, Petroleum distillates, n.o.s., 3, III	Particulars in the shipper's declaration: UN1268, Petroleum distillates, n.o.s., (contains: Straight-run Kerosene, Distillates (petroleum), hy- drodesulfurized middle), 3, III	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Carc.	Carcinogenicity

United States: en Page: 34 / 37



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

Abbr.	Descriptions of used abbreviations
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LHS	Lower hazard substance

United States: en Page: 35 / 37



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

Abbr.	Descriptions of used abbreviations
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest Observed Effect Level
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
Muta.	Germ cell mutagenicity
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
NOEC	No Observed Effect Concentration
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RCP	Reciprocal calculation procedure
Repr.	Reproductive toxicity
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

United States: en Page: 36 / 37



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner - bottle

Version number: 10.0 Revision: 2021-01-05 Replaces version of: 2020-12-10 (9)

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture. Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H224	Extremely flammable liquid and vapor.
H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H371	May cause damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United States: en Page: 37 / 37