


SAFETY DATA SHEET**K-Seal Ultimate**

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification**Product identifier****Product name** K-Seal Ultimate**Product number** ST3501**Recommended use of the chemical and restrictions on use****Application** Additive for engine cooling systems.**Uses advised against** No specific uses advised against are identified.**Details of the supplier of the safety data sheet**

Supplier Solv-Tec
75 N. Main Street
Medford Lakes
NJ, 08055
USA
Tel: 609 261 4242
Fax: 609 261 4498
info@kseal.com

Emergency telephone number 609 261 4242 (Monday - Friday 08:30 - 16:30h)

Emergency telephone**2. Hazard(s) identification****Classification of the substance or mixture****OSHA Regulatory Status** This Product is Hazardous under the OSHA Hazard Communication Standard.**Physical hazards** Not Classified**Health hazards** Eye Irrit. 2A - H319 Repr. 1B - H360FD**Environmental hazards** Aquatic Acute 2 - H401 Aquatic Chronic 3 - H412**Label elements****Hazard symbols****Signal word** Danger

Hazard statements H319 Causes serious eye irritation.
H360FD May damage fertility. May damage the unborn child.
H401 Toxic to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

K-Seal Ultimate

Precautionary statements

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P264 Wash contaminated skin thoroughly after handling.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 If exposed or concerned: Get medical advice/ attention.
 P337+P313 If eye irritation persists: Get medical advice/ attention.
 P405 Store locked up.
 P501 Dispose of contents/ container in accordance with national regulations.

Contains

Disodium tetraborate decahydrate

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

bis(D-Gluconato-O1,O2)zinc 1 - <2.5% CAS number: 4468-02-4 M factor (Acute) = 1 M factor (Chronic) = 1
Classification Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410
4-Nonylphenol, branched, ethoxylated 1 - <2.5% CAS number: 127087-87-0 Classification Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Chronic 3 - H412
Disodium tetraborate decahydrate 1 - <2.5% CAS number: 1330-43-4 Classification Eye Irrit. 2A - H319 Repr. 1B - H360FD
Copper 0.5 - <1% CAS number: 7440-50-8 M factor (Acute) = 1 Classification Aquatic Acute 1 - H400 Aquatic Chronic 3 - H412

K-Seal Ultimate

Refractories, fibers, aluminosilicate	0.025 - <0.25%
CAS number: 142844-00-6	
Classification	
Carc. 1B - H350i	

The full text for all hazard statements is displayed in Section 16.

Ingredient notes The exact percentage/concentration is withheld as a trade secret in accordance with 29 CFR 1910.1200.

4. First-aid measures

Description of first aid measures

General information	Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.
Ingestion	Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.
Skin Contact	It is important to remove the substance from the skin immediately. Remove contamination with soap and water or recognized skin cleansing agent. Get medical attention if symptoms are severe or persist after washing. In the event of any sensitization symptoms developing, ensure further exposure is avoided.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 10 minutes.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.

Most important symptoms and effects, both acute and delayed

General information	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Spray/mists may cause respiratory tract irritation. Prolonged inhalation of high concentrations may damage respiratory system.
Ingestion	Gastrointestinal symptoms, including upset stomach.
Skin contact	The product contains a small amount of sensitizing substance. May cause an allergic skin reaction.
Eye contact	Irritating to eyes.

Indication of immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically. May cause sensitization or allergic reactions in sensitive individuals.

5. Fire-fighting measures

Extinguishing media

K-Seal Ultimate

Suitable extinguishing media	The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
<u>Special hazards arising from the substance or mixture</u>	
Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors. Carbon dioxide (CO ₂). Carbon monoxide (CO).
<u>Advice for firefighters</u>	
Protective actions during firefighting	Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Do not touch or walk into spilled material. Keep unnecessary and unprotected personnel away from the spillage. Avoid contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage.
-----------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Environmental precautions

Environmental precautions	Avoid discharge into drains or watercourses or onto the ground.
----------------------------------	-----------------------------------------------------------------

Methods and material for containment and cleaning up

Methods for cleaning up	Wear protective clothing as described in Section 8 of this safety data sheet. Do not empty into drains. Absorb spillage with non-combustible, absorbent material. The contaminated absorbent may pose the same hazard as the spilled material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. For waste disposal, see Section 13. Wash thoroughly after dealing with a spillage.
--------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Reference to other sections	For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.
------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

7. Handling and storage

Precautions for safe handling

Usage precautions	Keep out of the reach of children. Keep away from food, drink and animal feeding stuffs. Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Do not handle broken packages without protective equipment. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid discharge to the aquatic environment. Do not reuse empty containers.
--------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

K-Seal Ultimate

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

Conditions for safe storage, including any incompatibilities

Storage precautions

Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep containers upright. Protect containers from damage. Utilize retaining walls to prevent soil and water pollution in the event of spillage.

Storage class

Miscellaneous hazardous material storage.

Specific end uses(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.

8. Exposure controls/Personal protection

Control parameters

Occupational exposure limits

Disodium tetraborate decahydrate

Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m³ inhalable fraction

Short-term exposure limit (15-minute): ACGIH 6 mg/m³ inhalable fraction

A4

Copper

Long-term exposure limit (8-hour TWA): ACGIH 0.2 mg/m³ fume

Long-term exposure limit (8-hour TWA): ACGIH 1 mg/m³ dusts and mists

Long-term exposure limit (8-hour TWA): OSHA 0.1 mg/m³ fume

Long-term exposure limit (8-hour TWA): OSHA 1 mg/m³ dusts and mists as Cu

Refractories, fibers, aluminosilicate

Long-term exposure limit (8-hour TWA): ACGIH 0.2 f/cc respirable fibers: length > 5 µm, aspect ratio ≥3.1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination

ACGIH = American Conference of Governmental Industrial Hygienists.

A4 = Not Classifiable as a Human Carcinogen.

OSHA = Occupational Safety and Health Administration.

Ingredient comments

The constituents listed are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Copper (CAS: 7440-50-8)

Immediate danger to life and health 100 mg/m³

Exposure controls

Protective equipment



K-Seal Ultimate

Appropriate engineering controls	Provide adequate ventilation. Observe any occupational exposure limits for the product or ingredients. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimize worker exposure. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimize exposure.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Wear chemical splash goggles.
Hand protection	Wear protective gloves made of the following material: Rubber (natural, latex). Polyvinyl chloride (PVC). Nitrile rubber. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of skin contact.
Hygiene measures	Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn.
Environmental exposure controls	Keep container tightly sealed when not in use. Avoid release to the environment.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Liquid.
Color	Light brown.
Odor	Mild.
Odor threshold	Not available.
pH	pH (concentrated solution): 5.4-6.4
Melting point	Not available.
Initial boiling point and range	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	1.031-1.055 @ 21.1°C/70°F
Bulk density	8.6-8.8 lb/Ga
Solubility(ies)	Not known.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.

K-Seal Ultimate

Viscosity	Not applicable.
Explosive properties	Not considered to be explosive.
Oxidizing properties	Does not meet the criteria for classification as oxidizing.
Volatility	~50%

10. Stability and reactivity

Reactivity	See the other subsections of this section for further details.
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	No potentially hazardous reactions known.
Conditions to avoid	Avoid excessive heat for prolonged periods of time.
Materials to avoid	Strong oxidizing agents.
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitization

Respiratory sensitization Based on available data the classification criteria are not met.

Skin sensitization

Summary The product contains a small amount of sensitizing substance.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity Contains a substance which may be potentially carcinogenic. IARC Group 2B Possibly carcinogenic to humans.

K-Seal Ultimate

Reproductive toxicity

Summary Contains a substance/a group of substances which may damage fertility and the unborn child.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information

Avoid contact during pregnancy/while nursing. May damage fertility. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation

Spray/mists may cause respiratory tract irritation. Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion

Gastrointestinal symptoms, including upset stomach.

Skin Contact

May cause an allergic skin reaction. May cause sensitisation by skin contact.

Eye contact

Irritating to eyes.

Route of exposure

Ingestion Inhalation Skin and/or eye contact

Target Organs

No specific target organs known.

Medical considerations

Skin disorders and allergies.

Toxicological information on ingredients.

bis(D-Gluconato-O1,O2)zinc

Toxicological effects Not regarded as a health hazard under current legislation.

4-Nonylphenol, branched, ethoxylated

Skin corrosion/irritation

Animal data Irritating.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye damage.

Disodium tetraborate decahydrate

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 3,450.0

Species Rat

Notes (oral LD₅₀) REACH dossier information.

ATE oral (mg/kg) 3,450.0

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >2000 mg/kg, Dermal, Rabbit REACH dossier information.

K-Seal Ultimate

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LC₅₀ >2.04 mg/l, Inhalation, Rat REACH dossier information.

Skin corrosion/irritation

Animal data Dose: 0.5g, 24 hours, Rabbit Erythema/eschar score: No erythema (0). Edema score: No oedema (0). REACH dossier information.

Serious eye damage/irritation

Serious eye damage/irritation Dose: 0.08 mL, 14 days, Rabbit REACH dossier information.

Skin sensitization

Skin sensitization Buehler test - Guinea pig: Not sensitizing. REACH dossier information.

Germ cell mutagenicity

Genotoxicity - in vitro DNA damage and/or repair: Negative. REACH dossier information.

Genotoxicity - in vivo Chromosome aberration: Negative. REACH dossier information.

Carcinogenicity

Carcinogenicity NOAEL >5000 ppm, Oral, Mouse REACH dossier information.

Reproductive toxicity

Reproductive toxicity - fertility Three-generation study - NOAEL 100 mg/kg/day, Oral, Rat F1 REACH dossier information. May damage fertility.

Reproductive toxicity - development Developmental toxicity: - NOAEL: 55 mg/kg/day, Oral, Rat REACH dossier information. May damage the unborn child.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEL 100 mg/kg/day, Oral, Rat REACH dossier information.

Copper

Toxicological effects Not regarded as a health hazard under current legislation.

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >2500 mg/kg, Oral, Rat REACH dossier information.

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >2000 mg/kg, Dermal, Rat REACH dossier information.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LD₅₀ >5.11 mg/l, Inhalation, Rat REACH dossier information.

Skin corrosion/irritation

Animal data Dose: 0.5 g, 4 hours, Rabbit Erythema/eschar score: No erythema (0). Edema score: No oedema (0). REACH dossier information.

Skin sensitization

Skin sensitization Guinea pig maximization test (GPMT) - Guinea pig: Not sensitizing. REACH dossier information.

Germ cell mutagenicity

Genotoxicity - in vitro Gene mutation: Negative. REACH dossier information.

K-Seal Ultimate

Genotoxicity - in vivo	DNA damage and/or repair: Negative. REACH dossier information.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Two-generation study - NOAEL 1000 ppm, Oral, Rat P REACH dossier information.
<u>Aspiration hazard</u>	
Aspiration hazard	Not relevant.

12. Ecological information

Toxicity Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting effects.

Ecological information on ingredients.

bis(D-Gluconato-O1,O2)zinc

Toxicity	Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410 Very toxic to aquatic life with long lasting effects.
<u>Acute aquatic toxicity</u>	
LE(C)₅₀	0.1 < L(E)C ₅₀ ≤ 1
M factor (Acute)	1
<u>Chronic aquatic toxicity</u>	
M factor (Chronic)	1

4-Nonylphenol, branched, ethoxylated

Toxicity Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting effects.

Disodium tetraborate decahydrate

<u>Acute aquatic toxicity</u>	
Acute toxicity - fish	LC ₅₀ , 96 hours: 74 mg/l, Limanda limanda (common dab)
Acute toxicity - aquatic invertebrates	LC ₅₀ , 96 hours: 147 mg/l, Legumia recta (Black sandshell mussel)
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: 40.2 mg/l, Selenastrum capricornutum

Copper

Toxicity	Aquatic Acute 1 - H400 Aquatic Chronic 3 - H412 Very toxic to aquatic life with long lasting effects.
<u>Acute aquatic toxicity</u>	
LE(C)₅₀	0.1 < L(E)C ₅₀ ≤ 1
M factor (Acute)	1
Acute toxicity - fish	LC ₅₀ , 96 hours: 0.2 mg/l, Oncorhynchus mykiss (Rainbow trout)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 0.529 mg/l, Daphnia magna
<u>Chronic aquatic toxicity</u>	

K-Seal Ultimate

Short term toxicity - embryo and sac fry stages NOEC, 45 days: 11.4 µg/l, Oncorhynchus mykiss (Rainbow trout)

Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Ecological information on ingredients.

bis(D-Gluconato-O1,O2)zinc

Persistence and degradability The degradability of the product is not known.

4-Nonylphenol, branched, ethoxylated

Persistence and degradability The degradability of the product is not known.

Disodium tetraborate decahydrate

Persistence and degradability The degradability of the product is not known.

Copper

Persistence and degradability The product contains inorganic substances which are not biodegradable.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient Not available.

Ecological information on ingredients.

bis(D-Gluconato-O1,O2)zinc

Bio-Accumulative Potential No data available on bioaccumulation.

4-Nonylphenol, branched, ethoxylated

Bio-Accumulative Potential No data available on bioaccumulation.

Disodium tetraborate decahydrate

Bio-Accumulative Potential BCF: 0.7-1.4, Crassostrea gigas (Pacific oyster)

Partition coefficient log Pow: -1.53

Copper

Bio-Accumulative Potential Not relevant.

Mobility in soil

Mobility The product is water-soluble and may spread in water systems.

Ecological information on ingredients.

K-Seal Ultimate

bis(D-Gluconato-O1,O2)zinc

Mobility No data available.

4-Nonylphenol, branched, ethoxylated

Mobility No data available.

Disodium tetraborate decahydrate

Mobility Soluble in water.

Surface tension 71 mN/m @ 23°C

Copper

Mobility The product is insoluble in water.

Other adverse effects

Other adverse effects None known.

13. Disposal considerations

Waste treatment methods

General information The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

14. Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DOT).

UN Number

UN No. (International) Not applicable.

UN No. (DOT) Not applicable.

UN proper shipping name

Proper shipping name (International) Not applicable.

Proper shipping name (DOT) Not applicable.

Transport hazard class(es)

Transport Labels (International) No transport warning sign required.

DOT transport labels

No transport warning sign required.

K-Seal Ultimate

Packing group

Packing group (International) Not applicable.

DOT packing group Not applicable.

Environmental hazards

Environmentally Hazardous Substance

No.

Special precautions for user

Not applicable.

DOT reportable quantity Not applicable.

DOT TIH Zone Not applicable.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

Regulatory Status Classified in accordance with Appendix A, Appendix B and Appendix F of the OSHA Hazard Communication Standard 29 CFR §1910.1200.

Regulatory References OSHA Hazard Communication Standard 29 CFR §1910.1200

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed:

Copper

Final CERCLA RQ: 5000(2270) pounds (Kilograms)

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed.

SARA 313 Emission Reporting

The following ingredients are listed:

bis(D-Gluconato-O1,O2)zinc

1.0 %

4-Nonylphenol, branched, ethoxylated

1.0 %

Copper

1.0 %

CAA Accidental Release Prevention

None of the ingredients are listed.

OSHA Highly Hazardous Chemicals

None of the ingredients are listed.

US State Regulations

K-Seal Ultimate

California Proposition 65 Carcinogens and Reproductive Toxins

The following ingredients are listed:

Refractories, fibers, aluminosilicate

Carcinogen.

Ceramic fibers (airborne particles of respirable size)

California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed:

Copper

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed.

California Directors List of Hazardous Substances

The following ingredients are listed:

Copper

Massachusetts "Right To Know" List

The following ingredients are listed:

Disodium tetraborate decahydrate

Copper

Magnesium nitrate

Rhode Island "Right To Know" List

The following ingredients are listed:

Propane-1,2-diol

Copper

Magnesium nitrate

Minnesota "Right To Know" List

The following ingredients are listed:

Poly(ethylene) oxide

Propane-1,2-diol

Copper

New Jersey "Right To Know" List

The following ingredients are listed:

Propane-1,2-diol

Copper

Refractories, fibers, aluminosilicate

Magnesium nitrate

Pennsylvania "Right To Know" List

The following ingredients are listed:

Propane-1,2-diol

Disodium tetraborate decahydrate

Copper

Magnesium nitrate

K-Seal Ultimate

Inventories

US - TSCA

Some of the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

16. Other information

Training advice	Read and follow manufacturer's recommendations. Only trained personnel should use this material.
Revision comments	Document reviewed.
Revision date	10/25/2018
Revision	1
Supersedes date	6/1/2015
SDS No.	1971
Hazard statements in full	H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H350i May cause cancer by inhalation. H360FD May damage fertility. May damage the unborn child. H400 Very toxic to aquatic life. H401 Toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.