

# SAFETY DATA SHEET



## MOTOR MEDIC® UNIVERSAL POWER STEERING FLUID W/STOP LEAK

Version	Revision Date:	SDS Number:	Date of last issue: 03/12/2019
1.1	05/09/2019	600000001609	Date of first issue: 03/12/2019

### SECTION 1. IDENTIFICATION

Product name : MM PSF W/STOP LEAK, UNIVRSL 12/12OZ

Product code : M2713

#### Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : Dallas TX 75225

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Emergency telephone number : 1-800-424-9300 / 1-703-741-5970

#### Recommended use of the chemical and restrictions on use

Recommended use : POWER STEERING FLUID

Restrictions on use : Use only outdoors or in a well-ventilated area.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with 29 CFR 1910.1200

Not a hazardous substance or mixture.

#### GHS label elements

Not a hazardous substance or mixture.

#### Other hazards

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum)	64742-54-7	>= 90 - < 100
Distillates (petroleum)	64742-65-0	>= 1 - < 5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

### SECTION 4. FIRST AID MEASURES

**MOTOR MEDIC® UNIVERSAL POWER  
STEERING FLUID W/STOP LEAK**

Version	Revision Date:	SDS Number:	Date of last issue: 03/12/2019
1.1	05/09/2019	600000001609	Date of first issue: 03/12/2019

---

- |   |  |
|---|--|
| General advice  | : Move out of dangerous area.<br>Show this safety data sheet to the doctor in attendance.<br>Symptoms of poisoning may appear several hours later.<br>Do not leave the victim unattended.              |
| If inhaled  | : If breathed in, move person into fresh air.<br>If unconscious, place in recovery position and seek medical advice.<br>If symptoms persist, call a physician.   |
| In case of skin contact                                     | : If on skin, rinse well with water.   |
| In case of eye contact                                      | : Flush eyes with water as a precaution.<br>Remove contact lenses.<br>Protect unharmed eye.<br>Keep eye wide open while rinsing.   |
| If swallowed  | : Obtain medical attention.<br>Do NOT induce vomiting.<br>Do not give milk or alcoholic beverages.<br>Never give anything by mouth to an unconscious person.<br>If symptoms persist, call a physician. |
| Most important symptoms and effects, both acute and delayed | : None known.  |

---

**SECTION 5. FIREFIGHTING MEASURES**

- |   |   |
|---|---|
| Suitable extinguishing media                  | : Water spray<br>Carbon dioxide (CO2)   |
| Unsuitable extinguishing media                | : High volume water jet   |
| Specific hazards during fire-fighting         | : If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release. |
| Hazardous combustion products                 | : Carbon oxides   |
| Specific extinguishing methods                | : Product is compatible with standard fire-fighting agents.   |
| Further information                           | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.   |
| Special protective equipment for firefighters | : In the event of fire, wear self-contained breathing apparatus.  |

**MOTOR MEDIC® UNIVERSAL POWER  
STEERING FLUID W/STOP LEAK**

Version	Revision Date:	SDS Number:	Date of last issue: 03/12/2019
1.1	05/09/2019	600000001609	Date of first issue: 03/12/2019

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Avoid breathing dust.  
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.  
Prevent product from entering drains.  
Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapours/dust.  
Do not smoke.  
Dispose of rinse water in accordance with local and national regulations.  
Container hazardous when empty.  
Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Observe label precautions.
- Further information on storage stability : No decomposition if stored and applied as directed.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum)	64742-54-7	TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m <sup>3</sup>	ACGIH
		TWA (Mist)	5 mg/m <sup>3</sup>	OSHA P0
		TWA (Mist)	5 mg/m <sup>3</sup>	NIOSH REL
		ST (Mist)	10 mg/m <sup>3</sup>	NIOSH REL
Distillates (petroleum)	64742-65-0	TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1

# SAFETY DATA SHEET



## MOTOR MEDIC® UNIVERSAL POWER STEERING FLUID W/STOP LEAK

Version 1.1      Revision Date: 05/09/2019      SDS Number: 600000001609      Date of last issue: 03/12/2019  
Date of first issue: 03/12/2019

		TWA (Inhalable fraction)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

### Personal protective equipment

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Wear as appropriate:  
Impervious clothing  
Safety shoes

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not smoke.  
When using do not eat or drink.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : clear  
light yellow

Odour : hydrocarbon-like

Odour Threshold : not determined

pH : not determined

Melting point/freezing point : not determined

Boiling point/boiling range : not determined

Flash point : 176 °C  
Method: closed cup  
Value for Component

# SAFETY DATA SHEET



## MOTOR MEDIC® UNIVERSAL POWER STEERING FLUID W/STOP LEAK

Version	Revision Date:	SDS Number:	Date of last issue: 03/12/2019
1.1	05/09/2019	600000001609	Date of first issue: 03/12/2019

---

Evaporation rate	:	not determined
Flammability (solid, gas)	:	No data available
Self-ignition	:	not determined
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	not determined
Vapour pressure	:	< 0.1 hPa (20 °C) Value for Component
Relative vapour density	:	not determined
Density	:	0.8324 g/cm3
Solubility(ies)	:	
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	not determined
Decomposition temperature	:	not determined
Viscosity	:	
Viscosity, dynamic	:	not determined
Viscosity, kinematic	:	> 20.5 mm2/s (40 °C)
Molecular weight	:	Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	Hazardous polymerisation does not occur. No decomposition if stored and applied as directed.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	Carbon oxides

**MOTOR MEDIC® UNIVERSAL POWER  
STEERING FLUID W/STOP LEAK**

Version	Revision Date:	SDS Number:	Date of last issue: 03/12/2019
1.1	05/09/2019	600000001609	Date of first issue: 03/12/2019

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Eye contact  
Skin contact  
Ingestion

**Acute toxicity**

Not classified based on available information.

**Components:****Distillates (petroleum):**

Acute oral toxicity : LD50 (Rat): > 15 g/kg  
Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

**Distillates (petroleum):**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Components:****Distillates (petroleum):**

Result: Possibly irritating to skin

**Distillates (petroleum):**

Result: Possibly irritating to skin

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Remarks: Unlikely to cause eye irritation or injury.

**Components:****Distillates (petroleum):**

Result: No eye irritation  
Assessment: No eye irritation

**Distillates (petroleum):**

Result: Possibly irritating to eyes

**MOTOR MEDIC® UNIVERSAL POWER  
STEERING FLUID W/STOP LEAK**

Version	Revision Date:	SDS Number:	Date of last issue: 03/12/2019
1.1	05/09/2019	600000001609	Date of first issue: 03/12/2019

---

**Respiratory or skin sensitisation****Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

Known to be human carcinogen

Distillates (petroleum)

64742-65-0

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Components:****Distillates (petroleum):**

May be fatal if swallowed and enters airways.

**Distillates (petroleum):**

May be fatal if swallowed and enters airways.

**Further information****Product:**

Remarks: No data available

---

**SECTION 12. ECOLOGICAL INFORMATION****Toxicity**

Additional ecological information : No data available

# SAFETY DATA SHEET



## MOTOR MEDIC® UNIVERSAL POWER STEERING FLUID W/STOP LEAK

Version	Revision Date:	SDS Number:	Date of last issue: 03/12/2019
1.1	05/09/2019	600000001609	Date of first issue: 03/12/2019

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

### SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

#### International Regulations

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

##### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### National Regulations

##### 49 CFR

Not regulated as a dangerous good

##### 49 CFR

Not regulated as a dangerous good

### SECTION 15. REGULATORY INFORMATION

#### EPCRA - Emergency Planning and Community Right-to-Know Act

##### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Lead	7439-92-1	10	10 (D008)
Ethyl Acrylate	140-88-5	1000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

##### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

##### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.



# SAFETY DATA SHEET



## MOTOR MEDIC® UNIVERSAL POWER STEERING FLUID W/STOP LEAK

Version	Revision Date:	SDS Number:	Date of last issue: 03/12/2019
1.1	05/09/2019	600000001609	Date of first issue: 03/12/2019

**SARA 311/312 Hazards** : No SARA Hazards

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.


### California Prop. 65

WARNING: This product can expose you to chemicals including Ethyl Acrylate, Lead, Propylene Oxide, Ethylene Oxide, 1,4-Dioxane, Arsenic, Cadmium, which is/are known to the State of California to cause cancer, and Lead, Ethylene Oxide, Cadmium, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA:



Revision Date : 05/09/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN