



Safety Data Sheet

Product identifier used on the label: MAG 1 MULTI-VATF FS 6/1QT

Product Code: MAG62555

Revision Date: 04-28-2021

Replaces: 04-28-2021

1. Identification

Product identifier used on the label: **MAG 1 MULTI-VATF FS 6/1QT**

Product Code: MAG62555

Other means of identification:

Synonyms: No data available

Recommended use of the chemical and restrictions on use:

Recommended use: Automatic Transmission Fluid

Restrictions on use: Uses other than those described above

Name, address, and telephone number
of the chemical manufacturer,
importer, or other responsible party:

Warren Distribution, Inc.

950 S. 10th St., Suite 300

Omaha, NE 68108-3296

Phone number: +01 (800) 825-1235 +01 (402) 341-9397

E-mail address: sds@wd-wpp.com

Emergency phone number: CHEMTREC: +1 (800) 424-9300 International: +01 (703) 527-3887

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Hazard
Symbols:



GHS Classification: Skin Sensitizer Category 1

Signal Word: Warning

Hazard Statements: May cause an allergic skin reaction

Precautionary Statements:

Prevention: Avoid breathing dust/fume/gas/mist/ vapors/spray. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response: If on skin: Wash with plenty of water. Specific treatment (see Sections 4 - 8 of Safety Data Sheet). If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Disposal: Dispose of contents/container in accordance with

Safety Data Sheet

Product identifier used on the label: MAG 1 MULTI-VATF FS 6/1QT

Product Code: MAG62555

Revision Date: 04-28-2021

Replaces: 04-28-2021

local/regional/national/international regulations.

Hazards not otherwise classified: No data available

3. Composition/information on ingredients

Chemical Name	Common name and synonyms	CAS #	%
Highly refined synthetic base stocks	No data available	64742-54-7	30 - 60
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	No data available	72623-86-0	15 - 40
Petroleum distillates, hydrotreated light naphthenic	No data available	64742-53-6	1 - 5
Distillates, petroleum, solvent-dewaxed light paraffinic	No data available	64742-56-9	1 - 5
Amines, polyethylenepoly-, reaction products with succinic anhydride polyisobutenyl derivs., borated	No data available	EPA-ACC-17799	1 - 5
Distillates, petroleum, solvent-dewaxed heavy paraffinic	No data available	64742-65-0	1 - 5
Long chain alkyl amine thiophosphate	No data available	ACC # 251617	0.5 - 1.5
Long chain alkyl amine alkylene amine	No data available	64051-50-9	0.1 - 1
Petroleum distillates, solvent-refined heavy paraffinic	No data available	64741-88-4	0.1 - 1
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	No data available	72623-87-1	0.1 - 1

One or more hazardous ingredient(s) is claimed as a trade secret under the OSHA Hazard Communication Standard. The hazards of this (these) ingredient(s) are given on this SDS.

4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual

Safety Data Sheet

Product identifier used on the label: MAG 1 MULTI-VATF FS 6/1QT

Product Code: MAG62555

Revision Date: 04-28-2021

Replaces: 04-28-2021

	administer oxygen.
Eye Contact:	None expected to be needed, however, use an eye wash to remove a chemical from your eye regardless of the level of hazard.
Skin Contact:	If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Ingestion:	Minimal risk of harm if swallowed. Do not induce vomiting. Seek medical attention immediately. Provide medical care provider with this SDS.
Most important symptoms/effects, acute and delayed:	May cause an allergic skin reaction
Indication of immediate medical attention and special treatment needed, if necessary:	Specific treatment (see Sections 4 - 8 of Safety Data Sheet).

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media:	Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do not direct a stream of water into the hot burning liquid.
Unsuitable extinguishing media:	No data available
Specific hazards arising from the chemical:	Material may be ignited only if preheated to temperatures above the high flash point, for example in a fire.
Hazardous combustion products:	Carbon monoxide, Sulfur containing gases, Nitrogen containing gases, oxides of phosphorus, Hydrogen sulfide
Special protective equipment and precautions for fire-fighters:	Do not enter fire area without proper protection including self- contained breathing apparatus and full protective equipment. Use methods for the surrounding fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the
---	--

Safety Data Sheet

Product identifier used on the label: MAG 1 MULTI-VATF FS 6/1QT

Product Code: MAG62555

Revision Date: 04-28-2021

Replaces: 04-28-2021

Methods and materials for containment and cleaning up:

quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations. Used fluid should be disposed of at a recycling center.

7. Handling and storage

Precautions for safe handling:

Mildly irritating material. Avoid unnecessary exposure. Follow all protective equipment recommendations provided in Section 8.

Conditions for safe storage, including any incompatibilities:

Safe storage conditions:

Store in a cool dry place. Isolate from incompatible materials.

Materials to Avoid/Chemical Incompatibility:

Strong oxidizing agents

8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Highly refined synthetic base stocks	5 mg/m ³ TWA	5 mg/m ³ TWA	10 mg/m ³ STEL	No data available
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	5 mg/m ³ TWA	5 mg/m ³ TWA	10 mg/m ³ STEL	No data available
Distillates, petroleum, solvent-dewaxed heavy paraffinic	5 mg/m ³ TWA	5 mg/m ³ TWA	10 mg/m ³ STEL	No data available
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	5 mg/m ³ TWA	5 mg/m ³ TWA	10 mg/m ³ STEL	No data available

Appropriate engineering controls:

Use local exhaust ventilation or other engineering controls to minimize

Safety Data Sheet

Product identifier used on the label: MAG 1 MULTI-VATF FS 6/1QT

Product Code: MAG62555

Revision Date: 04-28-2021

Replaces: 04-28-2021

exposures and maintain operator comfort.

Individual protection measures, such as personal protective equipment:

Respiratory Protection:

Avoid breathing dust/fume/gas/mist/ vapors/spray.

Respirator Type(s):

None required where adequate ventilation is provided. If airborne concentrations are above the applicable exposure limits, use NIOSH/MSHA approved respiratory protection.

Eye protection:

Wear safety glasses when handling this product if there is a likelihood of contact with eyes.

Skin protection:

Where use can result in skin contact, practice good personal hygiene and wear impervious gloves. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

Gloves:

Neoprene, Nitrile

General hygiene conditions:

Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

9. Physical and chemical properties

Appearance (physical state, color etc.):

Physical state:

Liquid

Color:

Amber

Odor:

MildPetroleum

Odor Threshold:

Not determined

pH:

No data available

Melting point/freezing point:

Melting Point:

No data available

Freezing point:

No data available

Initial boiling point and boiling range (°C):

No data available

Flash Point (°C):

220

Evaporation Rate:

No data available

Flammability (solid, gas):

No data available

Upper/lower flammability or explosive limits:

Safety Data Sheet

Product identifier used on the label: MAG 1 MULTI-VATF FS 6/1QT

Product Code: MAG62555

Revision Date: 04-28-2021

Replaces: 04-28-2021

Upper flammability or explosive limits:	Not established
Lower flammability or explosive limits:	Not established
Vapor pressure:	No data available
Vapor density:	No data available
Relative density:	0.85
Solubility(ies):	Negligible; 0-1%
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	No data available
Decomposition Temperature:	Not determined
Viscosity:	33.45

10. Stability and reactivity

Reactivity:	There are no known reactivity hazards associated with this product.
Chemical stability:	Stable under normal conditions.
Possibility of hazardous reactions:	None expected under standard conditions of storage.
Conditions to avoid (e.g., static discharge, shock, or vibration):	Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition. Moisture (will lead to product performance degradation).
Incompatible materials:	Strong oxidizing agents
Hazardous decomposition products:	Carbon monoxide, Sulfur containing gases, Nitrogen containing gases, oxides of phosphorus, Hydrogen sulfide

11. Toxicological information

Description of the various toxicological (health) effects and the available data used to identify those effects:

Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact):	Skin contact
Symptoms related to the physical, chemical and toxicological characteristics:	May cause an allergic skin reaction

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Ingestion:	No hazard in normal industrial use. Estimated to be > 5.0 g/kg.
------------	---

Safety Data Sheet

Product identifier used on the label: MAG 1 MULTI-VATF FS 6/1QT

Product Code: MAG62555

Revision Date: 04-28-2021

Replaces: 04-28-2021

Skin Contact:	This material is likely to be moderately irritating to skin based on animal data. Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
Absorption:	Estimated to be > 5.0 g/kg; practically non-toxic
Inhalation:	No hazard in normal industrial use. Likely to be practically non-toxic based on animal data.
Eye Contact:	This material is estimated to be non-irritating eyes (Draize score <15 [rabbits]). Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.
Sensitization:	May cause an allergic skin reaction
Mutagenicity:	No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.
Carcinogenicity:	Not expected to cause cancer. This product meets the IP-346 criteria of <3% PAH's and is not considered a carcinogen by the International Agency for Research on Cancer.
Reproductive toxicity	Not known or reported to cause reproductive or developmental toxicity.
STOT-single exposure:	Based on available data, the classification criteria are not met.
STOT-repeated exposure:	Based on available data, the classification criteria are not met.
Aspiration hazard:	Based on available data, the classification criteria are not met.
Other information:	None known.

Numerical measures of toxicity (such as acute toxicity estimates):

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Long chain alkyl amine alkylene amine	Oral LD50 Rat > 2000 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	
Petroleum distillates, solvent-refined heavy paraffinic	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (4h) Rat > 5530 MG/M3
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil- based	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (4h) Rat > 5.2 mg/L
Long chain alkyl amine thiophosphate		Dermal LD50 Rabbit > 2000 mg/kg	
Distillates, petroleum, solvent-dewaxed light	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	Inhalation LC50 (4h) Rat > 5399 MG/M3

Safety Data Sheet

Product identifier used on the label: MAG 1 MULTI-VATF FS 6/1QT

Product Code: MAG62555

Revision Date: 04-28-2021

Replaces: 04-28-2021

paraffinic			
Distillates, petroleum, solvent-dewaxed heavy paraffinic	Oral LD50 Rat > 15000 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	Inhalation LC50 (4h) Rat > 2400 MG/M3
Petroleum distillates, hydrotreated light naphthenic	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (4h) Rat 2180 MG/M3
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	Oral LD50 Rat > 5000 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (4h) Rat > 5.2 mg/L
Highly refined synthetic base stocks	Oral LD50 Rat > 15000 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	

Is the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA:

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
There are no components that are known or reported to cause cancer.			

12. Ecological information

Ecotoxicity (aquatic and terrestrial, where available):

Slight ecological hazard. In high concentrations, this product may be dangerous to plants and/or wildlife.

Ecological Toxicity Data:

Chemical Name	CAS #	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	EC50 (48h) Daphnia magna > 1000 mg/L	No data available	LC50 (96h) Rainbow Trout > 5000 mg/L
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	EC50 (48h) Daphnia magna > 1000 mg/L	No data available	LC50 (96h) Rainbow Trout > 5000 mg/L
Long chain alkyl amine alkylene amine	64051-50-9	EC50 (48h) Daphnia magna 73.4 mg/L	Aquatic ERC50 (72h) Pseudokirchneriella subcapitata > 100 mg/L	LC50 (96h) Rainbow Trout > 100 mg/L
Long chain alkyl amine	ACC # 251617	No data available	Aquatic ERC50	No data available

Safety Data Sheet

Product identifier used on the label: MAG 1 MULTI-VATF FS 6/1QT

Product Code: MAG62555

Revision Date: 04-28-2021

Replaces: 04-28-2021

thiophosphate			(72h) Green Algae 22 mg/L	
Distillates, petroleum, solvent-dewaxed light paraffinic	64742-56-9	LC50 (48h) > 1000 mg/L	No data available	LC50 (96h) > 5000 mg/L
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	EC50 (48h) Daphnia magna > 1000 mg/L	No data available	LC50 (96h) Rainbow Trout > 5000 mg/L
Petroleum distillates, hydrotreated light naphthenic	64742-53-6	EC50 (48h) Daphnia magna > 1000 mg/L	No data available	LC50 (96h) Rainbow Trout > 5000 mg/L
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	EC50 (48h) Daphnia magna > 1000 mg/L	No data available	LC50 (96h) Rainbow Trout > 5000 mg/L
Highly refined synthetic base stocks	64742-54-7	EC50 (48h) Daphnia magna > 1000 mg/L	No data available	LC50 (96h) Rainbow Trout > 5000 mg/L

Persistence and degradability:

Biodegrades slowly.

Bioaccumulative potential:

Bioconcentration may occur.

Mobility in soil:

This material is expected to have essentially no mobility in soil. It absorbs strongly to most soil types.

**Other adverse effects (such as
hazardous to the ozone layer):**

None known.

13. Disposal considerations

**Description of waste residues and
information on their safe handling and
methods of disposal, including the
disposal of any contaminated
packaging:**

Dispose of contents and container in accordance with
local/regional/national/international regulations.

Contaminated packaging:

Recycle containers whenever possible.

14. Transport information

Carriage of dangerous goods by road (DOT), rail or inland waterways:

DOT Basic Description:

Not regulated for road transport

Safety Data Sheet

Product identifier used on the label: MAG 1 MULTI-VATF FS 6/1QT

Product Code: MAG62555

Revision Date: 04-28-2021

Replaces: 04-28-2021

International carriage of dangerous goods by sea (IMDG/IMO):

UN number: Not regulated by IMDG

UN Proper shipping name: Not applicable

Transport hazard class(es): Not applicable

Packing group, if applicable: Not applicable

International carriage of dangerous goods by air (IATA):

UN number: Not regulated by IATA

UN Proper shipping name: Not applicable

Transport hazard class(es): Not applicable

Packing group, if applicable: Not applicable

Environmental hazards (e.g., Marine pollutant (Yes/No)): None.

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): No data available

Special precautions which a user needs to be aware of or needs to comply with in connection with transport or conveyance either within or outside their premises: No data available

15. Regulatory information

Safety, health and environmental regulations specific for the product in question:

TSCA Status: All components of this material are on the Active US TSCA Inventory or are exempt.

Regulated Components:

Chemical Name	CAS #	CERCLA	Sara EHS	Sara 313	U.S. HAP
Highly refined synthetic base stocks	64742-54-7	N	N	N	N
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	N	N	N	N

Safety Data Sheet

Product identifier used on the label: MAG 1 MULTI-VATF FS 6/1QT

Product Code: MAG62555

Revision Date: 04-28-2021

Replaces: 04-28-2021

Petroleum distillates, hydrotreated light naphthenic	64742-53-6	N	N	N	N
Amines, polyethylenepoly-, reaction products with succinic anhydride polyisobutenyl derivs., borated	EPA-ACC-17799	N	N	N	N
Distillates, petroleum, solvent-dewaxed light paraffinic	64742-56-9	N	N	N	N
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	N	N	N	N
Long chain alkyl amine thiophosphate	ACC # 251617	N	N	N	N
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	N	N	N	N
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	N	N	N	N
Long chain alkyl amine alkylene amine	64051-50-9	N	N	N	N

Chemical Name	CAS #	California Prop 65 - Cancer	California Prop 65 - Dev. Toxicity	California Prop 65 - Reprod fem	California Prop 65 - Reprod male
Highly refined synthetic base stocks	64742-54-7	N	N	N	N
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	N	N	N	N
Petroleum distillates, hydrotreated light	64742-53-6	N	N	N	N

Safety Data Sheet

Product identifier used on the label: MAG 1 MULTI-VATF FS 6/1QT

Product Code: MAG62555

Revision Date: 04-28-2021

Replaces: 04-28-2021

naphthenic					
Amines, polyethylenepoly-, reaction products with succinic anhydride polyisobutenyl derivs., borated	EPA-ACC- 17799	N	N	N	N
Distillates, petroleum, solvent- dewaxed light paraffinic	64742-56-9	N	N	N	N
Distillates, petroleum, solvent- dewaxed heavy paraffinic	64742-65-0	N	N	N	N
Long chain alkyl amine thiophosphate	ACC # 251617	N	N	N	N
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	N	N	N	N
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	N	N	N	N
Long chain alkyl amine alkylene amine	64051-50-9	N	N	N	N

Chemical Name	CAS #	Massachusetts RTK List	New Jersey RTK List	Pennsylvania RTK List	Rhode Island RTK List	Minnesota Hazardous Substance List
Highly refined synthetic base stocks	64742-54-7	N	N	N	N	N
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	N	N	N	N	N
Petroleum distillates, hydrotreated light	64742-53-6	Y	N	N	N	N

Safety Data Sheet

Product identifier used on the label: MAG 1 MULTI-VATF FS 6/1QT

Product Code: MAG62555

Revision Date: 04-28-2021

Replaces: 04-28-2021

naphthenic						
Amines, polyethylenepoly-, reaction products with succinic anhydride polyisobutenyl derivs., borated	EPA-ACC- 17799	N	N	N	N	N
Distillates, petroleum, solvent- dewaxed light paraffinic	64742-56-9	Y	N	N	N	N
Distillates, petroleum, solvent- dewaxed heavy paraffinic	64742-65-0	N	N	N	N	N
Long chain alkyl amine thiophosphate	ACC # 251617	N	N	N	N	N
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	N	N	N	N	N
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	N	N	N	N	N
Long chain alkyl amine alkylene amine	64051-50-9	N	N	N	N	N

16. Other information, including date of preparation or last revision.

SDS Prepared by:

MCHONGOOFAFA

Revision Date:

04-28-2021

Revision Number:

2

Reason for revision:

Activated by Document Formulation Generation

References:

No data available

Other Info:

No data available

Disclaimer:

This safety data sheet and the information it contains is offered to you in good faith as accurate. We have reviewed any information contained in

Safety Data Sheet

Product identifier used on the label: MAG 1 MULTI-VATF FS 6/1QT

Product Code: MAG62555

Revision Date: 04-28-2021

Replaces: 04-28-2021

the data sheet which we have received from outside sources and we believe the information to be correct, but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either expressed or implied.