

1. Identification of the Substance / Preparation and of the Company / Undertaking

Product identifier

Product Name Prime Guard -35°F Power Blast
Stock Numbers PRIM93506, PRIM93555

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Windshield Wiper Fluid
Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Highline Aftermarket
Supplier Address 4500 Malone Road Memphis, TN 38118 US
Supplier Phone Number 901-775-5555
email sds@highlineaftermarket.com

Emergency Telephone Number **PERS 24 Hour Assistance**
Domestic Shipments and to Canada: 1-800-633-8253
International Shipments 1-801-629-0667

2. Hazards Identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 3
Acute toxicity - Dermal	Category 3
Acute toxicity - Inhalation (Vapors)	Category 3
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Specific target organ toxicity (single exposure)	Category 1
Specific target organ toxicity (repeated exposure)	Category 2
Flammable liquids	Category 3

GHS Label elements, including precautionary statements

Emergency Overview

Signal Word

Hazard Statement:

Harmful if swallowed
 Toxic if contact with skin
 Toxic if inhaled
 Causes damage to organs
 Flammable liquid and vapor

Appearance Purple

Danger



Physical State Liquid

Odor Mild Alcohol

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Wear protective gloves/protective clothing/eye protection/face protection
Use only outdoors or in a well-ventilated area
Do not breathe dust/fume/gas/mist/vapors/spray
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ ventilating/ lighting/ equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool

Precautionary Statements - Response

IF exposed: Call a POISON CENTER or doctor/physician
Specific treatment (see supplemental first aid instructions on this label)

Skin

Call a POISON CENTER or doctor/physician if you feel unwell
Wash contaminated clothing before reuse
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
Rinse mouth

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

0.00406% of the mixture consists of ingredient(s) of unknown toxicity

Other information

PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. Composition / Information on Ingredients

Chemical Name	CAS No	Weight-%	Trade Secret
Methyl alcohol	67-56-1	15 - 40	*
Ethylene glycol	107-21-1	1-5	*

*The exact percentage (concentration) of composition has been withheld as a trade secret

First Aid Measures**First aid measures**

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Seek immediate medical attention/advice. Remove contact lenses, if present and easy to do. Continue rinsing.
Skin Contact	Immediate medical attention is required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, (trained personnel should) give oxygen.
Ingestion	Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects	Coughing and/ or wheezing. Difficulty in breathing.
--	---

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

5. Fire-fighting Measures**Suitable Extinguishing Media**

Dry chemical, Carbon dioxide (CO₂), water spray. Alcohol resistant foam.

Unsuitable extinguishing media

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Vapors can form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.

Uniform Fire Code Toxic: Liquid
 Flammable Liquid: I-C

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to No.

Mechanical Impact

Sensitivity to Static Yes.

Discharge

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal Precautions ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Full encapsulating vapor protective clothing should be worn for spills and leaks with no fire. Stop leak if you can do it without risk.

Other Information Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Environmental Precautions

Environmental Precautions Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Methods for Containment A vapor suppressing foam may be used to reduce vapors. Absorb with dry earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Use clean non-sparking tools to collect absorbed material. Dike far ahead of liquid spill for later disposal. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. Handling and Storage

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Do not breathe vapor or mist. Use only with adequate ventilation and in closed systems. Use personal protection equipment. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use grounding and

bonding connection when transferring this material to prevent static discharge, fire or explosion. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions.

Conditions for safe storage, including any incompatibilities

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children.

Protect from moisture. Store away from other materials. Store locked up. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

Incompatible Products

None known based on information supplied.

8. Exposure Controls / Personal Protection

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Methyl alcohol 67-56-1	STEL = 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 325 mg/m ³ STEL: 250 ppm
Ethylene glycol 107-21-1	Ceiling: 100 mg/m ³ aerosol only	(vacated) Ceiling: 50 ppm (vacated) Ceiling: 125 mg/m ³	

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection

None required for consumer use. If splashes are likely to occur. Tight sealing safety goggles.

Skin and Body Protection

None required for consumer use. Repeated or prolonged contact. Wear protective gloves, protective clothing and antistatic boots.

Respiratory Protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Take off contaminated clothing and wash before reuse. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work areas and clothing is recommended. Do not breathe vapor or mist.

9. Physical and Chemical Properties

Physical and Chemical Properties

Physical State

Liquid

Appearance

Liquid

Odor

Mild Alcohol

Color

Purple

Odor Threshold

No information available

Property

Values

Remarks Method

pH

9.8

None known

Melting / freezing point

No data available

None known

Boiling point / boiling range

78 °C / 172 °F

None known

Flash Point

29 °C / 84 °F

None known

Evaporation Rate

No data available

None known

Flammability (solid, gas)

No data available

None known

Flammability Limit in Air

Upper flammability limit

No data available

Lower flammability limit

No data available

Vapor pressure

No data available

None known

Vapor density

No data available

None known

Specific Gravity

No data available

None known

Water Solubility

Miscible in water

None known

Solubility in other solvents

No data available

None known

Partition coefficient: n-octanol/water

No data available

None known

Autoignition temperature

No data available

None known

Decomposition temperature

No data available

None known

Kinematic viscosity

No data available

None known

Dynamic viscosity

No data available

None known

Explosive properties

No data available

Oxidizing Properties

No data available

Other Information

Softening Point

No data available

VOC Content (%)

No data available

Particle Size

No data available

Particle Size Distribution

10. Stability and Reactivity

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Excessive heat. Heat, flames and sparks.

Incompatible materials

None known based on information supplied.

Hazardous Decomposition Products

Carbon oxides.

11. Toxicological Information

Information on likely routes of exposure

Product Information

Inhalation

Specific test data for the substance or mixture is not available. Toxic by inhalation. (based on components).

Eye Contact

Specific test data for the substance or mixture is not available.

Skin Contact

Specific test data for the substance or mixture is not available. Toxic in contact with skin. May be absorbed through the skin in harmful amounts. (based on components).

Ingestion

Specific test data for the substance or mixture is not available. May be harmful if swallowed. (based on components).

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl alcohol 67-56-1	= 5628 mg/kg (Rat)	-	= 83.2 mg/L (Rat) 4 h
Ethylene glycol 107-21-1	= 4000 mg/kg (Rat)		

Information on toxicological effects

Symptoms

Coughing and/ or wheezing. Difficulty in breathing.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization

No information available.

Mutagenic Effects

No information available.

Carcinogenicity

Contains no ingredient listed as a carcinogen.

Reproductive Toxicity

No information available.

STOT - single exposure

Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from acute exposure. (STOT SE). If this product is a mixture, the classification is not based on toxicology studies for this product but is based solely on toxicology studies for ingredients found within this product. Detailed substance and/or ingredient information may be provided in other sections of this SDS. Target organs effects listed in this document may result from a single overexposure to this product. Causes damage to organs if swallowed. Causes damage to organs in contact with skin.

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).

Chronic Toxicity

No known effect based on information supplied. Effects from this product caused by acute exposure may cause permanent damage to target organs and/or may cause chronic conditions. Avoid repeated exposure.

Target Organ Effects

Prolonged exposure may cause chronic effects.
Respiratory system. Systemic Toxicity. Central Nervous System (CNS). Eyes. Gastrointestinal tract (GI). Skin.

Aspiration Hazard

No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	292.00 mg/kg
ATEmix (dermal)	891.00 mg/kg (ATE)
ATEmix (inhalation-dust/mist)	1.49 mg/l
ATEmix (inhalation-vapor)	9.00 ATEmix

12. Ecological Information

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Methyl alcohol 67-56-1		96h LC50: = 28200 mg/L (Pimephales promelas) 96h LC50: > 100 mg/L (Pimephales promelas) 96h LC50: 19500 - 20700 mg/L (Oncorhynchus mykiss) 96h LC50: 18 - 20 mL/L (Oncorhynchus mykiss) 96h LC50: 13500 - 17600 mg/L (Lepomis macrochirus)	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	

Ethylene glycol 107-21-1	96h EC50: 6500 – 13000 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 41000 mg/L (Oncorhynchus mykiss) 96h LC50: 14 – 18 mL/L (Oncorhynchus mykiss) 96h LC50: 40761 mg/L (Oncorhynchus mykiss) 96h LC50: 27540 mg/L (Lepomis macrochirus) 96h LC50: 16000 mg/L (Poecilia reticulata) 96h LC50: 40000 – 60000 mg/L	EC50 = 10000 mg/L 16 h EC50 = 620 mg/L 30 min EC50 = 620./L 30 min	48h EC50: = 46300 mg/L
-----------------------------	--	---	---	---------------------------

Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow
Methyl alcohol 67-56-1	-0.77
Ethylene glycol 107-21-1	-1.93

Other adverse effects

No information available.

13. Disposal Considerations
Waste treatment methods
Disposal methods

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated Packaging

Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number

D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methyl alcohol 67-56-1		Included in waste stream: F039		U154

California Hazardous Waste Codes

212

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Methyl alcohol 67-56-1	Toxic Ignitable

14. Transport Information
DOT
5 Liters or Less:
Proper Shipping Name
Hazard Class
Description

Stock Number PRIM93506

CONSUMER COMMODITY

3

CONSUMER COMMODITY, ORM- D

**Emergency Response Guide
Number**

131

In quantities greater than 5 liters:**Proper Shipping Name**

Stock Number PRIM93555

FLAMMABLE LIQUID, N.O.S. (METHY ALCOHOL) UN1993

Hazard Class

3

Description

FLAMMABLE LIQUID, N.O.S. (METHY ALCOHOL) UN1993

**Emergency Response Guide
Number**

128

TDG**UN-No.**

UN1986

Proper Shipping Name

ALCOHOLS, FLAMMABLE, TOXIC, N.O.S.

Hazard Class

3

Subsidiary Class

6.1

Packing Group

III

DescriptionUN1986, ALCOHOLS, FLAMMABLE, TOXIC, N.O.S. (METHYL ALCOHOL,
AMMONIUM HYDROXIDE), 3(6.1), III**MEX****UN-No.**

UN1986

Proper Shipping Name

ALCOHOLS, FLAMMABLE, TOXIC, N.O.S.

Hazard Class

3

Subsidiary Class

6.1

Packing Group

III

DescriptionUN1986, ALCOHOLS, FLAMMABLE, TOXIC, N.O.S. (METHYL ALCOHOL,
AMMONIUM HYDROXIDE), 3(6.1), III**ICAO****UN-No.**

UN1986

Proper Shipping Name

ALCOHOLS, FLAMMABLE, TOXIC, N.O.S.

Hazard Class

3

Subsidiary Class

6.1

Packing Group

III

DescriptionUN1986, ALCOHOLS, FLAMMABLE, TOXIC, N.O.S. (METHYL ALCOHOL,
AMMONIUM HYDROXIDE), 3(6.1), III**IATA****UN-No.**

UN1986

Proper Shipping Name

ALCOHOLS, FLAMMABLE, TOXIC, N.O.S.

Hazard Class

3

Subsidiary Class

6.1

Packing Group

III

DescriptionUN1986, ALCOHOLS, FLAMMABLE, TOXIC, N.O.S. (METHYL ALCOHOL,
AMMONIUM HYDROXIDE), 3(6.1), III**IMDG/IMO****UN-No.**

UN1986

Proper Shipping Name

ALCOHOLS, FLAMMABLE, TOXIC, N.O.S.

Hazard Class

3

Subsidiary Class	6.1
Packing Group	III
EmS-No.	F-E, S-D
Description	UN1986, ALCOHOLS, FLAMMABLE, TOXIC, N.O.S. (METHYL ALCOHOL, 3(6.1), III, FP 29C

RID

UN-No.	UN1986
Proper Shipping Name	ALCOHOLS, FLAMMABLE, TOXIC, N.O.S.
Hazard Class	3
Packing Group	III
Classification code	FT1
Description	UN1986, ALCOHOLS, FLAMMABLE, TOXIC, N.O.S. (METHYL ALCOHOL, AMMONIUM HYDROXIDE), 3(6.1), III
ADR/RID Labels	6.1

ADR

UN-No.	UN1986
Proper Shipping Name	ALCOHOLS, FLAMMABLE, TOXIC, N.O.S.
Hazard Class	3
Packing Group	III
Classification code	F1
Description	UN1986, ALCOHOLS, FLAMMABLE, TOXIC, N.O.S. (METHYL ALCOHOL, AMMONIUM HYDROXIDE), 3(6.1), III
ADR/RID Labels	6.1

ADN

UN-No.	UN1986
Proper Shipping Name	ALCOHOLS, FLAMMABLE, TOXIC, N.O.S.
Hazard Class	3
Packing Group	III
Classification code	FT1
Special Provisions	274, 802
Description	UN1986, ALCOHOLS, FLAMMABLE, TOXIC, N.O.S. (METHYL ALCOHOL, AMMONIUM HYDROXIDE), 3(6.1), III
Hazard Labels	3 + 6.1
Limited Quantity	5 L
Ventilation	VE01, VE02

15. Regulatory Information

International Inventories

TSCA	Complies
DSL	All components are listed either on the DSL or NDSL.
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory	
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List	

US Federal Regulations
SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA).
 This product contains a chemical or chemicals which are subject to the reporting requirements of the

Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Methyl alcohol - 67-56-1	67-56-1	30 - 40	1.0
Ethylene glycol 107-21-1	107-21-1	1 - 5	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act) This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Methyl alcohol 67-56-1	5000 lb.		RQ= 2270 kg final RQ RQ= 5000 lb final RQ
Ethylene glycol 107-21-1	5000 lb.		RQ= 5000 kg final RQ RQ= 2270 lb final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
C.I. Food red 15 – 81 – 88 - 9	Carcinogen

US State Right-to-know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Methyl alcohol 67-56-1	X	X	X	X	X
Ethylene glycol 107-21-1	X	X	X	X	X

International Regulations

Mexico

National occupational exposure limits

	Component	Carcinogen Status	Exposure Limits	
	Methyl alcohol 67-56-1 (15 - 40)		Mexico: TWA= 200 ppm Mexico: TWA= 260 mg/m ³ Mexico: STEL= 250 ppm Mexico: STEL= 310 mg/m ³	
	Ethylene glycol 107-21-1 (1 – 5)		Mexico: Ceiling 100 mg/m ³	

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

B2 - Flammable liquid



16. Other Information

NFPA Health Hazards 3 Flammability 3 Instability 0 Physical and Chemical
HMIS Health Hazards 3 * Flammability 3 Physical Hazard 0 Personal Protection X

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By: Randy Boitz

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet