



## Safety Data Sheet

Copyright, 2019, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	29-5600-1	<b>Version Number:</b>	2.02
<b>Issue Date:</b>	02/26/19	<b>Supersedes Date:</b>	09/07/18

### Product identifier

3M™ Headlight Lens Restoration System, PN 39008, 39008B, 39008F, 39008F2, 39033, 39078, 39078S

### ID Number(s):

60-4550-5554-5, 60-4550-6558-5, 60-4550-7083-3, 60-4551-0351-9, 60-4551-0850-0, 60-4551-0851-8

7000045522, 7010327964, 7100190993

### Recommended use

Automotive

### Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Automotive Aftermarket

<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

### Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

**This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:**

29-3593-0

**DISCLAIMER:** The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at [www.3M.com](http://www.3M.com)



## Safety Data Sheet

Copyright, 2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document Group:** 29-3593-0  
**Issue Date:** 06/14/21

**Version Number:** 5.02  
**Supersedes Date:** 08/22/19

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Rubbing Compound, 05973, 05974, 05968, 3900, 39002, 39002S, 39005

#### Product Identification Numbers

ID Number	UPC	ID Number	UPC
LB-K100-0959-1		LB-K100-0959-2	
LB-K100-0961-4		LB-K100-0960-9	00051131039001
LB-K100-0954-8	00051131059689	LB-K100-0933-1	00051131059733
LB-K100-0933-2	00051131059740	LB-K100-0961-0	00051131390027
LB-K100-0961-1	00051131390058	60-4550-5785-5	00051131059733
60-4550-5787-1	00051131059740	60-4550-5806-9	
60-4550-6559-3	00051131390027	60-4550-7122-9	00051131390058
60-4551-0213-1	00051131039001	60-4551-0214-9	00051131390027
60-4551-0215-6	00051131390027	60-4551-0216-4	00051131390058

7000120042, 7000021276, 7000120073, 7100159911, 7100168978, 7100169724, 7100177111

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Automotive, Rubbing Compound

#### 1.3. Supplier's details

**MANUFACTURER:** 3M  
**DIVISION:** Automotive Aftermarket  
**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA  
**Telephone:** 1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

#### 2.1. Hazard classification

Specific Target Organ Toxicity (repeated exposure): Category 1.

**2.2. Label elements****Signal word**

Danger

**Symbols**

Health Hazard |

**Pictograms****Hazard Statements**

Causes damage to organs through prolonged or repeated exposure:  
respiratory system |

**Precautionary Statements****General:**

Keep out of reach of children.

**Prevention:**

Do not breathe dust/fume/gas/mist/vapors/spray.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

**Response:**

Get medical advice/attention if you feel unwell.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

1% of the mixture consists of ingredients of unknown acute oral toxicity.

2% of the mixture consists of ingredients of unknown acute inhalation toxicity.

**SECTION 3: Composition/information on ingredients**

<b>Ingredient</b>	<b>C.A.S. No.</b>	<b>% by Wt</b>
Water	7732-18-5	30 - 60 Trade Secret *
Silica	7631-86-9	15 - 40 Trade Secret *
Hydrotreated Light Petroleum Distillates	64742-47-8	10 - 30 Trade Secret *
Kaolinite	1318-74-7	3 - 7 Trade Secret *
Solvent Dewaxed Heavy Paraffinic Distillate (Petroleum)	64742-65-0	1 - 5 Trade Secret *
Glycerin	56-81-5	< 2 Trade Secret *
Oleic Acid	112-80-1	< 2 Trade Secret *
Illite	12173-60-3	0.5 - 1.5 Trade Secret *
Hydrotreated Light Paraffinic Distillates (Petroleum)	64742-55-8	< 1 Trade Secret *
Poly(Oxyethylene)Sorbitan Monostearate	9005-67-8	0.1 - 1 Trade Secret *
Solvent Dewaxed Light Paraffinic Distillates (Petroleum)	64742-56-9	< 1 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade

secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

**Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

Non-combustible. Use a fire fighting agent suitable for surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Keep out of reach of children. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment.

### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Aluminum, insoluble compounds	1318-74-7	ACGIH	TWA(respirable fraction):1 mg/m3	A4: Not class. as human carcin
Glycerin	56-81-5	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	
Kerosine (petroleum)	64742-47-8	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3	A3: Confirmed animal carcin., SKIN
Mineral oils (untreated and mildly treated)	64742-55-8	ACGIH	Limit value not established:	A2: Suspected human carcin., Cntrl all exposr-low as possib
Paraffin oil	64742-55-8	OSHA	TWA(as mist):5 mg/m3	
Mineral oils (untreated and mildly treated)	64742-56-9	ACGIH	Limit value not established:	A2: Suspected human carcin., Cntrl all exposr-low as possib
MINERAL OILS, HIGHLY-REFINED OILS	64742-56-9	ACGIH	TWA(inhalable fraction):5 mg/m3	A4: Not class. as human carcin
Paraffin oil	64742-56-9	OSHA	TWA(as mist):5 mg/m3	
Paraffin oil	64742-65-0	OSHA	TWA(as mist):5 mg/m3	
PETROLEUM DISTILLATES	64742-65-0	OSHA	TWA:2000 mg/m3(500 ppm)	
SILICA, AMORPHOUS	7631-86-9	OSHA	TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

When only incidental contact is anticipated, alternative glove material(s) may be used. If contact with the glove does occur, remove immediately and replace with a set of new gloves. For incidental contact, gloves made of the following material(s) may be used: Nitrile Rubber

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties****Appearance**

Physical state  
Color

Liquid  
Tan

**Odor**

Slight Solvent

**Odor threshold**

*No Data Available*

**pH**

7.5 - 8.5

**Melting point**

*Not Applicable*

**Boiling Point**

98.3 °C

**Flash Point**

No flash point

**Evaporation rate**

*No Data Available*

**Flammability (solid, gas)**

Not Applicable

**Flammable Limits(LEL)**

*No Data Available*

**Flammable Limits(UEL)**

*No Data Available*

**Vapor Pressure**

*No Data Available*

**Vapor Density**

*No Data Available*

**Density**

1.2 g/ml

**Specific Gravity**

1.2 [Ref Std: WATER=1]

**Solubility in Water**

Negligible

**Solubility- non-water**

*No Data Available*

**Partition coefficient: n-octanol/ water**

*No Data Available*

**Autoignition temperature**

*No Data Available*

**Decomposition temperature**

*No Data Available*

**Viscosity**

6,000 - 18,000 centipoise [Test Method: Brookfield] [Details: #6]

<b>Hazardous Air Pollutants</b>	Spindle]
<b>Molecular weight</b>	0.00002 lb HAPS/lb solids [ <i>Test Method</i> :Calculated]
<b>Volatile Organic Compounds</b>	<i>No Data Available</i>
<b>Volatile Organic Compounds</b>	213 g/l [ <i>Test Method</i> :calculated SCAQMD rule 443.1]
<b>Percent volatile</b>	15.2 % weight [ <i>Test Method</i> :calculated per CARB title 2]
<b>VOC Less H2O &amp; Exempt Solvents</b>	58.3 % weight
	415 g/l [ <i>Test Method</i> :calculated SCAQMD rule 443.1]

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat

Sparks and/or flames

### 10.5. Incompatible materials

None known.

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	At Elevated Temperatures
Carbon dioxide	At Elevated Temperatures

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

May cause additional health effects (see below).

#### Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

#### Eye Contact:

Dust created by cutting, grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.



**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

**Additional Health Effects:****Prolonged or repeated exposure may cause target organ effects:**

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

**Carcinogenicity:**

<b>Ingredient</b>	<b>CAS No.</b>	<b>Class Description</b>	<b>Regulation</b>
Generic: Mineral oils (untreated and mildly treated)	64742-55-8	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Generic: Mineral oils (untreated and mildly treated)	64742-55-8	Known human carcinogen	National Toxicology Program Carcinogens
Generic: Mineral oils (untreated and mildly treated)	64742-56-9	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Generic: Mineral oils (untreated and mildly treated)	64742-56-9	Known human carcinogen	National Toxicology Program Carcinogens

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

<b>Name</b>	<b>Route</b>	<b>Species</b>	<b>Value</b>
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Hydrotreated Light Petroleum Distillates	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydrotreated Light Petroleum Distillates	Inhalation-Vapor (4 hours)	Rat	LC50 > 12 mg/l
Hydrotreated Light Petroleum Distillates	Ingestion	Rat	LD50 > 5,000 mg/kg
Kaolinite	Dermal		LD50 estimated to be > 5,000 mg/kg
Kaolinite	Ingestion	Human	LD50 > 15,000 mg/kg
Solvent Dewaxed Heavy Paraffinic Distillate (Petroleum)	Dermal	Rabbit	LD50 > 5,000 mg/kg
Solvent Dewaxed Heavy Paraffinic Distillate (Petroleum)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 4 mg/l
Solvent Dewaxed Heavy Paraffinic Distillate (Petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Oleic Acid	Dermal	Guinea pig	LD50 > 3,000 mg/kg
Oleic Acid	Ingestion	Rat	LD50 57,000 mg/kg
Glycerin	Dermal	Rabbit	LD50 estimated to be > 5,000 mg/kg
Glycerin	Ingestion	Rat	LD50 > 5,000 mg/kg
Poly(Oxyethylene)Sorbitan Monostearate	Dermal		LD50 estimated to be > 5,000 mg/kg
Poly(Oxyethylene)Sorbitan Monostearate	Ingestion	Rat	LD50 > 62,640 mg/kg
Solvent Dewaxed Light Paraffinic Distillates (Petroleum)	Dermal	Rabbit	LD50 > 5,000 mg/kg
Solvent Dewaxed Light Paraffinic Distillates (Petroleum)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 4 mg/l
Solvent Dewaxed Light Paraffinic Distillates (Petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Silica	Rabbit	No significant irritation
Hydrotreated Light Petroleum Distillates	Rabbit	Mild irritant
Kaolinite	Professional judgement	No significant irritation
Oleic Acid	Rabbit	Minimal irritation
Glycerin	Rabbit	No significant irritation
Solvent Dewaxed Light Paraffinic Distillates (Petroleum)	Rabbit	Minimal irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Silica	Rabbit	No significant irritation
Hydrotreated Light Petroleum Distillates	Rabbit	Mild irritant
Kaolinite	Professional judgement	No significant irritation
Oleic Acid	Rabbit	Mild irritant
Glycerin	Rabbit	No significant irritation
Solvent Dewaxed Light Paraffinic Distillates (Petroleum)	Rabbit	No significant irritation

**Skin Sensitization**

Name	Species	Value
Silica	Human and animal	Not classified
Hydrotreated Light Petroleum Distillates	Guinea pig	Not classified
Glycerin	Guinea pig	Not classified
Solvent Dewaxed Light Paraffinic Distillates (Petroleum)	Guinea pig	Not classified

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Silica	In Vitro	Not mutagenic
Oleic Acid	In Vitro	Some positive data exist, but the data are not sufficient for classification
Solvent Dewaxed Light Paraffinic Distillates (Petroleum)	In vivo	Not mutagenic
Solvent Dewaxed Light Paraffinic Distillates (Petroleum)	In Vitro	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Kaolinite	Inhalation	Multiple animal species	Not carcinogenic
Oleic Acid	Dermal	Mouse	Not carcinogenic
Oleic Acid	Ingestion	Rat	Not carcinogenic
Oleic Acid	Not Specified	Multiple animal	Not carcinogenic

		species	
Glycerin	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification
Solvent Dewaxed Light Paraffinic Distillates (Petroleum)	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

## Reproductive Toxicity

### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Glycerin	Ingestion	Not classified for female reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not classified for development	Rat	NOAEL 2,000 mg/kg/day	2 generation

## Target Organ(s)

### Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Silica	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Kaolinite	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL NA	occupational exposure
Kaolinite	Inhalation	pulmonary fibrosis	Not classified	Rat	NOAEL Not available	
Oleic Acid	Ingestion	liver   immune system	Not classified	Rat	NOAEL 2,250 mg/kg/day	108 weeks
Oleic Acid	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 2,550 mg/kg/day	108 weeks
Glycerin	Inhalation	respiratory system   heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 3.91 mg/l	14 days
Glycerin	Ingestion	endocrine system   hematopoietic system   liver   kidney and/or bladder	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 years
Solvent Dewaxed Light Paraffinic Distillates (Petroleum)	Dermal	hematopoietic system   liver   kidney and/or bladder	Not classified	Rabbit	NOAEL 5,000 mg/kg/day	3 weeks

## Aspiration Hazard

Name	Value
Hydrotreated Light Petroleum Distillates	Aspiration hazard
Solvent Dewaxed Light Paraffinic Distillates (Petroleum)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## SECTION 12: Ecological information

### Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

#### EPCRA 311/312 Hazard Classifications:

##### Physical Hazards

Not applicable

##### Health Hazards

Specific target organ toxicity (single or repeated exposure)

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: Other information

### NFPA Hazard Classification

**Health:** 1 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**Document Group:** 29-3593-0

**Version Number:** 5.02

**Issue Date:** 06/14/21

**Supersedes Date:** 08/22/19

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at [www.3M.com](http://www.3M.com)