

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Date of issue: 03/08/2017 Revision date: 03/09/2020 Version: 2.2

SECTION 1: Identification

Identification

Product name : Winter Treat Plus : 103051, 103052, 103073 Product code

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Diesel fuel additive

1.3. Details of the supplier of the safety data sheet

Manufacturer

R.B. Howes & Co., Inc. 3511 North Ohio Street Wichita, KS 67219 - USA

T 401-294-5500, 1-800 GET HOWES (438-4693)

Manufacturer

R.B. Howes & Co., Inc. 35 Regan Road

Brampton, ON L7A 1B2 - Canada

T 401-294-5500, 1-800 GET HOWES (438-4693)

Emergency telephone number

Emergency number : CHEMTREC 1 (800) 424-9300 / 703-527-3887

SECTION 2: Hazard identification

Classification of the substance or mixture

GHS classification

Flam. Liq. 3 Skin Irrit. 2 Carc. 2 Repr. 2 Asp. Tox. 1

2.2. **Label elements**

GHS labelling

Hazard pictograms (GHS)





Signal word (GHS)

Hazard statements (GHS)

Precautionary statements (GHS)

: Danger

: Flammable liquid and vapour. Causes skin irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May be fatal if swallowed and enters airways

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosionproof electrical, lighting, ventilating equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

Unknown acute toxicity

Not applicable

SECTION 3: Composition/information on ingredients

Substances

Not applicable

03/09/2020 EN (English) Page 1

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

3.2. Mixtures

Name	Product identifier	%
Stoddard solvent	(CAS-No.) 8052-41-3	15 - 40
Distillates, petroleum, hydrotreated light naphthenic	(CAS-No.) 64742-53-6	10 - 30
Petroleum distillates, hydrotreated light	(CAS-No.) 64742-47-8	10 - 30
Solvent naphtha, petroleum, light aromatic	(CAS-No.) 64742-95-6	7 - 13
Benzene, 1,2,4-trimethyl-	(CAS-No.) 95-63-6	5 - 10
Solvent naphtha, petroleum, heavy aromatic	(CAS-No.) 64742-94-5	1 - 5
Xylenes (o-, m-, p- isomers)	(CAS-No.) 1330-20-7	1 - 5
1,3,5-Trimethylbenzene	(CAS-No.) 108-67-8	0.5 - 1.5
1,2,3-Trimethylbenzene	(CAS-No.) 526-73-8	0.5 - 1.5
Nonane	(CAS-No.) 111-84-2	0.5 - 1.5
Naphthalene	(CAS-No.) 91-20-3	0.5 - 1.5
Ethylbenzene	(CAS-No.) 100-41-4	0.1 - 1
Isopropylbenzene	(CAS-No.) 98-82-8	0.1 - 1

^{*}Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before

reuse. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : IF SWALLOWED: immediately call a POISON CENTER or doctor/physician. Do NOT induce

vomiting. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the

skin.

Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear

production, with possible redness and swelling.

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Carbon dioxide. Water spray or fog.

Unsuitable extinguishing media : Do not use water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour. Products of combustion may include, and are not limited to:

oxides of carbon.

Explosion hazard : May form flammable/explosive vapour-air mixture.

Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Advice for firefighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Cool down the containers exposed to heat with a water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Sect

: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition. Use special care to avoid static electric charges.

03/09/2020 EN (English) 2/11

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment

: Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.

Methods for cleaning up

: Sweep or shovel spills into appropriate container for disposal. Provide ventilation. Spilled material may present a slipping hazard.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Handle empty containers with care because residual vapours are flammable.

Precautions for safe handling

: Keep away from sources of ignition - No smoking. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Avoid contact with skin and eyes. Avoid breathing vapour or mist. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area.

Hygiene measures

: Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

- : Proper grounding procedures to avoid static electricity should be followed:
- Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Stoddard solvent (8052-41-3)		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	Remark (ACGIH)	Eye, skin, & kidney dam;
OSHA	OSHA PEL (TWA) (mg/m³)	2900 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	500 ppm
IDLH	US IDLH (mg/m³)	20000 mg/m³
NIOSH	NIOSH REL (TWA) (mg/m³)	350 mg/m³
NIOSH	NIOSH REL (ceiling) (mg/m³)	1800 mg/m³

Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)

Not applicable

Petroleum distillates, hydrotreated light (64742-47-8)

Not applicable

Solvent naphtha, petroleum, light aromatic (64742-95-6)

Not applicable

_			. (05 00 0)	
Benzene.	1.2.	4-trimeth	vl- (95-63-6)	

NIOSH	NIOSH REL (TWA) (mg/m³)	125 mg/m³
NIOSH	NIOSH REL (TWA) (ppm)	25 ppm

Solvent naphtha, petroleum, heavy aromatic (64742-94-5)

Not applicable

03/09/2020 EN (English) 3/11

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Xylenes (o-, m-, p- isomers)	(1330-20-7)	
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
ACGIH	Remark (ACGIH)	URT & eye irr; CNS impair
OSHA	OSHA PEL (TWA) (mg/m³)	435 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
1,2,3-Trimethylbenzene (526	, , , , ,	···
NIOSH	NIOSH REL (TWA) (mg/m³)	125 mg/m³
NIOSH	NIOSH REL (TWA) (ppm)	25 ppm
1,3,5-Trimethylbenzene (108	L-67-8)	<u> '' </u>
NIOSH	NIOSH REL (TWA) (mg/m³)	125 mg/m³
NIOSH	NIOSH REL (TWA) (ppm)	25 ppm
Nonane (111-84-2)		<u> </u>
ACGIH	ACGIH TWA (ppm)	200 ppm
NIOSH	NIOSH REL (TWA) (mg/m³)	1050 mg/m³
NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
Naphthalene (91-20-3)		<u> </u>
ACGIH	ACGIH TWA (ppm)	10 ppm
OSHA	OSHA PEL (TWA) (mg/m³)	50 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	10 ppm
IDLH	US IDLH (ppm)	250 ppm
NIOSH	NIOSH REL (TWA) (mg/m³)	50 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	10 ppm
NIOSH	NIOSH REL (STEL) (mg/m³)	75 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	15 ppm
Ethylbenzene (100-41-4)		TO PP
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	URT irr; kidney dam (nephropathy)
OSHA	OSHA PEL (TWA) (mg/m³)	435 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
IDLH	US IDLH (ppm)	800 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m³)	435 mg/m³
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (mg/m³)	545 mg/m³
NIOSH	NIOSH REL (STEL) (ppm)	125 ppm
Isopropylbenzene (98-82-8)	, , , , ,	<u> </u>
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	Remark (ACGIH)	Lung cancer; liver and lung dam; A2 (Suspected Human Carcinogen: Human data are accepted as adequate in quality but are conflicting or insufficient to classify the agent as a confirmed human carcinogen; OR, the agent is carcinogenic in experimental animals at dose(s), by route(s) of exposure, at site(s), of histologic type(s), or by mechanism(s) considered relevant to worker exposure. The A2 is used primarily when there is limited evidence or carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals with relevance to humans)

03/09/2020 EN (English) 4/11

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Isopropylbenzene (98-82-8)		
OSHA	OSHA PEL (TWA) (mg/m³)	245 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	50 ppm
IDLH	US IDLH (ppm)	900 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m³)	245 mg/m³
NIOSH	NIOSH REL (TWA) (ppm)	50 ppm

8.2. Exposure controls

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below

recommended exposure limits. Ensure good ventilation of the work station.

Hand protection : Wear suitable gloves resistant to chemical penetration.

Eye protection : Safety glasses or goggles are recommended when using product.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection

must be based on known or anticipated exposure levels, the hazards of the product and the

safe working limits of the selected respirator.

Environmental exposure controls : Avoid release to the environment.

Other information : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or

smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : No data available Colour : Light amber Odour : Distinctive Odour threshold No data available рΗ : No data available : No data available Melting point Freezing point : No data available : 164 °C (327 °F) Boiling point

Flash point : $\geq 54.4 \,^{\circ}\text{C} \, (\geq 130 \,^{\circ}\text{F}) \, [\text{Closed cup}]$

Relative evaporation rate (butylacetate=1) : No data available

Flammability (solid, gas) : Flammable liquid and vapour

Vapour pressure : < 0.1 mm Hg
Relative vapour density at 20 °C : > 1 (air = 1)
Relative density : < 0.9 (water = 1)
Solubility : Insoluble
Partition coefficient n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

: No data available

Viscosity, kinematic : 9.494 cSt @ 40 °C (104 °F)

Viscosity, dynamic : No data available
Explosive limits : No data available
Explosive properties : No data available
Oxidising properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions. May form flammable/explosive vapour-air mixture.

03/09/2020 EN (English) 5/11

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Sources of ignition. Heat. Incompatible materials. Direct sunlight.

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.

Acute toxicity (dermal) : Not classified.

Acute toxicity (inhalation) : Not classified.

Acute toxicity (inhalation)	: Not classified.
Distillates, petroleum, hydrotreated light na	phthenic (64742-53-6)
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	2180 mg/m³ (Exposure time: 4 h)
Petroleum distillates, hydrotreated light (64	742-47-8)
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.2 mg/l/4h
Solvent naphtha, petroleum, light aromatic	(64742-95-6)
LD50 oral rat	8400 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	3400 ppm/4h
Benzene, 1,2,4-trimethyl- (95-63-6)	
LD50 oral rat	3280 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat	18 g/m³ (Exposure time: 4 h)
Solvent naphtha, petroleum, heavy aromati	c (64742-94-5)
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2 ml/kg
LC50 inhalation rat	> 590 mg/m³ (Exposure time: 4 h)
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	> 4350 mg/kg
LD50 dermal	1700 mg/kg
LC50 inhalation rat	29.08 mg/l/4h
LC50 inhalation rat (Vapours - mg/l/4h)	27.57 mg/l/4h
1,3,5-Trimethylbenzene (108-67-8)	
LC50 inhalation rat	24 g/m³ (Exposure time: 4 h)
Nonane (111-84-2)	
LC50 inhalation rat	3200 ppm/4h
Naphthalene (91-20-3)	
LD50 oral rat	1110 mg/kg
LD50 dermal rabbit	1120 mg/kg
LC50 inhalation rat	> 340 mg/m³ (Exposure time: 1 h)
Ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15400 mg/kg
LC50 inhalation rat	17.4 mg/l/4h

03/09/2020 EN (English) 6/11

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Isopropylbenzene (98-82-8)	
LD50 oral rat	1400 mg/kg
LD50 dermal rabbit	12300 μl/kg
LC50 inhalation rat	> 3577 ppm (Exposure time: 6 h)
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified.
Respiratory or skin sensitisation	: Not classified.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Suspected of causing cancer.
Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC group	3 - Not classifiable
Naphthalene (91-20-3)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen
In OSHA Hazard Communication Carcinogen	Yes
list	
Ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes
Isopropylbenzene (98-82-8)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen
In OSHA Hazard Communication Carcinogen list	Yes
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: Not classified.
Solvent naphtha, petroleum, light aromatic (6	4742-95-6)
STOT-single exposure	May cause drowsiness or dizziness.
Xylenes (o-, m-, p- isomers) (1330-20-7)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Winter Treat Plus	
Viscosity, kinematic (calculated value)	< 20.5 mm²/s @ 40 °C (104 °F)
	: May cause irritation to the respiratory tract.
	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the
-yr	skin.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.
SECTION 12: Ecological information	

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)	
LC50 fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Petroleum distillates, hydrotreated light (64742-47-8)	
LC50 fish 1 45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	

03/09/2020 EN (English) 7/11

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Petroleum distillates, hydrotreated ligh	,
LC50 fish 2	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
Solvent naphtha, petroleum, light arom	atic (64742-95-6)
LC50 fish 1	9.22 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Benzene, 1,2,4-trimethyl- (95-63-6)	
LC50 fish 1	7.19 - 8.28 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Solvent naphtha, petroleum, heavy aro	matic (64742-94-5)
LC50 fish 1	19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	0.95 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	2.34 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LC50 fish 1	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 fish 2	2.661 - 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 2	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)
<u>'</u>	
1,3,5-Trimethylbenzene (108-67-8)	2.49 mg/l /Evnoquro timo: 06 h. Coogias: Dimanhalas prometos)
LC50 fish 1	3.48 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
Naphthalene (91-20-3)	
LC50 fish 1	5.74 - 6.44 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	2.16 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	1.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 Daphnia 2	1.96 mg/l (Exposure time: 48 h - Species: Daphnia magna [Flow through])
Ethylbenzene (100-41-4)	
LC50 fish 1	11.0 - 18.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	1.8 - 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])
NOEC chronic crustacea	0.956 mg/l
Isopropylbenzene (98-82-8)	
LC50 fish 1	6.04 - 6.61 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	0.6 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	4.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 Daphnia 2	7.9 - 14.1 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
2.2. Persistence and degradability	
Winter Treat Plus	
Persistence and degradability	Not established.
r crostorioe and degradability	1101 Ostabilorioa.
2.3. Bioaccumulative potential	
Winter Treat Plus	
Bioaccumulative potential	Not established.
Petroleum distillates, hydrotreated ligh	t (64742-47-8)
BCF fish 1	61 - 159
Benzene, 1,2,4-trimethyl- (95-63-6)	
Partition coefficient n-octanol/water	3.63
Solvent naphtha, petroleum, heavy arol	
BCF fish 1	61 – 159
Partition coefficient n-octanol/water	2.9 – 6.1
Xylenes (o-, m-, p- isomers) (1330-20-7)	
	0.0 45
BCF fish 1 Partition coefficient n-octanol/water	0.6 - 15 2.77 - 3.15

03/09/2020 EN (English) 8/11

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Naphthalene (91-20-3)	
BCF fish 1	30 - 430
Partition coefficient n-octanol/water	3.6
Ethylbenzene (100-41-4)	
BCF fish 1	15
Partition coefficient n-octanol/water	3.2
Isopropylbenzene (98-82-8)	
BCF fish 1	35.5
Partition coefficient n-octanol/water	3.7

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known effects from this product.

Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Additional information : Handle empty containers with care because residual vapours are flammable.

SECTION 14: Transport information

Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

In accordance with DOT/TDG

UN-No.(DOT/TDG) : UN1268

Proper Shipping Name (DOT/TDG) : Petroleum distillates, n.o.s.

Class (DOT/TDG) : Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT/TDG) : III

Transport by sea

This product is currently not packaged to comply with IMDG regulations. It is not intended to be shipped by sea.

Transport by air

This product is currently not packaged to comply with IATA regulations. It is not intended to be shipped by air.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Benzene, 1,2,4-trimethyl- (95-63-6)

Subject to reporting requirements of United States SARA Section 313

Xylenes (o-, m-, p- isomers) (1330-20-7)	
Subject to reporting requirements of United State Listed on EPA Hazardous Air Pollutant (HAPS)	s SARA Section 313
CERCLA RQ	100 lb
Nonane (111-84-2)	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a final TSCA section 4 test rule.
Naphthalene (91-20-3)	
Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a final TSCA section 4 test rule.
CERCLA RQ	100 lb

03/09/2020 EN (English) 9/11

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Ethylbenzene (100-41-4)	
Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a final TSCA section 4 test rule.
CERCLA RQ	1000 lb
Isopropylbenzene (98-82-8)	
Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	5000 lb

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

15.3. US State regulations

MARNING:

This product can expose you to Naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Benzene, 1,2,4-trimethyl-(95-63-6)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S Pennsylvania - RTK (Right to Know) List
Xylenes (o-, m-, p- isomers)(1330-20-7)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S Pennsylvania - RTK (Right to Know) List
1,3,5-Trimethylbenzene(108-67-8)	U.S Massachusetts - Right To Know List
Nonane(111-84-2)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
Naphthalene(91-20-3)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S Pennsylvania - RTK (Right to Know) List
Ethylbenzene(100-41-4)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S Pennsylvania - RTK (Right to Know) List
Isopropylbenzene(98-82-8)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S Pennsylvania - RTK (Right to Know) List
Distillates, petroleum, hydrotreated light naphthenic(64742-53-6)	U.S Massachusetts - Right To Know List
Stoddard solvent(8052-41-3)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Revision date : 03/09/2020 Other information : None.

Prepared by : Nexreg Compliance Inc.

www.Nexreg.com

NFPA health hazard : 2
NFPA fire hazard : 2
NFPA reactivity : 0





03/09/2020 EN (English) 10/11

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Indication of changes:

Disclosure.

SDS HazCom 2012 - WHMIS 2015 (NexReg) - Section 15

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

03/09/2020 EN (English) 11/11