

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.23.2018

Page 1 of 10

POR-15 EPOXY PUTTY - PART A

SECTION 1: Identification

Product identifier

Product name: POR-15 EPOXY PUTTY - PART A

Product code: 49033-A, 249033-A



Recommended use of the product and restriction on use

Relevant identified uses: Sealant & Adhesive

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

United States

P.O.R. Products

38 Portman Road

New Rochelle, NY 10801

914-636-0700

Emergency telephone number:

United States

ChemTel Inc.

+1 800 255 3924

+1 813 248 0585

SECTION 2: Hazard(s) identification

GHS classification:

Eye irritation, category 2A

Skin irritation, category 2

Skin sensitization, category 1

Label elements

Hazard pictograms:



Signal word: Warning

Hazard statements:

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

Precautionary statements:

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists get medical advice/attention

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.23.2018

Page 2 of 10

POR-15 EPOXY PUTTY - PART A

P321 Specific treatment (see first aid instructions on this label).
P362 Take off contaminated clothing and wash before reuse
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P332+P313 If skin irritation occurs: Get medical advice/attention
P362+P364 Take off contaminated clothing and wash it before reuse.
P363 Wash contaminated clothing before reuse
P333+P313 If skin irritation or a rash occurs: Get medical advice/attention
P501 Dispose of contents/container according to local regulations.

Hazards not otherwise classified: None

SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 14808-60-7	Silica, crystalline quartz	0.1-1
CAS number: 25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	10-30
CAS number: 14807-96-6	Talc	30-60
CAS number: 65997-17-3	Glass, oxide, chemicals	30-60

Additional Information: None

SECTION 4: First aid measures

Description of first aid measures

General notes:

Not determined or not applicable.

After inhalation:

Loosen clothing as necessary and position individual in a comfortable position
Maintain an unobstructed airway
Get medical advice/attention if you feel unwell

After skin contact:

Rinse affected area with soap and water
If symptoms develop or persist, seek medical attention
Take off all contaminated clothing
Gently blot or brush away excess product
Wash with plenty of lukewarm, gently flowing water
Get medical advice if skin irritation occurs or you feel unwell

After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes
If symptoms develop or persist, seek medical attention
Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open
Remove contact lenses, if present and easy to do so
Continue rinsing for 15-20 minutes
Get medical advice if eye irritation persists

After swallowing:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.23.2018

Page 3 of 10

POR-15 EPOXY PUTTY - PART A

Rinse mouth thoroughly

Seek medical attention if irritation, discomfort, or vomiting persists

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Not determined or not applicable.

Delayed symptoms and effects:

Not determined or not applicable.

Immediate medical attention and special treatment

Specific treatment:

Not determined or not applicable.

Notes for the doctor:

Not determined or not applicable.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

Use appropriate fire suppression agents for adjacent combustible materials or sources of ignition

Unsuitable extinguishing media:

Not determined or not applicable.

Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors

Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

Special precautions:

Carbon monoxide and carbon dioxide may form upon combustion

Heating causes a rise in pressure, risk of bursting and combustion

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation

Ensure air handling systems are operational

Wear protective eye wear, gloves and clothing

Environmental precautions:

Should not be released into the environment

Prevent from reaching drains, sewer or waterway

Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing

Sweep or scoop up solid material while minimizing dust generation

Dispose of contents / container in accordance with local regulations

Reference to other sections:

Not determined or not applicable.

SECTION 7: Handling and storage

Precautions for safe handling:

Use only with adequate ventilation.

Avoid breathing dust.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.23.2018

Page 4 of 10

POR-15 EPOXY PUTTY - PART A

Do not eat, drink, smoke or use personal products when handling chemical substances.

Conditions for safe storage, including any incompatibilities:

Keep container tightly sealed.

Keep container dry.

Store in a cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
United States (OSHA)	Talc	14807-96-6	OSHA PEL Ceiling 20 mppcf
	Silica, crystalline quartz	14808-60-7	OSHA Z-3 TWA 0.1 mg/m ³ (Respirable fraction); 0.3 mg/m ³ (Total dust)
ACGIH	Talc	14807-96-6	ACGIH TLV TWA 2 mg/m ³ ; (Inhalable particulate matter containing no asbestos and < 1% crystalline silica)
	Glass, oxide, chemicals	65997-17-3	8-Hour Exposure Limit (TLV-TWA): 1 fibers/cm ³
	Silica, crystalline quartz	14808-60-7	ACGIH TLV TWA: 0.025 mg/m ³ (Respirable fraction)
NIOSH	Talc	14807-96-6	NIOSH REL TWA 2.0 mg/m ³
	Glass, oxide, chemicals	65997-17-3	NIOSH Recommended exposure limit (REL) [for up to a 10-hour workday during a 40-hour workweek] is: 3 fibers/cm ³
	Silica, crystalline quartz	14808-60-7	NIOSH TWA 0.05 mg/m ³
Portugal	Talc	14807-96-6	NP 1796-2007 8-hour exposure limit: 2 mg/m ³ (respirable fraction)
Australia	Silica, crystalline quartz	14808-60-7	TWA: 0.1 mg/m ³ (Respirable dust)

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

Biological monitoring may also be appropriate for some substances.

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

Personal protection equipment

Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.23.2018

Page 5 of 10

POR-15 EPOXY PUTTY - PART A

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

General hygienic measures:

- Avoid contact with skin, eyes and clothing.
- Wash hands before breaks and at the end of work.
- Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	White pasty solid
Odor	Ethereal
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	Product does not sustain combustion
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Flammable in the presence of sources of ignition
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	1.923
Solubilities	Easily soluble in: methanol and acetone; Insoluble in: cold water and hot water.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	>200°C (>392°F)
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

Other information

SECTION 10: Stability and reactivity

Reactivity:

Does not react under normal conditions of use and storage.

Chemical stability:

Stable under normal conditions of use and storage.

Possibility of hazardous reactions:

None under normal conditions of use and storage.

Conditions to avoid:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.23.2018

Page 6 of 10

POR-15 EPOXY PUTTY - PART A

None known.

Incompatible materials:

None known.

Hazardous decomposition products:

None known.

SECTION 11: Toxicological information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Skin corrosion/irritation

Assessment: Causes skin irritation

Product data:

No data available.

Substance data:

Name	Result
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Irritating to the skin.

Serious eye damage/irritation

Assessment: Causes serious eye irritation

Product data:

No data available.

Substance data:

Name	Result
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Irritating effect on the eyes.

Respiratory or skin sensitization

Assessment: May cause an allergic skin reaction

Product data:

No data available.

Substance data:

Name	Result
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Sensitization possible through skin contact.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Species	Result
Glass, oxide, chemicals	Not applicable	May cause cancer via inhalation.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.23.2018

Page 7 of 10

POR-15 EPOXY PUTTY - PART A

Name	Species	Result
Silica, crystalline quartz	Silica, crystalline quartz	Airborne particles of respirable size are known to cause cancer.

International Agency for Research on Cancer (IARC):

Name	Classification
Talc	Group 3 - Not classifiable as to its carcinogenicity to humans
Glass, oxide, chemicals	Group 2B
Silica, crystalline quartz	Group 1 - Carcinogenic to humans

National Toxicology Program (NTP):

Name	Classification
Glass, oxide, chemicals	Reasonably anticipated to be human carcinogens
Silica, crystalline quartz	Known to be human carcinogens

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Silica, crystalline quartz	Component affects the lungs through repeated exposure.

Specific target organ toxicity (repeated exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.23.2018

Page 8 of 10

POR-15 EPOXY PUTTY - PART A

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	EC50 - Scenedesmus capricornutum - 9 mg/L - 48 h

Chronic (long-term) toxicity

Product data: No data available.

Substance data: No data available.

Persistence and degradability

Product data: No data available.

Substance data: No data available.

Bioaccumulative potential

Product data: No data available.

Substance data: No data available.

Mobility in soil

Product data: No data available.

Substance data: No data available.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

SECTION 14: Transport information

United States Transportation of dangerous goods (49 CFR DOT)

UN number	Not Regulated
UN proper shipping name	Not Regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

International Maritime Dangerous Goods (IMDG)

UN number	Not Regulated
UN proper shipping name	Not Regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.23.2018

Page 9 of 10

POR-15 EPOXY PUTTY - PART A

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	Not Regulated
UN proper shipping name	Not Regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

SECTION 15: Regulatory information

United States regulations

Inventory listing (TSCA):

14807-96-6	Talc	Listed
65997-17-3	Glass, oxide, chemicals	Listed
25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Listed
14808-60-7	Silica, crystalline quartz	Listed

Significant New Use Rule (TSCA Section 5): Not determined.

Export notification under TSCA Section 12(b): Not determined.

SARA Section 302 extremely hazardous substances: Not determined.

SARA Section 313 toxic chemicals:

14807-96-6	Talc	Not Listed
65997-17-3	Glass, oxide, chemicals	Not Listed

CERCLA: Not determined.

RCRA: Not determined.

Section 112(r) of the Clean Air Act (CAA): Not determined.

Massachusetts Right to Know:

14807-96-6	Talc	Listed
65997-17-3	Glass, oxide, chemicals	Listed
14808-60-7	Silica, crystalline quartz	Listed

New Jersey Right to Know:

14807-96-6	Talc	Listed
65997-17-3	Glass, oxide, chemicals	Listed
14808-60-7	Silica, crystalline quartz	Not Listed

New York Right to Know:

14807-96-6	Talc	Not Listed
65997-17-3	Glass, oxide, chemicals	Not Listed
14808-60-7	Silica, crystalline quartz	Not Listed

Pennsylvania Right to Know:

14807-96-6	Talc	Listed
------------	------	--------

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200


Initial preparation date: 04.23.2018

Page 10 of 10

POR-15 EPOXY PUTTY - PART A

65997-17-3	Glass, oxide, chemicals	Listed
14808-60-7	Silica, crystalline quartz	Listed

California Proposition 65:

 **WARNING:** This product can expose you to Silica, crystalline quartz, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 2-0-0

HMIS: 2-0-0

Initial preparation date: 04.23.2018

End of Safety Data Sheet

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.23.2018

Page 1 of 10

POR-15 EPOXY PUTTY - PART B

SECTION 1: Identification

Product identifier

Product name: POR-15 EPOXY PUTTY - PART B

Product code: 49033-B, 249033-B



Recommended use of the product and restriction on use

Relevant identified uses: Sealant & Adhesive

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

United States

P.O.R. Products

38 Portman Road

New Rochelle, NY 10801

914-636-0700

Emergency telephone number:

United States

ChemTel Inc.

+1 800 255 3924

+1 813 248 0585

SECTION 2: Hazard(s) identification

GHS classification:

Eye irritation, category 2A

Skin irritation, category 2

Skin sensitization, category 1

Label elements

Hazard pictograms:



Signal word: Warning

Hazard statements:

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

Precautionary statements:

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists get medical advice/attention

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.23.2018

Page 2 of 10

POR-15 EPOXY PUTTY - PART B

P321 Specific treatment (see first aid instructions on this label).
P362 Take off contaminated clothing and wash before reuse
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P332+P313 If skin irritation occurs: Get medical advice/attention
P362+P364 Take off contaminated clothing and wash it before reuse.
P363 Wash contaminated clothing before reuse
P333+P313 If skin irritation or a rash occurs: Get medical advice/attention
P501 Dispose of contents/container according to local regulations.

Hazards not otherwise classified: None

SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 14808-60-7	Silica, crystalline quartz	0.1-1
CAS number: 90-72-2	Phenol, 2,4,6-tris[(dimethylamino)methyl]-	1-5
CAS number: 25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	1-5
CAS number: 14807-96-6	Talc	30-60
CAS number: 65997-17-3	Glass, oxide, chemicals	10-30

Additional Information: None

SECTION 4: First aid measures

Description of first aid measures

General notes:

Not determined or not applicable.

After inhalation:

Loosen clothing as necessary and position individual in a comfortable position

Maintain an unobstructed airway

Get medical advice/attention if you feel unwell

After skin contact:

Rinse affected area with soap and water

If symptoms develop or persist, seek medical attention

Take off all contaminated clothing

Gently blot or brush away excess product

Wash with plenty of lukewarm, gently flowing water

Get medical advice if skin irritation occurs or you feel unwell

After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes

If symptoms develop or persist, seek medical attention

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open

Remove contact lenses, if present and easy to do so

Continue rinsing for 15-20 minutes

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.23.2018

Page 3 of 10

POR-15 EPOXY PUTTY - PART B

Get medical advice if eye irritation persists

After swallowing:

Rinse mouth thoroughly

Seek medical attention if irritation, discomfort, or vomiting persists

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Not determined or not applicable.

Delayed symptoms and effects:

Not determined or not applicable.

Immediate medical attention and special treatment

Specific treatment:

Not determined or not applicable.

Notes for the doctor:

Not determined or not applicable.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

Use appropriate fire suppression agents for adjacent combustible materials or sources of ignition

Unsuitable extinguishing media:

Not determined or not applicable.

Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors

Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

Special precautions:

Carbon monoxide and carbon dioxide may form upon combustion

Heating causes a rise in pressure, risk of bursting and combustion

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation

Ensure air handling systems are operational

Wear protective eye wear, gloves and clothing

Environmental precautions:

Should not be released into the environment

Prevent from reaching drains, sewer or waterway

Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing

Sweep or scoop up solid material while minimizing dust generation

Dispose of contents / container in accordance with local regulations

Reference to other sections:

Not determined or not applicable.

SECTION 7: Handling and storage

Precautions for safe handling:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.23.2018

Page 4 of 10

POR-15 EPOXY PUTTY - PART B

Use only with adequate ventilation.

Avoid breathing dust.

Do not eat, drink, smoke or use personal products when handling chemical substances.

Conditions for safe storage, including any incompatibilities:

Keep container tightly sealed.

Keep container dry.

Store in a cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
United States (OSHA)	Talc	14807-96-6	OSHA PEL Ceiling 20 mppcf
	Silica, crystalline quartz	14808-60-7	OSHA Z-3 TWA 0.1 mg/m ³ (Respirable fraction); 0.3 mg/m ³ (Total dust)
ACGIH	Talc	14807-96-6	ACGIH TLV TWA 2 mg/m ³ ; (Inhalable particulate matter containing no asbestos and < 1% crystalline silica)
	Glass, oxide, chemicals	65997-17-3	8-Hour Exposure Limit (TLV-TWA): 1 fibers/cm ³
	Silica, crystalline quartz	14808-60-7	ACGIH TLV TWA: 0.025 mg/m ³ (Respirable fraction)
NIOSH	Talc	14807-96-6	NIOSH REL TWA 2.0 mg/m ³
	Glass, oxide, chemicals	65997-17-3	NIOSH Recommended exposure limit (REL) [for up to a 10-hour workday during a 40-hour workweek] is: 3 fibers/cm ³
	Silica, crystalline quartz	14808-60-7	NIOSH TWA 0.05 mg/m ³
Portugal	Talc	14807-96-6	NP 1796-2007 8-hour exposure limit: 2 mg/m ³ (respirable fraction)
Australia	Silica, crystalline quartz	14808-60-7	TWA: 0.1 mg/m ³ (Respirable dust)

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

Biological monitoring may also be appropriate for some substances.

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

Personal protection equipment

Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

Skin and body protection:

Select glove material impermeable and resistant to the substance.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.23.2018

Page 5 of 10

POR-15 EPOXY PUTTY - PART B

Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Beige colored pasty solid
Odor	Amine-like
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	Product does not sustain combustion
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Flammable in the presence of sources of ignition
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	1.92 g/cm ³
Relative density	1.923
Solubilities	Easily soluble in: methanol and acetone; Insoluble in: cold water and hot water.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	>200°C (>392°F)
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

Other information

SECTION 10: Stability and reactivity

Reactivity:

Does not react under normal conditions of use and storage.

Chemical stability:

Stable under normal conditions of use and storage.

Possibility of hazardous reactions:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.23.2018

Page 6 of 10

POR-15 EPOXY PUTTY - PART B

None under normal conditions of use and storage.

Conditions to avoid:

None known.

Incompatible materials:

None known.

Hazardous decomposition products:

None known.

SECTION 11: Toxicological information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Route	Result
Phenol, 2,4,6-tris[(dimethylamino)methyl]-	oral	LD50 - Rat - 1,200 mg/kg

Skin corrosion/irritation

Assessment: Causes skin irritation

Product data:

No data available.

Substance data:

Name	Result
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Irritating to the skin.
Phenol, 2,4,6-tris[(dimethylamino)methyl]-	Irritating to the skin.

Serious eye damage/irritation

Assessment: Causes serious eye irritation

Product data:

No data available.

Substance data:

Name	Result
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Irritating effect on the eyes.
Phenol, 2,4,6-tris[(dimethylamino)methyl]-	Irritating effect on the eyes.

Respiratory or skin sensitization

Assessment: May cause an allergic skin reaction

Product data:

No data available.

Substance data:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.23.2018

Page 7 of 10

POR-15 EPOXY PUTTY - PART B

Name	Result
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Sensitization possible through skin contact.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Species	Result
Glass, oxide, chemicals	Not applicable	May cause cancer via inhalation.
Silica, crystalline quartz	Silica, crystalline quartz	Airborne particles of respirable size are known to cause cancer.

International Agency for Research on Cancer (IARC):

Name	Classification
Talc	Group 3 - Not classifiable as to its carcinogenicity to humans
Glass, oxide, chemicals	Group 2B
Silica, crystalline quartz	Group 1 - Carcinogenic to humans

National Toxicology Program (NTP):

Name	Classification
Glass, oxide, chemicals	Reasonably anticipated to be human carcinogens
Silica, crystalline quartz	Known to be human carcinogens

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Silica, crystalline quartz	Component affects the lungs through repeated exposure.

Specific target organ toxicity (repeated exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Aspiration toxicity

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.23.2018

Page 8 of 10

POR-15 EPOXY PUTTY - PART B

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	EC50 - Scenedesmus capricornutum - 9 mg/L - 48 h

Chronic (long-term) toxicity

Product data: No data available.

Substance data: No data available.

Persistence and degradability

Product data: No data available.

Substance data: No data available.

Bioaccumulative potential

Product data: No data available.

Substance data: No data available.

Mobility in soil

Product data: No data available.

Substance data: No data available.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

SECTION 14: Transport information

United States Transportation of dangerous goods (49 CFR DOT)

UN number	Not Regulated
UN proper shipping name	Not Regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.23.2018

Page 9 of 10

POR-15 EPOXY PUTTY - PART B

Special precautions for user	None
------------------------------	------

International Maritime Dangerous Goods (IMDG)

UN number	Not Regulated
UN proper shipping name	Not Regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	Not Regulated
UN proper shipping name	Not Regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

SECTION 15: Regulatory information

United States regulations

Inventory listing (TSCA):

14807-96-6	Talc	Listed
65997-17-3	Glass, oxide, chemicals	Listed
25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxiran	Listed
90-72-2	Phenol, 2,4,6-tris[(dimethylamino)methyl]-	Listed
14808-60-7	Silica, crystalline quartz	Listed

Significant New Use Rule (TSCA Section 5): Not determined.

Export notification under TSCA Section 12(b): Not determined.

SARA Section 302 extremely hazardous substances: Not determined.

SARA Section 313 toxic chemicals:

14807-96-6	Talc	Not Listed
65997-17-3	Glass, oxide, chemicals	Not Listed

CERCLA: Not determined.

RCRA: Not determined.

Section 112(r) of the Clean Air Act (CAA): Not determined.

Massachusetts Right to Know:

14807-96-6	Talc	Listed
65997-17-3	Glass, oxide, chemicals	Listed
14808-60-7	Silica, crystalline quartz	Listed

New Jersey Right to Know:

14807-96-6	Talc	Listed
------------	------	--------

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 04.23.2018

Page 10 of 10

POR-15 EPOXY PUTTY - PART B

65997-17-3	Glass, oxide, chemicals	Listed
14808-60-7	Silica, crystalline quartz	Not Listed


New York Right to Know:

14807-96-6	Talc	Not Listed
65997-17-3	Glass, oxide, chemicals	Not Listed
14808-60-7	Silica, crystalline quartz	Not Listed

Pennsylvania Right to Know:

14807-96-6	Talc	Listed
65997-17-3	Glass, oxide, chemicals	Listed
14808-60-7	Silica, crystalline quartz	Listed

California Proposition 65:

 **WARNING:** This product can expose you to Silica, crystalline quartz, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 2-0-0

HMIS: 2-0-0

Initial preparation date: 04.23.2018

End of Safety Data Sheet