



SAFETY DATA SHEET

1. Identification

Product identifier Motor Medic TranSeal Automatic Transmission Sealer

Other means of identification

SDS number M1512
Part No. M1512
Tariff code 3811.90.0000

Recommended use Seal Sweller

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name RSC Chemical Solutions
Address 600 Radiator Road
Indian Trail, NC 28079
United States
Telephone Customer Service: (704) 821-7643
Technical: (704) 684-1811
Website www.rscbrands.com
E-mail sds@rscbrands.com
Emergency phone number Emergency Telephone: (303) 623-5716
Emergency Contact: RMPDC (877) 740-5015

2. Hazard(s) identification

Physical hazards Flammable liquids Category 3
Health hazards Skin corrosion/irritation Category 2
Specific target organ toxicity, single exposure Category 3 respiratory tract irritation
Aspiration hazard Category 1
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.

Storage	Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), Hydrotreated Heavy Naphthenic		64742-52-5	60 - < 70
Solvent Naphtha (petroleum), Light Arom.		64742-95-6	10 - < 20
Trimethylbenzene		25551-13-7	3 - < 5
1,2,3-trimethylbenzene		526-73-8	1 - < 3
1,2,4-Trimethylbenzene		95-63-6	1 - < 3
Mesitylene; (1,3,5-trimethylbenzene)		108-67-8	1 - < 3
BENZENE,1-METHYLETHYL-		98-82-8	< 1
BENZENE, DIMETHYL		1330-20-7	< 0.3
Other components below reportable levels			10 - < 20

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep out of the reach of children. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
BENZENE, DIMETHYL (CAS 1330-20-7)	PEL	435 mg/m3	
BENZENE,1-METHYLETHY L- (CAS 98-82-8)	PEL	100 ppm 245 mg/m3	
Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	PEL	50 ppm 5 mg/m3	Mist.
Solvent Naphtha (petroleum), Light Arom. (CAS 64742-95-6)	PEL	2000 mg/m3 500 ppm 400 mg/m3	
		100 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
1,2,3-trimethylbenzene (CAS 526-73-8)	TWA	25 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	25 ppm	
BENZENE, DIMETHYL (CAS 1330-20-7)	STEL	150 ppm	
BENZENE,1-METHYLETHYL- (CAS 98-82-8)	TWA	100 ppm	
	TWA	50 ppm	
Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
Mesitylene; (1,3,5-trimethylbenzene) (CAS 108-67-8)	TWA	25 ppm	
Trimethylbenzene (CAS 25551-13-7)	TWA	25 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
1,2,3-trimethylbenzene (CAS 526-73-8)	TWA	125 mg/m3	
		25 ppm	
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	125 mg/m3	
		25 ppm	
BENZENE,1-METHYLETHYL- L- (CAS 98-82-8)	TWA	245 mg/m3	
		50 ppm	
Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.
Mesitylene; (1,3,5-trimethylbenzene) (CAS 108-67-8)	TWA	125 mg/m3	
		25 ppm	
Solvent Naphtha (petroleum), Light Arom. (CAS 64742-95-6)	TWA	400 mg/m3	
		100 ppm	

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
BENZENE, DIMETHYL (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

Skin designation applies.

US - Tennessee OELs: Skin designation

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

Can be absorbed through the skin.

Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.
Individual protection measures, such as personal protective equipment	
Eye/face protection	wear safety glasses with side shields (or goggles)
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	Chemical respirator with organic vapor cartridge and full facepiece if threshold limits are exceeded.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Liquid Clear.
Physical state	Liquid.
Form	Liquid.
Color	Amber
Odor	Petroleum
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-20 °F (-28.89 °C) estimated
Initial boiling point and boiling range	500 °F (260 °C) estimated
Flash point	138.0 °F (58.9 °C) Tag Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	2.8 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	550 °F (287.78 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	7.67 lbs/gal estimated
Explosive properties	Not explosive.
Flammability class	Combustible II estimated

Oxidizing properties	Not oxidizing.
Percent volatile	0.65 % estimated
Specific gravity	0.92 estimated
VOC	0.65 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 3160 mg/kg
BENZENE, DIMETHYL (CAS 1330-20-7)		
<u>Acute</u>		
Oral		
LD50	Rat	3523 - 8600 mg/kg
BENZENE,1-METHYLETHYL- (CAS 98-82-8)		
<u>Acute</u>		
Oral		
LD50	Rat	1400 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

BENZENE, DIMETHYL (CAS 1330-20-7) 3 Not classifiable as to carcinogenicity to humans.

BENZENE,1-METHYLETHYL- (CAS 98-82-8) 2B Possibly carcinogenic to humans.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

BENZENE,1-METHYLETHYL- (CAS 98-82-8) Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 7.19 - 8.28 mg/l, 96 hours
BENZENE, DIMETHYL (CAS 1330-20-7)		
Aquatic		
Fish	LC50	Bluegill (Lepomis macrochirus) 7.711 - 9.591 mg/l, 96 hours
BENZENE,1-METHYLETHYL- (CAS 98-82-8)		
Aquatic		
Crustacea	EC50	Brine shrimp (Artemia sp.) 3.55 - 11.29 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 2.7 mg/l, 96 hours
Mesitylene; (1,3,5-trimethylbenzene) (CAS 108-67-8)		
Aquatic		
Fish	LC50	Goldfish (Carassius auratus) 9.89 - 15.05 mg/l, 96 hours
Solvent Naphtha (petroleum), Light Arom. (CAS 64742-95-6)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia pulex) 2.7 - 5.1 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 8.8 mg/l, 96 hours
		8.8 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)	
BENZENE, DIMETHYL	3.12 - 3.2
BENZENE,1-METHYLETHYL-	3.66

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.


Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT	
UN number	Not available.
UN proper shipping name	Consumer commodity, MARINE POLLUTANT (Solvent Naphtha (Petroleum) Light Aromatic)
Transport hazard class(es)	
Class	ORM-D
Subsidiary risk	-
Label(s)	None
Packing group	Not available.
Environmental hazards	
Marine pollutant	Yes
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None
IATA	
UN number	UN1268
UN proper shipping name	Petroleum Distillates (Solvent Naphtha (petroleum), Light Arom.)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	Not available.
Environmental hazards	No.
ERG Code	9L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1268
UN proper shipping name	Petroleum Distillates (Solvent Naphtha (petroleum), Light Arom.), MARINE POLLUTANT (Solvent Naphtha (Petroleum) Light Aromatic, BENZENE, DIMETHYL)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	
Marine pollutant	Yes
EmS	F-A, S-F
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Solvent Naphtha (Petroleum) Light Aromatic BENZENE, DIMETHYL	
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.



Marine pollutant



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

BENZENE, DIMETHYL (CAS 1330-20-7)

Listed.

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1,2,4-Trimethylbenzene	95-63-6	1 - < 3
BENZENE,1-METHYLETHYL-	98-82-8	< 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

BENZENE, DIMETHYL (CAS 1330-20-7)

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

Listed: April 6, 2010

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,2,4-Trimethylbenzene (CAS 95-63-6)

BENZENE, DIMETHYL (CAS 1330-20-7)

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)

Mesitylene; (1,3,5-trimethylbenzene) (CAS 108-67-8)

Solvent Naphtha (petroleum), Light Arom. (CAS 64742-95-6)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	05-06-2015
Revision date	03-22-2017
Version #	05
HMIS® ratings	Health: 2 Flammability: 2 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 2 Instability: 0
NFPA ratings	



Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information

Physical & Chemical Properties: Multiple Properties
Transport Information: Material Transportation Information
GHS: Classification