

Issuing date 08-04-2015

Revision Date 08-15-2019

Version 04

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name TiteSeal Autobody Undercoating - Paintable

Recommended use of the chemical and restrictions on use

Product code T1616

Product Type Aerosol

Synonyms None

Other information Tariff Code: 4005.10.0000.

Supplier's details

Recommended Use Undercoating

Uses advised against No information available

Manufactured For:

Blumenthal Brands Integrated, LLC

600 Radiator Road

Indian Trail, NC 28079

Telephone: Customer Service and Technical (704) 821-7643

Website : www.solvewithB.com

E-mail sds@solvewithB.com

Emergency telephone number

Chemical Emergency Phone Number POISON CONTROL (RMPDC) (303) 623-5716
POISON CONTROL (RMPDC) (877)740-5015

2. HAZARDS IDENTIFICATION

Classification

NOTE: This product is a consumer product and is labeled in accordance with US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The container label may not include the OSHA label elements listed in this document. Always carefully review the entire SDS and the product label prior to use in the work place.

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Aerosols	Category 1
Gases under pressure	Compressed Gas

GHS Label elements, including precautionary statements

Emergency Overview

Signal Word: DANGER

Hazard Statements

Extremely Flammable Aerosol
 Pressurized container; may burst if heated Causes serious eye irritation.
 Suspected of causing cancer.
 Suspected of damaging fertility or the unborn child
 May cause damage to organs (Central Nervous System, Respiratory System, Eyes, Skin, Ears, Kidney, Blood, Bone Marrow, and Liver) through prolonged or repeated exposure.
 May be fatal if swallowed and enters airways.



Precautionary Statements - Prevention

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Wear protective gloves, protective clothing, eye protection, face protection.
 Wash face, hands and any exposed skin thoroughly after handling.
 Do not breathe dust, fume, gas, mist, vapors, spray.
 Keep away from heat, sparks, open flames, hot surfaces - No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use.

Precautionary Statements - Response

If exposed or concerned: Get medical advice, attention.
 Specific treatment (see first aid on this label).
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 If eye irritation persists: Get medical advice, attention
 IF ON SKIN: Wash with plenty of soap and water.

T1616 TITSEAL AUTOBODY UNDERCOATING

If skin irritation occurs: Get medical advice, attention.
Take off contaminated clothing and wash it before reuse.
IF SWALLOWED: Immediately call a POISON CENTER, doctor, physician.
Do NOT induce vomiting.

Precautionary Statements - Storage

Store locked up.
Protect from sunlight. Store in a well-ventilated place
Do not expose to temperatures exceeding 122°F (50°C)

Precautionary Statements - Disposal

Dispose of contents, container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC)

None

Other information

0% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
CALCIUM CARBONATE	1317-65-3	30-40
PROPANE/ISOBUTANE/NBUTANE	68476-86-8	20-30
PETROLEUM RESINS	64742-16-1	10-20
PETROLEUM DISTILLATES	64742-89-8	1-10
TOLUENE	108-88-3	1-10
METHYL ACETATE	79-20-9	1-10
METHANOL	67-56-1	0.1-1.0
XYLENE	1330-20-7	0.1-1.0
CARBON BLACK	1333-86-4	0.1-1.0
SILICA, CRYSTALLINE	14808-60-7	<0.1
ETHYL BENZENE	100-41-4	<0.1
BENZENE	71-43-2	<0.1

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice	Avoid contact with eyes, skin, and clothing. Avoid breathing vapors, mist, or gas.
Eye contact	Immediately flush with plenty of water for at least 15 minutes. After initial flushing, remove any contact lenses and continue flushing. If eye irritation persists, consult a doctor.
Skin contact	Wash off with soap and plenty of water. Remove and wash contaminated clothing before re-use. If skin irritation persists, call a physician.
Inhalation	Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.
Ingestion	Call a physician or Poison Control Center immediately. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.

T1616 TITSEAL AUTOBODY UNDERCOATING

Most important symptoms/effects, acute and delayed

Main Symptoms	Causes skin and serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.
----------------------	--

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water fog. Dry chemical. Carbon dioxide (CO₂). Cool containers / tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Extremely Flammable / Flammable. Keep product and empty container away from heat and sources of ignition.

Explosion Data

Sensitivity to Mechanical Impact none.

Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Use with adequate ventilation to keep the exposure levels below the OELS. Follow safe handling advice and personal protective equipment recommendations.
-----------------------------	--

Environmental precautions

Environmental precautions	Vapors can accumulate in low areas. Report spills as required by local and federal regulations. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system. Should not be released into the environment.
----------------------------------	--

Methods and materials for containment and cleaning up

Methods for Containment	Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.
--------------------------------	--

Methods for cleaning up	Soak up with inert absorbent material. Contain liquid and collect with an inter, non-combustible material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Prevent product from entering drains. Take precautionary measures against static discharges.
--------------------------------	---

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling	Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Contents under pressure. Do not puncture or incinerate cans. Handle in accordance with good industrial hygiene and safety practice. Take precautionary measures against static discharges.
--------------------------------	---

T1616 TITSEAL AUTOBODY UNDERCOATING

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces, and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

Incompatible products Strong acids, alkalis, oxidizing agents.

Aerosol Level 1

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
CALCIUM CARBONATE 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
TOLUENE 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³
METHYL ACETATE 79-20-9	STEL: 250 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 610 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 610 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 760 mg/m ³	IDLH: 3100 ppm TWA: 200 ppm TWA: 610 mg/m ³ STEL: 250 ppm STEL: 760 mg/m ³
METHANOL 67-56-1	STEL: 250 ppm TWA: 200 ppm Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³
XYLENE 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	Not Established
CARBON BLACK 1333-86-4	TWA: 3 mg/m ³ inhalable particulate matter	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
SILICA, CRYSTALLINE 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 µg/m ³ (vacated) TWA: 0.1 mg/m ³ respirable dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust
QUARTZ 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 µg/m ³ (vacated) TWA: 0.1 mg/m ³ respirable dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust
GRAPHITE	TWA: 2 mg/m ³ respirable	TWA: 15 mg/m ³ total dust	IDLH: 1250 mg/m ³

T1616 TITSEAL AUTOBODY UNDERCOATING

7782-42-5	particulate matter all forms except graphite fibers	synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural	TWA: 2.5 mg/m ³ natural respirable dust
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
BENZENE 71-43-2	STEL: 2.5 ppm TWA: 0.5 ppm Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 10 ppm applies to industry segments exempt from the benzene standard at 29 CFR 1910.1028 TWA: 1 ppm (vacated) TWA: 10 ppm unless specified in 1910.1028 (vacated) STEL: 50 ppm 10 min unless specified in 1910.1028 (vacated) Ceiling: 25 ppm unless specified in 1910.1028 Ceiling: 25 ppm STEL: 5 ppm see 29 CFR 1910.1028	IDLH: 500 ppm TWA: 0.1 ppm STEL: 1 ppm
NAPHTHALENE 91-20-3	TWA: 10 ppm Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 10 ppm TWA: 50 mg/m ³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m ³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m ³	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m ³ STEL: 15 ppm STEL: 75 mg/m ³
ACETALDEHYDE 75-07-0	Ceiling: 25 ppm	TWA: 200 ppm TWA: 360 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 180 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 270 mg/m ³	IDLH: 2000 ppm

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d962 (11th Cir., 1992).

Exposure controls

Engineering Measures

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Safety glasses with side-shields.

Skin and body protection

Chemical resistant apron. Protective gloves.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state	Aerosol	Odor	Solvent
Appearance	Opaque	Odor Threshold	
Color	Black		

<u>Property</u>	<u>Values</u>	<u>Remarks • Methods</u>
pH	No information available	
Melting/freezing point	No information available	
Boiling point/boiling range		
Flash Point	-91.87 °C / -133.37 °F	Based on propellant
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limits in Air		
upper flammability limit		
lower flammability limit		
Vapor pressure		
Vapor density		
Specific Gravity	1.172	
Water solubility	None	
Partition coefficient: n-octanol/water		
Autoignition temperature	No information available	Not applicable
Decomposition temperature		
Viscosity	No information available	
Explosive properties		

Other information

VOC Content(%)	39.62
----------------	-------

10. STABILITY AND REACTIVITY

Reactivity

Stable under recommended storage conditions

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Strong acids, alkalis, oxidizing agents.

Hazardous Decomposition Products

Carbon oxides , Hydrocarbons, Fumes.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	Respiratory irritation may occur if excessive exposure to product by inhalation.
------------	--

T1616 TITSEAL AUTOBODY UNDERCOATING

Eye contact	Causes serious eye irritation.
Skin contact	Causes skin irritation.
Ingestion	May be fatal if swallowed and enters airways.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
PETROLEUM DISTILLATES 64742-89-8	-	= 3000 mg/kg (Rabbit)	-
TOLUENE 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
METHYL ACETATE 79-20-9	> 5 g/kg (Rat)	> 5 g/kg (Rabbit)	> 49000 mg/m ³ (Rat) 4 h
METHANOL 67-56-1	= 6200 mg/kg (Rat)	= 15840 mg/kg (Rabbit)	= 22500 ppm (Rat) 8 h
XYLENE 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
CARBON BLACK 1333-86-4	> 15400 mg/kg (Rat)	-	-
ETHYL BENZENE 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h
BENZENE 71-43-2	= 810 mg/kg (Rat)	> 8200 mg/kg (Rabbit)	= 44.66 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms	Causes skin and serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs (listed below) through prolonged or repeated exposure. May be fatal if swallowed and enters airways.
-----------------	---

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Irritating to skin.
Eye damage/irritation	Irritating to eyes.
Sensitization	Not a known sensitizer.
Germ cell mutagenicity	Not a germ cell mutagen.
Carcinogenicity	The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen. Silica, Crystalline, Ethyl Benzene, and Benzene are in the product at <0.1 % reportable levels.

Chemical Name	ACGIH	IARC	NTP	OSHA
TOLUENE 108-88-3	-	Group 3	-	-
XYLENE 1330-20-7	-	Group 3	-	-
CARBON BLACK 1333-86-4	A3	Group 2B	-	X
SILICA, CRYSTALLINE 14808-60-7	A2	Group 1	Known	X
ETHYL BENZENE 100-41-4	A3	Group 2B	-	X
BENZENE 71-43-2	A1	Group 1	Known	X

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

T1616 TITSEAL AUTOBODY UNDERCOATING

Reproductive toxicity	Product is or contains a chemical which is a known or suspected reproductive hazard.
Specific target organ systemic toxicity (single exposure)	No known effect based on information supplied.
Specific target organ systemic toxicity (repeated exposure)	May cause damage to Target Organs listed below through prolonged or repeated exposure.
Chronic toxicity	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.
Target Organ Effects	Central Nervous System, Respiratory System, Eyes, Skin, Kidney, Blood, Bone Marrow, and Liver.
Aspiration hazard	May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity	0% of the mixture consists of ingredient(s) of unknown toxicity.
The following values are calculated based on chapter 3.1 of the GHS document .	
ATEmix (oral)	25485 mg/kg
ATEmix (dermal)	21089 mg/kg
ATEmix (inhalation-dust/mist)	127.7 mg/l
ATEmix (inhalation-vapor)	284587 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
PETROLEUM DISTILLATES 64742-89-8	4700 mg/L EC50 Pseudokirchneriella subcapitata 72h	-	-	-
TOLUENE 108-88-3	433 mg/L EC50 Pseudokirchneriella subcapitata 96h 12.5 mg/L EC50 Pseudokirchneriella subcapitata 72h static	15.22 - 19.05 mg/L LC50 Pimephales promelas 96h flow-through 12.6 mg/L LC50 Pimephales promelas 96h static 5.89 - 7.81 mg/L LC50 Oncorhynchus mykiss 96h flow-through 14.1 - 17.16 mg/L LC50 Oncorhynchus mykiss 96h static 5.8 mg/L LC50 Oncorhynchus mykiss 96h semi-static 11.0 - 15.0 mg/L LC50 Lepomis macrochirus 96h static 54 mg/L LC50 Oryzias latipes 96h static 28.2 mg/L LC50 Poecilia reticulata 96h semi-static 50.87 - 70.34 mg/L LC50 Poecilia reticulata 96h static	-	5.46 - 9.83 mg/L EC50 Daphnia magna 48h Static 11.5 mg/L EC50 Daphnia magna 48h
METHYL ACETATE 79-20-9	120 mg/L EC50 Desmodesmus subspicatus 72h	295 - 348 mg/L LC50 Pimephales promelas 96h flow-through 250 - 350 mg/L LC50 Brachydanio rerio 96h static	-	1026.7 mg/L EC50 Daphnia magna 48h
METHANOL 67-56-1	-	28200 mg/L LC50 Pimephales promelas 96h flow-through 100 mg/L LC50 Pimephales promelas 96h static 19500 - 20700 mg/L LC50 Oncorhynchus mykiss 96h flow-through 18 - 20 mL/L LC50 Oncorhynchus mykiss 96h static 13500 - 17600 mg/L LC50 Lepomis macrochirus 96h flow-through	-	-

T1616 TITSEAL AUTOBODY UNDERCOATING

XYLENE 1330-20-7	-	13.4 mg/L LC50 Pimephales promelas 96h flow-through 2.661 - 4.093 mg/L LC50 Oncorhynchus mykiss 96h static 13.5 - 17.3 mg/L LC50 Oncorhynchus mykiss 96h 13.1 - 16.5 mg/L LC50 Lepomis macrochirus 96h flow-through 19 mg/L LC50 Lepomis macrochirus 96h 7.711 - 9.591 mg/L LC50 Lepomis macrochirus 96h static 23.53 - 29.97 mg/L LC50 Pimephales promelas 96h static 780 mg/L LC50 Cyprinus carpio 96h semi-static 780 mg/L LC50 Cyprinus carpio 96h 30.26 - 40.75 mg/L LC50 Poecilia reticulata 96h static	-	3.82 mg/L EC50 water flea 48h 0.6 mg/L LC50 Gammarus lacustris 48h
ETHYL BENZENE 100-41-4	4.6 mg/L EC50 Pseudokirchneriella subcapitata 72h 438 mg/L EC50 Pseudokirchneriella subcapitata 96h 2.6 - 11.3 mg/L EC50 Pseudokirchneriella subcapitata 72h static 1.7 - 7.6 mg/L EC50 Pseudokirchneriella subcapitata 96h static	11.0 - 18.0 mg/L LC50 Oncorhynchus mykiss 96h static 4.2 mg/L LC50 Oncorhynchus mykiss 96h semi-static 7.55 - 11 mg/L LC50 Pimephales promelas 96h flow-through 32 mg/L LC50 Lepomis macrochirus 96h static 9.1 - 15.6 mg/L LC50 Pimephales promelas 96h static 9.6 mg/L LC50 Poecilia reticulata 96h static	-	1.8 - 2.4 mg/L EC50 Daphnia magna 48h
BENZENE 71-43-2	29 mg/L EC50 Pseudokirchneriella subcapitata 72h	10.7 - 14.7 mg/L LC50 Pimephales promelas 96h flow-through 5.3 mg/L LC50 Oncorhynchus mykiss 96h flow-through 22.49 mg/L LC50 Lepomis macrochirus 96h static 28.6 mg/L LC50 Poecilia reticulata 96h static 22330 - 41160 µg/L LC50 Pimephales promelas 96h static 70000 - 142000 µg/L LC50 Lepomis macrochirus 96h static	-	8.76 - 15.6 mg/L EC50 Daphnia magna 48h Static 10 mg/L EC50 Daphnia magna 48h

Persistence and degradability

.

Bioaccumulation

Chemical Name	log Pow
PROPANE/ISOBUTANE/NBUTANE 68476-86-8	2.8
TOLUENE 108-88-3	2.7
METHYL ACETATE 79-20-9	0.18
METHANOL 67-56-1	-0.77
XYLENE 1330-20-7	3.15
ETHYL BENZENE 100-41-4	3.2
BENZENE 71-43-2	2.1

T1616 TITSEAL AUTOBODY UNDERCOATING

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations.

Contaminated packaging

Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT

UN number UN1950
UN proper shipping name Aerosols, flammable, Limited Quantity
Transport hazard class(es)
Class 2.1
Subsidiary risk -
Packing group Not available.
Environmental hazards
Marine pollutant No

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82

Packaging exceptions 306

IATA

UN number UN1950
UN proper shipping name Aerosol, flammable, Limited Quantity
Transport hazard class(es)
Class 2.1
Subsidiary risk -
Packing group Not available.
Environmental hazards No

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1950
UN proper shipping name Aerosols
Transport hazard class(es)
Class 2.1
Subsidiary risk -
Packing group Not available.
Environmental hazards
Marine pollutant No
EmS F-D, S-U


Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk
according to Annex II
of MARPOL 73/78
and the IBC Code**

T1616 TITSEAL AUTOBODY UNDERCOATING

DOT

Not established.



IATA



IMDG



15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
CALCIUM CARBONATE	X	X	X	X	X	X	X	X
PROPANE/ISOBUTANE/NBUTANE	X	X	X	Not listed	X	X	X	X
PETROLEUM RESINS	X	X	X	X	X	X	X	X
PETROLEUM DISTILLATES	X	X	X	Not listed	X	X	X	X
TOLUENE	X	X	X	X	X	X	X	X
METHYL ACETATE	X	X	X	X	X	X	X	X
METHANOL	X	X	X	X	X	X	X	X
XYLENE	X	X	X	X	X	X	X	X
CARBON BLACK	X	X	X	X	X	X	X	X
SILICA, CRYSTALLINE	X	X	X	X	X	X	X	X
ETHYL BENZENE	X	X	X	X	X	X	X	X
BENZENE	X	X	X	X	X	X	X	X

T1616 TITSEAL AUTOBODY UNDERCOATING

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does contain a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
TOLUENE - 108-88-3	108-88-3	1-10	1.0
METHANOL - 67-56-1	67-56-1	0.1-1.0	1.0
XYLENE - 1330-20-7	1330-20-7	0.1-1.0	1.0
ETHYL BENZENE - 100-41-4	100-41-4	<0.1	0.1
BENZENE - 71-43-2	71-43-2	<0.1	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Star Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

Clean Water Act

This product does contain the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TOLUENE 108-88-3	1000 lb	X	X	X
XYLENE 1330-20-7	100 lb			X
ETHYL BENZENE 100-41-4	1000 lb	X	X	X
BENZENE 71-43-2	10 lb	X	X	X

CERCLA

This material, as supplied, does contain substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
TOLUENE 108-88-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
METHANOL 67-56-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
BENZENE 71-43-2	10 lb		RQ 10 lb final RQ RQ 4.54 kg final RQ

T1616 TITSEAL AUTOBODY UNDERCOATING

U.S. State Regulations

California Proposition 65



WARNING: This product can expose you to chemicals including carbon black, which is known to the State of California to cause cancer, and toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
CALCIUM CARBONATE 1317-65-3	X	X	X
PETROLEUM DISTILLATES 64742-89-8			X
TOLUENE 108-88-3	X	X	X
METHYL ACETATE 79-20-9	X	X	X
METHANOL 67-56-1	X	X	X
XYLENE 1330-20-7	X	X	X
CARBON BLACK 1333-86-4	X	X	X
SILICA, CRYSTALLINE 14808-60-7	X	X	X
QUARTZ 14808-60-7	X	X	X
NAPHTHENIC ACIDS 1338-24-5	X	X	X
GRAPHITE 7782-42-5	X	X	X
ETHYL BENZENE 100-41-4	X	X	X
BENZENE 71-43-2	X	X	X
NAPHTHALENE 91-20-3	X	X	X
ACETALDEHYDE 75-07-0	X	X	X

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical hazards -
<u>HMIS</u>	Health Hazard 2*	Flammability 4	Physical Hazard 1	Personal protection B
<i>Chronic Hazard Star Legend</i>	<i>Repeated or prolonged exposure may cause central nervous system damage Chronic Health Star Hazard</i>			
Issue Date:	08-04-2015			
Issuing date	08-15-2019			
Version #:	04			

Revision Note

(M)SDS sections updated 1 16

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet