



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Foam Protectant - Aerosol

Version number: GHS 7.0
Replaces version of: 2020-10-21 (GHS 6)

Revision: 2021-03-18

SECTION 1: Identification

1.1 Product identifier

Trade name **Armor All Extreme Tire Foam Protectant - Aerosol**
Alternative number(s) 070612189301

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses General use

1.3 Details of the supplier of the safety data sheet

Energizer Manufacturing, Inc.
25225 Detroit Rd.
Westlake OH 44145
United States

Telephone: 800-383-7323; 314-985-2000 (USA / CANADA)
Website: <http://data.energizer.com>

Energizer Trading Ltd.
Sword House, Totteridge Road, High Wycombe, HP13 6DG, UK

Telephone: +44(0)8000353376
e-mail: ConsumerServiceEU@energizer.com

1.4 Emergency telephone number

Emergency information service 1-314-985-1511 Int'l: 1-800-526-4727
This number is only available during the following office hours: Mon-Fri 09:00 AM - 05:00 PM

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
B.3	flammable aerosol	2	Flam. Aerosol 2	H223
B.5	gases under pressure	C	Press. Gas C	H280

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Contains gas under pressure; may explode if heated.

Armor All Extreme Tire Foam Protectant - Aerosol

Version number: GHS 7.0
Replaces version of: 2020-10-21 (GHS 6)

Revision: 2021-03-18

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word warning

- Pictograms

GHS02, GHS04



- Hazard statements

H223 Flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

- Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3 Other hazards

Hazards not otherwise classified

Contains epoxy constituents. May produce an allergic reaction.

Harmful to aquatic life (GHS category 3: aquatic toxicity - acute).



SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
isobutane	CAS No 75-28-5	5 – < 10	Muta. 1B / H340 Carc. 1A / H350 Flam. Gas 1 / H220 Press. Gas C / H280	
propane	CAS No 74-98-6	1 – < 5	sA / OSHA002 Flam. Gas 1 / H220 Press. Gas C / H280	





Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Foam Protectant - Aerosol

Version number: GHS 7.0
Replaces version of: 2020-10-21 (GHS 6)

Revision: 2021-03-18

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
sodium nitrite	CAS No 7632-00-0	< 1	Acute Tox. 3 / H301 Ox. Sol. 3 / H272	 

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Thaw frosted parts with lukewarm water. Do not rub affected area.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Contact with the product can cause burns and/or frostbite. Contains gas under pressure; may explode if heated.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Foam Protectant - Aerosol

Version number: GHS 7.0
Replaces version of: 2020-10-21 (GHS 6)

Revision: 2021-03-18

Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Foam Protectant - Aerosol

Version number: GHS 7.0
Replaces version of: 2020-10-21 (GHS 6)

Revision: 2021-03-18

Managing of associated risks

- Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight.

Control of the effects

Protect against external exposure, such as

Frost

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/ m ³]	STEL [ppm]	STEL [mg/ m ³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m ³]	Nota tion	Sour ce
US	propane	74-98-6	PEL (CA)	1,000	1,800						Cal/ OSHA PEL
US	propane	74-98-6	REL	1,000 (10 h)	1,800 (10 h)						NIOSH REL
US	propane	74-98-6	PEL	1,000	1,800						29 CFR 1910.1 000
US	propane	74-98-6	TLV®							oxy- gen, Simpl e Asp., E	AC- GIH® 2019
US	isobutane	75-28-5	REL	800 (10 h)	1,900 (10 h)						NIOSH REL
US	isobutane	75-28-5	TLV®			1,000				E	AC- GIH® 2019

Notation

Ceiling-C

E

oxygen

ceiling value is a limit value above which exposure should not occur

explosive

Adequate oxygen delivery to the tissues is necessary for sustaining life



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Foam Protectant - Aerosol

Version number: GHS 7.0
Replaces version of: 2020-10-21 (GHS 6)

Revision: 2021-03-18

Notation

Simple Asp. simple asphyxiants
STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
sodium nitrite	7632-00-0	DNEL	2 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
sodium nitrite	7632-00-0	DNEL	2 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
sodium nitrite	7632-00-0	PNEC	0.0054 mg/l	aquatic organisms	freshwater	short-term (single instance)
sodium nitrite	7632-00-0	PNEC	0.00616 mg/l	aquatic organisms	marine water	short-term (single instance)
sodium nitrite	7632-00-0	PNEC	21 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
sodium nitrite	7632-00-0	PNEC	0.0195 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
sodium nitrite	7632-00-0	PNEC	0.0223 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
sodium nitrite	7632-00-0	PNEC	0.000733 mg/kg	terrestrial organisms	soil	short-term (single instance)
sodium nitrite	7632-00-0	PNEC	0.0054 mg/l	aquatic organisms	water	intermittent release

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Foam Protectant - Aerosol

Version number: GHS 7.0
Replaces version of: 2020-10-21 (GHS 6)

Revision: 2021-03-18

Skin protection

- Hand protection

Wear protective gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

During spraying wear suitable respiratory equipment.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	aerosol (spray aerosol)
Color	various
Odor	characteristic

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	-161.5 °C at 1,013 hPa
Flash point	-83 °C
Evaporation rate	Not determined
Flammability (solid, gas)	flammable aerosol in accordance with GHS criteria

Explosive limits



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Foam Protectant - Aerosol

Version number: GHS 7.0
Replaces version of: 2020-10-21 (GHS 6)

Revision: 2021-03-18

- Lower explosion limit (LEL)	3 vol%
- Upper explosion limit (UEL)	15 vol%
Vapor pressure	not determined
Density	not determined
Vapor density	this information is not available
Relative density	Information on this property is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	>410 °C
Viscosity	not relevant (aerosol)
Explosive properties	none
Oxidizing properties	none

9.2 Other information

Propellant content	6.776 %
Temperature class (USA, acc. to NEC 500)	T2 (maximum permissible surface temperature on the equipment: 300°C)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Gas under pressure. Risk of ignition.

If heated:

Danger of explosion, Gas under pressure, Danger of bursting container

10.2 Chemical stability

See below "Conditions to avoid".



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Foam Protectant - Aerosol

Version number: GHS 7.0
Replaces version of: 2020-10-21 (GHS 6)

Revision: 2021-03-18

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
sodium nitrite	7632-00-0	oral	100 mg/kg

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Contains epoxy constituents. May produce an allergic reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Foam Protectant - Aerosol

Version number: GHS 7.0
Replaces version of: 2020-10-21 (GHS 6)

Revision: 2021-03-18

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
isobutane	75-28-5	LC50	49.9 mg/l	fish	96 h
isobutane	75-28-5	EC50	19.37 mg/l	algae	96 h
propane	74-98-6	LC50	49.9 mg/l	fish	96 h
propane	74-98-6	EC50	19.37 mg/l	algae	96 h
sodium nitrite	7632-00-0	LC50	26.3 mg/l	fish	96 h
sodium nitrite	7632-00-0	EC50	15.4 mg/l	aquatic invertebrates	48 h
sodium nitrite	7632-00-0	ErC50	>100 mg/l	algae	72 h
sodium nitrite	7632-00-0	NOEC	100 mg/l	algae	72 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Foam Protectant - Aerosol

Version number: GHS 7.0
Replaces version of: 2020-10-21 (GHS 6)

Revision: 2021-03-18

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number

DOT	UN 1950
IMDG-Code	UN 1950
ICAO-TI	UN 1950

14.2 UN proper shipping name

DOT	Aerosols
IMDG-Code	AEROSOLS
ICAO-TI	Aerosols, flammable

14.3 Transport hazard class(es)

DOT	2.1
IMDG-Code	2.1
ICAO-TI	2.1

14.4 Packing group

not assigned

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

There is no additional information.

Armor All Extreme Tire Foam Protectant - Aerosol

Version number: GHS 7.0
Replaces version of: 2020-10-21 (GHS 6)

Revision: 2021-03-18

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

DOT

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration	UN1950, Aerosols, 2.1
Reportable quantity (RQ)	53,763 lbs (24,409 kg) (sodium nitrite) (formaldehyde ... %)
Danger label(s)	2.1



Special provisions (SP)	N82
ERG No	126

International Maritime Dangerous Goods Code (IMDG) - Additional information

Particulars in the shipper's declaration	UN1950, AEROSOLS, 2.1, -83°C c.c.
Marine pollutant	-
Danger label(s)	2.1



Special provisions (SP)	63, 190, 277, 327, 344, 381, 959
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
EmS	F-D, S-U
Stowage category	-

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Particulars in the shipper's declaration	UN1950, Aerosols, flammable, 2.1
Danger label(s)	2.1



Special provisions (SP)	A145, A167
Excepted quantities (EQ)	E0
Limited quantities (LQ)	30 kg



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Foam Protectant - Aerosol

Version number: GHS 7.0
Replaces version of: 2020-10-21 (GHS 6)

Revision: 2021-03-18

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings

Name of substance	CAS No	Remarks	Effective date
sodium nitrite	7632-00-0		1995-01-01

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
sodium nitrite	7632-00-0		1	100 (45,4)

Legend

1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act

Clean Air Act

Name of substance	CAS No	Type of registration	Basis for listing	Threshold quantity (lbs)
isobutane	75-28-5	Flammable substance	f	10000
propane	74-98-6	Flammable substance	f	10000

Legend

f Flammable gas.

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	Name acc. to inventory	CAS No	Functional-ity	Authoritative Lists
Water		7732-18-5	solvents	
Silicone compound		63148-62-9	water repellent	



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Foam Protectant - Aerosol

Version number: GHS 7.0
Replaces version of: 2020-10-21 (GHS 6)

Revision: 2021-03-18

Name of substance	Name acc. to inventory	CAS No	Functional-ity	Authoritative Lists
Isobutane	Isobutane	75-28-5	propellant	EC Annex VI CMRs - Cat. 1A EC Annex VI CMRs - Cat. 1B
Propane		74-98-6	propellant	
Proprietary Ethoxylated Alcohol #1		Propriet-ary	surfactant	
Proprietary Ethoxylated Alcohol #2		Propriet-ary	surfactant	
Polyalkoxylated Heptamethyl-trisiloxane		67674-67-3	surfactant	
Triethanolamine		102-71-6	pH Adjuster	
Acrylic polymer(s)		Propriet-ary	protective coating	
Sodium nitrite		7632-00-0	preservative	
1,3-bis(hydroxymethyl)-5,5-dimethylimidazolidine-2,4-dione	DMDM hydantoin	6440-58-0	preservative	Nonfunctional constituents
2,4-Imidazolidinedione, (hydroxymethyl)-5,5-dimethyl-		27636-82-4	preservative	

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	Name acc. to inventory	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Thres hold	De Minimis Concentration Threshold
sodium nitrite	Sodium nitrite	7632-00-0				1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	Name acc. to inventory	CAS No	References	Remarks
isobutane	Alkanes		N	
propane	Propane	74-98-6	A, O	
propane	Alkanes		N	
propane	Gases, Simple Asphyxiants		A	gases

Legend

A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
gases Refers to displacement of air asphyxiation hazard.
N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Foam Protectant - Aerosol

Version number: GHS 7.0
Replaces version of: 2020-10-21 (GHS 6)

Revision: 2021-03-18

Legend

O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

- Hazardous Substance List (NJ-RTK)

Name of substance	Name acc. to inventory	CAS No	Remarks	Classifications
Triethanolamine	triethanolamine	102-71-6		
isobutane	isobutane (propane, 2-methyl-)	75-28-5		F4
propane	propane	74-98-6		F4
sodium nitrite	sodium nitrite	7632-00-0		

Legend

F4 Flammable - Fourth Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name of substance	Name acc. to inventory	CAS No	Classification
isobutane	PROPANE, 2-METHYL-	75-28-5	
propane	PROPANE	74-98-6	
sodium nitrite	NITROUS ACID, SODIUM SALT	7632-00-0	E

Legend

E Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	Name acc. to inventory	CAS No	References
Triethanolamine	Triethanolamine	102-71-6	F
isobutane	Butane	106-97-8	T, F
propane	liquefied petroleum gas	74-98-6	T

Legend

F Flammability (NFPA®)
T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

The presence of Prop 65 chemicals in the product does not indicate whether or not a label warning is required.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Foam Protectant - Aerosol

Version number: GHS 7.0
Replaces version of: 2020-10-21 (GHS 6)

Revision: 2021-03-18

Proposition 65 List of chemicals

Name acc. to inventory	CAS No	Remarks	Type of the toxicity
1,4-dioxane	123-91-1		cancer
ethylene oxide	75-21-8		cancer
ethylene oxide	75-21-8		female
ethylene oxide	75-21-8		developmental, male
diethanolamine	111-42-2		cancer
formaldehyde	50-00-0	gas	cancer
methanol	67-56-1		developmental

Drug precursors, Chemicals designated within the Controlled Substances Act, 21 U.S.C. § 802, paragraphs 34 (list I) and 35 (list II)

none of the ingredients are listed

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	0	no significant risk to health
Flammability	4	material that rapidly or completely vaporizes at atmospheric pressure and normal ambient temperature or that is readily dispersed in air and burn readily
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	4	material that rapidly or completely vaporizes at atmospheric pressure and normal ambient temperature or that is readily dispersed in air and burn readily
Health	0	material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Foam Protectant - Aerosol

Version number: GHS 7.0
Replaces version of: 2020-10-21 (GHS 6)

Revision: 2021-03-18

Category	Degree of hazard	Description
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
AU	AICS	not all ingredients are listed
CA	DSL	not all ingredients are listed
CN	IECSC	not all ingredients are listed
EU	ECSI	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	not all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	not all ingredients are listed
US	TSCA	not all ingredients are listed

Legend

AICS	Australian Inventory of Chemical Substances
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Foam Protectant - Aerosol

Version number: GHS 7.0
Replaces version of: 2020-10-21 (GHS 6)

Revision: 2021-03-18

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.3	Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.		yes
3.2		Description of the mixture: change in the listing (table)	yes
12.1		Aquatic toxicity (acute) of components of the mixture: change in the listing (table)	yes
12.7	Other adverse effects	Other adverse effects: Data are not available.	yes
14.1	UN number: 1950	UN number	yes
14.1		DOT: UN 1950	yes
14.1		IMDG-Code: UN 1950	yes
14.1		ICAO-TI: UN 1950	yes
14.2	UN proper shipping name: Aerosols	UN proper shipping name	yes
14.2		DOT: Aerosols	yes
14.2		IMDG-Code: AEROSOLS	yes
14.2		ICAO-TI: Aerosols, flammable	yes
14.3	Class: 2.1 (gases) (aerosol) (flammable)		yes
14.3		DOT: 2.1	yes
14.3		IMDG-Code: 2.1	yes
14.3		ICAO-TI: 2.1	yes



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Foam Protectant - Aerosol

Version number: GHS 7.0
Replaces version of: 2020-10-21 (GHS 6)

Revision: 2021-03-18

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
14.4	Packing group: not assigned to a packing group	Packing group: not assigned	yes
14.7	Index number: 1950		yes
14.7	Proper shipping name: Aerosols		yes
14.7	Class: 2.1		yes
14.7		Danger label(s): change in the listing (table)	yes
14.7	UN number: 1950		yes
14.7	Proper shipping name: AEROSOLS		yes
14.7	Class: 2.1		yes
14.7	UN number: 1950		yes
14.7	Proper shipping name: Aerosols, flammable		yes
14.7	Class: 2.1		yes
15.1	California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987	California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987: The presence of Prop 65 chemicals in the product does not indicate whether or not a label warning is required.	yes
15.1		Drug precursors, Chemicals designated within the Controlled Substances Act, 21 U.S.C. § 802, paragraphs 34 (list I) and 35 (list II): none of the ingredients are listed	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Foam Protectant - Aerosol

Version number: GHS 7.0
Replaces version of: 2020-10-21 (GHS 6)

Revision: 2021-03-18

Abbr.	Descriptions of used abbreviations
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
ERG No	Emergency Response Guidebook - Number
Flam. Gas	Flammable gas
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Foam Protectant - Aerosol

Version number: GHS 7.0
Replaces version of: 2020-10-21 (GHS 6)

Revision: 2021-03-18

Abbr.	Descriptions of used abbreviations
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LHS	Lower hazard substance
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
Muta.	Germ cell mutagenicity
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
NOEC	No Observed Effect Concentration
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
Ox. Sol.	Oxidizing solid
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Press. Gas	Gas under pressure
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
sA	Simple asphyxiants
STEL	Short-term exposure limit
TLV®	Threshold Limit Values
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Foam Protectant - Aerosol

Version number: GHS 7.0
Replaces version of: 2020-10-21 (GHS 6)

Revision: 2021-03-18

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H220	Extremely flammable gas.
H223	Flammable aerosol.
H272	May intensify fire; oxidizer.
H280	Contains gas under pressure; may explode if heated.
H301	Toxic if swallowed.
H340	May cause genetic defects.
H350	May cause cancer.
OSHA002	May displace oxygen and cause rapid suffocation.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.