

A00173 MST HD CARPET SPOT RMVR 20net19

Version 1.0

Revision Date 02/24/2015

Print Date 06/05/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : A00173 MST HD CARPET SPOT RMVR 20net19

Material number : 000000000001001611

Manufacturer or supplier's details

Company : Zep Inc.

Address : 1310 Seaboard Industrial Blvd., NW
Atlanta, GA 30318

Telephone : 404-352-1680

Emergency telephone numbers**For SDS Information** : Compliance Services 1-877-428-9937**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded**For a Transportation Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.
In the District of Columbia 202-483-7616**SECTION 2. HAZARDS IDENTIFICATION****Emergency Overview**

| | |
|------------|------------------------------------|
| Appearance | Aerosol containing a liquefied gas |
| Colour | clear |
| Odour | characteristic |

GHS ClassificationFlammable aerosols : Category 2
Gases under pressure : Liquefied gas
Eye irritation : Category 2A**GHS Label element**

Hazard pictograms :



Signal word : Warning

Hazard statements : H223 Flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P264 Wash skin thoroughly after handling.

A00173 MST HD CARPET SPOT RMVR 20net19

Version 1.0

Revision Date 02/24/2015

Print Date 06/05/2015

P280 Wear eye protection/ face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Potential Health Effects**Carcinogenicity:****IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

| Chemical Name | CAS-No. | Concentration [%] |
|--|-------------|-------------------|
| butane | 106-97-8 | >= 5 - < 10 |
| propan-2-ol | 67-63-0 | >= 5 - < 10 |
| 2-(2-butoxyethoxy)ethanol | 112-34-5 | >= 5 - < 10 |
| acetone | 67-64-1 | >= 1 - < 5 |
| D-Glucopyranose, oligomers, decyl octyl glycosides | 68515-73-1 | >= 1 - < 5 |
| 1-phenoxypropan-2-ol | 770-35-4 | >= 1 - < 5 |
| propane | 74-98-6 | >= 1 - < 5 |
| D-Glucopyranose, oligomeric, C10-16-alkyl glycosides | 110615-47-9 | >= 1 - < 5 |

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.

A00173 MST HD CARPET SPOT RMVR 20net19

Version 1.0

Revision Date 02/24/2015

Print Date 06/05/2015

- If unconscious place in recovery position and seek medical advice.
- In case of skin contact : In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Wash contaminated clothing before re-use.
Call a physician if irritation develops or persists.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
Remove contact lenses.
If eye irritation persists, consult a specialist.
- If swallowed : DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
Water spray jet
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon dioxide (CO₂)
Carbon monoxide
Nitrogen oxides (NO_x)
Smoke
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.

A00173 MST HD CARPET SPOT RMVR 20net19

Version 1.0

Revision Date 02/24/2015

Print Date 06/05/2015

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Always replace cap after use.
Dispose of rinse water in accordance with local and national regulations.
Do not breathe vapours or spray mist.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
No smoking.
Observe label precautions.
Keep in a dry, cool and well-ventilated place.
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|-------------|----------|----------------------------------|---|-----------|
| butane | 106-97-8 | TWA | 800 ppm 1,900 mg/m ³ | NIOSH REL |
| | | TWA | 800 ppm 1,900 mg/m ³ | OSHA P0 |
| propan-2-ol | 67-63-0 | TWA | 200 ppm | ACGIH |
| | | STEL | 400 ppm | ACGIH |
| | | TWA | 400 ppm | NIOSH REL |

A00173 MST HD CARPET SPOT RMVR 20net19

Version 1.0

Revision Date 02/24/2015

Print Date 06/05/2015

| | | | | |
|---------|---------|------|--------------------------|-----------|
| | | | 980 mg/m3 | |
| | | ST | 500 ppm 1,225 mg/m3 | NIOSH REL |
| | | TWA | 400 ppm 980 mg/m3 | OSHA Z-1 |
| | | TWA | 400 ppm 980 mg/m3 | OSHA P0 |
| | | STEL | 500 ppm 1,225 mg/m3 | OSHA P0 |
| acetone | 67-64-1 | TWA | 500 ppm | ACGIH |
| | | STEL | 750 ppm | ACGIH |
| | | TWA | 250 ppm 590 mg/m3 | NIOSH REL |
| | | TWA | 1,000 ppm 2,400 mg/m3 | OSHA Z-1 |
| | | TWA | 750 ppm 1,800 mg/m3 | OSHA P0 |
| | | STEL | 1,000 ppm 2,400 mg/m3 | OSHA P0 |
| propane | 74-98-6 | TWA | 1,000 ppm | ACGIH |
| | | TWA | 1,000 ppm 1,800 mg/m3 | NIOSH REL |
| | | TWA | 1,000 ppm 1,800 mg/m3 | OSHA Z-1 |
| | | TWA | 1,000 ppm 1,800 mg/m3 | OSHA P0 |

Biological occupational exposure limits

| Component | CAS-No. | Control parameters | Biological specimen | Sampling time | Permissible concentration | Basis |
|-------------|---------|--------------------|---------------------|--|---------------------------|-----------|
| PROPAN-2-OL | 67-63-0 | Acetone | Urine | End of shift at end of workweek | 40 mg/l | ACGIH BEI |
| 2-PROPANONE | 67-64-1 | Acetone | Urine | End of shift (As soon as possible after exposure ceases) | 50 mg/l | ACGIH BEI |

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Ensure that eyewash stations and safety showers are close to the workstation location.
Safety glasses

A00173 MST HD CARPET SPOT RMVR 20net19

Version 1.0

Revision Date 02/24/2015

Print Date 06/05/2015

- Skin and body protection : impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Aerosol containing a liquefied gas
- Colour : clear
- Odour : characteristic
- Odour Threshold : no data available
- pH : no data available
- Melting point/freezing point : no data available
- Boiling point : no data available
- Flash point :
not applicable
- Evaporation rate : 1
- Upper explosion limit : no data available
- Lower explosion limit : no data available
- Vapour pressure : 4,136 hPa (21 °C)
- Relative vapour density : no data available
- Density : 0.985 g/cm³
- Solubility(ies)
- Water solubility : soluble
- Partition coefficient: n-octanol/water : no data available
- Auto-ignition temperature : not determined
- Thermal decomposition : no data available
- Viscosity
- Viscosity, kinematic : no data available
- Heat of combustion : 10.46 kJ/g

SECTION 10. STABILITY AND REACTIVITY

A00173 MST HD CARPET SPOT RMVR 20net19

Version 1.0

Revision Date 02/24/2015

Print Date 06/05/2015

| | |
|------------------------------------|---|
| Reactivity | : Stable |
| Chemical stability | : Stable under normal conditions. |
| Possibility of hazardous reactions | : No decomposition if stored and applied as directed. Vapours may form explosive mixture with air. |
| Conditions to avoid | : Heat, flames and sparks. Extremes of temperature and direct sunlight. |
| Incompatible materials | : Strong oxidizing agents |
| Hazardous decomposition products | : Carbon dioxide (CO ₂) Carbon monoxide Nitrogen oxides (NO _x) |

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity****Product:**

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:**propan-2-ol:**

Acute oral toxicity : LD50 Oral rat: 4,396 mg/kg
Method: Calculation method

Skin corrosion/irritation**Product:**

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation**Product:**

Remarks: Eye irritation

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

A00173 MST HD CARPET SPOT RMVR 20net19

Version 1.0

Revision Date 02/24/2015

Print Date 06/05/2015

Reproductive toxicity

no data available

butane:**propan-2-ol:****2-(2-butoxyethoxy)ethanol:****acetone:****D-Glucopyranose, oligomers, decyl octyl glycosides:****1-phenoxypropan-2-ol:****propane:****D-Glucopyranose, oligomeric, C10-16-alkyl glycosides:****STOT - single exposure**

no data available

STOT - repeated exposure

no data available

Aspiration toxicity

no data available

Further information**Product:**

Remarks: no data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

no data available

Persistence and degradability

no data available

Bioaccumulative potential**Product:**

Partition coefficient: n-octanol/water : Remarks: no data available

Components:**butane :**

Partition coefficient: n-octanol/water : Pow: 2.89

2-(2-butoxyethoxy)ethanol :

Partition coefficient: n-octanol/water : Pow: 1

D-Glucopyranose, oligomeric, C10-16-alkyl glycosides :

Partition coefficient: n-octanol/water : Pow: 0.07

Mobility in soil

no data available

A00173 MST HD CARPET SPOT RMVR 20net19

Version 1.0

Revision Date 02/24/2015

Print Date 06/05/2015

Other adverse effects

no data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : no data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):
ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel):
UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):
UN1950, AEROSOLS, 2.1, - Limited quantity

A00173 MST HD CARPET SPOT RMVR 20net19

Version 1.0

Revision Date 02/24/2015

Print Date 06/05/2015

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA Reportable Quantity**

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|----------------|-----------|-----------------------|--------------------------------|
| sodium nitrite | 7632-00-0 | 100 | * |

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard
Sudden Release of Pressure Hazard

SARA 302 : SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65 WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

methanol

67-56-1

The components of this product are reported in the following inventories:

| | |
|--------------|--|
| TSCA | On TSCA Inventory |
| DSL | This product contains one or several components that are not on the Canadian DSL nor NDSL. |
| AICS | Not in compliance with the inventory |
| NZIoC | Not in compliance with the inventory |
| PICCS | Not in compliance with the inventory |
| IECSC | Not in compliance with the inventory |

Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

A00173 MST HD CARPET SPOT RMVR 20net19


Version 1.0

Revision Date 02/24/2015

Print Date 06/05/2015

Further information

NFPA:



HMIS III:

| | |
|-----------------|---|
| HEALTH | 3 |
| FLAMMABILITY | 3 |
| PHYSICAL HAZARD | 2 |

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

OSHA GHS Label Information:

Hazard pictograms



Signal word

: **Warning:**

Hazard statements

: Flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation.

Precautionary statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash skin thoroughly after handling. Wear eye protection/ face protection.

Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.