1. Identification:

Product Identity: HD3000 GRY

Recommended Use: Water-borne floor Seal

Producer / Distributor

Multi-Clean 600 Cardigan Road Shoreview, MN 55126

Telephone Number for Information: 651-481-1900 **Emergency Telephone Number:** 800-255-3924



Acute Aquatic Toxicity Category 2

2. Hazard Identification:

Classification:

Health Class Physical Class Environment Class

Skin Irritation Category 2 Serious Eye Damage Category

Skin Sensitizer

Reproductive Toxicity Category 2

Specific Target Organ Toxicity - Repeated Exposure Category 2

Label

Symbols





Signal Word

Danger

Hazard Statements:

Causes serious eye damage.

Causes skin irritation.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

May cause damage to central nervous system, liver, and/or kidneys.

Precautionary Statements:

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing/eye protection/face protection.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash hands thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF ON SKIN: Wash with plenty of water.

If skin irritation or rash occurs: Get medical attention.

Take off contaminated clothing and wash it before reuse.

If exposed or concerned: Get medical attention.

Store locked up.

Dispose of contents in accordance with local regulations.

Composition/Information on Ingredients Percent by Ingredient **CAS Number** Weight Modified Aliphatic Polyamide Proprietary 10 - 302-Butoxy Ethanol 111-76-2 1 - 5 Polyamine Polymer Proprietary 5 - 10Titanium Dioxide 13463-67-7 10 - 30 Alcohol Ethoxylates 34398-01-1 1 - 5 Water 7732-18-5 60 - 100

4. First-Aid Measures:

Ingestion: If Swallowed: Drink water in large amounts and call a physician immediately. Never give anything by mouth to an unconscious

person.

Eye Contact: Flush eyes with running water for at least 15 minutes. If irritation persists, obtain medical attention.

Skin Contact: Flush thoroughly with cool water. Remove and wash contaminated clothing before reuse.

Inhalation: For Overexposure to Vapors: Remove victim to fresh air, contact a physician.

5. Fire Fighting Measures:

Suitable Extinguishing Media: Not Applicable

Special Fire Fighting Procedures: Not Applicable

Unusual Fire and Explosion Hazards Not Applicable

6. Accidental Release Measures:

Dike and contain spill with inert material (sand, earth, etc.). Collect spill with a mop, absorbent material (example: floor-dry) or vacuum. Thoroughly rinse affected area with water.

7. Handling and Storage:

Handling: Keep from freezing. Keep out of reach of children.

Storage: Maintain Temperature Minimum 40°F (4°C) - Maximum 100°F (38°C)

8. Exposure Controls / Personal Protection:

Exposure Limits:
Ingredients CAS Number Osha PEL ACGIH TLV
2-Butoxy Ethanol 111-76-2 25 ppm 25 ppm

Exposure Controls:

Engineering Controls: Normal good ventilation is sufficient

Personal Protective Equipment:

Eye Protection: Approved Safety Goggles or Glasses **Skin Protection:** Chemical Resistant Rubber Gloves

Respiratory Protection: Not required, Avoid breathing spray mist

9. Physical and Chemical Properties:

Physical State: Liquid pH: 9 - 10

Appearance: Gray Specific Gravity (H20 = 1): 1.26

Odor: Mild Alcohol Flammability: None

Vapor Pressure (MM HG): NA %volatile: 63%

Vapor Density (Air = 1): > 1

10. Stability and Reactivity:

Chemical Stability: Stable

Possibility of Hazardous Reactions: None are known Incompatability (Materials to Avoid): None are known Hazardous Decomposition or By-products: None Hazardous Polymerization: Will not Occur

Conditions to Avoid: None are known

11. Toxicological Information:

Signs and Symptoms of Overexposure: Causes irritation on contact, Vapors may affect Central Nervous system, Liver and Kidneys.

Acute Effects:

Eye Contact:Severe Eye damage can result from direct contact.Skin Contact:Causes irritation and/or sensitization on direct contact

Inhalation: Overexposure to Butyl vapors may be harmful

Ingestion: May be harmful if swallowed

Target Organ Effects: Central nervous system, Liver, Kidneys and is Suspected of damaging fertility or the unborn child.

Chronic Effects: overexposure to 2-Butoxy Ethanol has been found to affect the target organs listed

Acute Toxicity Values:

Oral LD $_{50}$ = > 5000 mg/kg Dermal LD $_{50}$ = > 5000 mg/kg Inhalation (Vapor) LC $_{50}$ = > 50 mg/l

12. Ecological Information:

Persistence and Degradability: Product is Readily Biodegradable

Bio Accumulative Potential: Not Available

Mobility in Soil: Not Available
Aquatic Toxicity: Toxic to Aquatic Life

13. Disposal Considerations:

Sanitary landfill or sewer in accordance with existing pollution control ordinances.

14. Transportation Information:

UN Number: None

Shipping Name: Paint, Lacquer, or Varnish

Transport Hazard Class: None

Packing Group: None **Marine Pollutant:** NO

15. Regulatory Information:

TSCA Status: All ingredients listed

Clean Water Act: None of the chemicals in this product are listed under the CWA

Clean Air Act: Glycol Ethers (2-Butoxy Ethanol (111-76-2)) is listed as a hazardous air pollutant (HAP)

CERCLA Reportable Quantity: None

SARA Title III Information:

Section 302 Extremely Hazardous Chemicals: None Listed

Section 311 / 312 Hazard Category: Immediate Health, Chronic Health Section 313 Toxic Chemicals: Glycol Ethers (2-Butoxy Ethanol (111-76-2))

State Regulations: None

International Regulations: WHMIS Controlled Product Hazard Class: D2B

16. Other Information:

Prepared By: Ron Camp

Telephone Number: 651-481-1900

Revision Date: 6/7/2013 **Supersedes:** 4/1/2012

The information contained herein is based on data considered accurate; however no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. The company assumes no responsibility for personal injury or property damage to vendees, users, or third parties caused by the material. Such vendees or users assume all risks associated with the use of the



Health	2
Flammability	0
Physical hazards	0