# MATERIAL SAFETY DATA SHEET

### SECTION I - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: LEMON PUMP SPRAY DISINFECTANT

ID NUMBER: LB305

PRODUCT USE/CLASS:

MANUFACTURER: LUBAR CHEMICAL

1700 CAMPBELL

KANSAS CITY, MO 64108

EMERGENCY TELEPHONE:816-234-3000

PREPARER: TERRY HALL PHONE: 816-471-2560

PREPARE DATE: 06/25/99

### SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME

CAS NUMBER

CAS NUMBER

IS LESS THAN

TLV-TWA

TLV-STEL

PEL-TWA

DESIGNATION

TETRASODIUM ETHYLENEDIAMINE TETRACE 64-02-8

1.5 %

25 MG/M3

NO INFO

NO INFO

NO INFO

(See Section XI for abbreviation legend)

### SECTION III - PHYSICAL DATA

BOILING RANGE: 200 - 212 F VAPOR DENSITY: Is heavier than air OI

ODOR: LEMON

SPECIFIC GRAVITY: 1.0141

APPEARANCE: CLEAR LIQUID

EVAPORATION RATE: Is slower than Ether (See Section XI for abbreviation legend)

SOLUBILITY IN H2O: COMPLETE

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 200 F

LOWER EXPLOSIVE LIMIT: N.A.

UPPER EXPLOSIVE LIMIT: N.A.

(TAGLIABUE CLOSED CUP)

EXTINGUISHING MEDIA: ALCOHOL FOAM CO2 DRY CHEMICAL FOAM WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE KNOWN.

SPECIAL FIREFIGHTING PROCEDURES: FIREFIGHTERS SHOULD WEAR SELF CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING.

## SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE - EYE CONTACT: SEVERE IRRIATION.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: IRRITATION.

EFFECTS OF OVEREXPOSURE - INHALATION: OVEREXPOSURE MAY CAUSE DIZZINESS, NAUSEA.

EFFECTS OF OVEREXPOSURE - INGESTION: MAY CAUSE DIZZINESS, NAUSEA, LARGE AMOUNTS MAY HAVE TOXIC EFFECTS.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: No Information.

FIRST AID - EYE CONTACT: FLUSH WITH WATER 15 MINUTES, LIFTING EYELIDS.

FIRST AID - SKIN CONTACT: FLUSH WITH WATER.

FIRST AID - INHALATION: REMOVE TO FRESH AIR.

FIRST AID - INGESTION: DO NOT INDUCE VOMITING. GIVE LARGE QUANTITIES OF WATER OR MILK. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION. GET MEDICAL ATTENTION.

PRIMARY ROUTE(S) OF ENTRY: INGESTION EYE CONTACT

# SECTION VI - REACTIVITY DATA

HAZARDOUS DECOMPOSITION PRODUCTS: NORMAL DECOMPOSITION TO CARBON DIOXIDE, CARBON MONOXIDE, NITROUS OXIDE AND AMMONIA VAPORS. CARBON MONOXIDE HAZARDOUS IN ENCLOSED HIGH CONC.

CONDITIONS TO AVOID: STRONG OXIDIZING AGENTS.

INCOMPATABILITY: ANIONIC SURFACTANTS OR SOAPS.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

(Continued on Page 2)

Product: LB305

Preparation Date: 06/25/99

Page 2

### SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: PREVENT SPILLS FROM ENTERING SEWERS, OR ANY UNAUTHORIZED WATER SYSTEMS. DIKE FOR RECOVERYOR DISPOSAL. SMALL AMOUNTS, FLUSH TO SEWER.

WASTE DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH APPROPRIATE FEDERAL, STATE AND LOCAL REGULATIONS.

### SECTION VIII - SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION: NIOSH/OSHA APPROVED RESPIRATOR TYPES SUITABLE FOR MATERIALS IN SECTION II RECOMMENDED. APPROVED CHEMICAL/MECHANICAL FILTERS RECOMMENDED WHEN VENTILATION IS RESTRICTED.

VENTILATION: SUFFICIENT VENTILATION, IN VOLUME AND PATTERN, SHOULD BE PROVIDED TO KEEP AIR CONTAMINATION BELOW CURRENT APPLICABLE OSHA PERMISSIBLE EXPOSURE LIMIT OR ACGHI'S TLV LIMIT.

SKIN PROTECTION: GLOVES NEEDED FOR EXTRA SENSITIVE SKIN.

EYE PROTECTION: SAFETY GLASSES OR GOGGLES.

OTHER PROTECTIVE EQUIPMENT: No Information.

HYGENIC PRACTICES: WASH AFTER EACH USE.

#### SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE IN A COOL DRY AREA, KEEP AWAY FROM SPARKS AND OPEN FLAMES.

OTHER PRECAUTIONS: OBEY ALL HAZARD WARNINGS WHEN CONTAINERS ARE EMPTIED.

## SECTION X - HMIS RATINGS

**HMIS RATINGS** 

HEALTH: 2

FLAMMABILITY: 1

REACTIVITY: 0

### SECTION XI - OTHER REGULATIONS

SARA SECTION 313: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

---- CHEMICAL NAME ----- CAS NUMBER

WT/WT %

ETHYLENE OXIDE

75-21-8

0.01 %

PREVIOUS MSDS REVISION DATE: 11/17/97

LEGEND: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information contained on this MSDS is been checked and should be accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.