

Spartan Chemical Company, Inc. **Material Safety Data Sheet**

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label):

Product Division: Janitorial

Product Number: 7115; 7495

Spartan Chemical Company, Inc.

Product/Technical Information: 1-(800)-537-8990

1110 Spartan Drive Maumee OH 43537

Medical Emergency:1-(888)-314-6171 (24 hours)

Chemical Leak/Spil CHEMTREC 1-(800) 424-9300 (24 hours)
Emergency:

Shinning Dec	crintion: Corresive liquid	s, n.o.s., 8, UN 1760, III, (contains hydrocl	hloric (muriatic) acid)
NFPA Ratings:		HMIS Ratings:	
Health:	3 - Serious	Health:	3 - Serious; Chronic Hazard
Fire:	0 - Minimal	Fire:	0 - Minimal
Reactivity:	0 - Minimal	Reactivity:	0 - Minimal
. 44		Pers. Prot. Equip.:	See Section VIII

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

				Table Z- 1 - A		NTP, IARC
Chemical Name(s)	% W	CAS Registry No.		STEL mg/m ³	CELING mg/m ³	or OSHA Carcinogen
*Hydrochloric acid	5-10	7647-01-0	Not Established	Not Established	7	No

Comment: *This substance is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (SARA) and of 40 CFR 372.

SECTION III: PHYSICAL DATA

Boiling Point:	210-212 °F	Vapor Pressure:	Undetermined
Vapor Density (AIR = 1):	Unknown	Solubility in Water:	Complete
pH:	< 1	Specific Gravity (H ₂ O=1):	
Evaporation Rate (but.ace.=1):		Percent Solid by Weight:	< 1-2
Physical State:	Liquid		-
Appearance & Odo	r: Opaque green liqu	id nine fragrance	

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point:	> 212°F	Method Used:	ASTM-D56
Flammable Limits:	Not Established	Flame Extension:	N/A
Extinguishing Media	Product does not support c surrounding fire.	ombustion. Use extinguishing m	aedia appropriate for
	Wear NIOSH approved self-contained breathing apparatus and protective clothing. Cool fire-exposed containers with water spray.		
	Combustion products are toxic. Acid action on most metals may release hydrogen, an explosive gas.		

SECTION V: HEALTH HAZARD DATA

Threshold Limit Value:	Not Established	Primary Routes of Entry: Inhalation, Skin Contact, Eye & Oral
Effects of Overexposure- Conditions to Avoid:	include pain, redness, swelling MAY BE FATAL IF SWALL and diarrhea. INHALATION OF VAPORS TO THE RESPIRATORY T difficulty breathing. Do not get in eyes on skin or	EYE DAMAGE AND SKIN BURNS: Symptoms may and tissue damage. Harmful if absorbed through the skin LOWED. Symptoms may include nausea, vomiting, pain S OR MIST MAY CAUSE IRRITATION OR HARM TRACT. Breathing vapors or mist may cause coughing and clothing. Do not swallow. Avoid breathing product ghly with soap and water after handling.
Conditions Aggravated by Use:	Use of this product may aggravincluding asthma and dermatiti	vate preexisting skin; eye and respiratory disorders is.

Emergency & First Aid Procedures:

I	Flush eyes with water for at least 15 minutes. Remove contact lenses. Get medical attention.
	Remove contaminated clothing. Rinse skin immediately with plenty of water for at least 15 minutes. Get medical attention if irritation persists. Wash contaminated clothing before reuse.
	Get immediate medical attention. Do not induce vomiting. Drink one or two glasses of water to dilute product. Do not give anything by mouth to an unconscious person.
Inhalation:	Move person to fresh air. Get medical attention if irritation persists.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

SECTION VI: REACTIVITY DATA

Stability: Stable	Incompatible Materials: Strong alkalis; hy (bleach) ammonia	
Hazardous Decomposition Products:	Hazardous Polymerization: Will Not Occur	

SECTION VII: SPILL OR LEAK PROCEDURES

Material is Released or Spilled:	Small spills of one quart or less may be flushed with plenty of water to sanitary sewer system (If permitted by local sewer regulations). Dike and contain larger spills with inert material and transfer liquid to containers for recovery or disposal.
Waste Disposal Method:	Dispose of in compliance with all federal, state and local laws and regulations.

SECTION VIII: SPECIAL PROTECTION INFORMATION

	Not normally required when good general ventilation is provided. However, if exposure limits (see Section II) are exceeded or respiratory irritation occurs, use of a NIOSH approved respirator suitable for the use-conditions and chemicals in Section II should be considered.
	Provide good general ventilation. Local exhaust ventilation may be necessary for some operations.
Protective Gloves(Specify Type):	Rubber or neoprene gloves are recommended.
Eye Protection(Specify Type):	Splash goggles are recommended to prevent eye contact.
In 555	Acid resistant aprons and boots are recommended where body or foot contact is likely. Eye wash stations and washing facilities should be readily accessible. See 29 CFR 1910.132-138.

SECTION IX: SPECIAL PRECAUTIONS

Storing:	Do not contaminate water, food or feed by storage or disposal. Keep from freezing. Do not use with other chemicals. Mixtures of this product with other chemicals, particularly those containing chlorine bleach or ammonia may result in the production of toxic gases, fire or explosion.
Other Precautions:	Keep out of reach of children.

© SCC 06/30/2005 M*95

Name:

Ronald T. Cook

Title:

Manager, Regulatory Affairs

Effective 06/30/2005 Supercedes:

04/09/2004

Date: Ref: 29 CFR 1910.1200 (OSHA) Changes:

Update Section IX

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.