

A00242MA MST MANGO 20net10

Version 1.0

Revision Date 08/30/2017

Print Date 09/11/2017

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name

: A00242MA MST MANGO 20net 10

Material number

: 00000000001020755

Manufacturer or supplier's details

Company

Address

1310 Seaboard Industrial Blvd., NW

Atlanta, GA 30318

Telephone

404-352-1680

Emergency telephone numbers				
For SDS Information	 :	Compliance Services 1-877-428-9937	*******	
For a Medical Emergency	:	877-541-2016 Toll Free - All Calls Recorded		
For a Transportation Emergency		CHEMTREC: 800-424-9300 - All Calls Recorded. In the District of Columbia 202-483-7616		

Recommended use of the chemical and restrictions on use

Recommended use : Air Care

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	colourless
Odour	acetone-like

GHS Classification

Flammable aerosols

: Category 1

Gases under pressure

: Liquefied gas

Eye imitation

: Category 2A

Specific target organ toxicity - : Category 3 (Central nervous system)

single exposure

GHS label elements

Hazard pictograms



Signal word Danger

Hazard statements : H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

: Prevention:



A00242MA MST MANGO 20net10

Version 1.0

Revision Date 08/30/2017

Print Date 09/11/2017

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear eye protection/ face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Call a POISON

CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye imitation persists: Get medical advice/

attention.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F. P403 Store in a well-ventilated place.

Disposal:

Dispose of contents/container in accordance with local

regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
acetone	67-64-1	>= 70 - < 90
propane	74-98-6	>= 10 - < 20
butane	106-97-8	>= 5 - < 10

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice

Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled

: Consult a physician after significant exposure.

If unconscious place in recovery position and seek medical

advice.

In case of skin contact

In case of contact, immediately flush skin with plenty of water.

Take off contaminated clothing and shoes immediately. Get medical attention if irritation develops and persists.

Wash contaminated clothing before re-use.

In case of eye contact

: Immediately flush eye(s) with plenty of water.

Remove contact lenses.



A00242MA MST MANGO 20net10

Version 1.0 Revision Date 08/30/2017

Print Date 09/11/2017

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye imitation persists, consult a specialist.

If swallowed

: Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash. Symptoms may include difficulty breathing, coughing, wheezing, throat irritation, and tightness/closure of airway.

May cause an allergic skin reaction. Causes serious eye imitation.

Review section 2 of SDS to see all potential hazards.

Notes to physician

: Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media

: Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2)

Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information

: Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and

: Use personal protective equipment.

Ensure adequate ventilation.



A00242MA MST MANGO 20net10

Version 1.0 Revision Date 08/30/2017 Print Date 09/11/2017 emergency procedures Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. : Prevent product from entering drains. Environmental precautions Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. Methods and materials for : Soak up with inert absorbent material (e.g. sand, silica gel, containment and cleaning up acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.
For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects. No smoking.

Observe label precautions.

Keep in a dry, cool and well-ventilated place.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm	OSHA Z-1



OSHA P0

CAL PEL

1,900 mg/m3

1,900 mg/m3

1,900 mg/m3

800 ppm

800 ppm

A00242MA MST MANGO 20net10

Version 1.0	Revision	Revision Date 08/30/2017		Print Date 09/11/2017	
			2,400 mg/m3	1	
		TWA	750 ppm 1,800 mg/m3	OSHA P0	
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0	
		STEL	750 ppm 1,780 mg/m3	CAL PEL	
		С	3,000 ppm	CAL PEL	
		PEL	500 ppm 1,200 mg/m3	CAL PEL	
propane	74-98-6	TWA	1,000 ppm	ACGIH	
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL	
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1	
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0	
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL	
butane	106-97-8	TWA	800 ppm	NIOSH REL	

Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure	25 mg/l	ACGIH BEI

TWA

PEL

Engineering measures

: effective ventilation in all processing areas

Personal protective equipment

Respiratory protection

: No personal respiratory protective equipment normally

required.

Hand protection

Remarks

: Skin should be washed after contact.

Eye protection

: Always wear eye protection when the potential for inadvertent

eye contact with the product cannot be excluded.

Skin and body protection

: No special protection is required.

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.



A00242MAMST MANGO 20net10

Version 1.0

Revision Date 08/30/2017

Print Date 09/11/2017

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

: Aerosol containing a liquefied gas

Colour

: colourless

Odour

: acetone-like

Odour Threshold

No data available

pΗ

Not applicable

Melting point/freezing point

: No data available

Boiling point

No data available

Flash point

.

Not applicable

Evaporation rate

: No data available

Flammability (solid, gas)

: Extremely flammable aerosol.

Upper explosion limit

: No data available

Lower explosion limit

: No data available

Vapour pressure

: No data available

Relative vapour density

: No data available

Density

: No data available

Solubility(ies)

Water solubility

: partly soluble

Solubility in other solvents

: not determined

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature

: not determined

Thermal decomposition

: No data available

Heat of combustion

: 34.80 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity

: Stable

Chemical stability

: Stable under normal conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

No decomposition if stored and applied as directed.



A00242MA MST MANGO 20net10

Version 1.0

Revision Date 08/30/2017

Print Date 09/11/2017

Conditions to avoid

: Heat, flames and sparks.

Incompatible materials

: Amines

Bases

Oxidizing agents

Hazardous decomposition

products

: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

: None known.

Condition

Symptoms of Overexposure

: Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash. Symptoms may include difficulty breathing, coughing, wheezing, throat irritation, and tightness/closure of airway.

Carcinogenicity:

IARC

No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH

No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA

No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Acute toxicity

Components:

acetone:

Acute oral toxicity

; LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity

: LC50 Rat: 132 mg/l Exposure time: 3 h

LC50 Rat: 50.1 mg/l

Acute dermal toxicity

: LD50 Guinea pig: > 7,426 mg/kg

LD50 Rabbit: > 7,426 mg/kg



A00242MAMST MANGO 20net10

Version 1.0

Revision Date 08/30/2017

Print Date 09/11/2017

Skin corrosion/irritation

Product:

Remarks: May irritate skin.

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:



A00242MA MST MANGO 20net10

 Version 1.0
 Revision Date 08/30/2017
 Print Date 09/11/2017

Partition coefficient: n-

octanol/water

: Remarks: No data available

Components:

butane :

Partition coefficient: n-

: Pow: 2.89

octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

: The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging

: Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN1950, Aerosols, flammable, 2.1, - Limited quantity



A00242MA MST MANGO 20net10

Version 1.0

Revision Date 08/30/2017

Print Date 09/11/2017

Transportation Regulation: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list

: No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
acetone	67-64-1	5000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards

: Fire Hazard

Sudden Release of Pressure Hazard

Acute Health Hazard

SARA 302

: No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis)

reporting levels established by SARA Title III, Section 313.

California Prop 65

This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

The components of this product are reported in the following inventories:

TSCA

On TSCA Inventory

DSL

This product contains one or several components that are not on the

Canadian DSL nor NDSL.



A00242MA MST MANGO 20net10

Version 1.0

Revision Date 08/30/2017

Print Date 09/11/2017

For information on the country notification status for other regions please contact the manufacturer's regulatory group.


Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

HMIS III:

	ICAL HAZA		_
FLAN	MABILITY	7	4
HEAL	.TH		2

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms







Signal word Hazard statements

Danger:

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary statements

Prevention: Keep aw ay from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/ face protection.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	1.0
Revision Date:	08/30/2017
Print Date:	09/11/2017

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this



A00242MA MST MANGO 20net10

Version 1.0

Revision Date 08/30/2017

Print Date 09/11/2017

document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®,Rexodan®, Mykal™, and a number of private labeled brands.