## SAFETY DATA SHEET



# **PURELL® Advanced Instant Hand Sanitizer Fragrance Free**

Version Revision Date: MSDS Number: Date of last issue: 12/19/2014
1.3 02/10/2015 36432-00004 Date of first issue: 12/11/2014

### **SECTION 1. IDENTIFICATION**

Product name : PURELL® Advanced Instant Hand Sanitizer Fragrance Free

### Manufacturer or supplier's details

Company name of supplier : GOJO Industries, Inc.

Address : One GOJO Plaza, Suite 500

Akron OH 44311

Telephone : 1 (330) 255-6000

Emergency telephone : 1-800-424-9300 CHEMTREC

### Recommended use of the chemical and restrictions on use

Recommended use : Hand Sanitizer

Restrictions on use : This is a personal care or cosmetic product that is safe for

consumers and other users under normal and reasonably foreseeable use. Cosmetics and consumer products, specifically defined by regulations around the world, are exempt from the requirement of an SDS for the consumer. While this material is not considered hazardous, this SDS contains valuable information critical to the safe handling and proper use of the product for industrial workplace conditions as well as unusual and unintended exposures such as large spills. This SDS should be retained and available for employees and other users of this product. For specific intended-use guidance, please refer to the information

provided on the package or instruction sheet.

### **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Flammable liquids : Category 3

Eye irritation : Category 2A

**GHS Label element** 

Hazard pictograms





Signal Word : Warning

Hazard Statements : H226 Flammable liquid and vapor.



Version Revision Date: MSDS Number: Date of last issue: 12/19/2014
1.3 02/10/2015 36432-00004 Date of first issue: 12/11/2014

H319 Causes serious eye irritation.

Precautionary Statements : Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces. -

No smoking.

P233 Keep container tightly closed.

P241 Use explosion-proof electrical/ ventilating/ lighting/

equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately

all contaminated clothing. Rinse skin with water/shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/

attention. Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

#### Other hazards

Vapors may form explosive mixture with air.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

## **Hazardous ingredients**

Chemical Name	CAS-No.	Concentration (%)
Ethanol	64-17-5	>= 50 - < 70
Propan-2-ol	67-63-0	>= 1 - < 5

#### **SECTION 4. FIRST AID MEASURES**

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.

Get medical attention if symptoms occur.



 Version
 Revision Date:
 MSDS Number:
 Date of last issue: 12/19/2014

 1.3
 02/10/2015
 36432-00004
 Date of first issue: 12/11/2014

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.

If swallowed : If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

: Causes serious eye irritation.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment

when the potential for exposure exists.

Notes to physician : Treat symptomatically and supportively.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Water spray

Alcohol-resistant foam

Dry chemical

Carbon dioxide (CO2)

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during fire

fighting

: Do not use a solid water stream as it may scatter and spread

fire.

Flash back possible over considerable distance. Vapors may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

: Carbon oxides

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, : Remove all sources of ignition.



 Version
 Revision Date:
 MSDS Number:
 Date of last issue: 12/19/2014

 1.3
 02/10/2015
 36432-00004
 Date of first issue: 12/11/2014

protective equipment and emergency procedures

Use personal protective equipment.

Follow safe handling advice and personal protective

equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

: Non-sparking tools should be used. Soak up with inert absorbent material.

Suppress (knock down) gases/vapors/mists with a water spray

jet.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material

can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

### **SECTION 7. HANDLING AND STORAGE**

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use with local exhaust ventilation.

Use only in an area equipped with explosion proof exhaust

ventilation.

Advice on safe handling : Do not breathe vapors or spray mist.

Do not swallow. Do not get in eyes.

Avoid prolonged or repeated contact with skin.

Handle in accordance with good industrial hygiene and safety

practice.

Non-sparking tools should be used. Keep container tightly closed.

Keep away from heat and sources of ignition.

Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Keep tightly closed.



Version Revision Date: MSDS Number: Date of last issue: 12/19/2014
1.3 02/10/2015 36432-00004 Date of first issue: 12/11/2014

Keep in a cool, well-ventilated place.

Store in accordance with the particular national regulations.

Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents Organic peroxides Flammable solids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures which in contact with water emit

flammable gases Explosives Gases

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

# Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethanol	64-17-5	TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		STEL	1,000 ppm	ACGIH
Propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1

### **Biological occupational exposure limits**

Ingredients	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentratio n	Basis
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work- week	40 mg/l	ACGIH BEI

**Engineering measures** : Minimize workplace exposure concentrations.

Use only in an area equipped with explosion proof exhaust

ventilation

Use with local exhaust ventilation.



Version Revision Date: MSDS Number: Date of last issue: 12/19/2014
1.3 02/10/2015 36432-00004 Date of first issue: 12/11/2014

### Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material : Impervious gloves

Material : Flame retardant gloves

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before

breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:

Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Wear the following personal protective equipment: Flame retardant antistatic protective clothing.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hygiene measures : Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

# **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Color : clear

Odor : alcohol-like



Version Revision Date: MSDS Number: Date of last issue: 12/19/2014
1.3 02/10/2015 36432-00004 Date of first issue: 12/11/2014

Odor Threshold : No data available

pH : 6.5 - 8.5

Melting point/freezing point : No data available

Initial boiling point and boiling

range

: No data available

Flash point : 24 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Density : 0.88 g/cm3

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

: Not applicable

Autoignition temperature : No data available

Decomposition temperature : The substance or mixture is not classified self-reactive.

Viscosity

Viscosity, kinematic : 6,000 - 17,000 mm2/s (20 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Flammable liquid and vapor.

Vapors may form explosive mixture with air. Can react with strong oxidizing agents.



Version Revision Date: MSDS Number: Date of last issue: 12/19/2014
1.3 02/10/2015 36432-00004 Date of first issue: 12/11/2014

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: No hazardous decomposition products are known.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

# Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

# **Acute toxicity**

Not classified based on available information.

#### **Product:**

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

#### **Ingredients:**

Ethanol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 124.7 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Propan-2-ol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 72.6 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

#### Skin corrosion/irritation

Not classified based on available information.

#### **Product:**

Result: No skin irritation

# Ingredients:

Ethanol:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation



Version Revision Date: MSDS Number: Date of last issue: 12/19/2014 1.3 02/10/2015 36432-00004 Date of first issue: 12/11/2014

**Propan-2-ol:**Species: Rabbit

Result: No skin irritation

## Serious eye damage/eye irritation

Causes serious eye irritation.

<u>Ingredients:</u>

Ethanol:

Species: Rabbit

Result: Irritation to eyes, reversing within 21 days

Method: OECD Test Guideline 405

**Propan-2-ol:** Species: Rabbit

Result: Irritation to eyes, reversing within 21 days

#### Respiratory or skin sensitization

Skin sensitization: Not classified based on available information.

Respiratory sensitization: Not classified based on available information.

Product:

Assessment: Does not cause skin sensitization.

**Ingredients:** 

Ethanol:

Test Type: Local lymph node assay (LLNA)

Routes of exposure: Skin contact

Species: Mouse Result: negative

Propan-2-ol:

Test Type: Buehler Test

Routes of exposure: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: negative

# Germ cell mutagenicity

Not classified based on available information.

**Ingredients:** 

Ethanol:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)

Species: Mouse

Application Route: Ingestion

Result: negative



Version Revision Date: MSDS Number: Date of last issue: 12/19/2014
1.3 02/10/2015 36432-00004 Date of first issue: 12/11/2014

Propan-2-ol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

# Carcinogenicity

Not classified based on available information.

#### **Ingredients:**

### Propan-2-ol: Species: Rat

Application Route: inhalation (vapor)

Exposure time: 104 weeks

Method: OECD Test Guideline 451

Result: negative

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential carcino-

gen by OSHA.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

### Reproductive toxicity

Not classified based on available information.

#### **Ingredients:**

Ethanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Mouse

Application Route: Ingestion
Method: OECD Test Guideline 416

Result: negative

Propan-2-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion



Version Revision Date: MSDS Number: Date of last issue: 12/19/2014 1.3 02/10/2015 36432-00004 Date of first issue: 12/11/2014

Result: negative

#### STOT-single exposure

Not classified based on available information.

# Ingredients:

Propan-2-ol:

Assessment: May cause drowsiness or dizziness.

#### STOT-repeated exposure

Not classified based on available information.

#### Repeated dose toxicity

### **Ingredients:**

# Ethanol: Species: Rat

NOAEL: 2,400 mg/kg

Application Route: Ingestion

Exposure time: 2 y

# Propan-2-ol:

Species: Rat

NOAEL: 5000 ppm

Application Route: inhalation (vapor)

Exposure time: 104 w

Method: OECD Test Guideline 413

# **Aspiration toxicity**

Not classified based on available information.

# **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

# Ingredients:

Ethanol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 1,000 mg/l

Exposure time: 48 h

Toxicity to algae : EC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): 9.6 mg/l

Exposure time: 9 d



Version Revision Date: MSDS Number: Date of last issue: 12/19/2014
1.3 02/10/2015 36432-00004 Date of first issue: 12/11/2014

Toxicity to bacteria : EC50 (Photobacterium phosphoreum): 32.1 mg/l

Exposure time: 0.25 h

Propan-2-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 10,000 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 24 h

Toxicity to algae : ErC50 (Scenedesmus quadricauda (Green algae)): > 1,800

mg/l

Exposure time: 8 d

Toxicity to bacteria : EC50 (Pseudomonas putida): > 1,050 mg/l

Exposure time: 16 h

### Persistence and degradability

**Ingredients:** 

Ethanol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 84 % Exposure time: 20 d

Propan-2-ol:

Biodegradability : Result: rapidly degradable

**Bioaccumulative potential** 

**Ingredients:** 

Ethanol:

Partition coefficient: n-

octanol/water

: log Pow: -0.35

Propan-2-ol:

Partition coefficient: n-

octanol/water

: log Pow: 0.05

Mobility in soil

No data available

Other adverse effects

No data available

#### **SECTION 13. DISPOSAL CONSIDER ATIONS**

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Dispose of as unused product.



Version Revision Date: MSDS Number: Date of last issue: 12/19/2014
1.3 02/10/2015 36432-00004 Date of first issue: 12/11/2014

Empty containers should be taken to an approved waste

handling site for recycling or disposal.

Do not burn, or use a cutting torch on, the empty drum.

### **SECTION 14. TRANSPORT INFORMATION**

### International Regulation

**UNRTDG** 

UN number : UN 1987

Proper shipping name : ALCOHOLS, N.O.S.

(Ethanol, Propan-2-ol)

Class : 3
Packing group : III
Labels : 3

IATA-DGR

UN/ID No. : UN 1987
Proper shipping name : Alcohols, n.o.s.

(Ethanol, Propan-2-ol)

Class : 3 Packing group : III

Labels : Flammable Liquids

366

Packing instruction (cargo

aircraft)

Packing instruction : 355

(passenger aircraft)

**IMDG-Code** 

UN number : UN 1987

Proper shipping name : ALCOHOLS, N.O.S.

(Ethanol, Propan-2-ol)

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-D
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

# **Domestic regulation**

**49 CFR** 

UN/ID/NA number : UN 1987

Proper shipping name : ALCOHOLS, N.O.S.

Class : 3 Packing group : III

Labels : FLAMMABLE LIQUID

ERG Code : 127



Version Revision Date: MSDS Number: Date of last issue: 12/19/2014
1.3 02/10/2015 36432-00004 Date of first issue: 12/11/2014

Marine pollutant : no

#### **SECTION 15. REGULATORY INFORMATION**

### **EPCRA - Emergency Planning and Community Right-to-Know**

#### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Propan-2-ol 67-63-0 3.4086 %

# **US State Regulations**

Pennsylvania Right To Know

Ethanol	64-17-5	50 - 70 %	
Water	7732-18-5	30 - 50 %	
Propan-2-ol	67-63-0	1 - 5 %	

**New Jersey Right To Know** 

Ethanol	64-17-5	50 - 70 %	
Water	7732-18-5	30 - 50 %	
Propan-2-ol	67-63-0	1 - 5 %	

California Prop 65 This product does not contain any chemicals known to the

State of California to cause cancer, birth, or any other

reproductive defects.

## The ingredients of this product are reported in the following inventories:

AICS : All ingredients listed or exempt.

#### **Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), NECSI (Taiwan), TSCA (USA)




Version Revision Date: MSDS Number: Date of last issue: 12/19/2014
1.3 02/10/2015 36432-00004 Date of first issue: 12/11/2014

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

### NFPA:



Special hazard.

#### HMIS III:

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, \* = Chronic

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA Z-1 / TWA : 8-hour time weighted average

Sources of key data used to compile the Material Safety

**Data Sheet** 

: Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 02/10/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8