

**A00390 MST PENETRATING LUBE 20net19**

Version 1.0

Revision Date 02/10/2015

Print Date 06/11/2015

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : A00390 MST PENETRATING LUBE 20net19

Material number : 000000000001002456

**Manufacturer or supplier's details**

Company : Zep Inc.

Address : 1310 Seaboard Industrial Blvd., NW  
Atlanta, GA 30318

Telephone : 404-352-1680

**Emergency telephone numbers****For SDS Information** : Compliance Services 1-877-428-9937**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded**For a Transportation Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.  
In the District of Columbia 202-483-7616**SECTION 2. HAZARDS IDENTIFICATION****Emergency Overview**

Appearance	Aerosol containing a compressed gas
Colour	opaque, brown
Odour	solvent-like

**GHS Classification**Flammable aerosols : Category 2  
Gases under pressure : Compressed gas  
Skin irritation : Category 2  
Eye irritation : Category 2A  
Carcinogenicity : Category 1A**GHS Label element**

Hazard pictograms



Signal word : Danger

Hazard statements : H223 Flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H350 May cause cancer.Precautionary statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read

**A00390 MST PENETRATING LUBE 20net19**

Version 1.0

Revision Date 02/10/2015

Print Date 06/11/2015

and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P264 Wash skin thoroughly after handling.

P280 Wear eye protection/ face protection.

P280 Wear protective gloves.

P281 Use personal protective equipment as required.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

**Storage:**

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:**

P501 Dispose of contents/container in accordance with local regulation.

**Potential Health Effects****Carcinogenicity:**

<b>IARC</b>	Group 1: Carcinogenic to humans	
	trichloroethylene	79-01-6
	Group 2A: Probably carcinogenic to humans	
<b>ACGIH</b>	tetrachloroethylene	127-18-4
	Suspected human carcinogen	
	trichloroethylene	79-01-6
<b>OSHA</b>	Confirmed animal carcinogen with unknown relevance to humans	
	tetrachloroethylene	127-18-4
	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	
<b>NTP</b>	Reasonably anticipated to be a human carcinogen	
	tetrachloroethylene	127-18-4
	trichloroethylene	79-01-6

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS****Hazardous components**

**A00390 MST PENETRATING LUBE 20net19**

Version 1.0

Revision Date 02/10/2015

Print Date 06/11/2015

Chemical Name	CAS-No.	Concentration [%]
tetrachloroethylene	127-18-4	>= 50 - < 70
Stoddard solvent	8052-41-3	>= 10 - < 20
trichloroethylene	79-01-6	>= 5 - < 10
carbon dioxide	124-38-9	>= 1 - < 5
1,2,4-trimethylbenzene	95-63-6	>= 1 - < 5

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : If unconscious place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Remove contaminated clothing and shoes.  
Wash clothing before reuse.  
Wash off immediately with plenty of water for at least 15 minutes.  
Call a physician if irritation develops or persists.
- In case of eye contact : Remove contact lenses.  
Immediately flush eyes for at least 15 minutes. Get medical attention.  
Keep eye wide open while rinsing.  
Protect unharmed eye.
- If swallowed : Keep respiratory tract clear.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
DO NOT induce vomiting unless directed to do so by a physician or poison control center.  
Take victim immediately to hospital.

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide  
Smoke  
Chlorine compounds  
Sulphur oxides
- Specific extinguishing :

**A00390 MST PENETRATING LUBE 20net19**

Version 1.0

Revision Date 02/10/2015

Print Date 06/11/2015

## methods

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

## Further information

- : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

## Special protective equipment for firefighters

- : Wear self-contained breathing apparatus for firefighting if necessary.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

## Personal precautions, protective equipment and emergency procedures

- : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

## Environmental precautions

- : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

## Methods and materials for containment and cleaning up

- : Sweep up or vacuum up spillage and collect in suitable container for disposal.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

---

**SECTION 7. HANDLING AND STORAGE**

## Advice on safe handling

- : Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.

## Conditions for safe storage

- : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
No smoking.  
Keep container tightly closed in a dry and well-ventilated

**A00390 MST PENETRATING LUBE 20net19**

Version 1.0

Revision Date 02/10/2015

Print Date 06/11/2015

place.

Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Observe label precautions.

Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Oxidizing agents  
Keep away from metals.

Storage temperature : < 49 °C

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
tetrachloroethylene	127-18-4	TWA	25 ppm	ACGIH
		STEL	100 ppm	ACGIH
		TWA	100 ppm	OSHA Z-2
		CEIL	200 ppm	OSHA Z-2
		Peak	300 ppm	OSHA Z-2
		TWA	25 ppm 170 mg/m3	OSHA P0
Stoddard solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	350 mg/m3	NIOSH REL
		C	1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,900 mg/m3	OSHA Z-1
		TWA	100 ppm 525 mg/m3	OSHA P0
trichloroethylene	79-01-6	TWA	10 ppm	ACGIH
		STEL	25 ppm	ACGIH
		TWA	100 ppm	OSHA Z-2
		CEIL	200 ppm	OSHA Z-2
		Peak	300 ppm	OSHA Z-2
		TWA	50 ppm 270 mg/m3	OSHA P0
		STEL	200 ppm 1,080 mg/m3	OSHA P0
carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m3	NIOSH REL
		ST	30,000 ppm 54,000 mg/m3	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m3	OSHA Z-1
		TWA	10,000 ppm 18,000 mg/m3	OSHA P0
		STEL	30,000 ppm 54,000 mg/m3	OSHA P0

## A00390 MST PENETRATING LUBE 20net19

Version 1.0

Revision Date 02/10/2015

Print Date 06/11/2015

1,2,4-trimethylbenzene	95-63-6	TWA	25 ppm 125 mg/m <sup>3</sup>	NIOSH REL
------------------------	---------	-----	---------------------------------	-----------

## Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
TETRACHLOROETHENE	127-18-4	Tetrachloroethylene	In blood	Prior to shift (16 hours after exposure ceases)	0.5 mg/l	ACGIH BEI
TETRACHLOROETHENE		Tetrachloroethylene	In end-exhaled air	Prior to shift (16 hours after exposure ceases)	3 .parts per million	ACGIH BEI
TRICHLOROETHENE	79-01-6	Trichloroacetic acid	Urine	End of shift at end of workweek	15 mg/l	ACGIH BEI
TRICHLOROETHENE		Trichloroethanol	In blood	End of shift at end of workweek	0.5 mg/l	ACGIH BEI
TRICHLOROETHENE		Trichloroethylene	In blood	End of shift at end of workweek		ACGIH BEI
TRICHLOROETHENE		Trichloroethylene	In end-exhaled air	End of shift at end of workweek		ACGIH BEI

## Personal protective equipment

- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.  
In the case of dust or aerosol formation use respirator with an approved filter.
- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : impervious clothing

**A00390 MST PENETRATING LUBE 20net19**

Version 1.0

Revision Date 02/10/2015

Print Date 06/11/2015

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	: Aerosol containing a compressed gas
Colour	: opaque, brown
Odour	: solvent-like
Odour Threshold	: no data available
pH	: not applicable
Melting point/freezing point	: no data available
Boiling point	: no data available
Flash point	: no data available
Evaporation rate	: no data available
Upper explosion limit	: no data available
Lower explosion limit	: no data available
Vapour pressure	: no data available
Relative vapour density	: no data available
Density	: 1.210 g/cm <sup>3</sup>
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: no data available
Auto-ignition temperature	: not determined
Thermal decomposition	: no data available
Viscosity	
Viscosity, kinematic	: no data available
Heat of combustion	: 18.53 kJ/g

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.

**A00390 MST PENETRATING LUBE 20net19**

Version 1.0

Revision Date 02/10/2015

Print Date 06/11/2015

Possibility of hazardous reactions	: Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Oxidizing agents Aluminium Metals
Hazardous decomposition products	: Carbon oxides Sulphur oxides Chlorine

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity****Product:**

Acute oral toxicity	: Acute toxicity estimate : 4,421 mg/kg Method: Calculation method
Acute inhalation toxicity	: Acute toxicity estimate : > 10 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method

**Components:****tetrachloroethylene:**

Acute oral toxicity	: LD50 Oral rat: 2,629 mg/kg
Acute inhalation toxicity	: LC50 rat: 34,200 mg/l Exposure time: 8 h
Acute dermal toxicity	: LD50 Dermal rabbit: 5,000 mg/kg
<b>trichloroethylene:</b>	
Acute oral toxicity	: LD50 Oral rat: 4,920 mg/kg
Acute inhalation toxicity	: LC50 mouse: 8450 ppm Exposure time: 4 h
Acute dermal toxicity	: LD50 Dermal rabbit: > 20,000 mg/kg

**Skin corrosion/irritation****Product:**

Remarks: Irritating to skin.



**A00390 MST PENETRATING LUBE 20net19**

Version 1.0

Revision Date 02/10/2015

Print Date 06/11/2015

**Serious eye damage/eye irritation****Product:**

Remarks: Severe eye irritation

**Respiratory or skin sensitisation**

no data available

**Germ cell mutagenicity**

no data available

**Carcinogenicity**

no data available

**Reproductive toxicity**

no data available

tetrachloroethylene:

Stoddard solvent:

trichloroethylene:

carbon dioxide:

1,2,4-trimethylbenzene:

**STOT - single exposure**

no data available

**STOT - repeated exposure**

no data available

**Aspiration toxicity**

no data available

**Further information****Product:**

Remarks: no data available

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

no data available

**Persistence and degradability**

no data available

**Bioaccumulative potential****Product:**

Partition coefficient: n-octanol/water : Remarks: no data available

**A00390 MST PENETRATING LUBE 20net19**

Version 1.0

Revision Date 02/10/2015

Print Date 06/11/2015

**Components:****tetrachloroethylene :**

Partition coefficient: n-octanol/water : log Pow: 3.40

**trichloroethylene :**

Partition coefficient: n-octanol/water : log Pow: 2.29

**Mobility in soil**

no data available

**Other adverse effects**

no data available

**Product:****Regulation**

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

**Remarks**

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

**Additional ecological information**

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life.

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods****Waste from residues**: The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.**Contaminated packaging**: Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.**SECTION 14. TRANSPORT INFORMATION**Transportation Regulation: 49 CFR (USA):  
ORM-D, CONSUMER COMMODITYTransportation Regulation: IMDG (Vessel):  
UN1950, AEROSOLS, 2.1, - Limited quantity

**A00390 MST PENETRATING LUBE 20net19**

Version 1.0

Revision Date 02/10/2015

Print Date 06/11/2015

Transportation Regulation: IATA (Cargo Air):  
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):  
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):  
UN1950, AEROSOLS, 2.1, - Limited quantity

**SECTION 15. REGULATORY INFORMATION**
**EPCRA - Emergency Planning and Community Right-to-Know Act**
**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
tetrachloroethylene	127-18-4	100	182

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Acute Health Hazard  
Chronic Health Hazard  
Fire Hazard  
Sudden Release of Pressure Hazard

**SARA 302** : SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

tetrachloroethylene	127-18-4	54.99 %
trichloroethylene	79-01-6	8.385 %
1,2,4-trimethylbenzene	95-63-6	1.0023 %

**California Prop 65** WARNING! This product contains a chemical known to the State of California to cause cancer.

tetrachloroethylene	127-18-4
trichloroethylene	79-01-6

**The components of this product are reported in the following inventories:**

<b>TSCA</b>	On TSCA Inventory
<b>DSL</b>	All components of this product are on the Canadian DSL.
<b>AICS</b>	On the inventory, or in compliance with the inventory
<b>NZIoC</b>	Not in compliance with the inventory
<b>PICCS</b>	On the inventory, or in compliance with the inventory
<b>IECSC</b>	On the inventory, or in compliance with the inventory

**Inventory Acronym and Validity Area Legend:**


**A00390 MST PENETRATING LUBE 20net19**

Version 1.0

Revision Date 02/10/2015

Print Date 06/11/2015

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

**SECTION 16. OTHER INFORMATION**
**Further information**
**NFPA:**

**HMIS III:**

<b>HEALTH</b>	<b>2*</b>
<b>FLAMMABILITY</b>	<b>0</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

**OSHA GHS Label Information:**

Hazard pictograms



Signal word

: **Danger:**

Hazard statements

: Flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause cancer.

Precautionary statements

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash skin thoroughly after handling. Wear eye protection/ face protection. Wear protective gloves. Use personal protective equipment as required.

**Response:** IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/ attention. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.

**Storage:** Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:** Dispose of contents/container in accordance with local regulation.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

**A00390 MST PENETRATING LUBE 20net19**

Version 1.0

Revision Date 02/10/2015

Print Date 06/11/2015

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.