US - OSHA SAFETY DATA SHEET



 Issue Date
 25-Nov-2014
 Revision Date
 04-Apr-2019
 Version
 3

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Battery Electrolyte

Other means of identification

Product Code 853022 UN/ID No. UN2796 Synonyms Not available.

Recommended use of the chemical and restrictions on use

Recommended Use Used to activate dry batteries.
Uses Advised Against Any other not listed above

Details of the supplier of the safety data sheet

Supplier Address

Yuasa Battery, Inc. 2901 Montrose Avenue Laureldale, PA 19605 United States

www.yuasabatteries.com

Emergency telephone number

Company Phone Number (610) 929-5781 **24 Hour Emergency Phone Number** CHEMTREC:

Domestic (800) 424-9300 International 1(703) 527-3887

2. HAZARDS IDENTIFICATION

Classification

Health Hazards

Skin Corrosion/Irritation	Category 1 Sub-category A
Serious Eye Damage/Eye Irritation	Category 1

Physical Hazards

Not classified.

OSHA Regulatory Status

This product is considered hazardous by the 2012 OSHA Hazard Communication Standard/Globally Harmonized System of Classification and Labelling of Chemicals (GHS); (29 CFR 1910.1200; Revision 3).

Label elements

Emergency Overview

Danger

Hazard Statements

Fatal if inhaled.

Causes severe skin burns and eye damage.



Appearance Clear liquid.

Physical State Liquid.

Odor Pungent

Precautionary Statements - Prevention

Wear protective gloves/clothing/eye protection/face protection.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear respiratory protection

Wash face, hands and any exposed skin thoroughly after handling.

Precautionary Statements - Response

Specific treatment is urgent.

Immediately call a POISON CENTER or doctor.

If in eyes: Řinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Wash contaminated clothing before reuse.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

Take off contaminated clothing and wash it before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Immediately call a POISON CENTER or doctor.

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting.

Precautionary Statements - Storage

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal facility.

Hazards not otherwise classified (HNOC)

Not available.

Other information

Not available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200; Revision 3).

Chemical Name	CAS No.	Weight-%
Sulfuric acid	7664-93-9	36-45

^{*}Note: Non-hazardous chemical ingredients are not listed

4. FIRST AID MEASURES

First aid measures

Eye Contact In case of eye contact, immediately flush eyes with fresh water for at least 15 minutes while

holding the eyelids open. Remove contact lenses if worn. Get medical attention if irritation

persists. Immediate medical attention is required.

Skin Contact For minor skin contact, avoid spreading material on unaffected skin. In case of contact

with substance, immediately flush skin with running water for at least 20 minutes. Remove and isolate contaminated clothing and shoes. Immediate medical attention is not required.

Inhalation Immediately move exposed subject to fresh air. If not breathing, provide artificial respiration.

If breathing is difficult, administer oxygen. Seek medical attention immediately.

In case of accidental ingestion, wash out mouth with copious amounts of water. Seek

medical attention immediately. Do not induce vomiting unless directed by medical

personnel. Never give anything by mouth to an unconscious person.

Self-Protection of the First Aider Do not use mouth-to-mouth methods if victim ingested or inhaled the substance; give

artificial respiration with the aid of a pocket mask equipped with a one-way valve or another

proper respiratory medical device.

Most important symptoms and effects, both acute and delayed

Symptoms Inhalation: Corrosive. Burning sensation. Sore throat. Cough. Labored breathing. Shortness

of breath. Symptoms may be delayed. Skin: Corrosive. Redness. Pain. Blisters. Serious

skin burns. Eyes: Corrosive. Redness. Pain. Severe deep burns.

Indication of any immediate medical attention and special treatment needed

Note to Physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Small Fire Dry chemical, CO₂, or water spray.

Large Fire Dry chemical or CO₂, alcohol - resistant foam or water spray.

Unsuitable Extinguishing Media Any not listed above.

Specific hazards arising from the chemical

Hazardous decomposition products formed: Sulfur oxides (SOx).

produce corrosive fumes.

Explosion data

Sensitivity to Mechanical Impact None known.
Sensitivity to Static Discharge None known.

Protective equipment and precautions for firefighters

Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible. Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection. As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions.

Keep out of low areas. Keep unauthorized personnel away. Stay upwind.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Ventilate enclosed areas. Do not touch damaged containers or spilled material unless

wearing appropriate protective clothing.

Other information Non-emergency personnel should utilize chemical gloves.

For emergency responders Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area) as an

immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Do not get water inside container. Personal protective equipment: Wear chemical gloves,

goggles, acid resistant clothing and boots, respirator if insufficient ventilation.

Environmental precautions

Environmental Precautions Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for

additional ecological information.

Methods and material for containment and cleaning up

Methods for Containment

Stop leak if you can do it without risk. Absorb with earth sand or other non-combustible

material. Do not allow discharge of non-neutralized acid to sewer. Cautiously neutralize

spilled liquid.

Methods for Cleaning UpDispose of in accordance with local, state, and national regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle and open container with care. Avoid contact with skin and eyes. Use only with

adequate ventilation. Use caution when combining with water; DO NOT add water to corrosive liquid, ALWAYS add corrosive liquid to water while stirring to prevent release of heat, steam and fumes. Do not get in eyes or on skin or clothing. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Eyewash stations and safety showers should be provided with unlimited water supply. Handle in

accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from incompatible materials. Store locked up. Keep container/package tightly

closed in a cool, well-ventilated place. Ventilate enclosed areas. Storage class: Class 8B: Non-flammable corrosive materials.

Incompatible materialsBases, halides, organic materials, carbides, fulminates, nitrates, picrates, cyanides,

chlorates, alkali halides, zinc salts, permanganates, e.g. potassium permanganate,

hydrogen peroxide, azides, perchlorates, nitromethane, phosphorous; Reacts violently with:

cyclopentadiene, cyclopentanone oxime, nitroaryl amines, hexalithium disilicide,

phosphorous(iii) oxide, powdered metals.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure GuidelinesThis product, as supplied, contains the following hazardous materials with occupational

exposure limits established by the region-specific regulatory bodies.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Sulfuric acid	TWA: 0.2 mg/m ³ thoracic	TWA: 1 mg/m ³	IDLH: 15 mg/m ³
7664-93-9	particulate matter	(vacated) TWA: 1 mg/m ³	TWA: 1 mg/m ³

Appropriate engineering controls

Engineering Controls

The health hazard risks of handling this material are dependent on factors, such as physical

form and quantity. Site-specific risk assessments should be conducted to determine the appropriate exposure control measures. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain

airborne levels as low as reasonably achievable.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Wear appropriate chemical safety goggles safety glasses, or face shield as described by

OSHA eye and face protection regulations in 29 CFR 1910.133 at all times while handling

this product. Have eyewash stations available where eye contact can occur.

Skin and Body Protection Wear protective gloves with elbow length gauntlet. Wear synthetic apron. Under severe

exposure or emergency conditions, wear acid-resistant clothing and boots.

Respiratory Protection Where risk assessment shows air-purifying respirators are appropriate use a full-face

respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

General Hygiene Considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and

Odor

Pungent

protective equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Liquid.
Appearance Clear liquid.

ColorClear.Odor ThresholdNot available.

<u>Property</u> <u>Values</u> <u>Remarks</u>

pH Not available.

Melting Point/Freezing Point Not available.

Boiling Point/Boiling Range 95 °C - 95.5556 °C

Flash Point Not available.
Evaporation Rate Not available.
Flammability (solid, gas) Not available.

Flammability Limit in Air

Upper Flammability Limit:Not available.Lower Flammability Limit:Not available.Vapor Pressure10 mmHg

Vapor Density 1

Specific Gravity

Water Solubility

Solubility in Other Solvents

Partition Coefficient

Autoignition Temperature

Decomposition Temperature

1.215-1.35

Soluble in water.

Not available.

Not available.

Not available.

Kinematic ViscosityNot available.Dynamic ViscosityNot available.Explosive PropertiesNot available.Oxidizing PropertiesNot available.

Other information

Softening Point
Molecular Weight
VOC Content (%)
Not available.
Not available.

Density 10.1392-11.2658 lbs/gal

Bulk Density Not available.

10. STABILITY AND REACTIVITY

Reactivity

Reacts with a number of compounds.

Chemical stability

Stable under normal conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to avoid

Contact with organic materials, combustibles, strong reducing agents, metals, strong oxidizers, water.

Incompatible materials

Bases, halides, organic materials, carbides, fulminates, nitrates, picrates, cyanides, chlorates, alkali halides, zinc salts, permanganates, e.g. potassium permanganate, hydrogen peroxide, azides, perchlorates, nitromethane, phosphorous; Reacts violently with: cyclopentadiene, cyclopentanone oxime, nitroaryl amines, hexalithium disilicide, phosphorous(iii) oxide, powdered metals.

Hazardous decomposition products

Sulfur oxides (SOx).

11. TOXICOLOGICAL INFORMATION

Product Information

Acute Toxicity

This product is not classified under Acute Toxicity (Inhalation) as this does not apply for

liquid forms of sulfuric acid or sulfuric acid solutions contained within a battery.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50	Intravenous LD50
Sulfuric acid	= 2140 mg/kg (Rat)	-	85 - 103 mg/m ³ (Rat) 1 h	-
7664-93-9				

Information on toxicological effects

Symptoms Inhalation: Corrosive. Burning sensation. Sore throat. Cough. Labored breathing. Shortness

of breath. Symptoms may be delayed. Skin: Corrosive. Redness. Pain. Blisters. Serious

skin burns. Eyes: Corrosive. Redness. Pain. Severe deep burns.

Delayed and immediate effects as well as chronic effects from short- and long-term exposure

Skin Corrosion/Irritation Causes severe burns to skin.

Serious Eye Damage/Eye Irritation Corrosive to eyes.

Sensitization No data available.

Germ Cell Mutagenicity Sulfuric acid has been shown to be without effect in the Ames test using various strains of

S. typhimurium (pH 4 to 9) and E. coli (0.002 to 0.005%), both with and without S9. It has been shown to cause chromosomal aberrations in CHO cells (pH 3.5 to 7.4, both with and

without S9), and in a non-standard assay in developing sea urchin embryos.

Carcinogenicity The International Agency for Research on Cancer (IARC) has classified "strong inorganic

acid mist containing sulfuric acid" as a Category 1 carcinogen, a substance that is carcinogenic to humans. This classification does not apply to liquid forms of sulfuric acid or sulfuric acid solutions contained within a battery. Batteries subjected to abusive charging at excessively high currents for prolonged periods without vent caps in place may create a surrounding atmosphere of the offensive strong inorganic acid mist

containing sulfuric acid.

Chemical Name	ACGIH	IARC	NTP	OSHA
Sulfuric acid	A2	Group 1		X
7664-93-9		·		

Reproductive Toxicity In a developmental toxicity study conducted under a method similar to OECD test Guideline

414, no significant effects on mean numbers of implants/dam, live fetuses/litter or

resorptions/litter were observed in mice and rabbits exposed by inhalation to sulfuric acid

aerosol at 5 and 20 mg/cu m during gestation...

Developmental Toxicity No data available.

STOT - Single Exposure Not classified.

STOT - Repeated Exposure Not classified.

Aspiration Hazard Not applicable.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Ī	Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
	Sulfuric acid 7664-93-9		500: 96 h Brachydanio rerio mg/L LC50 static		29: 24 h Daphnia magna mg/L EC50

Persistence and degradability

Not available.

Bioaccumulation

Not available.

Mobility

Not available.

Other adverse effects

Not available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

US EPA Waste Number Not available.

California Hazardous Waste Codes Not available.

This product contains the following substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status	
Sulfuric acid	Toxic	
7664-93-9	Corrosive	

14. TRANSPORT INFORMATION

DOT

UN/ID No. UN2796

Proper shipping name Battery fluid, acid

Hazard Class 8
Subsidiary class 8
Packing Group ||

Special Provisions A3, A7, B2, B15, IB2, N6, N34, T8, TP2, 154

Passenger aircraft/rail: 1.00 L Cargo aircraft/rail: 30.00 L

TDG

UN/ID No. UN2796

Proper shipping name Battery fluid, acid

Hazard Class 8
Subsidiary class 8
Packing Group ||

Special Provisions

Explosive Limit and Limited Quantity Index: 1.00

Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index: 1.00

MEX Not regulated.

ICAO (air)

UN/ID No. UN2796

Proper shipping name Battery fluid, acid

Hazard Class 8
Packing Group || Special Provisions -

<u>IATA</u>

UN/ID No. UN2796

Proper shipping name Battery fluid, acid

Hazard Class 8
Packing Group || Special Provisions -

IMDG

UN/ID No. UN2796

Proper shipping name Battery fluid, acid

Hazard Class 8
Packing Group II
Special Provisions Marine pollutant No

RID .

UN/ID No. UN2796

Proper shipping name Battery fluid, acid

Hazard Class8Packing GroupIIClassification codeC1Special Provisions-Labels8

<u>ADR</u>

UN/ID No. UN2796

Proper shipping name Battery fluid, acid

Hazard Class 8
Packing Group II
Classification code C1
Special Provisions Labels 8

ADN Not regulated.

15. REGULATORY INFORMATION

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Sulfuric acid - 7664-93-9	7664-93-9	36-45	1.0

SARA 311/312 Hazard Categories

Acute Health HazardNoChronic Health HazardNoFire HazardNoSudden Release of Pressure HazardNoReactive HazardNo

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Sulfuric acid 7664-93-9	1000 lb			Χ

CERCLA

This material, as supplied, contains the following substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemic	al Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Sulfur 7664	c acid 93-9	1000 lb	1000 lb	RQ 1000 lb final RQ RQ 454 kg final RQ

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

Revision Date 04-Apr-2019

U.S. State Right-to-Know Regulations

This product may contain substances regulated by state right-to-know regulations.

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Sulfuric acid	X	X	X
7664-93-9			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable.

16. OTHER INFORMATION

Prepared By IES Engineers Issue Date 25-Nov-2014 Revision Date 04-Apr-2019

Revision Note Changes in Section 3 and 15

Disclaimer

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Yuasa, Inc. assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Yuasa, Inc. assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

End of Safety Data Sheet