HILLYARD The Cleaning Resource*

SAFETY DATA SHEET

1. Identification

Product identifier HTG CONCRETE SEAL PART A

Other means of identification

SDS number 568-177A

Product code HIL00500PARTA

Recommended use Concrete Floor Coating

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer Manufacturer

Company nameHILLYARD INDUSTRIESAddress302 North Fourth St.

St. Joseph, MO 64501

Contact person Regulatory Affairs

Telephone number (816) 233-1321 (Ext. 8285)

Fax (816) 383-8485

E-mail regulatoryaffairs@hillyard.com

Emergency telephone # (800) 424-9300

(Only in the event of chemical emergency involving a spill, leak, fire, exposure,

or accident involving chemicals.)

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Sensitization, skin

Not classified.

OSHA defined hazards Not classified.

Label elements

Environmental hazards



Signal word Warning

Hazard statement May cause an allergic skin reaction.

Precautionary statement

Prevention Wear protective gloves. Contaminated work clothing should not be allowed out of the workplace.

Use With Adequate Ventilation. Avoid breathing vapors or spray mist. Open windows and doors,

Category 1

use exhaust fans or other means to insure fresh air entry during application and drying.

Response If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. Wash contaminated clothing before reuse.

Storage Store away from incompatible materials.

Disposal Buyer assumes all risk and liability associated with disposal of this product (original concentration

or dilution) in violation of applicable law in compliance with applicable federal, state and local

requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-ph enyleneoxymethylene)]bis-,homopol ymer		25085-99-8	30 - < 40
Titanium dioxide		13463-67-7	20 - < 30
Other components below reportable leve	ls .		40 - < 50

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

IngestionRinse mouth. Get medical attention if symptoms occur.Most importantMay cause an allergic skin reaction. Dermatitis. Rash.

symptoms/effects, acute and delayed

Indication of immediate

medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

and precautions for firefighte Fire fighting

Move containers from fire area if you can do so without risk.

equipment/instructions
Specific methods
General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Value **Form** Components Type Titanium dioxide (CAS PEL 15 mg/m3 Total dust. 13463-67-7) **US. ACGIH Threshold Limit Values**

Components Value Type Titanium dioxide (CAS **TWA** 10 mg/m3 13463-67-7)

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Chemical splash goggles where there is a potential for eye contact. Eye/face protection

Skin protection

Wear appropriate chemical resistant gloves. **Hand protection**

Other Avoid contact with the skin. Normal work clothing (long sleeved shirts and long pants) is

recommended.

Not normally required with adequate ventilation. In case of insufficient ventilation, wear suitable Respiratory protection

respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

9. Physical and chemical properties

Gray liquid, mild odor **Appearance**

Liquid. **Physical state Form** Liquid. Gray Color Mild odor Odor Not available. Odor threshold

6 - 8

Melting point/freezing point Not applicable / Not available

Initial boiling point and boiling

range

212 °F (100 °C)

> 212.0 °F (> 100.0 °C) Tag Closed Cup Flash point

< 1 Ethyl ether = 1 Evaporation rate Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper (%) 2.3 mm Hq Vapor pressure $0.62 \, Air = 1$ Vapor density Relative density 1.367 at 77°F

Solubility(ies)

Solubility (water) 100 % Complete Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature

401 °F (205 °C) estimated

Decomposition temperature

Not available. Not available.

Other information

Viscosity

11.39 Density 43 - 45 % Percent volatile VOC (Weight %) < 160 g/l

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. Chemical stability

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful. May cause an allergic skin reaction. Skin contact

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity May cause an allergic skin reaction.

Prolonged skin contact may cause temporary irritation. Skin corrosion/irritation Direct contact with eyes may cause temporary irritation. Serious eye damage/eye

irritation

Respiratory or skin sensitization

Not a respiratory sensitizer. Respiratory sensitization

Skin sensitization May cause an allergic skin reaction.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Titanium Dioxide is listed as a class 2B (possibly carcingenic to humans) in powdered form. Carcinogenicity

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Not an aspiration hazard. **Aspiration hazard**

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product Species Test Results

HTG CONCRETE SEAL PART A

Aquatic

EC50 Daphnia 20520.8184 mg/l. 48 hours estimated Crustacea Fish LC50 Fish 20520.8184 mg/l, 96 hours estimated

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

> contents/container in accordance with local/regional/national/international regulations. Buyer assumes all risk and liability associated with disposal of this product (original concentration or

dilution) in violation of applicable law.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication US federal regulations

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Hazard categories**

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No. Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Nο

chemical

SARA 313 (TRI reporting)

Not regulated.

^{*} Estimates for product may be based on additional component data not shown.

Other federal regulations

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

US. Massachusetts RTK - Substance List

Not regulated.

US. New Jersey Worker and Community Right-to-Know Act

US. Pennsylvania Worker and Community Right-to-Know Law

Not listed.

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region Inventory name On inventory (yes/no)*

Yes

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

02-11-2015 Issue date

Version #

Health: 2 **HMIS®** ratings

> Flammability: 0 Physical hazard: 0

Disclaimer No representations or warranties, either express or implied, of merchantability, fitness for a

particular purpose, or of any nature are made with respect to the product(s) or information contained in this material safety data sheet. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. The buyer or user assumes all risks associated with the use, misuse or disposal of this product. The buyer or user is responsible to comply with all federal, state or local regulations concerning the use, misuse or

disposal of these products.

HIL00500PARTA Version #: 01 Issue date: 02-11-2015

HILLYARD The Cleaning Resource*

SAFETY DATA SHEET

1. Identification

Product identifier HTG CONCRETE SEAL

Other means of identification

SDS number 568-177B

Product code HIL00500PARTB
Recommended use Not available.
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer Manufacturer

Company nameHILLYARD INDUSTRIESAddress302 North Fourth St.

St. Joseph, MO 64501

Contact person Regulatory Affairs

Telephone number (816) 233-1321 (Ext. 8285)

Fax (816) 383-8485

E-mail regulatoryaffairs@hillyard.com

Emergency telephone # (800) 424-9300

(Only in the event of chemical emergency involving a spill, leak, fire, exposure,

or accident involving chemicals.)

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 1
Sensitization, skin Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage.

Precautionary statement

Prevention Avoid breathing mist or vapor. Wash thoroughly after handling. Contaminated work clothing must

not be allowed out of the workplace. Wear protective gloves. Wear eye/face protection.

Response If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated

clothing and wash before reuse.

Storage Store away from incompatible materials.

Disposal Buyer assumes all risk and liability associated with disposal of this product (original concentration

or dilution) in violation of applicable law in compliance with applicable federal, state and local

requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

Material name: HTG CONCRETE SEAL HIL00502PARTB Version #: 01 Issue date: 02-10-2015

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Tetraethylenepentamine		112-57-2	1 - < 3
Other components below reportable levels			90 - 100

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention immediately.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important

symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to **General information**

protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters During fire, gases hazardous to health may be formed.

Move containers from fire area if you can do so without risk. Fire fighting

equipment/instructions

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage Precautions for safe handling Do not get this material in contact with eyes. Avoid breathing mist or vapor. Avoid contact with

Material name: HTG CONCRETE SEAL

eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. AIHA Workplace Environmental Exposure Level (WEEL) Guides

ComponentsTypeValueFormTetraethylenepentamine
(CAS 112-57-2)TWA5 mg/m3Aerosol.1 ppmAerosol.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US WEEL Guides: Skin designation

Tetraethylenepentamine (CAS 112-57-2)

Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical splash goggles where there is a potential for eye contact.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Avoid contact with the skin. Wear suitable protective clothing.

Respiratory protection No personal respiratory protective equipment normally required. In case of insufficient ventilation,

wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance Yellow Liquid
Physical state Liquid.
Form Liquid.
Color Yellow
Odor Amine odor
Odor threshold Not available.
pH 9.5 - 10.5

Melting point/freezing point Not applicable / Not available

Initial boiling point and boiling 21

range

212 °F (100 °C)

Flash point > 212.0 °F (> 100.0 °C) Tag Closed Cup

Evaporation rate < 1 Ethyl ether = 1
Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 2.3 mm Hg

Vapor density 0.62 Air=1

Relative density 1.055 at 77°F

Solubility(ies)

Solubility (water) 100 % Complete

Material name: HTG CONCRETE SEAL

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

 Density
 8.78 lb/gal

 Percent volatile
 57 - 58 %

 VOC (Weight %)
 0 %

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye damage.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity May cause an allergic skin reaction.

Product	Species	Test Results
HTG CONCRETE SEAL		
Acute		
Dermal		
LD50	Rabbit	59.9673 g/kg estimated
Oral		
LD50	Rat	190.805 g/kg estimated

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

Causes serious eye damage.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Material name: HTG CONCRETE SEAL

Specific target organ toxicity -

single exposure

Not classified.

single exposure

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Tetraethylenepentamine 1.503

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations. Buyer assumes all risk and liability associated with disposal of this product (original concentration or dilution) in violation of applicable law.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

Material name: HTG CONCRETE SEAL SDS US

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

Tetraethylenepentamine (CAS 112-57-2)

US. New Jersey Worker and Community Right-to-Know Act

Tetraethylenepentamine (CAS 112-57-2)

US. Pennsylvania Worker and Community Right-to-Know Law

Tetraethylenepentamine (CAS 112-57-2)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

02-10-2015 Issue date

Version # 01

Health: 3 **HMIS®** ratings

> Flammability: 0 Physical hazard: 0

Disclaimer No representations or warranties, either express or implied, of merchantability, fitness for a

> particular purpose, or of any nature are made with respect to the product(s) or information contained in this material safety data sheet. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. The buyer or user assumes all risks associated with the use, misuse or disposal of this product. The buyer or user is responsible to comply with all federal, state or local regulations concerning the use, misuse or

disposal of these products.

HIL00502PARTB Version #: 01 Issue date: 02-10-2015

Material name: HTG CONCRETE SEAL