

MATERIAL SAFETY DATA SHEET

DATE: June 27, 1991

PRODUCT NAME: Dri-Matic Carpet Cleaning Compound

* Windsor Industries, Inc EMERGENCY INFORMATION *
* Englewood, CO 80110 MEDICAL (303) 762-1800 *

● SECTION 1: GENERAL INFORMATION ●

PRODUCT NAME: Dri-Matic Cleaner
PRODUCT CLASS: Cleaning Compound
PRECAUTIONS: Irritant. Do not get on skin or eyes.

● SECTION II: HAZARDOUS INGREDIENTS *

INGREDIENT	CAS #	%
Polyurethane	9009-54-5	25-40
Ethanol	64-17-5	5-15
Acrylate Dispersion with Anionic Tensid	9003-04-7	2-10

● SECTION III: PHYSICAL/CHEMICAL DATA *

BOILING POINT: N/A
% VOLATILE BY WEIGHT: 67.4%
EVAPORATION RATE: SLOWER TEAN PURE ETHYL ALCOHOL
VAPOR DENSITY: HEAVIER THAN AIR
VAPOR PRESSURE: <5 MM HG @ 70 DEG F
94 MM HG @ 100 DEG F
328 MM HG @ 137 DEG F
DENSITY: 15.6 LB/CU FT

MATERIAL SAFETY DATA SHEET

DATE: June 27, 1991

PAGE 2

PRODUCT NAME: Dri-Matic Carpet Cleaning Compound

* SECTION IV: FIRE AND EXPLOSION DATA *

FLASH POINT (TCC): NONE; DRY SOLID RESIDUE CAN BE IGNITED

EXTINGUISHING MEDIA : WATER, DRY OR CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES: RESPIRATORY PROTECTION TO
PROTECT AGAINST TOXIC FUMES

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE

* SECTION V: REACTIVITY DATA *

STABILITY: STABLE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

INCOMPATIBILITY (MATERIALS TO AVOID): STRONG OXIDIZERS

HAZARDOUS DECOMPOSITION PRODUCTS: WILL PRODUCE TOXIC
FUMES WHEN HEATED TO HIGH TEMPERATURES.

* SECTION VI: HEALTH HAZARD DATA *

EFFECTS OF OVEREXPOSURE/EMERGENCY AND FIRST AID PROCEDURES

EYES: CONTACT WITH EYES MAY BE IRRITATING
FLUSH EYES IMMEDIATELY WITH PLENTY OF WATER.

SKIN: PROLONGED OR REPEATED CONTACT WITH SKIN MAY CAUSE
IRRITATION. WASH OFF SKIN WITH WATER. REMOVE
CONTAMINATED CLOTHING AND CLEAN BEFORE REUSE.

INHALATION: MAY CAUSE DIZZINESS, DROWSINESS, HEADACHE,
NAUSEA AND VOMITING. IF VAPORS OR MIST
CAUSE IRRITATION OR DISTRESS, REMOVE TO
FRESH AIR.
GIVE OXYGEN OR APPLY ARTIFICIAL RESPIRATION
IF NEEDED.

INGESTION: IF SWALLOWED, CONSULT A PHYSICIAN IMMEDIATELY.
DO NOT INDUCE VOMITING.

MATERIAL SAFETY DATA SHEET

DATE: June 27, 1991

PAGE 3

PRODUCT NAME: Dri-Matic Carpet Cleaning Compound

CHRONIC EFFECTS AND MEDICAL CONDITIONS AGGRAVATED BY OVER-EXPOSURE:
CHRONIC EFFECTS AND MEDICAL CONDITIONS AGGRAVATED BY OVER-
EXPOSURE TO THIS PRODUCT HAVE NOT BEEN ESTABLISHED.
UNNECESSARY EXPOSURE TO THIS PRODUCT /OR ANY CHEMICAL SHOULD
BE AVOIDED.

IF ANY SYMPTOMS PERSIST, CONSULT A PHYSICIAN.

CARCINOGEN: THIS PRODUCT IS NOT CONSIDERED A CARCINOGEN BY
OSHA, NTP, OR IARC.

* SECTION VII: SPILL, LEAK, AND DISPOSAL PROCEDURES *

VENTILATE AREA. SWEEP UP ALL SPILLS.

SMALL SPILLS: SHOVEL INTO WASTE CONTAINER, FLUSH AREA WITH WATER.

LARGE SPILLS: RECOVER MATERIAL FOR REPROCESSING OR DISPOSAL.

WASTE DISPOSAL: DISPOSE IN ACCORDANCE WITH ALL APPLICABLE STATE,
LOCAL, AND FEDERAL REGULATIONS. MATERIAL SHOULD
BE DISPOSED IN A PERMITTED LANDFILL IN ACCORDANCE
WITH STATE, LOCAL, AND FEDERAL REGULATIONS.
EMPTY CONTAINER MAY RETAIN VAPOR OR PRODUCT RESIDUE.
OBSERVE ALL LABELED SAFEGUARDS UNTIL CONTAINER IS
CLEANED, RECONDITIONED, OR DESTROYED.

MATERIAL SAFETY DATA SHEET

DATE: June 27, 1991

PAGE 4

PRODUCT NAME: Dri-Matic Carpet Cleaning Compound

* SECTION VIII: PROTECTIVE MEASURES *

EYE PROTECTION: WEAR GOGGLES OR OTHER EYE PROTECTION WHEN HANDLING.

PROTECTIVE GLOVES: USE IMPERVIOUS GLOVES AND CLOTHING TO PREVENT SKIN CONTACT

RESPIRATORY PROTECTION:

IF VAPORS ARE PRESENT, USE NIOSH OR MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS, AIR LINE RESPIRATOR, OR A SELF-CONTAINED BREATHING APPARATUS.

VENTILATION:

USE VENTILATION ADEQUATE TO KEEP ETHANOL VAPOR BELOW ITS TLV (SEE SECTION 11)

OTHER PROTECTIVE EQUIPMENT:

WEAR PROTECTIVE CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT. REMOVE CONTAMINATED CLOTHING IMMEDIATELY.

EYE WASH STATION AND SAFETY SHOWER SHOULD BE NEAR WORK AREA.

● SECTION IX: SPECIAL PRECAUTIONS *

OTHER PRECAUTIONS:

WASH THOROUGHLY AFTER HANDLING.
IF INGESTED, CALL A PHYSICIAN.