



# SAFETY DATA SHEET

## 1. Identification

**Product number** 1000011192  
**Product identifier** **Heavy Duty Foaming Oven Cleaner**  
**Company information** Claire Manufacturing Co.  
1005 S. Westgate Drive  
Addison, IL 60101 United States  
**Company phone** General Assistance 1-630-543-7600  
**Emergency telephone US** 1-866-836-8855  
**Emergency telephone outside US** 1-952-852-4646  
**Version #** 01  
**Recommended use** Cleaner  
**Recommended restrictions** None known.

## 2. Hazard(s) identification

**Physical hazards** Flammable aerosols Category 1  
**Health hazards** Skin corrosion/irritation Category 1  
Serious eye damage/eye irritation Category 1  
**Environmental hazards** Not classified.  
**OSHA defined hazards** Not classified.

### Label elements



**Signal word** Danger

**Hazard statement** Extremely flammable aerosol. Causes severe skin burns and eye damage. Causes serious eye damage.

### Precautionary statement

#### Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

#### Response

If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment (see this label). Wash contaminated clothing before reuse.

#### Storage

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

#### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)** The Safety Information Sheet Chemicals of hazardous chemical can be obtained through phone, email or on the company website.

**Supplemental information** None.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	2.5 - 10
Diethylene Glycol Monobutyl Ether		112-34-5	2.5 - 10

Chemical name	Common name and synonyms	CAS number	%
Sodium Hydroxide		1310-73-2	2.5 - 10
Propane		74-98-6	1 - 2.5
Other components below reportable levels			80 - 90

#: This substance has workplace exposure limit(s).

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First-aid measures

<b>Inhalation</b>	Move to fresh air. Call a physician if symptoms develop or persist.
<b>Skin contact</b>	Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash clothing separately before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
<b>Most important symptoms/effects, acute and delayed</b>	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

## 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Fire-fighting equipment/instructions</b>	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
<b>General fire hazards</b>	Extremely flammable aerosol.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

### Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid contact with skin, eyes and clothing. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

### Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS). Level 1 Aerosol (NFPA 30B)

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm
Sodium Hydroxide (CAS 1310-73-2)	PEL	2 mg/m3

#### US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Butane (CAS 106-97-8)	STEL	1000 ppm	
Diethylene Glycol Monobutyl Ether (CAS 112-34-5)	TWA	10 ppm	Inhalable fraction and vapor.
Sodium Hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3	

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm
Sodium Hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3

### Biological limit values

No biological exposure limits noted for the ingredient(s).

### Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Wear safety glasses with side shields (or goggles) and a face shield. Do not get in eyes. Eye wash fountain is recommended.

#### Hand protection

Wear appropriate chemical resistant gloves.

#### Skin protection

#### Other

Wear appropriate chemical resistant clothing.

#### Respiratory protection

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

#### Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties****Appearance**

**Physical state** Gas.

**Form** Aerosol.

**Color** Colorless.

**Odor** Characteristic.

**Odor threshold** Not available.

**pH** 13 - 14

**Melting point/freezing point** Not available.

**Initial boiling point and boiling range** 212 °F (100 °C) estimated

**Flash point** -156.0 °F (-104.4 °C) Propellant estimated

**Evaporation rate** Not available.

**Flammability (solid, gas)** Not available.

**Upper/lower flammability or explosive limits**

**Flammability limit - lower (%)** Not available.

**Flammability limit - upper (%)** Not available.

**Explosive limit - lower (%)** Not available.

**Explosive limit - upper (%)** Not available.

**Vapor pressure** 27.3 psig @70F estimated

**Vapor density** Not available.

**Relative density** Not available.

**Solubility(ies)**

**Solubility (water)** Not available.

**Partition coefficient (n-octanol/water)** Not available.

**Auto-ignition temperature** Not available.

**Decomposition temperature** Not available.

**Viscosity** Not available.

**Other information**

**Specific gravity** 0.664 estimated

**10. Stability and reactivity**

**Reactivity** Reacts violently with strong acids. This product may react with oxidizing agents.

**Chemical stability** Material is stable under normal conditions.

**Possibility of hazardous reactions** No dangerous reaction known under conditions of normal use. Hazardous polymerization does not occur.

**Conditions to avoid** Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Do not mix with other chemicals. Contact with incompatible materials. Fire or intense heat may cause violent rupture of packages.

**Incompatible materials** Acids. Strong oxidizing agents. Oxidizing agents.

**Hazardous decomposition products** No hazardous decomposition products are known.

**11. Toxicological information****Information on likely routes of exposure**

**Ingestion** Causes digestive tract burns. Ingestion may cause severe irritation of the mouth, the esophagus and the gastrointestinal tract.

<b>Inhalation</b>	May cause irritation to the respiratory system. Prolonged inhalation may be harmful.
<b>Skin contact</b>	Causes severe skin burns.
<b>Eye contact</b>	Causes serious eye damage.
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Causes severe eye damage.

#### Information on toxicological effects

**Acute toxicity** Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Product	Species	Test Results
---------	---------	--------------

Heavy Duty Foaming Oven Cleaner (CAS Mixture)

#### Acute

##### Dermal

LD50	Rat	15720 mg/kg
------	-----	-------------

##### Inhalation

LC50	Rat	3940 mg/l/4h
------	-----	--------------

Components	Species	Test Results
------------	---------	--------------

Butane (CAS 106-97-8)

#### Acute

##### Inhalation

LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l

Diethylene Glycol Monobutyl Ether (CAS 112-34-5)

#### Acute

##### Dermal

LD50	Guinea pig	2 ml/kg, 2 Days
	Rabbit	2764 mg/kg, 24 Hours

##### Oral

LD100	Rabbit	4000 mg/kg
LD50	Guinea pig	2000 mg/kg
	Mouse	2410 mg/kg
	Rabbit	2500 - 3000 mg/kg
	Rat	3306 mg/kg

Propane (CAS 74-98-6)

#### Acute

##### Inhalation

LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l 658 mg/l/4h

Sodium Hydroxide (CAS 1310-73-2)

#### Acute

##### Dermal

LD50	Rat	1350 mg/kg
------	-----	------------

\* Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Causes severe skin burns and eye damage.

**Serious eye damage/eye irritation** Causes serious eye damage.

#### Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>	
Not listed.	
<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.
<b>Specific target organ toxicity - single exposure</b>	Not classified.
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.
<b>Aspiration hazard</b>	Not an aspiration hazard. Not likely, due to the form of the product.
<b>Chronic effects</b>	Prolonged inhalation may be harmful.

## 12. Ecological information

<b>Ecotoxicity</b>	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
--------------------	--

Product	Species		Test Results
Heavy Duty Foaming Oven Cleaner (CAS Mixture)			
Aquatic			
Algae	IC50	Algae	1481 mg/L, 72 Hours
Crustacea	EC50	Daphnia	48 Hours
Fish	LC50	Fish	631 mg/L, 96 Hours
Components	Species		Test Results
Diethylene Glycol Monobutyl Ether (CAS 112-34-5)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	1300 mg/l, 96 hours
Sodium Hydroxide (CAS 1310-73-2)			
Aquatic			
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	34.59 - 47.13 mg/l, 48 hours
Fish	LC50	Fish	45, 96 Hours

\* Estimates for product may be based on additional component data not shown.

<b>Persistence and degradability</b>	No data is available on the degradability of this product.
--------------------------------------	--

<b>Bioaccumulative potential</b>	No data available.
----------------------------------	--------------------

### Partition coefficient n-octanol / water (log Kow)

Butane	2.89
Diethylene Glycol Monobutyl Ether	0.56
Propane	2.36

<b>Mobility in soil</b>	No data available.
-------------------------	--------------------

<b>Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.
------------------------------	---

## 13. Disposal considerations

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

**14. Transport information****DOT**

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	8
<b>Label(s)</b>	2.1, 8
<b>Packing group</b>	Not applicable.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	153, N82
<b>Packaging exceptions</b>	LTD QTY
<b>Packaging non bulk</b>	None
<b>Packaging bulk</b>	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

**IATA**

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable, containing substances in Class 8, Packing Group III
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	8
<b>Label(s)</b>	2.1, 8
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	No.
<b>ERG Code</b>	10C
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Allowed.
<b>Cargo aircraft only</b>	Allowed.
<b>Packaging Exceptions</b>	LTD QTY

**IMDG**

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	AEROSOLS
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	8
<b>Label(s)</b>	2.1, 8
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	No.
<b>EmS</b>	F-D, S-U
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
<b>Packaging Exceptions</b>	LTD QTY

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

DOT



IATA; IMDG



## 15. Regulatory information

### US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
All components are on the U.S. EPA TSCA Inventory List.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

Sodium Hydroxide (CAS 1310-73-2) Listed.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### Hazard categories

Immediate Hazard - Yes  
Delayed Hazard - No  
Fire Hazard - Yes  
Pressure Hazard - No  
Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

#### SARA 311/312 Hazardous chemical

No

#### SARA 313 (TRI reporting)

Not regulated.

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

#### Safe Drinking Water Act (SDWA)

Not regulated.

### US state regulations

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

#### US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)



Sodium Hydroxide (CAS 1310-73-2)

**US. New Jersey Worker and Community Right-to-Know Act**

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Sodium Hydroxide (CAS 1310-73-2)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Sodium Hydroxide (CAS 1310-73-2)

**US. Rhode Island RTK**

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Sodium Hydroxide (CAS 1310-73-2)

**US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other information, including date of preparation or last revision**

**Issue date** 01-15-2015

**Version #** 01

**References** EPA: AQUIRE database  
NLM: Hazardous Substances Data Base  
US. IARC Monographs on Occupational Exposures to Chemical Agents

**Disclaimer** We cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.