MATERIAL SAFETY DATA SHEET

NFPA RATING: Health = 3 Flammability = 0 Reactivity = 0 **HMIS RATING:** Health = 3 Flammability = 0 Physical Hazard = 0

SECTION I – IDENTITY AND MANUFACTURER'S INFORMATION *(566N-24A)

Distributor:Capital Supply CompanyProduct Name:HI-LITE SUPER MOV-IT IIAddress:620 12th AvenueDate Prepared:January 16, 2012 (version 3)New York, NY 10036-1004Prepared by:Regulatory Affairs Department

Emergency Telephone No.: (800)-424-9300 (Only in the event of chemical emergency involving a spill, leak, fire, exposure or

accident involving chemicals.) Other information calls: (816) 233-1321 (Ext. 8285)

*SECTION II - INGREDIENTS/IDENTITY INFORMATION

(Specific Chemical Identity:	CAS#	OSHA PEL	ACGIH TLV	OTHER LIMITS	%
Common Name(s)				RECOMMENDED	
Water	7732-18-5	None	None	N/A	
Sodium metasilicate (1)	6834-92-0	N/E	N/E	2 mg/M^3	5-10
Ethanolamine (2)	141-43-5	3 ppm	3 ppm	N/A	3-5
Benzyl alcohol (3)	100-51-6	N/E	N/E	N/A	
*Sulfonated OleicAcid Sodium Salt	68443-05-0	None	None	N/A	

- (1) Exposure may be elevated as ceiling for Sodium hydroxide per OSHA: $PEL = 2mg./M^3$ or $TLV = 2mg.M^3$
- (2) Regulated by OSHA, and the following states: CA, CT, FL, ID, IL, LA, MA, ME, MN, NJ, PA, RI, WA, WI.
- (3) Regulated by FL, MA, PA.
- *VOC (concentrate) = 6.00%; VOC (Min. Dilution 1:4) = 1.20%

N/A= Not Applicable N/E= Not Established

*SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

*Boiling Point: corr. 205° F Specific Gravity ($H_2O = 1$): 25° C = 1.06 *Density = 8.82 lbs/gl

Vapor Pressure (mm Hg.): 17.2 *Percent Volatile by Weight (%): 90.5 – 91.5 **Vapor Density (AIR = 1):** 0.8 *Evaporation Rate (ethyl ether = 1): slower than 1

Solubility in Water: complete Appearance and Odor: clear amber liquid; non-objectionable odor

pH (concentrate) = 12.5 - 13.5

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash point: None (Tag Closed Cup) Flammable Limits: LEL = N/A UEL = N/A

Extinguishing Media: Water, carbon dioxide, dry chemical or foam.

Special Fire Fighting Procedures: Normal fire fighting procedures may be used. Cool and cautiously approach or handle

fire-exposed containers.

Unusual Fire and Explosion Hazards: N/A

SECTION V - PHYSICAL HAZARDS

Stability: Stable Conditions to Avoid: N/A

Incompatibility (Materials to Avoid): Oxidizing materials and strong acids.

Hazardous Decomposition Products or Byproducts: Produces normal products of combustion when exposed to fire.

Hazardous Polymerization: Will not occur Conditions to Avoid: None known

SECTION VI - HEALTH HAZARD DATA

Routes of entry: Inhalation? Yes Skin? Yes Ingestion? Yes

HEALTH HAZARDS (1. Acute and 2. Chronic)

- 1. Direct contact with concentrate in eyes can cause severe irritation and damage.
- 2. Prolonged and repeated exposure to skin may produce irritation or damage. Inhalation of spray mist may result in varying degrees of irritation.

Chemical listed as Carcinogen or Potential Carcinogen:

National Toxicology Program = No I.A.R.C. Monographs = No OSHA = No

This product has no carcinogens listed by IARC, NTP, NIOSH, or ACGIH as of this date, greater than or equal to 0.1%.

SECTION VI - HEALTH HAZARD DATA cont.

Signs and Symptoms of Exposure: Concentrated product may produce skin and eye burns. Ingestion may produce burns of the mouth throat, esophagus and stomach.

Date: January 16, 2011

Medical Conditions Generally Aggravated by Exposure: Skin problems such as industrial dermatitis.

Emergency and First Aid Procedures: Eyes: In case of contact immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses and again flush eyes with water. GET MEDICAL ATTENTION. Skin: Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing and thoroughly clean contaminated shoes before reuse. Ingestion: If swallowed do not induce vomiting; immediately give large amounts of water and CALL A PHYSICIAN, hospital emergency room or poison control center. Inhalation: Remove victim to fresh air; if respiratory tract remains irritated, call a physician.

SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken In Case Material Is Released Or Spilled: Absorb with floor dry or similar inert material. Sweep or scrape up and put in appropriate container. Rinse spill area thoroughly with water. Use appropriate protective equipment.

Waste Disposal Method: Disposal is regulated by the Resource Conservation and Recovery Act; concentrate is corrosive per EPA Hazardous Waste Classification. Disposal of regulated quantities should be neutralized at a permitted facility in accordance with all federal, state and local requirements.

Precautions To Be Taken In Handling And Storing: Keep container closed when not in use. Container disposal: Triple rinse (or equivalent), then offer clean, dry container for recycling or reconditioning. Waste from normal use may be sewered to publicowned treatment works in compliance wit applicable federal, state and local requirements.

Other Precautions: Do not use with fog mist or fine droplet sprayer without respiratory protection. This product contains no reportable quantities of toxic chemicals subject to the reporting requirements of Section 313 of SARA Title III Emergency Planning and Community Right to Know Act of 1986 and 40 CFR Part 372.

SECTION VIII – CONTROL MEASURES

Respiratory Protection (Specify Type): Ventilate to keep air concentration below TLV on ethanolamine or metasilicate.

Ventilation:

Local Exhaust = Recommended Mechanical (General) = Recommended Special = N/A Other = N/A

Protective Gloves: Impervious gloves when working with concentrate **Eye Protection:** Chemical safety goggles when working with concentrate

Other Protective Clothing or Equipment: Impervious to water and alkaline liquid where concentrate is a concern.

Work / Hygienic Practices: Wash thoroughly after handling.

*SECTION IX - TRANSPORTATION INFORMATION:

Applicable Regulations: DOT = $\underline{\text{Yes}}$; $\underline{\text{IMCO}} = \underline{\text{No}}$; $\underline{\text{IATA}} = \underline{\text{No}}$

Proper shipping name: Corrosive Liquids, N.O.S., (Sodium Metasilicate),

UN No.: 1760 Limited Qty.: not applicable DOT Exception: not applicable

Package Label = Corrosive Hazard Class = 8 Package Group = II

EPA Hazardous waste/number code: not listed

Hazardous waste characteristics:

Ignitability = not applicable; **Corrosivity** = yes; **Reactivity** = not applicable

DISCLAIMER OF WARRANTIES

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY NATURE ARE MADE WITH RESPECT TO THE PRODUCT(S) OR INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET.

The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate.

THE BUYER OR USER ASSUMES ALL RISKS ASSOCIATED WITH THE USE, MISUSE OR DISPOSAL OF THIS PRODUCT. THE BUYER OR USER IS RESPONSIBLE TO COMPLY WITH ALL FEDERAL, STATE OR LOCAL REGULATIONS CONCERNING THE USE, MISUSE OR DISPOSAL OF THESE PRODUCTS.

Version 3, * Denotes revisions since last published MSDS. Supersedes Version 2 July 12, 2011