

DATE REVISED: Feb 14, 2019

Page: 1 of 6

SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: VAN SON UV TKP-LED COLORS

Product Codes: TKPLEDXXXX General Use: Printing inks

Product Description: A mixture of pigments in multifunctional acrylate vehicle.

MANUFACTURER: T&K TOKA Co., Ltd.

ADDRESS: No.283-1, Chikumazawa, Miyoshi-machi, Irumagun Saitama 354-8577, Japan

GENERAL INFORMATION: Telephone 631-715-7000

EMERGENCY TELEPHONE NUMBERS: Telephone 631-715-7000 8:30-17:30

NORTH AMERICAN OFFICE: 490 Wheeler Road, Hauppauge, NY 11788

-

2. HAZARDS IDENTIFICATION

UN Hazard Classification:

HAZARD CLASS: Not Applicable UN/NA NUMBER: Not Applicable

GUIDE NUMBER: 171
EU DSD* Classification:
Xn; R52/53

GHS Classification [EU CLP Classification**]:

Physical Flammable Liquid - Not classified Health Acute Toxicity (oral)) - Not classfied

Acute Toxicity (dermal) - Not classified Acute Toxicity (inhalation) - Not classified Serious eye damage/eye irritation - Category 2A

Skin Corrosion/Irritation - Category 2

Skin Sensitization - Category 1

Respiratory sensitizer - Not classified

Mutagenicity - Not classified Carcinogenicity - Not classified

Reproductive Toxicity - Category 2

Target Organ Toxicity (following single exposure) - Not classified Target Organ Toxicity (following repeated exposure) - Not classified

Environmental

Aquatic Toxicity (acute) - Category 3 Aquatic Toxicity (chronic) - Category 3

GHS Label

Symbols Pictgram code





Signal word Warning

^{*}DSD(<u>D</u>angerous <u>S</u>ubstances <u>D</u>irective) based on current EU (directives 67/548/EEC, and

^{**}Classified based on the EU CLP regulation (Regulation on Classification, Labelling and Packaging of substances and mixtures) [REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008].

Lozond	Ctatamaamta
Hazaro	Statements

Hazard Code

Causes skin irritation.

May cause allergic skin reaction.

Causes serious eye irritation.

May cause damaging fertility or the unborn child.

Prevention Code

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Do not get in eyes, on skin, or on clothing.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

Other Precautionary Statements

Specific treatment (see PREVENTION on this sheet).

Take off contaminated clothing and wash before reuse.

Wash contaminated clothing before reuse.

Collect spillage.

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Store locked up.

Dispose of contents/container to Federal, State and local regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances presenting a health or environmental hazard within the meaning of Directive 67/548/EEC, Regulation (EC) No 1272/2008 of The European Parliament and of The Council of 16 December 2008.

COMPOSITION		CONTENT	upper -EU DSD (Risk) Classification(
	CAS#	wt%	lower -EU CLP Classification		
Photosensitive resin	Trade secret	5-15			
Acrylic ester monomer	Mixture	40-60			
Photo initiator A	71868-10-5	1-10	Xn, N R: 22-51/53		
(2-Methyl-1-(4-			Acute Tox. 4, Aquatic, Chronic 2		
methylthiophenyl)-2-			GHS07, GHS09, Wng		
morpholinopropan-1-one)			H302, H411		
Photo initiator	Trade secret	1-10			
Additives	Mixture	1-10			
Carbon black	1333-86-4	0-20			
Titanium dioxide	13463-67-7	0-50			
Pigments	Various	0-20			
Additives	Mixture	1-10			

^(*) For full text of Products R-phrases see section 15

4. FIRST AID MEASURES

EYE CONTACT: Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

SKIN CONTACT: If feels itching or burning of the skin, remove contaminated clothing. Immediately wash skin thoroughly with mild soap and plenty of water. Get immediate medical attention. Wash contaminated clothing before reuse.

Inhalation: Remove person to fresh air. If respiratory irritation, headache, dizziness, nausea, vomiting, breathing difficulty or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, give artificial respiration.

INGESTION: If swallowed, do not induce vomiting unless directed by medical personnel. Get immediate medical attention.

5. FIRE-FIGHTING MEASURES

Suitable Extinguish Media: Use dry chemical powder, carbon dioxide, or foam to extinguish fire.

Extinguishing media which must not be used: Extinguishers with water.

Special Fire Fighting Procedures: Exposed firefighters must wear proper protective equipment and positive pressure self-contained breathing apparatus with full face mask. Move containers from fire area if it can be done without risk. Do not enter fire area without proper protection. Fight fire from safe distance/protected location. Water should be used to cool fire-exposed containers, structures and to protect personnel. Do not flush down sewer or other drainage systems.

HAZARDOUS DECONPOSITION PRODUCTS: Products of combustion are hazardous including carbon monoxide and Carbon dioxide.

6. ACCIDENTAL RELEASE MEASURES

GENERAL: Avoid skin contact and breathing vapor. Consult an expert on the disposal of recovered material. Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind; keep out of low areas. (Also see Section 8).

LAND SPILL: Vapor protective clothing should be worn for spills and leaks. Shut off ignition sources; no flares, smoking or flames in hazard area. Prevent additional discharge of product, if possible to do so without hazard. Small spills: Take up with sand or other noncombustible absorbent material and place into containers for later disposal. Large spills: Dike far ahead of

WATER SPILL: Remove from surface by skimming or with suitable absorbents. Do not flush to sewer or waterways. Prevent release to the environment if possible.

7. HANDLING AND STORAGE

Handling

Avoid contact with eyes. Avoid prolonged repeated skin contact and breathing mists/vapours. Keep container closed. Use in well-ventilated area away from all ignition sources. Use good personal hygiene practices.

Wash hands before eating, drinking, smoking. Remove contaminated clothing and clean before re-use.

Keep away from heat and flame. Keep operating temperatures below ignition temperatures at all times. Use nonsparking tools.

Storage

SPECIAL SENSITIVITY: Heat. Direct rays of the sun.

Risk of possibly rupturing container by fire, high heat sources, raising temperature.

Store in tightly closed containers in cool, dry, well-ventilated area away from heat, sources of ignition and incompatibles. Ground lines and equipment used during transfer to reduce the possibility of static spark-initiated fire or explosion. Store at ambient or lower temperature. Store out of direct sunlight. Protect against physical damage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Substance	OSHA		ACGIH	
	TWA	STEL	TWA	STEL
Carbon black	3.5mg/m3	n/e	3.5mg/m3	n/e
Titanium dioxide	15mg/m3	n/e	10mg/m3	n/e

Product Name: VAN SON UV TKP-LED COLORS Page: 4 of 6

OSHA Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200) : These substances are considered hazardous ingredients (List on "Table Z-1")

ACGIH: Carbon black TLV; 3.5mg/m3 as TWA & A4 (not classifiable as a human carcinogen)[ACGIH2004]. Titanium Dioxide TLV; as TWA 10mg/m3 A4 (not classifiable as a human carcinogen)[ACGIH2001].

Engineering Controls

VENTILATION: Local exhaust ventilation may be necessary to contorol air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source. Provide mechanical ventilation for confined spaces. Use explosion-proof ventilation equipment

PERSONAL PROTECTIVE EQUIPMENT (PPE)

Wear chemical safety splash-proof goggles for eye protection and face shield. Avoid skin contact. Wear impervious gloves for skin protection. Use NIOSH approved respirators when necessary.

9. PHYSICAL and CHEMICAL PROPERTIES

APPEARANCE : Paste VAPOR PRESSURE : No Data Available

COLOR: Various colors VAPOR DENSITY (AIR=1): No Data Available

ODOR: Mild MOLECULAR FORMULA: Mixture FLASH POINT: >170°C/338°F MOLECULAR WEIHGT: Mixture

BOILING POINT: Not Applicable SPECIFIC GRAVITY: 1.1-1.5 at 25°C/77°F MELTING POINT: Not Applicable SOLUBILITY IN WATER: May Partly Soluble

AUTO IGNITION TEMPERATURE: No Data Available

10. STABILITY AND REACTIVITY

The material is stable in normal use and stocking conditions. It can release carbon oxides and vapours that can be harmful to health if taken to hot temperatures or in case of fire.

Condition to avoid: Avoid open flames, welding arcs, or other high temperature sources which include thermal decomposition.

Incompatibles: Oxidizing agents, and strong Alkaline.

Hazardous Rractions/Decomposition Products: Reacts with strong oxidizing agents. Thermal decomposition products may include oxides of carbon and nitrogen, or sulfur.

11. TOXICOLOGICAL INFORMATION

Corrosive and Irritant Properties

Photoinitiator A Oral LD50(rat) 1984 mg/kg

Dermal LD(rabbit) > 2000 mg/kg Ames test : Negative

GHS Information Photoinitiator A

Acute Tox. 4 Acute Toxicity (oral)) - Category 4

Evaluation of Carcinogenicity are not applicable by IARC, EPA, EU, and NTP.

12. ECOLOGICAL INFORMATION

Aquatic toxicity Information

Photoinitiator A Brachydanio rerio (Fish) LC50 : 9 mg/L (OECD)

Large Daphnia EC50: 15.3 mg/L (OECD)

A growth obstruction to the algae EC50: 1.7 mg/L

Residual property/Rapid degradability: The difficulty resolution, BOD 0%

HPLC (28days), An average of 1.3%

GHS Information Photoinitiator A

Aquatic Chronic 2 Aquatic Toxicity (chronic) -Category 2

13. DI SPOSAL CONSIDERATIONS

Dispose of in accordance with Federal, State and local regulations.

Empty containers must be handled with care due to product residue.

14. TRANSPORT INFORMATION

U.S. Department of Transportation (DOT) Proper SHIPPING NAME: Not applicable

HAZARD CLASS: Not applicable UN/NA NO: Not applicable Packing Group: Not applicable Label Codes: Not applicable Labels Required: Not applicable

The following description is transport in accordance with ADR for road, RID for rail, IMDG for sea and ICAO for air transport.

ADR/RID/IMDG/ICAO/IATA Class: Not applicable

UN Number : Not applicable

Proper SHIPPING NAME: Not applicable

Label: Not applicable

Packing group: Not applicable

15. REGULATORY INFORMATION

(1). U.S. Federal Regulations

Toxic Substances Control Act (TSCA) information

All components of this product are included on the 8(b)TSCA Inventory list.

Superfund Amendments and Reauthorization Act (SARA) Title II Information These products contains none of the substances subject to reporting requirements of SARA section 313 (40 CFR 372)

Component CAS Number Maximum %

- -

National Fire Protection Assotiation (NFPA) Ratings: This information is intended solely for the use of individuals trained in the NFPA system.



(2). EU Regulations

European Inventry of Existing Chemicals (EINECS): All of the components of this product are included on EINECS.

The following information is based on current EU (directives 67/548/EEC - 28th update [2001/59/EC], 1999/45/EC and 2001/58/EC).

EU Classification

Designation according to EC guidelines in label:

[EU Classification] Xi; Xn, R: 52/53 S: 7-9-16-24/25-26-28-29-33-36/37-61-62

Code letter and hazard designation of product: Xi (Irritant) Xn (Harmful)

Symbol

Risk (R) Phrases: R52/53 Harmul to aquatic organisms, may cause long-term adverse sffects in the aquatic environment.

Product Name: VAN SON UV TKP-LED COLORS Page: 6 of 6

Safety (S) Phrases:

S7 Keep container tightly closed.

S9 Keep container in a well-ventilated place.

S16 Keep away from sources of ignition-No smoking.

S24/25 Avoid contact with eyes and skin.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek madical advice.

S28 After contact with skin, wash immediately with plenty of water and seek medical advice.

S29 Do not empty into drains.

S36/37 Wear suitable protective clothing and gloves.

S61 Avoid release to the environment. Refer to special instructions/Safety data sheet

S62 If swallowed, do not induce vomitting: seek medical advice immediately and show this container or label

Contains: Photo initiator A

Follow all regulations in your country.

16. OTHER INFORMATION

Revision Indicator: 04

To the best of our knowledge, the information contained herein is accurate. However, neither T&K TOKA Co., LTD. Nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot garantee that these are the only hazards which exist.