

SAFETY DATA SHEET

Page 1 of 4

1. IDENTIFICATION

PRODUCT NAME: MICROTECH OXYGEN BLEACH

ALSO KNOWN AS: OXYGEN BLEACH

RECOMMENDED USE: LAUNDRY OXYGEN BLEACH

RESTRICTIONS ON USE: DO NOT USE IN A MANNER INCONSISTENT WITH THE LABEL.

LABEL BRAND: MICROTECH

SDS 100993K CODE 5336321, 101105575

USCHEMICAL 316 HART STREET WATERTOWN, WI 53094 USA

MEDICAL EMERGENCY: 1-866-923-4913 USA SPILL EMERGENCY: 1-800-424-9300 USA

PRODUCT INFORMATION: 1-800-558-9566 USA (8 A.M. TO 5 P.M. CST MONDAY TO FRIDAY)

INTERNET ADDRESS: www.uschemical.com

2. HAZARD(S) IDENTIFICATION

CLASSIFICATION: OXIDIZING LIQUIDS (CATEGORY 2).

SKIN CORROSION (CATEGORY 1B), EYE DAMAGE (CATEGORY 1),

ACUTE TOXICITY: ORAL (CATEGORY 4), STOT SINGLE EXPOSURE (CATEGORY 3)



SIGNAL WORD: DANGER

PICTOGRAMS: FLAME OVER CIRCLE, CORROSION, EXCLAMATION MARK HAZARD STATEMENTS: MAY INTENSIFY FIRE; OXIDIZER. CAUSES SEVERE SKIN BURNS AND SERIOUS EYE DAMAGE. HARMFUL IF SWALLOWED. MAY CAUSE RESPIRATORY IRRITATION.

PRECAUTIONARY STATEMENTS: Wear chemical-splash safety goggles, chemical-resistant protective gloves and protective footwear. Avoid contact with eyes, skin and clothing. Do not breathe vapors or mists. Use only in a well-ventilated area. Do not eat, drink, or smoke when using this product. Wash hands and affected areas thoroughly after handling. Keep away from heat. Keep away from clothing and other combustible materials. Take any precaution to avoid mixing with combustibles. Mix only with water. Do not mix with ammonia, bleach or other chemicals. Can react to release hazardous gases.

FIRST AID: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. **IF ON SKIN (OR HAIR):** Take off immediately all contaminated clothing. Rinse skin with water for at least 15 minutes. Wash contaminated clothing before reuse. **IF SWALLOWED:** Rinse mouth. Call a Poison Center or physician if you feel unwell. **Do not** induce vomiting. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing.

START FIRST AID. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

EMERGENCY TELEPHONE: 1-866-923-4913

Storage: Store tightly closed only in original corrosive-resistant plastic container. Store locked up.

Disposal: Dispose of contents in accordance with all federal, state and local applicable laws and regulations.

KEEP OUT OF REACH OF CHILDREN. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

HAZARDS NOT OTHERWISE CLASSIFIED: Not applicable.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| HAZARDOUS INGREDIENT(S) | CAS# | WEIGHT % |
|---|-----------|----------|
| HYDROGEN PEROXIDE | 7722-84-1 | 35.0 |
| STATE RIGHT TO KNOW: SEE SECTION 15 FOR STATE RTK CHEMICAL NAMES IN MIXTURE. | | |
| INGREDIENT DISCLOSURE: FOR MORE INGREDIENT INFORMATION VISIT www.uschemical.com | | |

4. FIRST-AID MEASURES

Page 2 of 4

IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING FOR AT LEAST 15 MINUTES. IF ON SKIN (OR HAIR): TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER FOR AT LEAST 15 MINUTES. WASH CONTAMINATED CLOTHING BEFORE REUSE. IF SWALLOWED: RINSE MOUTH. CALL A POISON CENTER OR PHYSICIAN IF YOU FEEL UNWELL. Do NOT INDUCE VOMITING. IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING.

START FIRST AID. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

EMERGENCY TELEPHONE: 1-866-923-4913

MOST IMPORTANT SYMPTOMS / EFFECTS: CAUSES SEVERE SKIN BURNS AND SERIOUS EYE DAMAGE. MAY CAUSE BLINDNESS WITHOUT IMMEDIATE FIRST AID. HARMFUL IF SWALLOWED. CAUSES BURNS AND SERIOUS DAMAGE TO MOUTH, THROAT AND STOMACH. CORROSIVE TO ALL BODY TISSUES. MEDICAL CONDITIONS AGGRAVATED: NONE KNOWN.

NOTE TO PHYSICIAN: CALL 1-866-923-4913 FOR EXPOSURE MANAGEMENT ASSISTANCE.

5. FIRE-FIGHTING MEASURES

CHEMICAL HAZARDS: MAY INTENSIFY FIRE; OXIDIZER. CORROSIVE. EXPLOSION RISK. COMBUSTION PRODUCT HAZARDS: OXYGEN, OXIDES OF CARBON AND OTHER FUMES. METHODS: SELECT EXTINGUISHER AND METHODS BASED ON FIRE SIZE AND TYPE. EQUIPMENT: WEAR SCBA AND FULL PROTECTIVE GEAR AS CONDITIONS WARRANT. NFPA RATING: HEALTH-3/FLAMMABILITY-0/ INSTABILITY-1/SPECIAL HAZARD-OX SUITABLE EXTINGUISHERS: WATER. CO2 OR HALON MAY PROVIDE LIMITED CONTROL. UNSUITABLE EXTINGUISHERS: DO NOT USE DRY CHEMICAL OR FOAMS.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: EVACUATE UNPROTECTED PERSONNEL FROM AREA. WEAR PERSONAL PROTECTION INCLUDING RUBBER BOOTS. SEE SECTION 8. VENTILATE AREA IF NEEDED. BE CAREFUL NOT TO SLIP. WASH THOROUGHLY AFTER CLEAN-UP. KEEP AWAY FROM COMBUSTIBLE AND INCOMPATIBLE MATERIALS. ENVIRONMENTAL PRECAUTIONS: PREVENT SPILL FROM ENTERING DRAIN, STORM

ENVIRONMENTAL PRECAUTIONS: PREVENT SPILL FROM ENTERING DRAIN, STORM SEWER OR SURFACE WATERWAY. PREVENT WATER AND SOIL CONTAMINATION. CLEAN-UP METHODS: SMALL SPILLS MAY BE WIPED UP AND RINSED WITH WATER. FOR LARGER SPILLS, DIKE TO CONTAIN. PUMP TO LABELED CONTAINER OR ABSORB SPILLAGE AND SCOOP UP WITH INERT ABSORBENT MATERIAL. NEVER RETURN SPILLED PRODUCT INTO ITS ORIGINAL CONTAINER. NEVER PUT SPILLED MATERIAL INTO ANOTHER CONTAINER FOR DISPOSAL WITHOUT A PRESSURE RELIEF BUNG. STANDARD SPILL ABSORBENT MAY REACT DANGEROUSLY WITH THIS PRODUCT AND IF CONFINED WILL CAUSE A CONTAINER BURST HAZARD. SEEK TRAINED PERSONNEL TO SUPERVISE NEUTRALIZATION AND MANAGEMENT OF SPILL. RESIDUAL HYDROGEN PEROXIDE THAT IS ALLOWED TO DRY ON ORGANIC MATERIALS LIKE PAPER, WOOD OR OTHER COMBUSTIBLES, CAN CAUSE THE MATERIAL TO IGNITE AND RESULT IN A FIRE. AFTER SPILL COLLECTION, RINSE AREA WITH WATER AND FOLLOW WITH NORMAL CLEAN-UP PROCEDURES.

7. HANDLING AND STORAGE

HANDLING: FOLLOW ALL LABEL DIRECTIONS. INSTRUCT PERSONNEL ABOUTPROPER USE, HAZARDS, PRECAUTIONS, AND FIRST AID MEASURES. AVOID INHALATION, INGESTION, AND CONTACT WITH SKIN, EYES AND CLOTHING. DO NOT TASTE OR SWALLOW. REMOVE AND WASH CONTAMINATED CLOTHING AND FOOTWEAR BEFORE REUSE. PRODUCT RESIDUE MAY REMAIN IN EMPTY CONTAINERS. HANDLE CAREFULLY TO AVOID DAMAGING CONTAINER.

STORAGE: STORE TIGHTLY CLOSED ONLY IN ORIGINAL CORROSIVE-RESISTANT PLASTIC CONTAINER. STORE LOCKED UP. STORE AT AMBIENT TEMPERATURES IN A DRY AREA OUT OF

DIRECT SUNLIGHT. AVOID TEMPERATURES BELOW 35°F (1.6°C) OR ABOVE 120°F (49°C). ROTATE STOCK REGULARLY. KEEP AWAY FROM FOOD AND DRINK. KEEP OUT OF REACH OF CHILDREN.

Page 3 of 4

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMITS: HYDROGEN PEROXIDE = 1 PPM TWA (ACGIH/OSHA)

ENGINEERING CONTROLS: GENERAL ROOM VENTILATION IS TYPICALLY ADEQUATE.

PERSONAL PROTECTION

EYES: CHEMICAL-SPLASH SAFETY GOGGLES.

HANDS: CHEMICAL-RESISTANT PROTECTIVE GLOVES (NITRILE, NEOPRENE OR RUBBER). **RESPIRATORY:** NIOSH/MSHA CERTIFIED RESPIRATOR IF EXPOSURE LIMITS ARE EXCEEDED.

FEET: PROTECTIVE FOOTWEAR.

BODY: SUITABLE PROTECTIVE CLOTHING.

HYGIENE MEASURES: HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICE. TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING AND WASH IT BEFORE REUSE. WASH HANDS AND AFFECTED AREAS THOROUGHLY AFTER HANDLING. PROVIDE SUITABLE FACILITIES FOR QUICK DRENCHING OR FLUSHING OF THE EYES AND BODY IN CASE OF CONTACT OR SPLASH HAZARD.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: COLORLESS LIQUID

ODOR: PUNGENT

ph concentrate: Below 3.5 (ACIDIC)

pH @ USE DILUTION: 6.0

PHYSICAL STATE: LIQUID RELATIVE DENSITY (WATER): 1.135

SOLUBILITY (WATER): COMPLETE

VAPOR PRESSURE: N.AV.

VAPOR DENSITY: N. AV. VISCOSITY: NON-VISCOUS

AUTO-IGNITION TEMPERATURE: N.AV. **DECOMPOSITION TEMPERATURE:** N.AV.

EXPLOSIVE LIMITS (LEL/UEL): NONE

EVAPORATION RATE: N.AV.

FLAMMABILITY (SOLID, GAS): N.AP.

FLASH POINT: NONE

INITIAL BOILING POINT/RANGE: N.AV.

MELTING POINT/FREEZING POINT: -27°F, -33°C

ODOR THRESHOLD: N.AV.

PARTITION COEFF. (N-OCTANOL/WATER): N.AV

OTHER: N.AV.

10. STABILITY AND REACTIVITY

REACTIVITY: MIXING WITH INCOMPATIBLES CAN RELEASE HEAT + HAZARDOUS GASES.

CHEMICAL STABILITY: STABLE UNDER RECOMMENDED STORAGE CONDITIONS.

POSSIBILITY OF HAZARDOUS REACTIONS: SEE REACTIVITY. WILL NOT POLYMERIZE. **CONDITIONS TO AVOID:** TEMPERATURES BELOW 35°F (1.6°C) OR ABOVE 120°F (49°C).

MATERIALS TO AVOID: ACIDS, BASES, BLEACH, METALS, SALTS OF METALS,

REDUCING AGENTS, ORGANIC MATERIALS, FLAMMABLE MATERIALS AND

CONTAMINATION OF ANY KIND. MIX ONLY WITH WATER.

HAZARDOUS DECOMPOSITION PRODUCTS: NONE UNDER NORMAL CONDITIONS.

11. TOXICOLOGICAL INFORMATION

ROUTES OF EXPOSURE: EYES, SKIN, INGESTION, INHALATION,

INFORMATION ON ROUTES OF EXPOSURE: NO LC50/LD50 TEST DATA ON MIXTURE.

ACUTE EFFECTS /SYMPTOMS: CORROSIVE TO ALL BODY TISSUES.

EYES: CAUSES SERIOUS EYE DAMAGE. MAY CAUSE PAIN, REDNESS AND WATERING.

SKIN: CAUSES SEVERE SKIN BURNS. MAY CAUSE DELAYED PAIN, REDNESS AND BLISTERING.

INGESTION: CAUSES BURNS AND SERIOUS DAMAGE TO MOUTH, THROAT AND STOMACH.

INHALATION: CAUSES IRRITATION OR BURNS TO NOSE, THROAT + RESPIRATORY SYSTEM.

CHRONIC / OTHER EFFECTS: NO REPORTABLE GERM CELL MUTAGENS, SKIN SENSITIZERS.

RESPIRATORY SENSITIZERS, REPRODUCTIVE TOXINS OR ASPIRATION HAZARDS.

SPECIFIC TARGET ORGANS (SINGLE): MAY CAUSE RESPIRATORY IRRITATION.

SPECIFIC TARGET ORGANS (REPEATED): NONE KNOWN.

NUMERICAL MEASURES OF TOXICITY: ATEmix (ORAL-RAT) = 1232 MG / KG

CARCINOGENS: HYDROGEN PEROXIDE / 7722-84-1 (IARC GROUP 3).

NO REPORTABLE ACGIH, NTP, OR OSHA CARCINOGENS.

12. ECOLOGICAL INFORMATION

Page 4 of 4

ECOLOGICAL INFORMATION: OSHA WILL NOT BE ENFORCING INFORMATION REQUIREMENTS IN SECTION 12, AS THIS AREA IS NOT UNDER ITS JURISDICTION.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: UNDILUTED PRODUCT IS REGULATED UNDER ENVIRONMENTAL AND TRANSPORTATION LAWS AS AN IGNITABLE AND CORROSIVE WASTE (RCRA CLASS D001, D002). DISPOSE OF CONTENTS IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL APPLICABLE LAWS AND REGULATIONS. CONSULT STATE AND LOCAL AUTHORITIES FOR RESTRICTIONS ON DISPOSAL OF CHEMICAL WASTE. MANAGE CHEMICAL WASTES THROUGH AN APPROVED WASTE TREATMENT FACILITY. DO NOT REUSE EMPTY CONTAINER. RINSE EMPTY CONTAINER THOROUGHLY WITH WATER BEFORE DISCARDING CONTAINER IN ACCORDANCE WITH CURRENT LOCAL COMMUNITY CODES. PLEASE RECYCLE EMPTY CONTAINER WHENEVER POSSIBLE. SEE SECTION 8 FOR EXPOSURE CONTROLS/PERSONAL PROTECTION TO MINIMIZE EXPOSURE.

14. TRANSPORT INFORMATION

DOT / IMDG / TDG: UN2014, HYDROGEN PEROXIDE, AQUEOUS SOLUTIONS, 5.1 (8), II

15. REGULATORY INFORMATION

EPA CERCLA RQ: NO **EPA REGISTERED: NO**

OSHA HAZARDOUS: YES. SEE SECTION 8 TO MINIMIZE EXPOSURE.

PHOSPHORUS CONTENT: 0.00%

PROPOSITION 65: NO

SARA 311/312 HAZARD CATEGORIES: SEE SECTION 2 FOR GHS HAZARD CLASSES.

SARA 313 CHEMICALS: NO

STATE RIGHT TO KNOW: WATER/7732-18-5. HYDROGEN PEROXIDE/7722-84-1 TSCA INVENTORY STATUS: ALL COMPONENTS ARE LISTED ON THE INVENTORY.

USE DILUTION (1:832): NO PPE OR SDS REQUIRED AT PROPER USE DILUTIONS.

VOC: 0.00% CALCULATION METHOD USED IS BASED ON CALIFORNIA ARB STANDARD.

16. OTHER INFORMATION

PREPARATION DATE: 2-2-24 PREPARED BY: RC **REVISED SECTION: 16** ABBREVIATIONS: N.AV. = NOT AVAILABLE N.AP. = NOT APPLICABLE

NOTICE TO READER

THIS DOCUMENT HAS BEEN PREPARED USING DATA FROM SOURCES CONSIDERED TECHNICALLY RELIABLE. IT DOES NOT CONSTITUTE A WARRANTY, EXPRESS OR IMPLIED, AS TO THE ACCURACY OF THE INFORMATION CONTAINED WITHIN. ACTUAL CONDITIONS OF USE AND HANDLING ARE BEYOND SELLER'S CONTROL. USER IS RESPONSIBLE FOR EVALUATING ALL AVAILABLE INFORMATION WHEN USING PRODUCT FOR ANY PARTICULAR USE AND TO COMPLY WITH ALL FEDERAL, STATE, PROVINCIAL AND LOCAL LAWS AND REGULATIONS.