

B-9990

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 4-3-2018

1. PRODUCT & COMPANY IDENTIFICATION						
1.1	Product Name:	#MyDentity MyStardust Intense Shine Spray				
1.2	Chemical Name:	Aerosol Shine Spray				
1.3	Synonyms:	#MyDentity MyStardust Intense Shine Spray – 55%VOC – B-9990				
1.4	Trade Names:	#MyDentity MyStardust Intense Shine Spray				
1.5	Product Uses/ Restrictions	Professional and Cosmetic Use				
1.6	Distributor's Name:	KIK Custom Products				
1.7	Distributor's Address:	2030 Old Candler Road, Gainesville, GA 30507 USA				
1.8	Emergency Phone:	CHEMTEL: +1 (703) 527-3887 / +1 (800) 424-9300				
1.9	Business Phone / Fax:	+1 (770) 534-0300 / +1 (770) 534-8954				

2. HAZARDS IDENTIFICATION

2.1 Hazard Identification: This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia)

DANGER! EXTREMELY FLAMMABLE AEROSOL. PRESSURIZED CONTAINER: MAY BURST IF HEATED. HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES EYE IRRITATION.

<u>Classification:</u> Level 3 Aerosol; Category 1 Flammable Aerosol

Hazard Statements:

Flammable Aerosol- Category 3

Gases under Pressure – Liquefied Gas

Causes eye irritation -Category 2 - Sub category B

<u>Precautionary Statement</u> (P): Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

<u>Precautionary Statements – response</u>: Avoid breathing vapors/spray. Use only in well-ventilated area. IF INHALED; Remove person to fresh air and keep comfortable for breathing. IF IN EYES; Rinse cautiously with water for several minutes. Remove contact lenses, if present, continue rinsing. If eye irritation persists: Get medical advice/attention.

<u>Precautionary Statements – Storage</u>: Protect from sunlight. Do no expose to temperature exceeding 48°C (120 °F). Keep product locked up and out of reach of children. Store in well ventilated areas.

<u>Precautionary Statements – Disposal</u>: Dispose of contents/container to licensed and permitted disposal or recycling facility.

Hazards not otherwise classified (HNOC)

Not Applicable



3. COMPOSITION & INGREDIENT INFORMATION

Substance / Chemical Name(s)	CAS No.	EINECS No.	%	Other
Propane	74-98-6	200-827-9	5 - 20	Flam. Gas 1; H220
Isobutane	75-28-5	200-857-2	5 - 20	Flam. Gas 1; H220
ETHANOL (SD ALCOHOL 40B)	64-17-5	200-578-6	5 - 20	Flam. Liq. 2; H225

4. FIRST AID MEASURES

4.1	First Aid:	Ingestion:	If ingested, do not induce vomiting! If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
		Skin:	If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with plenty of soap and water. Remove contaminated clothing and wash thoroughly before ruse. If irritation, redness or swelling persists, consult a physician immediately.
		Eyes:	If product get in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Raise and lower eyelid(s) while flushing to ensure thorough irrigation. If problems persist seek immediate medical attention.
		Inhalation:	Remove victim to fresh air and keep comfortable for breathing.



B-9990

4.2	Effects of Exposure:	Ingestion:	If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression.			
		Skin:	May be irritating to skin. The product can cause allerg	· -	elts, dermatitis) i	
			some sensitive individuals upon prolonged or repeated	d exposure.		
		Eyes:	Moderately irritating to the eyes.	*h		
			Vapors of this product may be moderately irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and			
		Inhalation:	difficulty breathing. Inhalation of concentrated vapors		-	
			drowsiness, dizziness, headaches, nausea).	s can cause hervous system dep	iression (e.g.,	
1.3	Symptoms of Overexposure	Ingestion:	May cause nausea, vomiting and/or diarrhea and centi	ral nervous system denression		
4.3	o,promo or over exposure	ingestion.	Prolonged contact with skin may result in bleaching an		t can cause allerg	
		Skin:	skin reactions (e.g., rashes, welts, dermatitis) in some			
			overexposure may include redness, itching, and irritati			
		_	Overexposure in eyes, may cause redness, itching and		ge to eves) Contac	
		Eyes:	may cause mild eye irritation including stinging, wateri		,,,	
		Inhalation:	Symptoms of overexposure can include coughing, whe		ficulty breathing.	
	Asuta Haalth Effacts.		itation to eyes and skin near affected areas. Additionally			
.4	Acute Health Effects:		dizziness, headaches and nausea.			
		No harmful o	or chronic health effects are expected to occur from a sin	gle accidental ingestion. These	ingredients may	
4.5	Chronic Health Effects:		kin and mucous membrane of the eye and respiratory sy			
+.5	Chronic Health Lifects.	symptoms in	some sensitive individuals. May also induce skin sensiti	zation and respiratory hyperser	nsitivity. Possible	
		allergic derm	atitis.			
4.6	Target Organs:		spiratory system.			
1.7	Medical Conditions		hazards may be delayed. Most common symptoms	HEALTH	1	
	Aggravated by Exposure		ting properties to eyes, respiratory system and skin.	FLAMMABILITY	3	
		Existing dern	natological conditions (such as eczema) and respiratory	PHYSICAL HAZARDS	0	
		_		TITISICALTIALANDS	U	
		conditions (s	uch as bronchial asthma and/or bronchitis) may be	PROTECTIVE EQUIPMENT	В	
		_	uch as bronchial asthma and/or bronchitis) may be			
. 1	Fire and Explosion Hazards	conditions (s exacerbated	uch as bronchial asthma and/or bronchitis) may be 5. FIREFIGHTING MEASURES	PROTECTIVE EQUIPMENT EYES SKIN		
5.1	Fire and Explosion Hazards:	conditions (s exacerbated	5. FIREFIGHTING MEASURES sol (NFPA 30B). Aerosols may burst at temperatures abo	PROTECTIVE EQUIPMENT EYES SKIN EVE 120° F (48°C). Cool		
5.1	Fire and Explosion Hazards:	Level 2 Aero uninvolved of	5. FIREFIGHTING MEASURES sol (NFPA 30B). Aerosols may burst at temperatures abountainers to prevent possible bursting. Aerosols may be	PROTECTIVE EQUIPMENT EYES SKIN EVE 120° F (48°C). Cool projectile hazards when		
5.1	Fire and Explosion Hazards:	Level 2 Aero uninvolved cobursting. If a	5. FIREFIGHTING MEASURES Sol (NFPA 30B). Aerosols may burst at temperatures abountainers to prevent possible bursting. Aerosols may be perosols are bursting, stay clear until bursting is complete.	PROTECTIVE EQUIPMENT EYES SKIN EVE 120° F (48°C). Cool projectile hazards when e. Containers may rupture		
5.1	Fire and Explosion Hazards:	Level 2 Aero uninvolved obursting. If a and release to	5. FIREFIGHTING MEASURES sol (NFPA 30B). Aerosols may burst at temperatures abountainers to prevent possible bursting. Aerosols may be derosols are bursting, stay clear until bursting is complete a clammable liquids and/or exposed gases if exposed to the	PROTECTIVE EQUIPMENT EYES SKIN EVE 120° F (48°C). Cool projectile hazards when e. Containers may rupture e heat of fire. Keep		
		Level 2 Aero uninvolved of bursting. If a and release to containers of	5. FIREFIGHTING MEASURES sol (NFPA 30B). Aerosols may burst at temperatures abountainers to prevent possible bursting. Aerosols may be perosols are bursting, stay clear until bursting is completed and bursting and or exposed gases if exposed to the pool by spraying them with water until the fire has been exposed to the pool by spraying them with water until the fire has been exposed.	PROTECTIVE EQUIPMENT EYES SKIN EVE 120° F (48°C). Cool projectile hazards when e. Containers may rupture e heat of fire. Keep		
5.2	Extinguishing Methods:	Level 2 Aero uninvolved of bursting. If a and release to containers of Water Fog, F	5. FIREFIGHTING MEASURES sol (NFPA 30B). Aerosols may burst at temperatures about ontainers to prevent possible bursting. Aerosols may be derosols are bursting, stay clear until bursting is completed flammable liquids and/or exposed gases if exposed to the bool by spraying them with water until the fire has been ending.	PROTECTIVE EQUIPMENT EYES SKIN EVE 120° F (48°C). Cool projectile hazards when e. Containers may rupture e heat of fire. Keep xtinguished.	B 3	
5.2		Level 2 Aero uninvolved of bursting. If a and release of containers of Water Fog, F	5. FIREFIGHTING MEASURES sol (NFPA 30B). Aerosols may burst at temperatures abountainers to prevent possible bursting. Aerosols may be perosols are bursting, stay clear until bursting is completed and bursting is completed and bursting them with water until the fire has been ended to the policy spraying them with water until the fire has been ended to the policy of the policy	PROTECTIVE EQUIPMENT EYES SKIN EVE 120° F (48°C). Cool projectile hazards when e. Containers may rupture e heat of fire. Keep xtinguished. apparatus (pressure-		
5.2	Extinguishing Methods:	Level 2 Aero uninvolved of bursting. If a and release of containers of Water Fog, F As in any fire demand_an	5. FIREFIGHTING MEASURES Sol (NFPA 30B). Aerosols may burst at temperatures about ontainers to prevent possible bursting. Aerosols may be derosols are bursting, stay clear until bursting is completed and and a completed of the sol by spraying them with water until the fire has been endem, CO ₂ , Dry Chemical approved self-contained breathing defull protective gear. Keep containers cool until well after the second of the second and the second of the second and the second of	PROTECTIVE EQUIPMENT EYES SKIN EVE 120° F (48°C). Cool projectile hazards when e. Containers may rupture e heat of fire. Keep xtinguished. apparatus (pressure- ier the fire is out. Use	B 3	
5.2	Extinguishing Methods:	Level 2 Aero uninvolved of bursting. If a and release of containers of Water Fog, F As in any fire demand_an water spray	5. FIREFIGHTING MEASURES Sol (NFPA 30B). Aerosols may burst at temperatures about ontainers to prevent possible bursting. Aerosols may be derosols are bursting, stay clear until bursting is completed and/or exposed gases if exposed to the pool by spraying them with water until the fire has been endead, CO ₂ , Dry Chemical 100, wear MSHA/NIOSH approved self-contained breathing did full protective gear. Keep containers cool until well after to cool fire-exposed surfaces and to protect personnel.	PROTECTIVE EQUIPMENT EYES SKIN EVE 120° F (48°C). Cool projectile hazards when e. Containers may rupture e heat of fire. Keep xtinguished. apparatus (pressure- er the fire is out. Use Fight fire upwind. Prevent	B 3	
5.1 5.2 5.3	Extinguishing Methods:	Level 2 Aero uninvolved of bursting. If a and release of containers of Water Fog, F As in any fire demand_an water spray runoff from a second container of the containers of t	5. FIREFIGHTING MEASURES Sol (NFPA 30B). Aerosols may burst at temperatures about ontainers to prevent possible bursting. Aerosols may be derosols are bursting, stay clear until bursting is completed and and a completed of the sol by spraying them with water until the fire has been endem, CO ₂ , Dry Chemical approved self-contained breathing defull protective gear. Keep containers cool until well after the second of the second and the second of the second and the second of	PROTECTIVE EQUIPMENT EYES SKIN EVE 120° F (48°C). Cool projectile hazards when e. Containers may rupture e heat of fire. Keep xtinguished. apparatus (pressure- ter the fire is out. Use Fight fire upwind. Prevent king water supply, or any	B 3	
5.2	Extinguishing Methods:	Level 2 Aero uninvolved of bursting. If a and release from any fire demand_an water spray runoff from anatural water	5. FIREFIGHTING MEASURES Sol (NFPA 30B). Aerosols may burst at temperatures about a surface on tainers to prevent possible bursting. Aerosols may be derosols are bursting, stay clear until bursting is completed and/or exposed gases if exposed to the cool by spraying them with water until the fire has been endead, CO ₂ , Dry Chemical approved self-contained breathing did full protective gear. Keep containers cool until well after to cool fire-exposed surfaces and to protect personnel. If the control or dilution from entering sewers, drains, dring the control or dilution from entering sewers, drains, dring the control or dilution from entering sewers, drains, dring the control or dilution from entering sewers, drains, dring the control or dilution from entering sewers, drains, dring the control or dilution from entering sewers, drains, dring the control or dilution from entering sewers, drains, dring the control or dilution from entering sewers, drains, dring the control or dilution from entering sewers, drains, dring the control or dilution from entering sewers, drains, dring the control or dilution from entering sewers, drains, dring the control or dilution from entering sewers, drains, dring the control or dilution from entering sewers.	PROTECTIVE EQUIPMENT EYES SKIN EVE 120° F (48°C). Cool projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished. Example 1 is out. Use Fight fire upwind. Prevent king water supply, or any HOSH-approved positive	B 3	
5.2	Extinguishing Methods:	Level 2 Aero uninvolved of bursting. If a and release from any fire demand_an water spray runoff from natural water pressure self	Sol (NFPA 30B). Aerosols may burst at temperatures about an analysis on tainers to prevent possible bursting. Aerosols may be derosols are bursting, stay clear until bursting is complete flammable liquids and/or exposed gases if exposed to the bool by spraying them with water until the fire has been endam, CO ₂ , Dry Chemical approved self-contained breathing of the protective gear. Keep containers cool until well after to cool fire-exposed surfaces and to protect personnel. If the fire control or dilution from entering sewers, drains, dring rway. Firefighters must use full bunker gear including NI	PROTECTIVE EQUIPMENT EYES SKIN EVE 120° F (48°C). Cool projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished. Example 1 is out. Use Fight fire upwind. Prevent king water supply, or any HOSH-approved positive	B 3	
5.2	Extinguishing Methods:	Level 2 Aero uninvolved of bursting. If a and release from any fire demand_an water spray runoff from natural water pressure self	Sol (NFPA 30B). Aerosols may burst at temperatures about an analysis on tainers to prevent possible bursting. Aerosols may be derosols are bursting, stay clear until bursting is completed and bursting them with water until the fire has been exposed to the pool by spraying them with water until the fire has been exposed. Dry Chemical approved self-contained breathing of the protective gear. Keep containers cool until well after to cool fire-exposed surfaces and to protect personnel. If the fire fighters must use full bunker gear including Nit-contained breathing apparatus to protect against potents.	PROTECTIVE EQUIPMENT EYES SKIN EVE 120° F (48°C). Cool projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished. Example 1 is out. Use Fight fire upwind. Prevent king water supply, or any HOSH-approved positive	B 3	
5.2	Extinguishing Methods:	Level 2 Aero uninvolved of bursting. If a and release from any fire demand_an water spray runoff from natural water pressure self	Sol (NFPA 30B). Aerosols may burst at temperatures about an analysis on tainers to prevent possible bursting. Aerosols may be derosols are bursting, stay clear until bursting is completed and bursting them with water until the fire has been exposed to the pool by spraying them with water until the fire has been exposed. Dry Chemical approved self-contained breathing of the protective gear. Keep containers cool until well after to cool fire-exposed surfaces and to protect personnel. If the fire fighters must use full bunker gear including Nit-contained breathing apparatus to protect against potents.	PROTECTIVE EQUIPMENT EYES SKIN EVE 120° F (48°C). Cool projectile hazards when e. Containers may rupture e heat of fire. Keep xtinguished. apparatus (pressure- ter the fire is out. Use Fight fire upwind. Prevent king water supply, or any IOSH-approved positive atial hazardous combustion	B 3	
5.2	Extinguishing Methods:	Level 2 Aero uninvolved of bursting. If a and release of containers of Water Fog, F As in any fire demand_ an water spray runoff from a natural water pressure self or decompositions.	5. FIREFIGHTING MEASURES Sol (NFPA 30B). Aerosols may burst at temperatures about a provent possible bursting. Aerosols may be derosols are bursting, stay clear until bursting is completed and bursting them with water until the fire has been exposed by spraying them with water until the fire has been exposed. On the pool by spraying them with water until the fire has been exposed. We water MSHA/NIOSH approved self-contained breathing at full protective gear. Keep containers cool until well after to cool fire-exposed surfaces and to protect personnel. If the control or dilution from entering sewers, drains, dring rway. Firefighters must use full bunker gear including Nith-contained breathing apparatus to protect against potentiation products and oxygen deficiencies.	PROTECTIVE EQUIPMENT EYES SKIN EVE 120° F (48°C). Cool projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished. apparatus (pressure- eer the fire is out. Use Fight fire upwind. Prevent king water supply, or any IOSH-approved positive etial hazardous combustion	1 3 0	
5.2	Extinguishing Methods: Firefighting Procedures:	Level 2 Aero uninvolved of bursting. If a and release of containers of Water Fog, F As in any fire demand_ an water spray runoff from a natural water pressure self or decompositions.	5. FIREFIGHTING MEASURES Sol (NFPA 30B). Aerosols may burst at temperatures about a prevent possible bursting. Aerosols may be derosols are bursting, stay clear until bursting is completed and bursting them with water until the fire has been exposed by spraying them with water until the fire has been exposed. Dry Chemical and protective gear. Keep contained breathing defull protective gear. Keep containers cool until well after to cool fire-exposed surfaces and to protect personnel. If the fire fire to cool fire-exposed surfaces and to protect personnel. If the contained breathing apparatus to protect against potential products and oxygen deficiencies. 6. ACCIDENTIAL RELEASE MEASUR ing any spill or leak, individuals involved in spill cleanup in the contained breathing apparatus to protect against potentials.	PROTECTIVE EQUIPMENT EYES SKIN EVE 120° F (48°C). Cool projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished. apparatus (pressure- eer the fire is out. Use Fight fire upwind. Prevent king water supply, or any IOSH-approved positive etial hazardous combustion	1 3 0	
5.2	Extinguishing Methods: Firefighting Procedures:	Level 2 Aero uninvolved of bursting. If a and release of containers of water Fog, F As in any fire demand_an water spray runoff from natural water pressure self or decomposition. Before clean Equipment (Small spills V	5. FIREFIGHTING MEASURES Sol (NFPA 30B). Aerosols may burst at temperatures about ontainers to prevent possible bursting. Aerosols may be derosols are bursting, stay clear until bursting is completed and bursting them with water until the fire has been exposed by spraying them with water until the fire has been exposed. On the fire has been exposed for the fire has been exposed surfaces and to protect personnel. If the cool fire-exposed surfaces and to protect personnel. If the contained breathing apparatus to protect against potential bursting and spray products and oxygen deficiencies. 6. ACCIDENTIAL RELEASE MEASUR ing any spill or leak, individuals involved in spill cleanup in the personnel personnel protective equipment including New part of the fire and the fire and the fire has been expected by the fire and the fire has been expected by the fire has been e	PROTECTIVE EQUIPMENT EYES SKIN INVE 120° F (48°C). Cool projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished. apparatus (pressure- ier the fire is out. Use Fight fire upwind. Prevent king water supply, or any IOSH-approved positive itial hazardous combustion ES must wear appropriate Persona ng gloves and protective eyewe	I Protective	
5.2	Extinguishing Methods: Firefighting Procedures:	Level 2 Aero uninvolved of bursting. If a and release of containers of Water Fog, F As in any fire demand_an water spray runoff from natural water pressure self or decompositions.	5. FIREFIGHTING MEASURES Sol (NFPA 30B). Aerosols may burst at temperatures about ontainers to prevent possible bursting. Aerosols may be derosols are bursting, stay clear until bursting is completed and bursting them with water until the fire has been eleman, CO ₂ , Dry Chemical and, wear MSHA/NIOSH approved self-contained breathing defull protective gear. Keep containers cool until well after to cool fire-exposed surfaces and to protect personnel. If the fire fire has been eleman, Firefighters must use full bunker gear including NI-contained breathing apparatus to protect against potentiation products and oxygen deficiencies. 6. ACCIDENTIAL RELEASE MEASUR ing any spill or leak, individuals involved in spill cleanup repersonal such as vermiculite or sand to soak up the products and oxygen deformed to soak up the products and sovermiculite or sand to soak up the products and to soak	PROTECTIVE EQUIPMENT EYES SKIN INVE 120° F (48°C). Cool projectile hazards when e. Containers may rupture e heat of fire. Keep xtinguished. apparatus (pressure- ier the fire is out. Use Fight fire upwind. Prevent king water supply, or any IOSH-approved positive itial hazardous combustion ES must wear appropriate Persona ing gloves and protective eyewe luct and place into a container for	I Protective ar. Use a non- for later disposal.	
5.2	Extinguishing Methods: Firefighting Procedures:	Level 2 Aero uninvolved of bursting. If a and release of containers of Water Fog, F As in any fire demand_an water spray runoff from natural water pressure self or decompositions. Before clean Equipment (Small spills V combustible not use water	5. FIREFIGHTING MEASURES Sol (NFPA 30B). Aerosols may burst at temperatures about ontainers to prevent possible bursting. Aerosols may be derosols are bursting, stay clear until bursting is completed and bursting them with water until the fire has been eleman, CO ₂ , Dry Chemical and, wear MSHA/NIOSH approved self-contained breathing defull protective gear. Keep containers cool until well after to cool fire-exposed surfaces and to protect personnel. If the fire the fire has been eleman, Firefighters must use full bunker gear including NI-contained breathing apparatus to protect against potentiation products and oxygen deficiencies. 6. ACCIDENTIAL RELEASE MEASUR ing any spill or leak, individuals involved in spill cleanup in the products are personal protective equipment including material such as vermiculite or sand to soak up the product or a material such as "speedy dry" to soak up material.	PROTECTIVE EQUIPMENT EYES SKIN INVE 120° F (48°C). Cool projectile hazards when e. Containers may rupture e heat of fire. Keep xtinguished. apparatus (pressure- ier the fire is out. Use Fight fire upwind. Prevent king water supply, or any IOSH-approved positive itial hazardous combustion ES must wear appropriate Persona ing gloves and protective eyewe luct and place into a container for the service of th	I Protective ar. Use a non- for later disposal. sparking material	
5.2	Extinguishing Methods: Firefighting Procedures:	Level 2 Aero uninvolved of bursting. If a and release of containers of Water Fog, F As in any fire demand_an water spray runoff from natural water pressure self or decompositions. Before clean Equipment (Small spills V combustible not use water (e.g., plastic	Sol (NFPA 30B). Aerosols may burst at temperatures about ontainers to prevent possible bursting. Aerosols may be derosols are bursting, stay clear until bursting is completed and bursting them with water until the fire has been eleman, CO ₂ , Dry Chemical and, CO ₂ , Dry Chemical and, CO ₃ , Dry Chemical and to protective gear. Keep containers cool until well after to cool fire-exposed surfaces and to protect personnel. If the fire control or dilution from entering sewers, drains, dring reway. Firefighters must use full bunker gear including Ningary spill or leak, individuals involved in spill cleanup in the products and oxygen deficiencies. 6. ACCIDENTIAL RELEASE MEASUR in any spill or leak, individuals involved in spill cleanup in the products and oxygen deficiencies. 6. Vear appropriate personal protective equipment including material such as vermiculite or sand to soak up the product or a material such as "speedy dry" to soak up material. brooms, shovels, dustpans) and place into a plastic contained brooms, shovels, dustpans) and place into a plastic contained brooms, shovels, dustpans) and place into a plastic contained brooms.	PROTECTIVE EQUIPMENT EYES SKIN EYES SKIN EYE 120° F (48°C). Cool projectile hazards when e. Containers may rupture e heat of fire. Keep xtinguished. Example 1 apparatus (pressure-ter the fire is out. Use Fight fire upwind. Prevent king water supply, or any lOSH-approved positive atial hazardous combustion ES must wear appropriate Personal g gloves and protective eyewe luct and place into a container of the sweep up material using non-terior or plastic liner within another systems.	I Protective ar. Use a non- for later disposal. sparking material ther container.	
5.2	Extinguishing Methods: Firefighting Procedures:	Level 2 Aero uninvolved of bursting. If a and release of containers of water Fog, F As in any fire demand_ an water spray runoff from natural water pressure self or decomposition of the composition of th	5. FIREFIGHTING MEASURES Sol (NFPA 30B). Aerosols may burst at temperatures about ontainers to prevent possible bursting. Aerosols may be derosols are bursting, stay clear until bursting is completed and/or exposed gases if exposed to the pool by spraying them with water until the fire has been exposed by spraying them with water until the fire has been exposed. Or comparison of the pool by spraying them with water until the fire has been exposed. Or comparison of the pool of the	PROTECTIVE EQUIPMENT EYES SKIN EYES SKIN EYE 120° F (48°C). Cool projectile hazards when e. Containers may rupture e heat of fire. Keep extinguished. Example 1 September 1 September 1 September 2 September 2 September 3 September 3 September 3 September 3 September 3 September 4 September 5 September 6 September 7	I Protective ar. Use a non- for later disposal. sparking materia ther container. d away from spill	
5.3	Extinguishing Methods: Firefighting Procedures:	Level 2 Aero uninvolved of bursting. If a and release from containers of water Fog, F. As in any fire demand_an water spray runoff from natural water pressure self or decomposition of the combustible not use water (e.g., plastic Large spills: I release. Isol	Sol (NFPA 30B). Aerosols may burst at temperatures about ontainers to prevent possible bursting. Aerosols may be derosols are bursting, stay clear until bursting is completed and bursting them with water until the fire has been eleman, CO ₂ , Dry Chemical and, CO ₂ , Dry Chemical and, CO ₃ , Dry Chemical and to protective gear. Keep containers cool until well after to cool fire-exposed surfaces and to protect personnel. If the fire control or dilution from entering sewers, drains, dring reway. Firefighters must use full bunker gear including Ningary spill or leak, individuals involved in spill cleanup in the products and oxygen deficiencies. 6. ACCIDENTIAL RELEASE MEASUR in any spill or leak, individuals involved in spill cleanup in the products and oxygen deficiencies. 6. Vear appropriate personal protective equipment including material such as vermiculite or sand to soak up the product or a material such as "speedy dry" to soak up material. brooms, shovels, dustpans) and place into a plastic contained brooms, shovels, dustpans) and place into a plastic contained brooms, shovels, dustpans) and place into a plastic contained brooms.	PROTECTIVE EQUIPMENT EYES SKIN E	I Protective ar. Use a non- for later disposal. sparking materia ther container. d away from spill elease if it can be	



Other Information:

SAFETY DATA SHEET

B-9990

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 4-3-2018 SDS Revision: 1.0 7. HANDLING AND STORAGE INFORMATION Do not eat, drink, or smoke while handling this product. Contents under pressure. Handle as to avoid puncturing 7.1 Work & Hygiene Practices container(s). When used as intended, no additional protective equipment is necessary. Use chemical goggles if eye contact is possible. Wash unintentional residues with soap and warm water. Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct Storage and Handling: sunlight. Avoid temperatures above 120 °F (48°C). Keep away from incompatible substances. Protect containers from 7.2 physical damage. To avoid unintentional spraying, keep cap in place when not in use. Storage level 1. **Special Precautions:** Spilled material may present a slipping hazard if left unattended. Clean all spills promptly. 7.3 8. EXPOSURE CONTROLS & PERSONAL PROTECTION **Exposure Limits:** ACGIH NOHSC **OSHA OTHER** Ppm (mg/m³) TLV STEL **ES-STEL ES-PEAK** STEL **IDLH** Chemical Name(s) **ES-TWA** PEL ETHANOL(SD ALCOHOL 40B) 1000 3000 1000 3300 1000 1800 NF 1900 1000 **Propane** NA 1000 NF NF 1000 NA 2100 Isobutane 600 750 NF NF NA NA NA NA Ventilation & Engineering General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Use local or general Controls exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. **Respiratory Protection:** No special respiratory protection is required under typical circumstances of use or handling. In instances where dusts of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia. Eye Protection: None required under normal conditions of use. Avoid eye contact. Safety glasses should be used when handling or using large quantities of this product (e.g., ≥ 1 gallon (3.8 L)). Hand Protection: None required under normal conditions of use. However, may cause skin irritation is some sensitive individuals. When handling large quantities (e.g., \geq 1 gallon (3.8 L)), wear rubber, nitrile or impervious plastic gloves. No apron required when handling small quantities. When handling large quantities (e.g., > **Body Protection:** 5 lbs.), eye wash station and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water. 9. PHYSICAL & CHEMICAL PROPERTIES 9.1 Appearance: Aerosol, misty oily spray 9.2 Odor: Fresh Sweet odor 9.3 Odor Threshold NA NA 9.5 NA Melting/Freezing Point Initial Boiling Point/ Boiling NA Range: -30 °F (-34 °C) TCC for propellant only; 35.6 °F (2 °C) EPA method 1010 Concentrate only 9.7 Flashpoint: 9.8 Upper/Lower Flammability NA limits Vapor Pressure: @ 20 °C (68° F) - Can pressure not to exceed 180 psig @ 55 °C (131 °F) 12.4 bar 9.10 Vapor Density >1 9.11 Relative Density: 0.85 - 0.959.12 Solubility: Soluble 9.13 **Partition Coefficient** NA (log Pow): Autoignition Temperature: NA 9.15 Decomposition NA Temperature. Viscosity: Aerosol at ambient temperature

Evaporation Rate >1: Percent Volatile < 55%



B-9990

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 4-3-2018

		10. STABILITY & REACTIVITY			
10.1	Stability:	Stable at normal temperatures.			
0.2	Hazardous Decomposition	·			
	Products:	Oxides of carbon (CO, CO ₂) and sulfur (SO ₂)			
0.3	Hazardous Polymerization:	Will not occur.			
0.4	Conditions to Avoid	Excessive heat, direct sunlight, flames, heat sources and incompatible substances.			
0.5	Incompatible Substances	Mixture with strong acids, alkalis or oxidizers.			
		11. TOXICOLOGICAL INFORMATION			
1.1	Routes of Entry:	Inhalation: YES Absorption: YES Ingestion: YES			
1.2	Toxicity Data:	This product was not tested on animals.			
	Acute Toxicity:	See Section 4.4			
	Chronic Toxicity:	See Section 4.5			
	Suspected Carcinogen:				
	1.6 Reproductive Toxicity: This product is not reported to cause reproductive toxicity in humans.				
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.			
Embryotoxicity: This product is not reported to produce embryotoxic effects in humans.					
	Teratogenicity:	This product is not report to cause teratogenic effects in humans.			
	Reproductive Toxicity:	This product is not report to cause reproductive effects in humans.			
1.7	Irritancy of Product:	See Section 4.3			
	Biological Exposure				
	Indices:	NA			
1.9	Physician	To all annuals and the life			
	Recommendations:	Treat symptomatically.			
		12. ECOLOGICAL INFORMATION			
2.1	Environmental Stability:	There is no specific data available for this product.			
2.2	Effects on Plants & Animals				
2.3	Effects on Aquatic Life:	The product itself has not been tested as a whole. There is no specific data available for this product.			
	'				
	1	13. DISPOSAL CONSIDERATIONS			
13.1	Waste Disposal:	Review current local, state and federal laws, codes, statutes and regulations to determine current status and			
		appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with			
local, state and federal laws and regulations. Contact the appropriate agency for specific information. A licens or waste hauler must provide treatment, transport, storage and disposal of hazardous waste.					
				3.2	Special Considerations:
		14. TRANSPORTATION INFORMATION			
4.1	49 CFR (GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL < 1.0 L); or			
		CONSUMER COMMODITY, ORM-D (IP VOL < 1.0 L) – until 12/31/2020			
4.2	IATA (AIR)	UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL < 0.5 L); or			
		ID8000, CONSUMER COMMODITY, ORM-D (IP VOL < 0.5 I=L)			
	IMDG (OCN):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL < 1.0 L)			
4.4	TDGR (Canadian GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL < 1.0 L); or			
		MARK PACKAGE "LIMITED QUANTITY", "LTD QTY", OR "QUANT LTÉE" OR "QUANTITÉ LIMITÉE"			
4.5	ADR/RID (EU):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL <u><</u> 1.0 L)			
	SCT (MEXICO):	UN1950, AEROSOLES, 2.1 (CANTIDAD LIMITADA, IP VOL < 1.0 L)			
	ADGR (AUS):				





B-9990

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 4-3-2018

		15. REGULATORY INFOR	MATION		
15.1	SARA Reporting Requirements:	This product does not contain any substance subject to SATA Title III, section 313 reporting requirements.			
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.			
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.			
15.4	CERCLA Reportable Quantity (RQ):	There are no specific Reportable Quantity			
15.5	Other Federal Requirements:	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR Subchapter G. (Cosmetics)			
15.6	Other Canadian Regulations:	This product has been classified according to the hazard information required by the CPR. The components of the the components of this product are listed on the Prioritic Aerosol)	e product are listed on the DSL/NDSL. None of		
15.7	State Regulatory Information:	Isobutane can be found on the following state criteria lists: MA, NJ, and PA. Propane is found on the following state criteria lists: MA, MN, NJ, PA and WA No other ingredients of this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).			
15.8	Other Requirements:	The primary components of this product are listed in Anr Isobutane: Flammable (F+). Risk Phrases (R): 12 – Highlout of reach of children. Keep container in a well-ventil No smoking. Propane: Flammable (F+). Risk Phrases (R). 12 – Highly F of reach of children. Keep container in a well-ventilated smoking, Flammable (F+)	y Flammable. Safety Phrases (S): 2-9-16 – Keep ated place. Keep away from sources of ignition – lammable. Safety Phrases (S): 2-9-16 – Keep out		
		16. OTHER INFORMA	TION		
16.1	Other Information:	DANGER! EXTREMELY FLAMMABLE AEROSOL. PRESSURIZED CONTAINER: MAY BURST IF HEATED, HIGHLY FLAMMABLE LIQUID AND VAPORS. CAUSES EYE IRRITATION. Keep away from heat, hot surfaces, sparks open flames and other ignition sources. No Smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing vapor/spray. Wash thoroughly with soap and water after handling. Use only in a well ventilated area. Wear eye protection. Protect from sunlight. Do not expose to temperature exceeding 48°C (120°F). IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. KEEP PRODUCT LOCKED-UP AND OUT OF REACH OF CHILDREN.			
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.			
	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the base of KIK Custom Product's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or complete=ness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.			
16.4	Prepared By:	KIK Custom Products 2030 Old Candler Road Gainesville, GA 30507 USA http://www.kikcorp.com	KIK CUSTOM PRODUCTS		




B-9990

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 4-3-2018





B-9990

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 4-3-2018

Full Face Respirator	Reactive	Irritant / Harmful
Biohazard	Oxidizing	Flammable
Infectious	Corrosive	Compressed
Toxic	Irritation	