

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250259632

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Holm; Michael et al.

---

### TRANSCRIPTION PRESENTATION OF COMMUNICATION SESSIONS

---

#### Abstract

A system is provided that includes a first network interface for a first network type and a second network interface for a second network type that is different from the first network type. The system also includes at least one processor configured to cause the system to perform operations. The operations may include obtaining, from the first network interface, audio from a communication session with a remote device established over the first network and obtaining an indication of a communication device available to participate in the communication session and direct audio obtained from the communication session to a remote transcription system. The operations may also include directing the audio to the second network interface for transmission to the communication device, obtaining transcript data from the remote transcription system based on the audio, and directing the transcript data to the second network interface for transmission to the communication device.

---

**Inventors:** Holm; Michael (Bountiful, UT), Pan; Jasper C. (Draper, UT)

**Applicant:** Sorenson IP Holdings, LLC (Salt Lake City, UT)

**Family ID:** 1000008561461

**Appl. No.:** 19/010950

**Filed:** January 06, 2025

#### Related U.S. Application Data

parent US continuation 18316427 20230512 parent-grant-document US 12190889 child US 19010950

parent US continuation 17650468 20220209 parent-grant-document US 11688401 child US 18316427

parent US continuation 17018810 20200911 parent-grant-document US 11250858 child US 17650468

parent US continuation 16592450 20191003 parent-grant-document US 10783891 child US

17018810

parent US continuation 15782734 20171012 parent-grant-document US 10468028 child US 16592450

us-provisional-application US 62407302 20161012

---

## Publication Classification

**Int. Cl.:** **G10L15/26** (20060101); **G10L15/01** (20130101); **G10L15/18** (20130101); **G10L15/28** (20130101); **G10L15/30** (20130101); **H04M1/247** (20210101); **H04M1/253** (20060101); **H04M1/72412** (20210101); **H04M3/42** (20060101); **H04M7/00** (20060101)

**U.S. Cl.:**

**CPC** **G10L15/26** (20130101); **G10L15/01** (20130101); **G10L15/18** (20130101); **G10L15/28** (20130101); **G10L15/30** (20130101); **H04M1/2473** (20130101); **H04M1/2475** (20130101); **H04M1/2535** (20130101); **H04M3/42221** (20130101); **H04M3/42391** (20130101); **H04M7/0036** (20130101); **H04M1/72412** (20210101); **H04M2201/40** (20130101); **H04M2201/60** (20130101)

---

## Background/Summary

**CROSS-REFERENCE TO RELATED APPLICATIONS [0001]** This patent application is a continuation of U.S. patent application Ser. No. 18/316,427, filed on May 12, 2023, which is a continuation of U.S. patent application Ser. No. 17/650,468, filed on Feb. 9, 2022, which is a continuation of U.S. patent application Ser. No. 17/018,810, filed on Sep. 11, 2020, which is a continuation of U.S. patent application Ser. No. 16/592,450, filed on Oct. 3, 2019, which is a continuation of U.S. patent application Ser. No. 15/782,734, filed on Oct. 12, 2017, which claims the benefit of U.S. Provisional Patent Application No. 62/407,302, filed on Oct. 12, 2016, the disclosures of each of which are hereby incorporated herein by this reference in their entireties.

### FIELD

[0002] The embodiments discussed herein are related to presentation of transcriptions in communication sessions.

### BACKGROUND

[0003] Modern telecommunication services provide features to assist those who are deaf or hearing-impaired. One such feature is a text captioned telephone system for the hearing impaired that uses a relay system. A relay system may be a telecommunication intermediary service that is intended to permit a hearing-impaired user to utilize a normal telephone network.

[0004] The subject matter claimed herein is not limited to embodiments that solve any disadvantages or that operate only in environments such as those described above. Rather, this background is only provided to illustrate one example technology area where some embodiments described herein may be practiced.

### SUMMARY

[0005] A system is provided that includes a first network interface configured to direct first network traffic over a first network of a first network type and a second network interface configured to direct second network traffic over a second network of a second network type that is different from the first network type. The system also includes one or more computer-readable media configured to store instructions and at least one processor communicatively coupled to the first network interface, the second network interface, and the computer-readable media, the at least

one processor configured to execute the instructions to cause the system to perform operations. The operations may include obtaining, from the first network interface, audio from a communication session with a remote device established over the first network. The operations may further include obtaining an indication of a communication device available to participate in the communication session with the remote device and directing audio obtained from the communication session to a remote transcription system. The operations may also include directing the audio to the second network interface for transmission to the communication device and obtaining transcript data from the remote transcription system based on the audio, the transcript data including a transcription of the audio. The operations may additionally include directing the transcript data to the second network interface for transmission to the communication device.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0006] Example embodiments will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

[0007] FIG. 1 illustrates an example environment for communication sessions that include presentations of transcriptions of the communication sessions;

[0008] FIG. 2 illustrates an example network device;

[0009] FIG. 3 illustrates another example environment for communication sessions that include presentations of transcriptions of the communication sessions;

[0010] FIG. 4 illustrates another example environment for communication sessions that include presentations of transcriptions of the communication sessions;

[0011] FIGS. 5a and 5b illustrates example operations to enable communication sessions that include presentations of transcriptions of the communication sessions;

[0012] FIG. 6 illustrates an example environment for presentation of transcriptions;

[0013] FIG. 7 illustrates an example method to present transcripts of a communication;

[0014] FIG. 8 illustrates another example method to present transcripts of a communication;

[0015] FIG. 9 illustrates another example method to present transcripts of a communication; and

[0016] FIG. 10 illustrates another example method to present transcripts of a communication.

### DESCRIPTION OF EMBODIMENTS

[0017] Some embodiments in this disclosure relate to a method and/or system that may transcribe communication sessions between multiple devices. In some embodiments, the method and/or system describe that a communication session between a remote device and a device selected from multiple devices may be directed by a host device that handles the communication protocols between the selected device and the remote device. In these and other embodiments, the selected device may receive audio from the remote device and the audio may be provided to a transcription system.

[0018] The transcription system may be configured to transcribe the audio and a transcript may be provided to the selected device or another device of the multiple devices for presentation to a hearing-impaired user. The transcript may assist the hearing-impaired user in understanding the audio and participate better in the communication session.

[0019] Thus, the method and/or system may be configured to facilitate an assisted call with a hearing-impaired user. As used in the present disclosure, a “hearing-impaired user” may refer to a person with diminished hearing capabilities. Hearing-impaired users often have some level of hearing ability that has usually diminished over a period of time such that the hearing-impaired user can communicate by speaking, but that the hearing-impaired user often struggles in hearing and/or understanding others. Thus, the system described may be an assistive service that may assist a hearing-impaired user to utilize a communication network and assist the hearing-impaired user's

understanding of a conversation by providing transcriptions to supplement voice conversation occurring during communication sessions that involve the hearing-impaired user.

[0020] In some embodiments, the communication session may be multiplexed so that each of the multiple devices may receive audio from the remote device. In these and other embodiments, the transcription may be provided to each of the multiple devices for presentation by the multiple devices. Alternatively or additionally, each of the multiple devices may provide audio to the remote device during the communication session.

[0021] The systems and/or methods described in this disclosure may assist in enabling the generation of a transcription of audio of multiple devices participating in a communication session with another device in place of the transcription of audio in only point-to-point communication sessions. Thus, the systems and/or methods provide at least a technical solution to a technical problem associated with the design of current transcription systems.

[0022] Turning to the figures, FIG. 1 illustrates an example environment **100** for communication sessions that include presentations of transcriptions of the communication sessions. The environment **100** may be arranged in accordance with at least one embodiment described in the present disclosure. The environment **100** may include a first network **102**, a device **110**, a public switched telephone network (PSTN) **112**, a remote device **114**, a first networked device **120a**, a second networked device **120b**, a third networked device **120c**, a second network **130**, and a transcription system **140**.

[0023] The device **110** may be a digital device that is configured to establish, maintain, and/or terminate communication sessions over various networks between various types of devices. In some embodiments, the device **110** may be configured to multiplex communications among multiple devices. In these and other embodiments, the device **110** may be configured to establish, maintain, and/or terminate a communication session between the remote device **114** and one or more of the first networked device **120a**, the second networked device **120b**, and the third networked device **120c** (referred to as the networked device(s) **120**). In these and other embodiments, the device **110** may be configured to operate as an intermediary between the remote device **114** and the networked devices **120**. For example, the device **110** may be configured to communicate with the remote device **114** using a first network type and to communicate with one or more of the networked devices **120** using a second network type. The device **110** may handle the networking protocols of the first and second network types such that the remote device **114** and the networked devices **120** are unaware of differences in the networks and handle the communication session as if there were no changes in the network types or protocols.

[0024] In some embodiments, the remote device **114** may be any electronic, analog, or digital device. For example, the remote device **114** may include a laptop computer, a smartphone, a mobile phone, a tablet computer, a phone console, a public switched telephone network (PSTN) phone, or any other communication device. The remote device **114** may be configured to participate in a communication session with other devices. In the communication session, audio may be exchanged between the remote device **114** and the device **110** by way of the PSTN **112**. In the present disclosure, reference to “audio,” “local audio,” “remote audio,” and “networked device audio” related to communication sessions may include signals or data that may represent or be used to construct or reconstruct the audio of a communication session. In the present disclosure, reference to “video,” “local video,” “remote video,” and “networked device video” related to communication sessions may include signals or data that may represent or be used to construct or reconstruct the video of a communication session. The video may be a stream of images that are reproduced to generate the video.

[0025] The PSTN **112** may be any combination of analog, digital, and/or optical networks that form a public switched telephone network that may transport audio of a communication session between the device **110** and the remote device **114**. For example, the device **110** may be directly coupled to an analog connection and the remote device **114** may be an analog connection. Between the analog

connections coupled to the device **110** and the remote device **114**, digital and/or optical networks may transport the audio between the device **110** and the remote device **114**.

[0026] In some embodiments, the device **110** may be further configured to communicate with the transcription system **140**. In these and other embodiments, the device **110** may be configured to provide audio from a communication session being handled by the device **110** to the transcription system **140** over the first network **102**.

[0027] In some embodiments, the first network **102** may have numerous different configurations. In some embodiments, the first network **102** may include a peer-to-peer network. The first network **102** may also be coupled to or may include portions of a telecommunications network for sending data in a variety of different communication protocols. In some embodiments, the first network **102** may be an Internet Protocol (IP) based network. In some embodiments, the first network **102** may include cellular communication networks for sending and receiving communications and/or data including via hypertext transfer protocol (HTTP), direct data connection, wireless application protocol (WAP), etc. The first network **102** may also include a mobile data network that may include third-generation (3G), fourth-generation (4G), long-term evolution (LTE), long-term evolution advanced (LTE-A), Voice-over-LTE (“VoLTE”) or any other mobile data network or combination of mobile data networks.

[0028] In some embodiments, the transcription system **140** may include any configuration of hardware, such as processors, servers, and databases that are networked together and configured to generate transcript data that includes a transcript of the audio by transcribing audio received over the first network **102**. For example, the transcription system **140** may include multiple computing systems, such as multiple servers that each include memory and at least one processor, which are networked together and configured to perform operations as described in this disclosure, among other operations. In some embodiments, the transcription system **140** may include computer-readable-instructions that are configured to be executed by the transcription system **140** to perform operations described in this disclosure.

[0029] In some embodiments, the transcription system **140** may be configured to transcribe audio received from the device **110** to generate transcript data of the audio. In some embodiments, the transcription system **140** may include human intermediaries that may re-voice the audio received by the transcription system **140**. The re-voiced audio may be transcribed by a system that is tuned or configured to the human intermediaries to generate the transcript data.

[0030] The transcription system **140** may provide the transcript data of the audio to the device **110**. The device **110** may be configured to provide the transcript data of the audio to the networked devices **120** that are participating in the communication session. In some embodiments, the transcript data may include a transcription of the audio and other information configured to direct how the transcription of the audio is presented.

[0031] In some embodiments, the device **110** may communicate with the networked devices **120** over the second network **130**. In some embodiments, the second network **130** may be configured as short-range wireless networks, such as a wireless local area network (LAN), a personal area network (PAN), or a wireless mesh network (WMN). For example, the second network **130** may be networks that use Bluetooth® Class 2 and Class 3 communications with protocols that are managed by the Bluetooth® Special Interest Group (SIG). Other examples of wireless networks may include the IEEE 802.11 networks (commonly referred to as WIFI®), Zigbee networks, among other types of LANS, PANS, and WMNS. In some embodiments, the second network **130** may be a combination of the wireless networks, such as Bluetooth® and IEEE 802.11 networks, among other types of combinations of short-range wireless networks.

[0032] In these and other embodiments, the second network **130** may be generally described as wireless networks, but different wireless protocols may be used for communication between the device **110** and the networked devices **120**. For example, the device **110** may be configured to communicate with the first networked device **120a** over an IEEE 802.11 network. During

overlapping periods of time, the device **110** may be configured to communicate with the second networked device **120b** over a Bluetooth network. Additionally, during overlapping periods of time, the device **110** may be configured to communicate with the third networked device **120c** over a Zigbee wireless network or some other wireless communication network. Thus, the term second network **130** as used herein does not indicate that a same type of network is used to communicate with each of the networked devices **120**, but rather refers generally to wireless networks that may be of any number of different types. Alternatively or additionally, the device **110** may communicate with each of the networked devices **120** over the same type of wireless network.

[0033] In some embodiments, the networked devices **120** may be multiple different types of devices that may be used by a hearing-impaired user(s) or other user(s). For example, the networked devices **120** may be electronic processing devices, such as desktop computers, laptop computers, tablets, smart phones, personal assistant devices, and other hand-held personal computing devices. In some embodiments, the networked devices **120** may be a television or other display device. In some embodiments, the networked devices **120** may be personal health care devices, such as a neck loop that acts as a handset, a hearing aid, a call button, an alert button, a headset, among other personal health care devices. In some embodiments, one or more of the networked devices **120** may be alert devices. In these and other embodiments, the one or more of the networked devices **120** may simply issue an alert when a request for a communication session is received at the device **110**. For example, the alert may be an audio, visual, or other type of alert. In some embodiments, one or more of the networked devices **120** may be speaker phones or other telephonic devices.

[0034] In some embodiments, the networked devices **120** may be a combination of the electronic processing devices, the display devices, the personal health care devices, the alert devices, and telephonic devices. For example, the first networked device **120a** may be a tablet, the second networked device **120b** may be a television, and the third networked device **120c** may be a neck loop that communicates with hearing aids of a hearing-impaired user.

[0035] The device **110** may be configured to periodically determine which of the networked devices **120** are available for communication sessions. For example, when one of the networked devices **120**, such as the first networked device **120a**, is first powered on, such as from a sleep mode or from being full-powered off, the first networked device **120a** may register with the device **110**. In some embodiments, the device **110** may send out periodic discovery signals to the networked devices **120** to allow the networked devices **120** to register with the device **110**. Alternatively or additionally, the networked devices **120** may include instructions/protocols to register with the device **110** when powered on.

[0036] The device **110** may keep a registry of all of the networked devices **120** that are registered with the device **110**. The device **110** may poll the networked devices **120** to help to maintain the accuracy of the registry. During the polling of the networked devices **120**, if one of the networked devices **120** does not respond, the device **110** may remove the one of the networked devices **120** from the registry.

[0037] The device **110** may use the registry to determine which of the networked devices **120** may participate in a communication session with the remote device **114**. For example, the networked devices **120** that are on the registry at the beginning of a communication session may be requested to be part of the communication session. After becoming part of the communication session, the networked devices **120** may receive audio from the communication session and transcript data of the audio. Alternatively or additionally, the networked devices **120** that are registered during a communication session or that accept requests of the communication session may be provided audio and transcript data of the audio from the communication session after registration.

[0038] In some embodiments, the device **110** may obtain further information regarding the networked devices **120**. The information may indicate various abilities of the networked devices **120**. For example, some of the networked devices **120** may be configured to broadcast audio from a

communication session but may lack a display for presentation of transcripts based on transcript data. Alternatively or additionally, some of the networked devices **120** may be configured to broadcast audio and display a presentation of transcripts but may lack a microphone or other device to allow the networked devices **120** to generate audio as part of the communication session. Alternatively or additionally, some of the networked devices **120** may be configured to indicate that a communication session is being requested but not allow participation in the communication session.

[0039] In these and other embodiments, the device **110** may provide the portions of the communication session that are appropriate for the networked devices **120**. For example, the device **110** may provide audio to a hearing aid but not transcript data of the audio as the hearing aid may not include a display to present the transcript data. Alternatively or additionally, the device **110** may use the information to determine which of the networked devices **120** may actively participate in the communication session. As used herein, to actively participate in a communication session may involve receiving audio and generating and transmitting audio during the communication session. For example, a tablet with a microphone may actively participate in a communication session because a user of the tablet may speak into the microphone such that the tablet may generate audio that is shared during the communication session. Likewise, the tablet may broadcast received audio over a speaker and present transcript data of the received audio on a display. As another example, a television may passively participate because the television may broadcast received audio over a speaker and present transcript data of the received audio on a display but may not include a microphone to allow the television to generate and transmit audio.

[0040] In some embodiments, one or more of the networked devices **120** may only actively participate in a communication session initiated by the one or more of the networked devices **120**. For example, the third networked device **120c** may be an alert button. In these and other embodiments, the third networked device **120c** may not receive transcript data or participate in communication sessions unless the communication session is commenced by the third networked device **120c**. In these and other embodiments, the alert button may be wearable by a user such that a communication session with a particular individual or system may be established if the user is unable to reach another device to begin a communication session.

[0041] In some embodiments, the information regarding the networked devices **120** may be updated during the polling of the networked devices **120**. In these and other embodiments, the device **110** may request information regarding the networked devices **120** during the polling. In some embodiments, the information may include whether the networked devices **120** may request a communication session with the remote device **114**. Alternatively or additionally, the information may be a current configuration of the networked devices **120**. In these and other embodiments, the networked devices **120** may change a configuration based on an interaction from a user, other devices, or particular settings in the networked devices **120**. For example, the networked devices **120** may change a configuration based on a schedule of configurations. For example, the first networked device **120a** may change its configuration based on a time of day or day of the week. In this example, at particular times, the first networked device **120a** may accept audio and transcript data. At other times, the first networked device **120a** may accept transcript data and not audio. In some embodiments, the received information may thus update the current configuration of one or more of the networked devices **120** in instances in which a corresponding configuration may have changed.

[0042] Various descriptions of the operation of elements in the environment **100** and interactions between the different elements of the environment **100** is now provided. In some embodiments, a communication session may be started by the remote device **114**. In these and other embodiments, the device **110** may be associated with a number or other identifier for making communication sessions. The remote device **114** may send a request for a communication session over the PSTN **112** to the device **110**. The device **110** may receive the communication session request and send the

request out to the networked devices **120** based on which of the networked devices **120** may actively participate in a communication session. The device **110** may determine which of the networked devices **120** may actively participate based on the information received from the networked devices **120**.

[0043] After one or more of the networked devices **120** accepts the request, the device **110** may establish the communication session between the one of the networked devices **120** that accepted the request and the remote device **114**. The device **110** may further indicate to the other networked devices **120** that a communication session is being established. The other networked devices **120** may request active participation, passive participation, or no participation in the communication session. Alternatively or additionally, at any point during the communication session, a participation status of the other networked devices **120** may change between active participation, passive participation, and no participation in the communication session. Alternatively or additionally, the device **110** may indicate the participation of the networked devices **120** in the communication session.

[0044] During the communication session, the device **110** may receive remote audio from the remote device **114**. The remote audio may be provided to the actively participating networked devices **120**. Alternatively or additionally, the remote audio may be provided to passively participating networked devices **120**. Thus, in some embodiments, the remote audio may be provided to each of the participating networked devices **120**.

[0045] The remote audio may also be provided to the transcription system **140** over the first network **102**. The transcription system **140** may generate transcript data of the remote audio and provide the transcript data to the device **110**. The device **110** may provide the transcript data to the participating networked devices **120** that are configured to present transcriptions.

[0046] In some embodiments, each of the actively participating networked devices **120** may also generate and send networked device audio to the device **110**. In these and other embodiments, the device **110** may send the networked device audio over the PSTN **112** to the remote device **114**. In some embodiments, the device **110** may also send the networked device audio to each of the other networked devices **120** participating in the communication session over the second network **130**. Furthermore, the device **110** may also send the networked device audio to the transcription system **140** over the first network **102**. The device **110** may receive transcript data from the transcription system **140** of the networked device audio. The device **110** may provide the transcript data of the networked device audio to each of the participating networked devices **120** except the one of the networked devices **120** that generated the networked device audio. Alternatively or additionally, the device **110** may provide the transcript data of the networked device audio to each of the participating networked device **120**. Thus, multiple users may participate in the communication session and receive transcript data of audio during the communication session of the audio that the multiple users did not originate.

[0047] When the remote device **114** terminates the communication session, the device **110** may receive an indication of the termination and terminate the communication session with each of the participating networked devices **120**. When all of the actively participating networked devices **120** terminate the communication session, the device **110** may terminate the communication session with the remote device **114** and the passively participating networked devices **120**. In these and other embodiments, when one of the actively participating networked devices **120** terminates the communication session but another actively participating networked device **120** does not terminate the communication session, the device **110** may maintain the communication session with the remote device **114**. In these and other embodiments, the actively participating networked devices **120** that previously terminated their active participation in the communication session may become passively participating networked devices **120** or may be removed from the communication session such that no further audio and/or transcript data are provided to the previous actively participating networked devices **120**.



[0048] As another example, in some embodiments, a communication session may be requested by the first networked device **120a**. In these and other embodiments, the first networked device **120a** may send a request for a communication session to the device **110**. The device **110** may send the request to the remote device **114**. After the remote device **114** accepts the request, the device **110** may provide an indication of the communication to the other networked devices **120** so that the other networked devices **120** may actively or passively participate in the communication session. As described previously, the audio during the communication session may be provided to some or all of the participating networked devices **120**, the transcription system **140**, and the remote device **114**. Furthermore, transcript data of the audio from the transcription system **140** may be provided to the participating networked devices **120**.

[0049] Another example of the operation of elements in the environment **100** is now provided. In this example, the first networked device **120a** may be a smartphone, the second networked device **120b** may be a Bluetooth neck-loop that provides audio to a hearing aid of a first user, and the third networked device **120c** may be a television. In these and other embodiments, the first networked device **120a** may actively participate, the second networked device **120b** may passively participate and be configured to receive audio and no transcript data and the third networked device **120c** may passively participate and be configured to receive transcript data and no audio. Furthermore, in this example, the remote device **114** may be a regular PSTN phone.

[0050] The device **110** may be associated with a PSTN phone number. In some embodiments, although not illustrated, a regular PSTN phone may be coupled to the PSTN **112** along with the device **110** in a residence of the first user and a second user. The remote device **114** may place a call to a phone number associated with an end node of the PSTN **112** coupled to the device **110** and the regular PSTN phone. In these and other embodiments, the central office of the PSTN **112** may be unaware of the device **110**. Rather, the central office and the PSTN **112** may not be configured differently than if the end node of the PSTN **112** coupled to the device **110** was only coupled to a regular PSTN phone. From the perspective of the PSTN **112**, the device **110** may behave as a regular PSTN phone.

[0051] After the call is placed by the remote device **114**, the PSTN **112** may forward the request to the device **110** and the PSTN phone that is coupled to the PSTN **112** along with the device **110** in a residence of the first user and a second user. The PSTN phone may ring and the device **110** may look at the registry and determine the networked devices **120** that are registered. Of the registered devices, the first networked device **120a** may actively participate in the communication session. The device **110** may indicate to the first networked device **120a** that a request for the communication session has been received. The second user may request that the communication session be established using the first networked device **120a**, which is a smart phone. The device **110** may follow the protocol to establish the communication session with the remote device **114**. The device **110** may also indicate to the second networked device **120b** and the third networked device **120c** that a communication session is occurring and the second networked device **120b** and the third networked device **120c** may request to participate in the communication session as passive devices.

[0052] Second user audio generated by the first networked device **120a** may be provided to the device **110** over the second network **130**. The device **110** may provide the second user audio to the second networked device **120b**, the transcription system **140**, and the remote device **114**. The audio may not be provided to the third networked device **120c** based on the third networked device **120c** being configured to not present audio. The transcript data of the second user audio may be provided to the third networked device **120c** and presented by the third networked device **120c**. The transcript data may not be provided to the second networked device **120b** based on the second networked device **120b** not being configured to present transcript data. Alternatively or additionally, the transcript data may be provided to the first networked device **120a**.

[0053] Third party audio may be generated by the remote device **114** and provided to the device

**110.** The device **110** may direct the remote audio to the transcription system **140**, the first networked device **120a**, and the second networked device **120b**. The transcript data of the remote audio is also provided to the first networked device **120a** and the third networked device **120c**. Alternatively or additionally, the transcript data may be provided to other devices of the networked devices **120** that are configured to receive transcript data. Thus, in this example, the second user may actively participate in the communication session with the remote device **114** using the smartphone. The second user may also be presented transcript data of audio from the remote device **114** by the first networked device **120a**.

[0054] The first user may passively participate in the communication session using the Bluetooth neck device and the television. In these and other embodiments, the first user may be presented audio from the first networked device **120a** and the remote device **114** by way of the Bluetooth neck device and transcript data of the audio from the first networked device **120a** and the remote device **114** may be presented to the first user by way of the television.

[0055] In these and other embodiments, the PSTN phone that is coupled to the PSTN **112** along with the device **110** in a residence of the first user and a second user may join and be part of the communication session. In some embodiments, transcript data of the audio from the regular PSTN phone may be created. Alternatively or additionally, transcript data of the audio from the regular PSTN phone may not be created. In any event, transcript data of the audio from the remote device **114** may be available on one or more of the networked devices **120** such that a third user may participate in the communication session using the regular PSTN phone while viewing transcriptions from the transcript data of the audio from the remote device **114** on one of the networked devices **120**.

[0056] Modifications, additions, or omissions may be made to the environment **100** without departing from the scope of the present disclosure. For example, the environment **100** may include more or less than the three networked devices **120** illustrated. Alternatively or additionally, the device **110** may include multiple devices. An example is provided with respect to FIG. 3. Furthermore, the environment **100** is illustrated as including the PSTN **112**. The environment **100** may be configured to not include the PSTN **112**. In these and other embodiments, the device **110** may include another network or may use the first network **102** to communicate with the remote device **114**. In these and other embodiments, additional data, such as video data may be shared among the remote device **114**, the device **110**, and the networked devices **120**.

[0057] As another example, in some embodiments, a user of the remote device **114** may be hearing impaired. In these and other embodiments, the transcription system **140** may provide transcript data of audio to the remote device **114** through a connection between the remote device **114** and the transcription system **140**.

[0058] As another example, in some embodiments, the transcription system **140** may provide alterations to the device **110** of previously provided transcript data. In these and other embodiments, the device **110** may distribute the alterations to the networked devices **120**.

[0059] FIG. 2 illustrates an example network device **200**. The device **200** may be arranged in accordance with at least one embodiment described in the present disclosure. The device **200** may include a processor **210**, a memory **212**, a first network interface **220a**, a second network interface **220b**, a third network interface **220c**, and a fourth network interface **220d**, referred to collectively as the network interfaces **220**.

[0060] In some embodiments, the device **200** may be an example of the device **110** of FIG. 1. In these and other embodiments, the device **200** may be configured to provide the functionality of the device **110**.

[0061] Generally, the processor **210** may include any suitable special-purpose or general-purpose computer, computing entity, or processing device including various computer hardware or software modules and may be configured to execute instructions stored on any applicable computer-readable storage media. For example, the processor **210** may include a microprocessor, a microcontroller, a

digital signal processor (DSP), an application-specific integrated circuit (ASIC), a Field-Programmable Gate Array (FPGA), or any other digital or analog circuitry configured to interpret and/or to execute program instructions and/or to process data.

[0062] Although illustrated as a single processor in FIG. 2, it is understood that the processor **210** may include any number of processors distributed across any number of networks or physical locations that are configured to perform individually or collectively any number of operations described herein. In some embodiments, the processor **210** may interpret and/or execute program instructions and/or processing data stored in the memory **212**. By interpreting and/or executing program instructions and/or process data stored in the memory **212**, the device **200** may perform operations, such as the operations performed by the device **110** of FIG. 1.

[0063] The memory **212** may include computer-readable storage media or one or more computer-readable storage mediums for carrying or having computer-executable instructions or data structures stored thereon. Such computer-readable storage media may be any available media that may be accessed by a general-purpose or special-purpose computer, such as the processor **210**. By way of example, and not limitation, such computer-readable storage media may include non-transitory computer-readable storage media including Random Access Memory (RAM), Read-Only Memory (ROM), Electrically Erasable Programmable Read-Only Memory (EEPROM), Compact Disc Read-Only Memory (CD-ROM) or other optical disk storage, magnetic disk storage or other magnetic storage devices, flash memory devices (e.g., solid state memory devices), or any other storage medium which may be used to carry or store desired program code in the form of computer-executable instructions or data structures and which may be accessed by a general-purpose or special-purpose computer. Combinations of the above may also be included within the scope of computer-readable storage media. In these and other embodiments, the term “non-transitory” as used herein should be construed to exclude only those types of transitory media that were found to fall outside the scope of patentable subject matter in the Federal Circuit decision of *In re Nuijten*, 500 F.3d 1346 (Fed. Cir. 2007). In some embodiments, computer-executable instructions may include, for example, instructions and data configured to cause the processor **210** to perform a certain operation or group of operations as described in the present disclosure.

[0064] The first network interface **220a** may be a PSTN network interface. The second network interface **220b** may be a Bluetooth network interface. The third network interface **220c** may be an Ethernet network interface. The fourth network interface **220d** may be a wireless network interface. The network interfaces **220** may each be configured to handle their associated protocol and to provide the information to the processor **210** and/or other elements of the device **200** not illustrated.

[0065] For example, the first network interface **220a** may be configured to handle protocols for a PSTN. In these and other embodiments, the first network interface **220a** may be configured to recognize dial tones, voltages, and other aspects of protocols for transmission and reception of audio over a PSTN. In some embodiments, the first network interface **220a** may receive analog audio from a PSTN. The first network interface **220a** may convert the analog audio to digital audio and provide the digital audio to the processor **210**. The processor **210** may provide the digital audio to other of the network interfaces **220** for transmission to other devices/systems, such as the transcription system **140** and the networked devices **120** of FIG. 1.

[0066] The first network interface **220a** may be configured to handle other protocols associated with a PSTN. For example, the first network interface **220a** may be configured to detect tones that indicate a voice mail is available, such as shutter tones. In these and other embodiments, the first network interface **220a** may be configured to obtain the voice mail, convert the voice mail to a digital voice mail, and provide the digital voice mail to the processor **210**. In these and other embodiments, the processor **210** may be configured to provide the digital voice mail to the third network interface **220c** for transmission to a transcription system. The processor **210** may also be configured to provide an indication of and/or the digital voice mail to one or more other devices by

way of the second network interface **220b** or the fourth network interface **220d**.

[0067] In some embodiments, the first network interface **220a** may also be configured to determine if the PSTN is functioning properly. For example, the first network interface **220a** may determine if there is no dial tone on the PSTN. In these and other embodiments, the first network interface **220a** may indicate the improper function of the PSTN to the processor **210**. The processor **210** may provide an indication of the improper function of the PSTN to an entity that oversees the PSTN through one or more of the other network interfaces **220**. In these and other embodiments, the processor **210** may be further configured to direct communication sessions directed to the PSTN to another network such that a communication session may be established even though the PSTN is not functioning properly.

[0068] The second network interface **220b** may be configured to handle protocols associated with a Bluetooth network. In these and other embodiments, the second network interface **220b** may receive digital data from the processor **210** for transmission over the Bluetooth network and send digital data to the processor **210** received over the Bluetooth network. The second network interface **220b** may package the digital data and handle the handshaking for communication with other devices over the Bluetooth network.

[0069] The third network interface **220c** may be configured to handle protocols associated with an Ethernet network. In these and other embodiments, the third network interface **220c** may receive digital data from the processor **210** for transmission over the Ethernet network and send digital data to the processor **210** received over the Ethernet network. The third network interface **220c** may package the digital data and handle the handshaking for communication with other devices over the Ethernet network.

[0070] The fourth network interface **220d** may be configured to handle protocols associated with a wireless network. In these and other embodiments, the fourth network interface **220d** may receive digital data from the processor **210** for transmission over the wireless network and send digital data to the processor **210** received over the wireless network. The fourth network interface **220d** may package the digital data and handle the handshaking for communication with other devices over the wireless network.

[0071] An example of the operation of the device **200** is provided. The example assumes that the device **200** is used in place of the device **110** of FIG. 1. A communication session may be established using the first network interface **220a** with the remote device **114**. Third party audio from the first network interface **220a** may be provided to the processor **210**. The processor **210** may direct the remote audio to the third network interface **220c** for transmission over the first network **102** to the transcription system **140**. The third network interface **220c** may also receive remote transcript data of the remote audio and provide the remote transcript data to the processor **210**. The processor **210** may provide the remote audio and the remote transcript data to the fourth network interface **220d** for transmission over the wireless network to the third networked device **120c**.

[0072] The fourth network interface **220d** may also receive networked audio from the third networked device **120c** over the wireless network and provide the networked audio to the processor **210**. The processor **210** may direct the networked audio to the third network interface **220c** for transmission to the transcription system **140** and to the first network interface **220a** for transmission over the PSTN **112** to the remote device **114**. The transcription system **140** may provide a networked transcript data to the third network interface **220c**, which may provide the networked transcript data to the processor **210**. The processor **210** may send the networked transcript data, the networked audio, the remote audio, and the remote transcript data to the second network interface **220b** for transmission over the Bluetooth network to the second networked device **120b**.

[0073] Modifications, additions, or omissions may be made to the device **200** without departing from the scope of the present disclosure. For example, the device **200** may include more or fewer

network interfaces **220**. For example, the device **200** may be coupled to a wireless router that may handle the wireless network hand shaking and protocol. In these and other embodiments, the third network interface **220c** may handle the traffic for both the third network interface **220c** and the fourth network interface **220d** as illustrated.

[0074] Alternatively or additionally, the network interfaces **220** may be configured for different types of networks than those described. Alternatively or additionally, the device **200** may include additional components/elements that may interact with the processor **210** and the network interfaces **220** to provide the functionality of the device **200** as described in the present disclosure.

[0075] FIG. **3** illustrates another example environment **300** for communication sessions that include presentations of transcriptions of the communication sessions. The environment **300** may be arranged in accordance with at least one embodiment described in the present disclosure. The environment **300** may include a first network **302**, a device **310**, a second network **312**, a remote device **314**, a first networked device **320a**, a second networked device **320b**, a third networked device **320c** (referred to collectively as the networked devices **320**), a second network **330**, and a transcription system **340**.

[0076] The first network **302**, the networked devices **320**, and the transcription system **340** may be analogous to the first network **102**, the networked devices **120**, and the transcription system **140** of FIG. **1**, respectively, and no further description is provided herein. The second network **312** may be analogous to the first network **302** and the first network **102** of FIG. **1**. In some embodiments, the second network **312** may be the same as the first network **302**.

[0077] The remote device **314** may be an electronic device with which a communication session may be established. In these and other embodiments, the communication session may be an audio or a video communication session.

[0078] The device **310** may include the functionality of the device **110** of FIG. **1** as well as additional functionality. In some embodiments, the device **310** may include a routing device **350** and a phone console **352**. The phone console **352** may include a display, a microphone, a speaker, and a handset. The phone console **352** may be configured to establish a communication session with the remote device **314**, using either video or audio. The phone console **352** may be further configured to present a transcription of the video or audio from the communication session based on transcript data. In these and other embodiments, a communication session with the phone console **352** may also be joined by one or more of the networked devices **320** in the manner described with respect to FIG. **1**.

[0079] The routing device **350** may be a routing device that is a slave to the phone console. The routing device **350** may be configured to interface with the different wireless networks of the second network **330**. In these and other embodiments, the phone console **352** may direct the routing of audio, video, and transcriptions among the networked devices **320** and the remote device **314** by way of the routing device **350**. In these and other embodiments, the routing device **350** may be used to handle the establishment of connections and handling protocol and packet handling between the phone console **352**, the networked devices **320**, and the transcription system **340**. In some embodiments, the phone console **352** may talk directly to the transcription system **340** over the first network **302**.

[0080] Modifications, additions, or omissions may be made to the environment **300** without departing from the scope of the present disclosure. For example, the routing device **350** may be part of the phone console **352**, such that the device **310** is housed in a single housing, analogous to device **110** of FIG. **1**. Alternately or additionally, the routing device **350** and the phone console **352** may be coupled through a different network than the second network **330**, such as a wired network.

[0081] FIG. **4** illustrates another example environment **400** for communication sessions that include presentations of transcriptions of the communication sessions. The environment **400** may be arranged in accordance with at least one embodiment described in the present disclosure. The environment **400** includes a first device **410**, a wireless access point **430**, an adapter **432**, and a user

device **420**.

[0082] The environment **400** illustrates another embodiment of a portion of the environment **300** or the environment **100** of FIGS. **3** and **1**, respectively. For example, the first device **410** and the wireless access point **430** may together perform the functionality of the device **110** of FIG. **1** and/or the device **200** of FIG. **2**. In these and other embodiments, the first device **410** may include a processor to direct the operations performed by the device **110** of FIG. **1** and/or the device **200** of FIG. **2**. The wireless access point **430** may be analogous to the fourth network interface **220d** of FIG. **2** and may provide information protocol and packet handling for a wireless network.

[0083] The user device **420** and the adapter **432** may together perform the functionality of one of the networked devices **120** and/or networked devices **320** of FIGS. **1** and **3**, respectively. In these and other embodiments, the user device **420** may be a device that provides functionality outside of the systems/methods described in the present disclosure. For example, the user device **420** may be a display. The adapter **432** may be used in connection with the user device **420** so that together the adapter **432** and the user device **420** may actively participate in a communication session and present a transcription of the communication session based on transcript data. For example, the user device **420** may be a television that does not include a microphone. The adapter **432** may be a microphone and include a processor and software that is configured to communicate with the first device **410** over a wireless network. The adapter **432** may provide audio and transcript data to the user device **420** for presentation by the user device **420** and may handle other functionality of the networked devices **120** and the networked devices **320** described in this disclosure.

[0084] Modifications, additions, or omissions may be made to the environment **400** without departing from the scope of the present disclosure. For example, the wireless access point **430** and the first device **410** may be combined as a single device.

[0085] FIGS. **5a** and **5b** illustrates example operations **500** to enable communication sessions that include presentations of transcriptions of the communication sessions. The operations **500** may be arranged in accordance with at least one embodiment described in the present disclosure. The operations **500** may include examples of communications and interactions between and operations performed by a device **510**, a remote device **514**, a first networked device **520a**, a second networked device **520b**, a third networked device **520c** (the networked devices **520**), and a transcription system **540**. In some embodiments, the device **510**, the remote device **514**, the first networked device **520a**, the second networked device **520b**, the third networked device **520c**, and the transcription system **540** may be analogous to the device **110**, the remote device **114**, the first networked device **120a**, the second networked device **120b**, the third networked device **120c**, and the transcription system **140**, respectively, of FIG. **1**. Accordingly, no further explanation is provided with respect thereto.

[0086] Generally, the operations **500** may relate to presentation of transcriptions of audio presented by one or more of the networked devices **520**. The interactions between the device **510**, the remote device **514**, the first networked device **520a**, the second networked device **520b**, the third networked device **520c**, and the transcription system **540** may occur over one or more networks as previously described and as described with respect to FIGS. **5a** and **5b**. The operations **500** illustrated are not exhaustive but are merely representative of operations **500** that may occur. Furthermore, one operation as illustrated may represent one or more communications, operations, and/or data exchanges between the device **510**, the remote device **514**, the first networked device **520a**, the second networked device **520b**, the third networked device **520c**, and the transcription system **540**.

[0087] At operation **542**, the first networked device **520a** may register with the device **510** over a first network. The first networked device **520a** may register with the device **510** after being discovered by the device **510**. In these and other embodiments, the first networked device **520a** may transmit data packets over the first network that include an identifier associated with the device **510**. When the device **510** recognizes that a data packet is being transmitted over the first

network, the device **510** may send a discovery request to the first networked device **520a** to thereby allow the first networked device **520a** to register with the device **510**. Alternatively or additionally, the device **510** may send out discover requests over the first network and the first networked device **520a** may respond to the discover request.

[0088] In some embodiments, the first network may be a wireless network. For example, the first network may be a short-range wireless network, such as a wireless local area network (LAN), a personal area network (PAN), or a wireless mesh network (WMN) as described in this disclosure. As described in this disclosure, the device **510** and the first networked device **520a** may be located such that communication over the short-range wireless network occurs without intermediary devices, such as additional servers or routers in other cloud based or Internet Protocol (IP) based networks.

[0089] In some embodiments, registration with the device **510** may include the first networked device **520a** indicating the capabilities of the first networked device **520a** to the device **510**. The capabilities may include whether the first networked device **520a** is able to receive and broadcast audio with a speaker, capture audio through a microphone and transmit the captured audio, receive transcript data and display transcriptions based on the transcript data, present a notification of a communication session, for example ringing or other notification, present communication session requester information, such as caller identification, among other capabilities. With respect to the example illustrated in FIGS. **5a** and **5b**, the first networked device **520a** may include an ability to receive and broadcast audio with a speaker and present a notification of a communication session.

[0090] At operation **544**, the second networked device **520b** may register with the device **510** over a second network. The second networked device **520b** may register with the device **510** after being discovered by the device **510**. The second networked device **520b** may be discovered in an analogous manner as described with the respect to the discovery of the first networked device **520a**.

[0091] In some embodiments, the second network may be a wireless network. For example, the second network may be a short-range wireless network, such as a wireless local area network (LAN), a personal area network (PAN), or a wireless mesh network (WMN) as described in this disclosure. As described in this disclosure, the device **510** and the first networked device **520a** may be located such that communication over the short-range wireless network occurs without intermediary devices, such as additional servers or routers in other cloud based or Internet Protocol (IP) based networks. As described with respect to FIGS. **5a** and **5b**, the first network and the second network may be different types of short-range wireless networks. However, in other embodiments, the first network and the second network may be the same type of short-range wireless network.

[0092] With respect to the example illustrated in FIGS. **5a** and **5b**, the second networked device **520b** may register with the device **510** by indicating that the second networked device **520b** includes an ability to receive and broadcast audio with a speaker, capture audio through a microphone and transmit the captured audio, and present a notification of a communication session.

[0093] At operation **546**, the third networked device **520c** may register with the device **510** over the first network. Alternatively or additionally, the third networked device **520c** may communicate with the device **510** over the second network or a third network that is a short-range wireless network. The third networked device **520c** may register with the device **510** after being discovered by the device **510**. The third networked device **520c** may be discovered in an analogous manner as described with respect to the discovery of the first networked device **520a**.

[0094] With respect to the example illustrated in FIGS. **5a** and **5b**, the third networked device **520c** may register with the device **510** by indicating that the third networked device **520c** includes an ability to receive transcript data and display transcriptions based on the transcript data.

[0095] At operation **548**, the device **510** may receive a communication request from the remote device **514** over a fourth network. The fourth network may include portions of a telecommunications network for sending data over a variety of different communication protocols.

The interface with the device **510** may be a cellular type network, a PSTN network, an IP network (such as a mobile data network or wired IP network) or other type of communication network, such as a short-range wireless network where the communication request is routed to the device **510** from the telecommunications network.

[0096] The device **510** may be configured to interface with the fourth network and handle the network and communication protocols to respond to the communication request and establish a communication session with the remote device **514**.

[0097] At operation **550**, in response to the communication request, the device **510** may send a notification to the first networked device **520a** and the second networked device **520b**. The notification may be sent to the first networked device **520a** and the second networked device **520b** based on the first networked device **520a** and the second networked device **520b** registering with the device **510** as including the ability to present a notification of a communication session. In some embodiments, the device **510** may send the notification using a protocol unique to the communication between the device **510** and the networked devices **520**. In these and other embodiments, the networked devices **520** may not be aware of the protocol or network from which the device **510** received the communication request. Rather, the networked devices **520** may respond using the protocol unique to the communication between the device **510** and the networked devices **520** without concern of any additional communication protocols that may be used to communicate with the remote device **514**.

[0098] For example, when the fourth network is a PSTN line, the device **510** may send the notification at operation **550**. The notification may be in response to a sine wave or other change in voltage or current on the fourth network indicating a communication request. The device **510** may not revoke the notification until after the sine wave or other change in voltage indicates that the request has ended or until some other action is taken, such as directing the communication request to voice mail.

[0099] At operation **552**, the second networked device **520b** may send a communication to the device **510** answering the request. The communication may be sent by the second networked device **520b** in response to a user interaction with the second networked device **520b**. For example, the second networked device **520b** may provide an indication of the notification by broadcasting audio, vibrating, and/or emitting light. In response, the user may interact with the second networked device **520b**. For example, when the second networked device **520b** is a PSTN phone, the user may move a receiver to place the receiver in an off-hook state. Alternatively or additionally, the second networked device **520b** may be a tablet or smart phone. In these and other embodiments, a user of the second networked device **520b** may click a button or interact with a screen of the second networked device **520b** to indicate to the second networked device **520b** to respond to the notification and request to establish a communication session.

[0100] At operation **554**, the device **510** may follow an appropriate protocol to establish a communication session with the remote device **514**. The remote device **514** may be unaware that the user is not interacting with the device **510** during the communication session. From the perspective of the remote device **514** and the fourth network, the device **510** may be the only device participating in the communication session. In short, the device **510** may function as a gate keeper and handle communications between the networked devices **520** and the device **510** without involving the remote device **514**. As a result, the networked devices **520** are unaware of the remote device **514** and the type of the fourth network. As a result, the networked devices **520** may include no additional hardware or software to allow them to participate in communication sessions that occur over a range of different types of networks.

[0101] The communication session may include passing of audio and/or video back and forth between the remote device **514** and the device **510**. For example, a user of the remote device **514** and a user of one or more of the networked devices **520** may carry on an audio only conversation or an audio and video conversation during the communication session.



[0102] At operation **556**, the device **510** may obtain remote audio from the remote device **514**. The remote audio may be audio captured by the remote device **514** that includes speech of the user of the remote device **514**.

[0103] At operation **558**, the device **510** may relay the remote audio to the first networked device **520a** and the second networked device **520b**. The device **510** may relay the remote audio to the first networked device **520a** and the second networked device **520b** because the first networked device **520a** and the second networked device **520b** indicated during the registration an ability to receive and broadcast audio.

[0104] The device **510** may be further configured to direct the remote audio to the transcription system **540**. In some embodiments, the device **510** may direct the remote audio to the transcription system **540** over a fifth network. In these and other embodiments, the fifth network may be an IP network, such as the Internet.

[0105] At operation **560**, the device **510** may obtain transcript data from the transcription system **540**. The transcript data may be generated by the transcription system **540** based on the remote audio. In these and other embodiments, the transcript data may include a transcription of the remote audio. The transcription system **540** may generate the transcript data in substantially real-time. As a result, the device **510** may receive the transcript data within one to ten seconds after sending the remote audio to the transcription system **540**.

[0106] At operation **562**, the first networked device **520a** may be configured to present the remote audio received from the device **510**. Presenting the remote audio may include broadcasting the remote audio through a speaker into the air to allow a user to hear the remote audio. At operation **564**, the second networked device **520b** may be configured to present the remote audio received from the device **510**. The operations **562** and **564** may occur at substantially the same-time such that there is little or no difference or delay between the remote audio presented by the first networked device **520a** and the second networked device **520b**.

[0107] At operation **566**, the device **510** may send the transcript data to the third networked device **520c**. At operation **568**, the third networked device **520c** may be configured to present a transcription of the remote audio based on the transcript data. To present the transcription, the third networked device **520c** may display the transcription on a screen to be read by a user of the third networked device **520c**.

[0108] The transcription may be presented to be substantially aligned with the presentation of the remote audio by the first networked device **520a** and the second networked device **520b**. For example, when the remote audio includes speech that includes a first word, the transcription of the first word may be displayed within one to ten seconds after the first word is broadcast as part of the remote audio. The transcription may assist a user of the first networked device **520a** and/or the second networked device **520b** to understand speech in the remote audio.

[0109] At operation **570**, the second networked device **520b** may record local audio based on sounds presented at a microphone of the second networked device **520b**. The sounds may be based on speech of a user of the second networked device **520b** that is participating in the communication session. The local audio may be a digitized version of the speech of the user.

[0110] At operation **572**, the second networked device **520b** may send the local audio to the device **510**. The device **510** may convert the local audio to the format needed to send the local audio to the remote device **514** and the transcription system **540**. For example, if the fourth network is a PSTN network, the device **510** may convert the digital local audio into analog for providing over the fourth network. As another example, if the fourth network is an IP network, the device **510** may packetize the local audio into IP network packets for sending over the IP network.

[0111] At operation **574**, the device **510** may send the local audio to the remote device **514**, the first networked device **520a**, and to the transcription system **540**. The remote device **514** may present the local audio by broadcasting the local audio over a speaker for a user of the remote device **514** to hear. In this manner, a user of the second networked device **520b** may communicate with a user of

the remote device **514**. The transcription system **540** may generate transcript data of the local audio. The transcript data of the local audio may include a transcription of the local audio.

[0112] At operation **575**, the first networked device **520a** may present the local audio obtained from the device **510**. As an example, the first networked device **520a** may be a hearing aid that provides audio but does not include a microphone. Thus, a user using the first networked device **520a** may passively participate in the communication session and hear a user of the remote device **514** and a user of the second networked device **520b**.

[0113] Note that the second networked device **520b** does not provide the local audio to the first networked device **520a**. In these and other embodiments, the first networked device **520a** and the second networked device **520b** may not be aware of the presence of the other. The first networked device **520a** and the second networked device **520b** may communicate with the device **510** and be unaware of other communications involving the device **510**.

[0114] At operation **576**, the transcription system **540** may provide the transcript data to the device **510** over the fifth network. At operation **578**, the device **510** may provide the transcript data to the third networked device **520c** over the network through which the device **510** and the third networked device **520c** are communicating, such as the second or third network.

[0115] At operation **580**, the third networked device **520c** may present a transcription of the local audio based on the transcript data of the local audio. The transcription may be displayed on a display so that the transcription may be read. The transcription may be displayed substantially aligned with the presentation of the audio by the first networked device **520a** in operation **575**. In these and other embodiments, presenting the transcription of the local audio may assist a user of the first networked device **520a** to understand the local audio provided by the second networked device **520b**.

[0116] At operation **582**, the second networked device **520b** may indicate to the device **510** to end the communication session. In some embodiments, the second networked device **520b** may receive input from a user to end the communication session. The second networked device **520b** may provide the indication to the device **510**.

[0117] At operation **584**, the device **510** may send an end communication session indication to the remote device **514**. In these and other embodiments, the device **510** may follow the protocol of the fourth network to send the end communication session indication. For example, when the fourth network is a PSTN network, the device **510** may change a connection status to indicate a termination of the communication session.

[0118] At operation **585**, the device **510** may send an end communication session to the first networked device **520a** and the third networked device **520c** to allow the first networked device **520a** and the third networked device **520c** to conclude the communication session.

[0119] At operation **586**, the second networked device **520b** may request a communication session with the remote device **514**. The communication session request may include information about the remote device **514**. The information may include a phone number or other identifier of the remote device **514**. The information may be in a form particular to the protocol used between the device **510** and the third networked device **520c**. In these and other embodiments, the device **510** may convert the information into a form that may be used to send a communication session request to the remote device **514**.

[0120] At operation **588**, the device **510** may send a communication request to the remote device **514** in response to receiving the request from the second networked device **520b**. At operation **590**, a communication session may be established between the device **510** and the remote device **514** based on the request from the second networked device **520b**.

[0121] At operation **592**, the second networked device **520b** may send the device **510** local audio. The local audio may be audio generated by a microphone of the second networked device **520b** based on speech of a user of the second networked device **520b**.

[0122] At operation **594**, the device **510** may send the local audio to the remote device **514** as

analogously performed in the operation 574. In operation 596, the device 510 may obtain remote audio from the remote device 514 as analogously performed in the operation 556. Additional operations may be performed analogously to performance of the operations 558, 560, 564, and 566 as previously explained.

[0123] Modifications, additions, or omissions may be made to the operations 500 without departing from the scope of the present disclosure. For example, in some embodiments, the operations 500 may not include one or more of the operations described. For example, the operations 500 may not include the operations 542, 562, 575, 576, and/or 578. In some embodiments, the operations 500 may include additional operations. As another example, in some embodiments, the operations 500 may be arranged in a different order. As another example, in some embodiments, the operations 500 may be performed by a different device. For example, the operation 580 may be performed by another networked device or by the first networked device 520a.

[0124] FIG. 6 illustrates an example environment 600 for presentation of transcriptions. The environment 600 may be arranged in accordance with at least one embodiment described in the present disclosure. The environment 600 may include a device 610, an adapter device 650 that includes a processing system 652, a television 660, a first cable 670, and a second cable 672. The device 610 may be analogous to the device 110 and 510 of FIGS. 1 and 5. In some embodiments, the adapter device 650 and the television 660 together may perform one or more of the operations analogous to the operations performed by networked devices 120 and 520 of FIGS. 1 and 5. In some embodiments, the adapter device 650 and the television 660 may be analogous to the adapter 432 and the user device 420, respectively, of FIG. 4. Accordingly, limited explanation to some of the elements and/or operations of the elements in the environment 600 may be provided in the discussion of FIG. 6.

[0125] The adapter device 650 may include the processing system 652 and may be coupled to the first cable 670. The processing system 652 may include one or more processors, computer-readable media, and other devices that are configured to perform or cause the adapter device to perform operations discussed in this disclosure.

[0126] The first cable 670 may be configured to carry a video stream that is configured to be provided to the television 660. The video stream may originate from a video stream source. The video stream source may be any type of video source, such as, a DVD® player, Blue-Ray® player, cable box, satellite television box, digital video recorder, computer, streaming player, or other device configured to provide a video stream. The first cable 670 may provide the video stream to the adapter device 650.

[0127] The second cable 672 may communicatively couple the adapter device 650 and the television 660. In these and other embodiments, the second cable 672 may carry the video stream from the adapter device 650 to the television 660. The second cable 672 may also be configured to carry additional information from the adapter device 650 to the television 660. The additional information may include a transcription of transcript data the adapter device 650 receives from the device 610 and/or control data to control the operation of the television 660.

[0128] The television 660 may be configured to display images received over the second cable 672. The images may include the video stream and/or the information from the adapter device 650. In some embodiments, the television 660 may be further configured to receive commands from the adapter device 650. The commands may include turning on, coming to an awake state from a sleep state, adjusting display settings, such as contrast and brightness, and adjusting volume levels, among other commands.

[0129] In some embodiments, the adapter device 650 may be configured to communicate with the device 610 over a wireless network. In these and other embodiments, the adapter device 650 may be configured to receive transcript data from the device 610. In response to receiving the transcript data, the adapter device 650 may be configured to provide the television 660 with the transcription from the transcript data.

[0130] In some embodiments, the adapter device **650** may be configured to combine the video stream from the first cable **670** with the transcription. In these and other embodiments, the adapter device **650** may provide the television **660** with the combined video stream and transcription. In these and other embodiments, the television **660** may be unaware of the transcription. Rather, the television **660** may receive a video stream with the transcription embedded therein such that the television **660** merely displays the received combined stream and, in the process, displays the transcription.

[0131] In some embodiments, the video stream and the transcription may be combined such that the transcription overlays the video stream. In these and other embodiments, the transcription may be transparent or semitransparent such that the video stream may be partially visible behind the transcription. In these and other embodiments, the video stream and the transcription may be combined using an alpha blending technique among other video blending techniques. In these and other techniques, the transcription may be combined with the video stream by adjusting pixel information of the video stream to display the transcription. Thus, in these and other embodiments, the combining of the video stream and the transcription does not indicate that the information is merely passed together to the television **660** from the adapter device **650**. Rather, the combining may indicate that the pixel data of the video stream may be altered such that when rendered, the television **660** displays the video stream and the transcription in front of the video stream. In these and other embodiments, the transcription may cover a portion of the video stream that is less than ten, twenty-five, fifty, or seventy-five percent, or some other portion of the video stream as displayed by the television **660**.

[0132] In these and other embodiments, the video stream may be a video stream that the television **660** is displaying before the adapter device **650** receives the transcript data from the device **610**. In these and other embodiments, the adapter device **650** may be relaying the video stream from the first cable **670** to the television **660** by way of the second cable **672**. In these and other embodiments, in response to receiving the transcript data, the adapter device **650** may begin combining a transcription based on the transcript data and the video stream. The combined video stream and transcription may be provided to the television **660** for display by the television **660**. In these and other embodiments, the transcription may not be associated with, correspond to, or otherwise correlate to the video stream. Rather, the transcription may be of remote audio of a communication session directed by the device **610**. The video stream may be the video stream that a user of the television **660** has selected to be viewing at the time that the communication session occurs and may not be related in any manner to the transcription besides occurring in overlapping time intervals.

[0133] In some embodiments, the transcription may be provided to the television **660** to be presented as closed-captioning. In these and other embodiments, the transcription may be presented in a similar manner as closed-captioning that is provided by a media provider in a video stream. In these and other embodiments, the transcription and the video stream may not be combined but may be passed together to the television **660**.

[0134] In some embodiments, the adapter device **650** may be configured to stop relaying the video stream to the television **660** in response to receiving transcript data from the device **610**. In these and other embodiments, the adapter device **650** may be configured to send a transcription to the television **660** for display in place of the video stream. As a result, the television **660** may display the transcription without the video stream. In some embodiments, the adapter device **650** may buffer the video stream while the television **660** is presenting the transcription. In these and other embodiments, the adapter device **650** may be controlled through the device **610**, which may receive commands from a different device, to control the buffered video stream. As a result, the buffered video stream may be played back after the communication session.

[0135] In some embodiments, the adapter device **650** may be configured to provide the transcription of transcript data when no video stream is being provided to the television **660**. In

these and other embodiments, the adapter device **650** may send the transcription to the television **660** without combining the transcription with a video stream.

[0136] In some embodiments, a number of pixels used by the transcription of a total number of pixels of the television **660** may be adjusted based on whether the transcription is being combined with a video stream. For example, when the transcription is combined with a video stream, the transcription may cover a first portion of the pixels of the video stream so that the transcription covers a first portion of the television **660**. When the transcription is not combined with a video stream, the transcription may cover a second portion of pixels in a stream provided to the television **660** so that the transcription covers a second portion of the television **660**. In these and other embodiments, the first portion of the pixels may be less than the second portion of the pixels and the first portion of the television **660** may be less than the second portion of the television **660**. For example, the first portion may be less than ten, twenty, thirty, or fifty percent and the second portion may be more than thirty, forty, fifty, seventy, or eighty-five percent. For example, when the transcription is combined with a video stream, by way of example, twenty words of the transcription may be displayed at one time. In contrast, when the transcription is not combined with a video stream, by way of example, fifty words of the transcription may be displayed at one time.

[0137] Alternatively or additionally, a font size of the transcription may be adjusted based on whether the transcription is combined with a video stream. For example, the font size of the transcription may be increased when the transcription is not combined with the video stream. In these and other embodiments, a number of words of the transcription displayed at one time may be the same whether the transcription is combined or is not combined with the video stream.

[0138] In some embodiments, the adapter device **650** may be configured to control the television **660**. For example, the adapter device **650** may issue commands to the television **660** that may include turning on, coming to an awake state from a sleep state, adjusting display settings, such as contrast and brightness, and adjusting volume levels, among other commands.

[0139] For example, when the television **660** is not displaying images, in response to an indication from the device **610**, the adapter device **650** may issue a command to the television **660** to turn-on. In these and other embodiments, the television **660** may not be displaying images because the television **660** is turned-off, in a sleep or hibernating state, or otherwise not displaying images.

[0140] The indication from the device **610** provided to the adapter device **650** may include the transcript data. Alternatively or additionally, the indication from the device **610** may be in response to the device **610** establishing a communication session before local or remote audio is received during the communication session that may result in transcript data. Alternatively or additionally, the indication from the device **610** may be in response to the device **610** providing audio to a transcription system when the device **610** is prepared to direct transcription data to the television **660**. In these and other embodiments, directing the television to come to a state ready to display images before transcript data is received by the adapter device **650** may help to ensure that a transcription of the transcript data may be provided to the television **660** and presented to a user without a portion of the transcription not being displayed as the television **660** is preparing to display images. Alternatively or additionally, the adapter device **650** may buffer the transcription as the adapter device **650** waits for the television **660** to be prepared to display images.

[0141] The adapter device **650** may be further configured to control a volume level of the television **660**. In these and other embodiments, the adapter device **650** may adjust a volume level of the television **660**, such as decreasing a volume level of the television **660**, in response to an indication from the device **610**. In some embodiments, the volume level may be decreased such that the volume level is muted. The device **610** may be configured to send an indication to the adapter device **650** in response to receiving a communication request, establishing a communication session, obtaining audio, sending audio to a transcription system, or obtaining transcript data, among others.

[0142] In some embodiments, an adjustment of the volume level of the television **660** may depend

on other networked devices that are participating in a communication session directed by the device **610**. For example, when a first networked device is participating in a communication session, the device **610** may indicate to the adapter device **650** to adjust the television to a first volume level. In contrast, when a second networked device is participating in a communication session, the device **610** may indicate to the adapter device **650** to adjust the television to a second volume level that is different than the first volume level. For example, the volume level of the television when the first networked device is a mobile phone may be higher than the volume level of the television when the first networked device is a tablet. In these and other embodiments, a location of a networked device participating in a communication session in relation to the location of the television **660** may result in an adjustment of the volume level of the television **660**. Alternatively or additionally, an adjustment of the display settings of the television **660** may depend on other networked devices that are participating in a communication session directed by the device **610**.

[0143] In some embodiments, an adjustment of font size of a transcription displayed by the television **660** may depend on other networked devices that are participating in a communication session directed by the device **610**. For example, when a first networked device is participating in the communication session, the transcription may be configured with a larger font size than when a second networked device is participating in the communication session.

[0144] In some embodiments, the networked devices that result in the transcription having a larger font size may be selected based on a location of the networked devices in relation to the television **660** as determined by the device **610**. In these and other embodiments, the device **610** may determine a location of a networked device based on a wireless network communication, signal strength over wireless or wired networks, and user input, among others. Alternatively or additionally, the networked devices that result in the transcription having a larger font size may be selected based on a user assigned to a networked device participating in the communication session. For example, a user of a hearing-aid networked device that is registered with the device **610** and participating in the communication session may have worse eyesight than a user of another networked device that is registered with the device **610**. Thus, when the hearing-aid networked device is participating in the communication session, the transcription may be displayed in a larger font size. Alternatively or additionally, the device **610** may determine that a user is using a networked device and is participating in a communication session based on voice characteristics and log-in information obtained by the networked device, such as user-ID, biometrics, etc. Based on a user using a networked device participating in the communication session, the font size of the transcription may be larger or smaller. In these and other embodiments, the device **610** and/or the adapter device **650** may automatically adjust the volume, font size, display settings, and other configurations based on the networked devices participating in a communication session without input from a user.

[0145] In some embodiments, the adapter device **650** may receive audio of a communication session from the device **610**. In these and other embodiments, the adapter device **650** may send the audio to the television **660** to be broadcast by the television. In some embodiments, the first cable **670** may already be providing audio to the television **660** as received over the first cable **670**. In these and other embodiments, the adapter device **650** may be configured to exchange the audio received from the first cable **670** with the audio received by the device **610** and send the audio from the device **610** to the television **660**. As a result, the audio broadcast by the television **660** may not correspond with the video stream displayed by the television **660** but with the transcription displayed by the television **660**.

[0146] Modifications, additions, or omissions may be made to the environment **600** without departing from the scope of the present disclosure. For example, in some embodiments, the environment **600** may not include the adapter device **650**. In these and other embodiments, the device **610** may perform the operations of the adapter device **650** and be directly coupled with the television over a wired or wireless connection, such as an 802.11 connection, a HDMI connection,

or some other connection. In these and other embodiments, the device **610** may direct the television **660** to display a transcription. Alternatively or additionally, some of the operations performed by the adapter device **650** may be performed by the television **650** and others of the operations may be performed by the device **610**. For example, the device **610** may send commands to the television **610** and the television **610** may combine the transcription with a video signal to display on the television **610**.

[0147] FIG. **7** is a flowchart of another example method **700** to present transcripts of a communication. The method **700** may be arranged in accordance with at least one embodiment described in the present disclosure. The method **700** may be performed, in some embodiments, by a device or system, such as the device **110**, the device **200**, the device **310**, and/or the device **510**, or another device. In these and other embodiments, the method **700** may be performed based on the execution of instructions stored on one or more non-transitory computer-readable media. Although illustrated as discrete blocks, various blocks may be divided into additional blocks, combined into fewer blocks, or eliminated, depending on the desired implementation.

[0148] The method **700** may begin at block **702**, where a request for a communication session may be obtained from a remote device. At block **704**, in response to obtaining the request, a communication session notification may be sent to a first local device.

[0149] At block **706**, a communication session initiation indication may be obtained from the first local device based on user input obtained by the first local device. In some embodiments, the user input may be in response to the communication session notification. At block **708**, in response to obtaining a communication session initiation, the communication session may be established with the remote device.

[0150] At block **710**, after establishing the communication session with the remote device, remote audio may be obtained from the remote device. At block **712**, the remote audio received from the remote device may be directed to a remote transcription system and to a second local device.

[0151] At block **714**, transcript data may be obtained from the remote transcription system based on the remote audio. The transcript data may include a transcription of the remote audio. At block **716**, the transcript data may be directed to a third local device. In some embodiments, the transcript data is only directed to the third local device such that it is not directed to the second local device.

[0152] It is understood that, for this and other processes, operations, and methods disclosed herein, the functions and/or operations performed may be implemented in differing order. Furthermore, the outlined functions and operations are only provided as examples, and some of the functions and operations may be optional, combined into fewer functions and operations, or expanded into additional functions and operations without detracting from the essence of the disclosed embodiments.

[0153] For example, in some embodiments, the method **700** may further include obtaining first audio from a fourth local device that does not obtain the transcript data and directing the first audio to the remote device as part of the communication session with the remote device.

[0154] In some embodiments, the method **700** may further include directing the first audio obtained from the fourth local device to the second local device. Alternatively or additionally, the method **700** may include obtaining second audio from one or more of: the first local device, the second local device, and the third local device and directing the second audio to the remote device as part of the communication session with the remote device.

[0155] In some embodiments, the communication session may be a video communication session. In these and other embodiments, the method **700** may further include, after establishing the communication session with the remote device, obtaining remote video from the remote device and directing the remote video to the second local device.

[0156] FIG. **8** is a flowchart of another example method **800** to present transcripts of a communication. The method **800** may be arranged in accordance with at least one embodiment described in the present disclosure. The method **800** may be performed, in some embodiments, by a

device or system, such as the device **110**, the device **200**, the device **310**, and/or the device **510**, or another device. In these and other embodiments, the method **800** may be performed based on the execution of instructions stored on one or more non-transitory computer-readable media. Although illustrated as discrete blocks, various blocks may be divided into additional blocks, combined into fewer blocks, or eliminated, depending on the desired implementation.

[0157] The method **800** may begin at block **802**, where information from multiple local devices may be obtained. The information may indicate a configuration of each of the multiple local devices with respect to a capability to: receive and broadcast remote audio and display transcriptions of the remote audio.

[0158] At block **804**, a communication session may be established with a remote device. At block **806**, after establishing the communication session with the remote device, the remote audio may be obtained from the remote device.

[0159] At block **808**, the remote audio may be directed to a first local device of the multiple local devices based on the first local device being configured to receive and broadcast remote audio. In some embodiments, the first local device being configured to receive and broadcast the remote audio may be indicated by information obtained about the first local device at block **802**.

[0160] At block **810**, transcript data that includes a transcription of the remote audio may be directed to a second local device of the multiple local devices based on the second local device being configured to display transcriptions of the remote device audio. In some embodiments, the first local device may not be configured to display transcriptions of the remote device audio such that the transcript data is not directed to the first local device. In some embodiments, the first local device not being configured to display transcriptions may be indicated by information obtained about the first local device at block **802**. Additionally or alternatively, the configurations of the second local device with respect to receiving or presenting audio or transcription data may be indicated by information obtained about the second local device at block **802**.

[0161] It is understood that, for this and other processes, operations, and methods disclosed herein, the functions and/or operations performed may be implemented in differing order. Furthermore, the outlined functions and operations are only provided as examples, and some of the functions and operations may be optional, combined into fewer functions and operations, or expanded into additional functions and operations without detracting from the essence of the disclosed embodiments.

[0162] For example, in some embodiments, the method **800** may further include directing the remote audio received from the remote device to a remote transcription system and obtaining the transcript data from the remote transcription system based on the remote audio.

[0163] Alternatively or additionally, the method **800** may further include detecting the multiple local devices and after detecting the multiple local devices, establishing a network connection with each of the multiple local devices. In these and other embodiments, the information indicating the configuration of each of the multiple local devices may be obtained after establishing a network connection with each of the multiple local devices.

[0164] In some embodiments, the communication session may be a video communication session and the information may indicate that a configuration of each of the multiple local devices with respect to a capability to: receive and broadcast remote audio, receive and display remote video, and display transcriptions of the remote device audio. In these and other embodiments, the method **800** may further include after establishing the communication session with the remote device, obtaining remote video from the remote device and directing the remote video to the second local device based on the second local device being configured to receive and display remote video.

[0165] In some embodiments, the information may indicate that a configuration of each of the multiple local devices with respect to a capability to: receive and broadcast remote audio, receive and transmit local audio, and display transcriptions of the remote device audio. In these and other embodiments, the method **800** may further include after establishing the communication session



with the remote device, obtaining local audio from a third local device of the multiple local devices that is configured to receive and transmit local audio and directing the local audio to the remote device.

[0166] FIG. **9** is a flowchart of another example method **900** to present transcripts of a communication. The method **900** may be arranged in accordance with at least one embodiment described in the present disclosure. The method **900** may be performed, in some embodiments, by a device or system, such as the device **110**, the device **200**, the device **310**, and/or the device **510**, or another device. In these and other embodiments, the method **900** may be performed based on the execution of instructions stored on one or more non-transitory computer-readable media. Although illustrated as discrete blocks, various blocks may be divided into additional blocks, combined into fewer blocks, or eliminated, depending on the desired implementation.

[0167] The method **900** may begin at block **902**, where a communication session with a remote device may be established over a network. In some embodiments, the network may be selected from a group including: a cellular network, a public switched telephone network, and an Internet Protocol (IP) network.

[0168] At block **904**, after establishing the communication session with the remote device, remote audio may be obtained from the remote device that is provided by the remote device as part of the communication session.

[0169] At block **906**, the remote audio received from the remote device may be directed to a local device participating in the communication session and to a remote transcription system. At block **908**, transcript data may be obtained from the remote transcription system based on the remote audio. The transcript data may include a transcription of the remote audio.

[0170] At block **910**, the transcript data may be directed to a television for presentation of the transcription of the remote audio by the television such that the transcription of the remote audio is presented substantially aligned with presentation of the remote audio by the local device. In these and other embodiments, the transcript data may be directed to the television by way of an adapter device.

[0171] It is understood that, for this and other processes, operations, and methods disclosed herein, the functions and/or operations performed may be implemented in differing order. Furthermore, the outlined functions and operations are only provided as examples, and some of the functions and operations may be optional, combined into fewer functions and operations, or expanded into additional functions and operations without detracting from the essence of the disclosed embodiments.

[0172] For example, in some embodiments, the method **900** may further include combining the transcript data with a television video stream and providing the combined transcript data and television video stream to the television to present the transcription of the remote audio. In these and other embodiments, combining the transcript data and the television video stream may include overlaying the transcription of the remote audio on the television video stream.

[0173] In some embodiments, the method **900** may further include in response to directing the transcript data to a television, reducing a level of television audio output by the television. Alternatively or additionally, the method **900** may further include in response to directing the transcript data to the television, directing the television to come to an awake state.

[0174] In some embodiments, the method **900** may further include obtaining local audio from the local device and directing the local audio to the remote device over the network.

[0175] FIG. **10** is a flowchart of another example method **1000** to present transcripts of a communication. The method **1000** may be arranged in accordance with at least one embodiment described in the present disclosure. The method **1000** may be performed, in some embodiments, by a device or system, such as the device **110**, the device **200**, the device **310**, and/or the device **510**, or another device. In these and other embodiments, the method **1000** may be performed based on the execution of instructions stored on one or more non-transitory computer-readable media.

Although illustrated as discrete blocks, various blocks may be divided into additional blocks, combined into fewer blocks, or eliminated, depending on the desired implementation.

[0176] The method **1000** may begin at block **1002**, where audio, obtained from a communication session established over a first network interface, may be directed to a remote transcription system. The first network interface may be configured to direct first network traffic over a first network of a first network type.

[0177] At block **1004**, an indication of multiple communication devices available to participate in the communication session may be obtained. In some embodiments, the communication session may be a video communication session.

[0178] At block **1006**, the audio may be directed to a second network interface for transmission to at least a first one of the multiple communication devices. The second network interface may be configured to direct second network traffic over a second network of a second network type that is different from the first network type.

[0179] In some embodiments, the first network may be a public switched telephone network and the second network may be a local wireless network. Alternatively or additionally, the first network may be a cellular network and the second network may be a local wireless network. Alternatively or additionally, the first network may be an Internet Protocol (IP) network and the second network may be a local wireless network.

[0180] In some embodiments, the audio may be directed to the remote transcription system over a third network of a third network type that is different from the first network type and the second network type.

[0181] At block **1008**, transcript data from the remote transcription system based on the audio may be obtained. The transcript data may include a transcription of the audio.

[0182] At block **1010**, the transcript data may be directed to the second network interface for transmission to at least a second one of the multiple communication devices.

[0183] In some embodiments, the first one of the multiple communication devices and the second one of the multiple communication devices may be one of the following: a television, a set-top box, a smart phone, a tablet, a personal health care device, and a telephone console, among other devices.

[0184] It is understood that, for this and other processes, operations, and methods disclosed herein, the functions and/or operations performed may be implemented in differing order. Furthermore, the outlined functions and operations are only provided as examples, and some of the functions and operations may be optional, combined into fewer functions and operations, or expanded into additional functions and operations without detracting from the essence of the disclosed embodiments.

[0185] For example, in some embodiments, the method **1000** may further include obtaining second audio from a second communication session separate from the communication session over the first network interface and directing the second audio to the remote transcription system. The method **1000** may also include obtaining a second indication of second multiple communication devices available to participate in the second communication session and directing the second audio to the second network interface for transmission to at least a first one of the second multiple communication devices. The first one of the second multiple communication devices may be different than the first one of the multiple communication devices.

[0186] The method **1000** may also include obtaining second transcript data from the remote transcription system of the second audio. The second transcript data may include a transcription of the second audio. The method **1000** may further include directing the second transcript data to the second network interface for transmission to at least a second one of the second multiple communication devices. In some embodiments, the second one of the multiple communication devices may be different than the second one of the second multiple communication devices.

[0187] As indicated above, the embodiments described herein may include the use of a special

purpose or general-purpose computer (e.g., the processor **210** of FIG. 2) including various computer hardware or software modules, as discussed in greater detail below. Further, as indicated above, embodiments described herein may be implemented using computer-readable media (e.g., the memory **212** of FIG. 2) for carrying or having computer-executable instructions or data structures stored thereon.

[0188] In some embodiments, the different components, modules, engines, and services described herein may be implemented as objects or processes that execute on a computing system (e.g., as separate threads). While some of the systems and methods described herein are generally described as being implemented in software (stored on and/or executed by general purpose hardware), specific hardware implementations or a combination of software and specific hardware implementations are also possible and contemplated.

[0189] In accordance with common practice, the various features illustrated in the drawings may not be drawn to scale. The illustrations presented in the present disclosure are not meant to be actual views of any particular apparatus (e.g., device, system, etc.) or method, but are merely idealized representations that are employed to describe various embodiments of the disclosure. Accordingly, the dimensions of the various features may be arbitrarily expanded or reduced for clarity. In addition, some of the drawings may be simplified for clarity. Thus, the drawings may not depict all of the components of a given apparatus (e.g., device) or all operations of a particular method.

[0190] Terms used herein and especially in the appended claims (e.g., bodies of the appended claims) are generally intended as “open” terms (e.g., the term “including” should be interpreted as “including, but not limited to,” the term “having” should be interpreted as “having at least,” the term “includes” should be interpreted as “includes, but is not limited to,” etc.).

[0191] Additionally, if a specific number of an introduced claim recitation is intended, such an intent will be explicitly recited in the claim, and in the absence of such recitation no such intent is present. For example, as an aid to understanding, the following appended claims may contain usage of the introductory phrases “at least one” and “one or more” to introduce claim recitations.

However, the use of such phrases should not be construed to imply that the introduction of a claim recitation by the indefinite articles “a” or “an” limits any particular claim containing such introduced claim recitation to embodiments containing only one such recitation, even when the same claim includes the introductory phrases “one or more” or “at least one” and indefinite articles such as “a” or “an” (e.g., “a” and/or “an” should be interpreted to mean “at least one” or “one or more”); the same holds true for the use of definite articles used to introduce claim recitations.

[0192] In addition, even if a specific number of an introduced claim recitation is explicitly recited, those skilled in the art will recognize that such recitation should be interpreted to mean at least the recited number (e.g., the bare recitation of “two recitations,” without other modifiers, means at least two recitations, or two or more recitations). Furthermore, in those instances where a convention analogous to “at least one of A, B, and C, etc.” or “one or more of A, B, and C, etc.” is used, in general such a construction is intended to include A alone, B alone, C alone, A and B together, A and C together, B and C together, or A, B, and C together, etc. For example, the use of the term “and/or” is intended to be construed in this manner.

[0193] Further, any disjunctive word or phrase presenting two or more alternative terms, whether in the description, claims, or drawings, should be understood to contemplate the possibilities of including one of the terms, either of the terms, or both terms. For example, the phrase “A or B” should be understood to include the possibilities of “A” or “B” or “A and B.”

[0194] However, the use of such phrases should not be construed to imply that the introduction of a claim recitation by the indefinite articles “a” or “an” limits any particular claim containing such introduced claim recitation to embodiments containing only one such recitation, even when the same claim includes the introductory phrases “one or more” or “at least one” and indefinite articles such as “a” or “an” (e.g., “a” and/or “an” should be interpreted to mean “at least one” or “one or

more”); the same holds true for the use of definite articles used to introduce claim recitations. [0195] Additionally, the use of the terms “first,” “second,” “third,” etc., are not necessarily used herein to connote a specific order or number of elements. Generally, the terms “first,” “second,” “third,” etc., are used to distinguish between different elements as generic identifiers. Absence a showing that the terms “first,” “second,” “third,” etc., connote a specific order, these terms should not be understood to connote a specific order. Furthermore, absence a showing that the terms first,” “second,” “third,” etc., connote a specific number of elements, these terms should not be understood to connote a specific number of elements. For example, a first widget may be described as having a first side and a second widget may be described as having a second side. The use of the term “second side” with respect to the second widget may be to distinguish such side of the second widget from the “first side” of the first widget and not to connote that the second widget has two sides.

[0196] All examples and conditional language recited herein are intended for pedagogical objects to aid the reader in understanding the invention and the concepts contributed by the inventor to furthering the art and are to be construed as being without limitation to such specifically recited examples and conditions. Although embodiments of the present disclosure have been described in detail, it should be understood that the various changes, substitutions, and alterations could be made hereto without departing from the spirit and scope of the present disclosure.

## Claims

**1-20.** (canceled)

**21.** A method comprising: obtaining, at a first device, transcript data of audio data, the transcript data including a transcription of the audio data and the transcript data being generated by a remote transcription system; directing, to a second device, at least a first portion of the transcript data for presentation of the first portion of the transcript data by the second device; and directing, to a third device, at least a second portion of the transcript data for presentation of the second portion of the transcript data by the third device, wherein the first device, the second device, and the third device are separate devices that are located within a same structure.

**22.** The method of claim 21, wherein neither the second device nor the third device obtain the audio data.

**23.** The method of claim 21, further comprising: obtaining, by the first device, the audio data; and directing the audio data to the remote transcription system for generation of the transcript data.

**24.** The method of claim 21, further comprising directing, by the first device, broadcasting of the audio data by a fourth device.

**25.** The method of claim 21, further comprising: obtaining, at the first device, video data that corresponds to the audio data; and directing the video data to one or more of the second device and the third device for presentation of the video data.

**26.** The method of claim 25, wherein the video data is presented by the one or more of the second device and the third device concurrently with the transcript data.

**27.** The method of claim 21, wherein the audio data results from a communication session between the first device and a fourth device that is not located in the structure.

**28.** The method of claim 21, wherein the first device is wirelessly connected to the second device and the third device.

**29.** A device comprising: one or more network interfaces, the one or more network interfaces configured to: obtain transcript data of audio data, the transcript data including a transcription of the audio data and the transcript data being generated by a remote transcription system; direct, to a second device, at least a first portion of the transcript data for presentation of the first portion of the transcript data by the second device; and direct, to a third device, at least a second portion of the transcript data for presentation of the second portion of the transcript data by the third device,

wherein the device, the second device, and the third device are separate devices that are located within a same structure.

- 30.** The device of claim 29, wherein neither the second device nor the third device obtain the audio data.
  - 31.** The device of claim 29, wherein the one or more network interfaces are further configured to: obtain the audio data; and direct the audio data to the remote transcription system for generation of the transcript data.
  - 32.** The device of claim 29, wherein the one or more network interfaces are further configured to: obtain video data that corresponds to the audio data; and direct the video data to one or more of the second device and the third device for presentation of the video data.
  - 33.** The device of claim 29, wherein the audio data results from a communication session between the device and a fourth device that is not located in the structure.
  - 34.** The device of claim 29, wherein the device is wirelessly connected to the second device and the third device.
  - 35.** One or more non-transitory computer-readable media that store instructions that, when executed by a device, direct the device to perform operations, the operations comprising: obtain transcript data of audio data, the transcript data including a transcription of the audio data and the transcript data being generated by a remote transcription system; direct, to a second device, at least a first portion of the transcript data for presentation of the first portion of the transcript data by the second device; and direct, to a third device, at least a second portion of the transcript data for presentation of the second portion of the transcript data by the third device, wherein the device, the second device, and the third device are separate devices that are located within a same structure.
  - 36.** The computer-readable media of claim 35, wherein neither the second device nor the third device obtain the audio data.
  - 37.** The computer-readable media of claim 35, wherein the operations further comprise: obtain the audio data; and direct the audio data to the remote transcription system for generation of the transcript data.
  - 38.** The computer-readable media of claim 35, wherein the operations further comprise: obtain video data that corresponds to the audio data; and direct the video data to one or more of the second device and the third device for presentation of the video data.
  - 39.** The computer-readable media of claim 35, wherein the audio data results from a communication session between the device and a fourth device that is not located in the structure.
  - 40.** The computer-readable media of claim 35, wherein the device is wirelessly connected to the second device and the third device.
-