



(19) **United States**

(12) **Patent Application Publication**
Wegener et al.

(10) **Pub. No.: US 2025/0249166 A1**

(43) **Pub. Date:** **Aug. 7, 2025**

(54) **PROCESSING A BIOLOGICAL CELL SUSPENSION FROM A SOURCE**

C12M 1/00 (2006.01)

C12N 5/078 (2010.01)

(71) Applicant: **Fenwal, Inc.**, Lake Zurich, IL (US)

(52) U.S. Cl.

CPC *A61M 1/3692* (2014.02); *A61M 1/0209*
(2013.01); *A61M 1/0272* (2013.01); *A61M*
1/0281 (2013.01); *C12N 5/0634* (2013.01);
A61M 1/3693 (2013.01); *A61M 2205/3379*
(2013.01); *C12M 47/04* (2013.01); *C12N*
2509/00 (2013.01)

(72) Inventors: **Christopher J. Wegener**, Libertyville, IL (US); **Steven C. Binninger**, Evanston, IL (US); **Alaina Schlinker**, Chicago, IL (US); **Bret Olson**, Evanston, IL (US)

(73) Assignee: **Fenwal, Inc.**, Lake Zurich, IL (US)

(21) Appl. No.: 19/090,910

(22) Filed: **Mar. 26, 2025**

Related U.S. Application Data

(63) Continuation of application No. 16/143,849, filed on Sep. 27, 2018, now Pat. No. 12,296,086.

(60) Provisional application No. 62/565,959, filed on Sep. 29, 2017.

Publication Classification


(51) **Int. Cl.**


A61M 1/36 (2006.01)

A61M 1/02 (2006.01)


ABSTRACT

A system and method for processing a biological cell suspension from a source to provide a product in a retentate container comprises a disposable fluid circuit and a reusable hardware unit. The reusable hardware unit comprises a controller which stores processing parameters comprising an estimated volume of biological cell suspension in the source and a concentration of cells in the biological cell suspension. The controller calculates a number of draws of the biological cell suspension and a volume of each draw and calculates a pump speed based on a received processing parameter. The controller controls pumping of the processing solution into the disposable fluid circuit to prime the disposable fluid circuit. The controller directs the withdrawal of the biological cell suspension from the source in batches in accordance with the calculated number of draws and volume of each draw.





உ






FIG. 3




FIG. 4

FIG. 5




FIG. 6

Multiple Containers




FIG 7

Batch Processing




FIG. 8

PROCESSING A BIOLOGICAL CELL SUSPENSION FROM A SOURCE

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] The present application is a continuation of application Ser. No. 16/143,849, filed Sep. 27, 2018, which claims the benefit of U.S. Provisional Application No. 62/565,949, filed Sep. 29, 2017, both of which are incorporated by reference herein in their entireties.

FIELD OF THE DISCLOSURE

[0002] The present disclosure is directed to systems and methods for processing suspensions of biological fluid. More particularly, the present disclosure is directed to systems and methods for processing large volumes of biological cell suspensions using a single fluid circuit. Even more particularly, the present disclosure is directed to systems and methods for automatically controlling the processing of large volumes of biological cell suspensions from one or more containers of such suspensions.

BACKGROUND

[0003] Biological cells may be processed for a variety of reasons. For example, blood cells previously collected may be washed and/or concentrated for subsequent use as part of a therapy. The processing of biological fluids such as biological cells, blood or blood components typically involves using a reusable processing apparatus ("hardware") and a disposable fluid circuit adapted for mounting or other association with the hardware. The fluid circuit typically includes, among other things, a separation device, (plastic) containers and associated tubing that defines a flow path through the circuit.

[0004] The processing of biological cell suspensions for the purpose of arriving at a therapeutically useful concentration of cells often requires working with large volumes of source fluid and/or cryopreserved products. Large volumes of source fluid are often provided in multiple source containers or a single large-volume source container. In neither case, the handling of large volumes presents challenges in managing the volume of the fluid to be processed within the confines of the disposable fluid circuit and/or the limits of the hardware and software capabilities. Often, in order to arrive at an effective concentration of cells, multiple procedures using multiple fluid circuits are carried out with the collected cells from each procedure being pooled together into a final product. This and other steps may also require additional human intervention or monitoring of the cell processing procedure(s) which may add time to the overall procedure. In the case of cryopreserved blood products, care must be exercised to ensure that previously frozen products do not thaw too quickly. Thus, the processing of multiple containers of cryopreserved products is typically performed one container at a time with separate disposable fluid circuits and separate entry of processing parameters required for each source container.

[0005] Accordingly, it would be desirable to have a more automated system that allows for one-time data entry for large volumes of biological cell suspensions to be processed, whether from multiple source containers or a single, larger-volume source container. It would be desirable to allow parameters such as starting concentrations of source fluid,

target concentrations of the final product, total volumes of fluid to be processed and/or the number of source containers to be entered and received by the system at the beginning of the processing procedure, and have the automated system determine the manner in which source fluid is drawn from the source container(s). It would also be desirable to provide a system and method that requires a unitary fluid circuit that is adapted for use with such large volumes of source fluid, whether provided in one or multiple source containers.

SUMMARY

[0006] In one aspect, the present disclosure is directed to a system for processing biological cell suspensions. The system includes a disposable fluid circuit that includes a separation device, a fluid flow path in flow communication with the separation device, and one more fluid access devices for establishing fluid communication between the flow path and one or more source containers of a biological cell suspension. The system also includes a reusable hardware unit that houses a separation device drive unit for receiving the separation device, an operator input and a controller coupled to the input. The controller is configured (a) to receive a processing parameter such as the total volume of biological cell suspension to be processed from one or more source containers (b) to receive a processing parameter such as the concentration of cells in the one or more source containers and (c) to calculate the number of draws from the one or more source containers and the volume of each said draw.

[0007] In another aspect, the present disclosure is directed to an automated method for processing a biological cell suspension from one or more source containers of a biological cell suspension. The method includes at least the steps of (a) receiving a processing parameter such as the total volume of biological cell suspension to be processed from one or more source containers (b) receiving a processing parameter such as the concentration of cells in said one or more source containers (c) calculating the number of draws from the one or more source containers and the volume of each the draws and (d) drawing the biological cell suspension from the one or more source containers.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] FIG. 1 is a schematic view of one embodiment of a disposable fluid circuit for use in the systems and methods described herein;

[0009] FIG. 2 is a schematic view of another embodiment of disposable fluid circuit with multiple source containers for use in the systems and methods described herein;

[0010] FIG. 3 is a perspective view of the separation device, with a portion of the housing wall broken away;

[0011] FIG. 4 is a view of the front panel of the reusable processing apparatus;

[0012] FIG. 5 is another view of the front panel of a reusable processing apparatus with a disposable fluid circuit mounted thereon;

[0013] FIG. 6 is a schematic view of the control circuitry, including the controller, of the device of FIGS. 3 and 4;

[0014] FIG. 7 is a flow chart setting forth steps of the method of sequential processing of multiple containers of a biological cell suspension in accordance with the systems shown and described herein; and

[0015] FIG. 8 is a flow chart setting forth steps of the method of batch processing of a single, large volume container of a biological cell suspension in accordance with the systems shown and described herein.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0016] The methods and systems disclosed herein typically employ a reusable separation apparatus and one or more disposable fluid circuits adapted for association with the reusable apparatus. The reusable separation apparatus may be any apparatus that can provide for the automated processing of biological cells, as well as automated preparation, such as priming, of the system prior to the processing of cells. By “automated,” it is meant that the apparatus can be pre-programmed to carry out the system priming and cell processing steps without substantial operator involvement. Of course, even in the automated system of the present disclosure, it will be understood that some operator involvement will be required, including the loading or mounting of the disposable fluid circuit(s) onto the reusable apparatus, attachment of one or more source containers and entering certain processing parameters. Additional manual steps may be required as well. However, the reusable apparatus can be programmed to perform the processing of the biological cells through the disposable circuit(s) described below without substantial operator intervention.

[0017] Examples of a reusable apparatus include the Aurora® Plasmapheresis System and the Lovo Cell Processing System, both sold by Fenwal, Inc., a Fresenius Kabi Company, of Lake Zurich, Illinois. Both the Aurora® Plasmapheresis System and the Lovo Cell Processing System are compact cell processors for washing and concentrating biological fluid such as certain blood cell components. The Lovo Cell Processing System uses a spinning membrane separator. A detailed description of a spinning membrane may be found in U.S. Pat. No. 5,194,145 to Schoendorfer, which is incorporated by reference herein in its entirety, and in International (PCT) Application No. PCT/US2012/028492, filed Mar. 9, 2012, the contents of which is also incorporated herein in its entirety. In addition, systems and methods that utilize a spinning porous membrane are also disclosed in U.S. Provisional Patent Application No. 61/537,856, filed on Sep. 22, 2011, International (PCT) Application No. PCT/US2012/028522, filed Mar. 9, 2012, International (PCT) Application No. PCT/US2012/054859, filed Sep. 12, 2012, and U.S. patent application Ser. No. 14/574,539, filed Dec. 18, 2014, the contents of each are incorporated herein by reference. The references identified above describe a membrane covered spinner having an interior collection system disposed within a stationary shell.

[0018] It will be appreciated that a reusable apparatus utilizing a principle of separation other than a spinning membrane, such as centrifugation, but still requiring a disposable fluid circuit may also be used in the methods and systems described herein.

[0019] Turning first to FIG. 1, the systems described herein preferably include a disposable fluid circuit for use in the processing of the biological fluid (e.g., suspension of biological cells). Fluid circuit 100 is adapted for mounting onto a reusable hardware component, described below. Circuit 100 may include an integrated separation device, such as, but not limited to, the spinning membrane 101 described herein. Circuit 100 may also include filtrate bag or

container 140, retentate or final container or bag 150, and in-process container 122. Disposable fluid circuits of the type described below may further include sampling assemblies (not shown) for collecting samples of biological cells or other intermediate products obtained during the biological fluid processing.

[0020] As will be seen in the Figures and described in greater detail below, the disposable fluid processing circuit includes tubing that defines flow paths throughout the circuit, as well as access sites for sterile or other connection to containers of processing solutions, such as wash solutions, treating agents, and sources of the biological fluid (e.g., cell suspension). As will be apparent from the disclosure herein, a single source container 102 or multiple source containers (102a, 102b, 102c, as shown in FIG. 2) for processing may be attached in sterile fashion to circuit 100.

[0021] As shown in FIGS. 1 and 2, the tubing of circuit 100 includes spaced tubing segments identified by reference numerals 162, 166, 168. The tubing segments are provided for mating engagement with the peristaltic pumps of the reusable hardware apparatus 200, also discussed below and shown, for example, in FIG. 5. The containers and the plastic tubing are made of conventional medical grade plastic that can be sterilized by sterilization techniques commonly used in the medical field, such as, but not limited to, radiation or autoclaving. Plastic materials useful in the manufacture of containers and tubing in the circuits disclosed herein include plasticized polyvinyl chloride. Other useful materials include acrylics. In addition, certain polyolefins may also be used.

[0022] The biological fluid, such as a (biological) cell suspension, to be processed is typically provided in a source container 102, shown in FIG. 1 as (initially) not connected to the disposable set. As noted above and shown in FIG. 2 and discussed in greater view below, one or more source container(s) (102a, 102b, 102c) may be connected (in sterile fashion) at the time of use. In one embodiment, wherein cryopreserved biological cells are to be processed, it may be preferable to connect each container of multiple containers just prior processing to maintain the cells at the desired temperature right up to the time of processing. Source container(s) 102 may include one or more access sites 103, 105, one of which may be adapted for (sterile) connection to fluid circuit 100 at docking site 104. Preferably, source containers may be attached in a sterile manner by employing sterile docking devices, such as the BioWelder, available from Sartorius AG, or the SCD 11B Tubing Welder, available from Terumo Medical Corporation. A second access port 105 may also be provided for extracting fluid from the source containers(s) 102. In accordance with the methods and systems described herein and as previously noted, multiple source containers 102a, 102b, 102c, etc., may be provided for the processing of larger volumes of the biological fluid. While three (3) source containers are shown, it will be appreciated that more (or fewer) than three source containers may be processed in the course of a processing procedure. Alternatively, a single, larger volume source container 102 may be attached in lieu of multiple source containers, as shown in FIG. 1. Depending on the type of cells being processed, and the desired concentration of the final cell product, source containers may vary in volume from “standard” containers capable of accommodating a volume of approximately 250-1000 ml to larger-sized source

containers that can hold many liters of source fluid such as 5, 10, 50 and up to 100 or more liters.

[0023] As shown in FIG. 2, where multiple source containers **102a**, **102b**, and **102c** are to be processed, circuit **100** may optionally include a manifold **107** (shown in dashed lines), or other branched member **109** that receives and communicates with individual source lines **110a**, **110b**, and **110c**. Manifold **107** or other branched member is in fluid communication with primary source line **106**, as shown. Flow through source line **110** (FIG. 1), or multiple, individual source lines **110a**, **110b**, and **110c** may be manually controlled by roller, slide clamp or Roberts-type clamps **111** (FIGS. 1) or **111a**, **111b**, and **111c** (FIG. 2).

[0024] With further reference to FIGS. 1 and 2, tubing (source line) **106** is connected to downstream branched-connector **118**. Branched-connector **118** communicates with tubing **106** and tubing **120**, which provides a fluid flow path from “in-process” container **122**, described in greater detail below. Tubing segment **124** extends from branched-connector **118** and is joined to a port of further downstream branched-connector **126**. A separate flow path defined by tubing **128** is also connected to a port of branched-connector **126**.

[0025] In accordance with the fluid circuit of FIGS. 1 and 2, one or more container(s) **135a/135b** of priming/wash or other processing/treating/buffering solution may be attached to fluid circuit **100**. As further shown in FIGS. 1 and 2, tubing **132a** (defining a flow path) preferably includes and terminates in an access site such as spike connector **134a**. Access sites **134a/134b** are provided to establish flow communication with containers **135a/135b** (shown in FIGS. 1 and 2) of a priming/wash fluid, such as saline or other solution. More preferably, flow communication between tubing **132a** and a container of priming/wash solution may be achieved by sterile connection device, such as, but not limited to, the previously mentioned Terumo SCD 11B. The priming/wash solution flows from the wash fluid source through tubing segment **132a**, and then passes through tubing **128** to the input of the branched-connector **126** described above. The priming/wash solution then flows through tubing segment **124** and source line **106** to one or more source containers (See FIGS. 1 and 2). It should be noted that access site **134b** may be used to establish fluid communication with additional containers of priming/wash solution (as shown) or other solutions and/or agents.

[0026] As further shown in FIGS. 1 and 2, tubing segment **136** defines a flow path connected at one end to branched-connector **126** and to an inlet port **20** of the separator **101**. Preferably, in accordance with the present disclosure, separation device **101** is a spinning membrane separator of the type previously identified and also described in U.S. Pat. No. 5,194,145 and U.S. Pat. No. 5,053,121, which are incorporated herein by reference, U.S. Provisional Patent Application Ser. No. 61/451,903, and PCT/US2012/028522, also previously incorporated herein by reference. In an alternative embodiment, separator **101** may utilize a different separation principle. For example, separator **101** may be a centrifuge.

[0027] As seen in FIGS. 1-3, spinning membrane separation device **101** has at least two outlet ports. Outlet **46** of separator **101** receives the separated filtrate and is connected to tubing **138**, which defines a flow path to filtrate/cell

container **140**. The filtrate/cell container may further include connection port **141** for sampling the contents within the filtrate/cell container **140**.

[0028] Separation device **101** preferably includes a second outlet **48** that is connected to tubing segment **142** for directing the retentate to branched-connector **144**, which branches into and defines a flow path to one or more in-process containers **122** and/or a flow path to a “final” retentate container **150**.

[0029] Turning to FIG. 3, spinning membrane separation device **101** is shown in greater detail. Such a device **101** forms part of the disposable circuit **100**.

[0030] Device **101** includes a generally cylindrical housing **12**, mounted concentrically about a longitudinal vertical central axis. An internal member **14** is mounted concentric with the central axis **11**. Housing **12** and internal member **14** are relatively rotatable. In the preferred embodiment, as illustrated, housing **12** is stationary and internal member **14** is a rotating spinner that is rotatable concentrically within cylindrical housing **12**, as shown by the thick arrow in FIG. 5. The boundaries of the flow path are generally defined by gap **16** between the interior surface of housing **12** and the exterior surface of rotary spinner **14**. The spacing between the housing and the spinner is sometimes referred to as the shear gap. The shear gap may be approximately 0.02-0.06 inches (0.05-0.15 cm) and may be of a uniform dimension along axis **11**, for example, where the axis of the spinner and housing are coincident. The shear gap may also vary circumferentially, for example, where the axis of the housing and spinner are offset.

[0031] The shear gap also may vary along the axial direction, for example preferably an increasing gap width in the direction. Such a gap width may range from about 0.02 to about 0.075 inches (0.05-0.19 cm). The gap width could be varied by varying the outer diameter of the rotor and/or the inner diameter of the facing housing surface. The gap width could change linearly or stepwise or in some other manner as may be desired. In any event, the width dimension of the gap is preferably selected so that at the desired relative rotational speed, Taylor-Couette flow, such as Taylor vortices, are created in the gap.

[0032] Biological fluid is fed from an inlet conduit **20** through an inlet orifice **22**, which directs the fluid into the fluid flow entrance region in a path tangential to the circumference about the upper end of the spinner **14**. At the bottom end of the cylindrical housing **12**, the housing inner wall includes an exit orifice **48**. Cylindrical housing **12** is completed by a bottom end housing terminating in an outlet orifice **46** concentric with the central axis.

[0033] In the illustrated embodiment, the surface of the rotary spinner **14** is at least partially, and is preferably substantially or entirely, covered by a cylindrical porous membrane **62**. The membrane **62** may have a nominal pore size between 0.8 and 10 microns (μm), for example. Membranes may be fibrous mesh membranes, cast membranes, track-etched membranes or other types of membranes that will be known to those of skill in the art. For example, in one embodiment, the membrane may have a polyester mesh (substrate) with nylon particles solidified thereon, thereby creating a tortuous path through which only certain sized components will pass. In an embodiment, the nylon membrane may have a pore size of approximately 0.8 μm and a thickness of approximately 150 μm or greater. Membranes of this type will typically retain all cellular components (e.g.,

red blood cells, white blood cells) and certain formed blood components, e.g., platelets. In another embodiment, the membrane may be made of a thin (approximately 10 μm thick) sheet of unsupported polycarbonate, for example, with a pore size of approximately 4.0 μm . In this embodiment, pores (holes) may be cylindrical and larger than those described above. The pores may be sized to allow small formed components (e.g., platelets, microparticles, etc.) to pass, while the desired cells (e.g., white blood cells and larger red blood cells) are collected.

[0034] FIG. 4 shows the front panel 201 of reusable hardware processing apparatus 200. Apparatus 200 may be of compact size suitable for placement on a table top of a lab bench and adapted for easy transport. Alternatively, apparatus 200 may be supported by a pedestal that can be wheeled to its desired location. In any event, as shown in FIG. 3, apparatus 200 includes a plurality of peristaltic pumps, such as pumps 202, 204, and 206 on front panel 201. Pump segments 166, 162, and 168 of the disposable fluid circuit (described above) are selectively associated with peristaltic pumps 202, 204, and 206. The peristaltic pumps articulate with the fluid sets of FIGS. 1 and 2 at the pump segments identified by reference numerals 162, 166, 168 and advance the priming solution and ultimately the cell suspension or other fluid within the disposable set, as will be understood by those of skill in the art. Apparatus 200 also includes clamps 210, 212, 214, 216, and 218. Clamps 210, 212, 214, 216, and 218 are used to control the flow of the cell suspension through different segments of the disposable set.

[0035] Apparatus 200 also includes several sensors to measure various conditions. The output of the sensors is utilized by device 200 to operate one or more processing or wash cycles. One or more pressure transducer sensor(s) 226 may be provided on apparatus 200 and may be associated with a disposable set 100 at certain points to monitor the pressure during a procedure. Pressure transducer 226 may be integrated into an in-line pressure monitoring site (at, for example, tubing segment 136), to monitor pressure inside separator 101. Air detector sensor 238 may also be associated with the disposable set 100, as necessary. Air detector 238 is optional and may be provided to detect the location of fluid/air interfaces. In accordance with the system priming described herein, air detector 238 may be used to generate an alert/alarm which may indicate incomplete priming or insufficient processing, requiring some correction and/or intervention by the operator. This is discussed in further detail below.

[0036] Apparatus 200 includes weight scales 240, 242, 244, 246, 250, and 252 from which the cell container, in-process container, source container, and any additional container(s) (e.g., wash or priming solution container, retentate container, filtrate container, source container) may depend and be weighed. (While apparatus 200 may include multiple weight scales that can accommodate more than one container of a type of fluid (e.g., source, wash, priming etc.), a single weight scale may be used for multiple, sequentially hung source containers as will be described below). The weights of the containers are monitored by weight sensors and recorded during a washing or other procedure, including during the priming steps described herein. Where multiple source containers are to be processed, some of the source containers may be suspended from a standard I.V. pole or the like (in which case scale measurements would not be taken but pump strokes counted). Similarly, an oversized single

container may also be suspended from a separate pole (without a weigh scale that communicates with the system's controller). From measurements of the weight sensors or other parameters, the device, under the direction of the controller, determines whether each container is empty, partially full or full, and controls the components of apparatus 200, such as the peristaltic pumps and clamps 210, 212, 214, 216, 218, 220, 222, and 224. In accordance with the present disclosure, weight sensors may provide volumes of biological fluid in source containers 102 (102a, 102b, 102c, etc.) and monitor the changing volume of priming/wash solutions in containers 135 (a and/orb) during priming, discussed in greater detail below.

[0037] Apparatus 200 includes at least one drive unit or "spinner" 248 (FIG. 3), which causes the indirect driving of the spinning membrane separator 101. Spinner 248 may consist of a drive motor connected and operated by apparatus 200, coupled to turn an annular magnetic drive member including at least a pair of permanent magnets. As the annular drive member is rotated, magnetic attraction between corresponding magnets within the housing of the spinning membrane separator cause the spinner within the housing of the spinning membrane separator to rotate.

[0038] FIG. 6 is a schematic view of the control unit or "controller" 300 included in device 200 of the present disclosure. The controller 300 may include a microprocessor 304 (which may include multiple physical and/or virtual processors). According to other embodiments, the controller 300 may include one or more electrical circuits designed to carry out the actions described herein. In an embodiment, controller 300 may include a microprocessor and other circuits or circuitry. In addition, the controller 300 may include one or more memories 306. The instructions by which the microprocessor 304 is programmed may be stored on the memory 306 associated with the microprocessor 304, which memory/memories 306 may include one or more tangible non-transitory computer readable memories, having computer executable instructions stored thereon, which when executed by the microprocessor 304 may cause the microprocessors 304 to carry out one or more actions as described herein.

[0039] As is also illustrated in FIG. 6, controller 300 may be coupled to one or more of the structures described above, for example, to receive information (e.g., in the form of signals) from these structures or to provide commands (e.g., in the form of signals) to these structures to control the operation of the structures. As illustrated in FIG. 6, the controller 300 may be coupled to the scales 240, 242, 244, 246, 250, 252, etc., (seen in FIG. 3) that hold solution containers or that are provided to collect blood components, the sensors associated with device 200, clamps 210, 212, 214, 216, 218, 220, 222, and the at least one input 302 to receive information from those devices. Additionally, the controller 300 may be coupled to pumps 202, 204, and 206 and the separator drive unit 248 to provide commands to those devices and to control their operation. It may also be possible that the controller 300 receives information from and provides commands to a given structure, such as one of the structures already mentioned. The controller 300 may be directly electrically connected to these structures to be coupled to them, or the controller 300 may be directly connected to other intermediate equipment that is directly connected to these structures to be coupled to them.

[0040] The at least one input **302** may include a number of different devices according to the embodiments described herein. For example, the input **302** could include a keyboard or keypad by which a user may provide information and/or instructions to the controller **300**. Alternatively, the input **302** may be a touch screen, such as may be used in conjunction with a video display **308** that is disposed on the front panel of the device **10**, the video display **308** also being coupled to the controller **300**. The assembly of the input/touch screen **302** and video display **308** may be one of the afore-mentioned structures to which the controller **300** is coupled from which the controller **300** receives information and to which the controller **300** provides commands. According to still other embodiments, the input **302** may be in the form of computer equipment that permits the cell processing system including the controller **300** to communicate (whether via wires, cables, etc. or wirelessly) with other cell processing systems over a local network, or with other cell processing systems or other computer equipment (e.g., a server) over local networks, wide area networks, or the Internet. According to such an embodiment, the input may include an internal transmitter/receiver device.

[0041] The methods of processing large volumes of biological cell suspensions will now be described.

[0042] As discussed, above, cell suspension processing in accordance with methods and systems described herein can be from multiple or single, large volume container. FIG. 7 sets forth steps in processing of a biological cell suspension from multiple containers. Typically, the suspensions contained within multiple source containers are intended to be concentrated (volume-reduced) to arrive at a final concentrated cell product. Such final cell product may be used in a therapeutic treatment of a patient by direct infusion or after being subjected to further processing such as cell culturing, phenotypic cell selection, cryopreservation, as well as other post collection processes as defined by the end user.

[0043] As shown in FIG. 7, processing may commence with the selection of the particular procedure (block **400**). At the outset of the selected procedure, the operator may enter certain product and processing parameters, as shown at block **402**. For example, the operator may enter the concentration of the cells in the multiple source containers and/or the desired concentration of the final cell product. Original cell concentrations may be determined by prior sampling of the cell suspension or by other parameters (e.g., pH, glucose, lactate) that may be indicative of a cell concentration. Alternatively, the cell concentration may be a pre-set, default value typical for the particular cell suspension to be processed. Additional parameters that may be entered by the operator may include the volume of the suspension in each of the multiple containers. The volumes of cell suspension contained in the multiple source containers may be provided in advance of the procedure or can be automatically determined by the system controller based on the weight of the container(s) as measured by the weight scales (**244**, **246**). Where multiple containers of cell suspensions are to be processed, the number of containers may also be entered. Still other parameters that may be selected or entered by the operator is a final concentration and/or volume for the fully processed cell suspension contained in the multiple source containers.

[0044] The controller **300** may receive the processing parameters via the input **302**. As mentioned above, the controller **300** may receive the process parameters by opera-

tor from the memory **306** associated with the controller **300**, some or all of which may be modified by the operator via the input **302**, for example.

[0045] Based on the parameters provided and entered, the system will calculate the processing conditions such as flow rate, pump speeds, volumes of consumed diluent (wash media), volumes of generated filtrate (waste), processing times, washout percentage or fold dilution (e.g., the percentage of original supernatant that has been removed to the filtrate stream) and process residuals for processing the entire volume of the cell suspension provided in the multiple containers. As described in U.S. patent application Ser. No. 15/456,853, the contents of which is incorporated herein by reference, the system, under the direction of the controller, will preferably conduct a preliminary process evaluation i.e., procedure simulation/estimation (block **404**) to determine, among other things, whether the processing conditions for the volume/concentration of the cell suspension are acceptable and/or fall within acceptable or pre-set ranges. For example, in large volume processing, the system may initially predict a higher than desired inlet flow rate in order to arrive at the desired final concentration (which could result in potentially exposing the cells to excessive shear in the tubing). In any event, should the procedure settings result in incompatible conditions, (including, but not limited to a final concentration that cannot be achieved, filtrate production that exceeds the available bag volume), the operator may be alerted to adjust certain parameters and/or add additional collection containers.

[0046] Other actions may be automatically initiated by the controller during the procedure/simulation estimation step (block **404**). For example, if the concentration of cells in one or more source containers exceeds a (pre-set) maximum filter concentration, the system under the direction of the controller will automatically dilute (at block **414**) the "feed" as it flows toward separator **101**.

[0047] Once the procedure/simulation estimation step (block **404**) is completed, the operator installs disposable fluid processing circuit **100** onto reusable hardware unit **200** (block **406**). The system may then undergo a series of installation checks (block **408**). Once these checks are completed, disposable fluid circuit **100** is ready for priming (block **410**). Priming of the fluid circuit may generally proceed as described in Ser. No. 15/600,447, the contents of which are incorporated herein by reference.

[0048] After priming of the fluid circuit, multiple source containers may be connected to the circuit in sterile fashion, as previously described (block **412**) and as shown on FIG. 5. While FIG. 5 shows multiple source containers (**102** (a)-(c)) attached, it is not necessary to attach all source containers simultaneously. More preferably and as shown in FIG. 7 by loop **417**, source containers **102** may be attached to the fluid circuit sequentially, one after another in the course of processing (i.e., as processing of one source container is completed, the next container is attached to the circuit etc. until all source containers have been processed). It will be understood that while the source containers **102** may be attached to circuit **100** one at a time during processing, parameters for source container volume and source concentration for all of the multiple containers **102** to be processed will have been entered or selected at the outset of the procedure e.g., block **402** or otherwise pre-set as an estimated (and typically the same) default value. This allows processing to continue without the need for the operator to

enter source container parameters at the time each container (of multiple source containers) is attached (block 412).

[0049] Once source container 102 has been attached, the system may (optionally) commence the source prime/pre-dilution step (block 414) described above i.e., in the event that the concentration of cells in one or more source containers exceeds a (pre-set) maximum filter concentration, the controller will automatically effect dilution (at block 414) of the “feed” as it flows toward separator 101.

[0050] Processing of the cell suspension from source container 102 proceeds by introducing the cell feed into separator 101 through inlet port 20 and into gap 16 of the separator where under the influence of the spinning membrane, the cell suspension is separated into concentrated cells (retentate) which exit through one of the outlets to in-process container 122 (block 416), and filtrate which passes through the pores of the spinning membrane and exits through a different outlet to waste/filtrate container 140.

[0051] As the source container parameters such as, but not limited to, source volume are entered or selected (by default) at the outset of processing (block 402), the system will recognize when the entire or substantially the entire contents of the source container has been processed. Alternatively, the system controller may receive information by weigh scales 244, 246 or air detector 238. The controller may then effect the source container rinsing step of block 418 wherein source container 102a may be rinsed with a rinsing solution (such as saline from container 135) and collected in the in-process container 122. Also, once the entered source volume has been processed, as determined by the controller from parameters entered at block 402 and/or based on reading from weigh scales 244, 246 conveyed to controller 300, the operator may attach the next source container 102b, if not previously attached. The controller may be configured to pause processing for a selected period of time to allow the operator to attach the next in-sequence container without additional data entry. As shown by loop 417 in FIG. 7, sequential processing (steps in blocks 414, 416, 418) of multiple source containers are repeated for each container until the entire volume of the cell suspension in all of the source containers 102 has been processed, with the retentate being collected in in-process container 122.

[0052] Depending on the desired targeted concentration for the final product entered at the outset of the procedure (block 402), the retentate residing in in-process container 122 (which is the combined cell output of the multiple source containers) may be further processed in a final cycle or in one or more intermediate cycles before undergoing the final cycle, as shown in FIG. 7. Retentate residing in in-process container 122 may be diluted (block 420) to below a maximum filter concentration or a target dilution volume predetermined by the operator and subjected to a final cycle (block 422) wherein the retentate is introduced for a final time into separator 101 where it is concentrated (volume-reduced) and expressed to one or more final container(s) 150 (block 424). In-process container 122 may be rinsed (block 426) during the final cycle, with the rinse being introduced into final container 150. An additional dilution of the final product may also be performed to arrive at a final concentration (block 428).

[0053] Alternatively, if after sequential processing of multiple source containers, further concentration or volume reduction may be needed or desired to arrive at the targeted final concentration, the retentate in in-process container 122

may, after dilution (block 420) be subjected to one or more intermediate cycles as depicted in blocks 430, 432 and 434 prior to the final cycle described above. During such intermediate cycling, diluted retentate is introduced into separator 101, processed and the newly concentrated retentate is returned to in-process container 122 where it is diluted (block 434) for another intermediate cycle or for the final cycle (422).

[0054] Thus, in accordance with the present disclosure, multiple source containers can be processed sequentially using a single fluid circuit to arrive at a final concentration for the final product.

[0055] In another embodiment, as shown in FIG. 1, processing may proceed from a single, typically large(r)-volume, source container rather than the multiple containers. Such containers may contain a cell suspension volume of approximately 1-100 liters. Where the source containers are too large to suspend from hardware unit 200, a separate pole (not shown) with a hook for receiving such container may be provided.

[0056] In accordance with the systems and methods described herein, processing from a single container of a large volume of a cell suspension will preferably proceed in “batch” fashion. By “batch” processing, it is meant that rather than continuously processing the entire contents of a source container, pre-determined volumes or “batches” of source fluid are withdrawn from the single source container and fully processed. Once the first pre-determined volume has been processed, the system will automatically withdraw and process a second pre-determined volume or “batch” of source fluid from the single source container. This process will be repeated until all of the source fluid has been processed. The steps in such “batch” processing are shown in FIG. 8.

[0057] As seen in FIG. 8, it will be appreciated that many of the steps in batch processing will be similar and often identical to the steps described above in connection with multiple container, sequential processing (FIG. 7). For example, as shown in block 500 of FIG. 8, the operator selects the procedure and then enters the desired source product information and procedural settings (block 502). As also described above, source product information may include the cell concentration in source container 102, the total volume of the cell suspension in the source container and the number of containers which, in the case, of batch processing is the default number of one (1). Additional procedural settings and information that may be entered include a final target concentration for the concentrated cells. As discussed above, source concentrations may be determined from pre-processing sampling or from pre-set or default values stored in the memory 306 of controller 300, subject to modification by the operator.

[0058] Once the applicable parameters have been entered, the system will calculate the processing conditions such as flow rate, pump speeds, volumes of consumed diluent (wash media), volumes of generated filtrate (waste), processing times, washout percentage and other process residuals to effect processing of the multiple batches of source fluid. The system, under the direction of the controller will also automatically undergo a procedure/simulation estimation (block 504) as substantially described above. During the procedure simulation/estimation step 504, the system will determine whether the processing conditions for the volume/concentration of the cell suspension are acceptable and/or fall

within the entered or pre-set ranges, as has been generally described above in connection with the sequential processing protocol. For example, if the input configuration results in an output configuration that exceeds the volume of the pre-attached collection containers, the system may prompt the user to attach additional containers for increased capacity.

[0059] Once the procedure/simulation estimation step (block 504) is completed, the operator installs disposable fluid processing circuit 100 onto reusable hardware unit 200 (block 506). The system will undergo a series of installation checks (block 508). Once these checks are completed, disposable fluid circuit is ready for priming (block 510). Priming of the fluid circuit may generally proceed as described in Ser. No. 15/600,447, the contents of which are incorporated herein by reference. After priming of the fluid circuit, single source container 102 may be connected (block 512) to the circuit in sterile fashion, as previously described.

[0060] Further processing continues as shown in blocks 514, 516 and 518 and is generally analogous to steps 414, 416 and 418 described in connection with the sequential processing shown in FIG. 7. Unlike sequential processing, however, there is no loop 417 in batch processing wherein additional source containers are connected upon emptying of the container. In batch processing as shown on FIG. 8, after the final batch has been processed, source container 102 may be rinsed (block 518) and the concentrated cell in the in-process container 122 is diluted, the system under the direction of the controller will determine whether to proceed to final cycle 522 or, if further volume-reduction is required to arrive at the targeted final concentration, proceed to one or more intermediate cycles (steps 532, 534 and 536). If the separated and concentrated cells in in-process container 122 are ready for the final cycle 522, the concentrated cells (retentate) undergoes a final volume reduction in separator 101 and the retentate of this step is expressed to final container 150.

[0061] During the final cycle, after in-process container is rinsed (with wash solution in container 135), the system, upon determining that there is additional source fluid remaining in source container 102, will initiate another draw of a batch of source fluid and repeat the volume reduction and other processing steps shown in blocks 516, 518, 520 as well as the steps of the intermediate cycle(s) 532, 534 and 536 and final cycle (524, 526, 528 and 530). Step 528 will prompt additional batch draws until the volume of source fluid is exhausted.

Other Examples

[0062] Aspects of the present subject matter described above may be beneficial alone or in combination with one or more other Aspects, as described below. Without limiting the foregoing description, in accordance with a first Aspect (i.e., Aspect 1) of the subject matter, there is provided a system for processing biological cell suspensions. The system includes a disposable fluid circuit that includes a separation device, a fluid flow path in flow communication with said separation device and one more fluid access devices for establishing fluid communication between the flow path and one or more containers of a biological cell suspensions. The system also includes a reusable hardware unit with a separation device drive unit for receiving said separation device, an operator input and a controller coupled to said input wherein the controller is configured to receive a processing

parameter comprising the total volume of biological cell suspension to be processed from one or more source containers. The controller is also configured to receive a processing parameter comprising the concentration of cells in said one or more source containers. In addition, the controller is configured to calculate the number of draws from one or more source containers and/or the volume of each of said draws.

[0063] Aspect 2. The system of Aspect 1 wherein the controller is further configured to receive a processing parameter comprising a final targeted cell concentration and to calculate the number and volume of draws based at least in part on said targeted cell concentration.

[0064] Aspect 3. The system of any one of Aspects 1 and 2 wherein the controller is configured to receive a processing parameter comprising the volume of the biological cell suspension to be processed and the number of biological cell suspension source containers.

[0065] Aspect 4. The system of any one of Aspects 1 through 3 wherein the controller is configured to receive a processing parameter comprising the number of a plurality of biological cell source containers, the actual or estimated volume of each of the plurality of source containers and/or the concentration of biological cells in each of the plurality of source containers.

[0066] Aspect 5. The system of Aspect 4 wherein the volume and/or concentration of each of the plurality of biological cell source containers are estimated to be the same.

[0067] Aspect 6. The system of any one of Aspects 1 through 5 wherein the controller is configured to sequentially draw a series of predetermined amounts of a biological cell suspension from a single source container of the biological cell suspension.

[0068] Aspect 7. The system of any one of Aspects 1 through 6 wherein the disposable fluid circuit comprises an in-process container, one or more waste containers and one or more final collection containers.

[0069] Aspect 8. The system of any one of Aspects 1 through 7 wherein the controller is configured to generate a prompt when the contents of one of a plurality of source containers have been processed by the system.

[0070] Aspect 9. The system of any one of Aspects 1 through 7 wherein the controller is configured to draw a pre-determined volume of a biological cell suspension from a sole source of the suspension.

[0071] Aspect 10. The system of any one of Aspects 1 through 9 wherein the separation device comprises a membrane mounted onto a spinning member within a separator housing including an inlet and one or more outlets and a gap defined by the membrane and an inner surface of said housing.

[0072] Aspect 11. The system of any one of Aspects 1 through 10 wherein the disposable fluid circuit is adapted for connection to a plurality of source containers.

[0073] Aspect 12. An automated method for processing a biological cell suspension from one or more source containers of a biological cell suspension comprising: receiving a processing parameter comprising the total volume of biological cell suspension to be processed from one or more source containers; receiving a processing parameter comprising the concentration of cells in the one or more source containers; calculating the number of draws from said one or

more source containers and the volume of each draw; and drawing the biological cell suspension from the one or more source containers.

[0074] Aspect 13. The method of Aspect 12 further comprising receiving a target concentration of a processed final cell product.

[0075] Aspect 14. The method of any one of Aspects 12 through 13 further comprising generating an alert if the final target concentration of a processed final cell product cannot be achieved with the biological cell suspension to be processed.

[0076] Aspect 15. The method of any one Aspects 13 through 14 further comprising calculating the number of draws from the one or more source containers and the volume of each of the draws based upon the final target concentration of a processed final cell product to the total volume of the biological cell suspension to be processed.

[0077] Aspect 16. The method of any one of Aspects 12 through 15 comprising drawing a biological cell suspension from one or more source containers of biological cell suspension into a disposable fluid circuit comprising one or more final collection containers, one or more waste containers and an in-process container.

[0078] Aspect 17. The method of any one of Aspects 12 through 15 comprising comparing the final target concentration of a processed final cell product to the total volume capacity of one or more collection containers.

[0079] Aspect 18. The method of any one of Aspects 16 through 17 comprising concentrating the biological cells and holding the concentrated biological cells in the process container.

[0080] Aspect 19. The method of Aspect 18 further comprising drawing a pre-determined volume of the biological cell suspension from the one or more source containers during the holding.

[0081] Aspect 20. The method of Aspect 19 further comprising continuously adding concentrated biological cells to the in-process container.

[0082] Aspect 21. The method of any one of Aspects 18-20 comprising monitoring the concentration of the concentrated biological cells in the in-process container.

[0083] Aspect 22. The method of any one of Aspects 12-21 comprising processing between 1-100 liters of a biological cell suspension using a single fluid circuit.

[0084] Aspect 23. The method of Aspect 22 comprising processing the biological cell suspension from a single container.

[0085] The description provided above is intended for illustrative purposes only and is not intended to limit the scope of the invention to any specific method, system, or apparatus, or device described herein except as may be explicitly delineated in the claims.

What is claimed is:

1. A system for processing a biological cell suspension from a source to provide a product in a retentate container, comprising:

a disposable fluid circuit including a separation device, a pump and a fluid flow path, the fluid flow path comprising first tubing to provide flow communication between the separation device and a source of a biological cell suspension, the first tubing comprising a branched-connector for receiving a processing solution pumped from a container of processing solution, and a second tubing coupled to a retentate container;

a reusable hardware unit comprising a separation device drive unit for receiving the separation device and for receiving the disposable fluid circuit by mounting the disposable fluid circuit on the hardware unit, an operator input comprising a touch screen, a second input comprising a transmitter/receiver device configured to communicate over a local network with a computer, and a controller for directing the processing of the biological cell suspension, the controller configured to:

store processing parameters comprising an estimated volume of biological cell suspension in the source and a concentration of cells in the biological cell suspension based on input from the touch screen or from the computer via the transmitter/receiver device;

calculate a number of draws of the biological cell suspension and a volume of each draw;

calculate a pump speed based on a received processing parameter;

pump the processing solution into the disposable fluid circuit to prime the disposable fluid circuit;

direct the withdrawal of the biological cell suspension from the source in batches in accordance with the calculated number of draws and volume of each draw;

separate a retentate from the withdrawn biological cell suspension; and

direct the retentate into the retentate container.

2. The system of claim 1, wherein the concentration of cells in the biological cell suspension are received from the computer via the transmitter/receiver device.

3. The system of claim 1, wherein the separation device comprises a centrifuge.

4. The system of claim 1, wherein the pump is a peristaltic pump.

5. The system of claim 1, wherein the reusable hardware unit comprises an air detector sensor coupled to the controller and configured to detect a fluid/air interface in the disposable fluid circuit.

6. The system of claim 1, wherein the reusable hardware unit comprises a weight scale coupled to the controller for measuring a weight of the retentate container.

7. The system of claim 1, wherein the controller is configured to perform installation checks prior to priming the disposable fluid circuit.

8. A system for processing a biological cell suspension from a source to provide a product in a retentate container, comprising:

a disposable fluid circuit including a separation device, a pump and a fluid flow path, the fluid flow path comprising first tubing to provide flow communication between the separation device and a source of a biological cell suspension, the first tubing comprising receiving a processing solution pumped from a container of processing solution, and a second tubing coupled to a retentate container;

a reusable hardware unit comprising a plasmapheresis system, the plasmapheresis system comprising a separation device drive unit for receiving the separation device and for receiving the disposable fluid circuit by mounting the disposable fluid circuit on the hardware unit, an operator input comprising a touch screen, a second input comprising a transmitter/receiver device configured to communicate over a network with a

server computer, and a controller for directing the processing of the biological cell suspension, the controller configured to:

receive processing parameters from the computer via the transmitter/receiver device;

calculate processing conditions for the processing of the biological cell suspension based on the received processing parameters, the processing conditions comprising at least one of flow rate, pump speed and processing time;

calculate a number of draws of the biological cell suspension and a volume of each draw;

pump the processing solution into the disposable fluid circuit to prime the disposable fluid circuit;

direct the withdrawal of the biological cell suspension from the source in batches in accordance with the calculated number of draws and volume of each draw;

separate a retentate from the withdrawn biological cell suspension; and

direct the retentate into the retentate container.

9. The system of claim 8, wherein the controller is configured to store an estimated volume of biological cell suspension in the source and a concentration of cells in the biological cell suspension.

10. The system of claim 8, wherein the separation device comprises a centrifuge.

11. The system of claim 8, wherein the pump is a peristaltic pump.

12. The system of claim 8, wherein the reusable hardware unit comprises an air detector sensor coupled to the controller and configured to detect a fluid/air interface in the disposable fluid circuit.

13. The system of claim 8, wherein the reusable hardware unit comprises a weight scale coupled to the controller for measuring a weight of the retentate container.

14. The system of claim 8, wherein the controller is configured to perform installation checks prior to priming the disposable fluid circuit.

15. A method of processing a biological cell suspension from a source to provide a product in a retentate container, comprising:

providing a reusable hardware unit comprising a plasmapheresis system, an operator input comprising a touch screen and a second input comprising a transmitter/receiver device configured to communicate over a network with a server computer;

receiving a disposable fluid circuit on the reusable hardware unit;

storing an estimated volume of biological cell suspension in the source and a concentration of cells in the biological cell suspension based on input from the touch screen or from the computer via the transmitter/receiver device;

calculating processing conditions for the processing of the biological cell suspension based on input from the touch screen or from the computer via the transmitter/receiver device, the processing conditions comprising at least one of flow rate, pump speed and processing time;

calculating a number of draws of the biological cell suspension and a volume of each draw;

pumping a processing solution into the disposable fluid circuit to prime the disposable fluid circuit;

directing the withdrawal of the biological cell suspension from the source in batches in accordance with the calculated number of draws and volume of each draw;

separating a retentate from the withdrawn biological cell suspension; and

directing the retentate into the retentate container.

16. The method of claim 15, further comprising detecting a fluid/air interface in the disposable fluid circuit.

17. The method of claim 15, further comprising measuring a weight of the retentate container.

18. The method of claim 15, further comprising performing installation checks prior to priming the disposable fluid circuit.

19. The method of claim 15, further comprising pre-process sampling to determine the concentration of cells.

20. The method of claim 15, further comprising receiving the estimated volume of biological cell suspension in the source from the touch screen or from the computer via the transmitter/receiver device.

* * * * *