

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250256031

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Fabricsius; Paul Erik et al.

FRONT LOADED AUTO INJECTOR FOR ADMINISTERING A MEDICAMENT

Abstract

Disclosed is a method for controlling an auto injector and an auto injector for administering a medicament from a cartridge having a first cartridge end and a second cartridge end and having a cartridge outlet at the first cartridge end, the cartridge comprising a cartridge compartment with a first cartridge subcompartment containing a first medicament component of the medicament and a second cartridge subcompartment containing a second medicament component of the medicament. The auto injector comprises: a housing; a cartridge receiver; a cartridge sensor; a drive module; an orientation sensor; and a processing unit.

Inventors: Fabricsius; Paul Erik (Holstebro, DK), Olesen; Jan (Holstebro, DK), Jensen; Steen (Dragør, DK), Egesborg; Henrik (Hellerup, DK), Pedersen; Per Mølgaard (Struer, DK)

Applicant: Ascendis Pharma A/S (Hellerup, DK)

Family ID: 1000008571991

Appl. No.: 19/174258

Filed: April 09, 2025

Foreign Application Priority Data

EP 15203168.8

Dec. 30, 2015

EP 16190461.0

Sep. 23, 2016

Related U.S. Application Data

parent US continuation 18112265 20230221 parent-grant-document US 12290663 child US 19174258

Publication Classification

Int. Cl.: **A61M5/20** (20060101); **A61M5/24** (20060101); **A61M5/315** (20060101); **A61M5/32** (20060101)

U.S. Cl.:

CPC **A61M5/2066** (20130101); **A61M5/20** (20130101); **A61M5/24** (20130101); **A61M5/31511** (20130101); **A61M5/31573** (20130101); **A61M5/31576** (20130101); **A61M5/326** (20130101); A61M2005/2411 (20130101); A61M2005/31588 (20130101); A61M2005/3267 (20130101); A61M2205/332 (20130101); A61M2205/3368 (20130101); A61M2205/50 (20130101); A61M2205/502 (20130101); A61M2205/6063 (20130101); A61M2205/82 (20130101); A61M2205/8206 (20130101)

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. application Ser. No. 18/112,265, filed Feb. 21, 2023, which is a continuation of U.S. application Ser. No. 16/060,630, filed Jun. 8, 2018 and issued as U.S. Pat. No. 11,607,496, which is a U.S. National Phase Application of PCT International Application Number PCT/EP2016/082858, filed on Dec. 29, 2016, designating the United States of America and published in the English language, which is an International Application of and claims the benefit of priority to European Patent Application No. 15203168.8, filed on Dec. 30, 2015 and European Patent Application No. 16190461.0, filed on Sep. 23, 2016. The disclosures of the above-referenced applications are hereby expressly incorporated by reference in their entireties.

FIELD

[0002] The present disclosure relates to an auto injector, such as an electronic auto injector, a cartridge for an auto injector, a system comprising an auto injector and a cartridge, and a method for operating an auto injector.

INTRODUCTION/BACKGROUND

[0003] Hypodermic syringes are widely used to deliver fluids to the body. It is known to have hypodermic syringes applicable for manual operation. However, auto injectors, such as electronic auto injectors, have been developed and are widely used to aid the administering of fluid or medicaments to the body.

[0004] To avoid relying on users correctly performing certain tasks, it is of increasing interest that the auto injector automatically carries out as much as possible of the injection process. Especially, when administering of the medicament requires several steps, such as if medicament needs to be mixed prior to injection, it may be beneficial to automate the process of preparing and administering the fluid, such as a medicament.

SUMMARY

[0005] There is a need for an auto injector, such as an electronic auto injector, with an improved automation of preparing and administering the medicament. The present disclosure provides an auto injector, a cartridge, a system, and a method improving the preparation and administering of medicament with an auto injector.

[0006] Accordingly, an auto injector for preparing and/or administering a medicament from a

cartridge is disclosed. The cartridge has a first cartridge end and a second cartridge end and having a cartridge outlet at the first cartridge end. The cartridge comprises a cartridge compartment. The cartridge compartment has a first cartridge subcompartment containing a first medicament component of the medicament and a second cartridge subcompartment containing a second medicament component of the medicament.

[0007] The auto injector comprising: a housing; a cartridge receiver; a cartridge sensor; a drive module; an orientation sensor; and a processing unit.

[0008] The cartridge receiver has a cartridge receiver opening. The cartridge receiver is configured to receive the cartridge by insertion of the second end of the cartridge through the cartridge receiver opening.

[0009] The cartridge sensor is configured to detect reception of the cartridge in the cartridge receiver and provide a cartridge detection signal indicative of the cartridge being received in the cartridge receiver.

[0010] The drive module is coupled to move a plunger rod between a retracted plunger rod position and an extended plunger rod position. The plunger rod is configured to move the first stopper, e.g. when the plunger rod is moved towards the extended plunger rod position.

[0011] The orientation sensor is configured to provide an orientation signal indicative of the orientation of the cartridge, e.g. when the cartridge is received in the cartridge receiver.

[0012] The processing unit is coupled to the orientation sensor, the cartridge sensor, and to the drive module.

[0013] The processing unit is configured to: receive a first input signal; receive the cartridge detection signal; receive the orientation signal; control the drive module to move the plunger rod to a mix plunger rod position following reception of the cartridge detection signal and the first input signal; and control the drive module to move the plunger rod to a prime plunger rod position following completion of movement of the plunger rod to the mix plunger rod position.

[0014] The processing unit may further be configured to receive a trigger event; and control the drive module to move the plunger rod to an injection plunger rod position following reception of the trigger event after completion of movement of the plunger rod to the prime plunger rod position.

[0015] Also disclosed is a cartridge for an auto injector, such as the disclosed auto injector. The cartridge has a first cartridge end and a second cartridge end and having a cartridge outlet at the first cartridge end. The cartridge comprises a cartridge compartment. The cartridge compartment has a first cartridge subcompartment containing a first medicament component of the medicament and a second cartridge subcompartment containing a second medicament component of the medicament. The cartridge is configured to be received by a cartridge receiver of an auto injector, such as a cartridge receiver of the disclosed auto injector, by insertion of the second end of the cartridge through the cartridge receiver opening of the auto injector.

[0016] Also disclosed is a system comprising an auto injector, such as the disclosed auto injector, and a cartridge, such as the disclosed cartridge.

[0017] Also disclosed is a method for operating an auto injector, such as the disclosed auto injector, e.g. an auto injector comprising a plunger rod and a cartridge receiver configured to receive a cartridge, such as the disclosed cartridge, e.g. a cartridge having a first cartridge end and a second cartridge end and having a cartridge outlet at the first cartridge end.

[0018] The method comprises: receiving a first input signal; detecting reception of the cartridge in the cartridge receiver; determining orientation of the cartridge; moving the plunger rod to a mix plunger rod position following detection of the cartridge being received in the cartridge receiver and reception of the first input signal; and moving the plunger rod to a prime plunger rod position following completion of movement of the plunger rod to the mix plunger rod position.

[0019] The method may further comprise receiving a trigger event; and moving the plunger rod to an injection plunger rod position following reception of the trigger event after completion of

movement of the plunger rod to the prime plunger rod position.

[0020] The trigger event may, for example, be an effect of a push of a button, an effect of an elapsed timeout, and/or an effect of a predetermined user behaviour. The trigger event may be indicative of the auto injector being pressed against the injection site.

[0021] It is an advantage of the present disclosure that the steps involved in preparing and/or administering a medicament are increasingly automated. It is further an advantage that such increased automation provides for increased safety in preparing and/or administering the medicament.

[0022] It is a further advantage of the present disclosure that an auto injector may be provided which is easier to use, and reduce the risk of erroneous administering of a medicament.

[0023] It is an advantage of the present disclosure that it may aid in determining characteristics of the received cartridge. It is a further advantage of the disclosure that an auto injector may be operated according to characteristics of the received cartridge.

[0024] The disclosure may enable determination or indication that the cartridge received is a used cartridge and/or a flawed cartridge and/or a counterfeit cartridge and/or a cartridge comprising a medicament not approved for the device. Thus, an advantage of the disclosure may be that it increases the safety of an auto injector, e.g. as the auto injector may be prevented or restricted from using a not new cartridge.

[0025] Thus, it is a further advantage of the present disclosure, that patient safety is increased, e.g. by decreasing the risk of transmitting infections, and/or by decreasing the risk of incorrect dosage of medicament.

[0026] It is envisaged that any embodiments or elements as described in connection with any one aspect may be used with any other aspects or embodiments, *mutatis mutandis*.

[0027] The cartridge has a cartridge outlet at the first cartridge end. The cartridge may comprise a cartridge back face, e.g. at the second cartridge end, such as opposite the cartridge outlet. The cartridge back face may comprise a cartridge back end opening. The cartridge back end opening may provide access for a plunger rod, such as the plunger rod of the auto injector, to the first stopper.

[0028] The cartridge compartment may contain the medicament. The cartridge outlet may be configured for fluid communication with the compartment, e.g. at the first cartridge end. The cartridge may be configured to expel medicament through the cartridge outlet. The cartridge outlet may be configured to be coupled with a needle, such as a hypodermic needle, to provide the medicament to be expelled through the needle.

[0029] The cartridge comprises a first stopper movable inside the cartridge compartment. The cartridge may comprise a second stopper movable inside the cartridge compartment. The second stopper may be between the first stopper and the cartridge outlet. The cartridge may comprise a third stopper movable inside the cartridge compartment. The third stopper may be between the second stopper and the cartridge outlet. The first stopper, the second stopper, and/or the third stopper may be movable inside the cartridge compartment towards the cartridge outlet, e.g. in a first stopper direction, such as towards the first cartridge end. For example, the medicament may be expelled through the cartridge outlet upon movement of the first stopper, the second stopper, and/or the third stopper, e.g. in the first stopper direction and/or towards the cartridge outlet.

[0030] The cartridge may be a dual-chamber cartridge. The cartridge compartment may have a first cartridge subcompartment and a second cartridge subcompartment. The first cartridge subcompartment may be between the first stopper and the second stopper. The second cartridge subcompartment may be between the second stopper and the cartridge outlet and/or the third stopper.

[0031] The first cartridge subcompartment may contain a first medicament component of the medicament. The second cartridge subcompartment may contain a second medicament component of the medicament. Each of the first medicament component and/or second medicament component

may be a powder composition, a fluid, a liquid, a gel, a gas, and/or any combination thereof. The first medicament component and/or the second medicament component may be solute, such as a powder composition. The first medicament component and/or the second medicament component may be a solvent, such as a fluid composition, such as a liquid composition. The second medicament component may be a powder composition and the first medicament component may be a fluid composition, e.g. water or ethanol or saline solution or buffer solution or preservative solution. The second medicament component may be a solute. The first medicament component may be a solvent. It is envisaged that the medicament may be any medicament being injectable via a hypodermic needle, for example after reconstitution of the medicament. The medicament may be a growth hormone. The medicament may be human growth hormone. The medicament may be a depot version, such as a long-acting version, of human growth hormone. The second medicament component may be a powder composition of human growth hormone.

[0032] The cartridge may have a bypass section providing fluid communication between the first cartridge subcompartment and the second cartridge subcompartment, e.g. when the second stopper is positioned in the bypass section. The cartridge may have a plurality of bypass sections providing fluid communication between neighbouring cartridge subcompartments, e.g. when a stopper separating the neighbouring cartridge subcompartment is positioned in the bypass section.

[0033] A reusable auto injector, such as the disclosed auto injector, may be especially useful when the cartridge comprises a plurality of subcompartments. For example an auto injector for a multi compartment or multi chamber cartridge may be more advanced, and therefore it may be beneficial to allow the auto injector to be used more than one time. For example, the auto injector may provide automated processes for mixing medicament components, such as for mixing medicament components initially provided in different subcompartments of the cartridge.

[0034] The cartridge may be comprised as part of a cartridge assembly. The cartridge assembly may comprise the cartridge. Additionally, the cartridge assembly may comprise a needle, such as a needle assembly comprising a needle, a needle cover, a cartridge holder, and/or a cartridge code feature.

[0035] The cartridge assembly may comprise the needle, such as the needle assembly comprising the needle. The needle assembly may comprise a needle cover and/or a needle hub. The cartridge assembly may comprise a cartridge holder. The cartridge holder may be configured to engage with the needle assembly. The cartridge holder may provide for attachment of the needle assembly to the cartridge.

[0036] The cartridge may comprise a cartridge code feature and/or the cartridge assembly may comprise the cartridge and the cartridge code feature. The cartridge code feature may comprise one or more of a colour, a bar code, an RFID tag, an NFC tag, an identification number, and a QR code. For example, the cartridge code feature may comprise a colour and/or a sequence of colours. The cartridge code feature may be positioned surrounding or partly surrounding a part of the cartridge compartment wherein a stopper, such as the first stopper, is initially positioned. Such position of the cartridge code feature may increase readability of the cartridge code feature, e.g. since the stopper may form a background for the cartridge code feature. The stopper, such as the first stopper may be a light colour, such as light grey or white. The stopper, such as the first stopper, may be a dark colour, such as dark blue, dark grey, or black. The stopper may form a dark background for the cartridge code feature. The stopper, such as the first stopper, may reduce reflection of light, e.g. to further increase readability of the cartridge code feature.

[0037] The cartridge code feature may be positioned at a specific position on the cartridge, e.g. independently of the stopper(s), such as the first stopper. For example, the cartridge code feature may be positioned at a code distance from the second cartridge end. All cartridges may have their cartridge code features positioned at the same position, e.g. positioned at the code distance from the second cartridge end. Such uniform position of the cartridge code feature may decrease complexity, and decrease size, of the auto injector, as the cartridge code feature is read in the same position for

all suitable cartridges.

[0038] The cartridge and the cartridge code feature may be manufactured as one element. For example, the cartridge code feature may be a certain form of the cartridge. Alternatively, the cartridge code feature may be attached to the cartridge, such as fastened, e.g. by glue, to the cartridge. For example, the cartridge code feature may be a colour code printed on the cartridge.

[0039] The cartridge code feature may be indicative of one or more cartridge specifications, such as medicament in the cartridge, concentration of medicament in the cartridge, viscosity of medicament in the cartridge, volume and/or mass of medicament in the cartridge, positions of stopper(s) in the cartridge compartment, etc. The cartridge code feature may be indicative of a position of the first stopper wherein air in the cartridge compartment is reduced, such as minimized and/or reduced to an amount appropriate for injection. The cartridge code feature may be indicative of the amount of medicament contained in the cartridge. The cartridge code feature may be indicative of a specific type of cartridge, such as an ID number of the specific type of cartridge. The auto injector, such as the processing unit of the auto injector, may be configured to determine one or more cartridge specifications based on an ID number, e.g. by table lookup. The cartridge code feature may be indicative of a suitable, such as optimal, speed of stopper movement, such as stopper movement in different phases of movement, such as during mixing, during air-shot, and/or injection. The cartridge code feature may be indicative of a suitable, such as optimal, speed of movement of the first stopper, such as speed of movement of the first stopper in different phases of movement, such as during mixing, during air-shot, and/or injection. The cartridge code feature may be indicative of time needed for optimal mixing of the first medicament component and the second medicament component. The cartridge code feature may be indicative of a suitable dwell time for the medicament, e.g. time to ensure that the medicament is distributed into the tissue, e.g. favourable time to wait after injection before retraction of the needle.

[0040] The auto injector may be a front-loaded auto injector. The auto injector comprises a cartridge receiver configured to receive the cartridge. The cartridge receiver may be configured to receive a cartridge assembly comprising the cartridge. The cartridge assembly may comprise a cartridge holder. The cartridge receiver has a cartridge receiver opening. The cartridge receiver may be configured to receive the cartridge by insertion of the cartridge, such as the second end of the cartridge, through the cartridge receiver opening. The cartridge may be inserted in a cartridge receiving direction. The cartridge receiving direction may be opposite the first stopper direction, e.g. when the cartridge is received in the cartridge receiver. The cartridge may be in a first angular position when inserted into the cartridge receiver. The cartridge may be retained in the cartridge receiver in a second angular position, e.g. after insertion of the cartridge in the cartridge receiver.

[0041] The cartridge receiver may be configured to receive a cartridge assembly comprising the cartridge and a cartridge holder. The cartridge assembly may be retained in the cartridge receiver by one or more cartridge retention members of the cartridge holder engaging with members of the cartridge receiver.

[0042] The cartridge and/or cartridge assembly may be lockable in the cartridge receiver, e.g. the cartridge and/or cartridge assembly may be locked in the cartridge receiver to prevent removal of the cartridge and/or cartridge assembly from the cartridge receiver. The cartridge and/or cartridge assembly may be locked in the cartridge receiver by movement of a plunger rod of the auto injector.

[0043] The auto injector may comprise a cartridge sensor. The cartridge receiver may comprise the cartridge sensor. The cartridge sensor may be configured to detect reception of the cartridge and/or cartridge assembly in the cartridge receiver. The cartridge sensor may provide a cartridge sensor signal indicative of whether the cartridge and/or cartridge assembly is received in the cartridge receiver. The cartridge sensor may provide a cartridge detection signal indicative of the cartridge and/or cartridge assembly being received in the cartridge receiver. The cartridge sensor signal may comprise the cartridge detection signal.

[0044] The auto injector may be an electronic auto injector. The auto injector may comprise a battery. The housing may accommodate the battery. The battery may be a rechargeable battery. For example, the battery may be a Li-ion battery or a NiCd battery or a NiMH battery. The battery may be configured to be charged by connection of a charger.

[0045] The auto injector comprises a drive module. The drive module may be coupled to move, such as actuate, such as advance, a plunger rod, such as between a retracted plunger rod position and an extended plunger rod position. Movement of the plunger rod may provide the cartridge and/or cartridge assembly to be locked in the cartridge receiver. For example, the cartridge and/or cartridge assembly may be locked in the cartridge receiver by advancement of the plunger rod from a retracted plunger rod position.

[0046] The drive module may comprise one or more electrical elements. The drive module may be configured to receive electrical power from the battery. The drive module may be electrically connected to the battery for receiving electrical power. The drive module may be accommodated by the housing. The drive module may comprise a motor, such as an electro-mechanical motor, such as a DC motor, e.g. a DC motor with or without brushes. The drive module may comprise a solenoid motor. The drive module may comprise a shape memory metal engine. The drive module may comprise an arrangement of springs configured to actuate the plunger rod. The drive module may comprise a pressurized gas configured to actuate the plunger rod.

[0047] The auto injector may comprise a plunger rod, such as the plunger rod movable by the drive module. The plunger rod may be configured to move a stopper, such as the first stopper of the cartridge. For example, when the plunger rod is moved towards the extended plunger rod position the plunger rod may be configured to move the first stopper towards the cartridge outlet, such as to expel medicament from the cartridge compartment through the cartridge outlet and/or to expel air from the cartridge compartment through the cartridge outlet.

[0048] The plunger rod may be moved to a pre-mix plunger rod position, such as towards the extended plunger rod position, such as from the retracted plunger rod position. The pre-mix plunger rod position may be a position wherein fluid communication between the first cartridge subcompartment and the second cartridge subcompartment is not yet established.

[0049] The plunger rod may be moved to a mix plunger rod position, such as towards the extended plunger rod position, such as from the retracted plunger rod position and/or the pre-mix plunger rod position. The mix plunger rod position may be a position wherein the first medicament component and the second medicament component are mixed, such as combined. The mix plunger rod position may be a position wherein the second stopper is positioned in the bypass section, such as to provide fluid communication between the first cartridge subcompartment and the second cartridge subcompartment.

[0050] The plunger rod may be moved to a prime plunger rod position, such as towards the extended plunger rod position, such as from the retracted plunger rod position and/or the mix plunger rod position. The prime plunger rod position may be a position wherein air has been expelled from the cartridge compartment. For example, the prime plunger rod position may be selected to position the first stopper in a position wherein air in the cartridge compartment is reduced, such as minimized and/or reduced to an amount appropriate for injection.

[0051] The plunger rod may be moved to an injection plunger rod position, such as towards the extended plunger rod position, such as from the retracted plunger rod position and/or the prime plunger rod position. The injection plunger rod position may be a position wherein the medicament has been expelled and/or injected from the cartridge compartment. For example, the injection plunger rod position may be selected to position the first stopper in a position wherein medicament in the cartridge compartment is reduced, such as minimized, such as in a position close to the cartridge outlet. The injection plunger rod position may be the extended plunger rod position.

[0052] The plunger rod may be moved towards the retracted plunger rod position, e.g. to the retracted plunger rod position. For example, the plunger rod may be moved towards the retracted

plunger rod position, e.g. to the retracted plunger rod position, after completion of injection, such as from the injection plunger rod position and/or the extended plunger rod position.

[0053] The processing unit may be configured to move the plunger rod to the pre-mix plunger rod position, the mix plunger rod position, the prime plunger rod position, the injection plunger rod position, the extended plunger rod position and/or the retracted plunger rod position.

[0054] The auto injector may comprise an ejection sensor, such as a plunger rod position sensor. The ejection sensor may be configured to detect the ejection, such as the expelling, of medicament and/or air in the cartridge compartment. The ejection sensor may be configured to detect and/or determine the position of the plunger rod and/or the position of the first stopper. The ejection sensor may be configured to detect conditions indicative of the position of the plunger rod and/or the position of the first stopper. The ejection sensor may be configured to provide an ejection sensor signal. The ejection sensor signal may be indicative of the position of the plunger rod and/or the first stopper.

[0055] The ejection sensor may comprise a tachometer, e.g. a tachometer of the drive module. The tachometer may be configured to count the revolutions of the drive module, such as a motor of the drive module, such as the revolutions of the drive module from a set point, such as a point wherein the position of the plunger rod is known, such as the retracted plunger rod position of the plunger rod. The count of revolutions of the drive module may be used to determine the actual position of the plunger rod, such as the pre-mix plunger rod position, the mix plunger rod position, the prime plunger rod position, the injection plunger rod position, the extended plunger rod position and/or the retracted plunger rod position.

[0056] The processing unit may be coupled to the ejection sensor, such as to the tachometer. The processing unit may receive from the ejection sensor a first ejection sensor signal, such as a tachometer signal, indicative of the count of revolutions of the drive module. The processing unit may determine the position of the plunger rod based on the first ejection sensor signal. The processing unit may receive a second ejection sensor signal, e.g. from the ejection sensor, indicative of the plunger rod being in a known position, such as the retracted plunger rod position. The processing unit may determine the position of the plunger rod based on the first ejection sensor signal and the second ejection sensor signal.

[0057] The cartridge may be lockable in the cartridge receiver, e.g. the cartridge may be locked in the cartridge receiver to prevent removal of the cartridge from the cartridge receiver. Movement of the plunger rod towards the extended plunger rod position may lock the cartridge in the cartridge receiver. For example, movement of the plunger rod to the mix plunger rod position may lock the cartridge in the cartridge receiver. Movement of the plunger rod towards the retracted plunger rod position may unlock the cartridge from the cartridge receiver. For example, movement of the plunger rod to the retracted plunger rod position may unlock the cartridge in the cartridge receiver. The cartridge may be locked in the cartridge receiver when the plunger rod is not in the retracted plunger rod position and/or close to the retracted plunger rod position. Coupling the position of the plunger rod with the locking of the cartridge in the cartridge receiver may provide the advantage that the release of the cartridge may be restricted or prevented when the auto injector is active.

[0058] The auto injector may comprise an orientation sensor. The orientation sensor may be configured to provide an orientation signal indicative of the orientation of the cartridge, e.g. when the cartridge is received in the cartridge receiver. The orientation signal may be indicative of the orientation of the cartridge relative to gravity, such as relative to the direction of gravity.

[0059] The orientation sensor may be configured to detect an orientation of the cartridge and/or an orientation indicative of the orientation of the cartridge, such as an orientation of the auto injector. The detected orientation may be relative to gravity, such as relative to the direction of gravity. The orientation sensor may be configured to detect the direction of gravity, and/or if the direction of gravity is within a certain range of a predetermined direction. The orientation sensor may comprise an accelerometer. The orientation sensor may comprise a plurality of accelerometers, such as three

accelerometers, such as three accelerometers arranged to detect acceleration in three dimensions, such as a three-dimensional accelerometer. The orientation sensor may comprise a tilt sensor, a tri-axial accelerometer, a single axis accelerometer, a magnetometer and/or any combination thereof, and the orientation sensor may provide a measure of roll, pitch and azimuth, a measure of acceleration and/or tilt in one or more directions.

[0060] The orientation sensor may be configured to detect if the cartridge is in a predetermined orientation. The orientation sensor may be configured to detect if the orientation of the auto injector is indicative of the cartridge being in the predetermined orientation. The predetermined orientation may be a vertical orientation. The predetermined orientation may be an orientation within 45 degrees of vertical, such as within 30 degrees of vertical. The predetermined orientation may be an orientation wherein the cartridge is orientated such that a longitudinal axis of the cartridge is within 45 degrees of vertical, such as within 30 degrees of vertical, and wherein the cartridge outlet is above the cartridge compartment, such as in a vertical position above the cartridge compartment.

[0061] The processing unit may be coupled to the orientation sensor. The processing unit may be configured to receive the orientation signal, e.g. indicative of the orientation of the cartridge when received in the cartridge receiver, and/or of the auto injector.

[0062] Movement of the plunger rod to the mix plunger rod position and/or to the prime plunger rod position and/or to the injection plunger rod position may be based on the orientation of the cartridge, e.g. on the orientation signal. For example, movement of the plunger rod to the mix plunger rod position and/or to the prime plunger rod position and/or to the injection plunger rod position may require that a tilt angle between vertical and a longitudinal axis extending along the cartridge is within 45 degrees, such as within 30 degrees, and/or that the cartridge outlet is in a vertical position above the cartridge compartment.

[0063] Control of the drive module to move the plunger rod to the mix plunger rod position and/or to the prime plunger rod position and/or to the injection plunger rod position may be based on the orientation of the cartridge, e.g. on the orientation signal.

[0064] The processing unit may be configured to control the drive module based on the orientation signal. For example, the processing unit may be configured to control the drive module to move the plunger rod to the mix plunger rod position and/or to the prime plunger rod position and/or to the injection plunger rod position based on the orientation signal. For example, the processing unit may be configured to control the drive module to move the plunger rod to the mix plunger rod position and/or to the prime plunger rod position and/or to the injection plunger rod position only if the orientation signal indicates that a tilt angle between vertical and a longitudinal axis extending along the cartridge is within 45 degrees, such as within 30 degrees, of vertical, and/or if the cartridge outlet is in a vertical position above the cartridge compartment.

[0065] The auto injector may comprise a code sensor. The code sensor may be configured to read a cartridge code feature, such as the cartridge code feature of the cartridge e.g. indicative of one or more cartridge specifications. The code sensor may be configured to provide a code signal indicative of the cartridge code feature. The processing unit may be coupled to the code sensor. The processing unit may be configured to receive the code signal.

[0066] The processing unit may be configured to determine an unauthorized cartridge, such as a counterfeit cartridge and/or a used cartridge, and/or a tampered cartridge, and/or a cartridge containing a wrong dose, and/or a cartridge containing a wrong medicament, based on the code signal.

[0067] The code sensor may comprise an optical sensor. The code sensor may comprise an optical sensor comprising a transmitter and a receiver, such as a light transmitter and a light receiver. The code sensor may be configured to read the cartridge code feature. The code sensor may be configured to read colour codes, bar codes, RFID tags, NFC tags, identification numbers, QR codes, and/or any combination hereof.

[0068] Movement of the plunger rod may be based on the code signal. For example, movement of

the plunger rod to the mix plunger rod position and/or the prime plunger rod position and/or the injection plunger rod position, may be based on the cartridge code feature, e.g. on the code signal. For example, control of the drive module to move the plunger rod to the prime plunger rod position may be based on the code signal. The processing unit may be configured to control the drive module based on the code signal. For example, the processing unit may be configured to control the drive module to move the plunger rod to the prime plunger rod position based on the code signal.

[0069] Basing the movement of the plunger rod on cartridge specification, e.g. on the code signal, provides that the plunger rod movement may be optimized to several types of cartridges. For example, the air-shot may be performed with reduced or no expelling of medicament, thereby increasing dosage accuracy and/or reducing patient discomfort, e.g. even with different cartridges.

[0070] Basing the movement of the plunger rod on cartridge specification, e.g. on the code signal, provides that the plunger rod movement may be optimized to several types of cartridges. For example, the plunger rod may be kept in a mix plunger rod position for a time depending on the cartridge specification following detection of the cartridge being received in the cartridge receiver and reception of the first input signal thereby ensuring appropriate mixing and/or reducing patient discomfort, e.g. even with different cartridges.

[0071] The auto injector may comprise a resistance sensor. The resistance sensor may be configured to provide a resistance signal. The resistance signal may be indicative of resistance against movement of the plunger rod. The processing unit may be coupled to the resistance sensor. The processing unit may be configured to receive the resistance signal.

[0072] The processing unit may be configured to determine an unauthorized cartridge, such as a counterfeit cartridge and/or a used cartridge, and/or a tampered cartridge, and/or a cartridge containing a wrong dose, and/or a cartridge containing a wrong medicament, based on the code signal and/or the resistance signal.

[0073] The resistance signal may be indicative of resistance against movement of the plunger rod in one direction, such as movement towards the extended plunger rod position. For example, the resistance signal may be indicative of the force necessary to move the plunger rod, e.g. towards the extended plunger rod position.

[0074] The resistance sensor may be configured to determine electrical power consumed by the drive module, e.g. by measuring electrical resistance, electrical current, and/or electrical voltage of the drive module and/or a combination thereof. The resistance sensor may comprise an electrical resistance sensor, an electrical current sensor, and/or an electrical voltage sensor. The drive module may comprise the resistance sensor.

[0075] The resistance sensor may be configured to measure pressure and/or force applied to a plunger rod front end of the plunger rod. The plunger rod front end may be configured to engage with the first stopper of the cartridge. The resistance sensor may be configured to measure pressure and/or force between the plunger rod and the stopper. For example, the resistance sensor may comprise a pressure transducer and/or a force transducer on the plunger rod front end. The plunger rod may comprise the resistance sensor.

[0076] Movement of the plunger rod may be based on the resistance signal. For example, movement of the plunger rod to the mix plunger rod position and/or the prime plunger rod position and/or the injection plunger rod position, may be based on resistance against movement of the plunger rod, e.g. on the resistance signal. For example, control of the drive module to move the plunger rod to the mix plunger rod position may be based on the resistance signal. The processing unit may be configured to control the drive module based on the resistance signal. For example, the processing unit may be configured to control the drive module to move the plunger rod to the mix plunger rod position based on the resistance signal.

[0077] Movement of the plunger rod to the mix plunger rod position and/or the prime plunger rod position and/or the injection plunger rod position may require that resistance against movement of the plunger rod is above a low resistance threshold, e.g. that the resistance signal indicates

resistance against movement of the plunger rod above a low resistance threshold. For example, the processing unit may be configured to control the drive module to move the plunger rod to the mix plunger rod position only if the resistance signal indicates resistance against movement of the plunger rod above a low resistance threshold, such as after completion of movement of the plunger rod to the pre-mix plunger rod position. The low resistance threshold may be between 1 N and 15 N, such as between 5 N and 11 N. The low resistance threshold may be 1 N, 5 N, or 10 N.

[0078] A cartridge parameter may be based on resistance against movement of the plunger rod, e.g. on the resistance signal. The processing unit may be configured to determine the cartridge parameter based on the resistance signal.

[0079] The cartridge parameter may be indicative of the cartridge being unused and/or full. For example, if the present plunger rod position has reached a plunger rod threshold, such as a predetermined plunger rod position between the retracted plunger rod position and the extended plunger rod position, and the resistance signal is indicative of resistance against movement of the plunger rod above the low resistance threshold, e.g. indicating a sufficient force necessary to move the plunger rod, hence indicating that the plunger rod has engaged the first stopper.

[0080] The cartridge parameter may be indicative of the cartridge being not full and/or empty, such as used. For example, if the present plunger rod position has reached a plunger rod threshold, such as a predetermined plunger rod position between the retracted plunger rod position and the extended plunger rod position, and the resistance signal is indicative of resistance against movement of the plunger rod below the low resistance threshold, e.g. indicating a small force necessary to move the plunger rod, hence indicating that the first stopper is in an advanced position.

[0081] The cartridge parameter may be indicative of the cartridge being flawed and/or that no needle is attached and/or attached needle is blocked, e.g. if the resistance signal is indicative of resistance against movement of the plunger rod above a high resistance threshold, e.g. indicating a large force necessary to move the plunger rod, hence indicating that the plunger rod and/or the first stopper is somehow blocked from advancement. The high resistance threshold may be between 8 N and 25 N, such as between 10 N and 20 N. The high resistance threshold may be 8 N, 11 N, or 15 N.

[0082] Thresholds, such as the plunger rod threshold, the low resistance threshold and/or the high resistance threshold, may be determined based on the cartridge and/or the cartridge code feature. The cartridge code feature may be indicative of the threshold, such as the plunger rod threshold, the low resistance threshold and/or the high resistance threshold.

[0083] The processing unit may be configured to determine the threshold, such as the plunger rod threshold, the low resistance threshold and/or the high resistance threshold, based on the code signal.

[0084] The auto injector may comprise a temperature sensor. The temperature sensor may be configured to provide a temperature signal, such as a temperature signal indicative of the temperature of the auto injector and/or of the cartridge and/or of the medicament. The temperature sensor may comprise an infrared sensor, such as an infrared optical sensor.

[0085] The processing unit may be coupled to the temperature sensor. The processing unit may be configured to receive the temperature signal.

[0086] Movement of the plunger rod to the mix plunger rod position and/or to the prime plunger rod position and/or to the injection plunger rod position may be based on the temperature of the auto injector and/or of the cartridge and/or of the medicament, e.g. on the temperature signal.

[0087] The auto injector, such as the processing unit, may be configured to control the drive module based on the temperature signal. For example, the processing unit may be configured to control the drive module to move the plunger rod to the mix plunger rod position and/or to the prime plunger rod position and/or to the injection plunger rod position based on the temperature signal.

[0088] The auto injector may comprise an input device, such as a first input device. The first input device may be a button or a touch sensitive area or a microphone. The first input device may be configured to provide the first input signal. The first input signal may be indicative of a first user interaction with the first input device. The first input device may be configured to provide a second input signal. The second input signal may be indicative of a second user interaction with the first input device.

[0089] The processing unit may be coupled to the first input device. The processing unit may be configured to receive the first input signal and/or the second input signal. The processing unit may be configured to control the drive module to move the plunger rod to the mix plunger rod position only after receiving the first input signal. The processing unit may be configured to control the drive module to move the plunger rod to the prime plunger rod position only after receiving the second input signal.

[0090] The auto injector may comprise a contact member. The contact member may be configured to be pressed against the injection site. The contact member may be movable between an extended contact member position and a retracted contact member position. The contact member may be biased towards the extended contact member position, e.g. by a contact member spring. The contact member may be configured to be moved towards the retracted contact member position, e.g. when pressed against the injection site. The contact member and/or a contact member sensor may be configured to provide a contact member signal indicative of position of the contact member. The auto injector and/or the contact member may comprise a contact member sensor configured to detect the position of the contact member. The contact member sensor may be configured to provide the contact member signal indicative of the contact member.

[0091] The contact member may be in a first contact member position, e.g. between the extended contact member position and the retracted contact member position. The contact member being in the first contact member position may indicate that the contact member is close to the retracted contact member position. The contact member being in the first contact member position may indicate that the contact member is pressed against the injection site. The contact member being in the first contact member position may indicate that a needle positioned on the cartridge is pressed sufficiently into the skin for injection of the medicament to start.

[0092] The contact member may be in a second contact member position, e.g. between the extended contact member position and the retracted contact member position, such as between the extended contact member position and the first contact member position. The contact member being in the second contact member position may indicate that the contact member is restricted from being biased to the extended contact member position. The contact member being in the second contact member position may indicate that a needle cover, such as a needle with a needle cover, is positioned on the cartridge.

[0093] The processing unit may be coupled to the contact member. The processing unit may be configured to receive the contact member signal. The trigger event may comprise the contact member signal being indicative of the contact member being in a first contact member position. The contact member may be a trigger member.

[0094] The auto injector may comprise a needle sensor. The needle sensor may be configured to detect a needle, and/or a needle assembly, and/or a needle cover of a needle assembly, of the cartridge assembly, e.g. when the cartridge assembly is received in the auto injector and/or in the cartridge receiver of the auto injector. The needle sensor may provide a needle signal indicative of the presence of a needle, and/or a needle assembly, and/or a needle cover of a needle assembly.

[0095] The processing unit may be coupled to the needle sensor. The processing unit may be configured to receive the needle signal. The processing unit may be configured to control the drive module based on the needle signal. For example, the processing unit may be configured to control the drive module to start movement of the plunger rod only if a needle is present, and/or only if a needle cover is not present.

[0096] The needle sensor may comprise the contact member. For example, the contact member may be configured to be in the second contact member position if a needle cover, such as a needle with a needle cover, is present on the cartridge. Movement of the plunger rod may be based on the position of the contact member, e.g. on the contact member signal. Movement of the plunger rod to the mix plunger rod position and/or the prime plunger rod position and/or to the injection plunger rod position may be based on the position of the contact member, e.g. on the contact member signal. For example, the movement of the plunger rod to the mix plunger rod position and/or the prime plunger rod position and/or to the injection plunger rod position may require that the contact member signal is indicative of the contact member not being in the second contact member position, such as the contact member signal being indicative of the contact member being in the extended contact member position.

[0097] Alternatively or additionally, movement of the plunger rod to the mix plunger rod position and/or the prime plunger rod position and/or to the injection plunger rod position may be based on detection of a needle cover. For example, the movement of the plunger rod to the mix plunger rod position and/or the prime plunger rod position and/or to the injection plunger rod position may require that a needle cover is detected after reception of the cartridge in the cartridge receiver, and that afterwards no needle cover is detected, e.g. detection that the needle cover has been removed.

[0098] The processing unit may be configured to control the drive module to move the plunger rod to the mix plunger rod position and/or the prime plunger rod position and/or to the injection plunger rod based on the contact member signal. For example, the processing unit may be configured to control the drive module to move the plunger rod to the mix plunger rod position and/or the prime plunger rod position and/or to the injection plunger rod only if the contact member signal is indicative of the contact member not being in the second contact member position, such as the contact member signal being indicative of the contact member being in the extended contact member position.

[0099] Movement of the plunger rod may comprise movement having a plunger rod speed, such as a first plunger rod speed and/or a second plunger rod speed. The plunger rod speed may be based on the position of the plunger rod. The plunger rod may be moved to the pre-mix plunger rod position, such as from the retracted plunger rod position, with a pre-mix plunger rod speed. The plunger rod may be moved to the mix plunger rod position, such as from the pre-mix plunger rod position, with a mix plunger rod speed. The plunger rod may be moved to the prime plunger rod position, such as from the mix plunger rod position, with a prime plunger rod speed. The plunger rod may be moved to the injection plunger rod position, such as from the prime plunger rod position, with an injection plunger rod speed. The pre-mix plunger rod speed may be faster than the mix plunger rod speed. The mix-plunger rod speed may be between 1 mm/second and 3 mm/second, such as 1.7 mm/second.

[0100] The pre-mix plunger rod speed, the mix plunger rod speed, the prime plunger rod speed, and/or the injection plunger rod speed, may be based on a cartridge specification, such as on the cartridge code feature, such as on the code signal. The processing unit may be configured to determine the pre-mix plunger rod speed, the mix plunger rod speed, the prime plunger rod speed, and/or the injection plunger rod speed, based on the code signal.

[0101] The pre-mix plunger rod speed, the mix plunger rod speed, the prime plunger rod speed, and/or the injection plunger rod speed, may be based on temperature, such as temperature of the auto injector and/or of the cartridge and/or of the medicament, such as on the temperature signal. The processing unit may be configured to determine the pre-mix plunger rod speed, the mix plunger rod speed, the prime plunger rod speed, and/or the injection plunger rod speed, based on the temperature signal.

[0102] The processing unit may be configured to control the drive module to move the plunger rod to the pre-mix plunger rod position, such as from the retracted plunger rod position, with the pre-mix plunger rod speed. The processing unit may be configured to control the drive module to move

the plunger rod to the mix plunger rod position, such as from the pre-mix plunger rod position, with the mix plunger rod speed. The processing unit may be configured to control the drive module to move the plunger rod to the prime plunger rod position, such as from the mix plunger rod position, with the prime plunger rod speed. The processing unit may be configured to control the drive module to move the plunger rod to the injection plunger rod position, such as from the prime plunger rod position, with the injection plunger rod speed.

[0103] The processing unit may be configured to control the drive module to move the plunger rod to the pre-mix plunger rod position following reception of the cartridge detection signal and the first input signal. The processing unit may be configured to control the drive module to move the plunger rod to the mix-plunger rod position following completion of movement of the plunger rod to the pre-mix plunger rod position.

[0104] Movements of the plunger rod, such as movement to the pre-mix plunger rod position, to the mix plunger rod position, to the prime plunger rod position, to the injection plunger rod position, and/or to the retracted plunger rod position, may be preceded by one or more elapsed time, such as delays. For example, movement of the plunger rod to the prime plunger rod position and/or movement of the plunger rod to the injection plunger rod position may require that a reconstitution time has elapsed since completion of the movement of the plunger rod to the mix plunger rod position. The reconstitution time may be chosen to allow sufficient time to ensure that the medicament is reconstituted, e.g. that the first medicament component and second medicament component has been sufficiently mixed. The reconstitution time may be based on a cartridge specification, e.g. the reconstitution time may be based on the cartridge code feature, e.g. the reconstitution time may be based on the code signal.

[0105] The processing unit may be configured to control the drive module to move the plunger rod to the mix plunger rod position and/or the prime plunger rod position and/or to the injection plunger rod position and/or the retracted plunger rod position based on the one or more elapsed time. For example, the processing unit may be configured to control the drive module to move the plunger rod to the prime plunger rod position only after the reconstitution time has elapsed since completion of the movement of the plunger rod to the mix plunger rod position. Alternatively or additionally, the processing unit may be configured to control the drive module to move the plunger rod to the injection plunger rod position only after the reconstitution time has elapsed since completion of the movement of the plunger rod to the mix plunger rod position.

[0106] The plunger rod may be moved towards the retracted plunger rod position, such as to the retracted plunger rod position, following completion of the movement of the plunger rod to the injection plunger rod position. The processing unit may be configured to control the drive module to move the plunger rod towards the retracted plunger rod position following completion of the movement of the plunger rod to the injection plunger rod position.

[0107] Movement of the plunger rod towards the retracted plunger rod position, such as to the retracted plunger rod position, such as after completion of the movement of the plunger rod to the injection plunger rod position, may require that a dwell time has elapsed, e.g. since completion of the movement of the plunger rod to the injection plunger rod position. The dwell time may be chosen to allow sufficient time to ensure that the medicament is distributed into the tissue. The dwell time may be influenced by the medicament and/or concentration of the medicament and/or the amount of medicament. The dwell time may be based on a cartridge specification, e.g. the dwell time may be based on the cartridge code feature, e.g. the dwell time may be based on the code signal.

[0108] The processing unit may be configured to control the drive module to move the plunger rod towards the retracted plunger rod position only after the dwell time has elapsed since completion of the movement of the plunger rod to the injection plunger rod position.

[0109] The auto injector may comprise a user interface, such as a user interface allowing user input and/or provide visual and/or audible output to the user. The user interface may comprise the first

input member, a second input member, the contact member, and/or a first output member. The first output member may be configured to provide output to a user, such as audible and/or visual output. The first output member may comprise an LED and/or a speaker.

[0110] The processing unit may be configured to provide one or more user outputs via the user interface. The one or more user outputs may comprise a first user output and/or a second user output. For example, the processing unit may provide the first user output via the first output member.

[0111] The processing unit may be configured to provide a user output, e.g. indicative of the injection being complete, via the user interface after the dwell time has elapsed since completion of the movement of the plunger rod to the injection plunger rod position.

[0112] The processing unit may be configured to provide a user output indicative of the orientation signal via the user interface. For example, while moving the plunger rod to the mix plunger rod position and/or to the prime plunger rod position. A user output indicative of the orientation signal may comprise a beeping sound with a varying beeping interval based on the orientation signal. For example, the varying beeping interval may be fast when the orientation signal is far away from the predetermined orientation and/or from vertical, and/or the varying beeping interval may be slow when the orientation signal is close to the predetermined orientation and/or vertical.

Description

BRIEF DESCRIPTION OF THE FIGURES

[0113] A more detailed description follows below with reference to the drawing, in which:

[0114] FIG. 1 illustrates an exemplary auto injector;

[0115] FIG. 2 illustrates an exemplary auto injector with a cartridge;

[0116] FIG. 3 schematically illustrates an exemplary cartridge;

[0117] FIGS. 4A, 4B, 4C and 4D schematically illustrate an exemplary cartridge assembly with exemplary cartridge code features;

[0118] FIG. 5 schematically illustrates an exemplary auto injector with a cartridge assembly;

[0119] FIGS. 6A, 6B, 6C, and 6D schematically illustrate an auto injector and a cartridge assembly;

[0120] FIG. 7 shows a block diagram of an exemplary auto injector;

[0121] FIGS. 8A, 8B, 8C, 8D, 8E, and 8F schematically illustrate an exemplary cartridge assembly and a plunger rod in exemplary positions;

[0122] FIG. 9 shows an exemplary graph of resistance vs. position;

[0123] FIG. 10 shows a flow chart of an exemplary method;

[0124] FIG. 11 shows a flow chart of an exemplary method;

[0125] FIG. 12 shows a flow chart of an exemplary method;

[0126] FIGS. 13A, 13B, 13C, and 13D schematically illustrate an exemplary user interface; and

[0127] FIG. 14 shows a flow chart of an exemplary method.

DETAILED DESCRIPTION

[0128] Various embodiments are described hereinafter with reference to the figures. Like reference numerals refer to like elements throughout. Like elements will, thus, not be described in detail with respect to the description of each figure. It should also be noted that the figures are only intended to facilitate the description of the embodiments. They are not intended as an exhaustive description of the claimed invention or as a limitation on the scope of the claimed invention. In addition, an illustrated embodiment needs not have all the aspects or advantages shown. An aspect or an advantage described in conjunction with a particular embodiment is not necessarily limited to that embodiment and can be practiced in any other embodiments even if not so illustrated, or if not so explicitly described.

[0129] FIG. 1 illustrates an exemplary auto injector 4. The auto injector 4 may be configured for

administering a medicament. The auto injector **4** may be an electronic auto injector.

[0130] The auto injector **4** comprises a housing **6**. The auto injector **4** comprises a cartridge receiver **300**. The cartridge receiver is configured to receive a cartridge and/or a cartridge assembly comprising a cartridge. The cartridge may contain the medicament.

[0131] The cartridge receiver **300** has a cartridge receiver opening **301**. The cartridge receiver **300** is configured to receive the cartridge and/or the cartridge assembly through the cartridge receiver opening **301** in a cartridge receiving direction **304** along a longitudinal axis L.

[0132] The auto injector **4** may comprise a user interface **1100**, as illustrated. The auto injector **4** comprises a trigger member, such as the contact member **1102**. The contact member **1102** may be configured to be pressed against an injection site. The contact member **1102** may be movable in the cartridge receiving direction **304**, relative to the housing, if pressed against the injection site. The contact member **1102** may be part of the user interface **1100**.

[0133] The user interface **1100** comprises a first input member **1108**, e.g. a button. The first input member **1108** may provide for a user input from a user. For example, the first input member **1108** may be used for receiving a push from a user to proceed to a next step.

[0134] The user interface **1100** comprises a first output member **1110** as illustrated, e.g. a plurality of LEDs. The first output member **1110** may provide for a user output to a user. The user interface **1100** may comprise a second output member (not shown), e.g. a speaker. The second output member may be configured to provide audible output to the user. For example, the first output member **1110** and/or the second output member may be used to indicate a step in the procedure to the user and/or to indicate an error message.

[0135] FIG. **1** illustrates an exemplary auto injector **4**. The auto injector **4** may be configured for administering a medicament. The auto injector **4** may be an electronic auto injector.

[0136] The auto injector **4** comprises a housing **6**. The auto injector **4** comprises a cartridge receiver **300**. The cartridge receiver is configured to receive a cartridge and/or a cartridge assembly comprising a cartridge. The cartridge may contain the medicament.

[0137] The cartridge receiver **300** has a cartridge receiver opening **301**. The cartridge receiver **300** is configured to receive the cartridge and/or the cartridge assembly through the cartridge receiver opening **301** in a cartridge receiving direction **304** along a longitudinal axis L.

[0138] The auto injector **4** may comprise a user interface **1100**, as illustrated. The auto injector **4** comprises a trigger member, such as the contact member **1102**. The contact member **1102** may be configured to be pressed against an injection site. The contact member **1102** may be movable in the cartridge receiving direction **304**, relative to the housing, if pressed against the injection site. The contact member **1102** may be part of the user interface **1100**.

[0139] The user interface **1100** may comprise a first input member **1108** as illustrated, e.g. a button. The first input member **1108** may provide for a user input from a user. For example, the first input member **1108** may be used for receiving a push from a user to proceed to a next step.

[0140] The user interface **1100** may comprise a first output member **1110** as illustrated, e.g. a plurality of LEDs. The first output member **1110** may provide for a user output to a user. The user interface **1100** may comprise a second output member (not shown), e.g. a speaker. The second output member may be configured to provide audible output to the user. For example, the first output member **1110** and/or the second output member may be used to indicate a step in the procedure to the user and/or to indicate an error message.

[0141] FIG. **2** illustrates an exemplary system **2**. The system **2** comprises an auto injector **4**, as described in relation to FIG. **1**, and an exemplary cartridge **700** received in the cartridge receiver **300**. The cartridge **700** is shown with a needle cover **908**. The needle cover **908** extending out of the contact member **1102** to allow removal of the needle cover **908** from the cartridge **700**.

[0142] FIG. **3** schematically illustrates an exemplary cartridge **700**, such as a cartridge **700** being configured to be received in the cartridge receiver of an auto injector, such as the auto injector described in relation to previous figures.

[0143] The cartridge **700** comprises a cartridge compartment **702**. The cartridge compartment **702** may be configured for containing a medicament. The cartridge **700** has a first end **718** and a second end **720**. The cartridge **700** comprises a cartridge outlet **714** at the first cartridge end **718**. The cartridge may be configured to expel medicament through the cartridge outlet **714**.

[0144] The cartridge comprises a first stopper **708** movable inside the cartridge compartment, e.g. in a first stopper direction **722**, e.g. towards the first cartridge end. For example, the medicament may be expelled through the cartridge outlet **714** upon movement of the first stopper **708** in the first stopper direction. The cartridge comprises a cartridge back face **716** at the second cartridge end. The cartridge back face **716** comprises a cartridge back end opening for providing access to the first stopper **708** for a plunger rod.

[0145] As illustrated, the cartridge **700** may be a dual chamber cartridge. The cartridge comprises a second stopper **710** movable inside the cartridge compartment **702**, e.g. in the first stopper direction **722**, e.g. towards the first cartridge end. The cartridge compartment **702** comprises a first cartridge subcompartment **704** and a second cartridge subcompartment **706**. The first cartridge subcompartment **704** is between the first stopper **708** and the second stopper **710**. The second cartridge subcompartment **706** is between the second stopper **710** and the cartridge outlet **714**. The cartridge comprises a bypass section **712** for providing fluid communication between the first cartridge subcompartment and the second cartridge subcompartment. The bypass section **712** provides fluid communication between the first cartridge subcompartment and the second cartridge subcompartment when the second stopper **710** is positioned in the bypass section **712**.

[0146] The first cartridge subcompartment **704** contains a first medicament component **792** of the medicament **790**. The first medicament component **792** may be a liquid as illustrated. The second cartridge subcompartment **706** contains a second medicament component **794** of the medicament **790**. The second medicament component **794** may be a powder composition. By positioning of the second stopper **710** within the bypass section **712**, the first medicament component **792** may be transmitted into the second cartridge subcompartment **706** via the bypass section **712**, thereby mixing the first medicament component **792** and the second medicament component **794** to achieve the combined medicament **790**.

[0147] FIGS. **4A**, **4B**, **4C**, and **4D** schematically illustrates an exemplary cartridge assembly **600**. The cartridge assembly **600** comprises an exemplary cartridge **700** and an exemplary cartridge code feature **1000**. The cartridge **700** has a first cartridge end **718** and a second cartridge end **720**. The first stopper direction **722** is from the second cartridge end **720** to the first cartridge first **718**. The cartridge code feature **1000** is positioned near the second cartridge end **720**, e.g. closer to the second cartridge end **720** than the first cartridge end **718**. In another exemplary cartridge assembly, the cartridge code feature **1000** may be positioned near the first cartridge end **718**.

[0148] FIGS. **4A**, **4B**, **4C**, and **4D** illustrates different types of exemplary cartridge code features **1000**.

[0149] FIG. **4A** illustrates an exemplary cartridge assembly **600**, wherein the cartridge code feature **1000** comprises two strips. The two strips may be coloured, e.g. differently coloured. The combination and/or sequence of colours may be indicative of a code of the cartridge code feature **1000**.

[0150] FIG. **4B** illustrates an exemplary cartridge assembly **600**, wherein the cartridge code feature **1000** comprises bar codes. The cartridge code feature **1000** may comprise one or more bar codes. The bar code may be indicative of a number indicative of a code of the cartridge code feature **1000**.

[0151] FIG. **4C** illustrates an exemplary cartridge assembly **600**, wherein the cartridge code feature **1000** comprises differently grated strips. For example, as illustrated, the cartridge code feature **1000** may comprise two strips wherein the first strip is grated at 45 deg., and the second strip is grated at -45 deg. The grating, and/or the grating of the strips relative to each other, may be indicative of a code of the cartridge code feature **1000**.

[0152] FIG. **4D** illustrates an exemplary cartridge assembly **600**, wherein the cartridge code feature

1000 comprises an electromagnetically readable tag, such as an RFID tag or an NFC tag. The electromagnetically readable tag may contain data that is indicative of a code of the cartridge code feature **1000**.

[0153] FIG. 5 illustrates an exemplary system 2. The system 2 comprises an auto injector 4, as described, for example, in relation to FIG. 1, and an exemplary cartridge assembly 600. The cartridge assembly 600 comprises a cartridge 700 with a cartridge compartment 702, a needle assembly 900, and a cartridge code feature 1000. The cartridge assembly 600 is received in the auto injector 4.

[0154] The cartridge assembly 600 comprises a cartridge holder 800. The cartridge holder 800 is configured for retention of the cartridge 700 in the cartridge receiver 300 of the auto injector 4. The cartridge holder 800 comprises a cartridge retention member 808. The cartridge retention member 808 engages with the cartridge receiver 300 for reception and retention of the cartridge 700 and the cartridge assembly 600 in the cartridge receiver 300.

[0155] The needle assembly 900 comprises a needle 902 and a needle hub 904. The needle assembly 900 is attached to the cartridge 700, e.g. by the needle hub 904 having a cartridge holder coupling portion 906, e.g. a threaded coupling portion, being in engagement with a needle assembly coupling portion 812 of the cartridge holder 800. The needle 902 extends through the cartridge outlet 714 of the cartridge 700. The cartridge outlet 714 may be blocked by a resilient sealing being penetrated by the needle 902, when the needle assembly 900 is attached to the cartridge 700.

[0156] The auto injector 4 comprises a code sensor 24 configured to read the cartridge code feature 1000. When the cartridge assembly 600 is inserted, as shown, the cartridge code feature 1000 is lined up with the code sensor 24.

[0157] The auto injector 4 comprises a plunger rod 400. The plunger rod 400 is configured to advance a first stopper of the cartridge 700. The plunger rod 400 comprises an outer plunger rod 404 with an inner thread, and an inner plunger rod 402 with an outer thread. The thread of the inner plunger rod 402 is in engagement with the thread of the outer plunger rod 404. The outer plunger rod 404 is prevented from rotating relative to the housing of the auto injector. The movement of the plunger rod 400 comprises rotation of the inner plunger rod 402. The rotation of the inner plunger rod 402 results in translational movement of the outer plunger rod 404, due to the outer plunger rod 404 being rotationally restricted. The outer plunger rod 404, when moved translationally in the first stopper direction 722, is configured to abut the first stopper of the cartridge 700, and to move the first stopper in the first stopper direction 722.

[0158] The drive module 500 is coupled to actuate the plunger rod 400. The drive module 500 is electrically connected to a battery for receiving electrical power. The drive module 500 comprises a motor 502, such as an electro-mechanical motor, such as a DC motor. The drive module 500 comprises a transmission 504 for coupling the motor 502 to the inner plunger rod 402 of the plunger rod 400.

[0159] Although the example shown comprises a motor 502, which may be an electro-mechanical motor, it will be readily understood that the auto injector 4 may be realised having an alternative drive module, such as comprising a solenoid motor, a shape memory metal engine, an arrangement of springs and/or a pressurized gas configured to actuate the plunger rod 400.

[0160] The auto injector 4 comprises an ejection sensor 26, such as a plunger rod position sensor. The ejection sensor 26 is configured to detect the position of the plunger rod 400. In the illustrated example, the ejection sensor 26 comprises a tachometer configured to count/detect the revolutions of the motor 502. Thus, the position of the plunger rod 400 may be determined based on the count of revolutions of the motor 502. The ejection sensor 26 may, based on the detection of the position of the plunger rod 400, detect the expelling of medicament and/or air in the cartridge compartment. The position of the plunger rod 400 may be indicative of the position of the first stopper of the cartridge 700, e.g. the most advanced position of the plunger rod 400, e.g. while the cartridge 700

is in the cartridge receiver **300**, may be indicative of the position of the first stopper of the cartridge **700**.

[0161] FIGS. **6A**, **6B**, **6C**, and **6D** schematically illustrate an auto injector **4** and a cartridge assembly **600**. FIGS. **6A**, **6B**, **6C**, and **6D** schematically illustrates exemplary positions of a contact member **1102** of the auto injector **4** in various situations.

[0162] The auto injector **4** comprises a cartridge receiver **300** configured for receiving and retaining a cartridge. The auto injector **4** comprises a contact member **1102**. The contact member **1102** may be movable between an extended contact member position and a retracted contact member position. The contact member **1102** comprises a contact member protruding part **1112**. The contact member protruding part **1112** is configured to move with the contact member **1102**. The contact member **1102** may be biased, e.g. by a contact member spring (not shown), towards the extended contact member position.

[0163] The contact member comprises a needle cover engagement member **1114**. The needle cover engagement member **1114** is configured to abut a needle cover abutment face, e.g. of a needle cover positioned on the cartridge inserted into the cartridge receiver **300**.

[0164] The auto injector **4** comprises a contact member sensor **1104** configured to detect a position of the contact member **1102**. The contact member sensor **1104** comprises a first contact member sensor **1130** and a second contact member sensor **1132**. The first contact member sensor **1130** and the second contact member sensor **1132** may be optical sensors. The contact member sensor **1104** detects the position of the contact member **1102** by the contact member protruding part **1112** covering the first contact member sensor **1130** when the contact member **1102** is in a first contact member position, and the contact member protruding part **1112** covering the second contact member sensor **1132** when the contact member **1102** is in a second contact member position.

[0165] The first contact member position may be detected by the first contact member sensor **1130** being covered and the second contact member sensor **1132** being covered. The second contact member position may be detected by the first contact member sensor **1130** not being covered and the second contact member sensor **1132** being covered. The extended contact member position may be detected by the first contact member sensor **1130** not being covered and the second contact member sensor **1132** not being covered.

[0166] FIG. **6A** schematically illustrates the auto injector **4** with no received cartridge and/or cartridge assembly. The contact member **1102** is in the extended contact member position. A cartridge may be inserted into the cartridge receiver **300** in the cartridge receiving direction **304** through the contact member **1102** defining a cartridge receiver opening **301**.

[0167] FIG. **6B** schematically illustrates the auto injector **4** with a cartridge assembly **600** received. The cartridge assembly **600** comprises a cartridge **700**, a cartridge holder **800** and a needle assembly **900**. The needle assembly comprises a needle **902** and a needle cover **908**. The needle cover has a needle cover abutment face **910**. The needle cover abutment face **910** engages the needle cover engagement member **1114** of the contact member **1102**. The contact member **1102** is in the second contact member position, e.g. caused by the presence of the needle cover **908** and the abutment of the needle cover abutment face **910** on the needle cover engagement member **1114**. The contact member protruding part **1112** covers the second contact member sensor **1132**. The contact member protruding part **1112** does not cover the first contact member sensor **1130**.

[0168] FIG. **6C** schematically illustrates the auto injector **4** with a cartridge assembly **600** received. Compared to FIG. **6B**, the needle cover **908** has been removed. The contact member **1102** is in the extended contact member position. The contact member **1102** is allowed to be moved to the extended contact member position since the needle cover abutment face **910** does not abut the needle cover engagement member **1114**. The contact member protruding part **1112** has moved with the contact member **1102**. The contact member protruding part **1112** does not cover the second contact member sensor **1132**. The contact member protruding part **1112** does not cover the first contact member sensor **1130**.

[0169] FIG. 6D schematically illustrates the auto injector **4** with a cartridge assembly **600** received. The contact member **1102** is in the first contact member position. The first contact member position may be the retracted contact member position, or close to the retracted contact member position. The contact member **1102** may have been moved to the first contact member position by the contact member **1102** being pressed against an injection site, thereby inserting the needle **902** into the injection site. The contact member protruding part **1112** has moved with the contact member **1102**. The contact member protruding part **1112** covers the first contact member sensor **1130**. The contact member protruding part **1112** covers the second contact member sensor **1132**.

[0170] FIG. 7 shows a block diagram of an exemplary auto injector **4**. The auto injector **4** comprises a plurality of sensors **22, 24, 26, 28, 30, 32, 34**, a processing unit **20**, a drive module **500**, and a user interface **1100**. The sensors **22, 24, 26, 28, 30, 32, 34** are coupled to the processing unit **20**. The user interface **1100** is coupled to the processing unit **20**. The processing unit is coupled to the drive module **500**.

[0171] The processing unit **20** receives signals from the sensors **22, 24, 26, 28, 30, 32, 34** and the user interface **1100**. The processing unit **20** is configured to control the drive module **500**. The processing unit **20** may control the drive module **500** based on one or more of the received signals from the sensors **22, 24, 26, 28, 30, 32, 34** and the user interface **1100**. The processing unit **20** is configured to provide user outputs via the user interface **1100**.

[0172] The auto injector **4** comprises an orientation sensor **22**. The orientation sensor **22** is configured to provide an orientation signal indicative of the orientation of a cartridge received in the auto injector **4**. For example, the orientation sensor **22** may be configured to detect the orientation of the auto injector **4**. The orientation of the cartridge may be determined based on the orientation of the auto injector **4**. The orientation sensor **22** may be configured to detect the direction of gravity. For example, the orientation sensor **22** may comprise an accelerometer.

[0173] The processing unit **20** is coupled to the orientation sensor **22**. The processing unit **20** is configured to receive the orientation signal. The processing unit **20** may determine the orientation of the cartridge based on the orientation signal. The processing unit **20** may control the drive module **500** based on the orientation signal. For example, the processing unit **20** may be configured to control the drive module **500** to move the plunger rod based on the orientation signal. For example, the processing unit **20** may be configured to control the drive module **500** to move the plunger rod towards the extended plunger rod position, such as to a pre-mix plunger rod position and/or a mix plunger rod position and/or the prime plunger rod position, only if the cartridge outlet is pointing upwards. Alternatively or additionally, the processing unit **20** may provide user output via the user interface **1100** based on the orientation signal.

[0174] The auto injector **4** comprises a code sensor **24**. The code sensor **24** is configured to read a cartridge code feature, and provide a code signal indicative of a cartridge code feature. For example, the code sensor may be configured to read/detect a colour code.

[0175] The processing unit **20** is coupled to the code sensor **24**. The processing unit **20** is configured to receive the code signal. The processing unit **20** may determine the cartridge code feature of the cartridge assembly based on the code signal. The processing unit **20** may control the drive module **500** based on the code signal. For example, the processing unit **20** may be configured to control the drive module **500** to move the plunger rod towards the extended plunger rod position, such as to the pre-mix plunger rod position and/or the mix plunger rod position and/or the prime plunger rod position and/or the injection plunger rod position, based on the code signal. The processing unit **20** may be configured to determine a threshold, such as a plunger rod threshold, and/or a resistance threshold, based on the code signal. Alternatively or additionally, the processing unit **20** may provide user output via the user interface **1100** based on the code signal.

[0176] The auto injector **4** comprises an ejection sensor **26**, such as a plunger rod position sensor. The ejection sensor **26** is configured to detect the position of the plunger rod of the auto injector **4**, and provide an ejection sensor signal indicative of the position of the plunger rod. The ejection

sensor **26** may comprise a tachometer coupled to the drive module **500**.

[0177] The processing unit **20** is coupled to the ejection sensor **26**. The processing unit **20** is configured to receive the ejection sensor signal. The processing unit **20** may determine the position of the plunger rod based on the ejection sensor signal. The processing unit **20** may control the drive module **500** based on the ejection sensor signal. For example, the processing unit **20** may be configured to control the drive module **500** to start, stop or continue movement of the plunger rod based on the ejection sensor signal. For example, the processing unit **20** may be configured to determine a present plunger rod position based on the ejection sensor signal. The plunger rod being in the pre-mix plunger rod position and/or the mix plunger rod position and/or the prime plunger rod position and/or the injection plunger rod position may be determined based on the ejection sensor signal. Alternatively or additionally, the processing unit **20** may provide user output via the user interface **1100** based on the ejection sensor signal.

[0178] The auto injector **4** comprises a cartridge sensor **28**. The cartridge sensor **28** is configured to detect reception of a cartridge assembly in the auto injector **4**. The cartridge sensor **28** provides a cartridge sensor signal indicative of reception of a cartridge assembly.

[0179] The processing unit **20** is coupled to the cartridge sensor **28**. The processing unit **20** is configured to receive the cartridge sensor signal. The processing unit **20** may control the drive module **500** based on the cartridge sensor signal. For example, the processing unit **20** may be configured to control the drive module **500** to start movement of the plunger rod if a cartridge assembly is received, and/or only if a cartridge assembly is received. Alternatively or additionally, the processing unit **20** may provide user output via the user interface **1100** based on the cartridge sensor signal.

[0180] The code sensor **24** and the cartridge sensor **28** may be the same sensor, e.g. the code sensor **24** may be configured to detect reception of a cartridge assembly and subsequently read the cartridge code feature.

[0181] The auto injector **4** comprises a needle sensor **30**. The needle sensor **30** is configured to detect a needle, and/or a needle assembly, and/or a needle cover of a needle assembly, of the cartridge assembly, when the cartridge assembly is received in the auto injector **4**. The needle sensor **30** provides a needle signal indicative of the presence of a needle, and/or a needle assembly, and/or a needle cover of a needle assembly, of the cartridge assembly.

[0182] The processing unit **20** is coupled to the needle sensor **30**. The processing unit **20** is configured to receive the needle signal. The processing unit **20** may control the drive module **500** based on the needle signal. For example, the processing unit **20** may be configured to control the drive module **500** to start movement of the plunger rod, e.g. towards the extended plunger rod position, such as to the pre-mix plunger rod position and/or the mix plunger rod position and/or the prime plunger rod position and/or the injection plunger rod position, only if a needle is present, and/or only if a needle cover is not present, such as removed. Detection of a needle cover may be indicative of a needle being present. The processing unit **20** may be configured to control the drive module **500** to start only if a needle cover has been detected, and subsequently is not detected, e.g. it has been removed. Alternatively or additionally, the processing unit **20** may provide user output via the user interface **1100** based on the needle signal.

[0183] The needle sensor **30** may be part of the contact member sensor, as exemplified in FIGS. **6A**, **6B**, **6C**, and **6D**.

[0184] The auto injector **4** comprises a temperature sensor **32**. The temperature sensor **32** is configured to detect a temperature, such as a temperature of the auto injector and/or of the cartridge and/or of the medicament. The temperature sensor **32** is configured to provide a temperature signal indicative of the temperature.

[0185] The processing unit **20** is coupled to the temperature sensor **32**. The processing unit **20** is configured to receive the temperature signal. The processing unit **20** may be configured to determine the temperature, such as the temperature of the auto injector and/or of the cartridge

and/or of the medicament based on the temperature signal. The processing unit **20** may control the drive module **500** based on the temperature signal. For example, the processing unit **20** may be configured to control the drive module **500** to move the plunger rod towards the extended plunger rod position, such as to the pre-mix plunger rod position and/or the mix plunger rod position and/or the prime plunger rod position and/or the injection plunger rod position, based on the temperature signal. The processing unit **20** may determine plunger rod positions based on the temperature signal. For example, the processing unit **20** may be configured to determine the pre-mix plunger rod position and/or the mix plunger rod position and/or the prime plunger rod position and/or the injection plunger rod position based on the temperature signal. Alternatively or additionally, the processing unit **20** may provide user output via the user interface **1100** based on the temperature signal.

[0186] The auto injector **4** comprises a resistance sensor **34**. The resistance sensor **34** is configured to detect resistance against movement of the plunger rod of the auto injector **4**. The resistance sensor **34** may be configured to detect resistance against movement of the plunger rod based on measurements of the drive module **500**. For example, the resistance sensor **34** may be configured to detect the electrical current of a motor of the drive module **500**. The resistance sensor **34** is configured to provide a resistance signal indicative of resistance against movement of the plunger rod.

[0187] The processing unit **20** is coupled to the resistance sensor **34**. The processing unit **20** is configured to receive the resistance signal. The processing unit **20** may be configured to determine the resistance against movement of the plunger rod based on the resistance signal. The processing unit **20** may control the drive module **500** based on the resistance signal. For example, the processing unit **20** may be configured to control the drive module **500** to adjust movement of the plunger rod based on the resistance signal. For example, the processing unit **20** may be configured to control the drive module **500** to start, stop or continue movement of the plunger rod based on the resistance signal. Alternatively or additionally, the processing unit **20** may provide user output via the user interface **1100** based on the resistance signal.

[0188] The auto injector **4** is illustrated comprising all of the above mentioned sensors. However, alternatively, the auto injector may comprise only one or any combination of one or more of the above mentioned sensors.

[0189] The auto injector comprises a user interface **1100**. The user interface **1100** may comprise one or more input members, e.g. a first input member, for receiving a user input. The user interface is configured to provide a user input signal indicative of the received user input. The user interface **1100** may provide a first input signal and/or a second input signal.

[0190] The processing unit **20** is coupled to the user interface **1100**. The processing unit **20** is configured to receive the user input signal, such as the first input signal and/or the second input signal. The processing unit **20** may control the drive module **500** based on the user input signal. For example, the processing unit **20** may be configured to control the drive module **500** to move the plunger rod towards the extended plunger rod position, such as to the pre-mix plunger rod position and/or the mix plunger rod position and/or the prime plunger rod position and/or the injection plunger rod, based on the user input signal and/or following the user input signal.

[0191] The auto injector comprises a housing **6** accommodating the sensors **22, 24, 26, 28, 30, 32, 34**, processing unit **20**, user interface **1100** and drive module **500**.

[0192] FIGS. **8A, 8B, 8C, 8D, 8E**, and **8F** schematically illustrate exemplary cartridge assemblies **600** and a plunger rod **400**. The cartridge assembly **600** comprises a cartridge **700**, such as the cartridge described in relation to FIG. **3**, a cartridge holder **800**, and a needle assembly **900**. For intelligibility, the auto injector comprising the plunger rod **400** is not shown.

[0193] The cartridge holder **800** comprises a cartridge retention member **808**. The cartridge retention member **808** is configured for engagement with a cartridge receiver of the auto injector. The cartridge holder **800** comprises a needle assembly coupling portion **812**. The needle assembly

coupling portion **812** is configured for engagement with a cartridge holder coupling portion **906** of the needle assembly **900**. The needle assembly coupling portion **812** allows attachment of a needle to the cartridge **700**.

[0194] The needle assembly **900** comprises a needle **902** and a needle hub **904**. The needle assembly **900** is attached to the cartridge **700**, e.g. by the needle hub **904** having a cartridge holder coupling portion **906**, e.g. a threaded coupling portion, being in engagement with a needle assembly coupling portion **812** of the cartridge holder **800**. The needle **902** extends through the cartridge outlet **714** of the cartridge **700**.

[0195] FIG. **8A** schematically illustrates a situation wherein the plunger rod **400** is in an exemplary retracted plunger rod position. The cartridge **700** may be a new cartridge. The first stopper **708** is positioned in an initial position. The second stopper **710** is in an initial position, e.g. behind the bypass section **712**, wherein the bypass section **712** does not form a fluid connection between the first subcompartment **704** and the second subcompartment **706**.

[0196] FIG. **8B** schematically illustrates a situation wherein the plunger rod **400** is in an exemplary pre-mix plunger rod position. Compared to FIG. **8A**, the plunger rod **400** is moved towards an extended plunger rod position. A plunger rod front end **410** of the plunger rod **400** abuts the first stopper **708**. Thus, the plunger rod **400** has started to move the first stopper **708** in the first stopper direction **722**, by movement in the first plunger rod direction **422**. The second stopper **710** is in a position, e.g. behind the bypass section **712**, wherein the bypass section **712** does not form a fluid connection between the first subcompartment **704** and the second subcompartment **706**.

[0197] FIG. **8C** schematically illustrates a situation wherein the plunger rod **400** is in an exemplary position wherein a fluid connection is established between the first subcompartment **704** and the second subcompartment **706** via the bypass section **712**. The plunger rod front end **410** of the plunger rod **400** abuts the first stopper **708**. The plunger rod **400** has moved the first stopper **708** in the first stopper direction **722**, by movement in the first plunger rod direction **422**. The second stopper **710** is in the bypass section **712**, wherein the bypass section **712** forms a fluid connection between the first subcompartment **704** and the second subcompartment **706**. Thus, further movement of the first stopper **708** in the first stopper direction **722**, e.g. by movement of the plunger rod **400** in the first plunger rod direction **422**, will transmit the content of the first subcompartment **704**, e.g. a first medicament component (not shown) into the second subcompartment **706**, e.g. through the bypass section **712**.

[0198] FIG. **8D** schematically illustrates a situation wherein the plunger rod **400** is in an exemplary mix plunger rod position. The plunger rod front end **410** abuts the first stopper **708**. The first stopper **708** abuts the second stopper **710**. The first subcompartment **704** is compressed. The second stopper **710** is in a position after the bypass section **712**. Thus, the fluid connection between the first subcompartment **704** and the second subcompartment **706** has been closed.

[0199] FIG. **8E** schematically illustrates a situation wherein the plunger rod **400** is in an exemplary prime plunger rod position. Compared to FIG. **8D**, the plunger rod **400** is moved towards an extended plunger rod position, e.g. to expel air from the cartridge compartment **702**.

[0200] FIG. **8F** schematically illustrates a situation wherein the plunger rod **400** is in an exemplary injection plunger rod position. For example after complete injection, the plunger rod **400** may be in the injection plunger rod position. The first stopper **708** and the second stopper **710** is in a position close to the cartridge outlet **714**. Contents of the cartridge component, e.g. the medicament, has been expelled, e.g. through the cartridge outlet **714** and/or the needle **902**. A residual volume of the medicament may be remaining in the cartridge.

[0201] FIG. **9** shows an exemplary trace **T** of resistance R_e against movement of the plunger rod dependent on the position **P** of the plunger rod. The plunger rod is moved from a retracted plunger rod position **PR** to an extended plunger rod position **PE**. In the beginning of the movement, the resistance against movement of the plunger rod is constant Ex_1 , e.g. the plunger rod does not yet push a stopper. Afterwards, a plunger rod front end of the plunger rod abuts a first stopper of the

cartridge, and the resistance against movement of the plunger rod increases Ex2. The increased resistance is caused by the resistance against movement of the first stopper, e.g. due to frictional force. The resistance may decrease slightly after the first stopper has started moving, as illustrated. When the plunger rod approaches the extended plunger rod position PE, the resistance may increase again Ex3, e.g. due to the first stopper approaching an end of the cartridge.

[0202] The trace T is an example of resistance against plunger rod movement when the cartridge received is a new and/or unused and/or normal cartridge. Determining a cartridge parameter may be based on the resistance and/or plunger rod position. Determining the cartridge parameter may be based on one or more thresholds, such as resistance thresholds, such as a low resistance threshold Re1 and/or a high resistance threshold Re2, and/or plunger rod thresholds, such as a first plunger rod threshold P1 and/or a second plunger rod threshold P2.

[0203] Other situations, such as situations wherein the cartridge received is apparently used and/or flawed, are exemplified by additional exemplary traces, T2, T3, T4.

[0204] Trace T2 illustrates an exemplary situation wherein the resistance against movement increases above the low resistance threshold Re1 before the plunger rod position has reached the first plunger rod threshold P1. Such situation may for example indicate a flawed cartridge, or that something is blocking the plunger rod from moving. Following such situation, the plunger rod may be retracted to the retracted plunger rod position and an error message may be provided through a user interface.

[0205] Trace T3 illustrates an exemplary situation wherein the resistance against movement has not increased above the low resistance threshold Re1 before the plunger rod position has reached the second plunger rod threshold P2. Such situation may for example indicate a cartridge wherein the first stopper is in an advanced position, e.g. a used cartridge. Following such situation, the plunger rod may be retracted to the retracted plunger rod position and an error message may be provided through a user interface.

[0206] Trace T4 illustrates an exemplary situation wherein the resistance against movement increases above the high resistance threshold Re2, e.g. after the plunger rod position has passed the first plunger rod threshold P1. Such situation may for example indicate that the first stopper is blocked from moving, e.g. the cartridge may be flawed. Following such situation, the plunger rod may be retracted to the retracted plunger rod position and an error message may be provided through a user interface.

[0207] The thresholds, such as the low resistance threshold Re1, the high resistance threshold Re2, the first plunger rod threshold P1, and/or the second plunger rod threshold P2 may be individually determined for the cartridge received. For example, the processing unit of the auto injector may be configured to determine one or more of the thresholds, based on a cartridge code feature of the cartridge and/or cartridge assembly received.

[0208] FIG. 10 shows a flow chart of an exemplary method 4000 for operating an auto injector. The method 4000 comprises: receiving 4002 a first input signal;

[0209] detecting 4004 reception of the cartridge, e.g. in a cartridge receiver of the auto injector; moving 4006 a plunger rod to a mix plunger rod position; determining 4008 orientation of the cartridge; moving 4010 the plunger rod to a prime plunger rod position based on the orientation of the cartridge; receiving 4012 a trigger event; and moving 4014 the plunger rod to an injection plunger rod position.

[0210] Receiving 4002 the first input signal may comprise receiving a user input signal from a user interface, e.g. originating from a user pressing a button. The first input signal may originate from a user turning on the auto injector.

[0211] Detecting 4004 reception of the cartridge may comprise detection of a user inserting the cartridge into the cartridge receiver through a cartridge receiver opening. Detecting 4004 reception of the cartridge may comprise detecting presence of a cartridge in the cartridge receiver.

[0212] Receiving 4002 the first input signal and detecting 4004 reception of the cartridge may be

interchanged.

[0213] Moving **4006** the plunger rod to the mix plunger rod position may follow detection **4004** of the cartridge being received in the cartridge receiver and reception **4002** of the first input signal. For example, moving **4006** the plunger rod to the mix plunger rod position may be performed only after a cartridge is detected **4004** and the first input signal is received **4002**.

[0214] Determining **4008** orientation of the cartridge may comprise determining orientation by an orientation sensor, such as an accelerometer. Determining **4008** orientation of the cartridge may comprise determining orientation of the auto injector. Determining **4008** orientation of the cartridge may comprise determining whether an outlet of the cartridge is pointing upwards.

[0215] Alternatively or additionally, moving **4006** the plunger rod to the mix plunger rod position may be preceded by determining **4008** orientation of the cartridge. For example, moving **4006** the plunger rod to the mix plunger rod position may require that the outlet of the cartridge is pointing upwards, e.g. determined by determining **4008** orientation of the cartridge.

[0216] Moving **4010** the plunger rod to a prime plunger rod position may follow completion of movement of the plunger rod to the mix plunger rod position. Moving **4010** the plunger rod to a prime plunger rod position may follow completion of movement of the plunger rod to the mix plunger rod position and an additional predetermined delay, e.g. to allow reconstitution of the medicament.

[0217] Moving **4010** the plunger rod to a prime plunger rod position may require that the outlet of the cartridge is pointing upwards, e.g. determined by determining **4008** orientation of the cartridge. Moving **4010** the plunger rod to a prime plunger rod position may be temporary paused if the orientation of the cartridge is not within a predefined range of orientations.

[0218] Receiving **4012** the trigger event may comprise receiving a user input signal from a user interface, e.g. receiving the trigger event from a trigger member, e.g. originating from a user pressing a button. The trigger event may originate from a user indicating a start of injection. The trigger event may originate from a user pressing a front part of the auto injector against an intended injection site. The trigger event may comprise a contact member signal being indicative of a contact member of the auto injector being in a first contact member position.

[0219] Moving **4014** the plunger rod to an injection plunger rod position may result in ejection of the medicament through the cartridge outlet, such as through a needle. Moving **4014** the plunger rod may follow reception of the trigger event **4012**, such as after completion of movement **4010** of the plunger rod to the prime plunger rod position.

[0220] FIG. **11** shows a flow chart of an exemplary method **4000'**. The method **4000'** comprises the same steps of the method **4000** as explained in relation to the previous figure. However the method **4000'** is an example of a method comprising additional steps of reading **4016** a cartridge code feature; detecting **4018** a temperature; detecting **4024** needle cover removal; moving **4020** the plunger rod to a pre-mix plunger rod position; and detecting **4022** resistance against movement of the plunger rod.

[0221] The method **4000'** comprises reading **4016** a cartridge code feature. The cartridge code feature may be indicative of one or more cartridge specifications. The subsequent steps of the method **4000'** may comprise adaptations based on the cartridge specifications. For example, subsequent steps of the method **4000'** may be tailored to the specific cartridge received and identified.

[0222] Detecting **4018** a temperature may comprise detecting a temperature of the cartridge and/or a temperature indicative of the temperature of the cartridge. The subsequent steps of the method **4000'** may comprise adaptations based on the temperature.

[0223] Reading **4016** the cartridge code feature and detecting **4018** the temperature may be performed simultaneously, as illustrated. However, alternatively, it may be performed sequentially.

[0224] Detecting **4024** needle cover removal may be a prerequisite of initiating movement of the plunger rod. For example, needle cover removal may be indicative of intended use of the cartridge

received.

[0225] Moving **4020** the plunger rod to a pre-mix plunger rod position may comprise initial movement of a first stopper of the cartridge, e.g. movement of the first stopper without commencing mixing of a two-component medicament.

[0226] Detecting **4022** resistance against movement of the plunger rod may be performed simultaneously with moving **4020** the plunger rod to the pre-mix plunger rod position, as illustrated. Detecting **4022** resistance against movement of the plunger rod may be indicative of cartridge parameters of the cartridge received, such as whether the cartridge is new or used or flawed.

[0227] Moving **4006** the plunger rod to the mix plunger rod position may follow reading **4016** the cartridge code feature, detecting **4018** the temperature, detecting **4024** needle cover removal, moving **4020** the plunger rod to the pre-mix plunger rod position, and detecting **4022** resistance against movement of the plunger rod.

[0228] Moving **4006** the plunger rod to the mix plunger rod position may be based on one or more of the cartridge code feature, the temperature, needle cover removal and/or resistance against movement of the plunger rod.

[0229] Moving **4010** the plunger rod to the prime plunger rod position may be based on one or more of the cartridge code feature, the temperature, needle cover removal and/or resistance against movement of the plunger rod.

[0230] Moving **4014** the plunger rod to the injection plunger rod position may be based on one or more of the cartridge code feature, the temperature, needle cover removal and/or resistance against movement of the plunger rod.

[0231] The method **4000** and/or the method **4000'** may include a first step of receiving the cartridge.

[0232] FIG. **12** shows a flow chart of an exemplary implementation of the exemplary method **4000'**. The flow chart shown may be an exemplary implementation in a processing unit of an auto injector.

[0233] The procedure is initiated by receiving **5002** a first input signal. A user may initiate the procedure by turning on the device thereby providing, e.g. via the user interface, the first input signal.

[0234] Following receipt **5002** of the first input signal, it is considered **5004** whether a cartridge is detected to be received in the cartridge receiver of the auto injector. If not, an output may be provided **5040** through the user interface.

[0235] If a cartridge is detected **5004**, or when a cartridge is detected **5004**, after receiving **5002** the first input signal, a cartridge code feature is read **5006**.

[0236] Following reading **5006** of the cartridge code feature, temperature is detected **5008**, such as the temperature of the cartridge received.

[0237] Following detection **5008** of the temperature and reading **5006** of the cartridge code feature, it is detected **5010** whether a needle cover is removed, such as not present. If a needle cover is not removed, a user output may be provided, e.g. through the user interface, prompting **5042** the user to remove the needle cover. If the needle cover is removed **5010**, or when the needle cover is removed **5010**, the plunger rod is moved **5012** to a pre-mix plunger rod position. During this movement resistance against movement of the plunger rod is measured.

[0238] The resistance against movement is analysed **5014** to determine whether it is acceptable or not. This analysis may be based on the cartridge code feature read **5006** and/or the temperature detected **5008**.

[0239] If the resistance **5014** is not acceptable, a user output may be provided **5044**, e.g. via the user interface. The output may indicate that the cartridge is to be replaced. Subsequently, the plunger rod is moved **5038** to a retracted plunger rod position, such as the starting position of the plunger rod.

[0240] If the resistance **5014** is acceptable the plunger rod is moved **5016** to a mix plunger rod position, e.g. to combine a first medicament component and a second medicament component.
[0241] After the plunger rod is moved **5016** to the mix plunger rod position a delay **5018** is inserted to provide the combined medicament components to reconstitute to the medicament for injection. The delay **5018** may be between 1 and 12 min, such as between 3 and 10 min. During a delay a user output may be provided via the user interface, the user output may be indicative for the reconstitution.

[0242] After the medicament is reconstituted and/or the delay suitable for reconstitution of the medicament has lapsed **5018**, the orientation of the cartridge is assessed **5020**. The cartridge orientation may be assessed from measuring the orientation of the auto injector. The orientation should be acceptable for performing an air-shot, e.g. the cartridge outlet of the cartridge should be pointing upwards, such that air may be expelled and/or reduced. If the orientation **5020** is not acceptable, e.g. the cartridge outlet is not pointing upwards and/or the cartridge is not within **45** deg. of vertical, the user is prompted **5046**, e.g. via the user interface, to orientate the auto injector correctly, e.g. point the cartridge outlet upwards.

[0243] If the orientation is acceptable **5020**, or when the orientation is acceptable, the plunger rod is moved **5022** to a prime plunger rod position, e.g. to expel air from the cartridge compartment. The prime plunger rod position may be determined based on the cartridge code feature read **5006** and/or the temperature detected **5008**.

[0244] After moving **5022** the plunger rod to the prime plunger rod position, the user is prompted, e.g. via the user interface, to perform a visual check **5024** of the medicament. For example, the user may be provided the possibility to abort the procedure if sediments of medicament are visible. To accept the visual quality of the medicament, the user may provide a second input signal, e.g. by pressing a button of the user interface. The button used for providing the second input signal may be the same button as for providing the first input signal. The prompting of the user to perform the visual check **5024** may cease and/or the procedure may be aborted if a time out, e.g. 4-5 hours, after the medicament is reconstituted and/or after the delay suitable for reconstitution of the medicament has lapsed **5018**.

[0245] After receiving the second input signal **5026**, the user may be prompted **5028**, e.g. via the user interface, to initiate injection of the medicament. The user may inject the medicament by providing a trigger event, e.g. by pressing a contact member of the auto injector towards an intended injection site, e.g. thereby inserting the needle into the tissue of the intended injection site. While not receiving **5030** the trigger event, the user is continuously prompted to initiate injection **5028**.

[0246] After receiving **5030** the trigger event, the plunger rod is moved **5032** to the injection plunger rod position, e.g. to eject the medicament of the cartridge, such as to inject the medicament into the tissue of the intended injection site.

[0247] After the plunger rod is moved **5032** to the injection plunger rod position, it may be preferred to delay retraction of the needle to allow the medicament to be distributed into the tissue. Thus, the auto injector prompts **5034** the user, e.g. via the user interface, to wait for a set dwell time, e.g. between 1 and 15 sec.

[0248] Following reception **5030** of the trigger event and/or movement **5032** of the plunger rod to the injection plunger rod position and/or prompting **5034** the user to wait for the set dwell time, skin contact is assessed **5036**, e.g. whether the contact member is still pressed against the intended injection site. If, after the dwell time, the skin contact is still present, the user is prompted **5048** that injection is done and/or that the user may remove the auto injector from the injection site.

[0249] If and/or when the skin contact is lost **5036**, the plunger rod is moved **5038** to the retracted plunger rod position.

[0250] After movement **5038** of the plunger rod to the retracted plunger rod position, the cartridge may be removed and discarded.

[0251] FIGS. 13A, 13B, 13C and 13D schematically illustrates an exemplary user interface **1100** of an exemplary auto injector **4**, such as an auto injector **4** as illustrated in FIG. 1.

[0252] The user interface **1100** comprises a first output member **1110** as illustrated, e.g. a plurality of LEDs. The first output member **1110** may provide for a user output to a user. The first output member **1110** may be used to indicate a step in the procedure to the user and/or to indicate an error message. The first output member **1110** comprises a first LED **1116**, a second LED **1118**, and a third LED **1120**.

[0253] The user interface **1100** may comprise a second output member (not shown), e.g. a speaker.

[0254] The user interface **1100** comprises a contact member **1102**, e.g. at a forward end of the auto injector **4**. The contact member **1102** may be configured to be pressed against an injection site. The contact member **1102** may serve as a third output member of the user interface **1100**, e.g. the contact member **1102** may be configured to light up, such as flash.

[0255] The user interface **1100** comprises a first input member **1108**, e.g. a button. The first input member **1108** may provide for a user input from a user. For example, the first input member **1108** may be used for receiving a push from a user to proceed to a next step. The first input member **1108** may serve as a fourth output member of the user interface **1100**, e.g. the first input member **1108** may be configured to light up, such as flash.

[0256] FIG. 13A schematically illustrates a situation of the user interface **1100** wherein none of the output members are active, e.g. the auto injector **4** may be turned off.

[0257] FIG. 13B schematically illustrates a situation of the user interface **1100** wherein the first input member **1108** and the contact member **1102** light up, such as flashes. The first input member **1108** and the contact member **1102** may flash synchronously and/or asynchronously. The situation shown may be a situation indicating that the user should press the first input member **1108** and/or insert a cartridge through the contact member **1102**. The situation shown may be a situation following that the auto injector is turned on.

[0258] FIG. 13C schematically illustrates a situation of the user interface **1100** wherein the first input member **1108** and the second LED **1118** light up, such as flashes. The situation shown may be a situation indicating that the user should press the first input member **1108** to proceed to a next step. The situation shown may be a situation following mixing of medicament components and/or before performing an air-shot.

[0259] FIG. 13D schematically illustrates a situation of the user interface **1100** wherein the first input member **1108** and the contact member **1102** and the third LED **1120** light up, such as flashes. The first input member **1108** and the contact member **1102** and the third LED **1120** may flash synchronously and/or asynchronously. The situation shown may be a situation indicating that the user should press the contact member **1102** against an intended injection site to inject the medicament. The situation shown may be a situation before injecting the medicament.

[0260] FIG. 14 shows a flow chart of a variation of the exemplary implementation shown in FIG. 12. The flow chart shown may be an exemplary implementation in a processing unit of an auto injector.

[0261] The procedure is initiated by receiving **5002** a first input signal. A user may initiate the procedure by turning on the device thereby providing, e.g. via the user interface, the first input signal.

[0262] Following receipt **5002** of the first input signal, it is considered **5004** whether a cartridge is detected to be received in the cartridge receiver of the auto injector. If not, an output may be provided **5040** through the user interface.

[0263] If a cartridge is detected **5004**, or when a cartridge is detected **5004**, after receiving **5002** the first input signal, a cartridge code feature is read **5006**.

[0264] Following reading **5006** of the cartridge code feature, temperature is detected **5008**, such as the temperature of the cartridge received.

[0265] Following detection **5008** of the temperature and reading **5006** of the cartridge code feature,

it is detected **5010** whether a needle cover is removed, such as not present. If a needle cover is not removed, a user output may be provided, e.g. through the user interface, prompting **5042** the user to remove the needle cover. If the needle cover is removed **5010**, or when the needle cover is removed **5010**, the plunger rod is moved **5012** to a pre-mix plunger rod position. During this movement resistance against movement of the plunger rod is measured.

[0266] The resistance against movement is analysed **5014** to determine whether it is acceptable or not. This analysis may be based on the cartridge code feature read **5006** and/or the temperature detected **5008**.

[0267] If the resistance **5014** is not acceptable, a user output may be provided **5044**, e.g. via the user interface. The output may indicate that the cartridge is to be replaced. Subsequently, the plunger rod is moved **5038** to a retracted plunger rod position, such as the starting position of the plunger rod.

[0268] If the resistance **5014** is acceptable the orientation of the cartridge is assessed **5020**. The cartridge orientation may be assessed from measuring the orientation of the auto injector. The orientation should be acceptable for combining a first medicament component and a second medicament component, e.g. to avoid excessive foaming during the process. For example, an acceptable orientation may be that the cartridge outlet of the cartridge is pointing upwards. If the orientation **5020** is not acceptable, e.g. the cartridge outlet is not pointing upwards and/or the cartridge is not within 45 deg. of vertical, the user is prompted **5046**, e.g. via the user interface, to orientate the auto injector correctly, e.g. point the cartridge outlet upwards.

[0269] If the orientation is acceptable **5020**, or when the orientation is acceptable, the plunger rod is moved **5016** to a mix plunger rod position, e.g. to combine the first medicament component and the second medicament component.

[0270] After the plunger rod is moved **5016** to the mix plunger rod position a delay **5018** is inserted to provide the combined medicament components to reconstitute to the medicament for injection. The delay **5018** may be between 1 and 12 min, such as between 3 and 10 min. During the delay a user output may be provided via the user interface, the user output may be indicative for the reconstitution progression. The delay may be dependent on the cartridge specification, e.g. from reading **5006** of the cartridge code feature.

[0271] After the medicament is reconstituted and/or the delay suitable for reconstitution of the medicament has lapsed **5018** the plunger rod is moved **5022** to a prime plunger rod position, e.g. to expel air from the cartridge compartment. The prime plunger rod position may be determined based on the cartridge code feature read **5006** and/or the temperature detected **5008**.

[0272] Determining orientation prior to moving the plunger rod to the prime plunger rod position may be omitted, e.g. by assuming the orientation of the auto injector is maintained from when the orientation was determined prior to moving the plunger rod to the mix plunger rod position. In an alternative implementation (not shown), orientation may be determined both prior to moving the plunger rod to the mix plunger rod position and prior to moving the plunger rod to the prime plunger rod position.

[0273] After moving **5022** the plunger rod to the prime plunger rod position, the user is prompted, e.g. via the user interface, to perform a visual check **5024** of the medicament. For example, the user may be provided the possibility to abort the procedure if sediments of medicament are visible. To accept the visual quality of the medicament, the user may provide a second input signal, e.g. by pressing a button of the user interface. The button used for providing the second input signal may be the same button as for providing the first input signal. The prompting of the user to perform the visual check **5024** may cease and/or the procedure may be aborted if a time out, e.g. 4-5 hours, after the medicament is reconstituted and/or after the delay suitable for reconstitution of the medicament has lapsed **5018**.

[0274] After receiving the second input signal **5026**, the user may be prompted **5028**, e.g. via the user interface, to initiate injection of the medicament. The user may inject the medicament by

providing a trigger event, e.g. by pressing a contact member of the auto injector towards an intended injection site, e.g. thereby inserting the needle into the tissue of the intended injection site. While not receiving **5030** the trigger event, the user is continuously and/or repeatedly prompted to initiate injection **5028**.

[0275] After receiving **5030** the trigger event, the plunger rod is moved **5032** to the injection plunger rod position, e.g. to eject the medicament of the cartridge, such as to inject the medicament into the tissue of the intended injection site.

[0276] After the plunger rod is moved **5032** to the injection plunger rod position, it may be preferred to delay retraction and/or removal of the needle to allow the medicament to be distributed into the tissue. Thus, the auto injector prompts **5034** the user, e.g. via the user interface, to wait for a set dwell time, e.g. between 1 and 15 sec, before he/she retracts the needle.

[0277] Following reception **5030** of the trigger event and/or movement **5032** of the plunger rod to the injection plunger rod position and/or prompting **5034** the user to wait for the set dwell time, skin contact is assessed **5036**, e.g. whether the contact member is still pressed against the intended injection site. If, after the dwell time, the skin contact is still present, the user is prompted **5048** that injection is done and/or that the user may remove the auto injector from the injection site.

[0278] If and/or when the skin contact is lost **5036**, the plunger rod is moved **5038** to the retracted plunger rod position.

[0279] After movement **5038** of the plunger rod to the retracted plunger rod position, the cartridge may be removed and discarded.

[0280] Exemplary auto injectors, cartridges, systems and methods are set out in the following items:

[0281] 1. An auto injector for preparing and/or administering a medicament from a cartridge having a first cartridge end and a second cartridge end and having a cartridge outlet at the first cartridge end, the cartridge comprising a cartridge compartment with a first cartridge subcompartment containing a first medicament component of the medicament and a second cartridge subcompartment containing a second medicament component of the medicament, the auto injector comprising: [0282] a housing; [0283] a cartridge receiver with a cartridge receiver opening, the cartridge receiver being configured to receive the cartridge by insertion of the second end of the cartridge through the cartridge receiver opening; [0284] a cartridge sensor configured to detect reception of the cartridge in the cartridge receiver and provide a cartridge detection signal indicative of the cartridge being received in the cartridge receiver; [0285] a drive module coupled to move a plunger rod between a retracted plunger rod position and an extended plunger rod position, the plunger rod being configured to move the first stopper; [0286] an orientation sensor configured to provide an orientation signal indicative of the orientation of the cartridge when received in the cartridge receiver; [0287] a processing unit coupled to the orientation sensor, the cartridge sensor, and to the drive module; [0288] the processing unit being configured to: [0289] receive a first input signal; [0290] receive the cartridge detection signal; [0291] control the drive module to move the plunger rod to a mix plunger rod position following reception of the cartridge detection signal and the first input signal; [0292] receive the orientation signal; and [0293] control the drive module to move the plunger rod to a prime plunger rod position based on the orientation signal and following completion of movement of the plunger rod to the mix plunger rod position.

[0294] 2. Auto injector according to item 1, wherein the processing unit is further configured to:

[0295] receive a trigger event; and

[0296] control the drive module to move the plunger rod to an injection plunger rod position following reception of the trigger event after completion of movement of the plunger rod to the prime plunger rod position.

[0297] 3. Auto injector according to any of items 1 or 2, wherein the orientation sensor comprises an accelerometer.

[0298] 4. Auto injector according to any of the preceding items comprising a code sensor

configured to read a cartridge code feature and provide a code signal indicative of the cartridge code feature, the processing unit being coupled to the code sensor and being configured to receive the code signal.

[0299] 5. Auto injector according to item 4, wherein the processing unit is configured to determine an unauthorized cartridge based on the code signal.

[0300] 6. Auto injector according to any of items 4 or 5, wherein control of the drive module to move the plunger rod to the prime plunger rod position is based on the code signal.

[0301] 7. Auto injector according to any of items 4-6, wherein movement of the plunger rod to the prime plunger rod position has a prime plunger rod speed, and wherein the prime plunger rod speed is based on the code signal.

[0302] 8. Auto injector according to any of items 4-7, wherein movement of the plunger rod to the mix plunger rod position has a mix plunger rod speed, and wherein the mix plunger rod speed is based on the code signal.

[0303] 9. Auto injector according to any of items 4-8, wherein movement of the plunger rod to the injection plunger rod position has an injection plunger rod speed, and wherein the injection plunger rod speed is based on the code signal.

[0304] 10. Auto injector according to any of the preceding items comprising a resistance sensor configured to provide a resistance signal indicative of resistance against movement of the plunger rod, the processing unit being coupled to the resistance sensor and being configured to receive the resistance signal.

[0305] 11. Auto injector according to item 10, wherein the processing unit is configured to determine an unauthorized cartridge based on the resistance signal.

[0306] 12. Auto injector according to any of items 10 or 11, wherein the processing unit is configured to determine a cartridge parameter based on the resistance signal.

[0307] 13. Auto injector according to any of items 10-12, wherein control of the drive module to move the plunger rod to the mix plunger rod position is based on the resistance signal.

[0308] 14. Auto injector according to any of items 10-13, wherein the processing unit is configured to control the drive module to move the plunger rod to the mix plunger rod position only if the resistance signal indicates resistance against movement of the plunger rod above a low resistance threshold.

[0309] 15. Auto injector according to any of the preceding items comprising a first input device configured to provide the first input signal, the first input signal being indicative of a first user interaction with the first input device, the processing unit being coupled to the first input device.

[0310] 16. Auto injector according to any of the preceding items comprising a contact member movable between an extended contact member position and a retracted contact member position, the contact member being biased towards the extended contact member position, and the contact member being configured to be moved towards the retracted contact member position when pressed against the injection site, the contact member is configured to provide a contact member signal indicative of position of the contact member, the processing unit is coupled to the contact member and configured to receive the contact member signal.

[0311] 17. Auto injector according to item 16 as dependent on item 2, the trigger event comprising the contact member signal being indicative of the contact member being in a first contact member position.

[0312] 18. Auto injector according to any of items 16 or 17, wherein the contact member is configured to be in a second contact member position if a needle cover is present on the cartridge, the processing unit is configured to control the drive module to move the plunger rod to the mix plunger rod position based on the contact member signal.

[0313] 19. Auto injector according to any of the preceding items, wherein the processing unit is configured to control the drive module to move the plunger rod to the prime plunger rod position only if the orientation signal indicates that a tilt angle between vertical and a longitudinal axis

extending along the cartridge is within 45 degrees of vertical and the cartridge outlet is in a vertical position above the cartridge compartment.

[0314] 20. Auto injector according to any of the preceding items, wherein the processing unit is configured to control the drive module to move the plunger rod to a pre-mix plunger rod position following reception of the cartridge detection signal and the first input signal, wherein movement of the plunger rod to the pre-mix plunger rod position has a pre-mix plunger rod speed, and movement of the plunger rod to the mix plunger rod position has a mix plunger rod speed, wherein the pre-mix plunger rod speed is faster than the mix plunger rod speed.

[0315] 21. Auto injector according to any of the preceding items, wherein the processing unit is configured to control the drive module to move the plunger rod to the prime plunger rod position and/or to the injection plunger rod position only after a reconstitution time has elapsed since completion of the movement of the plunger rod to the mix plunger rod position.

[0316] 22. Auto injector according to item 21 as dependent on any of items 4-9, wherein the reconstitution time is based on the code signal.

[0317] 23. Auto injector according to any of the preceding items, wherein the processing unit is configured to control the drive module to move the plunger rod towards the retracted plunger rod position following completion of the movement of the plunger rod to the injection plunger rod position.

[0318] 24. Auto injector according to any of the preceding items, wherein the processing unit is configured to control the drive module to move the plunger rod towards the retracted position only after a dwell time has elapsed since completion of the movement of the plunger rod to the injection plunger rod position.

[0319] 25. Auto injector according to any of the preceding items, wherein the processing unit is configured to provide a user output via a user interface after a dwell time has elapsed since completion of the movement of the plunger rod to the injection plunger rod position.

[0320] 26. Auto injector according to any of the preceding items, wherein control of the drive module to move the plunger rod to the mix plunger rod position is based on the orientation signal.

[0321] 27. Auto injector according to item 26, wherein the processing unit is configured to control the drive module to move the plunger rod to the mix plunger rod position only if the orientation signal indicates that a tilt angle between vertical and a longitudinal axis extending along the cartridge is within 45 degrees of vertical and the cartridge outlet is in a vertical position above the cartridge compartment.

[0322] 28. Auto injector according to any of the preceding items, wherein movement of the plunger rod to the mix plunger rod position locks the cartridge in the cartridge receiver.

[0323] 29. Auto injector according to any of the preceding items, wherein movement of the plunger rod to the retracted plunger rod position unlocks the cartridge in the cartridge receiver.

[0324] 30. Auto injector according to any of the preceding items, wherein the medicament is human growth hormone, such as a medicament with the formulation code ACP-011.

[0325] 31. A cartridge for an auto injector comprising a first cartridge end and a second cartridge end and having a cartridge outlet at the first cartridge end, the cartridge comprising a cartridge compartment with a first cartridge subcompartment containing a first medicament component of the medicament and a second cartridge subcompartment containing a second medicament component of the medicament, the cartridge being configured to be received by a cartridge receiver of an auto injector according to any of the preceding items by insertion of the second cartridge end of the cartridge through the cartridge receiver opening of the auto injector.

[0326] 32. A system comprising an auto injector according to any of items 1-30, and a cartridge according to item 31.

[0327] 33. A method for operating an auto injector comprising a plunger rod and a cartridge receiver configured to receive a cartridge, the cartridge having a first cartridge end and a second cartridge end and having a cartridge outlet at the first cartridge end, the cartridge comprising a

cartridge compartment with a first cartridge subcompartment containing a first medicament component of the medicament and a second cartridge subcompartment containing a second medicament component of the medicament, the method comprising: [0328] receiving a first input signal; [0329] detecting reception of the cartridge in the cartridge receiver; [0330] moving the plunger rod to a mix plunger rod position following detection of the cartridge being received in the cartridge receiver and reception of the first input signal; [0331] determining orientation of the cartridge; and [0332] moving the plunger rod to a prime plunger rod position based on the orientation of the cartridge and following completion of movement of the plunger rod to the mix plunger rod position.

[0333] 34. Method according to item 33 further comprising: [0334] receiving a trigger event; and [0335] moving the plunger rod to an injection plunger rod position following reception of the trigger event after completion of movement of the plunger rod to the prime plunger rod position.

Claims

1. (canceled)

2. An auto injector for preparing and/or administering a medicament from a cartridge having a first cartridge end and a second cartridge end and having a cartridge outlet at the first cartridge end, the cartridge comprising a cartridge compartment with a first cartridge subcompartment containing a first medicament component of the medicament and a second cartridge subcompartment containing a second medicament component of the medicament, the auto injector comprising: a housing; a cartridge receiver with a cartridge receiver opening, the cartridge receiver being configured to receive the cartridge by insertion of the second end of the cartridge through the cartridge receiver opening; a cartridge sensor configured to detect reception of the cartridge in the cartridge receiver and provide a cartridge detection signal indicative of the cartridge being received in the cartridge receiver; a drive module coupled to move a plunger rod between a retracted plunger rod position and an extended plunger rod position, the plunger rod being configured to move the first stopper; an orientation sensor configured to provide an orientation signal indicative of the orientation of the cartridge when received in the cartridge receiver; a processing unit coupled to the orientation sensor, the cartridge sensor, and to the drive module; the processing unit being configured to: receive a first input signal; receive the cartridge detection signal; receive the orientation signal control the drive module to move the plunger rod to a mix plunger rod position following reception of the cartridge detection signal and the first input signal; control the drive module to move the plunger rod to a prime plunger rod position following completion of movement of the plunger rod to the mix plunger rod position, wherein control of the drive module to move the plunger rod to the prime plunger rod position is based on the orientation signal; and wherein the processing unit is configured to control the drive module to move the plunger rod to the prime plunger rod position only after a reconstitution time has elapsed since completion of the movement of the plunger rod to the mix plunger rod position.

3. The auto injector according to claim 2, wherein the processing unit is further configured to: receive a trigger event; and control the drive module to move the plunger rod to the injection plunger rod position following reception of the trigger event after completion of movement of the plunger rod to the prime plunger rod position.

4. The auto injector according to claim 2, wherein the orientation sensor comprises an accelerometer.

5. The auto injector according to claim 2 comprising a code sensor configured to read a cartridge code feature and provide a code signal indicative of the cartridge code feature, the processing unit being coupled to the code sensor and being configured to receive the code signal.

6. The auto injector according to claim 2, wherein the processing unit is configured to determine an unauthorized cartridge based on the code signal.

7. The auto injector according to claim 2 comprising a first input device configured to provide the first input signal, the first input signal being indicative of a first user interaction with the first input device, the processing unit being coupled to the first input device.
8. The auto injector according to claim 2 comprising a contact member movable between an extended contact member position and a retracted contact member position, the contact member being biased towards the extended contact member position, and the contact member being configured to be moved towards the retracted contact member position when pressed against the injection site, the contact member is configured to provide a contact member signal indicative of position of the contact member, the processing unit is coupled to the contact member and configured to receive the contact member signal.
9. The auto injector according to claim 8, wherein a trigger event comprises the contact member signal being indicative of the contact member being in a first contact member position and, wherein the processing unit is further configured to: receive the trigger event; and control the drive module to move the plunger rod to the injection plunger rod position following reception of the trigger event after completion of movement of the plunger rod to the prime plunger rod position.
10. The auto injector according to claim 2, wherein the processing unit is configured to control the drive module to move the plunger rod to the prime plunger rod position only if the orientation signal indicates that a tilt angle between vertical and a longitudinal axis extending along the cartridge is within 45 degrees of vertical and the cartridge outlet is in a vertical position above the cartridge compartment.
11. The auto injector according to claim 2, wherein the reconstitution time is based on the code signal.
12. The auto injector according to claim 2, wherein the processing unit is configured to control the drive module to move the plunger rod towards the retracted plunger rod position following completion of the movement of the plunger rod to an injection plunger rod position.
13. The auto injector according to claim 2, wherein the processing unit is configured to control the drive module to move the plunger rod towards the retracted position only after a dwell time has elapsed since completion of the movement of the plunger rod to the injection plunger rod position.
14. The auto injector according to claim 2, wherein the processing unit is configured to provide a user output via a user interface after a dwell time has elapsed since completion of the movement of the plunger rod to the injection plunger rod position.
15. The auto injector according to claim 2, wherein the medicament is human growth hormone, such as a medicament with the formulation code ACP-011.
16. A cartridge for an auto injector comprising a first cartridge end and a second cartridge end and having a cartridge outlet at the first cartridge end, the cartridge comprising a cartridge compartment with a first cartridge subcompartment containing a first medicament component of the medicament and a second cartridge subcompartment containing a second medicament component of the medicament, the cartridge being configured to be received by a cartridge receiver of an auto injector according to claim 2 by insertion of the second cartridge end of the cartridge through the cartridge receiver opening of the auto injector.
17. A system comprising the auto injector according to claim 2, and a cartridge for an auto injector comprising a first cartridge end and a second cartridge end and having a cartridge outlet at the first cartridge end, the cartridge comprising a cartridge compartment with a first cartridge subcompartment containing a first medicament component of the medicament and a second cartridge subcompartment containing a second medicament component of the medicament, the cartridge being configured to be received by a cartridge receiver of the auto injector by insertion of the second cartridge end of the cartridge through the cartridge receiver opening of the auto injector.
18. A method for operating an auto injector according to claim 2, the method comprising: receiving a first input signal; detecting reception of the cartridge in the cartridge receiver; determining orientation of the cartridge; moving the plunger rod to a mix plunger rod position following

detection of the cartridge being received in the cartridge receiver and reception of the first input signal; and moving the plunger rod to a prime plunger rod position based on an orientation signal following completion of movement of the plunger rod to the mix plunger rod position, wherein the plunger rod is moved to the prime plunger rod position only after a reconstitution time has elapsed since completion of the movement of the plunger rod to the mix plunger rod position.

19. The method according to claim 18 further comprising: receiving a trigger event; and moving the plunger rod to an injection plunger rod position following reception of the trigger event after completion of movement of the plunger rod to the prime plunger rod position.
