

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250249134

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

STARKWEATHER; Jeremy et al.

MODULAR COMPONENTS, SYSTEMS, AND METHODS FOR DISINFECTING OBJECTS

Abstract

Systems, apparatus, and methods are described for a disinfecting system formed of a plurality of modular units, wherein each modular unit is (1) coupleable to at least one other modular unit from the plurality of modular units and (2) includes an energy source from a plurality of energy sources. The plurality of energy sources can be configured to provide energy having an intensity capable of disinfecting a surface of the object located in a disinfecting area.

Inventors: STARKWEATHER; Jeremy (Castle Rock, CO), YLIZARDE; Jason (Conroe, TX), WYNNE; John (Cincinnati, OH), EDMUNDOWICZ; Brent (Centennial, CO), STARKWEATHER; Austin (Denver, CO), WENGER; Stefan L. (Columbine Valley, CO)

Applicant: UV-Concepts Inc. (Englewood, CO)

Family ID: 67254003

Assignee: UV-Concepts Inc. (Englewood, CO)

Appl. No.: 19/029849

Filed: January 17, 2025

Related U.S. Application Data

parent US continuation 17401978 20210813 parent-grant-document US 12233175 child US 19029849

parent US continuation 16860141 20200428 parent-grant-document US 11090399 child US 17401978

parent US continuation PCT/US2019/038231 20190620 PENDING child US 16860141
us-provisional-application US 62687477 20180620

Publication Classification

Int. Cl.: **A61L2/10** (20060101); **A61L2/14** (20060101); **A61L2/20** (20060101); **A61L2/28** (20060101)

U.S. Cl.:

CPC **A61L2/10** (20130101); **A61L2/14** (20130101); **A61L2/202** (20130101); **A61L2/208** (20130101); **A61L2/28** (20130101); A61L2202/122 (20130101); A61L2202/15 (20130101); A61L2202/24 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 17/401,978, filed Aug. 13, 2021, titled “MODULAR COMPONENTS, SYSTEMS, AND METHODS FOR DISINFECTING OBJECTS,” which is a continuation of U.S. patent application Ser. No. 16/860,141, filed Apr. 28, 2020, titled “MODULAR COMPONENTS, SYSTEMS, AND METHODS FOR DISINFECTING OBJECTS,” now U.S. Pat. No. 11,090,399, which is a continuation of International Patent Application No. PCT/US2019/038231, filed Jun. 20, 2019, titled “MODULAR COMPONENTS, SYSTEMS, AND METHODS FOR DISINFECTING OBJECTS,” which claims priority to U.S. Provisional Patent Application No. 62/687,477, filed Jun. 20, 2018, titled “MODULAR COMPONENTS, SYSTEMS, AND METHODS FOR DISINFECTING OBJECTS,” the disclosure of each of which is incorporated by reference herein.

TECHNICAL FIELD

[0002] The present disclosure relates generally to modular components, systems, and methods for disinfecting objects. More specifically, the present disclosure relates to disinfecting structures formed of modular units that include energy sources, such as light sources capable of emitting ultraviolet (UV) light, which can be used to disinfect objects, including equipment within a medical facility.

BACKGROUND

[0003] Disinfection of objects and spaces can reduce the transmission of pathogens. In medical facilities, disinfection of equipment, instruments, and other objects is important to prevent the spread of illnesses between individuals. Disinfection can be accomplished using, for example, UV light or other energy sources and/or disinfecting agents.

[0004] The effectiveness of a disinfection system can depend on the physical setting and/or method of disinfection. For example, with UV disinfection, it has been shown that intensity, proximity, and line of sight affect the ability of UV light emitted from a disinfection system to effectively eliminate pathogens on equipment and/or within spaces. But many existing UV disinfection systems, once installed within a medical setting, are stationary. For example, UV disinfection stations for disinfecting publicly-used equipment are described by Taylor et al. in U.S. Pat. Nos. 7,791,044 and 8,536,541, the disclosures of which are hereby incorporated by reference in their entirety. The stationary units described in these patents are particularly useful for disinfecting mobile equipment, such as shopping carts, wheelchairs, gurneys, etc. Because the units are stationary, however, the units may have limited applications, e.g., be designed for a specific space and/or type of equipment. When changes occur with the space and/or equipment, the disinfection units may need to be manually moved, adapted, or replaced.

[0005] In addition, existing systems capable of disinfecting larger scale objects and/or spaces may

have dimensions that make them difficult to transport and deploy onsite. For example, such systems may have dimensions larger than standard size doorways and/or openings within a medical facility, and therefore require onsite construction and/or disassembly and reassembly to get through doorways and/or openings. Once the disinfection systems are assembled within a room or area, the systems may have limited mobility and/or adaptability. For example, such systems may be formed of a single, unitary structure that requires the entire system to be replaced (or a large portion of the system to be replaced) when individual, smaller components fail or require replacement over time. Such systems may also be difficult to move due to their large size and/or weight, be difficult to modify based on changes to equipment being disinfected and/or changes to the onsite location of the system, etc. These limitations and others can lead to significant costs, including downtime costs when a system is being installed, repaired, modified, and/or moved, and associated labor costs.

SUMMARY

[0006] Systems, apparatus, and methods described herein can overcome some of the disadvantages associated with existing disinfection systems. In particular, systems, apparatus, and methods described herein relate to disinfection systems having modular components.

[0007] In some embodiments, an apparatus includes a plurality of walls collectively defining a chamber sized to receive an object, where each wall from a set of walls from the plurality of walls is formed of a plurality of modular units, and each modular unit from the plurality of modular units is (1) coupleable to at least one other modular unit from the plurality of modular units and (2) includes an energy source from a plurality of energy sources. The at least one energy source from the plurality of energy sources can be configured to provide energy having an intensity capable of disinfecting a surface of the object when the object is received within the chamber.

[0008] In some embodiments, a kit includes components that can be assembled into a disinfection device. The kit can include a plurality of walls that can be assembled to collectively define a chamber sized to receive an object, where each wall from a set of walls from the plurality of walls is formed of a plurality of modular units, and each modular unit from the plurality of modular units is (1) coupleable to at least one other modular unit from the plurality of modular units and (2) includes an energy source from a plurality of energy sources. The at least one energy source from the plurality of energy sources can be configured to provide energy having an intensity capable of disinfecting a surface of the object when the object is received within the chamber.

[0009] In some embodiments, a method includes moving a plurality of modular units from a first location outside of an enclosed space to a second location inside the enclosed space through an opening, in which each modular unit from the plurality of modular units is sized to fit through the opening and includes an energy source; and assembling the plurality of modular units to form a structure that defines a chamber sized to receive an object, with each modular unit from the plurality of modular units arranged such that the energy source of that modular unit is disposed within the chamber and is configured to emit energy into the chamber to disinfect a surface of the object when the object is received within the chamber.

[0010] In some embodiments, a method includes positioning an object in a chamber of a disinfecting device including a portion formed from a plurality of modular units, the plurality of modular units including a plurality of energy sources and a plurality of fluid dispensers; energizing a set of energy sources from the plurality of energy sources to deliver energy at an intensity capable of disinfecting a surface of the object; and delivering, via a set of fluid dispensers from the plurality of fluid dispensers, a disinfecting agent into the chamber.

[0011] In some embodiments, an apparatus includes a plurality of modular units, in which each modular unit is (1) coupleable to at least one other modular unit from the plurality of modular units and (2) includes an energy source from a plurality of energy sources. A first set of energy sources from the plurality of energy sources can be configured to provide energy having an intensity capable of disinfecting a surface of the object when the surface of the object is disposed within a predefined distance from at least one of the plurality of modular units.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] The skilled artisan will understand that the drawings primarily are for illustrative purposes and are not intended to limit the scope of the inventive subject matter described herein. The drawings are not necessarily to scale; in some instances, various aspects of the inventive subject matter disclosed herein may be shown exaggerated or enlarged in the drawings to facilitate an understanding of different features. In the drawings, like reference characters generally refer to like features (e.g., functionally similar and/or structurally similar elements).

[0013] FIG. 1 schematically illustrates an example of a disinfection system, according to embodiments disclosed herein.

[0014] FIG. 2A schematically illustrates an example of a disinfection system including modular units, according to embodiments disclosed herein.

[0015] FIG. 2B schematically illustrates an example of a modular unit of a disinfection system, according to embodiments disclosed herein.

[0016] FIGS. 3A-3C schematically illustrate different configurations of modular units of disinfection systems, according to embodiments disclosed herein.

[0017] FIG. 4 schematically illustrates an example of a side panel of a disinfection system formed of modular units, according to embodiments disclosed herein.

[0018] FIGS. 5A, 5B, 5C, and 5D schematically illustrate different views of an example disinfection system including modular units, according to embodiments disclosed herein.

[0019] FIGS. 5A and 5B depict a top view of the disinfection system, with a movable panel of the disinfection system shown in two different configurations. FIG. 5C depicts a front view of the disinfection system. And FIG. 5D depicts a side view of the disinfection system.

[0020] FIG. 6 schematically illustrates an example disinfection system including modular units, according to embodiments disclosed herein.

[0021] FIG. 7 schematically illustrates an example disinfection system including modular units and capable of forming a sealed chamber, according to embodiments disclosed herein.

[0022] FIGS. 8A and 8B illustrate two different configurations of energy sources disposed on modular units of a disinfection system, according to embodiments disclosed herein.

[0023] FIGS. 9A and 9B illustrate two different views of an example energy source of a disinfection system, according to embodiments disclosed herein. FIG. 9A depicts a view of the energy source covering a surface of a modular unit of the disinfection system, and FIG. 9B depicts a cross-sectional view of a portion of the modular unit, showing the energy source and other layers of the modular unit.

[0024] FIG. 10 schematically illustrates an example of a disinfection system, according to embodiments disclosed herein.

[0025] FIG. 11 schematically illustrates an example of a disinfection system, according to embodiments disclosed herein.

[0026] FIG. 12 is a perspective view of an example of a disinfection system including modular units, according to embodiments disclosed herein.

[0027] FIGS. 13A and 13B depict different views of a modular unit of the disinfection system shown in FIG. 11.

[0028] FIG. 14A depicts an enlarged view of a portion of a modular unit of the disinfection system shown in FIG. 11.

[0029] FIG. 14B depicts an enlarged view of a portion of a modular unit of the disinfection system shown in FIG. 11, with a portion of an outer housing of the modular unit removed to shown an interior support structure of the modular unit.

[0030] FIGS. 15A and 15B depict different views of the disinfection system shown in FIG. 11. FIG.

14A depicts a side view of the disinfection system, and **FIG. 14B** depicts a top view of the disinfection system.

[0031] **FIG. 16** depicts a front view of the disinfection system shown in **FIG. 11**, including an example of medical equipment disposed within the disinfection system.

[0032] **FIG. 17** depicts a perspective view of an example of a disinfection system including modular units, according to embodiments disclosed herein.

[0033] **FIG. 18** is a perspective view of an example of a disinfection system including modular units, according to embodiments disclosed herein.

[0034] **FIG. 19** is a front view of the disinfection system shown in **FIG. 18**.

[0035] **FIG. 20** is a back view of the disinfection system shown in **FIG. 18**.

[0036] **FIGS. 21A-21D** depict different modular units of the disinfection system shown in **FIG. 18**.

[0037] **FIG. 22** is a flow chart of a method of disinfecting using a disinfection system, according to embodiments disclosed herein.

[0038] **FIG. 23** is a flow chart of a method of assembly a disinfection system, according to embodiments disclosed herein.

[0039] **FIG. 24** schematically illustrates a kit including modular units and other components of a disinfection system, according to embodiments disclosed herein.

DETAILED DESCRIPTION

[0040] Systems, apparatus, and methods described herein relate to disinfecting structures formed at least in part of modular units and/or components. Systems, apparatus, and methods disclosed herein can be designed to disinfect objects or areas using energy sources that emit light (e.g., UV light) at distances and intensities capable of disinfecting various surfaces and materials and/or disinfecting agents (e.g., hydrogen peroxide, peracetic acid, electrolyzed water, atmospheric pressure plasma, polymeric guanidine, ozone, or combinations thereof) in amounts capable of disinfecting various surfaces and materials. Systems, apparatus, and methods disclosed herein can be designed to disinfect, e.g., reduce the count of microorganisms (e.g., bacteria, viruses, etc.) from surfaces of objects, to various degrees, depending on requirements (e.g., set by a hospital or organization) and/or the nature or means of disinfection (e.g., the type of disinfection used, an amount of time for the disinfection, the object being disinfected, the distance of the object from the disinfecting source, etc.). For example, disinfection systems disclosed herein can be capable of disinfecting an object to a particular level (e.g., cleaning, sanitizing, low-level disinfecting, high-level disinfecting, sterilizing), depending on the classification of that object based on its risk of infection.

Embodiments of disinfection systems can be designed to select a level of disinfection based on a type of object and/or area being disinfected and operate to disinfect accordingly.

[0041] Although embodiments of the present disclosure are described with specific reference to systems and methods for disinfecting medical equipment (e.g., gurneys, wheelchairs, intravenous (IV) poles, dialysis machines, etc.) or medical enclosures (e.g., hospital rooms, surgery suites, diagnostic laboratories, etc.), it should be appreciated that such systems and methods may be used to disinfect a variety of items used or contacted by the public (e.g., shopping carts, shopping baskets, strollers, railings, door knobs, etc.) and a variety of enclosures (e.g., kitchens, public or private bathrooms, cafeterias, airplanes, buses, etc.).

[0042] **FIG. 1** is a high-level block diagram that schematically illustrates an example disinfection system **100**, according some embodiments. Disinfection system **100** includes a body **110** and one or more energy source(s) **122**. Disinfection system **100** can optionally include one or more reflective unit(s) **120**, spray unit(s) **160**, exhaust unit(s) **162**, and/or sensor(s) **164**.

[0043] Each energy source **122** is configured to emit energy that can be directed at objects disposed within a disinfecting area **125**. Each energy source **122** can be configured to emit light, such as, for example, UV light at a wavelength of approximately 320-400 nanometers (nm) (i.e., UV-A light), UV light at a wavelength of approximately 290-320 nm (i.e., UV-B light), UV light at a wavelength of approximately 200-280 nm (i.e., UV-C light), and/or high-intensity narrow-spectrum (HINS)

light (e.g., light at a wavelength of 405 nm). In some embodiments, a first set of energy source(s) **122** can be configured to emit a first type of energy (e.g., UV-B light) and a second set of energy source(s) **122** can be configured to emit a second type of energy (e.g., UV-C light). Each energy source **122** can include one or more mercury vapor bulbs or tubes, xenon gas bulbs or tubes, excimer bulbs or tubes, light emitting diodes (LED), light emitting nanoparticles, lasers, or other energy sources configured to emit light. For example, energy source(s) **122** may include light bulbs that are configured to emit at least 30 watts of UV energy (e.g., 36 watts of UV energy). As another example, energy source(s) **122** may include light emitting nanoparticles deposited or grown on a flexible conductive layer, as further described below in reference to FIGS. **9A** and **9B**. As another example, energy source(s) **122** can be configured to emit HINS light.

[0044] One or more energy source(s) **122** can be disposed within (e.g., removably or permanently) or near a reflective unit **120**, such that energy emitted from the energy source(s) **122** can be directed into a disinfecting area **125** and/or an object disposed within the disinfecting area **125**. Each reflective unit **120** can be formed of one or more reflective surface(s) capable of reflecting energy emitted from the energy source(s) **122**. For example, reflective unit(s) **120** can have a curved reflective surface (e.g., a hyperbolic reflective surface) that directs energy emitted from the energy source(s) **122** in multiple directions into the disinfecting area **125**. Alternatively, reflective unit(s) **120** can have a back surface and a plurality of reflective surfaces disposed off normal with respect to the back surface that direct energy emitted from energy source(s) in multiple directions into disinfecting area **125**. Reflective unit(s) **120** can include reflective materials, such as, for example, mirrors, powder-coated materials or metal sheets, or Pebbletone™ and Hammertone™ finishes.

[0045] Energy source(s) **122** can be configured to emit energy having an intensity at a predefined distance (e.g., 100 $\mu\text{W}/\text{cm}^2$ at 1 meter) that is capable of disinfecting the surfaces of an object disposed within that predefined distance. In embodiments including reflective unit(s) **120**, reflective unit(s) **120** can work in cooperation with energy source(s) **122** to ensure that a sufficient amount of energy for disinfecting an object is deposited on each surface of the object. Each surface of an object disposed within disinfecting area **125** can receive a collective amount of energy from various beams of energy (e.g., directly emitted by energy source(s) **122** and/or reflected via reflective unit(s) **120**) that is sufficient to disinfect the surface, i.e., sufficiently reduce or eliminate pathogens disposed on the surface.

[0046] Disinfecting area **125** can be disposed adjacent to and/or within body **110** of disinfection system **100**. For example, disinfecting area **125** can be located within a chamber **124** defined by body **110**, or disinfecting area **125** can be an area that is adjacent to body **110**. Body **110** can optionally define a chamber **124** for receiving an object requiring disinfecting. Chamber **124** can be sized to receive the object, and can include an opening **130** through which the object can be placed within chamber **124**. The object can be, for example, medical equipment such as a gurney, a wheelchair, a pole to support bags of fluid for intravenous delivery (an IV pole), a medical cart, a mobile or portable computer station, a dialysis machine, an anesthesia machine, an electrocardiogram (ECG) machine, and/or other types of mobile medical items. Body **110** can include a wall, panel, and/or other structure capable of moving between an open configuration and a closed configuration to open and close the opening **130** of chamber **124**. In some embodiments, chamber **124** can be designed to seal in energy and/or fluid, such that energy and/or fluid deposited within chamber **124** cannot exit chamber **124**. Such sealing can prevent energy and/or fluid within the chamber **124** from affecting surrounding objects and/or persons, and allow use of certain types of disinfecting agents that may be harmful to surrounding objects and/or persons. Alternatively, in some embodiments, chamber **124** can be designed as an open chamber. For example, disinfection system **100** may include walls or surfaces that partially surround an open space (e.g., a disinfecting area **125**). In such embodiments, any energy and/or disinfecting agents used with the disinfection system **100** may be ones that are not harmful to surrounding objects and/or persons. For example, a

UV light source such as an excimer light source can be used to disinfect without objects in an open chamber without causing safety concerns.

[0047] In some embodiments, disinfection system **100** can be designed with or for use with a conveyor unit or other type of transport unit configured to move an object being disinfected through the disinfecting area **125**. For example, disinfection system **100** can include one or more side panels or walls that are directed at the disinfecting area **125**, and a transport unit (e.g., conveyor belt) can be configured to move the object being disinfected through the disinfecting area **125**. In an embodiment, disinfection system **100** can include two side walls and a top wall (each formed of one or more modular units, as further described below) that encircle a space for receiving objects, and a bottom wall with a conveyor belt positioned thereon for moving the objects through the space. As objects are moved through the space encircled by the walls, the objects can be disinfected by one or more energy source(s) **122**, reflective unit(s) **120**, and/or spray unit(s) **160**. An example of a disinfection system with a conveyor unit is described in more detail with reference to FIG. **11**.

[0048] Disinfection system **100** can optionally include a transporting element **132**. Transporting element **132** can be any combination of suitable components configured for movement, such as, for example, a wheel, a caster, a rail, a skid, a sled, a track, etc. Transporting element **132** can be provided along a bottom or base of disinfection system **100** and can enable movement of disinfection system **100**, e.g., within a medical facility. Suitable examples of disinfection systems including transporting elements are disclosed in U.S. Patent Application Publication No. 2017/0340760, titled “System for disinfecting larger scale spaces and equipment,” filed May 23, 2017, the disclosure of which is incorporated herein by reference.

[0049] Disinfection system **100** can operate according to one or more disinfecting modes. Disinfection system **100** can be designed to vary the disinfecting mode based on user inputs and/or sensed information regarding an object, e.g., the location of the object relative to one or more energy source(s) **122**, the dimensions of the object, the type of object, the materials of the object, whether the object has hard or soft surfaces, the required level of disinfection associated with the object, etc. For example, disinfection system **100** can be configured to vary an amount of time of disinfection, use a subset of available energy source(s) **122**, use specific types of energy source(s) **122** (when multiple types are available), adjust the configuration and/or positioning of reflective unit(s) **120**, etc.

[0050] In some embodiments, disinfection system **100** includes spray unit(s) **160** (e.g. fluid dispensers) for applying one or more agents (e.g., disinfecting agent **190**, neutralizing agent **192**) to objects within disinfecting area **125**. Disinfection system **100** can use spray unit(s) **160** to apply the agents to further disinfect and/or treat an object being disinfected. Spray unit(s) **160** can be configured to dispense the agents in a liquid spray and/or a vapor/gas. In some embodiments, spray unit(s) **160** can be adjusted (e.g., via processor **154** and/or control panel **150**) to change a direction and/or spray profile of a sprayed substance. For example, spray unit(s) **160** can include one or more nozzles with openings that can be adjusted to vary an amount of liquid and/or vapor that is sprayed, the profile of the produced spray, and/or a direction of the produced spray. In some embodiments, spray unit(s) **160** can apply an electrostatic charge to the sprayed agent to encourage droplets of the agent to spread out more evenly and adhere to the neutral or negative charged surfaces of objects. In some embodiments, spray unit(s) **160** can be connected to a source of pressurized gas that can be used to generate aerosolized streams of disinfecting agent **190** and/or neutralizing agent **192**.

[0051] In some embodiments, disinfection system **100** can be configured to use one or more energy source(s) **122** to disinfect an object, as well as one or more spray unit(s) **160** to apply a disinfecting agent **190** and/or a neutralizing agent **192** to the object. By disinfecting with energy source(s) **122** and disinfecting agents **190**, disinfection system **100** can target different types surfaces and/or different types of pathogens. For example, energy source(s) **122** capable of emitting UV-C light have been shown to be effective at killing pathogens on hard surfaces, while a disinfecting agent

190 such as hydrogen peroxide has been shown to be effect at disinfecting soft surfaces. Therefore, disinfection system **100** may use both energy source(s) **122** and disinfecting agents **190** to disinfect an object having hard and soft surfaces. Disinfection system **100** may run a first disinfection cycle using energy source(s) **122** that emit UV-C light (e.g., a UV-C cycle) and a second disinfection cycle using the disinfecting agents **190** (e.g., a vapor cycle), sequentially or simultaneously. In an embodiment, disinfection system **100** can be configured for photocatalytic disinfection. For example, disinfection system, via spray unit(s) **160**, can apply a light-activated photosensitizer (e.g., titanium dioxide) to surfaces and use UV light and/or electromagnetic radiation emitted by one or more energy source(s) **122** to activate the photosensitizer and disinfect the surfaces.

[0052] Disinfecting agent **190** can include, for example, hydrogen peroxide, peracetic acid, electrolyzed water, atmospheric pressure plasma, polymeric guanidine, or ozone. Neutralizing agent **192** can be configured to reduce degradation of the object caused by the use of a disinfecting agent **190** and/or a particular type of energy source **122**. For example, neutralizing agent **192** can be applied before, during, and/or after activating the energy source(s) **122** and/or applying the disinfecting agent **190** to treat the surfaces of the object being disinfected, such that the object degrades less over time. Neutralizing agent **192** can also be configured to reduce the risk of harmful contact between a human and a disinfecting agent **190**. An example of a suitable neutralizing agent **192** can be water. Disinfecting agent **190** and/or neutralizing agent **192** can be delivered as a liquid spray and/or vapor.

[0053] Disinfection system **100** can optionally include exhaust unit(s) **162** configured to vent away air from disinfecting area **125** (e.g., to vent air out of chamber **124**) and/or supply clean air to disinfecting area **125** (e.g., to supply clean air into chamber **124**). Exhaust unit(s) **162** can be used in conjunction with spray unit(s) **160** to vent away air and/or vapors carrying disinfecting agent **190** and/or neutralizing agent **192**. When disinfection system **100** is used with spray unit(s) **160** and/or exhaust unit(s) **162**, body **110** can define a sealed chamber (e.g., chamber **124**) such that air containing disinfecting agents, neutralizing agents, and/or other substances can be sealed within the chamber and removed via exhaust unit(s) **162**, without exposing a user outside of the disinfecting area **125** to such air.

[0054] In some embodiments, disinfection system **100** includes one or more sensor(s) **164** for collecting information regarding components of disinfection system **100**, objects within and/or near disinfection system **100**, and/or other information that may affect the operation of disinfection system **100**. Sensor(s) **164** can be coupled and/or integrated into a panel or wall of disinfection system **100** or another component of disinfection system **100** (e.g., an energy source **122**, a reflective unit **120**, a spray unit **160**, or an exhaust unit **162**). Sensor(s) **100** can include, for example, motion sensors, image capture devices (e.g., cameras), light sensors, temperature sensors, pressure sensors, sound detectors, ozone sensors, etc. For example, sensor(s) **164** can include at least one motion sensor capable of detecting movement within and/or near disinfecting area **125** to determine whether a user may be harmed by energy, disinfecting agents, and/or other components of disinfection system **100**. In some embodiments, sensor(s) **164** can be configured to detect and/or determine information about objects within disinfecting area **125**. For example, sensor(s) **164** can include image capture devices that can capture images of objects within disinfecting area **125** and determine the object type, dimensions of the objects, distance and/or positioning of the objects relative to energy source(s) **122** and/or spray unit(s) **160**, or other information regarding the objects. Alternatively or additionally, sensor(s) **164** can include weight sensors, light sensors, etc. located on a base or floor associated with disinfection system, which can measure the weight, position, size, and/or orientation of objects within disinfecting area **125**. Disinfection system **100** can use this information to determine how to disinfect the objects. In some embodiments, sensor(s) **164** can be coupled to and/or integrated into an energy source **122**, reflective unit **120**, and/or a spray unit **160**, and be configured to monitor the operation of such components. For example, sensor(s) **164** can monitor temperatures and/or moisture levels associated with such components,

which can be used to confirm and/or modify disinfecting procedures.

[0055] In some embodiments, sensor(s) **164** can include a radio frequency identification (RFID) sensor, Quick Response (QR) reader, or other type of suitable sensor for identifying a user of the disinfection system **100** and/or objects placed within the disinfecting area **125**. Such sensor(s) **164** can be used to control access to and/or use of the disinfection system **100**, and/or to log information associated with use of the disinfection system **100**. For example, a RFID sensor can be configured to read a badge or other identifying card and/or device of a user to permit access by the user to the disinfection system **100**. A RFID sensor or a QR reader can be configured to read a tag (e.g., a RFID tag or QR code) located on an object placed in the disinfecting area **125** to identify the type of object. An onboard processor (e.g., processor **154**, described below) or another device in communication with the sensor(s) **164**, e.g., via a wired or wireless connection, can log the disinfections performed by the disinfection system **100**. In some embodiments, sensor(s) **164** can also detect when maintenance of the disinfection system **100** may be required, e.g., when a sensor **164** detects that a particular energy source **122** may no longer be functional.

[0056] Disinfection system **100** can include a control panel **150** with an input/output (I/O) interface **152**. Control panel **150**, via I/O interface **152**, can be configured to receive and process user inputs and/or monitor the operations and functions of disinfection system **100**. The control panel **150** can be electrically coupled to a processor **154**, which can be used to control one or more components of disinfection system **100**. Processor **154** can be any suitable processing device configured to execute functions associated with disinfection system **100**. For example, processor **154** can be configured to activate one or more energy source(s) **122**. In embodiments where disinfection system **100** includes reflective unit(s) **120**, processor **154** can be electrically coupled to one or more reflective unit(s) **120** and be configured to move (e.g., rotate, translate, etc.) the reflective unit(s) **120** to control the direction that energy is reflected, e.g., to target a surface of an object and/or specific area within disinfecting area **125**. In embodiments where disinfection system **100** includes sensor(s) **164**, processor **154** can be electrically coupled to one or more sensor(s) **164** and be configured to receive information from the sensor(s) **164** (e.g., information regarding objects within disinfecting area **125**, one or more components of disinfection system **100**, and/or an environment around disinfection system **100**). Processor **154** can be configured to select specific disinfection modes (e.g., disinfection type or cycle), deactivate the disinfection system **100** (e.g., in cases where a user may be harmed by disinfection procedures), change a disinfection step, and/or provide an alert or status update (e.g., an audio and/or visual alert, or an electronic alert), based on the information received from the sensor(s) **164**. Processor **154** can be, for example, one or more of a general purpose processor, a Field Programmable Gate Array (FPGA), an Application Specific Integrated Circuit (ASIC), a Digital Signal Processor (DSP), and/or the like. Disinfection system **100** can also include an onboard power source (e.g., a battery) and/or be coupled to a power source (e.g., be plugged into a wall socket). I/O interface **152** can include a user interface with one or more components that are configured to receive inputs and/or present outputs to users and/or user devices. For example, the user interface can include a display device (e.g., a display, a touch screen, etc.), an audio device (e.g., a microphone, a speaker), a keyboard, a scanner or reader (e.g., a radio-frequency identification (RFID) reader, a near-field communication (NFC) reader, etc.), etc.

[0057] In some embodiments, disinfection system **100** can be connected to a network (e.g., a local area network (LAN), a wide area network (WAN), a virtual network, a telecommunications network) implemented as a wired network and/or wireless network and be configured to communicate with other devices coupled to the network, e.g., another disinfection system **100**, a server, or other compute devices. Disinfection system **100** can be configured to receive and send information via the network, including, for example, information regarding the operation of and/or disinfections performed by disinfection system **100**. In some embodiments, disinfection system **100**, via the network, can be connected to a remote control panel or system through which a user can remotely control disinfections system **100**. In some embodiments, disinfection system **100** can

be connected to a cloud network that hosts one or more other applications that can interface with disinfection system **100** to provide other service(s). For example, disinfection system **100** can be connected to a remote server that tracks the object(s) that have been disinfected by the disinfection system **100**, and can provide this information to administrator and/or for reporting purposes. In some embodiments, disinfection system **100** can also report information regarding disinfected object(s) to cloud-based applications and/or devices that facilitate real-time updates to local staff within a medical facility (e.g., updates at a computer and/or electronic indicator tags on disinfected object(s)).

[0058] Disinfection system **100** can be a unitary structure, or disinfection system **100** can be implemented as multiple structures located in the vicinity of one another. In some embodiments, disinfection system **100** can be formed of modular units that can be assembled together to form disinfection system **100**, as further described below.

[0059] FIG. 2A depicts an example disinfection system **200**, according to embodiments disclosed herein. Disinfection system **200** can be formed of a plurality of modular units. Disinfection system **200** includes side walls **212**, **214**, a top wall **216**, and a back wall **218**. In some embodiments, disinfection system **200** can also include additional walls, e.g., a floor or bottom wall and/or a front door or wall (not depicted). Each wall **212**, **214**, **216**, **218** can be formed of one or more modular units. For example, wall **212** can optionally be formed of four modular units **212a**, **212b**, **212c**, **212d**; wall **214** can optionally be formed of four modular units **214a**, **214b**, **214c**, **214d**; and wall **216** can be formed of four modular units **216a**, **216b**, **216c**, **216d**. Alternatively, each of walls **212**, **214**, **216** can be formed of a single modular unit. Modular units **212a**, **212b**, **212c**, **212d** can be similar to one another and include the same components (e.g., energy source(s), reflective unit(s), spray unit(s), etc.) and/or also be similar to other modular units of other walls, e.g., modular units **214a**, **214b**, **214c**, **214d** and/or modular units **216a**, **216b**, **216c**, **216d**. Each modular unit can be designed to be interchangeable with one or more other modular units, e.g., modular unit **212a** can be interchangeable with any one of modular units **212b**, **212c**, **212d** and/or other modular units, such as one or more of modular units **214a**, **214b**, **214c**, **214d**, **216a**, **216b**, **216c**, **216d**.

[0060] Each modular unit can be manufactured and/or assembled at a manufacturing facility and transported to a location for onsite assembly into disinfection system **200**. Transportation costs can be reduced by transporting the modular units separately to an onsite location. Individual modular units can be dimensioned to fit through standard sized doorways and openings within a building, such as, for example, a medical facility. Each modular unit can also weigh and/or be dimensioned such that a human can directly lift and/or move the units, or use standard moving tools to lift and/or move the units, such as, for example, a dolly, a lift, a moving cart, etc.

[0061] Each modular unit can be coupled to the modular units adjacent to it via suitable fastening elements (e.g., mechanical fasteners, magnets, adhesives, etc.). In some embodiments, modular units can include built-in connectors for quick coupling and assembly, e.g., snap-on connectors, magnetic connectors, etc.

[0062] While disinfection system **200** is depicted as a box-shaped structure, in other embodiments, disinfection system can have a different shape, e.g., a spherical shape, a pyramidal shape, a cylindrical shape, etc.

[0063] FIG. 2B provides a schematic view of modular unit **212a**, which can be similar to and/or the same as other modular units depicted in FIG. 2A (e.g., modular units **212b**, **212c**, **212d**, **214a**, **214b**, **214c**, **214d**, **216a**, **216b**, **216c**, **216d**). Modular unit **212a** can include at least one reflective unit **220** and can optionally include one or more energy source(s) **22**, spray unit(s) **260**, and/or exhaust unit(s) **262**. Reflective unit **220** can be similar to reflective unit **120**, as described above. For example, reflective unit **220** can have one or more surfaces configured to reflect energy emitted by energy sources disposed on modular unit **212a** and/or other modular units (e.g., modular units **212b**, **212c**, **212d**, **214a**, **214b**, **214c**, **214d**, **216a**, **216b**, **216c**, **216d**). When modular unit **212a** is assembled in disinfection system **200**, reflective unit **220** can be disposed on an inner surface of

wall **212**, such that reflective unit **220** can be configured to direct energy emitted by energy sources into a chamber defined by walls **212**, **214**, **216**. In some embodiments, reflective unit **220** can be adjusted, e.g., manually and/or automatically, to change the direction that it directs energy into the chamber defined by walls **212**, **214**, **216**. Reflective unit **220** can have a concave shape (e.g., a hyperbolic shape) that can spread and reflect energy into the chamber, or have multiple reflective surfaces that are angled with respect to one another to spread and reflect light into the chamber. In some embodiments, reflective unit **220** can be implemented as a reflective coating that can cover a portion or all of an inner facing surface of modular unit **212a**. In other embodiments, reflective unit **220** can be implemented as a one or more reflective surface mounted on beams or other support structures attached to an inside surface of modular unit **212a**.

[0064] Energy source(s) **222** can be similar to energy source(s) **122**. For example, each energy source **222** can be configured to emit energy, such as, for example, UV light or HINS light. When modular unit **212a** is assembled in disinfection system **200**, energy source(s) **222** can be disposed on an inner surface of wall **212**, such that energy emitted by energy source(s) **222** can be directed into the chamber defined by walls **212**, **214**, **216**. In some embodiments, energy source(s) **222** can emit light that is predominantly UV-C light (e.g., at least 75% of which is UV-C light).

[0065] While reflective unit(s) **220** and energy source(s) **222** are described with reference to a modular unit **212a**, one or more reflective unit(s) **220** and/or energy source(s) **222** can be disposed on other modular units, e.g., one or more of modular units **212b**, **212c**, **212d**, **214a**, **214b**, **214c**, **214d**, **216a**, **216b**, **216c**, **216d**, or on other surfaces of disinfection system **200** (e.g., back wall **218** and/or a bottom wall or floor). Collectively, reflective unit(s) **220** and/or energy source(s) **222** disposed on the modular units, walls, and/or other portions of disinfection system **200** can ensure that an adequate amount of energy reaches each surface of an object that is located within the chamber, such that the object can be disinfected using the emitted energy. More specifically, reflective unit(s) **220** and/or energy source(s) **222** can be disposed in any suitable location, orientation, configuration, size, and/or number such that an object within the chamber defined by walls **212**, **214**, **216** is exposed to energy at sufficient intensities (e.g., at least 100 $\mu\text{W}/\text{cm}^2$ at 1 meter) for a sufficient amount of time to enable disinfection.

[0066] Spray unit(s) **160** can be similar to spray unit(s) **160**. For example, spray unit(s) **260** can be configured to deliver one or more agents (e.g., disinfecting agents, neutralizing agents) into the chamber. When modular unit **212a** is assembled in disinfection system **200**, spray unit(s) **260** can be disposed on an inner surface of wall **212**, such that spray unit(s) **260** can direct one or more agents at an object located within the chamber. Spray unit(s) **260** can be configured to deliver the agents as a liquid spray and/or vapor. In some embodiments, spray unit(s) **260** can be configured to electrically charge droplets of the agent such that the droplets are predisposed to evenly distribute and/or adhere to the surfaces of an object within the chamber. Modular unit **212a** can include fluid connection(s) **227** that are coupled to spray unit(s) **260** and can provide fluid communication between spray unit(s) **260** and a source of an agent (e.g., a fluid reservoir). Fluid connection(s) **227** can include ports and/or channels integrated into, coupled to, and/or coupleable to the modular unit **212a**.

[0067] Exhaust unit(s) **262** can be similar to exhaust unit(s) **162**. For example, exhaust unit(s) **262** can be configured to circulate air into and/or out of the chamber. For example, exhaust unit(s) **262** can be configured to vent air out of chamber, e.g., with a fan, by applying a vacuum or suction, or other suitable means. Additionally or alternatively, exhaust unit(s) **262** can circulate clean air into the chamber, e.g., via a fan, air pump, or other suitable means. Exhaust unit(s) **262** can be coupled to fluid connection(s) **227**, which provide an inlet and/or outlet path for air from the chamber. In some embodiments, exhaust unit(s) **262**, via fluid connection(s) **227**, can vent air through a filtration and/or air purification system, which can clean and/or disinfect the air for recirculation through other fluid channels and/or exhaust unit(s) **262** back into the chamber.

[0068] Modular unit **212a** can optionally include electrical connection(s) **226**. Electrical

connection(s) **226** can be coupled to one or more of reflective unit(s) **220**, energy source(s) **222**, spray unit(s) **260**, and/or exhaust unit(s) **262**, to connect those components to a power source and/or control unit (e.g., an onboard or off-board control unit, including, for example, a processor and/or control panel). The control unit (not depicted) can be used to control the operation of one or more of reflective unit(s) **220**, energy source(s) **222**, spray unit(s) **260**, and/or exhaust unit(s) **262**. For example, the control unit can be used to selectively activate, move, and/or adjust one or more of one or more of reflective unit(s) **220**, energy source(s) **222**, spray unit(s) **260**, and/or exhaust unit(s) **262**. In some embodiments, the control unit can be coupled to one or more sensors for detecting information about the objects within chamber, the surrounding environment, and/or a user of the disinfection system **200**.

[0069] Modular unit **212a** can include a connector **225**, which can be used to couple modular unit **212a** to other modular unit(s) (e.g., modular unit **212b** or **212c**). In some embodiments, connector **225** can include electrical connection(s) **226** and/or fluid connection(s) **227**, which can be coupled to one or more of reflective unit(s) **220**, energy source(s) **222**, spray units) **260**, and/or exhaust unit(s) **262**. Connector **225** can be disposed on a side of modular unit **212a**, such that connector **225** can be configured to couple to a connector on an adjacent modular unit (e.g., modular unit **212b** or **212c**) when the two modular units are attached to one another. In some embodiments, connector **225** can be designed as a snap-on connector that can engage with a corresponding connector located on an adjacent modular unit. Connector **225**, via a network of connections (e.g., including additional connectors, electrical connection(s), and/or fluid connection(s)) through modular units, can be coupled to an air ventilation system, an air filtration system, a source of disinfecting agent and/or neutralizing agent, a control unit, power source, etc.

[0070] While disinfection system **200** is depicted as having walls that can be formed of a single modular unit or, optionally, formed of four modular units placed in a two-by-two arrangement (e.g., wall **212** being formed of four modular units **212a**, **212b**, **212c**, **212d**), other disinfection systems can include walls with different arrangements and/or configurations (e.g., shapes, sizes, etc.) of modular units. For example, FIG. 3A depicts a wall **312** formed of two modular units **312a**, **312b** that are rectangular-shaped positioning in a two-by-one arrangement (i.e., with modular unit **312a** positioned above modular unit **312b**). FIG. 3B depicts a wall **412** formed of four modular units **412a**, **412b**, **412c**, **412d** that are rectangular-shaped and positioned in a four-by-one arrangement. FIG. 3C depicts a wall **512** formed of two modular units **512a**, **512b**, each having a triangular shape and coming together to form a rectangular shaped wall. Different arrangements and/or configurations of modular units can be used, e.g., to accommodate differently shaped components (e.g., energy sources, reflective units, spray units, exhaust units) and/or due to space limitations (e.g., during shipping and transport to an onsite location). In some embodiments, modular units can be designed with longer coupling surfaces (e.g., for coupling to adjacent modular units), such that more connections between the two modular units can be accommodated and/or more stability can be provided via the coupling.

[0071] FIG. 4 depicts another arrangement of modular units forming a wall **612** of a disinfection system. As depicted, wall **612** is formed of three modular units **612a**, **612b**, **612c**. Modular units **612a**, **612b**, **612c** can similar to and/or the same as one another. Modular units **612a**, **612b**, **612c** can be arranged in a L-shaped configuration, such that wall **612** can have ends with varying lengths. Specifically, wall **612** can have a first end with a length **L1** and a second end with a length **L2**, where length **L1** is equal to the combined length of two modular units **612a**, **612b** and length **L2** is equal to the length of a single modular unit **612c**. When wall **612** is assembled in a disinfection system, wall **612** can define a chamber that has regions with varying height such that it can receive a similarly shaped object. For example, the chamber can be configured to receive a gurney with an attached IV pole such that the height of the IV pole can be accommodated by the taller region defined by modular units **612a**, **612b**. Other arrangements and/or configurations of modular units can be used to construct disinfection systems capable of receiving objects having

other sizes and/or shapes.

[0072] Disinfection systems having a modular design can have improved customizability, adaptability, and/or serviceability. For example, individual modular units can be designed to be interchangeable with one another, and can be assembled together in a number of different ways to form differently shaped and/or sized disinfection systems. Depending on a user's disinfection needs and/or space limitations, the user can select from several different types of modular units, and can assemble those modular units in various ways to define differently sized and shaped disinfection areas and/or chambers. When a particular component of a modular unit requires maintenance and/or repair, that modular unit can be replaced without requiring the entire disinfection system to be serviced and/or replaced, thereby reducing repair costs and/or downtime. Additionally, when improvements to modular units are available (e.g., a new design of a particular modular unit becomes available), existing disinfection systems can be outfitted with the new modular units by replacing old units with the new ones without requiring a full redesign and/or replacement of the system.

[0073] FIGS. 5A, 5B, 5C, and 5D schematically illustrate an example disinfection system **700**, according to some embodiments. Disinfection system **700** includes a plurality of walls, i.e., side walls **712**, **714**, a top wall **716**, a back wall **718**, a front wall **719**, and optionally a base or bottom wall **736**. FIGS. 5A and 5B depict a top view of disinfection system **700**, with the top wall **716** removed to show interior features of the system. FIG. 5C depicts a front view of the disinfection system **700**, with the front wall **719** removed to show interior features of the system. And FIG. 5D depicts a side view of the disinfection system **700**, with the side wall **714** removed to show interior features of the system.

[0074] Walls **712**, **714**, **716**, **718**, **719**, **736** can define a chamber **724** sized to receive objects for disinfection. While walls **712**, **714**, **716**, **718**, **719**, **736** are depicted as extending substantially perpendicular from one another to define a rectangular-shaped chamber **724**, it can be appreciated that disinfection systems described herein can have different configurations and/or shapes. For example, any one of walls **712**, **714**, **716** can extend at an off-normal axis from back wall **718**, and can have a non-rectangular shape (e.g., a trapezoidal shape, a triangular shape, etc.). Walls **712**, **714**, **716** can define an opening **730** through which an object can be received within chamber **724**.

[0075] Front wall **719** can be movable between a closed configuration (as depicted in FIG. 5A) and an open configuration (as depicted in FIG. 5B). Front wall **719** can move between the closed configuration and the open configuration, as shown via arrow B. Front wall **719** can be coupled to side wall **712** via a joint **734**, and can pivot about joint **734** to move between the closed configuration and the open configuration. While front wall **719** is shown as a single panel, in other embodiments, front wall **719** can be formed of multiple panels and/or sections, and each panel can be coupled to the same or a different side wall. An example of such an arrangement is described below with reference to FIGS. 11-15. In some embodiments, front wall **719** can be coupled to side wall **712** (and/or other side walls) using a mechanical connector other than a joint, e.g., using an elastic material, a slider bar, etc. In some embodiments, disinfection system **700** can include a control unit that can electrically operate front wall **719**, e.g., to move it between an open configuration and a closed configuration. Front wall **719** can be formed of a rigid and/or flexible material (e.g., metal, cloth, fabric, plastic, etc.). In some embodiments, front wall **719** can be designed to be retractable, such that it can be retracted to expose opening **730**.

[0076] When front wall **719** is in the closed configuration, front wall **719** can seal opening **730** of chamber **724** such that energy (e.g., UV light) within chamber **724** does not exit chamber **724**. In some embodiments, walls **712**, **714**, **716**, **718**, **719**, **736** can form an air-sealed chamber such that air (e.g., air including disinfecting agent and/or neutralizing agent and/or contaminated air) cannot exit chamber **724**. By sealing in energy and/or air, front wall **719** can reduce the risk of a user outside of chamber **724** from being harmed by energy and/or air present within chamber **724**. When front wall **719** is in the open configuration, front wall **719** can allow access to opening **730** such

that an object can be placed within chamber 724 via opening 730.

[0077] One or more of walls 712, 714, 716, 718, 719, 736 can be formed of modular units. For example, wall 712 can be formed of four modular units 712a, 712b, 712c, 712d; wall 714 can be formed of four modular units 714a, 714b, 714c, 714d; and wall 716 can be formed of four modular units 716a, 716b, 716c, 716d. In some embodiments, one or of more walls 718, 719, 736 can also be formed of modular units, including some walls being formed of a single modular unit.

[0078] Modular units 712a, 712b, 712c, 712d, 714a, 714b, 714c, 714d, 716a, 716b, 716c, 716d can be designed to be interchangeable with one another. Therefore, each modular unit can have similar components as other modular units. An inner surface of each modular unit can include at least one reflective unit 720 and at least one energy source 722. Additional reflective unit(s) 720 and/or energy source(s) 722 can be positioned on the inside surfaces of walls 718, 719, 736, as shown in FIGS. 5A-5D. For example, an inner surface of wall 718 can include at least one reflective unit 720 and, optionally, one or more energy source(s) 722. An inner surface of wall 719 can include at least one reflective unit 720 and, optionally, one or more energy source(s) 722. And an inner surface of wall 736 can include at least one reflective unit 720 and, optionally, one or more energy source(s) 722. In an embodiment, each of modular units 712a, 712b, 712c, 712d, 714a, 714b, 714c, 714d, 716a, 716b, 716c, 716d can include at least one least one reflective unit 720 and at least one energy source 722, and each of walls 718, 719, 736 can include at least one reflective unit 720. While reflective unit(s) 720 and/or energy source(s) 722 are depicted on a central portion of the modular units, it can be appreciated that reflective unit(s) 720 and/or energy source(s) 722 can be located on any portion of an inner surface of a modular unit and/or cover an entire inner surface of a modular unit. And while reflective unit(s) 720 are depicted as surrounding energy source(s) 722, it can be appreciated that reflective unit(s) 720 and/or energy source(s) 722 can be positioned in any suitable arrangement, including arrangements where reflective unit(s) 720 and energy source(s) 722 each cover an entire inner surface of a modular unit. Further examples of these and other arrangements of reflective unit(s) 720 and/or energy source(s) 722 are described below with reference to FIGS. 8A, 8B, 9A, and 9B.

[0079] Reflective unit 720 can be similar to other reflective units described herein (e.g., reflective units 120 and/or 220). For example, reflective unit 720 can include one or more reflective surfaces that can reflect energy (e.g., disinfecting light emitted by an energy source 722). In some embodiments, reflective unit 720 can be implemented as a reflective coating and/or flat reflective surface. Energy source 722 can be similar to other energy sources described herein (e.g., energy source 122 and/or 222). For example, energy source 722 can be configured to emit a light capable of disinfecting a surface of an object, such as, for example, UV light and/or HINS light. Each energy source 722 can be disposed near and/or within a reflective unit 720, such that energy emitted by the energy source 722 can be reflected and directed into chamber 724 via the reflective unit 720. Other energy sources 722 and/or reflective units 720 located on other modular units can also emit and reflect energy into chamber 724, such that a collective amount of energy sufficient for disinfection is directed into chamber 724 and/or at an object disposed within chamber 724.

[0080] In some embodiments, one or more modular units 712a, 712b, 712c, 712d, 714a, 714b, 714c, 714d, 716a, 716b, 716c, 716d, or walls 712, 714, 716, 718, 719, 736 can be movable relative to other components of disinfection system 700. For example, wall 712 and/or an individual modular unit 712a, 712b, 712c, 712d can be movable along an axis D; wall 714 and/or an individual modular unit 714a, 714b, 714c, 714d can be movable along an axis E; wall 716 and/or an individual modular unit 716a, 716b, 716c, 716d can be movable along an axis F; and wall 718 can be movable along an axis C. Additionally or alternatively, one or more reflective unit(s) 720 and/or energy source(s) 722 can be movable relative to a wall or modular unit. Movement of walls, modular units, reflective unit(s) 720, and/or energy source(s) 722 can be controlled by a control unit (e.g., a processor and/or control panel, such as processor 154 and/or control panel 150), and/or be moved manually by a user (e.g., via a mechanical mechanism, such as a lever, and/or by directly

pushing or pulling on an individual component). Walls, modular units, reflective unit(s) **720**, and/or energy source(s) **722** may be moved to position reflective unit(s) **720** and/or energy source(s) **722** closer to an object within chamber **724** to increase the efficiency of the disinfection process. For example, if a small object is placed within chamber **724**, one or more walls, modular units, reflective unit(s) **720**, and/or energy source(s) **722** may be moved to reduce the distance between the object and reflective unit(s) **720** and/or energy source(s) **722** and/or a size of the overall chamber **724**, such that a greater intensity of energy is received at the surfaces of the object. Increasing the intensity of the energy received by the object can reduce disinfection time and/or improve disinfection efficacy.

[0081] While axes C, D, E, F are shown as being perpendicular to walls **718**, **712**, **714**, **716**, respectively, one of ordinary skill in the art would appreciate that walls, modular units, reflective unit(s) **720**, and/or energy source(s) **722** can move in other directions, such as, for example, rotate about an axis and/or translated in angled directions.

[0082] Optionally, in some embodiments, disinfection system **700** can include a transporting element **732**, such as, for example, wheels, casters, sleds, tracks, etc. Transporting element **732** may be disposed along a bottom surface of wall **736**. Transporting element **732** can be similar to other transporting elements described herein (e.g., transporting element **132**). For example, transporting element **732** can enable disinfection system **700** to maneuver through spaces, including rooms within a medical facility. In some embodiments, transporting element **732** can be retracted into openings formed in wall **736**.

[0083] In some embodiments, wall **736** can include a ramped surface **734** to facilitate placement of an object into chamber **724** and/or removal of an object from chamber **724**. In some embodiments, wall **736** can also include elements for guiding an object to a specific location within chamber **724** and/or restricting movement of the object within the chamber, such as, for example, stoppers, tracks, treads, depressions, etc. These elements can optionally be adjusted (e.g., via a processor and/or control panel, such as processor **154** and/or control panel **150**) to accommodate different types of objects and/or change a placement of an object within chamber **724**.

[0084] FIG. **6** schematically depicts a side view of an example disinfection system **800**, according to other embodiments disclosed herein. Disinfection system **800** can include similar components as other disinfection systems described herein (e.g., disinfection systems **100**, **200**, and/or **700**). Disinfection system **800** can include side walls (including a side wall **812**), a top wall **816**, a back wall **818**, and optionally a bottom wall **836**. In FIG. **6**, a second side wall similar to wall **812** is not depicted so that an interior of disinfection system **800** can be viewed.

[0085] At least one wall of disinfection system **800** can be formed of one or more modular units. For example, side wall **812** can be formed of modular units **812a**, **812b**, **812c**, **812d**; and top wall **816** can be formed of at least two modular units **816a**, **816b**. Optionally, back wall **818** and/or bottom wall **836** can be formed of one or more modular units. Modular units **812a**, **812b**, **812c**, **812d**, **816a**, **816b** can each include at least one reflective unit **820** and at least one energy source **822**. In some embodiments, back wall **818** can include a reflective inner surface **818a**, and/or bottom wall **836** can include a reflective inner surface **836a**. Reflective inner surfaces **818a**, **836a** can be implemented as a reflective coating and/or material that can reflect energy emitted by energy source(s) **822** into chamber **824**. In some embodiments, inner surfaces **818a**, **836a** can also include an energy source configured to emit energy, such as, for example, light emitting nanoparticles. Further details regarding reflective surfaces including light emitting nanoparticles are described with reference to FIGS. **9A** and **9B**.

[0086] Disinfection system **800** can include a flexible curtain or drape **819** as a front wall. Curtain **819** can be configured to move between an open configuration and a closed configuration. In the closed configuration, as depicted in FIG. **6**, curtain **819** can cover an opening to chamber **824**. In the open configuration, curtain **819** can be retracted (e.g., rolled up) via a wheel or pulley, and/or pulled aside using another mechanical and/or electrical mechanism, to expose the opening to

chamber **824** such that an object can be placed within chamber **824**. Curtain **819** can include an inner surface **819a** that can be a reflective surface. In some embodiments, inner surface **819a** can also include at least one energy source, e.g., light emitting nanoparticles.

[0087] In some embodiments, one or more walls, modular units, reflective unit(s) **820**, and/or energy source(s) **822** can be movable such that an angle or direction of reflective unit(s) **820** and/or energy source(s) **822** can be adjusted and/or a distance of reflective unit(s) **820** and/or energy source(s) **822** to an object be reduced.

[0088] FIG. 7 schematically depicts a side view of an example disinfection system **900**, according to other embodiments disclosed herein. Disinfection system **900** can be similar to disinfection system **700** (and include components that are similar to other disinfection systems described herein), but also include at least one spray unit **960**. Disinfection system **900** can include side walls (including a side wall **912**), a top wall **916**, a back wall **918**, and a bottom wall **936**. In FIG. 7, a second side wall similar to wall **912** is not depicted so that an interior of disinfection system **900** can be viewed.

[0089] At least one wall of disinfection system **900** can be formed of modular units. For example, side wall **912** of disinfection system can be formed of modular units **912a**, **912b**, **912c**, **912d**, and top wall **916** of disinfection system can be formed of at least two modular units **916a**, **916b**.

Modular units **912a**, **912b**, **912c**, **912d**, **916a**, **916b** can each include at least one reflective unit **920** and at least one energy source **922**. In some embodiments, one or more walls can include a reflective inner surface, e.g., back wall **918** can include a reflective inner surface **918a** and/or front wall **919** can include a reflective inner surface **919a**.

[0090] At least one wall and/or modular unit of disinfection chamber **900** can include a spray unit **960**. For example, modular units **916a**, **916b** can each include spray unit(s) **960**. Spray unit(s) **960** can be similar to spray unit(s) **160**, as described above. For example, spray unit(s) **960** can be configured to deliver substances, including, for example, a disinfecting agent, a neutralizing agent, and/or a photosensitizer. Spray unit(s) **960** can be configured to deliver such substances as a liquid spray and/or a vapor. Spray unit(s) **960** can be located on any portion of an inner surface of a modular unit and/or wall. In some embodiments, spray unit(s) **960** can be adjusted (e.g., via a processor and/or control panel, such as processor **154** and/or control panel **150**) to change a direction and/or spray profile of a sprayed substance. In some embodiments, spray unit(s) **960** can apply an electrostatic charge to the sprayed substance to encourage droplets of the substance to spread out more evenly and adhere to the neutral or negative charged surfaces of an object within chamber **924**.

[0091] Walls of disinfection chamber **900** can be designed to form a fluidically sealed chamber **924** that can prevent energy and/or other substances (e.g., a disinfecting agent, a neutralizing agent, and/or a photosensitizer) from exiting chamber **924**. In some embodiments, spray unit(s) **960** can be configured to deliver a single type of disinfecting agent. In other embodiments, some spray units **960** can be configured to deliver a first type of disinfecting agent while other spray units **960** can be configured to deliver a second type of disinfecting agent, e.g., in the case where different disinfecting agents may be required to kill different types of pathogens. In other embodiments, some spray units **960** can be configured to deliver a disinfecting agent while other spray units **960** can be configured to deliver a neutralizing agent, e.g., in the case where a neutralizing agent may be used to reduce the degradation effects caused by the disinfection agent. In other embodiments, some spray units **960** can be configured to deliver a disinfecting agent while other spray units **960** can be configured to deliver a photosensitizer, e.g., in the case where a photosensitizer and a disinfecting agent may be used, along with an energy source (e.g., a UV light source), to disinfect an object.

[0092] Disinfection system **900** includes at least one exhaust unit **962**. Exhaust unit **962** can be similar to exhaust unit **162**, described above. For example, exhaust unit **962** can be configured to circulate air into and/or out of chamber **924**, including air containing a disinfecting agent and/or a

neutralizing agent. Exhaust unit **962** can be disposed on an inner surface of bottom wall or base **936**. Alternatively or additionally, one or more exhaust units can be disposed on other walls and/or modular units of disinfection system **900**.

[0093] In some embodiments, one or more walls, modular units, reflective unit(s) **920**, energy source(s) **922**, and/or spray unit(s) **960** can be movable such that an angle or direction of reflective unit(s) **920**, energy source(s) **922**, and/or spray unit(s) **960** can be adjusted and/or a distance of reflective unit(s) **920**, energy source(s) **922**, and/or spray unit(s) **960** to an object be reduced.

[0094] FIGS. **8A**, **8B**, **9A**, and **9B** depict different configurations of modular units having one or more energy sources and/or reflective units. FIG. **8A** depicts an example modular unit **1012** having two reflective units **1020** and two energy sources **1022**. Modular unit **1012** can be similar to any of the modular units described herein (e.g., modular units forming a part of disinfection systems **200**, **700**, **800**, and/or **900**). Each energy source **1022** can be housed within a reflective unit **1020**.

Energy sources **1022** can be implemented as light bulbs or tubes, such as, for example, a mercury vapor bulb or tube, a xenon gas bulb or tube, etc. In an embodiment, each energy source **1022** can be configured to emit UV light having an intensity of at least $100\ \mu\text{W}/\text{cm}^2$ at 1 meter. Each reflective unit **1020** can have a concave shape such that energy emitted from each of the respective energy sources **1022** can be directed and/or focused by the reflective unit **1020** toward a disinfecting area (e.g., into a chamber) and/or an object disposed in the disinfecting area. In an embodiment, each reflective unit **1020** can have a plurality of reflective surfaces that are disposed off normal with respect to a back section of the reflective unit **1020**, such that energy emitted by each of the respective energy sources **1022** can be directed in multiple directions toward a disinfecting area and/or an object disposed in the disinfecting area.

[0095] Modular unit **1012** can be shaped as a panel with a width **L3** and a length **L4**. The width **L3** and the length **L4** of modular unit **1012** can be appropriately sized for treating medical equipment and/or other objects within a medical facility (e.g., a hospital). Additionally, modular unit **1012** can be dimensioned to fit through standard sized doorways and openings in medical facilities, such that the units can easily be moved between rooms. In an embodiment, modular unit **1012** can have a width **L3** of approximately 25 inches and a length **L4** of approximately 50 inches. Multiple modular units, such as modular unit **1012**, can be stacked relative to one another to form a disinfection system having dimensions for receiving various medical equipment and/or other objects. Examples of different arrangements of modular units are described with reference to FIGS. **11-16**.

[0096] FIG. **8B** depicts an example modular unit **1112** having a plurality of energy sources **1122**. Energy sources **1122** can be arranged on a reflective surface **1120** acting as a reflective unit. Reflective surface **1120** can be a flat and/or curved surface that directs and/or focuses light toward a disinfecting area and/or an object located in disinfecting area. Reflective surface **1120** can be formed of a reflective material and/or include a reflective coating. Energy sources **1122** can be LEDs that are configured to emit UV and/or HINS light. Similar to modular unit **1012**, modular unit **1112** can be sized to disinfect medical equipment or other objects located within a medical facility.

[0097] FIGS. **9A** and **9B** depict an example modular unit **1712** that includes a light source implemented as light emitting nanoparticles **1722**. The light emitting nanoparticles **1722** can be deposited or grown on a flexible conductive layer. In an embodiment, molecular beam epitaxy (MBE) can be used to deposit nanowire heterostructures (e.g., GaN nanowires, AlGaIn nanowires, InGaIn nanowires) onto a conductive layer, such as, for example, a metal foil or film (e.g., a titanium foil, a tantalum foil, etc.). The nanowires may grow in arrays along the conductive layer surface. When energized (e.g., excited), the nanowires may emit energy at wavelengths between 350-400 nm. FIG. **9B** provides a cross-sectional view of a portion of modular unit **1712**, showing a layer of the light emitting nanoparticles **1722** deposited on a conductive layer **1721** (e.g., a metal foil or film). Suitable examples of light emitting nanoparticles are described by Sarwar et al. in

“Semiconductor Nanowire Light-Emitting Diodes Grown on Metal: A Direction Toward Large-Scale Fabrication of Nanowire Devices,” published Aug. 25, 2015, available at <https://doi.org/10.1002/sml.201501909>, and “Nanowire LEDs Grown Directly on Flexible Metal Foil,” available at <https://aip.scitation.org/doi/am-pdf/10.1063/1.4945419>.

[0098] Optionally, a reflective layer **1720**, such as a thin coat or film, can be deposited on top of the light emitting nanoparticles **1722**. Reflective layer **1720** can be a partially reflective and partially transparent element. Specifically, reflective layer **1720** can be configured to allow energy emitted by light emitting nanoparticles **1722** located below reflective layer **1720** to pass through but reflect energy directed at the reflective layer **1720** in the opposite direction. Reflective layer **1720** and light emitting nanoparticles **1722** can be positioned around a disinfecting area and/or a chamber such that light emitted by nanoparticles **1722** and/or reflected by reflective layer **1720** can be directed at the disinfecting area and/or an object located in the disinfecting area. For example, when modular unit **1712** is assembled in a disinfection system having a chamber, reflective layer **1720** and light emitting nanoparticles **1722** can be located on an inside surface of the modular unit **1712** that faces the chamber such that it can direct energy into the chamber and/or at an object located in the chamber.

[0099] Similar to modular unit **1012**, modular unit **1712** can be sized to disinfect medical equipment or other objects located within a medical facility.

[0100] FIG. **10** depicts an example disinfection system **1600**. Disinfection system **1600** can include similar components as other disinfection systems disclosed herein (e.g., disinfection systems **100**, **200**, **700**, **800**, and/or **900**). Disinfection system **1600** can be formed of a plurality of modular units (e.g., modular units **1612a**, **1612b**, **1612c**, **1612d**), but the modular units do not form an enclosure that defines a chamber. Instead, disinfection system **1600** can be a wall-mounted or free-standing system that can focus and/or direct light at objects located in a disinfecting area (e.g., an object **1680**). Modular units **1612a**, **1612b**, **1612c**, **1612d** can be supported and orientated by one or more support elements **1616** (e.g., a beam, a rod, a platform, etc.). Modular units **1612a**, **1612b**, **1612c**, **1612d** can be similar to other modular units described herein (e.g., modular unit **212a**), and can include components such as a connector, an energy source, a reflective unit, a spray unit, an exhaust unit, and/or a sensor.

[0101] Disinfecting area can be, for example, a section of a room that is closed off using curtains or other barriers. Objects, such as object **1680**, can be transported into the disinfecting area via a transport device **1634**, such as, for example, a moving track. Alternatively, objects can be placed in disinfecting area by a user and/or a mechanical and/or electrical device (e.g., a robotic device).

[0102] Disinfection system **1600** can have a processor and/or control panel (not depicted) configured to control the operation of disinfection system **1600**. Optionally, disinfection system **1600** can also have other components, e.g., a source of disinfecting agent, neutralizing agent, etc., and/or a transporting element, such as described with reference to disinfection system **100** depicted in FIG. **1**.

[0103] FIG. **11** depicts an example disinfection system **1700**. Disinfection system **1700** can include similar components as other disinfection systems disclosed herein (e.g., disinfection systems **100**, **200**, **700**, **800**, **900**, and/or **1600**), and additionally include or be designed for use with a transport unit **1790**. Disinfection system **1700** can be formed of one or more modular units. For example, disinfection system **1700** can include side walls **1712**, **1714** and a top wall **1716** that can be optionally formed of one or more modular units. For example, wall **1712** can optionally be formed of four modular units **1712a**, **1712b**, **1712c**, **1712d**; wall **1714** can optionally be formed of four modular units **1714a**, **1714b**, **1714c**, **1714d**; and wall **1716** can be formed of four modular units **1716a**, **1716b**, **1716c**, **1716d**. Alternatively, each of walls **1712**, **1714**, **1716** can be formed of a single modular unit, two modular units, or any other number of modular units. One or more modular units **1712a**, **1712b**, **1712c**, **1712d**, **1714a**, **1714b**, **1714c**, **1714d**, **1716a**, **1716b**, **1716c**, **1716d** can be similar to other modular units, e.g., include the same components (e.g., energy

source(s), reflective unit(s), spray unit(s), etc.).

[0104] Each modular unit can be manufactured and/or assembled at a manufacturing facility and transported to a location for onsite assembly into disinfection system **1700**. Each modular unit can be coupled to the modular units adjacent to it via suitable fastening elements (e.g., mechanical fasteners, magnets, adhesives, etc.). In some embodiments, modular units can include built-in connectors for quick coupling and assembly, e.g., snap-on connectors, magnetic connectors, etc.

[0105] As depicted in FIG. **11**, disinfection system **1700** does not include a front wall or a back wall. Rather, side walls **1712**, **1714** and top wall **1716** define an open disinfecting area **1725**.

Disinfection system **1700** can include a transport device **1790** that transport objects through the disinfecting area **1725**. For example, objects can be placed on the transport device **1790** on a first side of the disinfection system **1700** and be transported through a first opening **1792** on the first side into the disinfecting area **1725**, and out through a second opening **1794** on a second side of the disinfection system **1700**. While the object is being transported through the disinfecting area **1725**, the object can be disinfected by one or more energy source(s), reflective unit(s), and/or spray unit(s) located on the modular units of the disinfection system **1700**.

[0106] The transport device **1790** can be any suitable device for moving an object through an area. For example, the transport device **1790** can be a conveyor belt that extends along a bottom side of the disinfection unit **1790**. Alternatively or additionally, the transport device **1790** can include robotic components (e.g., robotic arms, manipulators, etc.) configured to couple to the objects (e.g., grab, magnetically couple, etc.) and move them through the disinfecting area **1725** (e.g., by lifting, pulling, etc.). In some embodiments, the transport device **1790** can be designed to re-position an object (e.g., using tracks, flippers, manipulators, etc.) prior to or during movement of the object through the disinfecting area **1725**.

[0107] Since the disinfecting area **1725** is not entirely sealed from the surrounding environment, disinfection system **1700** can be designed for use with energy sources and/or disinfecting agents that are not harmful to surrounding objects and/or persons. For example, disinfection system **1700** can include light sources that are excimer lamps that emit far UV-C light, e.g., light having a wavelength of approximately 222 nm.

[0108] FIGS. **12-16** illustrate different views of an example disinfection system **1200**. Disinfection system **1200** can be similar to other disinfection systems described herein (e.g., disinfection systems **100**, **200**, **700**, **800**, and/or **900**), and can include similar components as those systems. Disinfection system **1200** includes a plurality of walls, including side walls **1212**, **1214**, a top wall **1216**, and a back wall **1218**. Each wall **1212**, **1214**, **1216**, **1218** can be formed from two modular units. Specifically wall **1212** is formed of modular units **1212a**, **1212b**; wall **1214** is formed of modular units **1214a**, **1214b**; wall **1216** is formed of modular units **1216a**, **1216b**; and wall **1218** is formed of modular units **1218a**, **1218b**.

[0109] Disinfection system **1200** also includes two panel sections **1219a**, **1219b** that can open and close. Panel sections **1219a**, **1219b** can be two bi-folding doors. When panel sections **1219a**, **1219b** are in an open configuration, as best shown in FIGS. **12** and **16**, panel sections **1219a**, **1219b** provide an opening **1230** into a chamber **1224** defined by walls **1212**, **1214**, **1216**, **1218**. When panel sections **1219a**, **1219b** are in a closed configuration, panel sections **1219a**, **1219b** seal off opening **1230** such that energy and/or fluids (e.g., air, liquid, vapor) within chamber **1224** cannot exit chamber **1224**. Each panel section **1219a**, **1219b** can fold into its open configuration (as shown in FIGS. **12** and **16**) and unfold into its closed configuration. Panel sections **1219a**, **1219b** can be mounted to a support frame **1238**, which can be coupled to modular units **1212a**, **1212b**, **1214a**, **1214b**, **1216a**, **1216b**. When panel sections **1219a**, **1219b** are in the open configuration, opening **1230** has a length **L15** and a height **L16**, as shown in FIG. **16**. While two panel sections **1219a**, **1219b** are shown, one of ordinary skill in the art would appreciate that other suitable components for closing and opening a chamber opening can be used, such as, for example, a single door that can pivot open and close, a single bi-folding door that can fold and unfold to open and close, a pair

of doors that can pivot open and close, a retractable curtain, etc.

[0110] Each modular unit **1212a**, **1212b**, **1214a**, **1214b**, **1216a**, **1216b**, **1218a**, **1218b** can be connected to adjacent modular units via one or more connectors **1225**. Connectors **1225** can be attachable to and/or integrated into one or more modular units. For example, connectors **1225** can include snap-on components that can mate with one another to connect two modular units together. Alternatively or additionally, connectors **1225** can include fasteners, adhesives, magnets, etc. that can adhere two adjacent modular units to one another. In some embodiments, connectors **1225** can include electrical connections and/or fluid connections, which can connect to electrical connections and/or fluid connections in adjacent modular units such that a network of electrical connections and/or fluid connections can be formed to connect one or more components of modular units **1212a**, **1212b**, **1214a**, **1214b**, **1216a**, **1216b**, **1218a**, **1218b** to power source(s), fluid source(s), a control panel, a processor, and/or other centralized elements.

[0111] FIGS. **13A**, **13B**, **14A**, and **14B** provide detailed views of modular units **1212a**, **1212b** of wall **1212**. While not depicted in detail, other modular units of disinfection system **1200** (e.g., modular units **1214a**, **1214b**, **1216a**, **1216b**, **1218a**, **1218b**) can be identical to and/or similar to modular units **121a**, **1212b**. Each modular unit **1212a**, **1212b** includes two reflective units **1220** and two energy sources **1222**. Reflective units **1220** and/or energy sources **1222** can be similar to other reflective units and energy sources described herein. For example, each reflective unit **1220** can have a reflective surface that can reflect energy emitted by energy sources **1222** into chamber **1224**. As depicted in FIGS. **13A**, **13B**, **14A**, and **14B**, each reflective unit **1220** can have a hyperbolically shaped reflective surface that can be configured to distribute energy emitted by energy sources **1222** and reflect it into chamber **1224**. Each energy source **1222** can be disposed within a reflective unit **1220**. Energy sources **1222** can include at least one light tube configured to emit disinfecting light (e.g., UV light). Energy sources **1222** can be connected to electrical connectors **1226** disposed within or adjacent to each reflective unit **1220**.

[0112] In some embodiments, additional reflective units **1220** and/or energy sources **1222** can be disposed on an inner surface of a front wall (e.g., panels **1219a**, **1219b**) and a bottom side of chamber **1214**. For example, reflective material (e.g., a coating and/or flat sheet) can be placed on panels **1219a**, **1219b** and/or a floor of chamber **1224** and function as reflective units **1220**. Reflective units **1220** and energy source **1222**, when assembled around chamber **1224** and operating together, can be configured to collectively deliver a sufficient amount of light at a sufficient intensity onto the surfaces of an object within chamber **1224**, such that the object can be adequately disinfected.

[0113] Each modular unit includes at least one removable cover or panel (e.g., panels **1272**, **1274**) to allow reflective units **1220** and/or energy sources **1222** to be inspected, repaired, or replaced. For example, FIG. **13A** provides a view of modular units **1212a**, **1212b** with panels **1274** removed, and FIG. **14B** provides a view of a portion of modular unit **1212a** with panel **1272** removed. Removal of any one of panels **1272**, **1274** can expose an internal structure of the modular unit and provide access to reflective units **1220** and/or energy sources **1222**. The internal support structure can include one or more vertical support elements **1228** and/or horizontal support elements **1278**. A back portion **1226** of reflective units can be mounted to one or more support elements **1228**, **1278**. In some embodiments, additional components (e.g., energy sources, spray units, etc.) can also be mounted directly to a support element. Panels **1272**, **1274** can be configured to protect reflective units **1220** and/or energy sources **1222**, as well as other internal components of the modular units.

[0114] In some embodiments, each modular unit can be easily detached from its adjacent modular units and removed from the disinfection system **1200** for inspection, repair, and/or replacement. In some embodiments, removal of a single modular unit does not compromise the overall structure of disinfection system **1200**, such that a single modular unit can be removed while the remaining, assembled modular units remain in place, e.g., supported by one another and/or surrounding support structure (e.g., support frame **1238**). Placement of a new modular unit (or the old modular

unit after undergoing inspection and/or repair) can then be efficiently accomplished without requiring significant reassembly efforts.

[0115] FIG. 15A depicts a side view of disinfection system **1200**, and FIG. 15B depicts a top view of disinfection system **1200**. As identified in FIGS. 15A and 15B, each modular unit **1212a**, **1212b**, **1214a**, **1214b**, **1216a**, **1216b**, **1218a**, **1218b** can have a width **L8**, a length **L9**, and a thickness **L10**. Two modular units can be stacked, one on top of the other, to form each of side walls **1212**, **1214** and back wall **1218**, and two modular units placed side-by-side can form top wall **1216**. Accordingly, the length **L9** of the modular units can be equal to two times the width **L8** of the modular units.

[0116] According to some embodiments, disinfection system **1200** can be sized to receive medical equipment **1280**, such as wheelchairs, IV poles, medical carts, mobile or portable computer stations, dialysis machines, anesthesia machines, ECG machines, and/or other types of mobile medical equipment. To form a chamber **1224** and an opening **1230** that are sized to receive standard-sized wheelchairs, portable computer stations, and/or medical carts, modular units having a width **L8** of approximately 25 inches and a length **L9** of approximately 50 inches can be used. Two modular units can be stacked on each of three sides of disinfection system **1200** (i.e., walls **1212**, **1214** and back wall **1218**) and two modular units can be used for top wall **1216**, such that a 50-by-50-by-50-inch enclosure can be formed.

[0117] Alternatively, modular units having a width **L8** of approximately 25 inches and a length **L9** of approximately 50 inches can be arranged two-by-two to form two side walls, two high to form a back wall, and two-by-two to form a top wall, such that a 50-by-100-by-50-inch enclosure can be formed. Examples of medical equipment that can be received in such an enclosure can include standard-sized gurneys, wheelchairs, portable computer stations, and/or medical carts. FIG. 17 depicts an example disinfection system **1300** having such an arrangement. As depicted, each of walls **1312**, **1314** can be formed of four modular units (i.e., wall **1312** can be formed of modular units **1312a**, **1312b**, **1312c**, **1312d**, and wall **1314** can be formed of modular units **1314a**, **1314b**, **1314c**, **1314d**), back wall (not depicted) can be formed of two modular units, and a top wall **1316** can be formed of four modular units **1316a**, **1316b**, **1316c**, **1316d**. Disinfection system **1300** can be similar to disinfection system **1200**, except for the different arrangement of modular units. Accordingly, disinfection system **1300** can have panel sections **1319a**, **1319b**, a chamber **1324**, reflective units **1320**, energy sources **1322**, connectors **1325**, and a support frame **1338**, similar to those of disinfection system **1200**. As depicted, disinfection system **1300** can be sized to receive a piece of medical equipment, such as a gurney **1380**, within its chamber **1324**.

[0118] Panel sections **1319a**, **1319b** can function as a door of disinfection system **1300**. Panel sections **1319a**, **1319b** can each be bi-folding doors that fold to expose an opening to chamber **1324** and unfold to close the opening. While two panel sections or bi-folding doors are shown in FIG. 17, it can be appreciated that a single larger bi-folding door that is attached to one side of support frame **1338** can be used in the alternative.

[0119] Alternatively, modular units having a width **L8** of approximately 25 inches and a length **L9** of approximately 50 inches can be arranged three high to form three sides (i.e., two side walls and a back wall) and two long to form a top wall, such that a 50-by-50-by-75-inch enclosure can be formed. Examples of medical equipment that can be received in such an enclosure can include standard-sized wheelchairs, wheelchairs with attached IV poles, IV poles, portable computer stations, medical carts, dialysis machines, and/or anesthesia machines.

[0120] FIGS. 18-20 illustrate different views of an example disinfection system **1800**. Disinfection system **1800** can be similar to other disinfection systems described herein (e.g., disinfection systems **100**, **200**, **700**, **800**, **900**, and/or **1200**), and can include components that are structurally and/or functionally similar to the components of those systems. For example, disinfection system **1800** includes a plurality of walls **1812**, **1814**, **1816**, **1818** that define a chamber **1824**. Each wall **1812**, **1814**, **1816**, **1818** can be formed of one or more modular units.

[0121] Depending on the size requirements of walls **1812**, **1814**, **1816**, **1818**, the modular units used to form those walls can have specific dimensions and/or configurations. For example, wall **1812** can be formed of two types of modular units, e.g., a first type of modular unit **1810a** and a second type of modular unit **1810b**. Wall **1814** can be formed of the same two types of modular units. Wall **1816** can be formed of a single modular unit, e.g., the first type of modular unit **1810a**. And wall **1818** can be formed of two types of modular units, e.g., a third type of modular unit **1810c** and a fourth type of modular unit **1810d**. Altogether, walls **1812**, **1814**, **1816**, **1818** can be formed of four different types of modular units **1810a**, **1810b**, **1810c**, **1810d**. While four different types of modular units are depicted in FIG. **18**, it can be appreciated that any number of types of modular units can be used to form disinfection systems described herein.

[0122] Each of the modular units **1810a**, **1810b**, **1810c**, **1810d** can include a set of reflective units or surfaces **1820** and a set of energy sources **1822**. Reflective units **1820** and/or energy sources **1822** can be similar to other reflective units and energy sources described herein. For example, each reflective unit **1820** can have a reflective surface that can reflect energy emitted by energy sources **1822** into chamber **1824**. As depicted in FIGS. **18-21D**, each reflective unit **1820** can have a hyperbolically shaped reflective surface that can be configured to distribute energy emitted by energy sources **1822** and reflect it into chamber **1824**. Each energy source **1822** can be disposed within a reflective unit **1820**. Energy sources **1822** can include at least one light tube configured to emit disinfecting light (e.g., UV light). Energy sources **1822** can be connected to electrical connectors **1826** disposed within or adjacent to each reflective unit **1820**. While not depicted, it can be appreciated that additional reflective units and/or energy sources can be disposed on additional walls or surfaces of disinfection system **1800**.

[0123] The four types of modular units **1810a**, **1810b**, **1810c**, **1810d** can have different dimensions and/or configurations. Each modular unit **1810a**, **1810b**, **1810c**, **1810d** can be designed to couple to adjacent modular units via one or more connectors **1825**. For example, connectors **1825** can include snap-on components that can mate with one another to connect two modular units together. Alternatively or additionally, connectors **1825** can include fasteners, adhesives, magnets, etc. that can adhere two adjacent modular units to one another. In some embodiments, connectors **1825** can include electrical connections and/or fluid connections, which can connect to electrical connections and/or fluid connections in adjacent modular units such that a network of electrical connections and/or fluid connections can be formed to connect one or more components of modular units **1810a**, **1810b**, **1810c**, **1810d** to power source(s), fluid source(s), a control panel, a processor, and/or other centralized elements.

[0124] The modular units **1810a**, **1810b**, **1810c**, **1810d** are dimensioned such that they fit with one another to form a box-shaped disinfection system **1800**. For example, as shown in FIGS. **21A-21D**, modular unit **1810a** can be L20-by-L22, modular unit **1810b** can be L20-by-L20, modular unit **1810c** can be L22-by-L22, and modular unit **1810d** can be L22-by-L20, such that the modular units **1810a**, **1810b**, **1810c**, **1810d** form a chamber **1824** having a length of approximately L20, a width of approximately L22, and a height of approximately L20 and L22. In an embodiment, L20 and L22 can be less than about 50 inches. In an embodiment, L20 can be approximately 48 inches and L22 can be approximately 36 inches. In an embodiment, L20 and L22 are each multiples of a common value (e.g., 12 inches), and are at least equal to or greater than that common value and less than approximately four times that common value. In an embodiment, L20 and L22 can each be at least between approximately 12 and approximately 48 inches. In an embodiment, L20 and L22 can be equal to one another.

[0125] While disinfection system **1800** is depicted as being box-shaped (e.g., having a rectangular cross-section), it can be appreciated that other shapes and/or configurations of disinfection system **1800** can be used, e.g., for receiving different sized objections as further described herein.

[0126] When disinfection system **1800** forms a chamber **1824** having dimensions of approximately 36-by-48-by-84 inches (e.g., when L20 is approximately 48 inches and L22 is approximately 36

inches) with an opening **1830** of approximately 36-by-84 inches, disinfection system **1800** can be sized to receive medical equipment, such as, for example, wheelchairs, IV poles, medical carts, computer stations, dialysis machines, anesthesia machines, ECG machines, etc. Alternatively, different arrangements and/or types of modular units can be used to accommodate other types of medical equipment. For example, multiple 36-by-36 inch modular units (e.g., modular unit **1810c**) can be used to form a smaller enclosure that is 36-by-36-by-36 inches, which can be used to disinfect wheelchairs without IV poles, computer stations, etc. As another example, two 48-by-48 inch modular units can be arranged side-by-side to form the side and top walls of a disinfection unit such that a longer chamber of approximately 96 inches in length can be formed to receive longer equipment such as gurneys.

[0127] Disinfection system **1800** can include a bottom wall **1836**, as depicted in FIGS. **18** and **19**. Bottom wall **1836** can be formed of a single unitary piece or be formed of multiple pieces that couple together to form a generally flat bottom surface for supporting objects within chamber **1824**. The bottom wall **1836** can have a reflective surface (e.g., for further reflecting and directing light energy toward an object being disinfected) or non-reflective surface. In an embodiment, bottom wall **1836** can be a rigid and durable material, e.g., a metal such as stainless steel. The bottom wall **1836** of the disinfection system **1800** can prevent energy and/or disinfecting agent(s) being delivered within chamber **1824** from affecting (e.g., degrading, discoloring) a floor or other surface upon which the disinfection system **1800** is positioned.

[0128] Disinfection system **1800** can optionally include a front door or wall (not depicted). For example, similar to other disinfection systems described here, disinfection system **1800** can include a door that is hinged, rolling, folded (e.g., bi-folded), sliding, etc. The front door can be movable between a closed position and an open position. In the closed position, the front door can prevent energy and/or disinfection agent(s) within the chamber **1824** from exiting the chamber and affecting surrounding objects and/or persons. In the open position, the front door can enable an object to be positioned within and/or removed from the chamber **1824**.

[0129] FIG. **22** is a flow chart of a method **1400** for disinfecting using a disinfection device, such as any of the disinfection systems disclosed herein. An object or article (e.g., a piece of medical equipment) can be placed in a disinfecting area, at **1402**. Disinfecting area can be an open space adjacent to a disinfection device and/or a space within a chamber (e.g., chamber **124**, **724**, **824**, **924**, **1224**, and/or **1334**) defined by a disinfection device. Optionally, the disinfecting area can be closed or sealed, at **1403**. The disinfection device can be activated, at **1404**. For example, a user can use his badge to turn on and activate the disinfection device. Alternatively, a user located at a remote location can use a control panel to activate the disinfection device. Optionally, at **1406**, the disinfection device, e.g., via sensors (e.g., sensor(s) **164**) and/or user inputs via a control panel having a user interface (e.g., control panel **150** having I/O interface **152**), can identify the type of article, e.g., the type of medical equipment. Based on the type of article that is identified, or based on other information inputted by a user (e.g., via the control panel and/or user interface), the disinfection device can identify a disinfecting mode to use, at **1408**.

[0130] At **1410**, the disinfection device can perform the disinfecting according to the disinfecting mode. In some embodiments, the disinfection mode may involve disinfecting using energy (e.g., UV light and/or pulses of HINS light) and one or more disinfecting agents (e.g., disinfecting agent **190**). For example, a set of energy sources capable of emitting energy at an intensity capable of disinfecting a surface of the article can be energized, and at least one disinfecting agent can be delivered to the disinfecting area via a set of spray units.

[0131] One or a combination of disinfecting agents may be used: aerosolized or vaporized hydrogen peroxide, aerosolized or vaporized peracetic acid-hydrogen peroxide combination, aerosolized or vaporized electrolyzed water, aerosolized or vaporized cold atmospheric pressure plasma, or aerosolized or vaporized polymeric guanidine. Optionally, prior to and/or during the disinfection process, the disinfection device can move device components (e.g., reflective units,

power sources, spray units, exhaust units, sensors, etc.) to perform the disinfection. For example, the disinfection device can move device components to position certain components closer to the article being disinfected, e.g., to increase efficiency and/or efficacy of disinfection. Optionally, at **1412**, the disinfection device can perform neutralizing by applying a neutralizing agent (e.g., neutralizing agent **192**), to reduce residual disinfecting from degrading the surfaces of the article being disinfecting and/or to reduce the risk of harmful contact of the disinfecting agent with a human after the article is removed from the disinfecting area. Optionally, at **1414**, the disinfection device, via sensors, processors, communication channels, etc., can log and/or report disinfecting data, such as, for example, the article that was disinfected, the user initiating the disinfection, etc. [0132] FIG. **23** depicts a flow chart of a method **2000** for assembling a disinfection device, such as any of the disinfection systems disclosed herein. A plurality of modular units can be moved from a first location outside of an enclosed space (e.g., a room of a hospital) to a second location inside the enclosed space through an opening (e.g., a doorway), at **2002**. Each modular unit can be sized to fit through the opening. The modular units can be assembled into one or more walls or panels, at **2003**. Optionally, at **2004**, the modular units can be assembled into one or more walls forming a structure that defines a chamber sized to receive an object (e.g., a piece of medical equipment). In some embodiments, the modular units can first be assembled into a plurality of walls, and the plurality of walls can be arranged to form the structure that defines the chamber.

[0133] FIG. **24** depicts various components that can form an example disinfection system **1500**. The components depicted in FIG. **24** can be provided in a kit, which can be delivered to an onsite location (e.g., a room in a hospital) for assembly at the onsite location. As shown, the components can include one or more modular unit(s) **1502**. Modular unit(s) **1502** can be similar to any of the other modular units disclosed herein, and can include similar components as those modular units. The components can include a control unit **1504**, which can be used to control and operate disinfection system **1500**, once it is assembled for use. Control unit **1504** can include, for example, a processor (e.g., processor **154**) and/or a control panel (e.g., control panel **150**). The components can optionally include a power source **1506** and/or electrical component **1508** connecting other components of disinfection system **1500** to the power source **1506** (e.g., modular unit(s) **1502** and/or components included on modular unit(s) **1502**, such as energy sources, reflective units, spray units, exhaust units, sensors, etc.). Alternatively, the components provided in the kit do not include a power source, but they include suitable electrical components to connect one or more components of disinfection system **1500** to a remote power source (e.g., via a power port). Optionally, the component can also include a disinfecting agent supply **1510**, a neutralizing agent supply **1512**, and/or fluid delivery components **1514** for establishing fluid communication between disinfecting agent supply **1510** and/or neutralizing agent supply **1512** to one or more spray units disposed on modular unit(s) **1502**. Optionally, the components can also include support structure **1516**, for supporting modular unit(s) **1502** in a specific arrangement and/or coupling modular unit(s) **1502** to one another in a specific arrangement.

[0134] While various embodiments have been described and illustrated herein, those of ordinary skill in the art will readily envision a variety of other means and/or structures for performing the function and/or obtaining the results and/or one or more of the advantages described herein, and each of such variations and/or modifications is deemed to be within the scope of the embodiments described herein. More generally, those skilled in the art will readily appreciate that all parameters, dimensions, materials, and configurations described herein are meant to be exemplary and that the actual parameters, dimensions, materials, and/or configurations will depend upon the specific application or applications for which the inventive teachings is/are used. Those skilled in the art will recognize, or be able to ascertain using no more than routine experimentation, many equivalents to the specific inventive embodiments described herein. It is, therefore, to be understood that the foregoing embodiments are presented by way of example only and that, within the scope of the appended claims and equivalents thereto; embodiments may be practiced otherwise

than as specifically described and claimed. Embodiments of the present disclosure are directed to each individual feature, system, article, material, kit, and/or method described herein. In addition, any combination of two or more such features, systems, articles, materials, kits, and/or methods, if such features, systems, articles, materials, kits, and/or methods are not mutually inconsistent, is included within the inventive scope of the present disclosure.

[0135] Also, various concepts may be embodied as one or more methods, of which an example has been provided. The acts performed as part of the method may be ordered in any suitable way. Accordingly, embodiments may be constructed in which acts are performed in an order different than illustrated, which may include performing some acts simultaneously, even though shown as sequential acts in illustrative embodiments.

[0136] As used herein, the terms “about” and/or “approximately” when used in conjunction with values and/or ranges generally refer to those values and/or ranges near to a recited value and/or range. In some instances, the terms “about” and “approximately” may mean within $\pm 10\%$ of the recited value. The terms “about” and “approximately” may be used interchangeably.

Claims

1. A kit, comprising: a plurality of modular units coupleable to one another to form a plurality of walls that collectively define a chamber sized to receive an object, the plurality of walls including a top wall, a back wall, and a set of side walls, the plurality of modular units including: a first set of modular units coupleable to each other to form a first side wall from the set of side walls; a second set of modular units coupleable to each other to form a second side wall from the set of side walls; and a third set of modular units coupleable to each other to form at least one of the top wall or the back wall; and a plurality of energy sources including at least one energy source disposed on each modular unit from the plurality of modular units, a set of energy sources from the plurality of energy sources configured to provide energy having an intensity capable of disinfecting a surface of the object when the object has been received within the chamber.
2. The kit of claim 1, further comprising a plurality of reflective surfaces including at least one reflective surface disposed on each modular unit from the plurality of modular units, each reflective surface from the plurality of reflective surfaces configured to reflect energy provided by at least one energy source from the plurality of energy sources, such that the energy can be directed toward the object when the object has been received within the chamber.
3. The kit of claim 1, wherein each modular unit from the plurality of modular units has a length that is less than a maximum length of the object.
4. The kit of claim 1, wherein each modular unit from the plurality of modular units has a width ranging from approximately 10 to approximately 50 inches and a length ranging from approximately 10 to approximately 50 inches.
5. The kit of claim 1, wherein each modular unit from the plurality of modular units has a width of at least approximately 12 inches and a length of no more than approximately 48 inches.
6. The kit of claim 1, wherein each wall from the plurality of walls has a width and a length that are multiples of a common value.
7. The kit of claim 1, wherein: the first set of modular units includes four modular units coupleable to each other to form the first side wall, the second set of modular units includes four modular units coupleable to each other to form the second side wall, the third set of modular units includes four modular units coupleable to each other to form the top wall, and the plurality of modular units further including a fourth set of modular units including two modular units coupleable to each other to form the back wall.
8. The kit of claim 1, wherein the energy source includes at least one of: a mercury vapor light source, a xenon gas light source, a light emitting diode (LED), or a light emitting nanoparticle.
9. The kit of claim 1, wherein the energy source includes a light source capable of emitting

ultraviolet (UV) light having a wavelength of approximately 200 nm to approximately 280 nm.

- 10.** The kit of claim 1, further comprising: a fluid dispenser configured to dispense a disinfecting agent into the chamber; and an exhaust unit configured to vent the disinfecting agent out from the chamber.
 - 11.** The kit of claim 10, wherein the fluid dispenser is disposable on at least one modular unit from the plurality of modular units.
 - 12.** The kit of claim 10, wherein the disinfecting agent includes at least one of: hydrogen peroxide, peracetic acid, electrolyzed water, atmospheric pressure plasma, polymeric guanidine, or ozone.
 - 13.** The kit of claim 10, wherein the fluid dispenser is further configured to dispense a neutralizing agent, after dispensing the disinfecting agent, to reduce degradation caused by the disinfecting agent.
 - 14.** The kit of claim 1, wherein each modular unit from the plurality of modular units has a surface that is configured to cooperatively engage a surface of at least one other modular unit from the plurality of modular units such that a seal is formed between that modular unit and the at least one other modular unit, the seal configured to prevent energy emitted by at least one energy source from the plurality of energy sources from exiting the chamber.
 - 15.** The kit of claim 1, further comprising a power source configured to supply power to the plurality of energy sources.
 - 16.** The kit of claim 15, wherein each modular unit from the plurality of modular units includes an electrical connector configured to connect, via an electrical path, to the power source, such that the power source can supply power to the at least one energy source disposed on that modular unit.
 - 17.** The kit of claim 16, wherein the electrical connector of that modular unit is disposed on at least one of: an edge of that modular unit and is configured to couple to an electrical connector of another modular unit from the plurality of modular units; a surface of that modular unit facing an interior of the chamber; or a surface of that modular unit external to the chamber.
 - 18.** The kit of claim 1, further comprising a transport unit disposable within the chamber, the transport unit configured to move the object into the chamber to be disinfected by the set of energy sources and to move the object out of the chamber after being disinfected by the set of energy sources.
 - 19.** The kit of claim 1, further comprising at least one foldable panel section configured to function as a door into the chamber, the at least one foldable panel section transitionable between an open configuration in which the object can be received into the chamber and a closed configuration in which the chamber is sealed from a surrounding environment.
 - 20.** An apparatus, comprising: a plurality of walls collectively defining a chamber sized to receive an object, at least three walls from the plurality of walls each formed of a plurality of modular units, the plurality of walls including a top wall, a back wall, and a set of side walls, each modular unit from the plurality of modular units coupleable to at least two other modular units from the plurality of modular units; and a plurality of energy sources including at least one energy source disposed on each modular unit from the plurality of modular units, a set of energy sources from the plurality of energy sources configured to provide energy having an intensity capable of disinfecting a surface of the object when the object has been received within the chamber.
-