

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12385683
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Choi; Sangbok et al.

Refrigerator

Abstract

The present invention provides a refrigerator comprising: a cabinet having a storage chamber; a door for opening or closing the storage chamber; a case in which an inlet through which air flows from the storage chamber and an outlet through which the air is discharged to the storage chamber are formed; an evaporator provided inside the case for exchanging heat with the air to supply cool air; and a differential pressure sensor provided inside the case.

Inventors: Choi; Sangbok (Seoul, KR), Eom; Yonghwan (Seoul, KR), Park; Kyongbae (Seoul, KR), Heo; Juyeong (Seoul, KR), Han; Cholok (Seoul, KR), Kim; Sungwook (Seoul, KR), Baik; Wookyung (Seoul, KR)

Applicant: LG Electronics Inc. (Seoul, KR)

Family ID: 1000008750258

Assignee: LG Electronics Inc. (Seoul, KR)

Appl. No.: 17/360531

Filed: June 28, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20210325103 A1	Oct. 21, 2021

Foreign Application Priority Data

KR	10-2016-0011109	Jan. 29, 2016
KR	10-2016-0011110	Jan. 29, 2016
KR	10-2016-0011111	Jan. 29, 2016
KR	10-2016-0019276	Feb. 18, 2016
KR	10-2016-0096676	Jul. 29, 2016

Related U.S. Application Data

continuation parent-doc US 16072342 US 11079162 WO PCT/KR2017/000861 20170125 child-doc US 17360531

Publication Classification

Int. Cl.: **F25D21/02** (20060101); **F25B49/02** (20060101); **F25D17/08** (20060101); **F25D21/00** (20060101); **G01L27/00** (20060101)

U.S. Cl.:

CPC **F25D21/025** (20130101); **F25B49/02** (20130101); **F25D17/08** (20130101); **F25D21/006** (20130101); **G01L27/007** (20130101); F25B2700/197 (20130101); F25B2700/21175 (20130101); F25D2317/063 (20130101); F25D2317/0672 (20130101); F25D2700/121 (20130101)

Field of Classification Search

CPC: F25D (21/025); F25D (17/08); F25D (21/006); G01L (11/002); G01L (13/028); G01L (13/06)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4481828	12/1983	Cheng	N/A	N/A
5842355	12/1997	Kalis et al.	N/A	N/A
2005/0279122	12/2004	Cohen et al.	N/A	N/A
2007/0256506	12/2006	Sette	N/A	N/A
2010/0000238	12/2009	Taras	62/428	G01K 15/00
2013/0042638	12/2012	Eom	62/151	F25D 21/02
2013/0081416	12/2012	Kim	62/151	F25D 21/006
2016/0091379	12/2015	Broden	73/718	G01L 19/0084
2017/0276563	12/2016	Shinohara	N/A	G01L 7/02

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2515614	12/2001	CN	N/A
1798947	12/2005	CN	N/A
1896652	12/2006	CN	N/A
103401151	12/2012	CN	N/A
104180553	12/2013	CN	N/A
H10253410	12/1997	JP	N/A
2010023581	12/2009	JP	N/A
0120536	12/1991	KR	N/A
1019920021110	12/1991	KR	N/A
940011916	12/1993	KR	N/A
100120536	12/1996	KR	N/A

100238060	12/1999	KR	N/A
1020040094875	12/2003	KR	N/A
100652775	12/2005	KR	N/A
100652775	12/2005	KR	N/A
1020100058813	12/2009	KR	N/A
101414138	12/2013	KR	N/A
101463041	12/2013	KR	N/A
20150051501	12/2014	KR	N/A
101536284	12/2014	KR	N/A

OTHER PUBLICATIONS

KR100652775B1 Translation (Year: 2006). cited by examiner

KR101536284B1 Translation (Year: 2015). cited by examiner

KR0120536B1 Translation (Year: 1992). cited by examiner

Office Action in Chinese Appln. No. 202110672347.0, dated May 24, 2022, 15 pages (with English translation). cited by applicant

CN Office Action in Chinese Appln. No. 201780019994.3, dated Apr. 8, 2020, 13 pages (with English translation). cited by applicant

KR Notice of Allowance in Korean Appln. No. 10-2018-7024802, dated Mar. 8, 2021, 7 pages (with English translation). cited by applicant

KR Office Action in Korean Application No. 10-2018-7024802, dated Dec. 21, 2020, 15 pages (with English translation). cited by applicant

Primary Examiner: Sanks; Schyler S

Attorney, Agent or Firm: Fish & Richardson P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 16/072,342, filed on Jul. 24, 2018, which is a National Stage application under 35 U.S.C. § 371 of International Application No. PCT/KR2017/000861, filed on Jan. 25, 2017, which claims the benefit of Korean Application No. 10-2016-0096676, filed on Jul. 29, 2016, Korean Application No. 10-2016-0019276, filed on Feb. 18, 2016, Korean Application No. 10-2016-0011111, filed on Jan. 29, 2016, Korean Application No. 10-2016-0011110, filed on Jan. 29, 2016, and Korean Application No. 10-2016-0011109, filed on Jan. 29, 2016. The disclosures of the prior applications are incorporated by reference in their entirety.

TECHNICAL FIELD

(1) The present invention relates to a refrigerator, and more particularly to a refrigerator having improved energy efficiency.

(2) In addition, the present invention relates to a differential pressure sensor and a refrigerator including the same, and more particularly to a differential pressure sensor capable of using a differential pressure and a refrigerator including the same.

BACKGROUND

(3) In general, a refrigerator includes a machinery compartment, which is located at the lower part of a main body of the refrigerator. The refrigerator is generally installed at the lower part of the refrigerator in consideration of the center of gravity of the refrigerator and in order to improve assembly efficiency and to achieve vibration reduction.

(4) A refrigeration cycle device is installed in the machinery compartment of the refrigerator in order to keep the interior of the refrigerator frozen/refrigerated using the property of a refrigerant, which absorbs external heat when a low-pressure liquid refrigerant is changed to a gaseous refrigerant, whereby food is kept fresh.

(5) The refrigeration cycle device of the refrigerator includes a compressor for changing a low-temperature, low-pressure gaseous refrigerant to a high-temperature, high-pressure gaseous refrigerant, a condenser for changing the high-temperature, high-pressure gaseous refrigerant, changed by the compressor, to a low-temperature, low-pressure liquid refrigerant, and an evaporator for changing the low-temperature, high-pressure liquid refrigerant, changed by the condenser, to a gaseous refrigerant in order to absorb external heat.

(6) When the compressor is driven, the temperature of the evaporator is lowered, whereby ice may be formed on the evaporator. In the case in which the amount of ice formed on the evaporator increases, the efficiency of heat exchange between the evaporator and air is lowered, whereby it is difficult to smoothly cool air to be supplied to a storage compartment. As a result, it is necessary to drive the compressor a larger number of times and for a larger amount of time.

(7) In addition, when ice is formed on the evaporator, a heater is driven in order to remove the ice from the evaporator. In the case in which the heater is unnecessarily frequently driven, the amount of power consumed by the refrigerator increases.

(8) In particular, power consumption of refrigerators produced in recent years has increased as the result of an increase in the storage capacity of the refrigerators. Research has thus been conducted into the reduction of power consumption.

SUMMARY

(9) One object of the present invention devised to solve the problem lies in a refrigerator having improved energy efficiency.

(10) Another object of the present invention devised to solve the problem lies in a refrigerator capable of determining whether the operation of the refrigerator is performed normally.

(11) Another object of the present invention devised to solve the problem lies in a refrigerator capable of determining a defrosting time using a sensor.

(12) Another object of the present invention devised to solve the problem lies in a refrigerator capable of determining whether a defrosting operation is performed normally using a sensor.

(13) Another object of the present invention devised to solve the problem lies in a refrigerator capable of determining whether a sensor has broken down using a sensor.

(14) Another object of the present invention devised to solve the problem lies in a refrigerator capable of preventing a differential pressure sensor from breaking down due to dew formed thereon.

(15) Another object of the present invention devised to solve the problem lies in a refrigerator capable of improving the accuracy of measurement when a differential pressure sensor is used.

(16) Another object of the present invention devised to solve the problem lies in a differential pressure sensor assembly capable of sensing whether frost is formed on an evaporator using a differential pressure sensor and a refrigerator including the same.

(17) A further object of the present invention devised to solve the problem lies in a differential pressure sensor assembly capable of stably installing a differential pressure sensor and a refrigerator including the same.

(18) The objects of the present invention can be achieved by providing a refrigerator including a cabinet having a storage compartment defined therein, a door for opening and closing the storage compartment, a case having therein an inlet, through which air is introduced from the storage compartment, and an outlet, through which air is discharged to the storage compartment, an evaporator provided in the case for exchanging heat with air to supply cool air, and a differential pressure sensor provided in the case, wherein the differential pressure sensor includes a first pipe having therein a first through-hole disposed between the evaporator and the inlet, a second pipe

having therein a second through-hole disposed between the evaporator and the outlet, and a connection member for interconnecting the first pipe and the second pipe, and wherein the differential pressure sensor senses a difference in pressure between the first through-hole and the second through-hole.

(19) The outlet may be disposed higher than the evaporator, and the inlet may be disposed lower than the evaporator.

(20) The connection member may include an electronic circuit for sensing the difference in pressure.

(21) The connection member may be disposed higher than the evaporator.

(22) The first pipe and the second pipe may extend above the evaporator.

(23) The first pipe or the second pipe may be formed to have a hollow shape, and the hollow shape may have a circular section.

(24) The refrigerator may further include a fan provided in the case for generating the flow of air that is introduced through the inlet and discharged through the outlet, wherein the connection member may be disposed higher than the fan.

(25) The first through-hole and the second through-hole may be disposed so as to face downwards.

(26) The first pipe or the second pipe may be provided with a plurality of communication holes, and the communication holes may be disposed so as to be perpendicular to the first through-hole or the second through-hole.

(27) The first pipe or the second pipe may be provided at one end thereof with a first expanded pipe part, the diameter of which gradually increases toward the end thereof.

(28) The first through-hole or the second through-hole may be provided in the lower part of the first expanded pipe part, and may be formed in the side surface of the first pipe or the second pipe.

(29) The first expanded pipe part may be provided at the lower part thereof with a second expanded pipe part, the diameter of which gradually increases toward the end thereof.

(30) A hole, through which air is guided so as to move upwards, may not be formed in the lower part of the second expanded pipe part.

(31) The lower end of the second expanded pipe part may extend so as to have a larger sectional area than the lower end of the first expanded pipe part.

(32) The section of the portion of the first pipe or the second pipe that is coupled to the connection member may be smaller than the section of the portion of the first pipe or the second pipe in which the first through-hole or the second through-hole is formed.

(33) The refrigerator may further include a heater provided in the case and a controller for performing control to drive the heater based on information sensed by the differential pressure sensor in order to defrost the evaporator.

(34) The refrigerator may further include a door switch for sensing whether the door opens and closes the storage compartment, wherein the controller may perform control such that the differential pressure sensor senses the difference in pressure when the door switch senses that the door to the storage compartment is closed.

(35) The refrigerator may further include a fan for generating the flow of air that is introduced through the inlet and discharged through the outlet, wherein the controller may perform control such that the differential pressure sensor senses the difference in pressure when the fan is driven.

(36) The refrigerator may further include an evaporator temperature sensor for measuring the temperature of the evaporator, wherein the controller may perform control to stop driving the heater in the case in which the temperature of the evaporator increases to a set temperature when defrosting is performed.

(37) According to the present invention, information necessary for a refrigerator is acquired using a single sensor. Consequently, it is possible to reduce measurement errors compared to the case in which two or more sensors are used. If two values are compared using two sensors, different effects may occur due to temperature or warm current at positions at which the sensors are installed or due

to opening and closing of a door, whereby different errors may occur at the two sensors. When the values acquired using the two sensors are compared, therefore, error may be increased compared to the case in which a single sensor is used.

(38) In addition, according to the present invention, it is possible to reduce power consumption and the amount of required resources, such as electrical wires, for installing two sensors compared to the case in which the two pressure sensors are used.

(39) In addition, according to the present invention, measurement is periodically performed using a sensor, whereby it is possible to reduce energy consumption.

(40) In addition, according to the present invention, the finishing of defrosting is determined based on information measured by an evaporator temperature sensor, whereby it is possible to secure reliability in determining the finishing of defrosting. Furthermore, according to the present invention, defrosting is finished based on the temperature sensed by the evaporator temperature sensor, whereby it is possible to reduce the number of times that a heater is driven to defrost an evaporator and thus to reduce actual power consumption.

(41) According to the present invention, it is possible to determine whether defrosting has failed, whereby it is possible to prevent the power consumption of the refrigerator from increasing.

(42) In addition, according to the present invention, it is possible to sense clogging of a differential pressure sensor, whereby it is possible to prevent poor defrosting due to the breakdown of the differential pressure sensor.

(43) In addition, according to the present invention, it is possible to determine the breakdown of the differential pressure sensor using the differential pressure sensor without using any additional sensor, whereby it is not necessary to provide an additional sensor.

(44) In addition, according to the present invention, the possibility of dew being formed on the differential pressure sensor is reduced, whereby it is possible to reduce an error in the values measured by the differential pressure sensor.

(45) According to the present invention, frost formed on the evaporator is sensed using the differential pressure sensor, which measures a difference in pressure, whereby it is possible to improve accuracy in determining whether frost is formed on the evaporator.

(46) In addition, according to the present invention, it is possible to easily install the differential pressure sensor.

(47) In addition, according to the present invention, the structure in which the differential pressure sensor is installed is reduced, whereby it is possible to reduce the amount of frost formed in a housing, in which the differential pressure sensor is accommodated, due to cool air that has passed through the evaporator. Furthermore, the resistance applied to the differential pressure sensor is reduced when cool air is supplied, whereby it is possible to smoothly supply cool air to a storage compartment.

(48) In addition, according to the present invention, the structure of the housing is simplified and the size of the housing is reduced, whereby it is possible to reduce the cost of manufacturing the housing.

(49) In addition, according to the present invention, it is possible to reduce the amount of a molding solution that is used to fill a space defined in the housing, since the size of the housing is reduced.

(50) In addition, according to the present invention, air introduced through a communication pipe moves to the differential pressure sensor while only a small amount of resistance is applied to the air, whereby it is possible to improve measurement accuracy.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a side cut-away view showing a refrigerator according to an embodiment of the

present invention;

(2) FIG. 2 is a view illustrating a principal part of FIG. 1;

(3) FIG. 3 is a plan view of FIG. 2;

(4) FIG. 4 is a side cut-away view showing a refrigerator according to another embodiment of the present invention;

(5) FIG. 5 is a control block diagram according to the present invention;

(6) FIG. 6 is a control flowchart for sensing frost formed on an evaporator according to an embodiment;

(7) FIG. 7 is a control flowchart for sensing frost formed on the evaporator according to a modified embodiment;

(8) FIG. 8 is a control flowchart for sensing whether defrosting failed according to an embodiment;

(9) FIG. 9 is a control flowchart for sensing whether defrosting failed according to a modified embodiment;

(10) FIG. 10 is a control flowchart for sensing the breakdown of a differential pressure sensor according to an embodiment;

(11) FIG. 11 is a control flowchart for sensing the breakdown of the differential pressure sensor according to a modified embodiment;

(12) FIG. 12 is a view illustrating an embodiment of a modified differential pressure sensor;

(13) FIGS. 13 to 16 are views illustrating embodiments of another modified differential pressure sensor;

(14) FIG. 17 is a side cut-away view showing a refrigerator according to an embodiment of the present invention;

(15) FIG. 18 is a view illustrating a principal part of FIG. 17;

(16) FIG. 19 is a plan view of FIG. 18;

(17) FIG. 20 is a view showing a differential pressure sensor assembly according to an embodiment of the present invention;

(18) FIGS. 21A to 21C are views showing a differential pressure sensor according to an embodiment;

(19) FIG. 22 is a perspective view of a housing;

(20) FIG. 23 is a side view of the housing;

(21) FIG. 24 is a front view of the housing;

(22) FIGS. 25 to 27 are sectional views of the housing;

(23) FIG. 28 is a view showing a differential pressure sensor assembly according to another embodiment of the present invention;

(24) FIG. 29 is a view showing a differential pressure sensor assembly according to a further embodiment of the present invention;

(25) FIGS. 30A to 30C are views showing a differential pressure sensor according to a further embodiment;

(26) FIG. 31 is a perspective view of a housing shown in FIG. 29;

(27) FIG. 32 is a side view of the housing shown in FIG. 29;

(28) FIG. 33 is a front view of the housing shown in FIG. 29; and

(29) FIGS. 34 to 36 are sectional views of the housing shown in FIG. 29.

DETAILED DESCRIPTION

(30) Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

(31) In the drawings, sizes and shapes of elements may be exaggerated for convenience and clarity of description. In addition, terms specially defined in consideration of the construction and operation of the present invention may vary depending upon the intentions of users or operators or usual practices. The definition of such terms must be made based on the disclosure of the present invention.

(32) A sensor applied to the present invention may include a flow sensor or a differential pressure sensor.

(33) In an embodiment of the present invention, a single differential pressure sensor is used, which is technically distinguished from the case in which two pressure sensors are used. In the case in which two pressure sensors are used, a difference in pressure between two positions may be calculated using a difference in pressure measured by the two pressure sensors.

(34) In general, a pressure sensor measures pressure in increments of 100 Pa. Since a differential pressure sensor is used in an embodiment of the present invention, it is possible to more accurately measure a difference in pressure than in the case in which a general pressure sensor is used. The differential pressure sensor cannot measure an absolute pressure value at a position at which measurement is performed but can calculate a difference in pressure between two positions. Consequently, it is possible for the differential pressure sensor to easily measure a difference in pressure in smaller increments than pressure sensors.

(35) In addition, in the case in which two pressure sensors are used, increased costs, related to the use of two sensors, are incurred, and a large amount of resources, such as electrical wires, for installing the two sensors are needed. In contrast, in the case in which a single differential pressure sensor is used, costs and resources necessary to install the sensor may be reduced.

(36) A differential pressure sensor is installed in a space in which air that has passed through a storage compartment is cooled by an evaporator. Air supplied from the storage compartment contains a large amount of water due to food stored in the storage compartment. When heat exchange is performed between the air and the evaporator, therefore, a large number of water drops may be generated as the result of cooling the air. That is, the differential pressure sensor is installed in a high-humidity space.

(37) In addition, when a refrigerant is evaporated by the evaporator, the temperature around the evaporator is very low. In contrast, when the refrigerant is not evaporated by the evaporator, the temperature around the evaporator is similar to the temperature in the storage compartment. The space in which the evaporator is installed has high temperature variation depending on the condition in which the evaporator is used.

(38) Since the space in which the evaporator is installed has high temperature variation and high humidity, various errors may be generated, and it may be difficult to accurately measure information using general sensors. Since a differential pressure sensor is used in an embodiment of the present invention, however, it is possible to more accurately sense information even under adverse conditions than in the case in which other kinds of sensors are used.

(39) Hereinafter, an exemplary embodiment of the present invention capable of concretely accomplishing the above objects will be described with reference to the accompanying drawings.

(40) FIG. 1 is a side cut-away view showing a refrigerator according to an embodiment of the present invention, FIG. 2 is a view illustrating a principal part of FIG. 1, and FIG. 3 is a plan view of FIG. 2. An evaporator is omitted from FIG. 2 for simplicity.

(41) Hereinafter, a description will be given with reference to FIGS. 1 to 3.

(42) The refrigerator includes a cabinet 2, having a plurality of storage compartments 6 and 8 defined therein, and doors 4 for opening and closing the storage compartments 6 and 8.

(43) The storage compartments 6 and 8 include a first storage compartment 6 and a second storage compartment 8. The first storage compartment 6 and the second storage compartment 8 may constitute a refrigerating compartment and a freezing compartment, respectively.

(44) Alternatively, the first storage compartment 6 and the second storage compartment 8 may constitute a freezing compartment and a refrigerating compartment, respectively. In yet another alternative, both the first storage compartment 6 and the second storage compartment 8 may constitute refrigerating compartments or freezing compartments.

(45) In the storage compartments 6 and 8 is provided a storage compartment temperature sensor 90 for measuring the temperature in the storage compartments 6 and 8. Alternatively, the temperature

sensor **90** may be installed in each of the storage compartments **6** and **8** to individually measure the temperature in each storage compartment.

(46) At the rear of the storage compartments is provided a case **35** for accommodating an evaporator **20**.

(47) The case **35** is provided with an outlet **38**, through which air is supplied from the case **35** to the storage compartments, and with an inlet **32**, through which air is supplied from the storage compartments into the case **35**.

(48) In the inlet **32** is provided an introduction pipe **30** for guiding air into the case **35**. As a result, the storage compartments **6** and **8** may be connected to the case **35** in order to define an airflow path.

(49) In the outlet **38** is provided a fan **40**, which may enable air to flow from the case **35** to the storage compartments **6** and **8**. The case **35** has a hermetically sealed structure, excluding the inlet **32** and the outlet **38**. When the fan **40** is driven, therefore, air flows from the inlet **32** to the outlet **38**.

(50) The air having passed through the fan **40**, i.e. cool air, may be supplied to the first storage compartment **6** through a duct **7** for guiding air to the first storage compartment **6**. The air having passed through the fan **40** may also be supplied to the second storage compartment **8**.

(51) In the case **35** is accommodated the evaporator **20**, which evaporates a refrigerant compressed by a compressor **60** in order to generate cool air. The air in the case **35** is cooled as the result of heat exchange with the evaporator **20**.

(52) Under the evaporator **20** is provided a heater for generating heat to defrost the evaporator **20**. It is not necessary to install the heater **50** under the evaporator **20**. It is sufficient to provide the heater in the case **35** in order to heat the evaporator **20**.

(53) An evaporator temperature sensor **92** may be provided at the evaporator **20** to measure the temperature of the evaporator **20**. When the refrigerant, passing through the evaporator **20**, is evaporated, the evaporator temperature sensor **92** may sense a low temperature. When the heater **50** is driven, the evaporator temperature sensor **92** may sense a high temperature.

(54) The compressor **60** may be installed in a machinery compartment, which is provided in the cabinet **2**, to compress the refrigerant that is supplied to the evaporator **20**. The compressor **60** is installed outside the case **35**.

(55) The inlet **32** is located under the evaporator **20**, and the outlet **38** is located above the evaporator **20**. The outlet **38** is located higher than the evaporator **20**, and the inlet **32** is located lower than the evaporator **20**.

(56) When the fan **40** is driven, therefore, air moves upwards in the case **35**. The air, introduced into the inlet **32**, undergoes heat exchange while passing through the evaporator **20**, and is discharged out of the case **35** through the outlet **38**.

(57) A sensor **100** is provided in the case **36**. In an embodiment, the sensor **100** includes a differential pressure sensor.

(58) The differential pressure sensor **100** includes a first through-hole **110**, disposed between the evaporator **20** and the inlet **32**, and a second through-hole **120**, disposed between the evaporator **20** and the outlet **38**.

(59) The differential pressure sensor **100** includes a main body for interconnecting the first through-hole **110** and the second through-hole **120**. The main body includes a first pipe **150**, having the first through-hole **110** formed therein, a second pipe **170**, having the second through-hole **120** formed therein, and a connection member **200** for interconnecting the first pipe **150** and the second pipe **170**.

(60) The connection member **200** may be disposed higher than the evaporator **20** in order to prevent moisture condensed on the evaporator **20** from falling to the connection member **200**. An electronic device may be installed at the connection member **200**. If water drops fall to the connection member, the electronic device may be damaged. The water drops, formed on the

evaporator **20**, fall due to gravity. In the case in which the connection member **200** is disposed above the evaporator **20**, the water drops formed on the evaporator **20** do not fall to the connection member **200**.

(61) Meanwhile, the first pipe **150** and the second pipe **170** may extend higher than the evaporator **20**. In order to locate the connection member **200** above the evaporator **20**, it is necessary for the first pipe **150** and the second pipe **170** to extend higher than the evaporator **20**.

(62) The first through-hole **110** and the second through-hole **120** may be disposed so as to face downwards, whereby it is possible to prevent the water drops condensed in the case **35** from being introduced into the first pipe **150** and the second pipe **170** through the first through-hole **110** and the second through-hole **120**, respectively. If the first through-hole **110** and the second through-hole **120** are disposed so as to face upwards, water drops falling due to gravity may be introduced into the first pipe **150** and the second pipe **170** through the first through-hole **110** and the second through-hole **120**, respectively, whereby the value measured by the differential pressure sensor **100** may be erroneous.

(63) The differential pressure sensor **100** senses a difference in pressure between the air passing through the first through-hole **110** and the air passing the second through-hole **120**. Since the first through-hole **110** and the second through-hole **120** are installed at different heights and the evaporator **20** is disposed therebetween, a difference in pressure occurs. A relatively low pressure is applied to the second through-hole **120**, which is a low-pressure part, and a relatively high pressure is applied to the first through-hole **110**, which is a high-pressure part. Consequently, the differential pressure sensor **100** senses a difference in pressure.

(64) Since air flows in the case **35** particularly when the fan **40** is driven, the differential pressure sensor **100** may measure a difference in pressure.

(65) FIG. **4** is a side cut-away view showing a refrigerator according to another embodiment of the present invention.

(66) In this embodiment, the sensor includes a flow sensor. This embodiment is different from the previous embodiment in that the flow sensor is used instead of the differential pressure sensor. Therefore, a duplicate description of the same elements will be omitted, and only different elements will be described.

(67) Referring to FIG. **4**, the flow sensor may measure the flow rate of moving air, and therefore the two through-holes may not be disposed at different heights, unlike the differential pressure sensor.

(68) As shown in FIG. **4**, the flow sensor **100** may be provided in the inlet **32** to measure the flow rate of air that is introduced into the case **35**.

(69) Alternatively, the flow sensor **100** may be provided in the outlet **38** to measure the flow rate of air that is discharged from the case **35** to the outside.

(70) Since the amount of air that is introduced through the inlet **32** or discharged through the outlet **38** is increased particularly when the fan **40** is driven, the flow sensor may measure the flow rate of moving air.

(71) FIG. **5** is a control block diagram according to the present invention.

(72) Referring to FIG. **5**, the refrigerator according to the present invention includes a compressor **60** for compressing a refrigerant. When it is necessary to cool storage compartments, a controller **96** may perform control to drive the compressor **60** in order to supply cool air to the storage compartments. Information about whether the compressor **60** is driven may be transmitted to the controller **96**.

(73) In addition, the refrigerator includes a fan **40** for generating an air flow to supply cool air to the storage compartments. Information about whether the fan **40** is driven may be transmitted to the controller **96**, and the controller **96** may transmit a signal for driving the fan **40**.

(74) A door switch **70** for acquiring information about whether doors **4**, for opening and closing the storage compartments, open and close the storage compartments is provided. Door switches **70**

may be individually provided at the respective doors to sense whether the doors open and close the respective storage compartments.

(75) In addition, a timer **80** for sensing an elapsed time is provided. The time measured by the timer **80** is transmitted to the controller **96**. For example, the controller **96** may receive a signal indicating that the doors **4** to the storage compartments are closed from the door switch **70**, and may then receive information about the elapsed time after the doors **4** to the storage compartments are closed based on the time measured by the timer **80**.

(76) Information about the temperature in the storage compartments, measured by a storage compartment temperature sensor **90** for measuring the temperature in the storage compartments, may be transmitted to the controller **96**.

(77) When defrosting is performed, information about the temperature of the evaporator, measured by an evaporator temperature sensor **92** for measuring the temperature of the evaporator, may also be transmitted to the controller **96**. The controller **96** may perform control to finish defrosting of the evaporator according to the information about the temperature of the evaporator, measured by the evaporator temperature sensor **92**.

(78) In addition, a heater **50** for heating the evaporator may be provided, and the controller **96** may issue a command to drive the heater **50**. When defrosting is started, the controller **96** may perform control to drive the heater **50**. When defrosting is finished, the controller **96** may perform control to finish driving of the heater **50**.

(79) In the present invention, information measured by the sensor **100** is transmitted to the controller **96**. The sensor may include a flow sensor or a differential pressure sensor. In the case in which the sensor is a flow sensor, information about the flow rate of air measured by the flow sensor is transmitted to the controller **96**. In the case in which the sensor is a differential pressure sensor, information about a difference in pressure measured by the differential pressure sensor is transmitted to the controller **96**.

(80) The controller **96** may acquire a defrosting time of the evaporator or information as to whether defrosting is performed normally and whether the sensor has broken down using information about the sensor **100**.

(81) In another embodiment of the present invention, in which the sensor **100** includes a flow sensor, defrosting may be determined as follows. In the case in which the amount of moving air, measured by the flow sensor **100**, is reduced to a set value or less when the fan **40** is driven, the controller **96** may perform control to drive the heater **50**.

(82) In the state in which no ice is formed on the evaporator **20**, air flow generated by the fan **40** when the fan **40** is driven is not greatly impeded. When ice is formed on the evaporator **20**, however, air resistance in the case **35** increases. Even when the fan **40** is driven at the same rpm, therefore, a relatively small amount of air flows.

(83) In another embodiment of the present invention, therefore, it is possible to determine whether it is necessary to defrost the evaporator **20** based on information about the flow rate measured by the flow sensor **100** when the fan **40** is driven.

(84) That is, in the case in which the flow rate measured by the flow sensor **100** is reduced to a set value, the heater **50** is driven to melt or remove ice formed on the evaporator **20**. Here, the set value is the flow rate value that is necessary for defrosting based on the amount of frost formed on the evaporator **20**, which may be stored by manufactures who manufacture refrigerators.

(85) The process of determining whether defrosting failed in another embodiment of the present invention will be described.

(86) In the case in which the sensor includes the flow sensor **100**, the flow rate measured by the flow sensor **110** after defrosting is performed may be smaller than a normal flow rate. A considerably large amount of ice may be formed on the evaporator **20**, whereby direct heat exchange between the evaporator **20** and air may not be smoothly performed.

(87) In this case, the flow of air passing through the evaporator **20** is not smooth. As a result, the

amount of air that passes through the flow sensor **100** may be reduced. That is, when an amount of air that is smaller than the amount of air that passes through the flow sensor **100** is measured in the state in which the evaporator **20** is sufficiently defrosted, the set value of the flow rate of air that starts to defrost the evaporator **20** may be reduced when subsequent defrosting is performed.

(88) That is, even in the case in which a smaller amount of ice is formed on the evaporator **20** than when previous defrosting was performed, the heater **50** may be driven in order to defrost the evaporator **20**. In another embodiment, whether the evaporator **20** was sufficiently defrosted is determined by the flow rate of air after previous defrosting was performed. In the case in which the flow rate of air does not reach a normal range even after defrosting is performed, the set value of the flow rate of air at the time of performing defrosting may be reduced when subsequent defrosting is performed such that defrosting can be performed earlier than before. Consequently, the evaporator **20** may be smoothly defrosted.

(89) In addition, in the case in which the set value of the flow rate of air is reduced, the set value of the temperature of the evaporator **20** to finish defrosting of the evaporator **20** may also be changed. That is, the evaporator **20** may be heated to a higher temperature than when previous defrosting was performed such that the evaporator **20** can be defrosted for a longer time. The time for which the heater **50** is driven may be increased in order to supply a larger amount of heat to the evaporator and to reduce the amount of ice formed on the evaporator **20**.

(90) FIG. **6** is a control flowchart for sensing frost formed on the evaporator according to an embodiment.

(91) Referring to FIG. **6**, in an embodiment of the present invention, a step (S**40**) of sensing a difference in pressure between the first through-hole **110**, disposed between the inlet **32**, through which air is introduced from the storage compartments **6** and **8**, and the evaporator **20**, and the second through-hole **120**, disposed between the outlet **38**, through which air is discharged to the storage compartments **6** and **8**, and the evaporator **20** using a single differential pressure sensor **100** and a step of driving the heater **50** to defrost the evaporator **20** when the difference in pressure is greater than a set pressure are included.

(92) Meanwhile, the term “difference in pressure” used in this specification may be the value of difference in pressure that is measured once or the average of the values of difference in pressure that are measured several times. The pressure measured by the differential pressure sensor **100** may be temporarily abnormal due to various external factors. In the case in which the average value of difference in pressure is used, reliability to the difference in pressure measured by the differential pressure sensor **100** may be improved.

(93) In the case in which the value of difference in pressure measured by the differential pressure sensor **100** is greater than the set pressure, this means that the difference in pressure between the first through-hole **110** and the second through-hole **120** increases. An increase in the difference in pressure may mean that the amount of ice formed on the evaporator **20** is increased and thus it is difficult for the evaporator **20** to smoothly perform heat exchange. As a result, cool air is not smoothly supplied from the evaporator **20** to the storage compartments **6** and **8**. Consequently, it may be necessary to defrost the evaporator.

(94) In addition, whether the fan **40** is being driven may be determined before the difference in pressure is sensed (S**20**).

(95) Air flow is generated between the first through-hole **110** and the second through-hole **120**, and a difference in pressure therebetween may be smoothly measured by the differential pressure sensor **100**, only when the fan **40** is driven.

(96) In the state in which the fan **40** is not driven, therefore, the differential pressure sensor **100** may not measure a difference in pressure.

(97) The storage compartments **6** and **8** are closed by the doors **4**, and the door switch **70** determines whether a predetermined amount of time has elapsed, and if not, the differential pressure sensor **100** may not measure a difference in pressure (S**30**). The door switch **70** may

determine whether the doors **4** are in a closed state before the elapsed time is measured by the timer **80**. Here, the elapsed time may be about 1 minute. However, the elapsed time may be changed variously.

(98) Air flow in the case **35** in the state in which the storage compartments **6** and **8** are not closed by the doors **4** may be different from air flow in the state in which the case **35** is closed.

(99) In addition, in the state in which the doors **4** are closed and the predetermined amount of time has not elapsed, unexpected air flow to the inlet **32** or to the outlet **38** may be generated as the result of closing the doors **4**.

(100) When the differential pressure sensor **100** measures a difference in pressure in this state, therefore, the measured difference in pressure may not properly reflect the pressure in the case **35**. In the case in which a defrosting time of the evaporator **20** is determined using such incorrect information, the heater **50** may be unnecessarily frequently driven, or the heater **50** may not be driven at a necessary time, whereby the evaporator **20** cannot be defrosted.

(101) Subsequently, a difference in pressure between the first through-hole **110** and the second through-hole **120** is measured by the differential pressure sensor **100** (**S40**). Information about the measured difference in pressure may be transmitted to the controller **96**.

(102) The controller **96** compares the measured difference in pressure, i.e. the differential pressure, with a set pressure **P1** (**S50**). When the differential pressure is higher than the set pressure **P1**, it may be determined that a large amount of ice is formed on the evaporator **20**, whereby it is necessary to defrost the evaporator. In the case in which a large amount of ice is formed on the evaporator **20**, it is difficult for the evaporator **20** to sufficiently perform heat exchange, whereby it is difficult to supply a sufficient amount of cool air to the storage compartments **6** and **8**. The set pressure **P1** may be set to about 20 Pa. However, the set pressure may be changed in consideration of the capacity, size, and the like of the refrigerator.

(103) The controller **96** performs control to drive the heater **50** such that heat is supplied to the evaporator **20** in order to defrost the evaporator (**S60**). The evaporator **20** is disposed in the same space partitioned in the case **35** as the space in which the heater **50** is disposed. When the heater **50** is driven, therefore, the temperature in the case **35** may be increased, whereby the temperature of the evaporator **20** may be increased.

(104) As a result, some of the ice formed on the evaporator may melt and change into water, some of which may fall from the evaporator **20**. Consequently, the area of the evaporator **20** that can directly exchange heat with air may be increased, thereby improving the heat-exchange efficiency of the evaporator **20**.

(105) While defrosting is performed, i.e. while the heater **50** is driven, the evaporator temperature sensor **92** measures the temperature of the evaporator **20**. When the temperature of the evaporator **20** exceeds a set temperature **T1**, it is determined that the evaporator **20** was sufficiently defrosted (**S70**).

(106) That is, the controller **96** may perform control to stop driving the heater **50**. That the temperature of the evaporator **20** exceeds the set temperature **T1** may not mean that all of the ice formed on the evaporator **20** is removed, but may mean that the evaporator **20** is ready to supply cool air to the storage compartments **6** and **8**.

(107) If the temperature of the evaporator **20** does not increase to the set temperature **T1**, it may be determined that the evaporator **20** was not sufficiently defrosted, and the heater **50** may continue to be driven to supply heat to the evaporator.

(108) In an embodiment, the defrosting time of the evaporator **20** is determined based on the differential pressure measured by the differential pressure sensor **100**. In order to improve the reliability of the differential pressure measured by the differential pressure sensor **100**, the condition in which air flow in the case **35** is stabilized may be added.

(109) In the case in which the evaporator **20** is unnecessarily frequently defrosted, the heater **50** is frequently driven. As a result, the amount of power consumed by the heater **50** is increased,

whereby the overall energy efficiency of the refrigerator is reduced.

(110) In addition, when hot air supplied from the heater **50** is introduced into the storage compartments **6** and **8** through the inlet or the outlet, the food stored in the storage compartments may rot. In addition, a larger amount of cool air may need to be supplied to the evaporator **20** in order to cool the air that is heated by the hot air supplied from the heater **50**.

(111) Therefore, an embodiment may provide a refrigerator capable of reliability determining a defrosting time to reduce unnecessary power consumption, whereby the overall energy efficiency thereof is improved, and a method of controlling the same.

(112) FIG. **7** is a control flowchart for sensing frost formed on the evaporator according to a modified embodiment.

(113) Referring to FIG. **7**, it is determined whether a sensing period using the differential pressure sensor **100** is satisfied (S**10**) before a step (S**20**) of determining whether the fan is driven, unlike the embodiment described with reference to FIG. **6**.

(114) The sensing period means a time interval at which differential pressure is measured using the differential pressure sensor **100**. For example, the sensing period may be set to 20 seconds. However, the sensing period may be changed depending on various conditions.

(115) In this modified embodiment, when the differential pressure is measured using the differential pressure sensor **100**, the differential pressure sensor **100** measures the differential pressure in the sensing period, i.e. at a predetermined time interval, whereby the amount of power consumed by the differential pressure sensor **100** may be reduced.

(116) If the differential pressure sensor **100** continuously measures the differential pressure regardless of the sensing period, the amount of power consumed by the differential pressure sensor **100** and the amount of power necessary to transmit information measured by the differential pressure sensor **100** to the controller **96** may be increased.

(117) In this modified embodiment, therefore, the differential pressure sensor **100** measures the differential pressure in the sensing period in order to improve the energy efficiency of the refrigerator.

(118) The other steps of FIG. **7** are identical to those of FIG. **6**, and therefore a duplicate description of the same steps will be omitted.

(119) FIG. **8** is a control flowchart for sensing whether defrosting has failed according to an embodiment.

(120) Steps S**20** to S**40** of FIG. **8** are identical to those described above, and therefore a duplicate description of the same steps will be omitted.

(121) Referring to FIG. **8**, it is determined first whether defrosting of the evaporator **20** is finished (S**110**). The reason for this is that the determination as to whether defrosting failed is a determination as to whether defrosting of the evaporator **20** was performed normally after the defrosting is performed. As previously described, in the case in which the differential pressure measured by the differential pressure sensor **100** exceeds a first set pressure P**1**, defrosting may be performed. In addition, the evaporator **20** may be heated until the temperature of the evaporator **20** reaches a first set temperature T**1**, and then defrosting may be finished.

(122) The finishing of defrosting may mean that the driving of the heater **50** is stopped, that a predetermined amount of time has elapsed since the driving of the heater **50** was stopped, or that another predetermined operation is finished after the driving of the heater **50** is stopped.

(123) After defrosting is finished, it is determined whether the driving of the compressor **60**, which compresses the refrigerant, is commenced (S**120**).

(124) At the time at which the compressor **60** is driven, i.e. at the time at which cool air is supplied to the storage compartments **6** and **8**, after defrosting is finished, it may be determined whether previous defrosting was performed normally.

(125) At this time, it may be determined whether previous defrosting was performed normally only after the compressor **60** is driven for the first time and before the driving thereof is stopped. Frost

may be formed on the evaporator **20** after the compressor **60** is driven to complete one-cycle cooling. If it is determined whether defrosting of the evaporator **20** was completed normally after one-cycle driving is performed, therefore, errors may occur.

(126) In the case in which the differential pressure measured by the differential pressure sensor **100** exceeds a second set pressure **P2**, the controller determines that residual ice remains on the evaporator **20** even though defrosting was performed beforehand (**S140**).

(127) Here, the first set pressure **P1** may be higher than the second set pressure **P2**. The reason for this is that, if the first set pressure **P1**, which is a differential pressure at which defrosting is performed, is maintained even after defrosting is completed, the defrosting effect is negligible.

(128) Meanwhile, the reason for this is that, in the case in which the differential pressure is the second set pressure **P2** even after defrosting is performed, it is determined that previous defrosting was not performed normally, but it is not necessary to additionally perform defrosting immediately. If defrosting is unnecessarily frequently performed, as previously described, the energy efficiency of the refrigerator may be reduced.

(129) Upon determining that residual ice remains on the evaporator **20**, the first set pressure **P1**, based on which subsequent defrosting is performed, may be changed to a set value (**S150**).

Changing the first set pressure **P1** to the set value may mean decreasing the first set pressure **P1**.

(130) The first set pressure **P1** may be continuously decreased. However, the first set pressure **P1** may be changed to the set value so as to be decreased only once. For example, in the case in which the first set pressure **P1** is 20 Pa when previous defrosting was performed and it is determined that defrosting was not performed normally, the first set pressure **P1**, based on which subsequent defrosting is performed, may be changed once to 10 Pa.

(131) Of course, the decreased first set pressure **P1** may be equal to or higher than the second set pressure **P2**. The reason for this is that the first set pressure **P1** is given to determine the defrosting time and the second set pressure **P2** is given to determine whether previous defrosting was performed normally.

(132) Upon determining that previous defrosting was not performed normally, the first set temperature **T1**, at which the evaporator **20** is heated, may be changed to a set value when subsequent defrosting is performed (**S160**). Changing the first set temperature **T1** to the set value may mean increasing the first set temperature **T1**.

(133) The first set temperature **T1** may be continuously increased. However, the first set temperature **T1** may be increased only once. For example, in the case in which the first set temperature **T1** is 5 degrees when previous defrosting was performed and it is determined that defrosting was not performed normally, the temperature of the evaporator **20** necessary to finish subsequent defrosting, i.e. the first set temperature **T1**, may be changed once to 7 degrees.

(134) In an embodiment, upon determining that previous defrosting was not performed normally, subsequent defrosting may be commenced earlier and for a longer time. Consequently, a larger amount of ice formed on the evaporator **20** may be removed than was removed upon previous defrosting.

(135) It is sensed whether the temperature of the storage compartments measured by the storage compartment temperature sensor **90** reaches a second set temperature **T2**, and related information is transmitted to the controller **96** (**S170**). Here, the second set temperature **T2** may mean a temperature set to cool the storage compartments. In the case in which the storage compartments are freezing compartments, the second set temperature may be a subzero temperature. In the case in which the storage compartments are refrigerating compartments, the second set temperature may be an above-zero temperature.

(136) When the temperature of the storage compartments reaches the second set temperature **T2**, it is determined that the storage compartments **6** and **8** no longer need to be cooled, and the driving of the compressor **60** is stopped (**S180**).

(137) When the temperature of the storage compartments does not reach the second set temperature

T2, which means that one cycle of the compressor **60** to cool the storage compartments **6** and **8** is not finished, the differential pressure sensor **100** may continuously sense whether previous defrosting was performed normally.

(138) When the differential pressure measured by the differential pressure sensor **100** is higher than the second set pressure P2 at step S130, it is determined that no residual ice remains on the evaporator **200** after previous defrosting is finished (S145).

(139) In the case in which the first set pressure P1 was changed or decreased to the set value previously based on information about the differential pressure measured by the differential pressure sensor **100**, the first set pressure P1 is maintained as an initial value. That is, the first set pressure P1 becomes equal to the first set pressure P1 when previous defrosting was performed (S155).

(140) In addition, in the case in which the first set temperature T1 was changed or increased to the set value previously based on information about the differential pressure measured by the differential pressure sensor **100**, the first set temperature T1 is maintained as an initial value. That is, the first set temperature T1 becomes equal to the first set temperature T1 when previous defrosting was performed (S165).

(141) In an embodiment, when defrosting is finished and the driving of the compressor **60** is commenced, it is determined whether previous defrosting was performed normally. That defrosting was performed normally may mean that the amount of ice formed on the evaporator **20** is sufficiently reduced, whereby the area of the evaporator **20** that can directly exchange heat with air is sufficiently secured.

(142) While the storage compartments are cooled to the second set temperature T2 by the compressor **60** after defrosting is finished, it may be determined whether previous defrosting was performed normally based on the differential pressure measured by the differential pressure sensor **100**. In the case in which a difference in pressure between the upper side of the evaporator **20** and the lower side of the evaporator **20** is not great based on the differential pressure measured by the differential pressure sensor **100** after defrosting is finished, it is determined that defrosting of the evaporator **20** was not performed normally. The conditions for defrosting the evaporator **20** may be changed.

(143) The above-described differential pressure, i.e. the difference in pressure, may mean the average of the values of difference in pressure that are measured by the differential pressure sensor **100**. A difference in pressure may be measured several times by the differential pressure sensor **100**, the average of the measured values of difference in pressure are calculated, and a determination may be performed based on the average in order to reduce errors of incorrect determination based on temporarily abnormal data.

(144) In addition, in an embodiment, it may be determined that previous defrosting was performed abnormally due to temporary errors even though the average is used. Consequently, the differential pressure sensor **100** may measure differential pressure until the driving of the compressor **60** is stopped in order to determine whether previous defrosting was performed normally.

(145) FIG. **9** is a control flowchart for sensing whether defrosting failed according to a modified embodiment.

(146) Referring to FIG. **9**, it is determined whether a sensing period using the differential pressure sensor **100** is satisfied (S10) before a step (S20) of determining whether the fan is driven, unlike the embodiment described with reference to FIG. **8**.

(147) The sensing period means a time interval at which differential pressure is measured using the differential pressure sensor **100**. For example, the sensing period may be set to 20 seconds. However, the sensing period may be changed depending on various conditions.

(148) In this modified embodiment, when the differential pressure is measured using the differential pressure sensor **100**, the differential pressure sensor **100** measures the differential pressure in the sensing period, i.e. at a predetermined time interval, whereby the amount of power

consumed by the differential pressure sensor **100** may be reduced.

(149) If the differential pressure sensor **100** continuously measures the differential pressure regardless of the sensing period, the amount of power consumed by the differential pressure sensor **100** and the amount of power necessary to transmit information measured by the differential pressure sensor **100** to the controller **96** may be increased.

(150) In this modified embodiment, therefore, the differential pressure sensor **100** measures the differential pressure in the sensing period in order to improve the energy efficiency of the refrigerator.

(151) FIG. **10** is a control flowchart for sensing the breakdown of the differential pressure sensor according to an embodiment.

(152) Steps **S20** to **S40** of FIG. **10** are identical to those described above, and therefore a duplicate description of the same steps will be omitted.

(153) Referring to FIG. **10**, in an embodiment, the differential pressure sensor **100** senses a differential pressure (**S40**), and when the differential pressure is less than a set value, it is determined that the pipes of the differential pressure sensor **100** are clogged.

(154) The differential pressure sensor **100** measures a difference in pressure between the air introduced through the first through-hole **110** and the air introduced through the second through-hole **120**. If the pipes having the first through-hole **110** and the second through-hole **120** formed therein are clogged, it is not possible to accurately measure the differential pressure.

(155) In an embodiment, the breakdown of the differential pressure sensor **100** may be determined based on the differential pressure measured by the differential pressure sensor **100**, whereby control may be easily performed.

(156) After the differential pressure is measured by the differential pressure sensor **100** several times, a differential pressure average P_{avg} , which is the average of measured values of differential pressure, is calculated (**S210**). The differential pressure average P_{avg} may be calculated by averaging two or more values of differential pressure.

(157) Subsequently, it is determined whether the differential pressure average P_{avg} is greater than a maximum average P_{max} calculated previously (**S220**).

(158) When the refrigerator is operated and the condition for measurement using the differential pressure sensor **100** is satisfied, the differential pressure sensor **100** continuously measure differential pressure. Consequently, the average of values of differential pressure measured by the differential pressure sensor **100** may be continuously calculated. In the case in which the number of values of differential pressure necessary to calculate the differential pressure average P_{avg} is set to 10, when the eleventh value of differential pressure is calculated, a new differential pressure average P_{avg} excluding the first value of differential pressure may be calculated. Of course, the number of values of differential pressure necessary to calculate the differential pressure average P_{avg} may be variously changed.

(159) When the differential pressure average P_{avg} is greater than the maximum average P_{max} calculated previously, the maximum average P_{max} is updated (**S225**). Consequently, the newly updated maximum average P_{max} is increased to the newly calculated differential pressure average P_{avg} .

(160) That the value of differential pressure measured by the differential pressure sensor **100** is increased may mean that a difference in pressure between the opposite sides of the evaporator **20** is increased, i.e. may mean that frost is formed on the evaporator **20**. It is natural that, when the refrigerator is used, frost is continuously formed on the evaporator **20**.

(161) That the value of differential pressure measured by the differential pressure sensor **100** is increased may mean that the differential pressure sensor **100** normally measures a difference in pressure between the upper part and the lower part of the evaporator **20**.

(162) When the differential pressure average P_{avg} is equal to or less than the maximum average P_{max} calculated previously, a first clogging determination step of determining whether the

differential pressure average P_{avg} is less than the value obtained by subtracting a reference value from the maximum average P_{max} is performed (S230).

(163) Here, the reference value may be less than the first set pressure P_1 , based on which it is determined that defrosting of the evaporator **20** is necessary. Particularly, the reference value may be equal to or less than $\frac{1}{3}$ of the first set pressure P_1 .

(164) At step S230, when the differential pressure measured by the differential pressure sensor **100** is small in the state in which ice is continuously formed on the evaporator **20** and thus a difference in pressure between the upper part and the lower part of the evaporator **20** is continuously increased, it may be determined that the pipes of the differential pressure sensor **100** are clogged.

(165) That is, when differential pressure that is less than the value obtained by subtracting the reference value from the maximum average P_{max} is sensed even though the differential pressure average P_{avg} is less than the maximum average P_{max} , it is determined that the pipes of the differential pressure sensor **100** are clogged (S250).

(166) The differential pressure measured by the differential pressure sensor **100** in the state in which the pipes of the differential pressure sensor **100** are clogged is an abnormal value. When a defrosting time is determined based on such information, therefore, the evaporator may be defrosted unnecessarily or later. As a result, the energy efficiency of the refrigerator may be reduced.

(167) At step S210, the differential pressure sensor **100** calculates the differential pressure average P_{avg} , and a second clogging determination step of determining whether the differential pressure average P_{avg} is less than a minimum average P_{min} is performed (S240). Here, the minimum average P_{min} may be a value of differential pressure measured in the state in which no frost is formed on the evaporator **20**.

(168) When the differential pressure measured by the differential pressure sensor **100** is less than the minimum average P_{min} even though no frost is formed on the evaporator **20**, it cannot be considered that differential pressure was measured normally by the differential pressure sensor **100**.

(169) The differential pressure sensor **100** calculates a difference in pressure between the upper part and the lower part of the evaporator **20**. Basically, since the evaporator impedes air flow, a difference in pressure equivalent to the minimum average P_{min} may be maintained. Nevertheless, when the differential pressure sensor **100** measures a differential pressure that is less than the minimum average P_{min} , this means that the pipes of the differential pressure sensor **100** are clogged. Consequently, it is not possible for the differential pressure sensor **100** to properly measure differential pressure.

(170) The above situation may be a situation in which ice is instantaneously formed in the pipes of the differential pressure sensor **100** or a situation in which bulky ice falls to regions of the differential pressure sensor **100** that are adjacent to the pipes, whereby the pipes are clogged.

(171) When the measured differential pressure average P_{avg} is less than the minimum average P_{min} , it is determined that the differential pressure sensor **100** is clogged (S250).

(172) In an embodiment, as step S220, the average of the values of differential pressure measured by the differential pressure sensor **100** may be calculated, and then the first clogging determination step and the second clogging determination step may be performed in a parallel fashion in order to sense the breakdown of the differential pressure sensor **100**.

(173) That is, when the differential pressure measured by the differential pressure sensor **100** is equal to or greater than a predetermined value but is less than a specific value, it is determined that the differential pressure sensor **100** has broken down.

(174) Upon determining that the differential pressure sensor **100** is clogged as the result of executing the two steps, it is determined whether clogging of the differential pressure sensor **100** was determined a specific number of times, for example, three times (S260).

(175) When clogging of the differential pressure sensor **100** was not determined the specific number of times, the evaporator **20** is defrosted (S280).

(176) The evaporator **20** and the differential pressure sensor **100** are installed in the case **35**. When the heater **50** is driven, therefore, the temperature in the case **35** may be increased. As a result, the differential pressure sensor **100** as well as the evaporator **20** may be heated.

(177) When the heater **50** is driven, therefore, ice in the pipes of the differential pressure sensor **100** or ice adjacent to the pipes may melt or be removed. When the heater **50** is driven, therefore, clogging of the differential pressure sensor **100** may be solved.

(178) At this time, the heater **50** may be driven until the temperature of the evaporator **20** reaches the second set temperature T2. That is, the heater may be driven until a defrosting condition described in the present invention is satisfied in order to solve clogging of the differential pressure sensor **100**.

(179) When clogging is determined the specific number of times, a condition for determining defrosting is changed (S270).

(180) When defrosting is performed at step S280 until clogging is determined the specific number of times, for example, three times, but clogging of the differential pressure sensor **100** is not solved, it may not be preferable to perform defrosting based on the differential pressure sensor **100**.

(181) Consequently, a condition for performing defrosting may be determined based on whether a predetermined amount of time has elapsed since the compressor **60** was driven. When the compressor **60** is driven, the temperature of the evaporator **20** is decreased, since the refrigerant is evaporated by the evaporator. In this state, frost may be formed on the evaporator **20**.

Consequently, the driving time of the compressor **60** may be used as the time for determining whether defrosting is necessary.

(182) In addition, a condition for performing defrosting may be determined based on whether a specific amount of time has elapsed since the doors **4** opened the storage compartments **6** and **8**. When the doors **4** open the storage compartments, external moisture is introduced into the storage compartments, and air from the storage compartments is introduced into the case, whereby the humidity in the case may be increased. When the humidity is increased, the amount of ice formed on the evaporator **20** is increased, whereby frost may be formed on the evaporator.

(183) Meanwhile, a condition for performing defrosting may be determined in consideration both of the driving time of the compressor **60** and of the open time of the doors **4**.

(184) In an embodiment, the differential pressure measured by the differential pressure sensor **100** is used in order to sense the breakdown of the differential pressure sensor **100**.

(185) The pipes of the differential pressure sensor **100** may be clogged in two situations. In an embodiment, the two situations may be checked in a parallel fashion in order to determine the breakdown of the differential pressure sensor in two situations.

(186) In an initial situation in which the pipes of the differential pressure sensor **100** are clogged, the heater **50** may be driven in order to repair the breakdown of the differential pressure sensor **100**.

(187) In the case in which the pipes of the differential pressure sensor **100** are unclogged even using the heater **50**, information about the differential pressure acquired by the differential pressure sensor **100** may be ignored, and a defrosting time may be determined based on some other condition. Even when the differential pressure sensor breaks down, therefore, the evaporator **20** may be stably defrosted. When the refrigerator is used, therefore, defrosting may be appropriately performed, whereby the energy efficiency of the refrigerator may be increased.

(188) FIG. **11** is a control flowchart for sensing the breakdown of the differential pressure sensor according to a modified embodiment.

(189) Referring to FIG. **11**, it is determined whether a sensing period using the differential pressure sensor **100** is satisfied (S10) before a step (S20) of determining whether the fan is driven, unlike the embodiment described with reference to FIG. **10**.

(190) The sensing period means a time interval at which differential pressure is measured using the differential pressure sensor **100**. For example, the sensing period may be set to 20 seconds.

However, the sensing period may be changed depending on various conditions.

(191) In this modified embodiment, when the differential pressure is measured using the differential pressure sensor **100**, the differential pressure sensor **100** measures the differential pressure in the sensing period, i.e. at a predetermined time interval, whereby the amount of power consumed by the differential pressure sensor **100** may be reduced.

(192) If the differential pressure sensor **100** continuously measures the differential pressure regardless of the sensing period, the amount of power consumed by the differential pressure sensor **100** and the amount of power necessary to transmit information measured by the differential pressure sensor **100** to the controller **96** may be increased.

(193) In this modified embodiment, therefore, the differential pressure sensor **100** measures the differential pressure in the sensing period in order to improve the energy efficiency of the refrigerator.

(194) FIG. **12** is a view illustrating an embodiment of a modified differential pressure sensor.

(195) Referring to FIG. **12**, the differential pressure sensor **100**, which is provided in the case, includes the first pipe **150**, having the first through-hole **110** formed therein, the second pipe **170**, having the second through-hole **120** formed therein, and the connection member **200** for interconnecting the first pipe **150** and the second pipe **170**.

(196) The connection member **200** may include an electronic circuit for sensing a difference in pressure between the first pipe **150** and the second pipe **170**. As shown in FIGS. **1** to **3**, therefore, the connection member **200** may be disposed higher than the evaporator **20** or the fan **40**.

(197) In the case in which the connection member **200** is disposed higher than the evaporator **20**, water drops falling from the evaporator **20** are prevented from falling to the connection member **200**, whereby it is possible to prevent the connection member **200** from being damaged by the water drops.

(198) Particularly, when the evaporator **20** is defrosted, ice formed on the evaporator **20** is melted, whereby a large number of water drops fall. In the case in which the connection member **200** is disposed under the evaporator **20**, the water drops fall to the connection member **200**. As a result, the electronic circuit may be adversely affected, whereby the differential pressure sensor **100** may be damaged.

(199) In addition, the connection member **200** may be molded such that water drops are prevented from penetrating into the connection member **200**. In addition, the portion of the connection member **200** at which the electronic circuit is installed may be covered such that water drops are prevented from easily penetrating into the electronic circuit.

(200) When the differential pressure sensor **100** is installed, moisture may be introduced into the differential pressure sensor **100**, or when the refrigerator is operated, the differential pressure sensor **100** may break down as the result of air flow. Consequently, it is important to choose the installation position of the differential pressure sensor **100** in consideration thereof.

(201) In addition, in the present invention, the connection member **200** may be disposed higher than the fan **40** such that air flow generated by the fan **40** is not impeded. In the structure of FIGS. **1** to **3**, air in the case is introduced through the inlet and is discharged through the outlet, and the fan **40** is installed in the outlet. When the connection member **200** is installed above the fan **40**, therefore, the connection member **200** does not resist the flow of air rising from the inlet to the output, whereby air flow is not impeded.

(202) Since the differential pressure sensor **100** is installed in the case (see FIGS. **1** to **3**), air passing through the storage compartments is cooled by the evaporator **20**. Since the air supplied to the storage compartments contains a large amount of moisture due to the food stored in the storage compartments, the air is cooled when the air exchanges heat with the evaporator **20**, whereby a large number of water drops may be generated. That is, the humidity of the space in which the differential pressure sensor **100** is installed is high.

(203) In addition, since the temperature of the evaporator **20** is much lower than room temperature, the temperature around the evaporator **20** is very low when the refrigerant is evaporated by the

evaporator **20**. When the refrigerant is not evaporated by the evaporator **20**, however, the temperature around the evaporator is similar to the temperature in the storage compartments. Consequently, the space in which the evaporator is installed has high temperature variation.

(204) Since the space in which the evaporator **20** is installed has high temperature variation and high humidity, it is difficult to accurately measure information using a general sensor. Since the differential pressure sensor is used in the embodiment of the present invention, however, it is possible to more accurately sense information even under adverse conditions than in the case in which other kinds of sensors are used.

(205) The present invention provides various kinds of modified differential pressure sensors in order to accurately measure differential pressure even under such adverse conditions.

(206) Referring to FIG. **12**, the section of the portion of the first pipe **150** that is coupled to the connection member **200** is smaller than the section of the portion of the first pipe in which the first through-hole **110** is formed. In addition, the section of the portion of the second pipe **170** that is coupled to the connection member **200** is smaller than the section of the portion of the second pipe in which the second through-hole **120** is formed.

(207) Even when defrost water, generated when the evaporator **20** is defrosted, comes into contact with the first through-hole **110** or the second through-hole **120** and moves into the first pipe **150** and the second pipe **170**, therefore, hot air may be easily introduced into the first pipe **150** and the second pipe **170** as the heater is driven, whereby defrosting may be easily performed.

(208) The first pipe **150** may be provided with a bent portion **210**, which changes the direction in which the first pipe **150** extends. The first pipe **150** may extend while avoiding the evaporator **20** due to the bent portion **210**.

(209) The bent portion **210** may be formed such that the section of the lower side thereof is larger than the section of the upper side thereof. That is, the bent portion **210** may be formed in the shape of a pipe that gradually expands downwards such that the size of the inner section of the first pipe **150** is changed.

(210) The first pipe **150** may not extend downwards, but may be bent at a predetermined angle and then extend downwards by the provision of the bent portion **210** (see FIG. **2**). In the case in which the heater is driven and the defrost water generated from the evaporator **20** is changed into vapor as the result of contacting the heater, the water comes into contact with the inner wall of the bent portion **210** even though the water is introduced into the first pipe **150**, whereby condensation may be easily performed. In the case in which, the first pipe **150** extends downwards vertically at the same angle, vapor may easily rise to the portion of the first pipe that is coupled to the connection member **200**, whereby water drops may be formed on the portion of the first pipe that is coupled to the connection member. In contrast, in the present invention, it is possible to prevent the first pipe **150** from being clogged by vapor, since the tilt angle of the bent portion **210** is changed.

(211) The second pipe **170** may also be provided with a bent portion **210**, which changes the direction in which the second pipe **170** extends. The second pipe **170** may extend while avoiding the evaporator **20** due to the bent portion **210**.

(212) The bent portion formed at the second pipe **170** performs substantially the same function as the bent portion formed at the first pipe **150** even though the bent portions are different from each other in terms of the concrete shapes thereof. Consequently, the same description may be applied thereto.

(213) Meanwhile, the first pipe **150** or the second pipe **170** may be formed to have a hollow shape, and the hollow shape may have a circular section. In the case in which a hollow in each of the first pipe **150** and the second pipe **170** has a quadrangular section, rather than a circular section, frost is formed at the angled parts of the hollow, whereby an excessive amount of frost may be formed. In contrast, in the case in which the hollow has a circular section, an excessive amount of frost may be prevented from being formed in a specific region of the hollow, whereby it is possible to prevent the hollow from being clogged.

(214) The first pipe **150** or the second pipe **170** may have an inner diameter of 5 mm or more. In the case in which the inner diameter of the first pipe **150** or the second pipe **170** is large, heat generated by the heater may be easily introduced into the first pipe **150** or the second pipe **170** when ice is formed in the first pipe **150** or the second pipe **170**, and water drops may easily fall from the first pipe **150** or the second pipe **170** when the ice is melted by the introduced heat. Here, the term “inner diameter” may mean the diameter of the empty space, i.e. the hollow, formed in the first pipe **150** or the second pipe **170**.

(215) The first pipe **150** or the second pipe **170** may be provided at one end thereof with a first expanded pipe part **220**, the diameter of which gradually increases toward the lower end thereof. The first through-hole **110** or the second through-hole **120** may be formed in the lower end of the first expanded pipe part **220** such that the diameter of the first through-hole **110** or the second through-hole **120** is increased by the first expanded pipe part **220**. The first expanded pipe part **220** will be described in more detail with reference to FIG. **13**.

(216) FIGS. **13** to **16** are views illustrating embodiments of another modified differential pressure sensor.

(217) FIG. **13** shows an example in which the first expanded pipe part **220** is provided at one end of the first pipe **150** or the second pipe **170**.

(218) The first through-hole **110** or the second through-hole **120** may be formed so as to have a circular section. The first through-hole **110** or the second through-hole **120** may be disposed so as to face downwards in the direction of gravity. Consequently, the defrost water falling from the case, in which the evaporator **20** or the differential pressure sensor **100** is installed, may be prevented from being introduced into the first pipe **150** or the second pipe **170**.

(219) The first expanded pipe part **220** may be generally formed so as to have a cylindrical shape having an increasing diameter.

(220) Referring to FIG. **14**, the first through-hole **110** or the second through-hole **120** is formed in the side surface of the lower end of the first expanded pipe part **220**. In FIG. **14**, the first through-hole **110** or the second through-hole **120** is formed in the side surface of the first pipe **150** or the second pipe **170**, unlike FIG. **13**. Since the first through-hole **110** and the second through-hole **120** are formed in the side surfaces of the first pipe **150** and the second pipe **170** and the first pipe **150** and the second pipe **170** extend downwards in the direction of gravity, it is possible for the differential pressure sensor to more accurately measure differential pressure. The reason for this is that the first through-hole **110** and the second through-hole **120** are disposed in the direction perpendicular to air flow in the case.

(221) Meanwhile, a plurality of first through-holes **110** or a plurality of second through-holes **120** may be formed along the circumference of the first pipe **150** or the second pipe **170**.

(222) A cover **230** may be provided at the lower end of the first expanded pipe part **220** to close the lower part of the first expanded pipe part **220**. The cover **230** extends so as to have a section larger than the inner diameter of the first expanded pipe part **220**, whereby air may be prevented from being introduced into the first pipe **150** or the second pipe **170** through the lower part of the first expanded pipe part **220**. In this case, the effect caused by the dynamic pressure of air may be reduced by the cover **230** even when the first pipe **150** or the second pipe **170** extends in the direction of gravity.

(223) In addition, when vapor generated during defrosting falls and when melting frost falls, water drops may rebound from the bottom surface of the case. Since the cover **230** closes the lower part of the first pipe **150** or the second pipe **170**, the rebounding water drops may be prevented from being introduced into the first pipe **150** or the second pipe **170**.

(224) Referring to FIG. **15**, the first expanded pipe part **220** is provided at the lower part thereof with a second expanded pipe part **240**, the diameter of which gradually increases toward the lower end thereof. That is, two expanded pipe parts may be installed at the first pipe **150** or the second pipe **170** so as to be disposed at different heights.

(225) In this case, an extension pipe, which extends from the first pipe **150** so as to have the same diameter as the upper side of the first expanded pipe part **220**, is located in the first expanded pipe part **220**, and the second expanded pipe part **240** is connected to the extension pipe.

(226) The first through-hole **110** or the second through-hole **120** is formed in the extension pipe. The first through-hole **110** or the second through-hole **120** may be formed in the side surface of the extension pipe, rather than the lower part of the extension pipe. When viewed in the lateral direction, the first through-hole **110** or the second through-hole **120** may be hidden by the first expanded pipe part **220**. Consequently, it is possible to prevent the defrost water from directly falling to the first through-hole **110** or the second through-hole **120** and from being introduced into the first pipe **150** or the second pipe **170**.

(227) A hole, through which air is guided to the first through-hole **110** or the second through-hole **120**, is not formed in the lower part of the second expanded pipe part **240**. The lower surface of the second expanded pipe part **240** is entirely closed. The lower end of the second expanded pipe part **240** extends so as to have a larger sectional area than the lower end of the first expanded pipe part **220**. As a result, air in the case may not be directly introduced into the first through-hole **110** or the second through-hole **120**. Consequently, it is possible for the differential pressure sensor **100** to more accurately measure static pressure than dynamic pressure caused by air flow.

(228) In addition, when vapor generated during defrosting falls and when melting frost falls, water drops may rebound from the bottom surface of the case. Since the second expanded pipe part **240** closes the lower part of the first pipe **150** or the second pipe **170** and the lower part of the first through-hole **110** or the second through-hole **120**, the water drops are prevented from being introduced into the first through-hole **110** or the second through-hole **120**. Consequently, the probability of the first pipe **150** or the second pipe **170** becoming clogged and the differential pressure sensor **100** breaking down may be reduced.

(229) Referring to FIG. **16**, a plurality of communication holes **240** may be formed in the first pipe **150** or the second pipe **170**, and the communication holes **240** may be disposed so as to be perpendicular to the first through-hole **110** or the second through-hole **120**.

(230) The communication holes **240** may be arranged in a line in the vertical direction.

(231) The communication holes **240** are formed in the side surface of the first pipe **150** or the second pipe **170**. Even when water drops are formed inside the first pipe **150** or the second pipe **170**, therefore, the water drops may be discharged out of the first pipe **150** or the second pipe **170** through the communication holes **240**. Consequently, it is possible to prevent the first pipe **150** or the second pipe **170** from being clogged by the water drops. That is, the probability that the differential pressure sensor **100** breaks down may be reduced due to the communication holes **240**, in addition to the first through-hole **110** or the second through-hole **120**.

(232) FIG. **17** is a side cut-away view showing a refrigerator according to an embodiment of the present invention, FIG. **18** is a view illustrating a principal part of FIG. **17**, and FIG. **19** is a plan view of FIG. **18**. An evaporator is omitted from FIG. **18** for simplicity.

(233) Hereinafter, a description will be given with reference to FIGS. **17** to **19**.

(234) The refrigerator includes a cabinet **2**, having a plurality of storage compartments **6** and **8** defined therein, and doors **4** for opening and closing the storage compartments **6** and **8**.

(235) The storage compartments **6** and **8** include a first storage compartment **6** and a second storage compartment **8**. The first storage compartment **6** and the second storage compartment **8** may constitute a refrigerating compartment and a freezing compartment, respectively. Alternatively, the first storage compartment **6** and the second storage compartment **8** may constitute a freezing compartment and a refrigerating compartment, respectively. In yet another alternative, both the first storage compartment **6** and the second storage compartment **8** may constitute refrigerating compartments or freezing compartments.

(236) In the storage compartments **6** and **8** is provided a storage compartment temperature sensor **90** for measuring the temperature in the storage compartments **6** and **8**. Alternatively, the

temperature sensor **90** may be installed in each of the storage compartments **6** and **8** to individually measure the temperature in each storage compartment.

(237) At the rear of the storage compartments is provided a case **35** for accommodating an evaporator **20**.

(238) The case **35** is provided with an outlet **38**, through which air is supplied from the case **35** to the storage compartments, and with an inlet **32**, through which air is supplied from the storage compartments into the case **35**.

(239) In the inlet **32** is provided an introduction pipe **30** for guiding air into the case **35**. As a result, the storage compartments **6** and **8** may be connected to the case **35** in order to define an airflow path.

(240) In the outlet **38** is provided a fan **40**, which may enable air to flow from the case **35** to the storage compartments **6** and **8**. The case **35** has a hermetically sealed structure, excluding the inlet **32** and the outlet **38**. When the fan **40** is driven, therefore, air flows from the inlet **32** to the outlet **38**.

(241) The air having passed through the fan **40**, i.e. cool air, may be supplied to the first storage compartment **6** through a duct **7** for guiding air to the first storage compartment **6**. The air having passed through the fan **40** may also be supplied to the second storage compartment **8**.

(242) In the case **35** is accommodated the evaporator **20**, which evaporates a refrigerant compressed by a compressor **60** in order to generate cool air. The air in the case **35** is cooled as the result of heat exchange with the evaporator **20**.

(243) Under the evaporator **20** is provided a heater for generating heat to defrost the evaporator **20**. It is not necessary to install the heater **50** under the evaporator **20**. It is sufficient to provide the heater in the case **35** in order to heat the evaporator **20**.

(244) An evaporator temperature sensor **92** may be provided at the evaporator **20** to measure the temperature of the evaporator **20**. When the refrigerant, passing through the evaporator **20**, is evaporated, the evaporator temperature sensor **92** may sense a low temperature. When the heater **50** is driven, the evaporator temperature sensor **92** may sense a high temperature.

(245) The compressor **60** may be installed in a machinery compartment, which is provided in the cabinet **2**, to compress the refrigerant that is supplied to the evaporator **20**. The compressor **60** is installed outside the case **35**.

(246) The inlet **32** is located under the evaporator **20**, and the outlet **38** is located above the evaporator **20**. The outlet **38** is located higher than the evaporator **20**, and the inlet **32** is located lower than the evaporator **20**.

(247) When the fan **40** is driven, therefore, air moves upwards in the case **35**. The air, introduced into the inlet **32**, undergoes heat exchange while passing through the evaporator **20**, and is discharged out of the case **35** through the outlet **38**.

(248) A differential pressure sensor assembly **1100** is provided in the case **36**. The differential pressure sensor assembly **1100** includes a differential pressure sensor for measuring pressure.

(249) The differential pressure sensor assembly **1100** includes a housing **1200**, in which a differential pressure sensor is provided. The housing **1200** is provided with a first communication pipe **1250** and a second communication pipe **1270**. The first communication pipe **1250** and the second communication pipe **1270** extend downwards from the housing **1200**.

(250) The first communication pipe **1250** is formed so as to have a hollow shape, and a first through-hole **1254** is formed inside the first communication pipe. The second communication pipe **1270** is formed so as to have a hollow shape, and a second through-hole **1274** is formed inside the second communication pipe.

(251) The second communication pipe **1270** extends above the evaporator **20**, and therefore the second through-hole **1274** is disposed above the evaporator **20**. That is, the second through-hole **1274** may be disposed between the evaporator **20** and the outlet **38**.

(252) The first communication pipe **1250** extends above the evaporator **20**, but a tube **1300** may be

coupled to the first communication pipe **1250**. A communication hole **1256** is formed inside the tube **1300**. The tube **1300** may extend below the evaporator **20**, i.e. to a position between the evaporator **20** and the inlet **32**. Consequently, the communication hole **1256** may be located under the evaporator **20** and the inlet **32**.

(253) The differential pressure sensor assembly **1100** may measure a difference in pressure between the upper side and the lower side of the evaporator **20** using a difference in pressure between air introduced from below the communication hole **1256** and air introduced from below the second through-hole **1274**.

(254) Air introduced through the communication hole **1256** may be directly introduced into the first through-hole **1254**. That is, the differential pressure sensor assembly **1100** senses a difference in pressure between the air passing through the first through-hole **1254** and the air passing through the second through-hole **1274**. A relatively low pressure is applied to the second through-hole **1274**, which is a low-pressure part, and a relatively high pressure is applied to the first through-hole **1254**, which is a high-pressure part. Consequently, the differential pressure sensor assembly **1100** senses a difference in pressure.

(255) Particularly, when the fan **40** is driven, air flows in the case **35**. Consequently, it is possible for the differential pressure sensor assembly **1100** to sense a difference in pressure.

(256) Meanwhile, the second communication pipe **1270** extends so as to be adjacent to the upper side of the evaporator **20**, and therefore it is possible to more accurately measure pressure at the upper side of the evaporator **20**.

(257) The tube **1300** may be made of a deformable material. When the tube **1300** extends to the lower part of the evaporator **20**, therefore, the tube may be easily installed while being deformed so as not to contact the evaporator **20**.

(258) The housing **1200** may be disposed in the middle of the fan **40** in the leftward-rightward direction, whereby it is possible to accurately measure pressures at opposite sides of the evaporator **20**. That is, the housing **1200** may be located in the middle of the fan **40**, whereby it is possible to sense a difference in pressure depending on the distribution of pressure caused by air flow generated by the fan **40**.

(259) When the fan **40** is driven, the lower part of the evaporator **20** forms a relatively high pressure, since the air under the evaporator **20** is air that has not passed through the evaporator **20**. In contrast, the upper part of the evaporator **20** forms a relatively low pressure due to the resistance of the evaporator **20**, since the air above the evaporator **20** is air that has passed through the evaporator **20**. As frost is formed on the evaporator **20**, the volume of ice formed on the evaporator is increased, whereby air resistance is increased. As a result, a difference in pressure between the upper side and the lower side of the evaporator **20** is increased, and the differential pressure sensor assembly **1100** may sense the difference in pressure. In the case in which the sensed difference in pressure is greater than a predetermined value, it may be determined that frost is formed on the evaporator to such an extent that defrosting is necessary.

(260) The differential pressure sensor assembly **1100** may measure a difference in pressure between the upper part of the evaporator **20** and the lower part of the evaporator **20** in order to sense whether frost is formed on the evaporator **20**. Since the differential pressure sensor assembly **1100** measures a change in pressure caused by air passing through the evaporator **20** and flowing in the case **35**, unlike conventional temperature sensors, it is possible to more accurately sense frost formed on the evaporator **20**. Particularly, even in the case in which a relatively large amount of ice is formed on one side of the evaporator **20**, it is possible to accurately sense frost formed on the evaporator **20**.

(261) FIG. **20** is a view showing a differential pressure sensor assembly according to an embodiment of the present invention.

(262) Referring to FIG. **20**, a differential pressure sensor assembly **1100** according to an embodiment of the present invention includes a differential pressure sensor **1110** and a housing

1200, in which the differential pressure sensor **1110** is installed.

(263) The housing **1200** may be fixed to one side wall of the case **35** such that the differential pressure sensor assembly **1100** is fixed in the case **35**.

(264) The housing **1200** includes a housing body **1210** having a space **1224** defined therein. The differential pressure sensor **1110** is accommodated in the space **1224**.

(265) In addition, the housing **1200** includes a first communication pipe **1250** and a second communication pipe **1270**, which are provided at the housing body **1210** so as to extend therefrom.

(266) The first communication pipe **1250** is provided with a hollow, which is a first through-hole **1254**. In addition the second communication pipe **1270** is provided with a hollow, which is a second through-hole **1274**.

(267) FIGS. **21A** to **21C** are views showing a differential pressure sensor according to an embodiment.

(268) FIG. **21A** is a front view of the differential pressure sensor **1110**, FIG. **21B** is a side view of the differential pressure sensor **1110**, and FIG. **21C** is a plan view of the differential pressure sensor **1110**.

(269) The differential pressure sensor **1110** includes a first port **1122**, through which air is introduced, a second port **1124**, through which the air, introduced through the first port **1122**, is discharged, and a substrate **1112**, on which the first port **1122** and the second port **1124** are installed.

(270) That is, the first port **1122** may be disposed at a high-pressure part, the pressure of which is relatively high, and the second port **1124** may be disposed at a low-pressure part, the pressure of which is relatively low.

(271) Since air moves from the high-pressure part to the low-pressure part, the air may be introduced through the first port **1122** and may be discharged through the second port **1124**. On the substrate **1112** may be provided a temperature sensor, which may measure a change in the temperature of the air introduced through the first port **1122** and moving toward the second port **1124** in order to sense a difference in pressure between the first port **1122** and the second port **1124**. Of course, it is possible to sense a difference in pressure using various methods.

(272) FIG. **22** is a perspective view of the housing, FIG. **23** is a side view of the housing, FIG. **24** is a front view of the housing, and FIGS. **25** to **27** are sectional views of the housing.

(273) FIG. **25** is an A-A sectional view, FIG. **26** is a B-B sectional view, and FIG. **27** is a C-C sectional view.

(274) The housing **1200** includes a first communication pipe **1250**, which is provided in the housing body **1210** so as to communicate with the first port **1122**. In addition, the housing **1200** includes a second communication pipe **1270**, which is provided in the housing body **1210** so as to communicate with the second port **1124**.

(275) The housing body **1210** includes a front wall **1211**, a left side wall **1216**, a right side wall **1218**, a ceiling **1214**, and a bottom surface **1213**. That is, the space **1224** may be defined by the front wall **1211**, the left side wall **1216**, the right side wall **1218**, the ceiling **1214**, and the bottom surface **1213**.

(276) The front wall **1211** may be fixed in the case **35** in the state of being in contact with one side wall of the case **35**.

(277) No rear wall is formed at the housing body **1210**. The housing body is provided in the rear surface thereof with an opening **1220**. The opening **1220** may be defined by edges of the left side wall **1216**, the right side wall **1218**, the ceiling **1214**, and the bottom surface **1213**.

(278) The differential pressure sensor **1110** may be installed in the housing **1200** through the opening **1220**. That is, the differential pressure sensor **1110** is inserted into the space **1224** through the opening **1220**.

(279) After the differential pressure sensor **1110** is inserted through the opening **1220**, a molding solution may be injected into the space **1224**. Since the differential pressure sensor **1110** is not

exposed to external moisture due to the molding solution, electric leakage due to current supplied to the differential pressure sensor **1110** is prevented. The molding solution is hardened for a predetermined amount of time after being injected.

(280) After the differential pressure sensor **1110** is installed, the space **1224** is filled with the molding solution, whereby no water drops are introduced into the space **1224**. In addition, since the space **1224** is filled, water drops falling from the ceiling **1214** or water drops falling from the case **35** move along the molding solution and then fall below the housing **1200**.

(281) In addition, since the opening **1220** is located in the rear surface of the housing body **1110**, water drops may move below the opening **1220** even when the water drops are formed in the opening **1220**.

(282) The ceiling **1214** is disposed so as to be inclined to the bottom surface **1213**. Specifically, the ceiling **1214** may be disposed so as to be closer to the bottom surface **1214** in the rearward direction, whereby the rear of the ceiling **1214** may be lower than the front of the ceiling **1214**.

(283) Water generated from the ceiling **1214** may not remain on the ceiling **1214** but may fall from the housing **1200**. The reason for this is that, if water remaining in the housing **1200** freezes, frost is formed in the housing **1200**, and therefore the amount of cool air that is discharged through the outlet **39** is reduced, whereby cooling efficiency is reduced.

(284) Since the front wall **1211** of the housing body **1210** is coupled to the case **35**, however, the ceiling **1214** may be inclined toward the rear of the housing body **1210**.

(285) In the space **1224** is provided a location unit **1230**, in which the differential pressure sensor **1110** is located. The location unit **1230** may protrude into the space **1224** in order to form a structure for fixing the differential pressure sensor **1110**.

(286) The location unit **1230** includes a location surface **1236**, disposed in surface contact with the differential pressure sensor **1110**, and a first hole **1232** and a second hole **1234**, formed in the location surface **1236**. The first hole **1232** communicates with the first communication pipe **1250**, and the second hole **1234** communicates with the second communication pipe **1270**.

(287) That is, air introduced through the first through-hole **1254** is guided to the first hole **1232**, and air discharged through the second hole **1234** is guided to the second through-hole **1274**.

(288) Meanwhile, a sealing member, such as an O-ring, may be provided at each of the first hole **1232** and the second hole **1234**. Consequently, the first through-hole **1254** may communicate with the first hole **1232** without leakage, and the second through-hole **1274** may communicate with the second hole **1234** without leakage.

(289) Since the location surface **1236** comes into surface contact with the differential pressure sensor **1110**, the location surface **1236** may set the tilt angle of the differential pressure sensor **1110**. That is, the differential pressure sensor **1110** may be coupled to the location surface **1236** in an inclined state.

(290) The location surface **1236** may be disposed so as to be inclined to the bottom surface **1213**. The location surface **1236** may be disposed so as to be perpendicular to the bottom surface **1213** such that the substrate **1112** of the differential pressure sensor **1110** is disposed so as to be perpendicular to the bottom surface **1213**.

(291) The first communication pipe **1250** and the second communication pipe **1270** extend from the same surface of the housing body **1210**. Here, the same surface of the housing body **1210** may be the bottom surface **1213**.

(292) Meanwhile, the first communication pipe **1250** and the second communication pipe **1270** are not disposed parallel to each other but are disposed so as to be inclined to each other. The first communication pipe **1250** is coupled to the tube **1300**, and the tube **1300** extends to the lower end of the evaporator **20**. In contrast, the second communication pipe **1270** is disposed at the upper end of the evaporator **20**. Consequently, the first communication pipe **1250** and the second communication pipe **1270** extend in different directions.

(293) The first communication pipe **1250** extends so as to be perpendicular to the bottom surface

1213. In contrast, the second communication pipe **1270** extends so as to be inclined to the bottom surface **1213** by an angle smaller than a right angle. The second communication pipe **1270** may extend from the bottom surface **1213** toward the right side wall **1218**.

(294) Meanwhile, the first communication pipe **1250** and the second communication pipe **1270** extend from the location unit **1230**. The directions in which the first communication pipe **1250** and the second communication pipe **1270** extend may be the same.

(295) The first communication pipe **1250** may be provided at the outer circumferential surface thereof with a catching protrusion **1256**. The catching protrusion **1256** may be tapered such that the section thereof gradually decreases downwards. When the tube **1300** is coupled to the first communication pipe **1250**, therefore, the tube **1300** may be prevented from being separated from the catching protrusion **1256**.

(296) The outer circumferential surface of the first communication pipe **1250** may be inserted into the inner circumferential surface of the tube **1300**, whereby the tube **1300** may be coupled to the first communication pipe **1250**.

(297) The second communication pipe **1270** may extend so as not to exceed the extension line of the right side wall **1218**.

(298) In the case in which the housing **1200** is manufactured by injection, it is necessary to manufacture a mold for manufacturing the housing **1200**. If the second communication pipe **1270** extends rightwards further than the right side wall **1218**, it is not easy to manufacture the mold. In addition, costs incurred to manufacture the mold are increased, whereby the cost of manufacturing the differential pressure sensor assembly **1100** is increased.

(299) In this embodiment, therefore, the second communication pipe **1270** extends so as not to be perpendicular to the bottom surface **1213** but to be inclined to the bottom surface **1213**, and extends so as not to exceed the right side wall **1218**.

(300) One end of the second communication pipe **1270** may have a surface cut in a direction parallel to the bottom surface **1213**. Consequently, the sectional area of the second through-hole **1274**, formed in the second communication pipe **1270**, may be increased at the one end of the second communication pipe **1270**.

(301) Since the second communication pipe **1270** is disposed in an inclined state, the second through-hole **1274** and the second hole **1234** are formed at positions that are spaced apart from each other in the leftward-rightward direction.

(302) When defrosting is performed using the heater **50**, ice formed on the evaporator **20** may melt and change into vapor, which may rise.

(303) Since the second through-hole **1274** is disposed at the upper side of the evaporator **20**, as shown in FIG. **24**, vapor rises vertically through the second through-hole **1274**. At this time, the rising vapor cannot directly move to the second hole **1234**, since the second communication pipe **1270** is disposed so as to be inclined.

(304) If the second hole **1234** and the second through-hole **1274** are disposed so as to overlap each other when viewed from above, the rising vapor may be easily introduced into the second hole **1234** through the second through-hole **1274**. As a result, the vapor may be supplied to the differential pressure sensor **1110**, which may cause various problems. In order to prevent this, in this embodiment, the second communication pipe **1270** is disposed so as to be inclined such that the second hole **1234** and the second through-hole **1274** do not overlap each other when viewed from above, and is formed so as to extend sufficiently far.

(305) The second communication pipe **1270** extends longer than the first communication pipe **1250**. Since it is not desirable for one end of the second communication pipe **1270** to extend longer than the right side wall **1218**, as described above, however, the location unit **1230** may be disposed so as to be biased to the left in the space **1224**, as shown in FIG. **24**. Consequently, the second communication pipe **1270** may extend such that the one end of the second communication pipe **1270** does not exceed the right side wall **1218**.

(306) The portion of the bottom surface **1213** between the first communication pipe **1250** and the second communication pipe **1270** may be biased to the side of the bottom surface **1213** at which the first communication pipe **1250** is located, rather than the middle part of the bottom surface **1213**.

(307) The distance **L1** between the location unit **1230** and the left side wall **1216** may be smaller than the distance **L2** between the location unit **1230** and the right side wall **1218**.

(308) The differential pressure sensor **1110** may also be disposed so as to be biased to the left in the space **1224** in order to secure space for extension of the length of the second communication pipe **1270**.

(309) As shown in FIG. **27**, the first through-hole **1254**, formed in the first communication pipe **1250**, may be larger than the first hole **1232**, and the first communication pipe **1250** may be expanded at the portion thereof that abuts the first hole **1232**.

(310) The second through-hole **1274**, formed in the second communication pipe **1270**, may be larger than the second hole **1234**, and the second communication pipe **1270** may be expanded at the portion thereof that abuts the second hole **1234**.

(311) The first port **1112** is coupled to the first hole **1232**, and the second port **1114** is coupled to the second hole **1234**. The section of each of the first port **1112** and the second port **1114** is relatively small, and the section of each of the first through-hole **1254** and the second through-hole **1274** is relatively large.

(312) Water drops may be easily formed in the first through-hole **1254** and the second through-hole **1274**, since the first through-hole and the second through-hole are exposed in the case **35**. In order to discharge the water drops to the outside, it is necessary to increase the size of each of the first through-hole **1254** and the second through-hole **1274** to such an extent that the water drops can be discharged from the first through-hole and the second through-hole. The reason for this is that, if the section of each of the first through-hole and the second through-hole is small, the water drops may easily rise due to a capillary phenomenon, and may not fall.

(313) FIG. **28** is a view showing a differential pressure sensor assembly according to another embodiment of the present invention.

(314) In this embodiment, the differential pressure sensor **1110** is disposed so as to be inclined to the bottom surface **1213** without being perpendicular thereto, unlike the previous embodiment. This embodiment is identical to the previous embodiment except that the installation angle of the differential pressure sensor **1110** is changed, and therefore a duplicate description of the same elements will be omitted.

(315) This embodiment is different from the previous embodiment in that the angle at which the first port **1122** and the first communication pipe **1250** communicate with each other and the angle at which the second port **1124** and the second communication pipe **1270** communicate with each other approximate a right angle.

(316) In addition, the depth of the first hole **1232** and the second hole **1234** may be increased in order to secure the depth of the first port **1122** and the second port **1124**, which are coupled to the location unit **1230**. In addition, the direction in which the first hole **1232** and the second hole **1234** are formed may extend in a direction that is parallel to the bottom surface **1213** in order to achieve easy insertion of the first port **1122** and the second port **1124**.

(317) FIGS. **29** to **36** are views showing a further embodiment of the present invention.

(318) A description of the previous embodiment of the present invention may be equally applied to the embodiment of FIGS. **29** to **36**. However, this embodiment is different from the previous embodiment in that the substrate **1112** is disposed parallel to the bottom surface **1213** of the housing body.

(319) Therefore, a duplicate description of the elements of this embodiment to which the description of the previous embodiment of the present invention is equally applied will be omitted, and only different elements will be described. The description of the previous embodiment of the

present invention is equally applied to the same elements of this embodiment of the present invention in order to describe this embodiment.

(320) In this embodiment, the location surface **1236** is disposed parallel to the bottom surface **1213**. The location surface **1236** may be provided so as to be parallel to the bottom surface **1213** such that the substrate **1112** of the differential pressure sensor **1110** is disposed parallel to the bottom surface **1213**. The location surface **1236** may adjust the position and installation angle of the differential pressure sensor **1110** while being in surface contact with the differential pressure sensor **1110**.

(321) In this embodiment of the present invention, the first port **1122** is disposed parallel to the first communication pipe **1250**, but the second port **1124** is disposed so as not to be parallel to the second communication pipe **1270**.

(322) Since the first port **1122** and the first communication pipe **1250** are parallel to each other, air introduced through the first through-hole **1254**, formed in the first communication pipe **1250**, may be introduced into the first port **1122** while moving vertically. Consequently, it is not necessary to bend the flow path along which air moves in order to reduce the flow-path resistance of air moving between the first communication pipe **1250** and the first port **1122**.

(323) The second port **1124** and the second communication pipe **1270** are not parallel to each other. However, air discharged from the second port **1124** may be discharged through the second communication pipe **1270** even though the air is not redirected 90 degrees or more. Consequently, it is possible to reduce the resistance to air discharged through the second port **1124**, compared to the case in which the angle between the direction in which air moves in the second port **1124** and the direction in which air moves in the second communication pipe **1270** is 90 degrees or more. In addition, the flow path along which air moves may be easily designed, whereby it is possible to easily design and manufacture the housing **1200**.

(324) The present invention is not limited to the above embodiments, and can be modified by those skilled in the art to which the present invention pertains, as can be seen from the scope of the appended claims. Such modified embodiments fall within the scope of the present invention.

(325) The following is the first list of embodiments.

(326) 1. A method of controlling a refrigerator comprising: sensing a differential pressure using a differential pressure sensor for measuring a difference in pressure between a first through-hole, disposed between an inlet, through which air is introduced from a storage compartment, and an evaporator, and a second through-hole, disposed between an outlet, through which air is discharged to the storage compartment, and the evaporator; and

(327) determining that a pipe of the differential pressure sensor is clogged when the differential pressure is less than a set value.

(328) 2. The method according to the first embodiment, further comprising:

(329) calculating an average of differential pressures

(330) before the step of determining that the pipe is clogged, wherein

(331) at the step of determining that the pipe is clogged, the average of differential pressures is compared with the set value.

(332) 3. The method according to the second embodiment, further comprising

(333) determining whether the average of differential pressures is less than a value obtained by subtracting a reference value from a maximum average (a first clogging determination step).

(334) 4. The method according to the third embodiment, wherein

(335) the reference value is less than a first set pressure, based on which it is determined that defrosting of the evaporator is necessary.

(336) 5. The method according to the fourth embodiment, wherein

(337) the reference value is equal to or less than $\frac{1}{3}$ of the first set pressure.

(338) 6. The method according to the second embodiment, further comprising

(339) updating a maximum average with the average of differential pressures when the average of differential pressures is greater than the maximum average.

(340) 7. The method according to the second embodiment, further comprising
(341) determining whether the average of differential pressures is less than a minimum average (a second clogging determination step).
(342) 8. The method according to the seventh embodiment, wherein
(343) the minimum average is a differential pressure value measured in a state in which no frost is formed on the evaporator.
(344) 9. The method according to the first embodiment, wherein
(345) a condition for defrosting the evaporator is changed upon determining that the pipe of the differential pressure sensor is clogged.
(346) 10. The method according to the ninth embodiment, wherein
(347) the changed condition is used to determine whether a predetermined amount of time has elapsed since a compressor was driven.
(348) 11. The method according to the ninth embodiment, wherein
(349) the changed condition is used to
(350) determine whether a specific time has elapsed since a door opened the storage compartment.
(351) 12. The method according to the first embodiment, further comprising
(352) determining whether a fan for generating air flow to supply cool air to the storage compartment is driven
(353) before the step of sensing the differential pressure.
(354) 13. The method according to the first embodiment, further comprising
(355) determining that a door for opening and closing the storage compartment is closed
(356) before the step of sensing the differential pressure.
(357) 14. The method according to the thirteenth embodiment, further comprising
(358) determining whether a predetermined amount of time has elapsed since the door was closed.
(359) 15. The method according to the first embodiment, further comprises
(360) measuring a temperature of the evaporator
(361) at a step of performing defrosting.
(362) 16. The method according to the first embodiment, further comprising
(363) determining whether a period of measuring the differential pressure using the differential pressure sensor is satisfied
(364) before the step of sensing the differential pressure.
(365) 17. A refrigerator comprising: a cabinet having a storage compartment defined therein;
(366) a door for opening and closing the storage compartment;
(367) a case having therein an inlet, through which air is introduced from the storage compartment, and an outlet, through which air is discharged to the storage compartment;
(368) a fan for generating a flow of air that is introduced through the inlet and discharged through the outlet;
(369) a differential pressure sensor provided in the case; and
(370) a controller for determining that a pipe of the differential pressure sensor is clogged when a differential pressure sensed by the differential pressure sensor is less than a set value.
(371) 18. The refrigerator according to the seventeenth embodiment, wherein
(372) the controller calculates an average of differential pressures sensed by the differential pressure sensor and compares the average with the set value.
(373) 19. The refrigerator according to the eighteenth embodiment, wherein
(374) the controller
(375) determines that the pipe of the differential pressure sensor is clogged when the average of differential pressures is less than a value obtained by subtracting a reference value from a maximum average.
(376) 20. The refrigerator according to the nineteenth embodiment, wherein
(377) the reference value is less than a first set pressure, based on which it is determined that

defrosting of an evaporator provided in the case is necessary.

(378) 21. The refrigerator according to the eighteenth embodiment, wherein

(379) the controller

(380) determines that the pipe of the differential pressure sensor is clogged when the average of differential pressures is less than a minimum average.

(381) 22. The refrigerator according to the twenty-first embodiment, wherein

(382) the minimum average is a differential pressure value measured in a state in which no frost is formed on the evaporator.

(383) 23. The refrigerator according to the eighteenth embodiment, wherein

(384) the controller

(385) sets a defrosting time of the evaporator without using the differential pressure measured by the differential pressure sensor upon determining that the pipe of the differential pressure sensor is clogged.

(386) 24. The refrigerator according to the twenty-third embodiment, wherein

(387) the controller

(388) performs control to drive a heater in order to defrost the evaporator when a predetermined amount of time elapses after a compressor is driven.

(389) 25. The refrigerator according to the twenty-third embodiment, wherein

(390) the controller

(391) performs control to drive a heater in order to defrost the evaporator when a specific time elapses after the door opens the storage compartment.

(392) 26. The refrigerator according to the seventeenth embodiment, wherein

(393) the differential pressure sensor comprises:

(394) a first through-hole disposed between the evaporator and the inlet;

(395) a second through-hole disposed between the evaporator and the outlet; and

(396) a main body for interconnecting the first through-hole and the second through-hole, and wherein

(397) the differential pressure sensor senses a difference in pressure between air passing through the first through-hole and air passing through the second through-hole.

(398) The following is the second list of embodiments.

(399) 1. A refrigerator comprising: a cabinet having a storage compartment defined therein;

(400) a door for opening and closing the storage compartment;

(401) a case having therein an inlet, through which air is introduced from the storage compartment, and an outlet, through which air is discharged to the storage compartment;

(402) an evaporator provided in the case for exchanging heat with air to supply cool air;

(403) a heater provided in the case;

(404) a fan for generating a flow of air that is introduced through the inlet and discharged through the outlet;

(405) a sensor provided in the case; and

(406) a controller for performing control to drive the heater based on information sensed by the sensor in order to defrost the evaporator.

(407) 2. The refrigerator according to the first embodiment, wherein

(408) the sensor comprises a flow sensor.

(409) 3. The refrigerator according to the second embodiment, wherein

(410) the flow sensor is provided in the inlet to measure a flow rate of air that is introduced into the case when the fan is driven.

(411) 4. The refrigerator according to the second embodiment, wherein

(412) the flow sensor is provided in the outlet to measure a flow rate of air that is introduced into the case when the fan is driven.

(413) 5. The refrigerator according to the second embodiment, wherein

(414) the controller
(415) performs control to drive the heater in a case in which an amount of moving air, measured by the flow sensor, is reduced to a set value or less when the fan is driven.
(416) 6. The refrigerator according to the first embodiment, wherein
(417) the sensor comprises a differential pressure sensor, wherein
(418) the differential pressure sensor comprises:
(419) a first through-hole disposed between the evaporator and the inlet;
(420) a second through-hole disposed between the evaporator and the outlet; and
(421) a main body for interconnecting the first through-hole and the second through-hole, and wherein
(422) the differential pressure sensor senses a difference in pressure between air passing through the first through-hole and air passing through the second through-hole.
(423) 7. The refrigerator according to the sixth embodiment, wherein
(424) the outlet is disposed higher than the evaporator, and
(425) the inlet is disposed lower than the evaporator.
(426) 8. The refrigerator according to the seventh embodiment, wherein
(427) the main body comprises:
(428) a first pipe having the first through-hole formed therein;
(429) a second pipe having the second through-hole formed therein; and
(430) a connection member for interconnecting the first pipe and the second pipe.
(431) 9. The refrigerator according to the eighth embodiment, wherein
(432) the connection member is disposed higher than the evaporator.
(433) 10. The refrigerator according to the ninth embodiment, wherein
(434) the first pipe and the second pipe extend higher than the evaporator.
(435) 11. The refrigerator according to the sixth embodiment, further comprising:
(436) a door switch for sensing whether the door opens and closes the storage compartment, wherein
(437) the controller performs control such that the differential pressure sensor senses the difference in pressure when the door switch senses that the door to the storage compartment is closed.
(438) 12. The refrigerator according to the sixth embodiment, wherein
(439) when the fan is driven,
(440) the controller performs control such that the differential pressure sensor senses the difference in pressure.
(441) 13. The refrigerator according to the sixth embodiment, further comprising:
(442) a timer for sensing an elapsed time, wherein
(443) the controller performs control such that the differential pressure sensor senses the difference in pressure when a time set by the timer elapses.
(444) 14. The refrigerator according to the first embodiment, further comprising:
(445) an evaporator temperature sensor for measuring a temperature of the evaporator, wherein
(446) the controller performs control to stop driving the heater in a case in which the temperature of the evaporator increases to a set temperature when defrosting is performed.
(447) 15. A method of controlling a refrigerator comprising: sensing a differential pressure using a differential pressure sensor for measuring a difference in pressure between a first through-hole, disposed between an inlet, through which air is introduced from a storage compartment, and an evaporator, and a second through-hole, disposed between an outlet, through which air is discharged to the storage compartment, and the evaporator; and
(448) driving a heater to perform defrosting of the evaporator when the differential pressure is greater than a set pressure.
(449) 16. The method according to the fifteenth embodiment, further comprising
(450) determining whether a fan for generating air flow to supply cool air to the storage

compartment is driven

(451) before the step of sensing the differential pressure.

(452) 17. The method according to the fifteenth embodiment, further comprising

(453) determining that a door for opening and closing the storage compartment is closed

(454) before the step of sensing the differential pressure.

(455) 18. The method according to the seventeenth embodiment, further comprising

(456) determining whether a predetermined amount of time has elapsed since the door was closed.

(457) 19. The method according to the fifteenth embodiment, further comprising

(458) measuring a temperature of the evaporator

(459) at the step of performing defrosting.

(460) 20. The method according to the fifteenth embodiment, further comprising

(461) determining whether a period of measuring the differential pressure using the differential pressure sensor is satisfied

(462) before the step of sensing the differential pressure.

(463) 21. The method according to the fifteenth embodiment, wherein

(464) the differential pressure is an average of differential pressures.

(465) The following is the third list of embodiments.

(466) 1. A method of controlling a refrigerator comprising: sensing a differential pressure using a differential pressure sensor for measuring a difference in pressure between a first through-hole, disposed between an inlet, through which air is introduced from a storage compartment, and an evaporator, and a second through-hole, disposed between an outlet, through which air is discharged to the storage compartment, and the evaporator;

(467) driving a heater to perform defrosting of the evaporator when the differential pressure is greater than a first set pressure; and

(468) changing the first set pressure to a set value when the differential pressure remeasured by the differential pressure sensor is greater than a second set pressure after defrosting is finished.

(469) 2. The method according to the first embodiment, wherein

(470) the first set pressure is higher than the second set pressure.

(471) 3. The method according to the first embodiment, wherein

(472) the changing the first set pressure to the set value is reducing the first set pressure.

(473) 4. The method according to the third embodiment, wherein

(474) the reduced first set pressure is equal to or higher than the second set pressure.

(475) 5. The method according to the first embodiment, wherein

(476) when the evaporator is defrosted again,

(477) defrosting is performed in a case in which the differential pressure is greater than the changed first set pressure.

(478) 6. The method according to the first embodiment, wherein

(479) the step of changing the first set pressure to the set value comprises

(480) changing a first set temperature, at which driving of the heater is stopped when the evaporator is defrosted, to a set value.

(481) 7. The method according to the sixth embodiment, wherein

(482) the changing the first set temperature to the set value is increasing the first set temperature.

(483) 8. The method according to the first embodiment, further comprising

(484) determining whether the compressor is driven

(485) after the step of performing defrosting.

(486) 9. The method according to the first embodiment, further comprising

(487) determining whether a temperature of the storage compartment reaches a second set temperature and, upon determining that the temperature of the storage compartment does not reach the second set temperature, sensing the differential pressure

(488) after the step of changing the first set pressure to the set value.

(489) 10. The method according to the first embodiment, further comprising
(490) maintaining the first set pressure as an initial value when the differential pressure remeasured by the differential pressure sensor is less than the second set pressure after defrosting is finished.
(491) 11. The method according to the tenth embodiment, wherein
(492) at the step of maintaining the first set pressure as the initial value,
(493) maintaining a first set temperature, at which driving of the heater is stopped when the evaporator is defrosted, as an initial value.
(494) 12. The method according to the first embodiment, wherein
(495) the step of changing the first set pressure to the set value is performed in a cycle in which a compressor starts to be initially driven after defrosting is finished.
(496) 13. The method according to the first embodiment, further comprising
(497) determining whether a fan for generating air flow to supply cool air to the storage compartment is driven
(498) before the step of sensing the differential pressure.
(499) 14. The method according to the first embodiment, further comprising
(500) determining that a door for opening and closing the storage compartment is closed
(501) before the step of sensing the differential pressure.
(502) 15. The method according to the fourteenth embodiment, further comprising
(503) determining whether a predetermined amount of time has elapsed since the door was closed.
(504) 16. The method according to the first embodiment, further comprising
(505) measuring a temperature of the evaporator
(506) at the step of performing defrosting.
(507) 17. The method according to the first embodiment, further comprising
(508) determining whether a period of measuring the differential pressure using the differential pressure sensor is satisfied
(509) before the step of sensing the differential pressure.
(510) 18. A refrigerator comprising: a cabinet having a storage compartment defined therein;
(511) a door for opening and closing the storage compartment;
(512) a case having therein an inlet, through which air is introduced from the storage compartment, and an outlet, through which air is discharged to the storage compartment;
(513) an evaporator provided in the case for exchanging heat with air to supply cool air;
(514) a heater provided in the case;
(515) a fan for generating a flow of air that is introduced through the inlet and discharged through the outlet;
(516) a sensor provided in the case; and
(517) a controller for performing control to drive the heater based on information sensed by the sensor in order to defrost the evaporator, wherein
(518) the controller determines whether residual ice remains on the evaporator based on the information sensed by the sensor after defrosting performed by the heater is finished.
(519) 19. The refrigerator according to the eighteenth embodiment, wherein
(520) the sensor comprises a flow sensor.
(521) 20. The refrigerator according to the nineteenth embodiment, wherein
(522) the flow sensor is provided in the inlet to measure a flow rate of air that is introduced into the case when the fan is driven.
(523) 21. The refrigerator according to the nineteenth embodiment, wherein
(524) the flow sensor is provided in the outlet to measure a flow rate of air that is introduced into the case when the fan is driven.
(525) 22. The refrigerator according to the nineteenth embodiment, wherein
(526) the controller
(527) changes a set value of a flow rate of air for defrosting the evaporator upon determining that

residual ice remains on the evaporator.

(528) 23. The refrigerator according to the nineteenth embodiment, wherein

(529) the controller

(530) changes a set value of a temperature of the evaporator for finishing defrosting of the evaporator upon determining that residual ice remains on the evaporator.

(531) 24. The refrigerator according to the eighteenth embodiment, wherein

(532) the sensor comprises a differential pressure sensor, wherein

(533) the differential pressure sensor comprises:

(534) a first through-hole disposed between the evaporator and the inlet;

(535) a second through-hole disposed between the evaporator and the outlet; and

(536) a main body for interconnecting the first through-hole and the second through-hole, and wherein

(537) the differential pressure sensor senses a difference in pressure between air passing through the first through-hole and air passing through the second through-hole.

(538) 25. The refrigerator according to the twenty-fourth embodiment, wherein

(539) the controller performs control to drive the heater in order to perform defrosting of the evaporator when the differential pressure measured by the differential pressure sensor reaches a first set pressure.

(540) 26. The refrigerator according to the twenty-fifth embodiment, wherein

(541) the controller performs control to reduce the first set pressure when the differential pressure measured by the differential pressure sensor is greater than a second set pressure after defrosting is finished.

(542) 27. The refrigerator according to the twenty-sixth embodiment, wherein

(543) the first set pressure is greater than the second set pressure.

(544) 28. The refrigerator according to the twenty-fifth embodiment, wherein

(545) the controller performs control to heat the evaporator to a higher temperature at a time of performing defrosting when the differential pressure measured by the differential pressure sensor is greater than a second set pressure after defrosting is finished.

(546) 29. The refrigerator according to the twenty-fifth embodiment, wherein

(547) the controller performs control to increase a driving time of the heater at a time of performing defrosting when the differential pressure measured by the differential pressure sensor is greater than a second set pressure after defrosting is finished.

(548) The following is the fourth list of embodiments.

(549) 1. A differential pressure sensor assembly comprising: a differential pressure sensor comprising a first port, through which air is introduced, a second port, through which the air, introduced through the first port, is discharged, and a substrate, on which the first port and the second port are installed; and

(550) a housing, in which the differential pressure sensor is installed, wherein

(551) the housing comprises:

(552) a housing body having a space defined therein, the differential pressure sensor being accommodated in the space;

(553) a first communication pipe provided in the housing body, the first communication pipe communicating with the first port; and

(554) a second communication pipe communicating with the second port, and wherein

(555) the first communication pipe and the second communication pipe are not disposed parallel to each other but are disposed so as to be inclined to each other.

(556) 2. The differential pressure sensor assembly according to the first embodiment, wherein

(557) the first communication pipe and the second communication pipe extend from a same surface of the housing body.

(558) 3. The differential pressure sensor assembly according to the first embodiment, wherein

(559) the first communication pipe and the second communication pipe are provided at a bottom surface of the housing body.

(560) 4. The differential pressure sensor assembly according to the first embodiment, wherein (561) the space

(562) is defined by a front wall, a left side wall, a right side wall, a ceiling, and a bottom surface of the housing body.

(563) 5. The differential pressure sensor assembly according to the fourth embodiment, wherein (564) the housing comprises an opening formed in a rear surface of the housing body, and (565) the opening is defined by edges of the left side wall, the right side wall, the ceiling, and the bottom surface.

(566) 6. The differential pressure sensor assembly according to the fourth embodiment, wherein (567) the ceiling is disposed so as to be inclined to the bottom surface.

(568) 7. The differential pressure sensor assembly according to the sixth embodiment, wherein (569) the ceiling is disposed so as to be closer to the bottom surface in a rearward direction.

(570) 8. The differential pressure sensor assembly according to the fourth embodiment, wherein (571) the first communication pipe extends so as to be perpendicular to the bottom surface.

(572) 9. The differential pressure sensor assembly according to the fourth embodiment, wherein (573) the second communication pipe extends so as to be inclined to the bottom surface by an angle smaller than a right angle.

(574) 10. The differential pressure sensor assembly according to the ninth embodiment, wherein (575) the second communication pipe extends from the bottom surface toward the right side wall.

(576) 11. The differential pressure sensor assembly according to the ninth embodiment, wherein (577) the second communication pipe extends so as not to exceed an extension line of the right side wall.

(578) 12. The differential pressure sensor assembly according to the ninth embodiment, wherein (579) one end of the second communication pipe has a surface cut in a direction parallel to the bottom surface.

(580) 13. The differential pressure sensor assembly according to the fourth embodiment, wherein (581) a second hole, formed in a portion of the second communication pipe that communicates with the space, and a second through-hole, formed in one end of the second communication pipe, are disposed at positions that are spaced apart from each other when viewed from above.

(582) 14. The differential pressure sensor assembly according to the fourth embodiment, wherein (583) a portion of the bottom surface between the first communication pipe and the second communication pipe is biased to one side of the bottom surface at which the first communication pipe is located, rather than a middle part of the bottom surface.

(584) 15. The differential pressure sensor assembly according to the fourth embodiment, wherein (585) a location unit, in which the differential pressure sensor is located, is provided in the space.

(586) 16. The differential pressure sensor assembly according to the fifteenth embodiment, wherein (587) the location unit comprises:

(588) a location surface disposed in surface contact with the differential pressure sensor;
(589) and

(590) a first hole and a second hole formed in the location surface, and wherein

(591) the first hole communicates with the first communication pipe, and

(592) the second hole communicates with the second communication pipe.

(593) 17. The differential pressure sensor assembly according to the sixteenth embodiment, wherein

(594) the location surface is disposed so as to be inclined to the bottom surface.

(595) 18. The differential pressure sensor assembly according to the sixteenth embodiment, wherein

(596) a first through-hole, formed in the first communication pipe, is larger than the first hole, and

(597) the first communication pipe is expanded at a portion thereof that abuts the first hole.

(598) 19. The differential pressure sensor assembly according to the sixteenth embodiment, wherein

(599) a second through-hole, formed in the second communication pipe, is larger than the second hole, and

(600) the second communication pipe is expanded at a portion thereof that abuts the second hole.

(601) 20. The differential pressure sensor assembly according to the sixteenth embodiment, wherein

(602) the location unit is disposed so as to be biased to a left in the space.

(603) 21. The differential pressure sensor assembly according to the sixteenth embodiment, wherein

(604) a distance between the location unit and the left side wall is smaller than a distance between the location unit and the right side wall.

(605) 22. The differential pressure sensor assembly according to the sixteenth embodiment, wherein

(606) the location surface is disposed so as to be perpendicular to the bottom surface.

(607) 23. The differential pressure sensor assembly according to the first embodiment, wherein

(608) the first communication pipe or the second communication pipe has a hollow shape.

(609) 24. The differential pressure sensor assembly according to the first embodiment, wherein

(610) the first communication pipe is provided at an outer circumferential surface thereof with a catching protrusion.

(611) 25. The differential pressure sensor assembly according to the twenty-fourth embodiment, wherein

(612) the catching protrusion is tapered such that a section thereof gradually decreases downwards.

(613) 26. A refrigerator comprising: a cabinet having a storage compartment defined therein;

(614) a door for opening and closing the storage compartment;

(615) a case having therein an inlet, through which air is introduced from the storage compartment, and an outlet, through which air is discharged to the storage compartment;

(616) an evaporator provided in the case for exchanging heat with air to supply cool air; and

(617) a differential pressure sensor assembly provided in the case, wherein

(618) the differential pressure sensor assembly comprises:

(619) a differential pressure sensor comprising a first port, through which air is introduced, a second port, through which the air, introduced through the first port, is discharged, and a substrate, on which the first port and the second port are installed; and

(620) a housing, in which the differential pressure sensor is installed, wherein

(621) the housing comprises:

(622) a housing body having a space defined therein, the differential pressure sensor being accommodated in the space;

(623) a first communication pipe provided in the housing body, the first communication pipe communicating with the first port; and

(624) a second communication pipe communicating with the second port, and wherein

(625) the first communication pipe and the second communication pipe extend above the evaporator, and

(626) a tube, which extends below the evaporator, is coupled to the first communication pipe.

(627) 27. The refrigerator according to the twenty-sixth embodiment, wherein

(628) the first communication pipe and the second communication pipe are not disposed parallel to each other but are disposed so as to be inclined to each other.

(629) 28. A differential pressure sensor assembly comprising: a differential pressure sensor comprising a first port, through which air is introduced, a second port, through which the air, introduced through the first port, is discharged, and a substrate, on which the first port and the

second port are installed; and
(630) a housing, in which the differential pressure sensor is installed, wherein
(631) the housing comprises:
(632) a housing body having a space defined therein, the differential pressure sensor being accommodated in the space;
(633) a first communication pipe provided in the housing body, the first communication pipe communicating with the first port; and
(634) a second communication pipe communicating with the second port, and wherein
(635) the first port is disposed parallel to the first communication pipe, and
(636) the first communication pipe and the second communication pipe are not disposed parallel to each other but are disposed so as to be inclined to each other.
(637) 29. The differential pressure sensor assembly according to the twenty-eighth embodiment, wherein
(638) a location unit comprises:
(639) a location surface disposed in surface contact with the differential pressure sensor;
(640) and
(641) a first hole and a second hole formed in the location surface, and wherein
(642) the first hole communicates with the first communication pipe, and
(643) the second hole communicates with the second communication pipe.
(644) 30. The differential pressure sensor assembly according to the twenty-ninth embodiment, wherein
(645) the location surface is disposed parallel to a bottom surface.
(646) 31. The differential pressure sensor assembly according to the thirtieth embodiment, wherein
(647) a first through-hole, formed in the first communication pipe, is larger than the first hole, and
(648) the first communication pipe is expanded at a portion thereof that abuts the first hole.
(649) 32. The differential pressure sensor assembly according to the thirty-first embodiment, wherein
(650) the first port is disposed in a center of the first through-hole when viewed from above, and
(651) the first port is disposed parallel to a direction in which the first communication pipe extends.

Claims

1. A refrigerator comprising: a cabinet that defines a storage compartment; a door configured to open and close at least a portion of the storage compartment; an inlet configured to receive air from the storage compartment, the inlet being disposed rearward relative to a rear surface of the storage compartment; an outlet configured to discharge air to the storage compartment, the outlet being disposed rearward relative to the rear surface of the storage compartment and disposed higher than the inlet; a fan configured to generate air flow to cause air to enter the inlet and discharge through the outlet, the fan being configured to generate the air flow in an upward direction from the inlet to the outlet; an evaporator that is located at the cabinet, that is configured to exchange heat with air, and that is configured to supply cool air to the storage compartment, the evaporator being arranged below the outlet and above the inlet; and a differential pressure sensor located at the cabinet and configured to produce a single value representing a differential pressure between two positions that are connected via pipes, the pipes comprising: a first pipe that defines a first through-hole between the evaporator and the inlet, and a second pipe that defines a second through-hole between the evaporator and the outlet, wherein the first pipe or the second pipe comprises a first expansion part that extends from an end of a corresponding pipe of the first pipe or the second pipe, wherein a lower part of the first expansion part defines the first through-hole or the second through-hole at a side surface of the corresponding pipe, wherein a diameter of the first expansion part increases toward a lower end of the first expansion part, and wherein the differential pressure sensor is

configured to calculate the differential pressure between the two positions without measuring absolute pressure values at the two positions.

2. The refrigerator according to claim 1, wherein the differential pressure sensor is a single pressure sensor that is provided in the refrigerator to sense the differential pressure between the first through-hole and the second through-hole.
3. The refrigerator according to claim 1, wherein the differential pressure sensor is installed in a space in which air, that has passed through the storage compartment, is cooled by the evaporator, and wherein the differential pressure sensor is configured to sense a difference in pressure between the air passing through the first through-hole and the air passing the second through-hole.
4. The refrigerator according to claim 3, wherein the first through-hole and the second through-hole are installed at different heights.
5. The refrigerator according to claim 1, wherein the first expansion part comprises a second expansion part that extends from the lower part of the first expansion part, and wherein a diameter of the second expansion part increases toward a lower end of the second expansion part.
6. The refrigerator according to claim 5, wherein a lower part of the second expansion part lacks a hole that allows air to move upward from the lower part of the second expansion part.
7. The refrigerator according to claim 5, wherein the second expansion part extends radially outward of the first expansion part.
8. The refrigerator according to claim 5, wherein a sectional area of the lower end of the second expansion part is greater than a sectional area of the lower end of the first expansion part.
9. The refrigerator according to claim 1, further comprising: a case that is disposed rearward relative to the rear surface of the storage compartment and that extends upward along the rear surface of the storage compartment, the case defining the inlet and the outlet, wherein the fan and the evaporator are disposed in the case.
10. The refrigerator according to claim 1, wherein the side surface of the corresponding pipe is a circumferential surface of the first expansion part and extends in a longitudinal direction of the corresponding pipe.
11. The refrigerator according to claim 10, wherein the differential pressure sensor further comprises a cover that covers the lower end of the first expansion part.
12. A refrigerator comprising: a cabinet that defines a storage compartment; a door configured to open and close at least a portion of the storage compartment; an inlet configured to receive air from the storage compartment, the inlet being disposed rearward relative to a rear surface of the storage compartment; an outlet configured to discharge air to the storage compartment, the outlet being disposed rearward relative to the rear surface of the storage compartment and disposed higher than the inlet; a fan configured to generate air flow to cause air to enter the inlet and discharge through the outlet, the fan being configured to generate the air flow in an upward direction from the inlet to the outlet; an evaporator that is located at the cabinet, that is configured to exchange heat with air, and that is configured to supply cool air to the storage compartment, the evaporator being arranged below the outlet and above the inlet; a differential pressure sensor located at the cabinet and configured to produce a single value representing a differential pressure between two positions that are connected via a pipe; a heater located at the cabinet; and a controller configured to control the refrigerator, wherein the controller is configured to control driving of the heater to defrost the evaporator based on the differential pressure sensed by the differential pressure sensor, and wherein the differential pressure sensor is configured to calculate the differential pressure between the two positions without measuring absolute pressure values at the two positions, the two positions including (i) a position between the evaporator and the inlet and (ii) a position between the evaporator and the outlet, wherein the differential pressure sensor comprises: a first pipe that defines a first through-hole between the evaporator and the inlet, a second pipe that defines a second through-hole between the evaporator and the outlet, and a connection member that is located vertically above the evaporator and connects upper ends of the first pipe and the second

pipe to each other, and wherein the differential pressure sensor is a single pressure sensor that is provided in the refrigerator to sense the differential pressure between the first through-hole and the second through-hole.

13. The refrigerator according to claim 12, further comprising an evaporator temperature sensor configured to measure a temperature of the evaporator, wherein the controller is configured to: drive the heater to defrost the evaporator, and stop driving of the heater in response to the measured temperature of the evaporator being increased to a set temperature.

14. The refrigerator according to claim 12, further comprising a door switch configured to sense whether the door opens and closes at least a portion of the storage compartment, wherein the controller is configured to, based on the door switch sensing that the door closes at least a portion of the storage compartment, control the differential pressure sensor to sense a difference in air pressure, or control a flow sensor to sense a flow rate.

15. The refrigerator according to claim 12, wherein the controller is configured to, based on the fan being driven, control the differential pressure sensor to sense a difference in air pressure, or control a flow sensor to sense a flow rate.

16. The refrigerator according to claim 12, wherein the controller determines whether a previous defrosting is performed normally or not, based on the differential pressure sensed by the differential pressure sensor.

17. The refrigerator according to claim 12, wherein the controller determines whether the differential pressure sensor breaks down, based on the differential pressure sensed by the differential pressure sensor.

18. A refrigerator comprising: a cabinet that defines a storage compartment; a door configured to open and close at least a portion of the storage compartment; an inlet configured to receive air from the storage compartment, the inlet being disposed rearward relative to a rear surface of the storage compartment; an outlet configured to discharge air to the storage compartment, the outlet being disposed rearward relative to the rear surface of the storage compartment and disposed higher than the inlet; a fan configured to generate air flow to cause air to enter the inlet and discharge through the outlet, the fan being configured to generate the air flow in an upward direction from the inlet to the outlet; an evaporator that is located at the cabinet, that is configured to exchange heat with air, and that is configured to supply cool air to the storage compartment, the evaporator being arranged below the outlet and above the inlet; and a differential pressure sensor located at the cabinet and configured to produce a single value representing a differential pressure between two positions that are connected via pipes, the pipes comprising: a first pipe that defines a first through-hole between the evaporator and the inlet, the first through-hole being oriented down toward the inlet, and a second pipe that defines a second through-hole between the evaporator and the outlet, the second through-hole being located vertically above the first through-hole and oriented down toward the evaporator, and wherein the differential pressure sensor is configured to calculate the differential pressure between the two positions without measuring absolute pressure values at the two positions.
