

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250258269

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Lehmann; Franz et al.

METHOD AND SYSTEM FOR CALCULATING AND ASSIGNING USE COORDINATES TO STATIONARY RADIO TRANSCEIVERS OF A LOCALIZATION SYSTEM

Abstract

A method calculates and assigns use coordinates to stationary radio transceivers of a localization system. The localization system includes a plurality of the stationary radio transceivers. The localization system determines multiple first relative location references between the radio transceivers. The method includes: providing additional information including multiple planar coordinates; and calculating and assigning the use coordinates for each of the stationary radio transceivers based on the additional information and the first relative location references.

Inventors: Lehmann; Franz (Dresden, DE), Weber; Richard (Dresden, DE)

Applicant: TRUMPF TRACKING TECHNOLOGIES GMBH (Ditzingen, DE); ZIGPOS GMBH (Dresden, DE)

Family ID: 1000008618439

Appl. No.: 19/193981

Filed: April 30, 2025

Foreign Application Priority Data

DE 10 2022 128 971.0

Nov. 02, 2022

Related U.S. Application Data

parent WO continuation PCT/EP2023/079655 20231024 PENDING child US 19193981

Publication Classification

Int. Cl.: G01S5/02 (20100101)

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of International Application No. PCT/EP2023/079655 (WO 2024/094498 A1), filed on Oct. 24, 2023, and claims benefit to German Patent Application No. DE 10 2022 128 971.0, filed on Nov. 2, 2022. The aforementioned applications are hereby incorporated by reference herein.

FIELD

[0002] The invention relates to a method and device for calculating and assigning use coordinates to stationary radio transceivers of a localization system. The invention further relates to a system for calculating and assigning use coordinates to stationary radio transceivers of a localization system.

BACKGROUND

[0003] From DE102018110145A, an indoor tracking system with spatially fixed transmitting/receiving units and mobile transmitting/receiving units is known.

[0004] Localization systems are based on the calculation of distances and/or angles to spatial points with known coordinates. Spatial points with known coordinates are typically stationary radio transceivers, also called anchors. When setting up the localization system, it may therefore be necessary to determine the coordinates of the anchors.

SUMMARY

[0005] In an embodiment, the present disclosure provides a method for calculating and assigning use coordinates to stationary radio transceivers of a localization system. The localization system includes a plurality of the stationary radio transceivers. The localization system determines multiple first relative location references between the radio transceivers. The method includes: providing additional information including multiple planar coordinates; and calculating and assigning the use coordinates for each of the stationary radio transceivers based on the additional information and the first relative location references.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0006] Subject matter of the present disclosure will be described in even greater detail below based on the exemplary figures. All features described and/or illustrated herein can be used alone or combined in different combinations. The features and advantages of various embodiments will become apparent by reading the following detailed description with reference to the attached drawings, which illustrate the following:

[0007] FIG. 1a shows a schematic representation of stationary radio transceivers and relative first location references between the radio transceivers according to an embodiment of the present invention;

[0008] FIG. 1b shows a further schematic representation of stationary radio transceivers and relative first location references between the radio transceivers according to an embodiment of the present invention;

[0009] FIG. 2 shows a schematic representation of a reference map with planar coordinates according to an embodiment of the present invention;

[0010] FIG. 3 shows a schematic representation of a control map according to an embodiment of

the present invention;

[0011] FIG. 4 shows a schematic representation of the determination of a position of a mobile radio transceiver according to an embodiment of the present invention;

[0012] FIG. 5 shows a schematic representation of the use of a mobile radio transmitter to improve the use coordinates according to an embodiment of the present invention; and

[0013] FIG. 6 shows a flow chart according to an embodiment of the present invention.

DETAILED DESCRIPTION

[0014] Embodiments of the present invention simplify the determination of the coordinates of the anchors.

[0015] Embodiments of the present invention can so by a method for calculating and assigning use coordinates to stationary radio transceivers of a localization system, wherein the localization system comprises a plurality of stationary radio transceivers, wherein the localization system determines multiple first relative location references between the radio transceivers, in particular embodiments by means of ultra-wideband radio technology, wherein additional information is provided, wherein the additional information includes multiple planar coordinates, wherein use coordinates are calculated and assigned for each of the stationary radio transceivers by means of the additional information and the first relative location references.

[0016] The relative first location references can be determined as distances and/or angles. The distance between two stationary radio transmitters can be determined, for example, by a travel time measurement of radio signals between the stationary radio transmitters. Very accurate distance measurement is possible, particularly when using ultra-wideband radio technology. Alternatively or in addition to the distance, reception angles of radio signals can be determined. A stationary radio transmitter with multiple antennas or an antenna array can determine the angle from which a radio signal is received.

[0017] From the first relative location references, a map can be created, for example by means of trilateration and/or triangulation, which indicates the positions of the stationary radio transmitters in relation to each other. A map created in this way can be unambiguous or ambiguous.

[0018] Planar coordinates indicate coordinates at which stationary radio transmitters are preferably present. Planar coordinates can remain unoccupied. Likewise, stationary radio transmitters can be present at other coordinates that are not planar coordinates. In preferred embodiments, a plurality of the stationary radio transmitters are substantially each present at one of the planar coordinates.

[0019] Based on the planar coordinates, the use coordinates of the stationary radio transceivers can be calculated and the use coordinates can be assigned to the stationary radio transceivers.

[0020] The use coordinates are the coordinates assigned to the stationary radio transceivers that are used when using the localization system. Based on the use coordinates of the stationary radio transceivers, positions of mobile radio transceivers can be determined.

[0021] The planar coordinates are, in a preferred embodiment, taken from a reference map. The reference map shows the planned positions of the stationary radio transmitters. Other objects such as walls, for example, can be recorded in the reference map. The planar coordinates are thus directly related to surrounding objects. In a preferred embodiment, at least one wall is recorded in the reference map and the wall is extracted from the reference map by means of image processing, wherein the wall is taken into account in the calculation and assignment of the use coordinates. Reflections of the radio signals on the wall can thus be taken into account.

[0022] In one embodiment, a graphical user interface is provided for entering the planar coordinates into the reference map. When entered into a digital map, the positions can be used directly as planar coordinates.

[0023] In an alternative embodiment, the planar coordinates are extracted from the reference map using image processing. The planar coordinates can, for example, be noted in the form of predetermined symbols in the reference map, so that the predetermined symbols are recognized by means of image processing and their position in the map is determined. This makes it very easy to

determine the planar coordinates from a human-readable representation.

[0024] In a further embodiment, the planar coordinates originate from a previous installation of the localization system. The procedure then checks whether the stationary radio transmitters have remained in their old positions. The set-up of the localization system can be checked and corrected very easily in this way. A warning is, in a preferred embodiment, issued if the use coordinates deviate from the planar coordinates by more than a predetermined threshold value. The warning informs the user that the use coordinates do not match the planar coordinates and that, consequently, the set-up of the localization system has changed. This can happen, for example, if stationary radio transceivers have been relocated.

[0025] In a preferred embodiment, the use coordinates are calculated such that second relative location references between the use coordinates substantially correspond to the first relative location references. This substantially means that the measured first relative location references have measurement uncertainties. It may therefore be impossible to fulfill all the first relative location references perfectly. In this case, the use coordinates are calculated in such a way that the deviation is optimized as far as possible for the application. Deviations may be weighted with the measurement uncertainties if necessary, i.e., if the measurement uncertainty is large, a larger deviation is tolerated than if the measurement uncertainty is small.

[0026] In a further preferred embodiment, the use coordinates are calculated for a plurality of the stationary radio transmitters such that differences between the respective use coordinates and the respective nearest planar coordinates are minimized. In other words, the use coordinates are calculated such that as many use coordinates as possible are as close as possible to planar coordinates. The procedure thus ensures that the use coordinates correspond as closely as possible to the planar coordinates.

[0027] In a particularly preferred embodiment, the differences between the first and second relative location references and between the respective use coordinates and the respective nearest planar coordinates are simultaneously minimized. The calculated usage data then forms a compromise between the best possible reproduction of the first relative location references and the approximation to the planar coordinates.

[0028] In a preferred embodiment, the differences between the respective use coordinates and the respective nearest planar coordinates and/or the first and second relative location relationships are minimized according to a linear or quadratic metric, and in particular embodiments, the metric of the least error squares.

[0029] In a preferred embodiment, at least one of the planar coordinates is assigned to one of the stationary radio transceivers. For this stationary radio transceiver, the difference between the use coordinates and the assigned planar coordinates is minimized. The assigned planar coordinate is not necessarily the closest planar coordinate.

[0030] In a preferred embodiment, the use coordinates are visualized in a control map. The control map can be based on the reference map. The visualization enables a very easy control of the calculated and assigned use coordinates. In a particularly preferred embodiment, the planar coordinates are visualized in addition to the use coordinates. This makes it easy to check the deviation of the use coordinates from the planar coordinates.

[0031] In a further preferred embodiment, at least one of the stationary radio transceivers outputs an acoustic or visual signal and the use coordinates of the signal-outputting stationary radio transceiver are visualized on the control map. In a preferred embodiment, a stationary radio transceiver can be selected and triggered to output a signal by means of a user interface.

[0032] In a preferred embodiment, a mobile radio transceiver is moved in an environment of the stationary radio transmitters, wherein third relative location references between the stationary radio transmitters and the mobile radio transmitter are determined, wherein the third relative location references are taken into account when calculating the use coordinates. How the third relative location references can be used is known from the dissertation "Automatisierte Integration von

funkbasierten Sensornetzen auf Basis simultaner Lokalisierung und Kartenerstellung” [“Automated integration of radio-based sensor networks based on simultaneous localization and mapping”] by Richard Weber, which can be accessed at <https://nbn-resolving.org/urn:nbn:de:bsz:14-qucosa2-752459>. The contents of the dissertation are hereby incorporated in their entirety by reference.

[0033] Embodiments of the present invention can further comprise a system for calculating and assigning use coordinates to stationary radio transceivers of a localization system, wherein the system comprises a plurality of stationary radio transceivers and a computing unit, wherein the computing unit is communicatively coupled to the stationary radio transceivers, wherein the computing unit has at least one interface for reading additional information, wherein the computing unit is provided and configured to carry out a method as described above.

[0034] In a preferred embodiment, the interface is a user interface, and in particular embodiments, a graphical user interface. The user interface can be used, for example, to enter planar coordinates or to output maps such as a reference map or a control map.

[0035] In a preferred embodiment, the interface is connected to a memory, wherein planar coordinates, and in particular embodiments in the form of a reference map, are stored in the memory.

[0036] Furthermore, embodiments of the present invention can comprise a computer program product, wherein the computer program product can be loaded directly into the internal memory of a digital computer and comprises software sections with which the steps according to a method according to an embodiment of the present invention are carried out when the computer program product is executed on the computer.

[0037] In a preferred embodiment, the computer program product is stored in a memory, and in particular embodiments a non-volatile memory.

[0038] The following description of preferred embodiments serves to explain embodiments of the present invention in greater detail with reference to the drawings.

[0039] Elements that are the same or have equivalent functions are provided with the same reference signs in all of the figures.

[0040] FIGS. **1a** and **1b** show a localization system **100** with a plurality of stationary radio transceivers **102**. The stationary radio transceivers **102** are configured to send and receive radio signals and to determine distances between the radio transceivers from the travel time of the radio signals between the radio transceivers **102**. In a variant, reception angles of the radio signals can be determined instead of the distances or in addition to the distances. It is possible to determine an angle, for example, using multiple receiving antennas on a radio transceiver or an antenna array. Distances and/or angles are referred to as the first relative location relationship **104**.

[0041] Based on the first relative location relationships **104** between the stationary radio transceivers **102**, the relative positions of the stationary radio transceivers to each other can be determined. FIGS. **1a** and **1b** show two possible relative positions of the stationary radio transceivers **102** with identical first relative location relationships **104**. Whether clear relative positions of the stationary radio transceivers **102** can be determined from the first relative location relationships **104** between the stationary radio transceivers **102** depends on the individual case.

[0042] A reference map **106** is shown in FIG. **2**. The reference map **106** shows walls **107** and planar coordinates **108**. For reasons of clarity, not all walls **107** and not all planar coordinates **108** are provided with reference symbols. The planar coordinates **108** indicate where stationary radio transceivers are to be expected relative to the walls **107**. The reference map **106** can be in the form of a digital image, for example as a pixel representation or as a vector graphic. By means of image processing, the coordinates of the planar coordinates **108** and the walls **107** can be extracted from the digital image.

[0043] A control map **114** is shown in FIG. **3**. The control map **114** shows the use coordinates **110** of the stationary radio transceivers **102** together with the walls **107** and the planar coordinates **108**. In addition, second relative location relationships **112** between the use coordinates **110** are shown.

For reasons of clarity, not all second relative location relationships **112**, planar coordinates **108** and use coordinates **110** are provided with reference symbols. It can be seen that the use coordinates **110** do not match the planar coordinates **108**. The use coordinates **110** were calculated in such a way that the differences of as many use coordinates **110** as possible to one respective planar coordinate **108** were minimized and at the same time the difference between the second relative location relationships **112** and the first relative location relationships **104** is minimized. In a perfect case, all differences would disappear. In most cases, as in this example, the differences will have to be minimized according to a suitable metric, here the metric of the smallest error squares.

[0044] The calculation of the use coordinates **110** from the first relative location relationships **104** and the planar coordinates **108** is carried out by a computing unit **116**. The computing unit **116** receives the first relative location relationships **104** and the planar coordinates **108**, for example in the form of the reference map **106** from FIG. 2, and calculates the use coordinates **110** of the stationary radio transceiver **102**. The use coordinates **110** are output by the computing unit **116** via an output device **118**, for example in the form of a control map **114**. It is understood that the use coordinates **110** can also be output to another computing unit. Alternatively or additionally, the use coordinates **110** can be stored in a memory and subsequently used by the computing unit **116**, for example when executing an application that requires the use coordinates.

[0045] In this example, the output device **118** is a touchscreen via which the computing unit **116** can display a graphical user interface and accept inputs. Using the graphical user interface, a user can, for example, enter or change planar coordinates. Alternatively or additionally, the user can use the user interface to select stationary radio transceivers **102** that are to output an acoustic or visual signal. The use coordinates **110** of the stationary radio transceiver which has output a signal are then visualized via the output device **118**.

[0046] A specific planar coordinate **108a** is assigned to a specific stationary radio transceiver **102a**. For this radio transceiver **102a**, the difference between the use coordinate **110** and the associated planar coordinate **108a** is minimized and no further planar coordinates are taken into account.

[0047] In this example, the difference between the use coordinates **110** and the respective nearest planar coordinates **108** is minimized for six of the seven stationary radio transceivers **102**. The use coordinate **110** of a stationary radio transceiver **102b** is so far away from all planar coordinates that the difference between the coordinates is not minimized. Instead, it is assumed that this stationary radio transceiver **102b** was installed at a different location from the planar coordinates.

[0048] In this example, a planar coordinate **108b** is so far away from the use coordinates **110** of the stationary radio transceivers **102** that it is assumed that no radio transceiver is present at this planar coordinate **108b**.

[0049] It is a coincidence that the number of planar coordinates **108** and use coordinates **110** are identical in this example. In general, there may be more or fewer planar coordinates **108** than use coordinates **110**.

[0050] FIG. 4 shows how the position of a mobile radio transceiver **120** is determined based on the use coordinates **110** of the stationary radio transceiver **102**. The stationary radio transceiver **102** and the mobile radio transceiver **120** exchange radio signals, here ultra-wideband pulses, and measure the travel times of the radio signals. From the travel times of the radio signals, third relative location references **122** are determined between the stationary radio transceivers **102** and the mobile radio transceiver **120**. The position of the mobile radio transceiver **120** is determined from the use coordinates **110** of the stationary radio transceiver **102** and the third relative location references **122**.

[0051] FIG. 5 shows that a mobile radio transceiver **120** is moved along a trajectory **124**. During the movement of the mobile radio transceiver **120**, multiple third relative location references **122** are determined between the mobile radio transceiver **120** and the stationary radio transceivers. The third relative location references thus obtained are offset against the first relative location references **104** and thus enable the calculation of the use coordinates **110** to be improved.

[0052] A flow chart **200** is shown in FIG. **6**. In a first step **202**, first relative location references **104** are determined between the stationary radio transceivers **102**. In a second step **204**, additional information is provided. The additional information contains at least multiple planar coordinates. In an optional third step **206**, third relative location references **122** are determined between the stationary radio transceivers **102** and a mobile radio transceiver **120**. In a fourth step **208**, use coordinates **110** for the stationary radio transceivers **102** are determined and assigned to them. The use coordinates **110** are output in an optional fifth step **210**.

[0053] While subject matter of the present disclosure has been illustrated and described in detail in the drawings and foregoing description, such illustration and description are to be considered illustrative or exemplary and not restrictive. Any statement made herein characterizing the invention is also to be considered illustrative or exemplary and not restrictive as the invention is defined by the claims. It will be understood that changes and modifications may be made, by those of ordinary skill in the art, within the scope of the following claims, which may include any combination of features from different embodiments described above.

[0054] The terms used in the claims should be construed to have the broadest reasonable interpretation consistent with the foregoing description. For example, the use of the article “a” or “the” in introducing an element should not be interpreted as being exclusive of a plurality of elements. Likewise, the recitation of “or” should be interpreted as being inclusive, such that the recitation of “A or B” is not exclusive of “A and B,” unless it is clear from the context or the foregoing description that only one of A and B is intended. Further, the recitation of “at least one of A, B and C” should be interpreted as one or more of a group of elements consisting of A, B and C, and should not be interpreted as requiring at least one of each of the listed elements A, B and C, regardless of whether A, B and C are related as categories or otherwise. Moreover, the recitation of “A, B and/or C” or “at least one of A, B or C” should be interpreted as including any singular entity from the listed elements, e.g., A, any subset from the listed elements, e.g., A and B, or the entire list of elements A, B and C.

LIST OF REFERENCE SYMBOLS

[0055] **100** Localization system [0056] **102** Stationary radio transceiver [0057] **104** First relative location references [0058] **106** Reference map [0059] **108** Planar coordinates [0060] **110** Use coordinates [0061] **112** Second relative location references [0062] **114** Control map [0063] **116** Computing unit [0064] **118** Output device [0065] **120** Mobile radio transceiver [0066] **122** Third relative location references [0067] **124** Trajectory [0068] **200** Flow chart [0069] **202** First step [0070] **204** Second step [0071] **206** Third step [0072] **208** Fourth step [0073] **210** Fifth step

Claims

1. A method for calculating and assigning use coordinates to stationary radio transceivers of a localization system, wherein the localization system comprises a plurality of the stationary radio transceivers, wherein the localization system determines multiple first relative location references between the radio transceivers, the method comprising: providing additional information comprising multiple planar coordinates; and calculating and assigning the use coordinates for each of the stationary radio transceivers based on the additional information and the first relative location references.
2. The method according to claim 1, wherein the multiple planar coordinates are taken from a reference map.
3. The method according to claim 2, wherein a graphical user interface is provided for entering the multiple planar coordinates into the reference map.
4. The method according to claim 2, wherein the multiple planar coordinates are extracted from the reference map based on image processing.
5. The method according to claim 4, wherein at least one wall is recorded in the reference map and

the wall is extracted from the reference map based on the image processing, wherein the wall is taken into account in the calculation and assignment of the use coordinates.

6. The method according to claim 1, wherein the multiple planar coordinates originate from a previous installation of the localization system.

7. The method according to claim 6, wherein a warning is issued if the use coordinates deviate from the multiple planar coordinates by more than a predetermined threshold value.

8. The method according to claim 1, wherein the use coordinates are calculated such that second relative location references between the use coordinates substantially correspond to the first relative location references.

9. The method according to claim 1, wherein the use coordinates are calculated for a plurality of the stationary radio transmitters such that differences between the respective use coordinates and respective closest planar coordinates are minimized.

10. The method according to claim 8, wherein differences between respective use coordinates and respective nearest planar coordinates and/or the first relative location references and the second relative location relationships are minimized according to a linear or quadratic metric.

11. The method according to claim 1, wherein at least one of the multiple planar coordinates is assigned to one of the plurality of stationary radio transceivers.

12. The method according to claim 1, wherein the use coordinates are visualized in a control map.

13. The method according to claim 1, wherein at least one of the plurality of stationary radio transceivers outputs an acoustic or visual signal and the use coordinates of the signal-outputting stationary radio transceiver are visualized on a control map.

14. A system for calculating and assigning use coordinates to stationary radio transceivers of the localization system, wherein the system comprises a plurality of stationary radio transceivers and a computing unit, wherein the computing unit is communicatively coupled to the plurality of stationary radio transceivers, wherein the computing unit has at least one interface for reading the additional information, and wherein the computing unit is provided and configured to carry out the method according to claim 1.

15. The system according to claim 14, wherein the at least one interface comprises a user interface.

16. The system according to claim 14, wherein the at least one interface is connected to a memory, wherein planar coordinates in the form of a reference map are stored in the memory.

17. A non-transitory computer readable medium, wherein the non-transitory computer readable medium can be loaded directly into an internal memory of a digital computer and comprises software sections with which the steps according to the method of claim 1 are carried out when the non-transitory computer readable medium is executed on the digital computer.

18. The method according to claim 1, wherein the localization system determines the multiple first relative location references between the radio transceivers based on ultra-wideband radio technology.

19. The method according to claim 10, wherein the linear or quadratic metric is a metric of the least error squares.

20. The system according to claim 15, wherein the user interface is a graphical user interface.
