

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250260476

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Zavesky; Eric et al.

SYNCHRONIZED SATELLITE COMMUNICATIONS

Abstract

Synchronized satellite communications can include receiving, at a computer having a processor, a data request that identifies a requesting device, data to be received by the requesting device, and a time at which the data is to be received by the requesting device. The processor can determine a geographic location of the requesting device and locations of a plurality of satellites; identify, based on the geographic location of the requesting device and the locations of the plurality of satellites, satellites that are to provide the data to the requesting device; generate instructions for loading network requirements to the satellites; and provide, to at least one of the satellites, the instructions. Additionally, embodiments of the concepts and technologies disclosed herein can be used to provide the same data and/or different data to multiple devices at the same time.

Inventors: Zavesky; Eric (Austin, TX), Pratt; James (Round Rock, TX), Bradley; Nigel (Canton, GA)

Applicant: AT&T Intellectual Property I, L. P. (Atlanta, GA)

Family ID: 1000007816276

Assignee: AT&T Intellectual Property I, L. P. (Atlanta, GA)

Appl. No.: 18/604759

Filed: March 14, 2024

Related U.S. Application Data

parent US continuation 17243796 20210429 parent-grant-document US 11962392 child US 18604759

Publication Classification

Int. Cl.: H04B7/185 (20060101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) [0001] The present application claims priority to and is a continuation of U.S. patent application Ser. No. 17/243,796, filed Apr. 29, 2021, all sections of the aforementioned application(s) and/or patent(s) are incorporated by reference herein in their entirety.

BACKGROUND

[0002] Providing network connectivity to users using satellites can present challenges. Satellites may have multiple modes of orbital patterns that can disrupt ground connections, as well as space-based radio connections. For example, some satellites may move in and out of radio range quickly. Similarly, satellites may encounter atmospheric and space-based interferences that may disrupt network connections.

SUMMARY

[0003] The present disclosure is directed to synchronized satellite communications. A user device can request data from satellites and/or a synchronized satellite communication service. In some embodiments, the user device can send to the synchronized satellite communication service and/or to one or more of the satellites a request for the data, for example, in a data request. In some embodiments, the data request can identify the data that is being requested by the user device, an identity and/or address of the user device, a location of the user device, a time at which or over which delivery of the data is being requested, combinations thereof, or the like. In some embodiments of the concepts and technologies disclosed herein, a satellite that receives the data request can forward, to the synchronized satellite communication service, a request that can provide some or all information in the data request to the synchronized satellite communication service. It be understood that this example is illustrative, and therefore should not be construed as limiting in any way.

[0004] The synchronized satellite communication service can be configured to determine, based on information in the data request and/or the request, the data that is to be delivered to the requesting device (e.g., the user device) and the time the data is to be provided to the user device. The synchronized satellite communication service also can be configured to determine the location of the user device and locations of one or more of the satellites at a current time and/or a future time if delivery of the data was requested at a future time. The synchronized satellite communication service also can be configured to determine a number of satellites that are to provide the data to the user device based, for example, on an amount of data being transferred, time constraints set for the data transmission, bandwidth limitations of the satellites, combinations thereof, or the like.

[0005] Based on the locations of the user device and the satellites, and based on the bandwidth needs and requirements, the synchronized satellite communication service can identify the satellites that are to provide the data to the user device. The synchronized satellite communication service can be configured to generate instructions to load the network requirements to the identified satellites, e.g., to send the instructions to the satellites to orchestrate and/or otherwise activate communication channels with the satellites. The instructions also can instruct the satellites how to divide the data among the satellites, and how the satellites will synchronize transmission of the resulting data portions to the user device so that the user device can assemble the data portions into the data. Additionally, embodiments of the concepts and technologies disclosed herein can be used to provide the same data and/or different data to multiple devices at the same time. These and other

aspects of the concepts and technologies disclosed herein will be illustrated and described herein in more detail.

[0006] According to one aspect of the concepts and technologies disclosed herein, a system is disclosed. The system can include a processor and a memory. The memory can store computer-executable instructions that, when executed by the processor, cause the processor to perform operations. The operations can include receiving a data request that can identify a requesting device, data to be received by the requesting device, and a time at which the data is to be received by the requesting device; determining a geographic location of the requesting device and locations of two or more satellites; identifying, based on the geographic location of the requesting device and the locations of the two or more satellites, satellites that are to provide the data to the requesting device; generating instructions for loading network requirements to the satellites; and providing, to at least one of the satellites, the instructions.

[0007] In some embodiments, the computer-executable instructions, when executed by the processor, can cause the processor to perform operations that further can include determining if changes should be made to the satellites that are to provide the data to the requesting device; and in response to a determination that the changes should be made, updating the geographic location of the requesting device and the locations of the satellites, and identifying the satellites based on an updated geographic location and updated locations. In some embodiments, the computer-executable instructions, when executed by the processor, can cause the processor to perform operations that further can include determining if a data transfer by the satellites to the requesting device has been completed; and in response to a determination that the data transfer has not been completed, again identifying the satellites.

[0008] In some embodiments, generating the instructions can include generating instructions that define how data is to be divided into data portions for delivery by the satellites and a time at which each data portion is to be delivered. In some embodiments, a first satellite can deliver a first of the data portions to the requesting device at a first time, and a second satellite can deliver a second of the data portions to the requesting device at the first time. In some embodiments, a first satellite can deliver a first of the data portions to the requesting device at a first time, and a second satellite can deliver a second of the data portions to the requesting device at a second time. In some embodiments, the satellites can deliver the data portions to the requesting device substantially simultaneously to increase available bandwidth for the requesting device.

[0009] In some embodiments, the data includes a first instance of data intended for the requesting device and a second instance of data intended for another device. A first satellite can deliver the first instance of data to the requesting device at the time, and a second satellite can deliver the second instance of data to the other device at the same time. In some embodiments, the first instance of data can include a first token that can be unique to the requesting device, and the second instance of data can include a second token that can be unique to the other device. In some embodiments, a first satellite can deliver the data to the requesting device at the time, and a second satellite can deliver the data to another device at the same time.

[0010] According to another aspect of the concepts and technologies disclosed herein, a method is disclosed. The method can include receiving, at a computer including a processor, a data request that can identify a requesting device, data to be received by the requesting device, and a time at which the data is to be received by the requesting device; determining, by the processor, a geographic location of the requesting device and locations of two or more satellites; identifying, by the processor and based on the geographic location of the requesting device and the locations of the two or more satellites, satellites that are to provide the data to the requesting device; generating, by the processor, instructions for loading network requirements to the satellites; and providing, by the processor and to at least one of the satellites, the instructions.

[0011] In some embodiments, the computer-executable instructions, when executed by the processor, can cause the processor to perform operations that further can include determining if

changes should be made to the satellites that are to provide the data to the requesting device; and in response to a determination that the changes should be made, updating the geographic location of the requesting device and the locations of the satellites, and identifying the satellites based on an updated geographic location and updated locations. In some embodiments, the computer-executable instructions, when executed by the processor, can cause the processor to perform operations that further can include determining if a data transfer by the satellites to the requesting device has been completed; and in response to a determination that the data transfer has not been completed, again identifying the satellites.

[0012] In some embodiments, generating the instructions can include generating instructions that define how data is to be divided into data portions for delivery by the satellites and a time at which each data portion is to be delivered. In some embodiments, a first satellite can deliver a first of the data portions to the requesting device at a first time, and a second satellite can deliver a second of the data portions to the requesting device at the first time. In some embodiments, a first satellite can deliver a first of the data portions to the requesting device at a first time, and a second satellite can deliver a second of the data portions to the requesting device at a second time. In some embodiments, the satellites can deliver the data portions to the requesting device substantially simultaneously to increase available bandwidth for the requesting device.

[0013] In some embodiments, the data includes a first instance of data intended for the requesting device and a second instance of data intended for another device. A first satellite can deliver the first instance of data to the requesting device at the time, and a second satellite can deliver the second instance of data to the other device at the same time. In some embodiments, the first instance of data can include a first token that can be unique to the requesting device, and the second instance of data can include a second token that can be unique to the other device. In some embodiments, a first satellite can deliver the data to the requesting device at the time, and a second satellite can deliver the data to another device at the same time.

[0014] According to yet another aspect of the concepts and technologies disclosed herein, a computer storage medium is disclosed. The computer storage medium can store computer-executable instructions that, when executed by a processor, cause the processor to perform operations. The operations can include receiving a data request that can identify a requesting device, data to be received by the requesting device, and a time at which the data is to be received by the requesting device; determining a geographic location of the requesting device and locations of two or more satellites; identifying, based on the geographic location of the requesting device and the locations of the two or more satellites, satellites that are to provide the data to the requesting device; generating instructions for loading network requirements to the satellites; and providing, to at least one of the satellites, the instructions.

[0015] In some embodiments, the computer-executable instructions, when executed by the processor, can cause the processor to perform operations that further can include determining if changes should be made to the satellites that are to provide the data to the requesting device; and in response to a determination that the changes should be made, updating the geographic location of the requesting device and the locations of the satellites, and identifying the satellites based on an updated geographic location and updated locations. In some embodiments, the computer-executable instructions, when executed by the processor, can cause the processor to perform operations that further can include determining if a data transfer by the satellites to the requesting device has been completed; and in response to a determination that the data transfer has not been completed, again identifying the satellites.

[0016] In some embodiments, generating the instructions can include generating instructions that define how data is to be divided into data portions for delivery by the satellites and a time at which each data portion is to be delivered. In some embodiments, a first satellite can deliver a first of the data portions to the requesting device at a first time, and a second satellite can deliver a second of the data portions to the requesting device at the first time. In some embodiments, a first satellite can

deliver a first of the data portions to the requesting device at a first time, and a second satellite can deliver a second of the data portions to the requesting device at a second time. In some embodiments, the satellites can deliver the data portions to the requesting device substantially simultaneously to increase available bandwidth for the requesting device.

[0017] In some embodiments, the data includes a first instance of data intended for the requesting device and a second instance of data intended for another device. A first satellite can deliver the first instance of data to the requesting device at the time, and a second satellite can deliver the second instance of data to the other device at the same time. In some embodiments, the first instance of data can include a first token that can be unique to the requesting device, and the second instance of data can include a second token that can be unique to the other device. In some embodiments, a first satellite can deliver the data to the requesting device at the time, and a second satellite can deliver the data to another device at the same time.

[0018] Other systems, methods, and/or computer program products according to embodiments will be or become apparent to one with skill in the art upon review of the following drawings and detailed description. It is intended that all such additional systems, methods, and/or computer program products be included within this description and be within the scope of this disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0019] FIG. 1 is a system diagram illustrating an illustrative operating environment for various embodiments of the concepts and technologies described herein.

[0020] FIG. 2 is a flow diagram showing aspects of a method for using synchronized satellite communications, according to an illustrative embodiment of the concepts and technologies described herein.

[0021] FIG. 3 is a flow diagram showing aspects of a method for using synchronized satellite communications, according to another illustrative embodiment of the concepts and technologies described herein.

[0022] FIG. 4 schematically illustrates a network, according to an illustrative embodiment of the concepts and technologies described herein.

[0023] FIG. 5 is a block diagram illustrating an example computer system capable of implementing aspects of the concepts and technologies disclosed herein, according to some illustrative embodiments of the concepts and technologies described herein.

[0024] FIG. 6 is a block diagram illustrating an example mobile device capable of implementing aspects of the concepts and technologies disclosed herein, according to some illustrative embodiments of the concepts and technologies described herein.

[0025] FIG. 7 is a diagram illustrating a computing environment capable of implementing aspects of the concepts and technologies disclosed herein, according to some illustrative embodiments of the concepts and technologies described herein.

DETAILED DESCRIPTION

[0026] The following detailed description is directed to synchronized satellite communications. A user device can request data from satellites and/or a synchronized satellite communication service. In some embodiments, the user device can send to the synchronized satellite communication service and/or to one or more of the satellites a request for the data, for example a data request. In some embodiments, the data request can identify the data that is being requested by the user device, an identity and/or address of the user device, a location of the user device, a time at which or over which delivery of the data is being requested, combinations thereof, or the like. In some embodiments of the concepts and technologies disclosed herein, a satellite that receives the data request can forward, to the synchronized satellite communication service, a request that can

provide some or all information in the data request to the synchronized satellite communication service. It should be understood that this example is illustrative, and therefore should not be construed as being limiting in any way.

[0027] The synchronized satellite communication service can be configured to determine, based on information in the data request and/or the request, the data that is to be delivered to the requesting device (e.g., the user device) and the time the data is to be provided to the user device. The synchronized satellite communication service also can be configured to determine the location of the user device and locations of one or more of the satellites at a current time and/or a future time if delivery of the data was requested at a future time. The synchronized satellite communication service also can be configured to determine a number of satellites that are to provide the data to the user device based, for example, on an amount of data being transferred, time constraints set for the data transmission, bandwidth limitations of the satellites, combinations thereof, or the like. Additionally, embodiments of the concepts and technologies disclosed herein can be used to provide the same data and/or different data to multiple devices at the same time.

[0028] Based on the locations of the user device and the satellites, and based on the bandwidth needs and requirements, the synchronized satellite communication service can identify the satellites that are to provide the data to the user device. The synchronized satellite communication service can be configured to generate instructions to load the network requirements to the identified satellites, e.g., to send the instructions to the satellites to orchestrate and/or otherwise activate communication channels with the satellites. The instructions also can instruct the satellites how to divide the data among the satellites, and how the satellites will synchronize transmission of the resulting data portions to the user device so that the user device can assemble the data portions into the data. These and other aspects of the concepts and technologies disclosed herein will be illustrated and described herein in more detail.

[0029] While the subject matter described herein is presented in the general context of program modules that execute in conjunction with the execution of an operating system and application programs on a computer system, those skilled in the art will recognize that other implementations may be performed in combination with other types of program modules. Generally, program modules include routines, programs, components, data structures, and other types of structures that perform particular tasks or implement particular abstract data types. Moreover, those skilled in the art will appreciate that the subject matter described herein may be practiced with other computer system configurations, including hand-held devices, multiprocessor systems, microprocessor-based or programmable consumer electronics, minicomputers, mainframe computers, and the like.

[0030] Referring now to FIG. 1, aspects of an operating environment **100** for various embodiments of the concepts and technologies disclosed herein for synchronized satellite communications will be described, according to an illustrative embodiment. The operating environment **100** shown in FIG. 1 includes a user device **102**. The user device **102** can operate in communication with and/or as part of a communications network (“network”) **104**, though this is not necessarily the case.

[0031] According to various embodiments, the functionality of the user device **102** may be provided by one or more server computers, desktop computers, terrestrial communication tower computing systems, mobile telephones, smartphones, laptop computers, other computing systems, and the like. It should be understood that the functionality of the user device **102** may be provided by a single device, by two or more similar devices, and/or by two or more dissimilar devices. For purposes of describing the concepts and technologies disclosed herein, the user device **102** is described herein as a smartphone. It should be understood that this embodiment is illustrative and should not be construed as limiting in any way.

[0032] The user device **102** can execute an operating system **106** and one or more application programs such as, for example, a synchronized satellite communication application **108** (labeled “SSC Application” in FIG. 1) and/or other applications (not illustrated in FIG. 1). The operating system **106** can include a computer program that can control the operation of the user device **102**.

The synchronized satellite communication application **108** can include an executable program that can be configured to execute on top of the operating system **106** to provide various functions. [0033] In particular, the synchronized satellite communication application **108** can be configured to coordinate communications between the user device **102** and one or more satellites **110A-N** (hereinafter collectively and/or generically referred to as “satellites **110**”) to obtain data and/or content for consumption, viewing, and/or other use by the user device **102** and/or one or more of the applications executing thereon. According to various embodiments of the concepts and technologies disclosed herein, the user device **102** can be configured to communicate with one or more of the satellites **110** via one or more satellite links, via one or more terrestrial satellite relays (that can relay signals to and from the user device **102** and the satellites **110**), and/or other communication links.

[0034] As will be explained in more detail below, one or more of the satellites **110** can host and/or execute a synchronization application **112** to coordinate communications between the satellites **110** and the user device **102**. Although the synchronization application **112** is only illustrated with regard to the satellite **110A**, it should be understood that one or more and/or each of the satellites **110** can host and/or execute an instance of the synchronization application **112**. For example, the satellite **110N** also executes the synchronization application **112** in the illustrated embodiment, though this is not separately shown in FIG. 1. Because one or more the satellites **110** can include or omit the synchronization application in some instances, it should be understood that the illustrated embodiment is illustrative and should not be construed as being limiting in any way.

[0035] The user device **102** also can be configured to communicate with a synchronized satellite communication service **114** or other application or service, which can be hosted and/or executed by a device such as a server computer **116**. According to various embodiments, the functionality of the server computer **116** may be provided by one or more server computers, application servers, web servers, desktop computers, terrestrial communication tower computing systems, other computing systems, and the like. It should be understood that the functionality of the server computer **116** may be provided by a single device, by two or more similar devices, and/or by two or more dissimilar devices. For purposes of describing the concepts and technologies disclosed herein, the server computer **116** is described herein as an application server. It should be understood that this embodiment is illustrative and should not be construed as limiting in any way.

[0036] In various embodiments of the concepts and technologies disclosed herein, the synchronized satellite communication application **108** can be configured to manage communications with the satellites **110** via direct communications with the satellites **110** and/or via communications with the server computer **116** (and/or the synchronized satellite communication service **114** hosted and/or executed thereby). It should be understood that these examples are illustrative, and therefore should not be construed as being limiting in any way.

[0037] According to various embodiments of the concepts and technologies disclosed herein, the synchronized satellite communication application **108** can be configured to generate a data request **118**. The data request **118** can correspond to a request for a data file, streaming content, or the like; for a type of information, stream, or the like; and/or another type of request for data. By way of example, the data request **118** can request the delivery of content to the user device **102**. In some embodiments, the data request **118** can include various types of information such as, for example, an identifier for the requesting device (e.g., the user device **102**); an address for the requesting device; data that identifies the data being requested by the user device **102**; timing information, if desired (e.g., when the data should be delivered); combinations thereof; or the like. In some embodiments, the user device **102** can send the data request **118** to the server computer **116** and in other embodiments, the user device **102** can send the data request **118** to one or more of the satellites **110**. Both example embodiments will be described below in more detail.

[0038] In some embodiments in which the data request **118** is sent by the user device **102** to the server computer **116**, the synchronized satellite communication service **114** can be configured to

recognize the data request **118**, and to identify the requesting device (e.g., the user device **102**); the data being requested; a time at which the requested data is to be delivered to the user device **102**; and/or other aspects of the data being requested as illustrated and described herein. In some embodiments, the synchronized satellite communication service **114** can obtain the data that is to be provided to the requesting device, e.g., by accessing a data storage location, server, or other resource to obtain a copy of the data. In some other embodiments, the data may be stored at or by one or more of the satellites **110**, so the synchronized satellite communication service **114** may not obtain a copy of the data in all embodiments. It should be understood that this example is illustrative, and therefore should not be construed as being limiting in any way.

[0039] In some embodiments, the synchronized satellite communication service **114** can be configured to generate and send to one or more of the satellites **110**, instructions **120**. The instructions **120** can be configured to instruct one or more of the satellites **110** to send the requested data to the requesting device at the requested time (or immediately if no time is specified). Thus, although not separately illustrated in FIG. **1**, the instructions **120** can be sent to the satellites **110** with the data (e.g., the server computer **116** can obtain a copy of the data and forward that data to the satellites **110** with and/or as part of the instructions **120**). It should be understood that this example is illustrative, and therefore should not be construed as being limiting in any way.

[0040] In some other embodiments in which the data request **118** is sent by the user device **102** to one or more of the satellites **110**, the data request **118** can be received by one or more of the satellites **110**. The receiving satellite **110** can be configured, e.g., via execution of the synchronization application **112**, to request establishment of one or more communication channels or links between the satellites **110** and the requesting device (e.g., the user device **102**) via which the data being requested can be delivered. In some embodiments, the satellites **110** can be configured to obtain the data from the server computer **116** as explained above, while in some other embodiments the satellites **110** may already store the data. Thus, in some embodiments, the satellites **110** can forward, to the server computer **116**, a request **122**. The request **122** can request establishment and/or orchestration of one or more communications channels and/or links between the satellites **110** and the requesting device (e.g., the user device **102**). In some embodiments, the request **122** also can include a request for the data that was requested by way of the data request **118**. The satellites **110** can receive, in response to the request **122**, the instructions **120** for effecting delivery of the data to the requesting device (e.g., the user device **102**). It should be understood that these examples are illustrative, and therefore should not be construed as being limiting in any way.

[0041] According to various embodiments of the concepts and technologies disclosed herein, the synchronized satellite communication service **114** can be configured to synchronize delivery of the data from the satellites **110** to the user device **102**. In particular, the synchronized satellite communication service **114** can be configured to determine a location of the user device **102** (or other device that has requested the data, e.g., by way of the data request **118**). According to various embodiments of the concepts and technologies disclosed herein, the location of the user device **102** can be determined without using terrestrial location determination technologies, though this is not necessarily the case in all embodiments.

[0042] In some embodiments, for example, the location of the user device **102** can be determined by the synchronized satellite communication service **114** via communications with the user device **102**, via communications with the satellites **110**, via communications with a location determination device or system, and/or in alternative manners. In some embodiments, the satellites **110** can be configured to track a location of the user device **102**, so the synchronized satellite communication service **114** can be configured to request the current location of the user device **102** from the satellites **110**. Because the location of the user device **102** can be determined in additional and/or alternative manners, it should be understood that these examples are illustrative, and therefore should not be construed as being limiting in any way.

[0043] Additionally, the synchronized satellite communication service **114** can be configured to

determine the locations of one or more of the satellites **110**. In particular, the synchronized satellite communication service **114** can be configured to determine a location of the one or more satellites **110** at a current time and/or to project or predict one or more locations of the one or more satellites **110** at some future time, e.g., when the data is to be delivered to the user device **102**. Thus, the synchronized satellite communication service **114** can be configured to determine, based on locations of the user device **102** and/or the satellites **110** at a current time and/or at some time in the future, which of the satellites **110** are to provide the data to the user device **102**. Thus, it can be appreciated that the synchronized satellite communication service **114** can be configured to identify the satellites **110** that will provide data to the user device **102** based on locations of the satellites **110** and/or the user device **102**. It should be understood that this example is illustrative, and therefore should not be construed as being limiting in any way.

[0044] Based on the locations of the user device **102** and the one or more satellites **110**, the synchronized satellite communication service **114** can identify the satellites **110** that are to provide the data to the user device **102**. In some embodiments, the synchronized satellite communication service **114** can predict which satellites **110** will be available at some future delivery time and identify, based on the predicted availability, the satellites **110** that will provide the data to the user device **102**. The synchronized satellite communication service **114** also can be configured to orchestrate communication links between the identified satellites **110** at some current time and/or at some time in the future (e.g., at a requested delivery time). It should be understood that this example is illustrative, and therefore should not be construed as being limiting in any way.

[0045] In some embodiments, the synchronized satellite communication service **114** can be configured to determine network requirements for the communication links between the satellites **110** and the user device **102**. The network requirements can include spatial location or relationship (e.g., a location in orbit, a location relative to a point on the surface of the earth, etc.); bandwidth requirements for the data transmission; security and/or communication protocols for the data transmission; time constraints (e.g., delivery time, transmission duration, etc.); combinations thereof; or the like. The synchronized satellite communication service **114** can then load the network requirements to the satellites **110** to create a satellite network between the identified satellites **110** and the user device **102**. According to various embodiments of the concepts and technologies disclosed herein, including the embodiment illustrated in FIG. **1**, the synchronized satellite communication service **114** can load the network requirements to the satellites by way of sending instructions **120** that encompass the requirements. It should be understood that this example is illustrative, and therefore should not be construed as being limiting in any way.

[0046] In some example embodiments, determining the network requirements can include determining security requirements and/or other considerations as illustrated and described herein. For example, certain satellites **110** may be chosen to participate in the synchronized satellite communication service **114** based on their orbital structure around the planet. For example, those satellites **110** that are closer to the earth (e.g., in low earth orbit (“LEO”) at a distance of about five hundred to one thousand kilometers versus in high earth orbit (“HEO”) at a distance of about ten thousand kilometers) may have a higher value for security or trust in the synchronized satellite communication service **114** because those satellites **110** may be less susceptible to communication attacks such as, for example, man-in-the-middle strategies, which may aim to intercept and/or relay spurious data. In another example, satellites **110** that are in a geostationary orbit (“GEO”) (e.g., at a distance of about thirty-six thousand kilometers) may have more associated security than those with a moving, elliptical orbit. It should be understood that this example is illustrative, and therefore should not be construed as being limiting in any way.

[0047] In some embodiments, identifying the satellites **110** that are to provide the data to the user device **102** can further include determining, based on various considerations, a number of satellites **110** that are to provide the data to the user device **102**. In particular, in some embodiments, the bandwidth of communications channels supported by the satellites **110** may be limited, so more

than one satellite **110** may be needed to deliver the data to the user device **102** in a required time limit (e.g., during a time the satellites **110** can communicate with the user device **102**). Thus, more than one satellite **110** may be required to provide the data to the user device **102**. Alternatively, an expected amount of bandwidth and/or demand for communications channels provided by the satellites **110** may dictate the use of more than one satellite **110**. Regardless of the motivation, more than one satellite **110** may be needed and may be identified by the synchronized satellite communication service **114**.

[0048] According to various embodiments of the concepts and technologies disclosed herein, the synchronized satellite communication service **114** can be configured to provide, e.g., in the instructions **120**, commands or other guidance for the satellites **110** on how to deliver the data to the user device **102** using multiple satellites **110**. In particular, the satellites **110** can be configured to create two or more data portions **124A-N** (hereinafter collectively and/or generically referred to as “data portions **124**”) that subsequently can be provided by the satellites **110** to the user device **102**. The two or more data portions **124** can collectively correspond to the data that was requested (labeled “data **126**” in FIG. **1**). Thus, the instructions **120** also can instruct the satellites **110** on how to divide the data **126** into the data portions **124** and how those data portions **124** will be delivered to the user device **102** (e.g., by which of the satellites **110**, at what time(s), etc.). It should be understood that this example is illustrative, and therefore should not be construed as being limiting in any way.

[0049] According to various embodiments of the concepts and technologies disclosed herein, the satellites **110** can be configured to track locations of the user device **102**, and to provide location updates **128** to the synchronized satellite communication service **114**. According to various embodiments, the location updates **128** can include updates to the locations of the user device **102** and/or updates to locations of the satellites **110**. It should be understood that these examples are illustrative, and therefore should not be construed as being limiting in any way.

[0050] In some embodiments of the concepts and technologies disclosed herein, one or more of the satellites **110** can execute a synchronization application **112**, as noted above. The synchronization application **112** can be configured to not only track the location of the user device **102**, but also to enforce security and location requirements on the user device **102** before delivering the data **126** (e.g., by coordinating the synchronized transmission of the data portions **124** to the user device **102**). In some embodiments, for example, the satellites **110** can identify a user device **102** by its specific location and/or address, and transmission of the data **126** may be restricted not only to the specific device that requested the data **126** (e.g., the user device **102**), but also at a particular location as defined by the instructions **120**, the network requirements, and/or elsewhere. Thus, embodiments of the concepts and technologies disclosed herein can provide secured communications between the satellites **110** and the user device **102**, where only specific devices at specific locations can receive the data **126** transmitted by the satellites **110**. These and/or other functionality of the satellites **110** may be controlled by the synchronization application **112**, in some embodiments. It should be understood that this example is illustrative, and therefore should not be construed as being limiting in any way.

[0051] According to various embodiments of the concepts and technologies disclosed herein, the satellites **110** can transmit the data portions **124** to the user device **102**, and the user device **102** can be configured, e.g., via execution of the synchronized satellite communication application **108**, to assemble the data portions **124** into the data **126**. Thus, while FIG. **1** depicts the data **126** being provided to the user device **102**, it should be understood that this indication is a schematic representation of how data portions **124** sent to the user device **102** can be effectively received as the data **126** (e.g., by assembly of the data portions **124** at the user device **102**). It should be understood that this example is illustrative, and therefore should not be construed as being limiting in any way.

[0052] As shown in FIG. **1**, another device **130** can also be configured to receive the data **126** (e.g.,

the same data **126** received by the user device **102**) or another instance of data **126** that can differ from the data **126** received by the user device **102**. As such, embodiments of the concepts and technologies disclosed herein can be used to deliver the same data **126** to multiple devices (e.g., the user device **102**, the other device **130**, and/or other devices) in a substantially simultaneous manner, in some embodiments. In some other embodiments of the concepts and technologies disclosed herein, multiple devices (e.g., the user device **102**, the other device **130**, and/or other devices) can each receive different data **126** at the same time or substantially simultaneously. For example, the user device **102** and the other device **130** can receive individualized instances of data **126** such as, for example, computer environment data (e.g., virtual reality data, cross-reality data, network data, etc.); personalized data (e.g., tokens, passwords, personalized links, etc.); and/or other information. It should be understood that these examples are illustrative, and therefore should not be construed as being limiting in any way.

[0053] According to various embodiments of the concepts and technologies disclosed herein, the other device **130** can execute an application that can be the same or similar to the synchronized satellite communication application **108**, though this is not illustrated in FIG. **1**. Thus, the other device **130** and/or the user device **102** can effectively be controlled by the synchronized satellite communication application **108** and/or the synchronized satellite communication service **114**, at least with regard to the requesting of and/or providing of data **126** to the user device **102** and/or the other device **130**. It should be understood that these examples are illustrative, and therefore should not be construed as being limiting in any way.

[0054] In practice, a user device **102** can request data **126** from satellites **110** and/or a synchronized satellite communication service **114**. In some embodiments, the user device **102** can send to the synchronized satellite communication service **114** and/or to one or more of the satellites **110**, a request for the data **126**, for example a data request **118**. In some embodiments, the data request **118** can identify the data **126** that is being requested by the user device **102**, an identity and/or address of the user device **102**, a location of the user device **102**, a time at which or over which delivery of the data **126** is being requested, combinations thereof, or the like. In some embodiments of the concepts and technologies disclosed herein, a satellite **110** that receives the data request **118** can forward, to the synchronized satellite communication service **114**, a request **122** that can provide some or all information in the data request **118** to the synchronized satellite communication service **114**. It should be understood that this example is illustrative, and therefore should not be construed as being limiting in any way.

[0055] The synchronized satellite communication service **114** can be configured to determine, based on information in the data request **118** and/or the request **122**, the data **126** that is to be delivered to the requesting device (e.g., the user device **102**) and the time the data **126** is to be provided to the user device **102**. The synchronized satellite communication service **114** also can be configured to determine a location of the user device **102** and locations of one or more of the satellites **110** at a current time and/or a future time if delivery of the data **126** was requested at a future time. The synchronized satellite communication service **114** also can be configured to determine a number of satellites that are to provide the data **126** to the user device **102** based, for example, on an amount of data being transferred, time constraints set for the data transmission, bandwidth limitations of the satellites **110**, combinations thereof, or the like.

[0056] Based on the locations of the user device **102** and the satellites **110**, and based on the bandwidth needs and requirements, the synchronized satellite communication service **114** can identify the satellite networks that are to provide the data **126** to the user device **102**. As used herein, a “satellite network” can refer to a communication link or channel established between a satellite **110** and a user device **102** or another device. It should be understood that this example is illustrative, and therefore should not be construed as being limiting in any way.

[0057] The synchronized satellite communication service **114** can be configured to generate instructions **120** to load the network requirements to the identified satellite networks, e.g., to send

the instructions **120** to the satellites **110** to orchestrate and/or otherwise activate communication channels with the satellites **110**. The instructions **120** also can instruct the satellites **110** how to divide the data **126** among the satellites **110**, and how the satellites **110** will synchronize transmission of the resulting data portions **124** to the user device **102** so that the user device **102** can assemble the data portions **124** into the data **126**. Additionally, as explained herein, multiple devices can receive the same data **126** and/or different instances of data **126** using the concepts and technologies disclosed herein. These and other aspects of the concepts and technologies disclosed herein will be illustrated and described herein in more detail.

[0058] FIG. **1** illustrates one user device **102**, one network **104**, two or more satellites **110**, one server computer **116**, and one other device **130**. It should be understood, however, that various implementations of the operating environment **100** can include one or more than one user device **102**; one or more than one network **104**; one, two, or more than two satellites **110**; zero, one, or more than one server computer **116**; and/or zero, one, or more than one other device **130**. As such, the illustrated embodiment should be understood as being illustrative, and should not be construed as being limiting in any way.

[0059] Turning now to FIG. **2**, aspects of a method **200** for using synchronized satellite communications will be described in detail, according to an illustrative embodiment. It should be understood that the operations of the methods disclosed herein are not necessarily presented in any particular order and that performance of some or all of the operations in an alternative order(s) is possible and is contemplated. The operations have been presented in the demonstrated order for ease of description and illustration. Operations may be added, omitted, and/or performed simultaneously, without departing from the scope of the concepts and technologies disclosed herein.

[0060] It also should be understood that the methods disclosed herein can be ended at any time and need not be performed in their entirety. Some or all operations of the methods, and/or substantially equivalent operations, can be performed by execution of computer-readable instructions included on a computer storage media, as defined herein. The term “computer-readable instructions,” and variants thereof, as used herein, is used expansively to include routines, applications, application modules, program modules, programs, components, data structures, algorithms, and the like. Computer-readable instructions can be implemented on various system configurations including single-processor or multiprocessor systems, minicomputers, mainframe computers, personal computers, hand-held computing devices, microprocessor-based, programmable consumer electronics, combinations thereof, and the like.

[0061] Thus, it should be appreciated that the logical operations described herein are implemented (1) as a sequence of computer implemented acts or program modules running on a computing system and/or (2) as interconnected machine logic circuits or circuit modules within the computing system. The implementation is a matter of choice dependent on the performance and other requirements of the computing system. Accordingly, the logical operations described herein are referred to variously as states, operations, structural devices, acts, or modules. These states, operations, structural devices, acts, and modules may be implemented in software, in firmware, in special purpose digital logic, and any combination thereof. As used herein, the phrase “cause a processor to perform operations” and variants thereof is used to refer to causing a processor of a computing system or device, such as the server computer **116**, to perform one or more operations and/or causing the processor to direct other components of the computing system or device to perform one or more of the operations.

[0062] For purposes of illustrating and describing the concepts of the present disclosure, the method **200** is described herein as being performed by the server computer **116** via execution of one or more software modules such as, for example, the synchronized satellite communication service **114**. It should be understood that additional and/or alternative devices and/or network nodes can provide the functionality described herein via execution of one or more modules, applications,

and/or other software including, but not limited to, the synchronized satellite communication service **114**. Thus, the illustrated embodiments are illustrative, and should not be viewed as limiting in any way.

[0063] The method **200** begins at operation **202**. At operation **202**, the server computer **116** can receive a data request such as the data request **118**. As explained above, the data request **118** can be received by the server computer **116** from the user device **102**, in some embodiments. In some other embodiments, the data request received in operation **202** can correspond to the request **122** that can be received by the server computer **116** from one or more of the satellites **110**. Thus, it can be appreciated that the user device **102** can send the data request **118** to the satellites **110**, and that satellites **110** can send, to the server computer **116**, the request **122** in operation **202**.

[0064] Regardless of how the information is provided to the server computer **116**, the server computer **116** can determine in operation **202** that a request for data **126** has been received. As noted above, the data request **118** and/or the request **122** can include information identifying the requesting device and/or an address associated with the requesting device; the data **126** being requested; a timing associated with the delivery of the data **126** to the requesting device; and/or other information. It should be understood that this example is illustrative, and therefore should not be construed as being limiting in any way.

[0065] From operation **202**, the method **200** can proceed to operation **204**. At operation **204**, the server computer **116** can determine a device location (e.g., a geographic location of the requesting device such as the user device **102**) and locations of one or more satellites **110** (e.g., locations, relative to the earth and/or relative to the requesting device of one or more of the satellites **110**). According to various embodiments of the concepts and technologies disclosed herein, the server computer **116** can perform operation **204** by sending to the satellites **110**, a request for a location of the requesting device (e.g., the user device **102**) and a request for the locations and/or positions of the satellites **110**. In some other embodiments, the server computer **116** can perform operation **204** by querying other location systems (e.g., a location server) for locations of the requesting device and the satellites **110**.

[0066] According to various embodiments of the concepts and technologies disclosed herein, operation **204** can include obtaining locations of the requesting device (e.g., the user device **102**) and the satellites **110** without using terrestrial location determination devices and/or systems such as the global positioning system ("GPS") and/or the like. It can be appreciated that a satellite-determined geographic location of the requesting device (e.g., the user device **102**) can be extremely accurate in terms of latitude, longitude, and/or elevation; particularly relative to GPS. In particular, some embodiments of the concepts and technologies disclosed herein can include determining geographic location of the requesting device (e.g., the user device **102**) to an accuracy of less than one meter. Similarly, the locations of the satellites **110** can be determined with extreme precision, in various embodiments. It should be understood that these example embodiments are illustrative, and therefore should not be construed as being limiting in any way.

[0067] From operation **204**, the method **200** can proceed to operation **206**. At operation **206**, the server computer **116** can identify one or more satellites **110** and/or satellite communication links to provide the data **126** requested in the request received in operation **202**. According to various embodiments of the concepts and technologies disclosed herein, the server computer **116** can identify, in operation **206**, two or more satellites **110** that will provide the data **126**. The identification of the satellites **110** in operation **206** can be based, for example, on the locations of the requesting device (e.g., the user device **102**) and the satellites **110**; on the amount of data **126** that is to be transmitted and/or the bandwidth required for the transmission; the timing of the delivery of the data **126**; and/or other considerations.

[0068] In particular, as noted above, the data **126** can be requested with a time indicator, namely an indicator that can specify a time at which the data **126** should be delivered to the requesting device; a time duration during which the data **126** should be delivered to the requesting device; or the like.

Thus, the server computer **116** can determine, based on an identification of the requesting device and the data **126**, how much data (e.g., in bits, bytes, or the like) is to be transmitted to the requesting device in how much time (e.g., in seconds, minutes, or the like).

[0069] By way of example, a requesting device such as the user device **102** can request the data **126** where the data **126** can include a file having a size of seven hundred fifty megabytes, and where the data is to be delivered at a specified time over a two-minute window. The server computer **116** can determine, for example, that the satellites **110** that are in a location at which the data **126** can be delivered at the specified time have a bandwidth capability of fifteen megabits per second. In this example, the server computer **116** can determine that one satellite **110** will be unable to deliver the data **126** to the user device **102** over two minutes. Thus, the server computer **116** can determine that two satellites **110** will deliver the data **126** in a synchronized manner to the user device **102**.

[0070] In particular, the server computer **116** can determine that the maximum bandwidth of the satellites **110** in this example is 3.75 Megabytes per second (MBps) based on the fifteen megabits per second figure; and therefore, that the data transfer would take one satellite two hundred seconds (three minutes and twenty seconds). As such, the server computer **116** can determine that two satellites **110** operating in a synchronized manner could deliver the data in one minute forty seconds, and those two satellites **110** can be identified by the server computer **116** based on projected and/or predicted locations of the satellites **110** at the future time, as well as the location of the user device **102**. It should be understood that this example is illustrative, and therefore should not be construed as being limiting in any way.

[0071] Thus, operation **206** can include identifying the satellites **110** to provide the data **126**; determining the amount of data (e.g., file size; stream size, etc.) that is to be transmitted; determining how many satellites **110** will be used to provide the data **126** (e.g., how many data portions **124** will be created); and identifying other requirements for the data transmission. Although not separately shown in FIG. 2, it can be appreciated that the server computer **116** can be configured to generate the instructions **120** in operation **206** or in a separate operation, where the instructions **120** can define the network requirements for the data transmission such as, for example, which satellites **110** are to provide the data **126**; a time at which the data **126** is to be provided; a duration of the data transmission; how the data **126** is to be divided (e.g., into data portions **124**); and the like. Because other network requirements are illustrated and described herein, it should be understood that these example requirements are illustrative and should not be construed as limiting in any way.

[0072] From operation **206**, the method **200** can proceed to operation **208**. At operation **208**, the server computer **116** can load the network requirements to the identified satellites **110**. In some embodiments of operation **208**, the server computer **116** can send the instructions **120** generated in operation **206** to the satellites **110** to effectively “load” the network requirements to the satellites **110**. In some embodiments of the concepts and technologies disclosed herein, the instructions **120** can be sent in operation **208** by the server computer **116** with a copy of the data **126** that is to be provided to the user device **102**. In some other embodiments, the satellites **110** may already store the data **126**. It should be understood that in some embodiments, the server computer **116** can trigger the loading of the network requirements and/or the providing of the instructions **120** in other manners and/or by other devices. Because the network requirements can be loaded to the satellites in additional and/or alternative manners, it should be understood that this example is illustrative, and therefore should not be construed as being limiting in any way.

[0073] From operation **208**, the method **200** can proceed to operation **210**. At operation **210**, the server computer **116** can update a device location (e.g., a current geographic location of the user device **102**) and satellite locations (e.g., current locations and/or positions of the satellites **110** relative to the earth, the user device **102**, other satellites **110**, or the like). Thus, operation **210** can correspond to the server computer **116** tracking movements of the satellites **110** and/or the

receiving device (e.g., the user device **102**); the server computer **116** receiving location updates from various entities; and/or otherwise tracking locations of the user device **102** and/or the satellites **110**. It should be understood that these examples are illustrative, and therefore should not be construed as being limiting in any way.

[0074] From operation **210**, the method **200** can proceed to operation **212**. At operation **212**, the server computer **116** can determine if any changes are needed. In particular, operation **212** can correspond to the server computer **116** determining if the satellites **110** identified in operation **206** should be changed based on changes in locations; changes in available and/or needed bandwidths; changes in the size or identification of the data **126**; changes in available satellites **110**; changes in positions of the satellites **110**; and/or other considerations. As such, operation **212** can correspond to the server computer **116** updating the identification in operation **206**, in some embodiments, or determining that the facts and/or situations that led the identification in operation **206** (e.g., location information, the size of the data **126**, the timing of the delivery of the data **126**, combinations thereof, or the like) have changed. Because other considerations are illustrated and described herein with regard to identifying the satellites **110** to transmit the data **126**, it should be understood that these example considerations are illustrative, and therefore should not be construed as being limiting in any way.

[0075] If the server computer **116** determines, in operation **212**, that changes are needed, the method **200** can return to operation **206**, and the server computer **116** can again identify the satellites **110** to provide the data **126**. Thus, it can be appreciated that operations **206-212** can be iterated until the server computer **116** determines, in any iteration of operation **212**, that changes are not needed.

[0076] In some embodiments of the concepts and technologies disclosed herein, the determination in operation **212** can instead be a determination if the transmission of the data **126** has been completed. In such an embodiment, operation **210** can be omitted from the method **200** or moved elsewhere in the method flow, and flow from operation **208** can instead proceed to the server computer **116** determining if the data transfer has been completed. Thus, the server computer **116** can determine, in operation **212**, if the requested data transfer has been completed, and if not, the server computer **116** can be configured to update the locations (as in operation **210**) and/or to determine if changes are needed by returning the method flow to operation **206** and again identifying the satellites **110** to provide the data **126**. Thus, it can be appreciated that the server computer **116** may not actually determine if changes are needed; rather the server computer **116** may merely re-determine the satellites **110** if the server computer **116** determines in operation **212** that the data transfer has not completed. In this embodiment, operations **206-212** can be iterated until the server computer **116** determines, in any iteration of operation **212**, that the data transfer has been completed. It should be understood that this example is illustrative, and therefore should not be construed as being limiting in any way.

[0077] If the server computer **116** determines, in operation **212**, that changes to the data transfer are not needed, the method **200** can proceed to operation **214**. In the alternative embodiment noted above, where operation **212** corresponds to a determination as to whether or not the data transfer has been completed, the method **200** can proceed to operation **214** if the server computer **116** determines, in operation **212**, that the data transfer has been completed. The method **200** can end at operation **214**.

[0078] Turning now to FIG. **3**, aspects of a method **300** for using synchronized satellite communications will be described in detail, according to an illustrative embodiment. For purposes of illustrating and describing the concepts of the present disclosure, the method **300** is described herein as being performed by one of the satellites **110** via execution of one or more software modules such as, for example, the synchronization application **112**. It should be understood that additional and/or alternative devices and/or network nodes can provide the functionality described herein via execution of one or more modules, applications, and/or other software including, but not

limited to, the synchronization application **112**. Thus, the illustrated embodiments are illustrative, and should not be viewed as limiting in any way.

[0079] The method **300** begins at operation **302**. At operation **302**, the satellite **110** can receive a data request such as the data request **118**. As explained above, the data request **118** can be received by the satellite **110** from the user device **102**, in some embodiments. In some other embodiments, the data request **118** can be forwarded to the satellite **110** by other devices associated with the network **104** and/or other networks. Regardless of how the information is provided to the satellite **110**, the satellite **110** can determine in operation **302** that a request for data **126** has been received. The data request **118** can include information identifying the requesting device (e.g., the user device **102**); an address associated with the requesting device; the data **126** being requested; a timing associated with the delivery of the data **126** to the requesting device; other information; combinations thereof; or the like. It should be understood that this example is illustrative, and therefore should not be construed as being limiting in any way.

[0080] From operation **302**, the method **300** can proceed to operation **304**. At operation **304**, the satellite **110** can request orchestration from the synchronized satellite communication service **114**. In particular, the satellite **110** can request, from the synchronized satellite communication service **114**, instructions for creating one or more satellite links with the requesting device to deliver the data **126** requested in operation **302**. In some embodiments, the satellite **110** can be configured to request the orchestration via a request **122**, which can include various data such as, for example, the identity of the requesting device; the location of the requesting device and/or the satellites **110**; an address associated with the requesting device; timing associated with the data transfer; an identification of the data **126** requested by way of the data request **118** received in operation **302**; combinations thereof; or the like. According to various embodiments of the concepts and technologies disclosed herein, the satellite **110** can be configured to determine the location of the requesting device directly and/or by querying other location systems (e.g., a location server) for locations of the requesting device and the satellites **110**.

[0081] According to various embodiments of the concepts and technologies disclosed herein, operation **304** can include obtaining locations of the requesting device (e.g., the user device **102**) and the satellites **110** without using terrestrial location determination devices and/or systems such as the global positioning system ("GPS") and/or the like. It can be appreciated that a satellite-determined geographic location of the requesting device (e.g., the user device **102**) can be extremely accurate in terms of latitude, longitude, and/or elevation; particularly relative to GPS. In particular, some embodiments of the concepts and technologies disclosed herein can include determining geographic location of the requesting device (e.g., the user device **102**) to an accuracy of less than one meter. Similarly, the locations of the satellites **110** can be determined with extreme precision, in various embodiments. It should be understood that these example embodiments are illustrative, and therefore should not be construed as being limiting in any way.

[0082] From operation **304**, the method **300** can proceed to operation **306**. At operation **306**, the satellite **110** can receive instructions **120** from the server computer **116**. In some embodiments, the instructions **120** can be received by the satellite **110** with the data **126** that was requested by the requesting device (e.g., if the satellite **110** did not already store the data **126**). Thus, it can be appreciated that the server computer **116** can be configured to identify one or more satellites **110** and/or satellite communication links to provide the data **126** as requested based, for example, on the locations of the requesting device (e.g., the user device **102**) and the satellites **110**; on the amount of data **126** that is to be transmitted and/or the bandwidth required for the transmission; the timing of the delivery of the data **126**; and/or other considerations, as explained in detail with reference to FIG. 2 above. Thus, operation **306** can include receiving the instructions **120** for delivering the data **126** to the requesting device. As noted above, the instructions **120** can define the network requirements for the data transmission such as, for example, which satellites **110** are to provide the data **126**; a time at which the data **126** is to be provided; a duration of the data

transmission; how the data **126** is to be divided (e.g., into data portions **124**); and the like. Because other network requirements are illustrated and described herein, it should be understood that these example requirements are illustrative and should not be construed as limiting in any way.

[0083] From operation **306**, the method **300** can proceed to operation **308**. At operation **308**, the satellite **110** can synchronize delivery of the data **126** to the requesting device (e.g., the user device **102**). Thus, the satellite **110** can be configured to perform operation **308** by identifying, based on the instructions **120**, another satellite **110** that will assist in delivering the data **126** to the user device **102**; timing associated with the data delivery; etc. In some embodiments, the satellite **110** can divide the data into the data portions **124** and provide, to the other satellite **110** that is to assist in delivering the data **126**, one of the data portions **124**. In some other embodiments, each of the satellites **110** may store a copy of the data **126**, so operation **308** can include the satellites **110** being instructed (by the instructions **120** and/or by one of the satellites **110** that can function as a controller for the data delivery), how to divide the data **126**.

[0084] In various embodiments of the concepts and technologies disclosed herein, a first satellite **110** (e.g., the satellite **110A** of FIG. **1**) may be configured to send, stream, and/or otherwise transfer a first data portion **124** (e.g., the data portion **124A**) to the requesting device (e.g., the user device **102**); and a second satellite **110** (e.g., the satellite **110N** of FIG. **1**) may be configured to send, stream, and/or otherwise transfer a second data portion **124** (e.g., the data portion **124N**) to the requesting device (e.g., the user device **102**). These transfers can be completed by the two satellites in a synchronized manner (e.g., substantially simultaneously in some embodiments and/or at various times in some other embodiments).

[0085] In particular, in some embodiments of the concepts and technologies disclosed herein, two or more satellites **110** can be configured to provide two or more data portions **124** to the requesting device simultaneously to increase available bandwidth (e.g., two satellites **110** can provide about double the bandwidth of one satellite **110** in some embodiments; two satellites **110** can provide about triple the bandwidth of one satellite **110** in some other embodiments; etc.). Thus, multiple satellites **110** can be synchronized to provide the data **126** in a shorter time than may be required with only one satellite **110**.

[0086] In some other embodiments, two or more satellites **110** can be configured to provide two or more data portions **124** to the requesting device in a non-simultaneous manner. For example, a first of the two satellites **110** may be in a communication range of the user device **102** for a first half of the time needed to transfer the data **126** to the requesting device, while a second of the two satellites **110** may be in a communication range of the user device **102** for the second half of the time needed to transfer the data **126** to the requesting device. Thus, the two satellites **110** may synchronize the data transfers to provide the data **126** to the requesting device without interruption. Because other uses of synchronization can be used for additional and/or alternative benefits (e.g., different numbers of satellites **110** at various times during the data transmission), it should be understood that these examples are illustrative, and therefore should not be construed as being limiting in any way.

[0087] In yet other embodiments of the concepts and technologies disclosed herein, a specific piece or instance of data **126** may not be transmitted to the requesting device. Rather, the requesting device (or multiple devices) may be provided with data connectivity during a defined time by the synchronized satellite communication service **114** and/or the satellites **110**. Thus, available bandwidth can be modified by the synchronized satellite communication service **114** by instructing the satellites **110** to connect to the requesting device(s) at specific times. Thus, some embodiments of the concepts and technologies disclosed herein can be used to provide flexible bandwidth to precise locations and/or precise users (e.g., devices) at precise times. It should be understood that this example is illustrative, and therefore should not be construed as being limiting in any way.

[0088] From operation **308**, the method **300** can proceed to operation **310**. At operation **310**, the satellite **110** can update a device location (e.g., a current geographic location of the user device

102) and satellite locations (e.g., current locations and/or positions of the satellites **110** relative to the earth, the user device **102**, other satellites **110**, or the like). Thus, operation **310** can correspond to the satellites **110** tracking movements of the receiving device (e.g., the user device **102**) and/or updating their own locations. It should be understood that these examples are illustrative, and therefore should not be construed as being limiting in any way.

[0089] From operation **310**, the method **300** can proceed to operation **312**. At operation **312**, the satellite **110** can determine if any changes are needed. In particular, operation **312** can correspond to the satellite **110** determining if any additional and/or alternative satellites **110** should be used to provide the data **126**. This determination can be based, for example, on changes in locations of the satellites **110** and/or the requesting device; changes in available and/or needed bandwidths; changes in the size or identification of the data **126**; changes in available satellites **110**; changes in positions of the satellites **110**; and/or other considerations. Because other considerations may result in changes being made to the satellites **110** providing the data **126**, it should be understood that these example considerations are illustrative, and therefore should not be construed as being limiting in any way.

[0090] If the satellite **110** determines, in operation **312**, that changes are needed, the method **300** can return to operation **306**, and the satellite **110** can again request orchestration from the synchronized satellite communication service **114**. Thus, it can be appreciated that operations **306-312** can be iterated until the satellite **110** determines, in any iteration of operation **312**, that changes are not needed.

[0091] In some embodiments of the concepts and technologies disclosed herein, the determination in operation **312** can be replaced with a determination as to whether the transmission of the data **126** has been completed, as explained with reference to FIG. 2. In such embodiments, operation **310** can be omitted from the method **300**, and flow from operation **308** can instead proceed to the satellite **110** determining if the data transfer has been completed in operation **312**. Thus, the satellite **110** can determine, in operation **312**, if the requested data transfer has been completed, and if not, the satellite **110** can be configured to request orchestration again from the synchronized satellite communication service **114** in case any changes are needed. In such embodiments, operations **306-312** can be iterated until the satellite **110** determines, in any iteration of operation **312**, that the data transfer has been completed. It should be understood that this example is illustrative, and therefore should not be construed as being limiting in any way.

[0092] If the satellite **110** determines, in operation **312**, that changes to the data transfer are not needed, the method **300** can proceed to operation **314**. In the alternative embodiment noted above, where operation **312** corresponds to a determination as to whether or not the data transfer has been completed, the method **300** can proceed to operation **314** if the satellite **110** determines, in operation **312**, that the data transfer has been completed. The method **300** can end at operation **314**.

[0093] In some embodiments of the concepts and technologies disclosed herein, the satellites **110** can be used to enable a high-trust communication system that can use synchronized transmissions from the satellites to protect communications. For example, the first of the satellites **110** can be configured to deliver a token, and a second of the satellites **110** can be configured to determine data that can be decoded using the token. In yet other embodiments, a message header, or the like, can be sent via a first communication channel (e.g., supported by a first satellite), and message content can be sent via second communication channel (e.g., supported by a second satellite **110**). Thus, in some embodiments of the concepts and technologies disclosed herein, the data portions **124** illustrated and described herein can correspond to portions of the data **126**, tokens, headers, and/or other information. It should be understood that these examples are illustrative, and therefore should not be construed as being limiting in any way.

[0094] While the above FIGURES have primarily described an embodiment in which a user device **102** requests and receives data **126** (optionally divided into data portions **124**), it should be understood that the concepts and technologies disclosed herein can also be used in some

embodiments to deliver multiple instances of the same data **126** (optionally divided into multiple instances of the same data portions **124**) to multiple recipients in a substantially simultaneous manner. For example, any number of devices (optionally including the user device **102**) can receive the same data **126** from one or more satellites **110** at substantially the same time, in some embodiments. Some other embodiments of the concepts and technologies disclosed herein can be used to deliver multiple instances of different data **126** (optionally divided into data portions **124**) to multiple recipients in a substantially simultaneous manner. For example, any number of devices (optionally including the user device **102**) can receive the personalized instances of data **126** (optionally divided into data portions **124**) from one or more satellites **110**, in some embodiments. [0095] For example, embodiments of the concepts and technologies disclosed herein can be used to support a virtual reality (“VR”) and/or cross-reality (“XR”) environment, wherein multiple devices (optionally including the user device **102**) can receive data **126** from the satellites **110**, where each device may receive a different instance of data **126** (e.g., data that is from the VR perspective of that device, etc.). Thus, embodiments of the concepts and technologies disclosed herein can support the satellites **110** delivering the same or different data **126** to multiple devices simultaneously, in some embodiments. It can be appreciated that because the satellites **110** can deliver data **126** in an extremely focused fashion (e.g., direct to a specific device at a specific location), that each of multiple devices can receive a custom instance of data **126** that can be personalized for that device. Thus, for example, a poll of users may be delivered/conducted via embodiments of the concepts and technologies disclosed herein, where a unique link, token, password, code, or the like (as the data **126**) can be delivered to multiple devices substantially simultaneously even at crowded locations using the satellites **110** for delivery of the data **126**. It should be understood that this example is illustrative, and therefore should not be construed as being limiting in any way.

[0096] Turning now to FIG. 4, additional details of the network **104** are illustrated, according to an illustrative embodiment. The network **104** includes a cellular network **402**, a packet data network **404**, for example, the Internet, and a circuit switched network **406**, for example, a publicly switched telephone network (“PSTN”). The cellular network **402** includes various components such as, but not limited to, base transceiver stations (“BTSs”), Node-B's or e-Node-B's, base station controllers (“BSCs”), radio network controllers (“RNCs”), mobile switching centers (“MSCs”), mobile management entities (“MMEs”), short message service centers (“SMSCs”), multimedia messaging service centers (“MMSCs”), home location registers (“HLRs”), home subscriber servers (“HSSs”), visitor location registers (“VLRs”), charging platforms, billing platforms, voicemail platforms, GPRS core network components, location service nodes, an IP Multimedia Subsystem (“IMS”), and the like. The cellular network **402** also includes radios and nodes for receiving and transmitting voice, data, and combinations thereof to and from radio transceivers, networks, the packet data network **404**, and the circuit switched network **406**.

[0097] A mobile communications device **408**, such as, for example, a cellular telephone, a user equipment, a mobile terminal, a PDA, a laptop computer, a handheld computer, and combinations thereof, can be operatively connected to the cellular network **402**. The cellular network **402** can be configured as a 2G GSM network and can provide data communications via GPRS and/or EDGE. Additionally, or alternatively, the cellular network **402** can be configured as a 3G UMTS network and can provide data communications via the HSPA protocol family, for example, HSDPA, EUL (also referred to as HSUPA), and HSPA+. The cellular network **402** also is compatible with 4G mobile communications standards, 5G mobile communications standards, other mobile communications standards, and evolved and future mobile communications standards.

[0098] The packet data network **404** includes various devices, for example, servers, computers, databases, and other devices in communication with one another, as is generally known. The packet data network **404** devices are accessible via one or more network links. The servers often store various files that are provided to a requesting device such as, for example, a computer, a terminal, a smartphone, or the like. Typically, the requesting device includes software (a “browser”) for

executing a web page in a format readable by the browser or other software. Other files and/or data may be accessible via “links” in the retrieved files, as is generally known. In some embodiments, the packet data network **404** includes or is in communication with the Internet. The circuit switched network **406** includes various hardware and software for providing circuit switched communications. The circuit switched network **406** may include, or maybe, what is often referred to as a plain old telephone system (POTS). The functionality of a circuit switched network **406** or other circuit-switched network are generally known and will not be described herein in detail.

[0099] The illustrated cellular network **402** is shown in communication with the packet data network **404** and a circuit switched network **406**, though it should be appreciated that this is not necessarily the case. One or more Internet-capable devices **410**, for example, a PC, a laptop, a portable device, or another suitable device, can communicate with one or more cellular networks **402**, and devices connected thereto, through the packet data network **404**. It also should be appreciated that the Internet-capable device **410** can communicate with the packet data network **404** through the circuit switched network **406**, the cellular network **402**, and/or via other networks (not illustrated).

[0100] As illustrated, a communications device **412**, for example, a telephone, facsimile machine, modem, computer, or the like, can be in communication with the circuit switched network **406**, and therethrough to the packet data network **404** and/or the cellular network **402**. It should be appreciated that the communications device **412** can be an Internet-capable device and can be substantially similar to the Internet-capable device **410**. In the specification, the network **104** is used to refer broadly to any combination of the networks **402**, **404**, **406**. It should be appreciated that substantially all of the functionality described with reference to the network **104** can be performed by the cellular network **402**, the packet data network **404**, and/or the circuit switched network **406**, alone or in combination with other networks, network elements, and the like.

[0101] FIG. **5** is a block diagram illustrating a computer system **500** configured to provide the functionality described herein for providing synchronized satellite communications, in accordance with various embodiments of the concepts and technologies disclosed herein. The computer system **500** includes a processing unit **502**, a memory **504**, one or more user interface devices **506**, one or more input/output (“I/O”) devices **508**, and one or more network devices **510**, each of which is operatively connected to a system bus **512**. The bus **512** enables bi-directional communication between the processing unit **502**, the memory **504**, the user interface devices **506**, the I/O devices **508**, and the network devices **510**.

[0102] The processing unit **502** may be a standard central processor that performs arithmetic and logical operations, a more specific purpose programmable logic controller (“PLC”), a programmable gate array, or other type of processor known to those skilled in the art and suitable for controlling the operation of the server computer. As used herein, the word “processor” and/or the phrase “processing unit” when used with regard to any architecture or system can include multiple processors or processing units distributed across and/or operating in parallel in a single machine or in multiple machines. Furthermore, processors and/or processing units can be used to support virtual processing environments. Processors and processing units also can include state machines, application-specific integrated circuits (“ASICs”), combinations thereof, or the like. Because processors and/or processing units are generally known, the processors and processing units disclosed herein will not be described in further detail herein.

[0103] The memory **504** communicates with the processing unit **502** via the system bus **512**. In some embodiments, the memory **504** is operatively connected to a memory controller (not shown) that enables communication with the processing unit **502** via the system bus **512**. The memory **504** includes an operating system **514** and one or more program modules **516**. The operating system **514** can include, but is not limited to, members of the WINDOWS, WINDOWS CE, and/or WINDOWS MOBILE families of operating systems from MICROSOFT CORPORATION, the LINUX family of operating systems, the SYMBIAN family of operating systems from SYMBIAN

LIMITED, the BREW family of operating systems from QUALCOMM CORPORATION, the MAC OS, iOS, and/or LEOPARD families of operating systems from APPLE CORPORATION, the FREEBSD family of operating systems, the SOLARIS family of operating systems from ORACLE CORPORATION, other operating systems, and the like.

[0104] The program modules **516** may include various software and/or program modules described herein. In some embodiments, for example, the program modules **516** include the synchronized satellite communication application **108**, the synchronization application **112**, and/or the synchronized satellite communication service **114**. These and/or other programs can be embodied in computer-readable media containing instructions that, when executed by the processing unit **502**, perform one or more of the methods **200** and **300** described in detail above with respect to FIGS. **2-3** and/or other functionality as illustrated and described herein. It can be appreciated that, at least by virtue of the instructions embodying the methods **200** and **300**, and/or other functionality illustrated and described herein being stored in the memory **504** and/or accessed and/or executed by the processing unit **502**, the computer system **500** is a special-purpose computing system that can facilitate providing the functionality illustrated and described herein. According to embodiments, the program modules **516** may be embodied in hardware, software, firmware, or any combination thereof. Although not shown in FIG. **5**, it should be understood that the memory **504** also can be configured to store the data request **118**, the instructions **120**, the request **122**, the data portions **124**, the data **126**, the location updates **128**, and/or other data, if desired.

[0105] By way of example, and not limitation, computer-readable media may include any available computer storage media or communication media that can be accessed by the computer system **500**. Communication media includes computer-readable instructions, data structures, program modules, or other data in a modulated data signal such as a carrier wave or other transport mechanism and includes any delivery media. The term “modulated data signal” means a signal that has one or more of its characteristics changed or set in a manner as to encode information in the signal. By way of example, and not limitation, communication media includes wired media such as a wired network or direct-wired connection, and wireless media such as acoustic, RF, infrared and other wireless media. Combinations of the any of the above should also be included within the scope of computer-readable media.

[0106] Computer storage media includes only non-transitory embodiments of computer readable media as illustrated and described herein. Thus, computer storage media can include volatile and non-volatile, removable and non-removable media implemented in any method or technology for storage of information such as computer-readable instructions, data structures, program modules, or other data. Computer storage media includes, but is not limited to, RAM, ROM, Erasable Programmable ROM (“EPROM”), Electrically Erasable Programmable ROM (“EEPROM”), flash memory or other solid state memory technology, CD-ROM, digital versatile disks (“DVD”), or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by the computer system **500**. In the claims, the phrase “computer storage medium” and variations thereof does not include waves or signals per se and/or communication media.

[0107] The user interface devices **506** may include one or more devices with which a user accesses the computer system **500**. The user interface devices **506** may include, but are not limited to, computers, servers, personal digital assistants, cellular phones, or any suitable computing devices. The I/O devices **508** enable a user to interface with the program modules **516**. In one embodiment, the I/O devices **508** are operatively connected to an I/O controller (not shown) that enables communication with the processing unit **502** via the system bus **512**. The I/O devices **508** may include one or more input devices, such as, but not limited to, a keyboard, a mouse, or an electronic stylus. Further, the I/O devices **508** may include one or more output devices, such as, but not limited to, a display screen or a printer.

[0108] The network devices **510** enable the computer system **500** to communicate with other

networks or remote systems via a network, such as the network **104**. Examples of the network devices **510** include, but are not limited to, a modem, a radio frequency (“RF”) or infrared (“IR”) transceiver, a telephonic interface, a bridge, a router, or a network card. The network **104** may include a wireless network such as, but not limited to, a Wireless Local Area Network (“WLAN”) such as a WI-FI network, a Wireless Wide Area Network (“WWAN”), a Wireless Personal Area Network (“WPAN”) such as BLUETOOTH, a Wireless Metropolitan Area Network (“WMAN”) such as a WiMAX network, or a cellular network. Alternatively, the network **104** may be a wired network such as, but not limited to, a Wide Area Network (“WAN”) such as the Internet, a Local Area Network (“LAN”) such as the Ethernet, a wired Personal Area Network (“PAN”), or a wired Metropolitan Area Network (“MAN”).

[0109] Turning now to FIG. **6**, an illustrative mobile device **600** and components thereof will be described. In some embodiments, the user device **102** and/or the other device **130** described above with reference to FIGS. **1-3** can be configured as and/or can have an architecture similar or identical to the mobile device **600** described herein in FIG. **6**. It should be understood, however, that the user device **102** and/or the other device **130** may or may not include the functionality described herein with reference to FIG. **6**. While connections are not shown between the various components illustrated in FIG. **6**, it should be understood that some, none, or all of the components illustrated in FIG. **6** can be configured to interact with one another to carry out various device functions. In some embodiments, the components are arranged so as to communicate via one or more buses (not shown). Thus, it should be understood that FIG. **6** and the following description are intended to provide a general understanding of a suitable environment in which various aspects of embodiments can be implemented and should not be construed as being limiting in any way.

[0110] As illustrated in FIG. **6**, the mobile device **600** can include a display **602** for displaying data. According to various embodiments, the display **602** can be configured to display various graphical user interface (“GUI”) elements such as, for example, text, images, video, virtual keypads and/or keyboards, messaging data, notification messages, metadata, internet content, device status, time, date, calendar data, device preferences, map and location data, combinations thereof, and/or the like. The mobile device **600** also can include a processor **604** and a memory or other data storage device (“memory”) **606**. The processor **604** can be configured to process data and/or can execute computer-executable instructions stored in the memory **606**. The computer-executable instructions executed by the processor **604** can include, for example, an operating system **608**, one or more applications **610** such as the synchronized satellite communication application **108**, the synchronization application **112**, the synchronized satellite communication service **114**, other computer-executable instructions stored in a memory **606**, or the like. In some embodiments, the applications **610** also can include a UI application (not illustrated in FIG. **6**).

[0111] The UI application can interface with the operating system **608** to facilitate user interaction with functionality and/or data stored at the mobile device **600** and/or stored elsewhere. In some embodiments, the operating system **608** can include a member of the SYMBIAN OS family of operating systems from SYMBIAN LIMITED, a member of the WINDOWS MOBILE OS and/or WINDOWS PHONE OS families of operating systems from MICROSOFT CORPORATION, a member of the PALM WEBOS family of operating systems from HEWLETT PACKARD CORPORATION, a member of the BLACKBERRY OS family of operating systems from RESEARCH IN MOTION LIMITED, a member of the IOS family of operating systems from APPLE INC., a member of the ANDROID OS family of operating systems from GOOGLE INC., and/or other operating systems. These operating systems are merely illustrative of some contemplated operating systems that may be used in accordance with various embodiments of the concepts and technologies described herein and therefore should not be construed as being limiting in any way.

[0112] The UI application can be executed by the processor **604** to aid a user in entering content, configuring settings, manipulating address book content and/or settings, multimode interaction,

interacting with other applications **610**, and otherwise facilitating user interaction with the operating system **608**, the applications **610**, and/or other types or instances of data **612** that can be stored at the mobile device **600**. The data **612** can include, for example, the data request **118**, the instructions **120**, the request **122**, the data portions **124**, the data **126**, the location updates **128**, and/or applications or program modules. According to various embodiments, the data **612** can include, for example, presence applications, visual voice mail applications, messaging applications, text-to-speech and speech-to-text applications, add-ons, plug-ins, email applications, music applications, video applications, camera applications, location-based service applications, power conservation applications, game applications, productivity applications, entertainment applications, enterprise applications, combinations thereof, and the like. The applications **610**, the data **612**, and/or portions thereof can be stored in the memory **606** and/or in a firmware **614**, and can be executed by the processor **604**.

[0113] It can be appreciated that, at least by virtue of storage of the instructions corresponding to the applications **610** and/or other instructions embodying other functionality illustrated and described herein in the memory **606**, and/or by virtue of the instructions corresponding to the applications **610** and/or other instructions embodying other functionality illustrated and described herein being accessed and/or executed by the processor **604**, the mobile device **600** is a special-purpose mobile device that can facilitate providing the functionality illustrated and described herein. The firmware **614** also can store code for execution during device power up and power down operations. It can be appreciated that the firmware **614** can be stored in a volatile or non-volatile data storage device including, but not limited to, the memory **606** and/or a portion thereof.

[0114] The mobile device **600** also can include an input/output (“I/O”) interface **616**. The I/O interface **616** can be configured to support the input/output of data such as location information, the data request **118**, the instructions **120**, the request **122**, the data portions **124**, the data **126**, the location updates **128**, user information, organization information, presence status information, user IDs, passwords, and application initiation (start-up) requests. In some embodiments, the I/O interface **616** can include a hardwire connection such as a universal serial bus (“USB”) port, a mini-USB port, a micro-USB port, an audio jack, a PS2 port, an IEEE 1394 (“FIREWIRE”) port, a serial port, a parallel port, an Ethernet (RJ45 or RJ48) port, a telephone (RJ11 or the like) port, a proprietary port, combinations thereof, or the like. In some embodiments, the mobile device **600** can be configured to synchronize with another device to transfer content to and/or from the mobile device **600**. In some embodiments, the mobile device **600** can be configured to receive updates to one or more of the applications **610** via the I/O interface **616**, though this is not necessarily the case. In some embodiments, the I/O interface **616** accepts I/O devices such as keyboards, keypads, mice, interface tethers, printers, plotters, external storage, touch/multi-touch screens, touch pads, trackballs, joysticks, microphones, remote control devices, displays, projectors, medical equipment (e.g., stethoscopes, heart monitors, and other health metric monitors), modems, routers, external power sources, docking stations, combinations thereof, and the like. It should be appreciated that the I/O interface **616** may be used for communications between the mobile device **600** and a network device or local device.

[0115] The mobile device **600** also can include a communications component **618**. The communications component **618** can be configured to interface with the processor **604** to facilitate wired and/or wireless communications with one or more networks such as the network **104** described herein. In some embodiments, other networks include networks that utilize non-cellular wireless technologies such as WI-FI or WIMAX. In some embodiments, the communications component **618** includes a multimode communications subsystem for facilitating communications via the cellular network and one or more other networks.

[0116] The communications component **618**, in some embodiments, includes one or more transceivers. The one or more transceivers, if included, can be configured to communicate over the same and/or different wireless technology standards with respect to one another. For example, in

some embodiments one or more of the transceivers of the communications component **618** may be configured to communicate using GSM, CDMAONE, CDMA2000, LTE, and various other 2G, 2.5G, 3G, 4G, 5G, and greater generation technology standards. Moreover, the communications component **618** may facilitate communications over various channel access methods (which may or may not be used by the aforementioned standards) including, but not limited to, TDMA, FDMA, W-CDMA, OFDM, SDMA, and the like.

[0117] In addition, the communications component **618** may facilitate data communications using GPRS, EDGE, the HSPA protocol family including HSDPA, EUL or otherwise termed HSUPA, HSPA+, and various other current and future wireless data access standards. In the illustrated embodiment, the communications component **618** can include a first transceiver (“TxRx”) **620A** that can operate in a first communications mode (e.g., GSM). The communications component **618** also can include an N.sup.th transceiver (“TxRx”) **620N** that can operate in a second communications mode relative to the first transceiver **620A** (e.g., UMTS). While two transceivers **620A-N** (hereinafter collectively and/or generically referred to as “transceivers **620**”) are shown in FIG. **6**, it should be appreciated that less than two, two, and/or more than two transceivers **620** can be included in the communications component **618**.

[0118] The communications component **618** also can include an alternative transceiver (“Alt TxRx”) **622** for supporting other types and/or standards of communications. According to various contemplated embodiments, the alternative transceiver **622** can communicate using various communications technologies such as, for example, WI-FI, WIMAX, BLUETOOTH, infrared, infrared data association (“IRDA”), near field communications (“NFC”), other RF technologies, combinations thereof, and the like. In some embodiments, the communications component **618** also can facilitate reception from terrestrial radio networks, digital satellite radio networks, internet-based radio service networks, combinations thereof, and the like. The communications component **618** can process data from a network such as the Internet, an intranet, a broadband network, a WI-FI hotspot, an Internet service provider (“ISP”), a digital subscriber line (“DSL”) provider, a broadband provider, combinations thereof, or the like.

[0119] The mobile device **600** also can include one or more sensors **624**. The sensors **624** can include temperature sensors, light sensors, air quality sensors, movement sensors, orientation sensors, noise sensors, proximity sensors, or the like. As such, it should be understood that the sensors **624** can include, but are not limited to, accelerometers, magnetometers, gyroscopes, infrared sensors, noise sensors, microphones, combinations thereof, or the like. Additionally, audio capabilities for the mobile device **600** may be provided by an audio I/O component **626**. The audio I/O component **626** of the mobile device **600** can include one or more speakers for the output of audio signals, one or more microphones for the collection and/or input of audio signals, and/or other audio input and/or output devices.

[0120] The illustrated mobile device **600** also can include a subscriber identity module (“SIM”) system **628**. The SIM system **628** can include a universal SIM (“USIM”), a universal integrated circuit card (“UICC”) and/or other identity devices. The SIM system **628** can include and/or can be connected to or inserted into an interface such as a slot interface **630**. In some embodiments, the slot interface **630** can be configured to accept insertion of other identity cards or modules for accessing distinct types of networks. Additionally, or alternatively, the slot interface **630** can be configured to accept multiple subscriber identity cards. Because other devices and/or modules for identifying users and/or the mobile device **600** are contemplated, it should be understood that these embodiments are illustrative, and should not be construed as being limiting in any way.

[0121] The mobile device **600** also can include an image capture and processing system **632** (“image system”). The image system **632** can be configured to capture or otherwise obtain photos, videos, and/or other visual information. As such, the image system **632** can include cameras, lenses, charge-coupled devices (“CCDs”), combinations thereof, or the like. The mobile device **600** may also include a video system **634**. The video system **634** can be configured to capture, process,

record, modify, and/or store video content. Photos and videos obtained using the image system **632** and the video system **634**, respectively, may be added as message content to an MMS message, email message, and sent to another mobile device. The video and/or photo content also can be shared with other devices via distinct types of data transfers via wired and/or wireless communication devices as described herein.

[0122] The mobile device **600** also can include one or more location components **636**. The location components **636** can be configured to send and/or receive signals to determine a geographic location of the mobile device **600**. According to various embodiments, the location components **636** can send and/or receive signals from global positioning system (“GPS”) devices, assisted-GPS (“A-GPS”) devices, WI-FI/WIMAX and/or cellular network triangulation data, combinations thereof, and the like. The location component **636** also can be configured to communicate with the communications component **618** to retrieve triangulation data for determining a location of the mobile device **600**. In some embodiments, the location component **636** can interface with cellular network nodes, telephone lines, satellites, location transmitters and/or beacons, wireless network transmitters and receivers, combinations thereof, and the like. In some embodiments, the location component **636** can include and/or can communicate with one or more of the sensors **624** such as a compass, an accelerometer, and/or a gyroscope to determine the orientation of the mobile device **600**. Using the location component **636**, the mobile device **600** can generate and/or receive data to identify its geographic location, or to transmit data used by other devices to determine the location of the mobile device **600**. The location component **636** may include multiple components for determining the location and/or orientation of the mobile device **600**.

[0123] The illustrated mobile device **600** also can include a power source **638**. The power source **638** can include one or more batteries, power supplies, power cells, and/or other power subsystems including alternating current (“AC”) and/or direct current (“DC”) power devices. The power source **638** also can interface with an external power system or charging equipment via a power I/O component **640**. Because the mobile device **600** can include additional and/or alternative components, the above embodiment should be understood as being illustrative of one possible operating environment for various embodiments of the concepts and technologies described herein. The described embodiment of the mobile device **600** is illustrative and should not be construed as limiting in any way.

[0124] FIG. 7 illustrates an illustrative architecture for a cloud computing platform **700** that can be capable of executing the software components described herein for providing and/or using synchronized satellite communications and/or for interacting with the synchronized satellite communication service **114**. Thus, it can be appreciated that in some embodiments of the concepts and technologies disclosed herein, the cloud computing platform **700** illustrated in FIG. 7 can be used to provide the functionality described herein with respect to the user device **102**, the server computer **116**, and/or the other device **130**. The satellites **110** also can be configured to incorporate some cloud-based technologies, in some embodiments.

[0125] The cloud computing platform **700** thus may be utilized to execute any aspects of the software components presented herein. Thus, according to various embodiments of the concepts and technologies disclosed herein, the synchronized satellite communication application **108**, the synchronization application **112**, and/or the synchronized satellite communication service **114** can be implemented, at least in part, on or by elements included in the cloud computing platform **700** illustrated and described herein. Those skilled in the art will appreciate that the illustrated cloud computing platform **700** is a simplification of but only one possible implementation of an illustrative cloud computing platform, and as such, the illustrated cloud computing platform **700** should not be construed as being limiting in any way.

[0126] In the illustrated embodiment, the cloud computing platform **700** can include a hardware resource layer **702**, a virtualization/control layer **704**, and a virtual resource layer **706**. These layers and/or other layers can be configured to cooperate with each other and/or other elements of a cloud

computing platform **700** to perform operations as will be described in detail herein. While connections are shown between some of the components illustrated in FIG. 7, it should be understood that some, none, or all of the components illustrated in FIG. 7 can be configured to interact with one another to carry out various functions described herein. In some embodiments, the components are arranged so as to communicate via one or more networks such as, for example, the network **104** illustrated and described hereinabove (not shown in FIG. 7). Thus, it should be understood that FIG. 7 and the following description are intended to provide a general understanding of a suitable environment in which various aspects of embodiments can be implemented and should not be construed as being limiting in any way.

[0127] The hardware resource layer **702** can provide hardware resources. In the illustrated embodiment, the hardware resources can include one or more compute resources **708**, one or more memory resources **710**, and one or more other resources **712**. The compute resource(s) **708** can include one or more hardware components that can perform computations to process data, and/or to execute computer-executable instructions of one or more application programs, operating systems, services, and/or other software including, but not limited to, the synchronized satellite communication application **108**, the synchronization application **112**, and/or the synchronized satellite communication service **114**, illustrated and described herein.

[0128] According to various embodiments, the compute resources **708** can include one or more central processing units (“CPUs”). The CPUs can be configured with one or more processing cores. In some embodiments, the compute resources **708** can include one or more graphics processing units (“GPUs”). The GPUs can be configured to accelerate operations performed by one or more CPUs, and/or to perform computations to process data, and/or to execute computer-executable instructions of one or more application programs, operating systems, and/or other software that may or may not include instructions that are specifically graphics computations and/or related to graphics computations. In some embodiments, the compute resources **708** can include one or more discrete GPUs. In some other embodiments, the compute resources **708** can include one or more CPU and/or GPU components that can be configured in accordance with a co-processing CPU/GPU computing model. Thus, it can be appreciated that in some embodiments of the compute resources **708**, a sequential part of an application can execute on a CPU and a computationally intensive part of the application can be accelerated by the GPU. It should be understood that this example is illustrative, and therefore should not be construed as being limiting in any way.

[0129] In some embodiments, the compute resources **708** also can include one or more system on a chip (“SoC”) components. It should be understood that the an SoC component can operate in association with one or more other components as illustrated and described herein, for example, one or more of the memory resources **710** and/or one or more of the other resources **712**. In some embodiments in which an SoC component is included, the compute resources **708** can be or can include one or more embodiments of the SNAPDRAGON brand family of SoCs, available from QUALCOMM of San Diego, California; one or more embodiment of the TEGRA brand family of SoCs, available from NVIDIA of Santa Clara, California; one or more embodiment of the HUMMINGBIRD brand family of SoCs, available from SAMSUNG of Seoul, South Korea; one or more embodiment of the Open Multimedia Application Platform (“OMAP”) family of SoCs, available from TEXAS INSTRUMENTS of Dallas, Texas; one or more customized versions of any of the above SoCs; and/or one or more other brand and/or one or more proprietary SoCs.

[0130] The compute resources **708** can be or can include one or more hardware components arranged in accordance with architectures available for license from ARM HOLDINGS of Cambridge, United Kingdom. Alternatively, the compute resources **708** can be or can include one or more hardware components arranged in accordance with architectures available from INTEL CORPORATION of Mountain View, California, and others. Those skilled in the art will appreciate the implementation of the compute resources **708** can utilize various computation architectures and/or processing architectures. As such, the various example embodiments of the compute

resources **708** as mentioned hereinabove should not be construed as being limiting in any way. Rather, implementations of embodiments of the concepts and technologies disclosed herein can be implemented using compute resources **708** having any of the particular computation architecture and/or combination of computation architectures mentioned herein as well as other architectures. [0131] Although not separately illustrated in FIG. 7, it should be understood that the compute resources **708** illustrated and described herein can host and/or execute assorted services, applications, portals, and/or other functionality illustrated and described herein. Thus, the compute resources **708** can host and/or can execute the synchronized satellite communication application **108**, the synchronization application **112**, the synchronized satellite communication service **114**, or other applications or services illustrated and described herein.

[0132] The memory resource(s) **710** can include one or more hardware components that can perform or provide storage operations, including temporary and/or permanent storage operations. In some embodiments, the memory resource(s) **710** can include volatile and/or non-volatile memory implemented in any method or technology for storage of information such as computer-readable instructions, data structures, program modules, or other data disclosed herein. Computer storage media is defined hereinabove and therefore should be understood as including, in various embodiments, random access memory (“RAM”), read-only memory (“ROM”), Erasable Programmable ROM (“EPROM”), Electrically Erasable Programmable ROM (“EEPROM”), flash memory or other solid state memory technology, CD-ROM, digital versatile disks (“DVD”), or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium that can be used to store data and that can be accessed by the compute resources **708**, subject to the definition of “computer storage media” provided above (e.g., as excluding waves and signals per se and/or communication media as defined in this application).

[0133] Although not illustrated in FIG. 7, it should be understood that the memory resources **710** can host or store the various data illustrated and described herein including, but not limited to, the data request **118**, the instructions **120**, the request **122**, the data portions **124**, the data **126**, the location updates **128**, and/or other data, if desired. It should be understood that this example is illustrative, and therefore should not be construed as being limiting in any way.

[0134] The other resource(s) **712** can include any other hardware resources that can be utilized by the compute resources(s) **708** and/or the memory resource(s) **710** to perform operations. The other resource(s) **712** can include one or more input and/or output processors (e.g., a network interface controller and/or a wireless radio), one or more modems, one or more codec chipsets, one or more pipeline processors, one or more fast Fourier transform (“FFT”) processors, one or more digital signal processors (“DSPs”), one or more speech synthesizers, combinations thereof, or the like.

[0135] The hardware resources operating within the hardware resource layer **702** can be virtualized by one or more virtual machine monitors (“VMMs”) **714A-714N** (also known as “hypervisors;” hereinafter “VMMs **714**”). The VMMs **714** can operate within the virtualization/control layer **704** to manage one or more virtual resources that can reside in the virtual resource layer **706**. The VMMs **714** can be or can include software, firmware, and/or hardware that alone or in combination with other software, firmware, and/or hardware, can manage one or more virtual resources operating within the virtual resource layer **706**.

[0136] The virtual resources operating within the virtual resource layer **706** can include abstractions of at least a portion of the compute resources **708**, the memory resources **710**, the other resources **712**, or any combination thereof. These abstractions are referred to herein as virtual machines (“VMs”). In the illustrated embodiment, the virtual resource layer **706** includes VMs **716A-716N** (hereinafter “VMs **716**”).

[0137] Based on the foregoing, it should be appreciated that systems and methods for synchronized satellite communications have been disclosed herein. Although the subject matter presented herein has been described in language specific to computer structural features, methodological and transformative acts, specific computing machinery, and computer-readable media, it is to be

understood that the concepts and technologies disclosed herein are not necessarily limited to the specific features, acts, or media described herein. Rather, the specific features, acts and mediums are disclosed as example forms of implementing the concepts and technologies disclosed herein. [0138] The subject matter described above is provided by way of illustration only and should not be construed as limiting. Various modifications and changes may be made to the subject matter described herein without following the example embodiments and applications illustrated and described, and without departing from the true spirit and scope of the embodiments of the concepts and technologies disclosed herein.

Claims

1. A system comprising: a processor; and a memory that stores computer-executable instructions that, when executed by the processor, cause the processor to perform operations comprising: determining a geographic location of a requesting device and locations of a plurality of satellites at a time that the requesting device will receive data; identifying, based on the geographic location of the requesting device and the locations of the plurality of satellites, satellites that will provide the data to the requesting device; and providing instructions to at least one of the satellites, wherein the instructions comprise satellite network requirements for the satellites to provide the data.
2. The system of claim 1, wherein the computer-executable instructions, when executed by the processor, cause the processor to perform further operations comprising: determining if changes should be made to the satellites that will provide the data to the requesting device; and in response to a determination that the changes should be made, updating the geographic location of the requesting device and the locations of the satellites, and identifying the satellites based on an updated geographic location and updated locations.
3. The system of claim 1, wherein the computer-executable instructions, when executed by the processor, cause the processor to perform operations further comprising: determining if a data transfer by the satellites to the requesting device has been completed; and in response to a determination that the data transfer has not been completed, again identifying the satellites.
4. The system of claim 1, wherein the instructions define how the data is to be divided into data portions for delivery by the satellites and the time at which each data portion is to be delivered, wherein a first satellite delivers a first of the data portions to the requesting device at the time, and wherein a second satellite delivers a second of the data portions to the requesting device at the time.
5. The system of claim 1, wherein the data comprises a first instance of the data intended for the requesting device and a second instance of data intended for another device, wherein a first satellite delivers the first instance of the data to the requesting device at the time, and wherein a second satellite delivers the second instance of data to the another device at the time.
6. The system of claim 5, the first instance of the data comprises a first token that is unique to the requesting device, and wherein the second instance of data comprises a second token that is unique to the another device.
7. The system of claim 1, wherein a first satellite delivers the data to the requesting device at the time, and wherein a second satellite delivers the data to another device at the time.
8. A method comprising: determining, by a computer comprising a processor, a geographic location of a requesting device and locations of a plurality of satellites at a time when the requesting device will receive data; identifying, by the processor and based on the geographic location of the requesting device and the locations of the plurality of satellites, satellites that can provide the data to the requesting device; providing, by the processor, instructions to at least one of the satellites, wherein the instructions comprising satellite network requirements for the satellites.
9. The method of claim 8, further comprising: determining if changes should be made to the satellites that will provide the data to the requesting device; and in response to a determination that the changes should be made, updating the geographic location of the requesting device and the

locations of the satellites, and identifying the satellites based on an updated geographic location and updated locations.

10. The method of claim 8, further comprising: determining if a data transfer by the satellites to the requesting device has been completed; and in response to a determination that the data transfer has not been completed, again identifying the satellites.

11. The method of claim 8, wherein the instructions define how the data is to be divided into data portions for delivery by the satellites and the time at which each data portion is to be delivered.

12. The method of claim 11, wherein a first satellite delivers a first portion of the data portions to the requesting device at the time, and wherein a second satellite delivers a second portion of the data portions to the requesting device at the time.

13. The method of claim 8, wherein the data comprises a first instance of data intended for the requesting device and a second instance of data intended for another device, wherein a first satellite delivers the first instance of data to the requesting device at the time, and wherein a second satellite delivers the second instance of data to the another device at the time.

14. The method of claim 8, wherein a first satellite delivers the data to the requesting device at the time, and wherein a second satellite delivers the data to another device at the time.

15. A non-transitory, computer storage medium having computer-executable instructions stored thereon that, when executed by a processor, cause the processor to perform operations comprising: determining a geographic location of a requesting device and locations of a plurality of satellites at a time when the requesting device will receive data; identifying, based on the geographic location of the requesting device and the locations of the plurality of satellites, satellites to provide the data to the requesting device; providing instructions to a satellite of the satellites, wherein the instructions comprising satellite network requirements for the satellites.

16. The non-transitory, computer storage medium of claim 15, wherein the computer-executable instructions, when executed by the processor, cause the processor to perform operations further comprising: determining if changes should be made to the satellites that will provide the data to the requesting device; and in response to a determination that the changes should be made, updating the geographic location of the requesting device and the locations of the satellites, and identifying the satellites based on an updated geographic location and updated locations.

17. The non-transitory, computer storage medium of claim 15, wherein the computer-executable instructions, when executed by the processor, cause the processor to perform operations further comprising: determining if a data transfer by the satellites to the requesting device has been completed; and in response to a determination that the data transfer has not been completed, again identifying the satellites.

18. The non-transitory, computer storage medium of claim 15, wherein the instructions define how the data is to be divided into data portions for delivery by the satellites and the time at which each data portion is to be delivered, wherein a first satellite delivers a first of the data portions to the requesting device at the time, and wherein a second satellite delivers a second of the data portions to the requesting device at the time.

19. The non-transitory, computer storage medium of claim 15, wherein the data comprises a first instance of data intended for the requesting device and a second instance of data intended for another device, wherein a first satellite delivers the first instance of data to the requesting device at the time, and wherein a second satellite delivers the second instance of data to the another device at the time.

20. The non-transitory, computer storage medium of claim 15, wherein a first satellite delivers the data to the requesting device at the time, and wherein a second satellite delivers the data to another device at the time.
