

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12386595
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Janzen; Mark et al.

Accessing stored code strings for execution to produce resources for diverse situations

Abstract

A software configuration includes to store, in a strings memory, combinations of possible source locations and of possible destination locations that are subject to rules pairwise, and to further store respective code strings in association with the respective combinations. The possible locations may be stored by alphanumeric designators, for convenience in looking up the code strings. These code strings may be in a form that is mostly alphanumeric, may embed numerical parameters, and may even represent numerical operations. In fact, a code string of this type may even be configured in the form of code which, upon being executed, implements the rule that is applicable to the combination of the code string's source location and their destination location. The looked-up code string, or a code module generated from it, may then indeed be executed, to produce a resource that complies with the applicable rule.

Inventors:	Janzen; Mark (Wichita, KS), Kavounas; Gregory T. (Bellevue, WA)
Applicant:	Avalara, Inc. (N/A, N/A)
Family ID:	1000008749868
Assignee:	Avalara, Inc. (Seattle, WA)
Appl. No.:	18/762356
Filed:	July 02, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240354067 A1	Oct. 24, 2024

Related U.S. Application Data

Publication Classification

Int. Cl.: G06F8/30 (20180101); G06F16/245 (20190101); G06Q20/20 (20120101)

U.S. Cl.:

CPC G06F8/30 (20130101); G06F16/245 (20190101); G06Q20/207 (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7783536	12/2009	William et al.	N/A	N/A
7933803	12/2010	Nadler et al.	N/A	N/A
8620578	12/2012	Brown et al.	N/A	N/A
8725407	12/2013	Hurley et al.	N/A	N/A
9760915	12/2016	Pavlou et al.	N/A	N/A
10332216	12/2018	Barsade et al.	N/A	N/A
10445818	12/2018	Chowdhary	N/A	N/A
10769611	12/2019	McNeel	N/A	N/A
10872100	12/2019	Shefferman et al.	N/A	N/A
11176620	12/2020	Lubczynski et al.	N/A	N/A
11238542	12/2021	Wixted et al.	N/A	N/A
2002/0138765	12/2001	Fishman et al.	N/A	N/A
2007/0136158	12/2006	Rawlings et al.	N/A	N/A
2007/0136159	12/2006	Rawlings et al.	N/A	N/A
2009/0187500	12/2008	Wilson et al.	N/A	N/A
2013/0013471	12/2012	Fishman	N/A	N/A
2013/0061208	12/2012	Tsao et al.	N/A	N/A
2014/0172656	12/2013	Shaw	N/A	N/A
2014/0351105	12/2013	Hamm	N/A	N/A
2016/0042466	12/2015	Herndon et al.	N/A	N/A
2016/0140668	12/2015	Maguire et al.	N/A	N/A
2019/0114609	12/2018	Burton et al.	N/A	N/A
2021/0158456	12/2020	Morgan et al.	N/A	N/A
2021/0303279	12/2020	Bird et al.	N/A	N/A

OTHER PUBLICATIONS

Notice of Allowance, U.S. Appl. No. 17/564,182, May 2, 2024, 23 pages. cited by applicant

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of application Ser. No. 17/564,182, filed Dec. 28, 2021 (now U.S. Pat. No. 12,061,879), which claims the benefit of Provisional Application No. 63/240,079, filed Sep. 2, 2021, which are hereby incorporated by reference.

BACKGROUND

(1) Providing, in a timely and efficient manner, accurate and reliable production of resources presents a technical problem for current ERP applications. Computations may be performed that implement rules, but the rules need to look up parameter values that would be different in diverse situations at run time, which presents the problem that the production of resources consumes a lot of time.

BRIEF SUMMARY

(2) The present description gives instances of software configurations, computer systems, storage media that may store programs, and methods.

(3) In embodiments, a software configuration includes to store, in a strings memory, combinations of possible source locations and of possible destination locations that are subject to rules pairwise, and to further store respective code strings in association with the respective combinations. The possible locations may be stored by alphanumeric designators, for convenience in looking up the code strings. These code strings may be in a form that is mostly alphanumeric, may embed numerical parameters, and may even represent numerical operations. In fact, a code string of this type may even be configured in the form of code which, upon being executed, implements the rule that is applicable to the combination of the code string's source location and their destination location. The looked-up code string, or a code module generated from it, may then indeed be executed, to produce a resource that complies with the applicable rule.

(4) Such software configurations can be implemented in use cases discussed later in this document. By storing a code string that is executable, and which already has numerical values for its parameters, time is saved from having to look up the values of the parameters for the diverse situations for producing each resource. In fact, the improvements in performance time can even be an order of magnitude. As such, the present disclosure provides configurations, systems, computer-readable media, and methods that solve these technical problems by increasing the speed of specialized software platforms and computer networks, and thus improving the technology of ERP software applications.

(5) Therefore, the systems and methods described herein for selected resource production improve the functioning of computers or other hardware, by reducing the processing, storage, and/or data transmission resources needed to perform various tasks in real time, and thereby enabling the tasks to be performed by less capable, capacious, and/or expensive hardware devices, enabling the tasks to be performed with less latency and/or preserving more of the conserved resources for use in performing other tasks or additional instances of the same task.

(6) As such, it will be appreciated that results of embodiments are larger than the sum of their individual parts, and have utility.

(7) These and other features and advantages of the claimed invention will become more readily apparent in view of the embodiments described and illustrated in this specification, namely in this written specification and the associated drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a diagram showing sample aspects of embodiments.
- (2) FIG. 2 shows a perspective view of a sample two-dimensional domain, a sample source location and a sample destination location within the domain, a sample item associated with the sample source location, and a sample code string, according to embodiments.
- (3) FIG. 3 shows a perspective view of a sample three-dimensional domain, a sample source location and a sample destination location within the domain, a sample item associated with the sample source location and a sample code string, according to embodiments.
- (4) FIG. 4A is a map of the City of Seattle, where a sample source location and a sample destination location are also shown, along with an associated sample code string, according to embodiments.
- (5) FIG. 4B is the map of FIG. 4A, which further has been partitioned in location code tiles to a four-level approximation, for generating location lookup codes, according to embodiments.
- (6) FIG. 5 is a diagram of a sample domain, a sample source location and a sample destination location within the domain, a sample code string, and in which the domain has been partitioned into tiles that have a first sample numbering scheme, according to embodiments.
- (7) FIG. 6 is a diagram of a sample domain, a sample source location and a sample destination location within the domain, a sample code string, and in which the domain has been partitioned into tiles that have a second sample numbering scheme, according to embodiments.
- (8) FIG. 7 is a diagram of a sample domain, a sample source location and a sample destination location within the domain, a sample code string, and in which the domain has been partitioned into tiles that have a third sample numbering scheme, according to embodiments.
- (9) FIG. 8 is a diagram of a sample domain, a sample source location and a sample destination location within the domain, a sample code string, and in which the domain has been partitioned into tiles that have a fourth sample numbering scheme, according to embodiments.
- (10) FIG. 9 is a diagram of a sample map with a portion identified and numbered per schemes in the prior art.
- (11) FIG. 10 is a diagram for describing aspects of accessing a strings memory and looking up a code string from it, according to embodiments.
- (12) FIG. 11A is a diagram for describing aspects of accessing a strings memory and looking up a code string from it, according to embodiments.
- (13) FIG. 11B is a diagram for describing aspects of accessing a strings memory when it is hosted remotely according to embodiments.
- (14) FIG. 11C is a diagram for describing aspects of accessing a strings memory when it is hosted remotely according to additional embodiments.
- (15) FIG. 12 is a diagram of first sample organization of a strings memory according to embodiments.
- (16) FIG. 13 is a diagram of second sample organization of a strings memory according to embodiments.
- (17) FIG. 14 is a table of sample values for a code string and a code module according to embodiments.
- (18) FIG. 15 is an image of a portion of a User Interface of an execution module, in which a sample code module can be seen, and which includes a logical “IF” statement according to embodiments.
- (19) FIG. 16A is a diagram of a sample way for a code module to be generated according to embodiments.
- (20) FIG. 16B is a table of sample values for embodiments of the components of FIG. 16A.
- (21) FIG. 17 is a diagram for showing a first example of how the executing of a code module can

be performed in conjunction with a base value according to embodiments.

(22) FIG. **18** is a diagram for showing a second example of how the executing of a code module can be performed in conjunction with a base value according to embodiments.

(23) FIG. **19** is a diagram of sample interactions for producing a resource according to embodiments.

(24) FIG. **20** is a diagram for showing the generation of a code module from two code strings according to embodiments.

(25) FIG. **21** is a diagram of other sample interactions for producing a resource according to embodiments.

(26) FIG. **22** is a flowchart for illustrating sample methods according to embodiments.

(27) FIG. **23** is a block diagram showing additional components of sample computer systems according to embodiments.

(28) FIG. **24** is a diagram of sample aspects for describing operational examples and use cases of embodiments.

(29) FIG. **25** is a flowchart for illustrating sample methods according to embodiments.

DETAILED DESCRIPTION

(30) As has been mentioned, the present description is about software configurations, computer systems, storage media that may store programs, and methods. Embodiments are now described in more detail.

(31) FIG. **1** is a diagram showing sample aspects of embodiments. A thick line **115** separates this diagram, although not completely or rigorously, into a top portion and a bottom portion. Above the line **115** the emphasis is mostly on entities, components, their relationships, and their interactions, while below the line **115** the emphasis is mostly processing of data that takes place often within one or more of the components above the line **115**.

(32) Above the line **115**, a sample computer system **195** according to embodiments is shown. The computer system **195** has one or more processors **194** and a memory **130**. The memory **130** stores programs **131** for running on the one or more processors **194**, and data **138**. The memory **130** may include designated portions for specific types of data **138**, for example the memory **130** may include one or more records memories designated for certain types of records designated by clients, by rules, by types of data and so on. The one or more processors **194** and the memory **130** of the computer system **195** thus implement a service engine **183**. Additional implementation details for the computer system **195** are given later in this document.

(33) The computer system **195** can be located in “the cloud.” In fact, the computer system **195** may optionally be implemented as part of an online software platform (OSP) **198**. The OSP **198** can be configured to perform one or more predefined services, for example via operations of the service engine **183**. Such services can be searches, determinations, computations, verifications, notifications, the transmission of specialized information, including data that effectuates payments, portions of code as data, code modules as data, the generation and transmission of documents, the online accessing other systems to effect registrations, and so on, including what is described in this document. Such services can be provided as a Software as a Service (SaaS).

(34) A user **192** may be standalone. The user **192** may use a computer system **190** that has a screen **191**, on which User Interfaces (UIs) may be shown. Additional sample implementation details for the computer system **190** are given later in this document. In embodiments, the user **192** and the computer system **190** are considered part of a primary entity **193**, which can be referred to also merely as entity. In such instances, the user **192** can be an agent of the entity **193**, and even within a physical site of the entity **193**, although that is not necessary. In embodiments, the computer system **190** or other device of the user **192** or the entity **193** are client devices for the computer system **195**.

(35) The computer system **190** may access the computer system **195** via a communications network **188**, such as the internet. In particular, the entities and associated systems of FIG. **1** may

communicate via physical and logical channels of the communication network **188**. For example, information may be communicated as data using the Internet Protocol (IP) suite over a packet-switched network such as the Internet or other packet-switched network, which may be included as part of the communication network **188**. The communication network **188** may include many different types of computer networks and communication media including those utilized by various different physical and logical channels of communication, now known or later developed. Non-limiting media and communication channel examples include one or more, or any operable combination of: fiber optic systems, satellite systems, cable systems, microwave systems, asynchronous transfer mode (“ATM”) systems, frame relay systems, digital subscriber line (“DSL”) systems, radio frequency (“RF”) systems, telephone systems, cellular systems, other wireless systems, and the Internet. In various embodiments the communication network **188** can be or include any type of network, such as a local area network (LAN), a metropolitan area network (MAN), a wide area network (WAN), or the internet.

(36) Downloading or uploading may be permitted from one of these two computer systems to the other, and so on. Such accessing can be performed, for instance, with manually uploading files, like spreadsheet files, etc. Such accessing can also be performed automatically as shown in the example of FIG. **1**. The computer system **190** and the computer system **195** may exchange requests and responses with each other. Such can be implemented with a number of architectures.

(37) In one such architecture, a device remote to the service engine **183**, such as computer system **190**, may have a certain application (not shown) and a connector (not shown) that is a plugin that sits on top of that certain application. The connector may be able to fetch from the remote device the details required for the service desired from the OSP **198**, form an object or payload **134**, and then send or push a request **184** that carries the payload **134** to the service engine **183** via a service call. The service engine **183** may receive the request **184** with the payload **134**. The service engine **183** may then parse the payload **134** to determine what is a requested resource as described below in more detail, produce the requested resource **179**, form a payload **137** that is an aspect of the resource **179**, and then push, send, or otherwise cause to be transmitted a response **187** that carries the payload **137** to the connector. The connector reads the response **187**, and forwards the payload **137** to the certain application. The resource **179** may be an only resource, or a first requested resource, and so on.

(38) In an alternative such architecture, a device remote to the service engine **183**, such as the computer system **190**, may have a particular application (not shown). In addition, the computer system **195** implements a REST (Representational State Transfer) API (Application Programming Interface) (not shown). REST or RESTful API design is designed to take advantage of existing protocols. While REST can be used over nearly any protocol, it usually takes advantage of HTTP (Hyper Text Transfer Protocol) when used for Web APIs. This alternative architecture enables the primary entity **193** to directly consume a REST API from their particular application, without using a connector. The particular application of the remote device may be able to fetch internally from the remote device the details required for the service desired from the OSP **198**, and thus send or push the request **184** to the REST API. In turn, the REST API talks in background to the service engine **183**. Again, the service engine **183** produces the requested resource **179**, and sends an aspect of it back to the REST API. In turn, the REST API sends the response **187** that has the payload **137** to the particular application.

(39) Moreover, in some embodiments, data from the computer system **190** and/or from the computer system **195** may be stored in an Online Processing Facility (OPF) **189** that can run software applications, perform operations, and so on. In such embodiments, requests and responses may be exchanged with the OPF **189**, downloading or uploading may involve the OPF **189**, and so on. In such embodiments, the computer system **190** and any devices of the OPF **189** can be considered to be remote devices, at least from the perspective of the computer system **195**.

(40) In some instances, the user **192** or the primary entity **193** may have instances of relationships

with secondary entities. Only one such secondary entity **196** is shown. In this example, the primary entity **193** has a relationship instance **197** with the secondary entity **196**.

(41) In some instances, the user **192** or the primary entity **193** may have data about one or more of the secondary entities, for example via relationship instances with them. The primary entity **193** and/or the secondary entity **196** may be referred to as simply entities. One of these entities may have one or more attributes. Such an attribute of such an entity may be any one of its name, type of entity, a place within a domain, a physical or geographical location such as an address, a contact information element, an affiliation, a characterization of another entity, a characterization by another entity, an association or relationship, ongoing or just relationship instances, with another entity, an asset of the entity, a declaration by or on behalf of the entity, and so on. Examples are now described.

(42) A domain **101** is shown above the line **115**. Within the domain **101** there are shown a source location **157** and a destination location **158**. The source location **157** and the destination location **158** can be defined within the domain **101** by a respective source location datapoint and a destination location datapoint, as described later in this document. While the source location **157** and the destination location **158** are shown within the single domain **101**, such is not required; indeed, each can be in its own domain, or subdomain, and so on. In some embodiments, a single domain is selected that includes both the source location and the destination location.

(43) In addition, an item **108** is shown at the source location **157**. But that is for this example only, and the item **108** could instead be at the destination location **158**, or in transit from one to the other, and so on. The item **108** is thus, in this example, shown within the domain **101**.

(44) The domain **101** may have two dimensions. For instance, the domain can be geographic. An example is now described.

(45) Referring now to FIG. 2, a domain **201** is a two-dimensional version of the domain **101**. Lines **241**, **242** are provided for perspective, but are not necessarily edges or boundaries of the domain **201**. The view of FIG. 2 is a perspective view, in that the lines **241**, **242** could be perpendicular with respect to each other—at least within a locale—when seen in a plane that they define, but that plane is not the plane of the drawing sheet. In such cases, the lines **241**, **242** could further be orthogonal axes, but that is not necessary.

(46) A source location **257** and a destination location **258** are shown within the domain **201**. A source location datapoint and a destination location datapoint may define the source location **257** and the destination location **258**, respectively, within the domain **201**. For instance, when the lines **241**, **242** are orthogonal axes, such datapoints could be defined in terms of coordinate values with respect to these axes. Other ways of defining the datapoints are also possible, as described later in this document.

(47) A sample item **208** is also shown as associated with the sample source location **257**. As mentioned previously, this association is shown like this for convenience only, for the moment only, and is not required.

(48) In embodiments, a code string **277** may be associated with one or more of i) the defined source location **257**, ii) the defined destination location **258**, and iii) the item **208**. Here only the association with the destination location **258** is shown, but this is only a non-limiting example. Additional information about code strings, such as the code string **277** and code strings **377**, **477**, **577**, **677**, **777** and **877**, is provided later in this document.

(49) The domain **101** may have three or more dimensions. For instance, the domain can be geographic, but differentiate further for different altitudes at different locations. An example is now described.

(50) Referring now to FIG. 3, a domain **301** is a three-dimensional version of the domain **101**. Lines **341**, **342**, **343** are provided for perspective, but are not necessarily edges or boundaries of the domain **301**. The view of FIG. 3 is a perspective view, in that the lines **341**, **342**, **343** could be perpendicular with respect to each other—at least within a locale—when seen in the volume that

they define. In such cases, the lines **341**, **342**, **343** could further be orthogonal axes, but that is not necessary.

(51) A source location **357** and a destination location **358** are shown within the domain **301**. A source location datapoint and a destination location datapoint may define the source location **357** and the destination location **358**, respectively, within the domain **301**. For instance, when the lines **341**, **342**, **343** are orthogonal axes, such datapoints could be defined in terms of coordinate values with respect to these axes. In particular, for the source location **357** a line segment **343-S** is also shown, which is parallel to the line **343**. And, for the destination location **358** a line segment **343-D** is also shown, which is parallel to the line **343**.

(52) A sample item **308** is also shown as associated with the sample source location **357**. As mentioned previously, this association is shown like this for convenience only, for the moment only, and is not required.

(53) In embodiments, a code string **377** may be associated with one or more of i) the defined source location **357**, ii) the defined destination location **358**, and iii) the item **308**. Here only the association with the destination location **358** is shown, but this is only a non-limiting example.

(54) Aspects of describing location datapoints are now described.

(55) FIG. **4A** shows a sample two-dimensional sub-domain **401** that is the City of Seattle. The sub-domain **401** may be part of a larger domain that is the State of Washington, or the United States of America.

(56) From FIG. **4A**, on the West the City of Seattle is bounded by a body of water, namely Elliot Bay. On the East, the City of Seattle is bounded by another body of water, namely Lake Washington. On the North, the City of Seattle is bounded by the City of Shoreline. On the South, the City of Seattle is bounded by the Cities of Burien, Tukwila and Renton, whose individual boundaries are not shown.

(57) A source location **457** and a destination location **458** are shown within the sub-domain **401**. Moreover, a code string **477** may be associated with one or more of i) the defined source location **457** and ii) the defined destination location **458**. Here only the association with the destination location **458** is shown, but this is only a non-limiting example.

(58) Various locations in the City of Seattle have mailing addresses. As such, at least one of the source location datapoint and the destination location datapoint may include a street address for, respectively, at least one of the source location **457** and the destination location **458**.

(59) Locations in the City of Seattle may be defined by a latitude and a longitude. As such, at least one of the source location datapoint and the destination location datapoint may include a latitude and a longitude for, respectively, at least one of the source location **457** and the destination location **458**.

(60) In embodiments, locations in the City of Seattle may be defined by location lookup codes. In particular, at least one of the source location datapoint and the destination location datapoint is a location lookup code.

(61) Such location lookup codes can be numerical, alphabetical, alphanumeric, and so on. Such location lookup codes can be implemented in a number of ways. Embodiments are now described.

(62) For instance, a location lookup code could be of the format: CCC.SS.RRR.NNN.MMM, where CCC is code for Country such as USA, SS is code for State or province within the Country such as WA for Washington State, RRR is code for Region within the State such as Seattle Metropolitan Area, NNN is code for Neighborhood or rural area within the Region, MMM a street or cross street or route number and mile number designation, and so on, in this example getting more and more local when going from left to right. This format would use preexisting divisions of a domain.

(63) In embodiments, location lookup codes, and defining datapoints for the source locations and the destination location, can be performed by partitioning a domain into segments or tiles, and then numbering these segments or tiles. Partitioning can be in any way, and tiles within a single domain

can be any shape or size. Preferably tiles are rectangular, and even square. Of course, this is understood in terms of the values of the longitude and latitude, when in fact the line of a geographical square tile closer to the equator is longer than its opposite line, due to the curvature of the earth. In embodiments, a domain is partitioned according to a partitioning scheme, and the location lookup codes follow the partitioning scheme, as they describe each tile. Examples are now described.

(64) FIG. 4B is the map of FIG. 4A, which further has been partitioned into location code tiles according to a partitioning scheme. The partitioning scheme includes that the tiles are square, and each tile maybe subdivided into nine smaller tiles, and so on.

(65) A large tile PN covers much of the center of the City of Seattle, and also the destination location 458. In this example, the “P” of the PN can be a set of digits that locates the large tile PN within the sub-domain 401. So, P will be the same for all the tiles within the sub-domain 401. The “N” of the PN a further specifying digit. In this case, N might be just the number 1. In such a case, a location lookup code for the destination location 458 is simply PN, or P1.

(66) The partitioning can be performed to define different locations in an area as much as is desired and possible. More partitioning will give finer resolution for boundaries or locations that matter with increased accuracy, but at the cost of increasing the burden of producing resources. Notably, in this example, the tile PN includes bodies of water, in particular Elliot Bay to the West and Lake Washington to the East. Even if neither the source location 457 nor the destination location 458 could validly be in water, in embodiments this is not a problem as portions of a tile may be formally defined as valid, but such portions may never be actually used. Where, however, boundaries or locations are encountered that matter, a tile may be further divided into tiles according to one more level of refinement, and so on.

(67) In the particular example of FIG. 4B, the partitioning is four levels deep. In addition to the PN tile at the center, at the lower left another tile PNN is shown. The tile PNN is one level deeper approximation, and equals 1/9th the size of the PN tile. The tile PNN has two numbers N following the prefix P, which reflects the increased resolution.

(68) A deeper, third approximation is tiles PNNN, each of which is 1/9th the size of the tile PNN. An even deeper, fourth approximation is tiles PNNNN, each of which is 1/9th the size of the tile PNNN. As such, the partitioning of FIG. 4B stops at the fourth level (“4L”), although that is not necessary. This may still produce resources inaccurately for a few locations at the boundary, for example the southern boundary. Partitioning may continue to deeper levels, until the inaccuracies are tolerable for the purposes of applications.

(69) The partitioning scheme of FIG. 4B is to further partition or subdivide each tile into $3 \times 3 = 9$ smaller tiles. There is no requirement that a) square tiles be used, b) the division be into 3×3 smaller tiles, and so on.

(70) Where the division is into $3 \times 3 = 9$ smaller tiles, a benefit is that there are enough single numbers among 0, 1, 2, . . . , 9 for using as the N of the PN, and therefore N can be kept into be a single number. Similarly, if each tile is subdivided into $5 \times 5 = 25$ smaller tiles, there are enough letters among the 26 letters of the English alphabet A, B, C, . . . , Z, and therefore N can be kept into be a single letter. And, if each tile is subdivided into $6 \times 6 = 36$ smaller tiles, there are enough alphanumeric characters from both the single-digit numbers and the letters of the English alphabet, and therefore N can be kept into be a single alphanumeric character.

(71) Examples are now provided for different numbering schemes of the tiles. In all of these examples the partitioning scheme is to subdivide, only as necessary from other considerations, each tile into $3 \times 3 = 9$ smaller tiles, which permits only numbers to be used to differentiate the subdivided tiles among each other. In all of these examples, the subdivision is three levels (3L) deep, namely into high, medium and low. Plus, these examples are presented for both the source location datapoint and the destination location datapoint. And, for all these examples, the number assigned by the numbering scheme to a tile can be a source location datapoint, a destination source location

datapoint, or even a source location lookup code, a destination location lookup code, and so on.

(72) FIG. 5 is provided for explaining a first numbering scheme. FIG. 5 shows a domain **501**, with a source location **557** and a destination location **558**. It also shows a code string **577** that is associated with the destination location **558**.

(73) In the vicinity of the source location **557** and the destination location **558**, the domain **501** has been partitioned, at the high level, into nine tiles **Q1**, **Q2**, . . . , **Q9**. In this example, **Q** can be a set of digits for that vicinity, common for all numbers of the locations in the page.

(74) In addition, the tile **Q5** is partitioned or subdivided at the next deeper level, the medium level, into nine tiles **Q51**, **Q52**, . . . , **Q59**. It will be observed that the source location **557** is within the tile **Q54**. As such, the source location datapoint **SLDP=Q54** can be used to define where the source location **557** is, within the domain **501**. This first numbering scheme could be used also for lookup codes, in which case a source location lookup code for the source location **557** would be **SLLC=Q54**.

(75) Moreover, the tile **Q55** is further partitioned or subdivided at the next deeper level, the low level, into nine tiles **Q551**, **Q552**, . . . , **Q559**. It will be observed that the destination location **558** is within the tile **Q559**. As such, the destination location datapoint **DLDP=Q559** can be used to define where the destination location **558** is, within the domain **501**. Plus, per the above, a destination location lookup code **DLLC=Q559** can be used for the destination location **558**.

(76) FIG. 6 is provided for explaining a second numbering scheme. FIG. 6 shows a domain **601**, with a source location **657** and a destination location **658**. It also shows a code string **677** that is associated with the destination location **658**.

(77) In the vicinity of the source location **657** and the destination location **658**, the domain **601** has been partitioned, at the high level, into eight high level tiles **R001**, **R002**, **R003**, **R004**, **R006**, **R007**, **R008**, **R009** and, instead of a ninth tile **R005** in the middle, more smaller ones to be described soon. In this example, **R** can be a set of digits for that vicinity, common for all numbers of the locations in the page.

(78) In the middle level, instead of a tile **R005**, there are eight medium tiles **R051**, **R052**, **R053**, **R054**, **R056**, **R057**, **R058**, **R059** and, instead of a tile **R055** in the middle, more even smaller ones, to be described soon. It will be observed that the source location **657** is within the tile **R054**. As such, the source location datapoint **SLDP=R054** can be used to define where the source location **657** is, within the domain **601**. This second numbering scheme could be used also for lookup codes, in which case a source location lookup code for the source location **657** would be **SLLC=R054**.

(79) Moreover, instead of a tile **R055**, there are nine low-level tiles **R551**, **R552**, . . . , **R559**. It will be observed that the destination location **658** is within the tile **R559**. As such, the destination location datapoint **DLDP=R559** can be used to define where the destination location **658** is, within the domain **601**. Plus, per the above, a destination location lookup code **DLLC=R559** can be used for the destination location **658**.

(80) In this numbering scheme, the **R** is the same, and all the tiles are described by the same number of digits following the **R**, which makes it easier for a system to parse them.

(81) FIG. 7 is provided for explaining a third numbering scheme. FIG. 7 shows a domain **701**, with a source location **757** and a destination location **758**. It also shows a code string **777** that is associated with the destination location **758**.

(82) In the vicinity of the source location **757** and the destination location **758**, the domain **701** has been partitioned, at the high level, into eight high level tiles **S100**, **S200**, **S300**, **S400**, **S600**, **S700**, **S800**, **S900** and, instead of a ninth tile **S500** in the middle, more smaller ones to be described soon. In this example, **S** can be a set of digits for that vicinity, common for all numbers of the locations in the page.

(83) In the middle level, instead of a tile **S500**, there are eight medium tiles **S510**, **S520**, **S530**, **S540**, **S560**, **S570**, **S580**, **S590** and, instead of a tile **S550** in the middle, more even smaller ones, to be described soon. It will be observed that the source location **757** is within the tile **S540**. As such,

the source location datapoint SLDP=S540 can be used to define where the source location 757 is, within the domain 701. This third numbering scheme could be used also for lookup codes, in which case a source location lookup code for the source location 757 would be SLLC=S540.

(84) Moreover, instead of a tile S550, there are nine low-level tiles S551, S552, . . . , S559. It will be observed that the destination location 758 is within the tile S559. As such, the destination location datapoint DLDP=S559 can be used to define where the destination location 758 is, within the domain 701. Plus, per the above, a destination location lookup code DLLC=S559 can be used for the destination location 758.

(85) In this numbering scheme, the S is the same, and all the tiles are described by the same number of digits following the S, which makes it easier for a system to parse them. Moreover, once a zero is reached within a number, the remaining digits are all known to be zeroes, which makes it even easier for a system to parse them.

(86) FIG. 8 is provided for explaining a fourth numbering scheme. FIG. 8 shows a domain 801, with a source location 857 and a destination location 858. It also shows a code string 877 that is associated with the destination location 858.

(87) In the vicinity of the source location 857 and the destination location 858, the domain 801 has been partitioned, at the high level, into eight high level tiles 1T1, 1T2, 1T3, 1T4, 1T6, 1T7, 1T8, 1T9 and, instead of a ninth tile 1T5 in the middle, more smaller ones to be described soon. In this example, T can be a set of digits for that vicinity, common for all numbers of the locations in the page.

(88) In the middle level, instead of a tile 1T5, there are eight medium tiles 2T51, 2T52, 2T53, 2T54, 2T56, 2T57, 2T58, 2T59 and, instead of a tile 2T55 in the middle, more even smaller ones, to be described soon. It will be observed that the source location 857 is within the tile 2T54. As such, the source location datapoint SLDP=2T54 can be used to define where the source location 857 is, within the domain 801. This fourth numbering scheme could be used also for lookup codes, in which case a source location lookup code for the source location 857 would be SLLC=2T54.

(89) Moreover, instead of a tile 2T55, there are nine low-level tiles 3T551, 3T552, . . . , 3T559. It will be observed that the destination location 858 is within the tile 3T559. As such, the destination location datapoint DLDP=3T559 can be used to define where the destination location 858 is, within the domain 801. Plus, per the above, a destination location lookup code DLLC=3T559 can be used for the destination location 858.

(90) In this numbering scheme, the T is the same for all the tiles, regardless of their size. However, the prefix before the T indicates how many digits are following. This makes it easier for a system to parse location datapoints and/or lookup codes of varying length.

(91) An already known concept is Open Location Codes (OLC). These codes provide a way to identify almost any place that exists on the earth, irrespective of the country or region, using only an alphanumeric code. The open location code system is based on the existing latitude and longitude system which uses a grid to divide areas into small area tiles. A unique code can be assigned to each of the area tiles. A complete OLC for that concept (also referred as global code) contains ten (10) characters in total, with a '+' character before the last two characters. For a given OLC, the first four (4) characters narrow down the area search to a grid of around 100×100 kilometers; and the remaining 6-character code can help pin down a more exact location—it describes the area roughly 14×14 meters. The definition of OLC is extensible: by adding characters, one can increase accuracy. For instance, an additional accuracy of up to 3×3 meters can be achieved with additional characters.

(92) FIG. 9 was thus created from the concept of Open Location Codes. FIG. 9 is a diagram of a sample map 901 in India. The capital city of India, New Delhi, can be seen near the top left of the map. A portion 902 of the map is identified as an even darker square, which has an area of approximately 100 km×100 km. As also intimated above, it will be understood that such geographic subdivisions treat the earth as substantially flat in that location, which is an

approximation that is more and more accurate the smaller the area becomes, and where therefore the earth's curvature plays a correspondingly lesser role.

(93) A numbering scheme in the prior art provides a number **903** for the even darker portion **902**. That number **903** is a global code **903**, in the context of a larger domain is the entire earth. This global code includes an area code 8GC2, which is not the same as an area code for telephone numbers. This area code describes the even darker portion **902**. The global code **903** also includes a local code CMXR+X6. A portion or all of the area code or the global code can be the P, Q, R, S, or T in the codes of the previous five drawings, and so on.

(94) Returning to FIG. **1**, in embodiments, the computer system **195** receives one or more datasets, and is configured to parse, input, or extract values from them. A sample received dataset **135** is shown below the line **115**. The dataset **135** may be received by the computer system **195** in a number of ways. In some embodiments, one or more requests may be received by the computer system **195** via a network. In this example, a request **184** is received by the computer system **195** via the network **188**. The request **184** has been transmitted by the computer system **190**. The received one or more requests can carry payloads. In this example, the request **184** carries a payload **134**. In such embodiments, the one or more payloads may be parsed by the computer system **195** to extract the dataset. In this example, the payload **134** can be parsed by the computer system **195** to extract the dataset **135**. In this example the single payload **134** encodes the entire dataset **135**, but that is not required. In fact, a dataset can be received from the payloads of multiple requests. In such cases, a single payload may encode only a portion of the dataset. And, of course, the payload of a single request may encode multiple datasets. Additional computers may be involved with the network **188**, some beyond the control of the user **192** or OSP **198**, and some within such control.

(95) The dataset **135** has values that can be numerical, alphanumeric, Boolean, and so on, as needed for what the values characterize. For example, an identity value ID may indicate an identity of the dataset **135**, so as to differentiate it from other such datasets. At least one of the values of the dataset **135** may characterize an attribute of a certain one of the entities **193** and **196**, as indicated by arrows **199** in combination with arrows **111**. (It should be noted that these arrows combinations describe correspondences, but not the journey of data in becoming the received dataset **135**.) In some embodiments, the dataset **135** has values that characterize attributes of both the primary entity **193** and the secondary entity **196**, but that is not required.

(96) In some embodiments the one or more datasets, or just the dataset **135**, include a base value BV. The base value BV may be a numerical base value for an aspect of the dataset, and so on. The aspect of the dataset may be the aspect of the value that characterizes the attribute, an aspect of the reason that the dataset was created in the first place, and so on.

(97) In some embodiments the one or more datasets, or just the dataset **135**, additionally include one or more of the following three elements: i) A source location datapoint which, in the example of FIG. **1** is seen as SLDP. The source location datapoint may define a source location within a domain that has at least two dimensions. For instance, the source location datapoint may define a source location **157** within the domain **101**. ii) A destination location datapoint which, in the example of FIG. **1** is seen as DLDP. The destination location datapoint may define a destination location within a domain that has at least two dimensions. For instance, the destination location datapoint DLDP may define a destination location **158** within the domain **101**. iii) An item code which, in the example of FIG. **1** is seen as IC. The item code may define an item from a set of items. For instance, the item code IC may define the item **108** from a set of items. Suitable schemes may be used for items, for example Product identification codes, UPC codes, Stock Keeping Unit (SKU), custom systems, and so on.

(98) In some embodiments, the computer system **195** is further configured to detect, from the one or more datasets, an indication about a length of the source location datapoint, or the destination location datapoint. In such embodiments, the parsing is performed according to the detected

indication. For instance, in the numbering scheme of FIG. 8, the first number, e.g., 1 or 2, is an indication about a length of the source location datapoint, telling how many digits follow after the "T". Accordingly, the parsing can be performed according to the detected indication, by looking for as many digits come after the "T".

(99) The dataset **135** may further have additional such values, as indicated by the horizontal dot-dot-dot in the right side of the dataset **135**.

(100) In embodiments, the computer system **195** is configured to cause a strings memory **170** to be accessed, in response to the received one or more datasets. The strings memory **170** may be hosted by the same place online software platform **198** that hosts the computer system **195**, or by hosted by a strings memory host platform, in which case the strings memory **170** can be accessed remotely, via a network, and so on, as described in more detail later in this document. The strings memory host platform may be remote, controlled by a different entity and so on.

(101) For causing the strings memory **170** to be accessed, and to be looked up, the computer system **195** may transmit a lookup query (not shown in FIG. 1) according to an arrow **171**. A looked-up code string CSA may be returned, according to an arrow **141**. In the event that the strings memory **170** is hosted remotely, the arrows **171** and **141** represent communications transmitted through a cloud, and so on.

(102) In embodiments, the strings memory **170** stores code strings **177**, which are described in more detail below. At least some of the code strings **177** may be stored in association with one or more of a) one or more source locations of the domain, b) one or more destination locations of the domain, and c) one or more items associated with the source locations and with the destination locations. This can be implemented in a number of ways, and examples are now described.

(103) In the example of FIG. 1, possible ones of the one or more source locations are listed in a column **172**. The listing may be in some encoded form, such a source location lookup code. For instance, the source location **157** may be represented by a source location lookup code SLLC. Such lookup codes may be alphanumeric, and so on.

(104) In the example of FIG. 1, possible ones of the one or more destination locations are listed in a column **173**. The listing may be in some encoded form, such a destination location lookup code. For instance, the destination location **158** may be represented by a destination location lookup code DLLC.

(105) In the example of FIG. 1, possible ones of the one or more source items are listed in a column **174**. The listing may be in some encoded form, such an item lookup code. For instance, the item **108** may be represented by an item lookup code ILC.

(106) The strings memory **170** may have multiple rows, each with different combinations of possible source locations, possible destination locations and possible items. For each of at least some of the rows, one code string can be provided, from the column **177**.

(107) The above was only one example. As will be seen later in this document, in other embodiments one or more of the columns **172**, **173**, **174** may be merged, and so on.

(108) In embodiments, the computer system **195** is configured to cause a first code string to be looked up from the code strings stored in the strings memory. In embodiments, the first code string is looked up in association with the one or more of i) the dataset's defined source location, ii) the defined destination location, and iii) the defined item.

(109) In the example of FIG. 1, the computer system **195** causes the looking up, from the strings memory **170**, of a code string CSA from the code strings **177**. The code string CSA is looked up in association with the one or more of i) the source location **157**, ii) the destination location **158**, and iii) the item **108**, that is/are defined in the dataset **135**. The looking up is depicted by arrow **171**, which selects the appropriate row, i.e., the row that has the right combination of the queried parameters.

(110) Embodiments for the looking up, per the arrow **171**, are now described in more detail.

(111) In some embodiments, the encoding of the dataset **135** is engineered to match in advance the

encoding of one or more portions of the strings memory. In such embodiments, the looking up can be performed by applying to the strings memory the parsed one or more of: i) the source location datapoint and ii) the destination location datapoint. Optionally also the parsed item code. An example is now described.

(112) FIG. **10** is a diagram for describing aspects of looking up a strings memory **1070**, which can be as the strings memory **170**. In this example, the strings memory **1070** has a column **1072** for possible source locations, a column **1073** for possible destination locations, a column **1074** for possible items, and a column **1077** for the corresponding stored associated code strings that can be looked up, all similarly with the strings memory **170**. In addition, the strings memory **1070** stores the same values as the strings memory **170**.

(113) In the example of FIG. **10**, a dataset **1035** is received by a computer system **1095**, which can be as the computer system **195**. In this diagram the computer system **1095** is shown artificially as a separate small block, so as to not unduly clutter the drawing. The dataset **1035** already encodes i) the source location lookup code SLLC as its source location datapoint SLDP, ii) the destination location lookup code DLLC as its destination location datapoint DLDP, and iii) the item lookup code ILC as its item code IC, which is why the values of the dataset **1035** are shown as they are. For the looking up, these values are used directly to query the strings memory **1070**, to look up the code string CSA, as shown by arrows **1071** similar to arrow **171**. In particular, a lookup query LQ **1061** can be formed, and be applied to the strings memory **1070** per the arrows **1071**. The code string CSA can be returned in response to the lookup query LQ **1061** according to an arrow **1041** similar to the arrow **141**.

(114) The computer system **1095** may be hosted by an online software platform (OSP) **1098**, which can be as the online software platform **198**. As already mentioned with the description of FIG. **1**, in some embodiments the strings memory **1070** is also hosted by the OSP **1098**, and the arrows **1071**, **1041** describe communications within the OSP **1098**.

(115) In other embodiments, the strings memory **1070** is hosted remotely. This is shown as optional in FIG. **10**, by the following optional features: a communications network **1088** that can be as the network **188**, the OSP **1098** optionally including only what is above the communications network **1088**, and a strings memory host platform **1049** that hosts the strings memory **1070**. In this case, as with the description of FIG. **1**, the arrows **1071**, **1041** pass through the network **1088**.

(116) Then a code module **1005** can be formed from the code string CSA, and the code module **1005** can be executed per an execution block **1009** to produce a resource **1079** according to an arrow **1078**, all similarly to how similar elements are described for FIG. **1**.

(117) The matching of encodings of FIG. **10** may be performed at the dataset level, for instance, on the client side, e.g., by use of a suitably planned software connector. Or, equivalently, the encoding of the strings memory **1070** may be performed to match the data brought by the dataset **1035**.

(118) In other embodiments, conversion is performed so that the data of the dataset **1035** matches the lookup codes used in the strings memory. In particular, the computer system **1095** can be configured to convert at least one of the source location datapoint and the destination location datapoint into a location lookup code. In such embodiments, the first code string is looked up by the location look up code. Optionally also the parsed item code. An example is now described.

(119) FIG. **11A** is a diagram for describing aspects of looking up a strings memory **1170**, which can be as the strings memory **170** or the strings memory **1070**, and which is why its more detailed information is not repeated.

(120) Similarly to FIG. **1**, in the example of FIG. **11A** a dataset **1135** is received by a computer system **1195-A**, which can be as the computer system **195**. In this diagram the computer system **1195-A** is shown artificially as a separate small block, so as to not unduly clutter the drawing. The dataset **1135** encodes i) its source location datapoint SLDP, ii) its destination location datapoint DLDP, and iii) its item code IC, which are parsed by the computer system **195**, as per the above. In this example, three conversions **1144** are then performed: i) the source location datapoint SLDP is

converted to the source location lookup code SLLC, ii) the destination location datapoint DLDP is converted to the destination location lookup code DLLC, and iii) the item code IC is converted to the item lookup code ILC. Fewer conversions may be performed, or more for additional elements, and so on.

(121) In some embodiments, the converting of operation **1144** includes adding one or more characters to the at least one of the source location datapoint and the destination location datapoint. The one or more characters can be a zero, or other characters for accommodating a numbering scheme of tiles. For instance, the added one or more characters can be one or more leading zeroes, such as might be the case for numbering tiles in the numbering scheme of FIG. 6. Or, the added one or more characters can be one or more trailing zeroes, such as might be the case for numbering tiles in the numbering scheme of FIG. 7.

(122) Then, for the looking up, these converted values are used to query the strings memory **1170**, to look up the code string CSA, as shown by arrows **1171** similar to arrow **171**. In particular, a lookup query LQA **1161-A** can be formed, and be applied to the strings memory **1170** per the arrows **1171**. The code string CSA can be returned in response to the lookup query LQA **1161-A** according to an arrow **1141-A** similar to the arrow **141**.

(123) Similarly with FIG. 10, FIG. 11A also shows the following optional features: a communications network **1188** that can be as the network **188**, the OSP **1198-A** optionally including only what is above the communications network **1188**, a strings memory host platform **1149-A** that hosts the strings memory **1170**, and a support computer **1147-A** that is hosted by the remote strings memory host platform **1149-A**, for operations of at least the strings memory **1170**, etc. In this case, as with the description of FIG. 1, the arrows **1171**, **1141-A** pass through the network **1188**.

(124) Then a code module A **1105** can be formed from the code string CSA, and the code module A **1105** can be executed per an execution A block **1009-A** to produce a resource A **1179-A** according to an arrow **1178-A**, all similarly to how similar elements in FIG. 1 are described.

(125) In some embodiments, where the strings memory is hosted by a strings memory host platform that is remote from an online software platform that hosts the computer system, only the code string is received, and is processed by the computer system. In such embodiments, causing the strings memory to be accessed includes at least: forming, by the computer system, a lookup query from at least one of the source location lookup code and the destination location lookup code; causing, by the computer system, the lookup query to be transmitted over a network from the computer system to a support computer that is hosted by the strings memory host platform; and receiving, by the computer system, the looked up first code string from the support computer.

(126) As example of that is seen in FIG. 11A, as optional only. Indeed, the strings memory **1170** is optionally hosted by a strings memory host platform **1149-A** that is remote from an online software platform **1198-A**. The strings memory host platform **1149-A** also hosts and is operated by a support computer **1147-A**. The strings memory **1170** is caused to be accessed by the computer system **1195-A** forming a lookup query LQA **1161-A** from at least one of the source location lookup code SLLC and the destination location lookup code DLLC; and causing the lookup query LQA **1161-A** to be transmitted over the network **1188** from the computer system **1195-A** to the support computer **1147-A** that is hosted by the strings memory host platform **1149-A**. From that, the code string SCA is looked up. In addition, the computer system **1195-A** receives the looked up code string SCA from the support computer **1147-A** via an arrow **1141-A**.

(127) In some embodiments, where the strings memory is hosted by a strings memory host platform that is remote from an online software platform that hosts the computer system, the code module is also formed remotely, and is then received and processed by the computer system. In such embodiments, causing the strings memory to be accessed includes at least: forming, by the computer system, a lookup query from at least one of the source location lookup code and the destination location lookup code; and causing, by the computer system, the lookup query to be

transmitted over a network from the computer system to the strings memory host platform for generation of the code module by a support computer in the strings memory host platform. In such embodiments, the first code module is caused to be generated by causing the support computer to generate the first code module. Then the generated first code module can be received by the computer system from the support computer.

(128) FIG. 11B shows as example of that. A computer system **1195-B** that can be as the computer system **195** is hosted by an online software platform **1198-B** that can be as the OSP **198**. A strings memory host platform **1149-B** is remote from the OSP **1198-B**, and communicates with it via the network **1188**. The strings memory **1170** is hosted this time, by the strings memory host platform **1149-B**. The strings memory host platform **1149-B** also hosts and is operated by a support computer **1147-B**.

(129) The strings memory **1170** is caused to be accessed by the computer system **1195-B** by: forming a lookup query LQB **1161-B**; and causing the lookup query LQB **1161-B** to be transmitted over the network **1188**, from the computer system **1195-B** to the strings memory host platform **1149-B**. From the strings memory **1170** that is hosted there, the code string SCA is looked up. The code module B **1105-B** is caused by the computer system **1195-B** to be generated by the computer system **1195-B** causing the support computer **1147-B** to generate the code module **1105-B**. Then the generated code module B **1105-B** is received by the computer system **1195-B** from the support computer **1147-B** via an arrow **1141-B**. Then the received code module B **1105-B** is executed by an execution B block **1109-B** of the computer system **1195-B** to produce, according to an arrow **1178-B**, a resource B **1179-B**.

(130) In some embodiments, where the strings memory is hosted by a strings memory host platform that is remote from an online software platform that hosts the computer system, the code module is also formed remotely, and is then executed to produce the first resource. Then the resource is received by the computer system, the notification can be sent, and so on. In such embodiments, causing the strings memory to be accessed includes at least: forming, by the computer system, a lookup query from at least one of the source location lookup code and the destination location lookup code; and causing, by the computer system, the lookup query to be transmitted over a network from the computer system to the strings memory host platform. In such embodiments, the first code module is caused to be generated by causing a support computer that is hosted by the strings memory host platform to generate the first code module. And, causing the first code module to be executed may include causing the support computer to execute the first code module to produce the first resource. Then the produced first resource can be received by the computer system from the support computer.

(131) FIG. 11C shows as example of that. A computer system **1195-C** that can be as the computer system **195** is hosted by an online software platform **1198-C** that can be as the OSP **198**. A strings memory host platform **1149-C** is remote from the OSP **1198-C**, and communicates with it via the network **1188**. The strings memory **1170** is hosted, this time, by the strings memory host platform **1149-C**. The strings memory host platform **1149-C** also hosts and is operated by a support computer **1147-C**.

(132) The strings memory **1170** is caused to be accessed by the computer system **1195-C** by: forming a lookup query LQC **1161-C**; and causing the lookup query LQC **1161-C** to be transmitted over the network **1188**, from the computer system **1195-C** to the strings memory host platform **1149-C**. From the strings memory **1170** that is hosted there, the code string SCA is looked up. A code module **1105-C** is caused by the computer system **1195-C** to be generated by the computer system **1195-C** causing the support computer **1147-C** to generate the code module **1105-C**. And, causing the code module **1105-C** to be executed may include the computer system **1195-C** causing the support computer **1147-C** to execute the code module **1105-C** by an execution C block **1109** to produce a resource C **1179-C** according to an arrow **1178-C**. Then the produced resource C **1179-C** is received by the computer system **1195-C** from the support computer **1147-C**, via an arrow **1141-**

C across the network **1188**. It will be understood that, since the resource C **1179-C** is produced remotely, the base value has to be communicated also across the network **1188**. This can be done in conjunction with the lookup query LQC **1161-C**, as suggested in FIG. **11C**, or separately. For instance, the base value BV can be embedded in the lookup query LQC **1161-C**.

(133) The variations of FIGS. **11A**, **11B**, **11C** can also apply to the embodiments of FIG. **1** and FIG. **10**.

(134) Returning now to various embodiments of querying the strings memory, the example of FIG. **10** had a strings memory **1070** that had separate columns for inputs for the source location datapoint, the destination location datapoint, and the item code. This is not necessary, and two types of embodiments are now described.

(135) In a first type of embodiments, the strings memory can be partitioned, for ease of access. For example, the strings memory can be partitioned according to different source location datapoints, according to different destination location datapoints, and according to different item codes.

(136) In a second type of embodiments, two or more of these columns may be combined into a single column; in such cases, the lookup query **1061**, **1161-A**, **1161-B**, **1161-C** can sometimes be a single query string; such a query string can be part of the lookup queries described above.

Examples are now described.

(137) In some embodiments, the looking up is performed by applying to the strings memory a single query string that is derived by concatenating, in any order, at least two of: a first query made from the source location datapoint, a second query made from the destination location datapoint, and a third query made from the item code. An instance is now described.

(138) FIG. **12** is a diagram for describing a sample organization of a strings memory **1270**, which can be as the strings memory **170**. In this example, the strings memory **1270** has a single column **1275** for possible queries about the source location, the destination location and the item. It may optionally have other columns per the dot-dot-dots for implementing additional selection or validity criteria. The strings memory **1270** also has a column **1277** for the corresponding stored associated code strings that can be looked up, all similarly with the strings memory **170**.

(139) A single query string QS **1245** has been derived by concatenating other queries. The concatenations are indicated by the “plus” signs **1277**. In the example of FIG. **12**, these other queries are: a first query Q1 made from the source location datapoint SLDP, a second query Q2 made from the destination location datapoint DLDP, and a third query Q3 made from the item code IC. These queries may be made by adding or substituting elements of the location datapoints, converting the item code from one system of codes to another, and so on.

(140) A single query can yield the result relatively fast, especially if the strings memory **1270** has no other columns and is in the form of a table or spreadsheet.

(141) In some embodiments, the looking up is performed by applying to the strings memory a single query string that is derived by concatenating, in any order, at least two of: the source location datapoint, the destination location datapoint, and the item code. An instance is now described.

(142) FIG. **13** is a diagram for describing a sample organization of a strings memory **1370**, which can be as the strings memory **170**. In this example, the strings memory **1370** has a single column **1375** for possible queries about the source location, the destination location and the item. It may optionally have other columns per the dot-dot-dots for implementing additional selection or validity criteria. The strings memory **1370** also has a column **1377** for the corresponding stored associated code strings that can be looked up, all similarly with the strings memory **170**.

(143) A single query string QS **1345** has been derived by concatenating the source location datapoint SLDP, the destination location datapoint DLDP, and the item code IC. The concatenations are indicated by the “plus” signs **1277**.

(144) Returning to FIG. **1**, the first code string that is thus looked up can be configured to implement a first rule of the domain about the one or more of the i) the defined source location, ii) the defined destination location, and iii) the defined item transitioning from the defined source

location and/or to the defined destination location. The first rule can be about the pair of the defined source location and the defined destination location, sometimes in the context of the defined item transitioning from the defined source location to the defined destination location.

(145) In the example of FIG. 1, the code string that is thus looked up is CSA. This is output from the strings memory 170 per the arrow 141, as previously described. The tip of the arrow 141 is shown as reaching into a code module A 105. In embodiments, a first code module, such as code module A 105, is generated from the first code string, such as the code string CSA. For clarification, and as will be seen also later, the first code module may be generated also from additional code strings, other considerations, and so on.

(146) A sample rule A 151 is shown as a pentagon. Arrows connecting the rule A 151 with other elements are intended to show relationships, not operations or transitions.

(147) In embodiments, a code string is a character string that uses a Domain Specific Language (DSL). A domain-specific language is created specifically to solve problems in a particular domain and is not intended to be able to solve problems outside of it (although that may be technically possible). Another example can be language of the type used in the Excel® product of Microsoft®, with proper adaptations. Examples of such a language could be largely in alphanumeric form, but further may include other characters, for instance the “equals” character (“=”), the “plus” character for addition (“+”), the “minus” character for subtraction (“-”), the “star” character for multiplication (“*”), the “larger than” character (“>”), the “smaller than” character (“<”), and so on. These are, coincidentally, the characters that can be used to compute the value of an expression in Microsoft® Excel®. In examples, this document uses the Microsoft® Excel® DSL.

(148) In some embodiments, the first code module is the first code string. An example is now described.

(149) FIG. 14 is a table of values 1400. Unconventionally, in table 1400 the titles are in the first row and the values are in the second row, for consistency with another table in this document. A code string CSA 1477 has the value shown, which starts with the “equals” (=) sign. A code module A 1405 has the value shown, which is the same as that of the code string CSA 1477.

(150) As such, in this example, the code string CSA 1477 and/or the code module A 1405 is a piece of code that is ready for execution. Execution of this piece of code may produce a resource.

(151) In some embodiments, the first code module references the base value as a variable. In the example of FIG. 14, the code module A 1405 indeed references the base value 1406, as a variable BV to be multiplied by a number.

(152) The example of FIG. 14 is where the code module A 1405 mandates a multiplication of the base value BV with the number 0.065. For instance, this code module A 1405 may be implementing a rule (not shown), that requires to: “multiply the base value by 0.065”. This rule is written in format understandable at least by Excel®. More complex rules are also possible, as seen immediately below.

(153) It will be observed that, while this code module A 1405 may be implementing a rule, it might not apply the rule at this stage. Rather, this code module A 1405 may be implementing a rule upon execution at a later stage. In fact, the rule can be applied at a later stage, as seen later in this document. To those very skilled in the art of computer coding, it might fairly seem that the code module A 1405 reflects a rule, embodies a rule, describes a rule, and so on, for the rule to: “multiply the base value by 0.065”.

(154) In some embodiments, the first code module includes a logical “IF” statement. An example is now described.

(155) FIG. 15 is an image of a portion 1500 of a User Interface of a Microsoft® Excel® program, which can provide the execution for a Code Module A 1505. The Code Module A 1505, as applied to cell D4, is =IF (B4>3500, B4*0.08, B4*0.04). In this expression, B4 is the cell that shows the applicable base value BV, which is why the occurrences of B4 are also designated as the base value 1506. This expression also includes a logical “IF” statement 1507.

(156) This code module A **1505** may be implementing a rule (not shown), that requires to: “If the base value is larger than 3500 multiply the base value by 0.08, else multiply the base value by 0.04”. This rule is written in format understandable at least by Microsoft® Excel®. More features of FIG. **15** are described later in this document.

(157) In the example of FIG. **14**, the code module A **1405** was identical to the code string CSA **1477** from the beginning. As such, the strings memory was storing ready-to-execute code that is looked up and then executed. Such is not required, however. In some embodiments, the computer system **195** is further configured to generate, from the first code string, the first code module that will be executed. Examples are now described.

(158) In some embodiments, generally speaking, the first code module is generated from a first code kernel of the first code string. In such embodiments, the first code kernel can be the first code string, or a subset of the first code string. Again, the first code kernel may include a logical “IF” statement. An example is now described.

(159) FIG. **16A** is a diagram of a sample way for a code module to be generated according to embodiments. A code string CSA **1677** includes a code kernel A **1604**. A code module A **1605** is made from the code kernel A **1604**.

(160) In some embodiments, the first code module is generated by further altering the first code kernel. The altering can be done in a preset manner, even per an instruction from the dataset, or specific data of the client. In some embodiments, altering may be performed by inputting the code kernel into a template subroutine, and so on. An example is now described.

(161) FIG. **16B** is a table **1600** of sample values for embodiments of the components of FIG. **16A**. In this example, the bottom row shows the value of the code module A **1605** as: =IF (BV>3500, BV*0.08, BV*0.04). It will be recognized that this is executable by at least Excel®, and in fact it is the same as the Code Module A **1505** of FIG. **15**, except that BV is written instead of B4.

(162) In the example of the table **1600**, the code kernel A **1604** is same as the code string CSA **1677**. In fact, both are the same as the code module A **1605**, except without the beginning “equals” (=) sign. This is also an example of where the code kernel A **1604** was altered, by adding, at the beginning, an “equals” (=) sign, to generate the code module A **1605**. The values of the table **1600** are also an example of where the code kernel A **1604** includes a logical “IF” statement.

(163) Returning to FIG. **1**, in embodiments the computer system **195** can be further configured to produce, by executing a first code module that is generated from the first code string, a first resource that complies with the first rule. In some embodiments, therefore, executing the code module resulting in applying the rule that the code module implements.

(164) As seen in the particular example of FIG. **1**, an execution block **109** is shown for the executing. The execution block **109** is shown as executing the code module **105** that is adjacent to it. As before, the code module **105** has been generated from the code string CSA. The execution produces a resource **179**, according to an arrow **178**. The resource **179** can be the first resource in a context, or the only resource in a context. (Same with first code module and first code string, seconds of each, and so on.) The resource **179** complies with the above-described rule A **151**. The resource can be a computational result prepared for the user **192**, the primary entity **193**, the secondary entity **196**, etc. Still in FIG. **1**, an arrow from the base value BV goes to the intersection of the execution block **109** and the code module A **105** because the base value BV can be used by either one, as will be seen later in this document.

(165) Many individual examples of produced resources are shown in the lower portion of FIG. **15**. A number of possible base values BV are listed in column B. For each such value, the produced resource is shown in column D. A sample produced resource **1579** is indicated. Also, the percentage applied each time is shown in column F. Upon checking, the percentage indeed goes from **4** to **8** when the BV goes from **3000** to **4000**.

(166) Excel® was thus very useful in the description of this document, but is not required to be used in actual embodiments. Excel® is also useful because it uses a high-level language with which

to write a code module in a way that can be stored in a strings memory as ready executable code, or approximately ready, and can be further transferred across the network **188**, **1088**, **1188** as a payload.

(167) In such embodiments, the executing can be performed in conjunction with the base value. This can be performed in a number of ways. Examples are now described.

(168) In some embodiments, the first code module includes the base value as a variable. For instance, FIG. **17** shows a code module A **1705** and an execution block **1709**, similar to those of FIG. **1**, and in fact similarly presented relative to each other. In addition, the code module A **1705** includes the base value BV as a variable. In particular, the code module A **1705** was formed to include as a variable the base value BV from when the base value BV was parsed from the received dataset. Examples of that were already seen in FIGS. **14** and **16B**.

(169) In some embodiments, the base value is called as a variable from outside the code module. For instance, the first code module can be executed by a subroutine that calls the base value as a variable. For example, FIG. **18** shows a code module A **1805** and an execution block **1809**, similar to those of FIG. **1**, and in fact similarly presented relative to each other. In addition, the execution block **1809** includes a subroutine **1848** that calls the base value BV as a variable.

(170) Returning to FIG. **1**, in embodiments the computer system **195** can be further configured to cause a notification about an aspect of the first resource to be transmitted over the network to one of an output device and another device.

(171) In the particular example of FIG. **1**, a notification **136** about an aspect of the resource **179** is generated. In particular, the notification **136** may inform about the aspect of the resource **179**, namely that it has been determined, where it can be found, what it is, or at least a portion or a statistic of its content, a rounded version of it, and so on. Of course, the planning should be that the recipient of the notification **136** understands what it is being provided.

(172) The notification **136** can be caused to be transmitted, for example, as an answer or other response to the received dataset **135**. The notification **136** can be transmitted to one of an output device and another device. The output device may be the screen of a local user or a remote user. The notification **136** may thus cause a desired image, message, or other such notification to appear on the screen, such as within a Graphical User Interface (GUI) and so on. The other device can be the remote device, from which the dataset **135** was received, as in the example of FIG. **1**. In particular, the computer system **195** may cause the notification **136** to be communicated by being encoded as a payload **137**, which is carried by a response **187**. The response **187** may be transmitted via the network **188** responsive to the received request **184**. The response **187** may be transmitted to the computer system **190**, or to OPF **189**, and so on. As such, the other device can be the computer system **190**, or the OPF **189**, or the screen **191** of the user **192**, and so on. In this example the single payload **137** encodes the entire notification **136**, but that is not required. Similarly with what is written above about encoding datasets in payloads, the notification **136** instead may be provided via two or more payloads, or in other cases the notification **136** and at least one other notification may be included in the same single payload. Along with the aspect of the resource **179**, it can be advantageous to embed in the payload **137** the identity value (ID) and/or one or more values of the dataset **135**. This will help the recipient correlate the response **187** to the request **184**, and therefore match the received aspect of the resource **179** as the answer or other response to the appropriate dataset.

(173) In the example of FIG. **1**, according to arrow **171**, a single code string SCA was found from the query formed by the data of the dataset **135**. This is not required. In fact, multiple code strings may be found from a query formed by the data of a single dataset. In particular, in embodiments the computer system can be further configured to cause a second code string to be looked up from the code strings stored in the strings memory. The second code string may be associated with the one or more of i) the dataset's defined source location, ii) the dataset's defined destination location, and iii) the dataset's defined item, just as the first code string was. In addition, the second code string

can be configured to implement the second rule about the one or more of the dataset's i) the defined source location, ii) the defined destination location, and iii) the defined item transitioning from the defined source location and/or to the defined destination location. The second rule can be distinct from the first rule. Examples are now described.

(174) FIG. **19** is a diagram showing a dataset **1935** that can be as the dataset **135**, and a strings memory **1970** that can largely be as the strings memory **170**. The strings memory **1970** is shown here as a table that has a column **1972** for possible source locations, a column **1973** for possible destination locations, a column **1974** for possible items, other possible columns as shown by the dot-dot-dots, and a column **1977** for possible code strings.

(175) A query is generated from the dataset **1935** and, according to the splitting arrow **1971**, the query finds two rows that meet its criteria in this example. The first of these rows yields a code string CSA, and the second of these rows yields a second code string CSB. The code string CSA implements a first rule A **1951**, and the second code string CSB implements a second rule B **1952**.

(176) In such embodiments, the first code module can be generated also from the second code string, and the first resource complies also with the second rule. For instance, in FIG. **19** a code module **1905** is shown as generated also from the second code string CSB, the code module **1905** is again executed by an execution block **1909** to produce a resource **1979** according to arrow **1978**, and the resource **1979** complies also with the second rule B **1952**. Here, for example the first rule could be that the resource include at least 6.5% of the base value, and the second rule could be that the resource include at least 1% of the base value.

(177) In such embodiments, the first code module can be generated from a first code kernel of the first code string and also from a second code kernel of the second code string. In fact, the first code module can be generated from a first code kernel of the first code string, from a plus sign, and from a second code kernel of the second code string. An example is now described.

(178) FIG. **20** is a diagram for showing the generation of a code module **2005**, which can be the code module **1905**. The code module **2005** is generated from a code kernel A **2004-A** of a first code string (such as code string CSA), from a plus sign **2007**, and from a code kernel B **2004-B** of a second code string (such as code string CSB). The plus sign **2007** can be concatenated to effectuate a composite instruction where the results of different instructions are added.

(179) The embodiment of FIG. **20** requires that, once a row is found by arrow **1971**, search continues until at least another row is found. Moreover, in some instances the resource **1979** may show no attribution of its components from the individual code strings CSA, CSB. Other embodiments are now described, which permit such attribution.

(180) In embodiments, after looking up a second code string from the code strings, the first code module is not generated also from the second code string. Rather, the computer system can be further configured to produce, by executing a second code module that is generated from the second code string, a second resource that complies with the second rule. Again, the executing can be in conjunction with the base value. The computer system can be further configured to sum a numerical value of the first resource and a numerical value of the second resource to produce a composite resource. In such cases, the notification can be about an aspect of the composite resource instead of about an aspect of the first resource. An example is now described.

(181) FIG. **21** is a diagram showing a dataset **2135** that can be as the dataset **135**, and a strings memory **2170** that can largely be as the strings memory **170**. The strings memory **2170** is shown here as a table that has a column **2172** for possible source locations, a column **2173** for possible destination locations, a column **2174** for possible items, an optional column **2176** for possible rule ids, other possible columns (not shown), and a column **2177** for possible code strings. When implemented, a rule id is a code that is stored in association with the code string, and may identify an aspect of the rule that the code string implements. Rule ids may thus be stored with each row. Or, equivalently, different strings memories may be provided, one per rule, and so on.

(182) Similarly with FIG. **19**, a query is generated from the dataset **2135** and, according to the

splitting arrow **2171**, the query finds two rows that meet its criteria in this example. The first of these rows yields a first code string CSA, and the second of these rows yields a second code string CSB. The first code string CSA implements a first rule **2151**, and the second code string CSB implements a second rule **2152**.

(183) Differently from FIG. **19**, however, in the example of FIG. **21** a first code module A **2105-A** is generated from the first code string CSA, and a second code module B **2105-B** is generated from the first code string CSB. A first execution A block **2109-A** executes the first code module A **2105-A** to produce a resource A **2179-A**. A second execution B block **2109-B** executes the second code module B **2105-B** to produce a second resource B **2179-B**. A numerical value of the resource A **2179-A** and a numerical value of the second resource B **2179-B** can be summed per an addition operation **2199** to produce a composite resource C **2179-C**.

(184) In such embodiments, the individual resources may be stored, for instance in one or more records memories. In particular, the computer system can be further configured to store the first resource in the records memory in association with the first rule, and also store the second resource in the records memory in association with the second rule, and so on with additional possible resources from a single query.

(185) For example, in some embodiments the strings memory may further store, in association with the first code string, a first rule id that identifies an aspect of the first rule, and a second rule id that identifies an aspect of the second rule. In such embodiments, the computer system can be further configured to store the first resource in the records memory in association with the first rule id, and store the second resource in the records memory in association with the second rule id.

(186) In the example of FIG. **21**, a first rule id RIDA identifies the first rule **2151**, and is stored in association with the first code string CSA. Also, a second rule id RIDB identifies the second rule **2152**, and is stored in association with the second code string CSB. A records memory **2138** is provided for storing the individual resources, before they are summed. The computer system can therefore be further configured to store the resource **2139-A** in association with the first rule id RIDA, and store the second resource **2139-B** in association with the second rule id RIDB.

(187) FIG. **22** shows a flowchart **2200** for describing methods according to embodiments. These methods may be implemented as described above, e.g., by computer system, and with the variations and additions described above.

(188) According to an operation **2210**, one or more datasets may be received by a computer system over a network. The one or more datasets may be received from a first remote computer different from the computer system.

(189) According to another operation **2220**, from the one or more datasets there may be parsed: a base value and one or more of: i) a source location datapoint that defines a source location within a domain that has at least two dimensions, ii) a destination location datapoint that defines a destination location within the domain, and iii) an item code that defines an item from a set of items.

(190) According to another operation **2230**, in response to the one or more datasets received at the operation **2210**, a number of sub-operations can be caused to be performed. These can be caused to be performed by the computer system itself internally within its online software platform. Or, these can be caused to be performed by the computer system causing a remote support computer **1147-A**, **1147-B**, **1147-C**, which may be hosted by a remote strings memory host platform to execute them, by crafting and sending an appropriately created lookup query **1061**, **1161-A**, **1161-B**, **1161-C**, or using other equivalent architecture.

(191) The operation **2230** includes a sub-operation **2240**, according to which a strings memory may be caused to be accessed. The strings memory may store code strings in association with one or more of a) one or more source locations of the domain, b) one or more destination locations of the domain, and c) one or more items associated with the source locations and with the destination locations. Accessing may be local or remote, as per the above.

(192) The operation **2230** also includes a sub-operation **2250**, according to which a first code string among the stored code strings may be caused to be looked up from the strings memory accessed at the operation **2240**. The first code string may be looked up in association with the one or more of the dataset's: i) defined source location, ii) defined destination location, and iii) defined item. The first code string may be configured to implement a first rule about the one or more of the i) the defined source location, ii) the defined destination location, and iii) the defined item transitioning from the defined source location and/or to the defined destination location.

(193) The operation **2230** optionally also includes a sub-operation **2260**, according to which a second code string among the stored code strings may be caused to be looked up from the strings memory. The second code string may be associated with the one or more of i) the defined source location, ii) the defined destination location, and iii) the defined item. The second code string may be configured to implement a second rule about the one or more of the dataset's: i) defined source location, ii) defined destination location, and iii) defined item transitioning from the defined source location and/or to the defined destination location. The second rule can be distinct from the first rule. In some of these embodiments, the computer system may cause a second code module, which is generated from the second code string, to be executed, the executing in conjunction with the base value, the executing producing a second resource that complies with the second rule, and so on.

(194) The operation **2230** may further include a sub-operation **2270**, according to which a first code module generated from the first code string, which was caused to be looked up at the sub-operation **2250**, may be caused to be executed by the computer system. The executing may be performed in conjunction with the base value. The executing may produce a first resource that complies with the first rule. This operation may be different if the optional operation **2260** has also been performed, as per the above.

(195) According to another operation **2280**, a notification about an aspect of the first resource can be caused to be transmitted over the network, to one of an output device and another device. This operation may be different if the optional operation **2260** has also been performed, as per the above.

(196) In the methods described above, each operation can be performed as an affirmative act or operation of doing, or causing to happen, what is written that can take place. Such doing or causing to happen can be by the whole system or device, or just one or more components of it. It will be recognized that the methods and the operations may be implemented in a number of ways, including using systems, devices and implementations described above. In addition, the order of operations is not constrained to what is shown, and different orders may be possible according to different embodiments. Examples of such alternate orderings may include overlapping, interleaved, interrupted, reordered, incremental, preparatory, supplemental, simultaneous, reverse, or other variant orderings, unless context dictates otherwise. Moreover, in certain embodiments, new operations may be added, or individual operations may be modified or deleted. The added operations can be, for example, from what is mentioned while primarily describing a different system, apparatus, device or method.

(197) Details about Computer Systems

(198) FIG. **23** shows details for a sample computer system **2395** and for a sample computer system **2390**. The computer system **2395** may be a server, while the computer system **2390** may be a personal device, such as a personal computer, a desktop computer, a personal computing device such as a laptop computer, a tablet computer, a mobile phone, and so on. Either type may be used for the computer system **195** and **190** of FIG. **1**, and/or a computer system that is part of OPF **189**.

(199) The computer system **2395** and the computer system **2390** have similarities, which FIG. **23** exploits for purposes of economy in this document. It will be understood, however, that a component in the computer system **2395** may be implemented differently than the same component in the computer system **2390**. For instance, a memory in a server may be larger than a memory in a personal computer, and so on. Similarly, custom application programs **2374** that implement

embodiments may be different, and so on.

(200) The computer system **2395** includes one or more processors **2394**. The processor(s) **2394** are one or more physical circuits that manipulate physical quantities representing data values. The manipulation can be according to control signals, which can be known as commands, op codes, machine code, etc. The manipulation can produce corresponding output signals that are applied to operate a machine. As such, one or more processors **2394** may, for example, include a Central Processing Unit (CPU), a Reduced Instruction Set Computing (RISC) processor, a Complex Instruction Set Computing (CISC) processor, a Graphics Processing Unit (GPU), a Digital Signal Processor (DSP), a Field-Programmable Gate Array (FPGA), an Application Specific Integrated Circuit (ASIC), any combination of these, and so on. A processor may further be a multi-core processor having two or more independent processors that execute instructions. Such independent processors are sometimes called “cores”.

(201) A hardware component such as a processor may also include programmable logic or circuitry that is temporarily configured by software to perform certain operations. For example, a hardware component may include software executed by a general-purpose processor or another type of programmable processor. Once configured by such software, hardware components become specific machines, or specific components of a machine, uniquely tailored to perform the configured functions and are no longer general-purpose processors. It will be appreciated that the decision to implement a hardware component mechanically, in dedicated and permanently configured circuitry, or in temporarily configured circuitry (e.g., configured by software) may be driven by cost and time considerations.

(202) As used herein, a “component” may refer to a device, physical entity or logic having boundaries defined by function or subroutine calls, branch points, Application Programming Interfaces (APIs), or other technologies that provide for the partitioning or modularization of particular processing or control functions. Components may be combined via their interfaces with other components to carry out a machine process. A component may be a packaged functional hardware unit designed for use with other components and a part of a program that usually performs a particular function of related functions. Components may constitute either software components (e.g., code embodied on a machine-readable medium) or hardware components. The hardware components depicted in the computer system **2395**, or the computer system **2390**, are not intended to be exhaustive. Rather, they are representative, for highlighting essential components that can be used with embodiments.

(203) The computer system **2395** also includes a system bus **2312** that is coupled to the processor(s) **2394**. The system bus **2312** can be used by the processor(s) **2394** to control and/or communicate with other components of the computer system **2395**.

(204) The computer system **2395** additionally includes a network interface **2319** that is coupled to system bus **2312**. Network interface **2319** can be used to access a communications network, such as the network **188**. Network interface **2319** can be implemented by a hardware network interface, such as a Network Interface Card (NIC), wireless communication components, cellular communication components, Near Field Communication (NFC) components, Bluetooth® components such as Bluetooth® Low Energy, Wi-Fi® components, etc. Of course, such a hardware network interface may have its own software, and so on.

(205) The computer system **2395** also includes various memory components. These memory components include memory components shown separately in the computer system **2395**, plus cache memory within the processor(s) **2394**. Accordingly, these memory components are examples of non-transitory machine-readable media. The memory components shown separately in the computer system **2395** are variously coupled, directly or indirectly, with the processor(s) **2394**. The coupling in this example is via the system bus **2312**.

(206) Instructions for performing any of the methods or functions described in this document may be stored, completely or partially, within the memory components of the computer system **2395**,

etc. Therefore, one or more of these non-transitory computer-readable media can be configured to store instructions which, when executed by one or more processors **2394** of a host computer system such as the computer system **2395** or the computer system **2390**, can cause the host computer system to perform operations according to embodiments. The instructions may be implemented by computer program code for carrying out operations for aspects of this document. The computer program code may be written in any combination of one or more programming languages, including an object-oriented programming language such as Java, Smalltalk or the like, and/or conventional procedural programming languages, such as the “C” programming language or similar programming languages such as C++, C Sharp, etc.

(207) The memory components of the computer system **2395** include a non-volatile hard drive **2333**. The computer system **2395** further includes a hard drive interface **2332** that is coupled to the hard drive **2333** and to the system bus **2312**.

(208) The memory components of the computer system **2395** include a system memory **2338**. The system memory **2338** includes volatile memory including, but not limited to, cache memory, registers and buffers. In embodiments, data from the hard drive **2333** populates registers of the volatile memory of the system memory **2338**.

(209) In some embodiments, the system memory **2338** has a software architecture that uses a stack of layers, with each layer providing a particular functionality. In this example the layers include, starting from the bottom, an Operating System (OS) **2350**, libraries **2360**, frameworks/middleware **2368** and application programs **2370**, which are also known as applications **2370**. Other software architectures may include less, more or different layers. For example, a presentation layer may also be included. For another example, some mobile or special purpose operating systems may not provide a frameworks/middleware **2368**.

(210) The OS **2350** may manage hardware resources and provide common services. The libraries **2360** provide a common infrastructure that is used by the applications **2370** and/or other components and/or layers. The libraries **2360** provide functionality that allows other software components to perform tasks more easily than if they interfaced directly with the specific underlying functionality of the OS **2350**. The libraries **2360** may include system libraries **2361**, such as a C standard library. The system libraries **2361** may provide functions such as memory allocation functions, string manipulation functions, mathematical functions, and the like.

(211) In addition, the libraries **2360** may include API libraries **2362** and other libraries **2363**. The API libraries **2362** may include media libraries, such as libraries to support presentation and manipulation of various media formats such as MPREG4, H.264, MP3, AAC, AMR, JPG, and PNG. The API libraries **2362** may also include graphics libraries, for instance an OpenGL framework that may be used to render 2D and 3D in a graphic content on the screen **2391**. The API libraries **2362** may further include database libraries, for instance SQLite, which may support various relational database functions. The API libraries **2362** may additionally include web libraries, for instance WebKit, which may support web browsing functionality, and also libraries for applications **2370**.

(212) The frameworks/middleware **2368** may provide a higher-level common infrastructure that may be used by the applications **2370** and/or other software components/modules. For example, the frameworks/middleware **2368** may provide various Graphic User Interface (GUI) functions, high-level resource management, high-level location services, and so forth. The frameworks/middleware **2368** may provide a broad spectrum of other APIs that may be used by the applications **2370** and/or other software components/modules, some of which may be specific to the OS **2350** or to a platform.

(213) The application programs **2370** are also known more simply as applications and apps. One such app is a browser **2371**, which is a software that can permit the user **192** to access other devices in the internet, for example while using a Graphic User Interface (GUI). The browser **2371** includes program modules and instructions that enable the computer system **2395** to exchange network

messages with a network, for example using Hypertext Transfer Protocol (HTTP) messaging.

(214) The application programs **2370** may include one or more custom applications **2374**, made according to embodiments. These can be made so as to cause their host computer to perform operations according to embodiments. Of course, when implemented by software, operations according to embodiments may be implemented much faster than may be implemented by a human mind; for example, tens or hundreds of such operations may be performed per second according to embodiments, which is much faster than a human mind can do.

(215) Other such applications **2370** may include a contacts application, a book reader application, a location application, a media application, a messaging application, and so on. Applications **2370** may be developed using the ANDROID™ or IOS™ Software Development Kit (SDK) by an entity other than the vendor of the particular platform, and may be mobile software running on a mobile operating system such as IOS™, ANDROID™, WINDOWS® Phone, or other mobile operating systems. The applications **2370** may use built-in functions of the OS **2350**, of the libraries **2360**, and of the frameworks/middleware **2368** to create user interfaces for the user **192** to interact with.

(216) The computer system **2395** moreover includes a bus bridge **2320** coupled to the system bus **2312**. The computer system **2395** furthermore includes an input/output (I/O) bus **2321** coupled to the bus bridge **2320**. The computer system **2395** also includes an I/O interface **2322** coupled to the I/O bus **2321**.

(217) For being accessed, the computer system **2395** also includes one or more Universal Serial Bus (USB) ports **2329**. These can be coupled to the I/O interface **2322**. The computer system **2395** further includes a media tray **2326**, which may include storage devices such as CD-ROM drives, multi-media interfaces, and so on.

(218) The computer system **2390** may include many components similar to those of the computer system **2395**, as seen in FIG. 23. In addition, a number of the application programs may be more suitable for the computer system **2390** than for the computer system **2395**.

(219) The computer system **2390** further includes peripheral input/output (I/O) devices for being accessed by a user more routinely. As such, the computer system **2390** includes a screen **2391** and a video adapter **2328** to drive and/or support the screen **2391**. The video adapter **2328** is coupled to the system bus **2312**.

(220) The computer system **2390** also includes a keyboard **2323**, a mouse **2324**, and a printer **2325**. In this example, the keyboard **2323**, the mouse **2324**, and the printer **2325** are directly coupled to the I/O interface **2322**. Sometimes this coupling is via the USB ports **2329**.

(221) In this context, “machine-readable medium” refers to a component, device or other tangible media able to store instructions and data temporarily or permanently and may include, but is not be limited to, a portable computer diskette, a thumb drive, a hard disk, random-access memory (RAM), read-only memory (ROM), buffer memory, flash memory, optical media, magnetic media, cache memory, an Erasable Programmable Read-Only Memory (EPROM), an optical fiber, a portable compact disc read-only memory (CD-ROM), an optical storage device, a magnetic storage device, or any suitable combination of the foregoing. The machine that would read such a medium includes one or more processors **2394**.

(222) The term “machine-readable medium” should be taken to include a single medium or multiple media (e.g., a centralized or distributed database, or associated caches and servers) able to store instructions that a machine such as a processor can store, erase, or read. The term “machine-readable medium” shall also be taken to include any medium, or combination of multiple media, that is capable of storing instructions (e.g., code) for execution by a machine, such that the instructions, when executed by one or more processors of the machine, cause the machine to perform any one or more of the methods described herein. Accordingly, instructions transform a general, non-programmed machine into a particular machine programmed to carry out the described and illustrated functions in the manner described.

(223) A computer readable signal traveling from, to, and via these components may include a

propagated data signal with computer readable program code embodied therein, for example, in baseband or as part of a carrier wave. Such a propagated signal may take any of a variety of forms, including, but not limited to, electro-magnetic, optical, or any suitable combination thereof. A computer readable signal medium may be any computer readable medium that is not a computer readable storage medium and that can communicate, propagate, or transport a program for use by or in connection with an instruction execution system, apparatus, or device.

Operational Examples—Use Cases

(224) The above-mentioned embodiments have one or more uses. Aspects presented below may be implemented as was described above for similar aspects. (Some, but not all of these aspects have even similar reference numerals.)

(225) Operational examples and sample use cases are possible where the attribute of an entity in a dataset is any one of the entity's name, type of entity, a physical location such as an address, a contact information element, an affiliation, a characterization of another entity, a characterization by another entity, an association or relationship with another entity (general or specific instances), an asset of the entity, a declaration by or on behalf of the entity, and so on. Different resources may be produced in such instances, and so on.

(226) FIG. 24 is diagram for an operational example and use case where the resource is a tax obligation 2479 of a primary entity 2493 and/or a secondary entity 2496, due to a sale transaction 2497. The transaction 2497 is an example of a relationship instance between the primary entity 2493 and the secondary entity 2496.

(227) The primary entity 2493 is a seller that has a source location 2457 in a geographic domain 2401. The source location 2457 indicates where the seller is, or is shipping from. The seller is selling an item 2408 to the secondary entity 2496 as the buyer. The secondary entity 2496 has a destination location 2458 that indicates where the buyer is at, and/or where the item 2408 is being shipped to.

(228) It will be recognized that aspects of FIG. 24 have similarities with aspects of FIG. 1. Portions of such aspects may be implemented as described for analogous aspects of FIG. 1. In particular, a thick line 2415 separates FIG. 24, although not completely or rigorously, into a top portion and a bottom portion. Above the line 2415 the emphasis is mostly on entities, components, their relationships, and their interactions, while below the line 2415 the emphasis is mostly processing of data that takes place often within one or more of the components above the line 2415.

(229) Above the line 2415, a computer system 2495 is shown, which is used to help customers, such as a user 2492, with tax compliance. Further in this example, the computer system 2495 is part of an OSP 2498 that is implemented as a Software as a Service (SaaS) provider, for being accessed by the user 2492 online. Alternately, the functionality of the computer system 2495 may be provided locally to a user.

(230) The user 2492 may be standalone. The user 2492 may use a computer system 2490 that has a screen 2491. In embodiments, the user 2492 and the computer system 2490 are considered part of the primary entity 2493, which is also known as entity 2493. The primary entity 2493 can be a business, such as a seller of items, a reseller, a buyer, and so on. In such instances, the user 2492 can be an employee, a contractor, or otherwise an agent of the entity 2493. In use cases the entity 2493 is a seller, the secondary entity 2496 is a buyer, and together they are performing the buy-sell transaction 2497. The buy-sell transaction 2497 may involve an operation, such as an exchange of data to form an agreement. This operation can be performed in person, or over the network 188, etc. In such cases the entity 2493 can even be an online seller, but that is not necessary. The transaction 2497 will have data that is known to the entity 2493, similarly with what was described by the relationship instance 197 of FIG. 1.

(231) In a number of instances, the user 2492 and/or the entity 2493 use software applications to manage their business activities, such as sales, resource management, production, inventory management, delivery, billing, and so on. The user 2492 and/or the entity 2493 may further use

accounting applications to manage purchase orders, sales invoices, refunds, payroll, accounts payable, accounts receivable, and so on. Such software applications, and more, may be used locally by the user **2492**, or from an Online Processing Facility (OPF) **2489** that has been engaged for this purpose by the user **2492** and/or the entity **2493**. In such use cases, the OPF **2489** can be a Mobile Payments system, a Point Of Sale (POS) system, an accounting application, an Enterprise Resource Planning (ERP) provider, an e-commerce provider, an electronic marketplace, a Customer Relationship Management (CRM) system, and so on.

(232) Businesses have tax obligations to various tax authorities of respective tax jurisdictions. A first challenge is in making the related determinations. Tax-related determinations, made for the ultimate purpose of tax compliance, are challenging because the underlying statutes and tax rules and guidance issued by the tax authorities are very complex. There are various types of tax, such as sales tax, use tax, excise tax, value-added tax, and issues about cross-border taxation including customs and duties, and many more. Some types of tax are industry specific. Each type of tax has its own set of rules. Additionally, statutes, tax rules, and rates change often, and new tax rules are continuously added. Compliance becomes further complicated when a taxing authority offers a temporary tax holiday, during which certain taxes are waived.

(233) Tax jurisdictions are defined mainly by geography. Businesses have tax obligations to various tax authorities within the respective tax jurisdictions. There are various tax authorities, such as that of a group of countries, of a single country, of a state, of a county, of a municipality, of a city, of a local district such as a local transit district and so on. So, for example, when a business sells items in transactions that can be taxed by a tax authority, the business may have the tax obligations to the tax authority. These obligations include requiring the business to: a) register itself with the tax authority's taxing agency, b) set up internal processes for collecting sales tax in accordance with the sales tax rules of the tax authority, c) maintain records of the sales transactions and of the collected sales tax in the event of a subsequent audit by the taxing agency, d) periodically prepare a form ("tax return") that includes an accurate determination of the amount of the money owed to the tax authority as sales tax because of the sales transactions, c) file the tax return with the tax authority by a deadline determined by the tax authority, and f) pay ("remit") that amount of money to the tax authority. In such cases, the filing and payment frequency and deadlines are determined by the tax authority.

(234) A challenge for businesses is that the above-mentioned software applications generally cannot provide tax information that is accurate enough for the businesses to be tax compliant with all the relevant tax authorities. The lack of accuracy may manifest itself as errors in the amounts determined to be owed as taxes to the various tax authorities, and it is plain not good to have such errors. For example, businesses that sell products and services have risks whether they over-estimate or under-estimate the sales tax due from a sale transaction. On the one hand, if a seller over-estimates the sales tax due, then the seller collects more sales tax from the buyers than was due. Of course, the seller may not keep this surplus sales tax, but instead must pay it to the tax authorities-if they cannot refund it to the buyers. If a buyer later learns that they paid unnecessarily more sales tax than was due, the seller risks at least harm to their reputation. Sometimes the buyer will have the option to ask the state for a refund of the excess tax by sending an explanation and the receipt, but that is often not done as it is too cumbersome. On the other hand, if a seller under-estimates the sales tax due, then the seller collects less sales tax from the buyers, and therefore pays less sales tax to the authorities than was actually due. That is an underpayment of sales tax that will likely be discovered later, if the tax authority audits the seller. Then the seller will be required to pay the difference, plus fines and/or late fees, because ignorance of the law is not an excuse. Further, one should note that sales taxes are considered trust-fund taxes, meaning that the management of a company can be held personally liable for the unpaid sales tax.

(235) For sales in particular, making correct determinations for sales and use tax is even more difficult. There are a number of factors that contribute to its complexity.

(236) First, some state and local tax authorities have origin-based tax rules, while others have destination-based tax rules. Accordingly, a sales tax may be charged from the seller's location or from the buyer's location.

(237) Second, the various tax authorities assess different, i.e., non-uniform, percentage rates of the sales price as sales tax, for the purchase and sale of items that involve their various tax jurisdictions. These tax jurisdictions include various states, counties, cities, municipalities, special taxing jurisdictions, and so on. As the United States switched, largely but not completely, from primarily origin-based sales tax to destination-based tax, the number of tax jurisdictions rapidly multiplied, and the incentives for local governments to implement new and varied tax rules and ever smaller jurisdictions multiplied. As such, there are over 10,000 different tax jurisdictions in the US, with many partially overlapping, and with sizes varying from many square miles to as small as a single building. In parallel, tens of thousands of tax rules and tax rates have been developed.

(238) Third, in some instances no sales tax is due at all because of the type of item sold. For example, in 2018 selling cowboy boots was exempt from sales tax in Texas, but not in New York. This non-uniformity gives rise to numerous individual taxability rules related to various products and services across different tax jurisdictions.

(239) Fourth, in some instances no sales tax is due at all because of who the individual buyer is. For example, certain entities are exempt from paying sales tax on their purchases, so long as they properly create and sign an exemption certificate and give it to the seller for each purchase made. Entities that are entitled to such exemptions may include wholesalers, resellers, non-profit charities, educational institutions, etc. Of course, who can be exempt is not exactly the same in each tax jurisdiction. And, even when an entity is entitled to be exempt, different tax jurisdictions may have different requirements for the certificate of exemption to be issued and/or remain valid.

(240) Fifth, it can be hard to determine which tax authorities a seller owes sales tax to. A seller may start with tax jurisdictions that it has a physical presence in, such as a main office, a distribution center or warehouse, an employee working remotely, and so on. Such ties with a tax jurisdiction establish the so-called physical nexus. However, a tax authority such as a state or even a city may set its own nexus rules for when a business is considered to be “engaged in business” with it, and therefore that business is subject to registration and collection of sales taxes. These nexus rules may include different types of nexus, such as affiliate nexus, click-through nexus, cookie nexus, economic nexus with thresholds, and so on. For instance, due to economic nexus, a remote seller may owe sales tax for sales made in the jurisdiction that are a) above a set threshold volume, and/or b) above a set threshold number of sales transactions.

(241) Lastly, even where a seller might not have reached any of the thresholds for economic nexus, a number of states are promulgating marketplace facilitator laws that sometimes use such thresholds. According to such laws, intermediaries that are characterized as marketplace facilitators per laws of the state have an obligation, instead of the seller, to collect sales tax on behalf of their sellers, and remit it to the state. The situation becomes even more complex when a seller sells directly to a state, and also via such an intermediary.

(242) To help with such complex determinations, the computer system **2495** may be specialized for tax compliance. The computer system **2495** may have one or more processors and memory, for example as was described for the computer system **195** of FIG. 1. The computer system **2495** thus implements a tax engine **2483** to make the determinations of tax obligations. The tax engine **2483** can be as described for the service engine **183**, and with suitable adjustments and augmentations.

(243) The computer system **2495** may further store locally entity data, i.e., data of user **2492** and/or of entity **2493**, either of which/whom may be a customer, and/or a seller or a buyer in a sales transaction. The entity data may include profile data of the customer, and transaction data from which a determination of a tax obligation is desired. In the online implementation of FIG. 24, the OSP **2498** has a database **2494** for storing the entity data. This entity data may be inputted by the

user **2492**, and/or caused to be downloaded or uploading by the user **2492** from the computer system **2490** or from the OPF **2489**, or extracted from the computer system **2490** or from OPF **2489**, and so on. In other implementations, a simpler memory configuration may suffice for storing the entity data.

(244) A digital tax content **2486** is further implemented within the OSP **2498**. The digital tax content **2486** can be implemented by a strings memory for tax rules **2470** for use by the tax engine **2483**. Some or all of the digital tax content **2486**, including the strings memory for tax rules **2470**, may be implemented locally within the OSP **2498**, or be hosted remotely, to a separate strings memory host platform. As part of managing the digital tax content **2486**, there may be continuous updates of the digital tax rules, by inputs gleaned from a set **2480** of different tax authorities **2481**, **2482**, Updating may be performed by humans, or by computers, and so on. As mentioned above, the number of the different tax authorities in the set **2480** may be very large.

(245) For a specific determination of a tax obligation, the computer system **2495** may receive one or more datasets. A sample received dataset **2435** is shown just below line **2415**, which can be similar to what was described for the dataset **135** of FIG. **1**. Its values SLDP, DLDP can correspond to the source location **2457** and to the destination location **2458** according to arrows **2411**. In this example, the computer system **2490** transmits a request **2484** that includes a payload **2434**, and the dataset **2435** is received by the computer system **2495** parsing the received payload **2434**. In this example the single payload **2434** encodes the entire dataset **2435**, but that is not required, as mentioned earlier.

(246) In this example, the dataset **2435** has been received because it is desired to determine any tax obligations arising from the buy-sell transaction **2497**. As such, the sample received dataset **2435** has values that characterize attributes of the buy-sell transaction **2497**, as indicated by arrows **2499** in combination with arrows **2411**. (It should be noted that these arrows combinations describe correspondences, but not the journey of the data of the buy-sell transaction **2497** in becoming the received dataset **2435**.) Accordingly, in this example the sample received dataset **2435** has a value ID for an identity of the dataset **2435** and/or the transaction **2497**. The dataset **2435** also has a value SLDP as the source location datapoint for the source location **2457**, a value DLDP as the destination location datapoint for the destination location **2458**, an item code IC about the item, a value BV for the purchase price of the item **2408**, and other values. These other values may include the name of the primary entity **2493** or the user **2492**, which can be the seller making sales transactions, some online. These other values may include relevant data of the primary entity **2493** or the user **2492**, such as an address, place(s) of business, prior nexus determinations with various tax jurisdictions, and so on. These other values may include parallel data for the secondary entity **2496**, which can be the buyer, plus data such as whether the secondary entity **2496** has entity-driven exemption status, and so on. The dataset **2435** may further have additional values, as indicated by the dot-dot-dot in the right side of the dataset **2435**. These values may characterize further attributes, such as what item was sold, for example by a Stock Keeping Unit (SKU), how many units of the item were sold, a date and possibly also time of the transaction **2497**, and so on.

(247) For item codes, the Harmonized System Code or HSCode may be used. The system is used by many economies around the world as a basis for their customs tariffs and for the collection of international trade statistics. Over 98% of the merchandise in international trade is classified in terms of the HS. Through its contribution to the harmonization of customs and trade procedures, the HS code reduces the costs related to international trade, as it eliminates the need for a “translator” for people to read and understand this code. We can take the HS code 1704.90.10.00 as an example: 17 relates to Chapter 17 of Section IV—Prepared foodstuffs; beverages, spirits, and vinegar; tobacco and manufactured tobacco substitutes; 04 relates to sugar confectionery (including white chocolate), not containing cocoa; 90 relates to confections or sweetmeats ready for consumption; and 10.00 relates to candied nuts.

(248) Accordingly, the HS code 1704.90.10.00 means candied nuts, for many countries.

(249) For the purposes of this document, the importance of HSCODES is that all products and services sold can be reduced to one of a few thousand categories necessary to determine the tax and that category can be expressed as a short alphanumeric character string. It is not necessary to store a database of all potential items (think UPC codes) and their tax rules. Simply storing the rules by category is sufficient.

(250) In the example of FIG. 24, the strings memory for tax rules **2470** may be populated by columns such as a column **2472** for possible source locations, a column **2473** for possible destination locations, a column **2474** for possible items, other columns as indicated by the dot-dot-dot, and a code strings column **2477** for code strings such as those shown earlier in this document. While these are shown as separate columns, this is done only for clarity. In fact, in other embodiments, the entries for the possible source locations and the possible destination locations, and also even those for the possible items, may be presented in suitable alphanumeric codes that are even concatenated.

(251) The entries in the strings memory for tax rules **2470** accommodate seller-and-buyer locations pair-wise, for determining the sales tax whether it is to be applied for origin-based or destination-based jurisdictions. By including the items, the sales tax can be overridden for diverse taxability of individual items, for temporary tax holidays, for exemptions from having to pay sales tax based on who the buyer is, and also based on nexus, and so on. The domain **2401** is selected to include both the source location **2457** and the destination location **2458**. For instance, in a sale by a seller Illinois to a buyer in Alabama, the domain **2401** can be the US, with its sales tax rules about origin and destination, and so on. In some applications, some tax rules include all possible destination locations given a source location. In some applications, some tax rules include all possible source locations given a destination location.

(252) In the example of FIG. 24, when the dataset **2435** is parsed, a query is formed in terms of a source location lookup code SLLC that matches the source location datapoint SLDP, a destination location lookup code DLLC that matches the source location datapoint DLDP, and maybe even an item lookup code ILC that matches the item IC. The query looks up and finds, per the arrow **2471**, a row with the source location lookup code SLLC, the destination location lookup code DLLC, and maybe even the item lookup code ILC, and which therefore looks up a code string CA that is configured to implement a tax Rule A **2451**.

(253) The code string CA implements, when executed, the sales tax or use tax being owed due to the transaction **2497** at a certain percentage of the purchase price, per the tax rules that the set **2480** of different tax authorities **2481**, **2482** . . . promulgate within the boundaries of their tax jurisdictions. There may be additional code strings, for example as shown in FIGS. 19, 21, for instance where, for a single transaction, there are sales taxes from multiple jurisdictions, such as the state, the city, the municipality and so on. A code string for the sales tax for the State of Kansas might be: “=BASE_AMOUNT×0.065”, and a code string for the sales tax for Sedgwick County might be: “=BASE_AMOUNT×0.01”. Someone purchasing from Sedgwick County from outside Kansas would have to pay both. These may be separate code strings, or a single concatenated code string with plus signs. More complex tariffs may be enabled, such as a tariff of: \$2.194/kg+10% of purchase price may be expressed in DSL as: “=(USD2.194/WEIGHT)+(BASE_AMOUNT×0.01)”

(254) A code module **2405** may be generated from the code string CA, similarly as the above. For instance, the looked-up code string CSA may be returned to the computer system **2495** according to an arrow **2441**, locally or through a cloud, and so on. The code module **2405** may be executed per an execution block **2409** to produce, per the arrow **2478**, a tax obligation **2479**. The tax obligation **2479** will comply with Rule A **2451**. As such, the tax obligation **2479** is akin to producing the resource **179** of FIG. 1.

(255) There could be two taxes due, similarly with FIG. 21. These can be recorded in separate memories, for audit purposes.

(256) The computer system **2495** may then cause a notification **2436** to be transmitted. The

notification **2436** can be about an aspect of the tax obligation **2479**, similarly with the notification **136** of FIG. **1**. In the example of FIG. **24**, the notification **2436** is caused to be transmitted by the computer system **2495** as an answer to the received dataset **2435**. The notification **2436** can be about an aspect of the tax obligation **2479**. In particular, the notification **2436** may inform about the aspect of the tax obligation **2479**, namely that it has been determined, where it can be found, what it is, or at least a portion or a statistic of its content, and so on.

(257) The notification **2436** can be transmitted to one of an output device and another device that can be the remote device, from which the dataset **2435** was received. The output device maybe the screen of a local user or a remote user. The notification **2436** may thus cause a desired image to appear on the screen, such as within a Graphical User Interface (GUI) and so on. The other device may be a remote device, as in this example. In particular, the computer system **2495** causes the notification **2436** to be communicated by being encoded as a payload **2437**, which is carried by a response **2487**. The response **2487** may be transmitted via the network **188** responsive to the received request **2484**. The response **2487** may be transmitted to the computer system **2490**, or to OPF **2489**, and so on. As such, the other device can be the computer system **2490**, or a device of the OPF **2489**, or the screen **2491** of the user **2492**, and so on. In this example the single payload **2437** encodes the entire notification **2436**, but that is not required, similarly with what is written above about encoding datasets in payloads. Of course, along with the aspect of the tax obligation **2479**, it is advantageous to embed in the payload **2437** the ID value and/or one or more values of the dataset **2435**. This will help the recipient correlate the response **2487** to the request **2484**, and therefore match the received aspect of the tax obligation **2479** as the answer to the received dataset **2435**.

(258) The tax information in the strings memory for tax rules **2470** could be updated by: a) beginning with a first information that is reflected on data structure, b) receiving additional information, c) identifying the affected row (parent row), d) breaking up the parent row to smaller ones (children rows), each child row initially having the parent row's information, and e) updating only some but not all of the children rows with the additional information.

(259) FIG. **25** shows a flowchart **2500** for describing methods according to embodiments, for the use case of where producing the resource is computing the sales tax. These methods may be implemented as described above, e.g., by a computer system, and with the variations and additions described above, and also adapted further to sales transactions and sales tax.

(260) According to an operation **2510**, a dataset is received from a seller, their device, and so on. The dataset represents a sales transaction, and could be as described for the dataset **2435**.

(261) According to another operation **2520**, from the received datasets there may be parsed: a base value and i) a seller location, ii) a buyer location, and iii) an item. The locations can be parsed from respective datapoints, and so on.

(262) According to another operation **2530**, in response to the dataset received at the operation **2510**, a number of sub-operations can be caused to be performed. These can be caused to be performed by the computer system itself internally within its online software platform. Or, these can be caused to be performed by the computer system causing a remote support computer to execute them.

(263) The operation **2530** may include a sub-operation **2540**, according to which a strings memory may be caused to be accessed. The strings memory can be as the strings memory for tax rules **2470**.

(264) The operation **2530** may also include a sub-operation **2550**, according to which a code string may be looked up from the strings memory accessed at the operation **2540**. The code string may be looked up in association with i) the seller location, ii) the buyer location, and iii) the item. The code string may be configured to implement a sales tax rule about i) the seller location, ii) the buyer location, and iii) the item being sold from the seller location to the buyer location.

(265) The operation **2530** may further include a sub-operation **2570**, according to which a sales tax that complies with the sales tax rule may be caused to be computed, by a computer system

executing the code string looked up at the sub-operation **2550**. The executing may be performed in conjunction with the base value.

(266) According to another operation **2580**, a notification about the sales tax can be caused to be transmitted over the network to the seller, their device and so on. The notification can be used to add the sales tax to the cost (base value) of the transaction.

(267) A person skilled in the art will be able to practice the present invention in view of this description, which is to be taken as a whole. Details have been included to provide a thorough understanding. In other instances, well-known aspects have not been described, in order to not obscure unnecessarily this description.

(268) Some technologies or techniques described in this document may be known. Even then, however, it does not necessarily follow that it is known to apply such technologies or techniques as described in this document, or for the purposes described in this document.

(269) This description includes one or more examples, but this fact does not limit how the invention may be practiced. Indeed, examples, instances, versions or embodiments of the invention may be practiced according to what is described, or yet differently, and also in conjunction with other present or future technologies. Other such embodiments include combinations and sub-combinations of features described herein, including for example, embodiments that are equivalent to the following: providing or applying a feature in a different order than in a described embodiment; extracting an individual feature from one embodiment and inserting such feature into another embodiment; removing one or more features from an embodiment; or both removing a feature from an embodiment and adding a feature extracted from another embodiment, while providing the features incorporated in such combinations and sub-combinations.

(270) A number of embodiments are possible, each including various combinations of elements. When one or more of the appended drawings—which are part of this specification—are taken together, they may present some embodiments with their elements in a manner so compact that these embodiments can be surveyed quickly. This is true even if these elements are described individually extensively in this text, and these elements are only optional in other embodiments.

(271) In general, the present disclosure reflects preferred embodiments of the invention. The attentive reader will note, however, that some aspects of the disclosed embodiments extend beyond the scope of the claims. To the respect that the disclosed embodiments indeed extend beyond the scope of the claims, the disclosed embodiments are to be considered supplementary background information and do not constitute definitions of the claimed invention.

(272) In this document, the phrases “constructed to”, “adapted to” and/or “configured to” denote one or more actual states of construction, adaptation and/or configuration that is fundamentally tied to physical characteristics of the element or feature preceding these phrases and, as such, reach well beyond merely describing an intended use. Any such elements or features can be implemented in a number of ways, as will be apparent to a person skilled in the art after reviewing the present disclosure, beyond any examples shown in this document.

(273) Parent patent applications: Any and all parent, grandparent, great-grandparent, etc. patent applications, whether mentioned in this document or in an Application Data Sheet (“ADS”) of this patent application, are hereby incorporated by reference herein as originally disclosed, including any priority claims made in those applications and any material incorporated by reference, to the extent such subject matter is not inconsistent herewith.

(274) Reference numerals: In this description a single reference numeral may be used consistently to denote a single item, aspect, component, or process. Moreover, a further effort may have been made in the preparation of this description to use similar though not identical reference numerals to denote other versions or embodiments of an item, aspect, component or process that are identical or at least similar or related. Where made, such a further effort was not required, but was nevertheless made gratuitously so as to accelerate comprehension by the reader. Even where made in this document, such a further effort might not have been made completely consistently for all of the

versions or embodiments that are made possible by this description. Accordingly, the description controls in defining an item, aspect, component or process, rather than its reference numeral. Any similarity in reference numerals may be used to infer a similarity in the text, but not to confuse aspects where the text or other context indicates otherwise.

(275) The claims of this document define certain combinations and sub-combinations of elements, features and acts or operations, which are regarded as novel and non-obvious. The claims also include elements, features and acts or operations that are equivalent to what is explicitly mentioned. Additional claims for other such combinations and sub-combinations may be presented in this or a related document. These claims are intended to encompass within their scope all changes and modifications that are within the true spirit and scope of the subject matter described herein. The terms used herein, including in the claims, are generally intended as “open” terms. For example, the term “including” should be interpreted as “including but not limited to,” the term “having” should be interpreted as “having at least,” etc. If a specific number is ascribed to a claim recitation, this number is a minimum but not a maximum unless stated otherwise. For example, where a claim recites “a” component or “an” item, it means that the claim can have one or more of this component or this item.

(276) In construing the claims of this document, 35 U.S.C. § 112 (f) is invoked by the inventor(s) only when the words “means for” or “steps for” are expressly used in the claims. Accordingly, if these words are not used in a claim, then that claim is not intended to be construed by the inventor(s) in accordance with 35 U.S.C. § 112 (f).

Claims

1. A method for a computer system, the method including at least: receiving, by the computer system over a network from a first remote computer system different from the computer system, one or more datasets; parsing, by the computer system from the one or more datasets, a base value and one or more of: i) a source location datapoint that defines a source location within a domain that has at least two dimensions, ii) a destination location datapoint that defines a destination location within the domain, and iii) an item code that defines an item from a set of items; causing, by the computer system, in response to the received one or more datasets: a) a strings memory to be accessed, in which the strings memory stores code strings in association with one or more of: i) one or more source locations of the domain, ii) one or more destination locations of the domain, and iii) one or more items associated with the one or more source locations of the domain and with the one or more destination locations of the domain, b) a first code string to be looked up from the code strings stored in the strings memory, in which the first code string is looked up in association with one or more of: i) the defined source location, ii) the defined destination location, and iii) the defined item, and in which the first code string is configured to implement a first rule of the domain about the one or more of: i) the defined source location, ii) the defined destination location, and iii) the defined item transitioning from the defined source location and/or to the defined destination location, and c) a first code module that is generated from the first code string to be executed, in which the executing of the first code module is in conjunction with the base value, and in which the executing of the first code module produces a first resource that complies with the first rule of the domain; and causing, by the computer system, a notification about an aspect of the first resource to be transmitted over the network to one of an output device and another device.

2. The method of claim 1, in which: the domain is geographic.

3. The method of claim 1, in which: the domain has three dimensions.

4. The method of claim 1, in which: at least one of the source location datapoint and the destination location datapoint includes a street address.

5. The method of claim 1, in which: at least one of the source location datapoint and the destination location datapoint includes a latitude and a longitude.

6. The method of claim 1, in which: at least one of the source location datapoint and the destination location data point is a location lookup code.
7. The method of claim 1, further including: detecting, by the computer system from the one or more datasets, an indication about a length of the source location datapoint, and in which the parsing is performed according to the detected indication.
8. The method of claim 1, in which: the looking up is performed by applying to the strings memory the parsed one or more of: i) the source location datapoint and ii) the destination location datapoint.
9. The method of claim 1, in which: the looking up is performed by applying to the strings memory the parsed one or more of: i) the source location datapoint, ii) the destination location datapoint, and iii) the item code.
10. The method of claim 1, further including: converting, by the computer system, at least one of the source location datapoint and the destination location datapoint into a location lookup code, and in which the first code string is looked up by the location lookup code.
11. The method of claim 10, in which: at least one of the source location datapoint and the destination location datapoint includes a latitude and a longitude.
12. The method of claim 10, in which: at least one of the source location datapoint and the destination location datapoint includes a street address.
13. The method of claim 10, in which: the converting includes adding one or more characters to the at least one of the source location datapoint and the destination location datapoint.
14. The method of claim 1, in which: the strings memory is hosted by a strings memory host platform remote from an online software platform that hosts the computer system; and causing the strings memory to be accessed includes at least: forming, by the computer system, a lookup query from at least one of a source location lookup code and a destination location lookup code; causing, by the computer system, the lookup query to be transmitted over a network from the computer system to a support computer system that is hosted by the strings memory host platform; and receiving, by the computer system, the looked up first code string from the support computer system.
15. The method of claim 1, in which: the strings memory is hosted by a strings memory host platform remote from an online software platform that hosts the computer system; causing the strings memory to be accessed includes at least: forming, by the computer system, a lookup query from at least one of a source location lookup code and a destination location lookup code; and causing, by the computer system, the lookup query to be transmitted over a network from the computer system to the strings memory host platform for generation of the first code module by a support computer system in the strings memory host platform; the first code module is caused to be generated by causing the support computer system to generate the first code module; and the generated first code module is received by the computer system from the support computer system.
16. The method of claim 1, in which: the strings memory is hosted by a strings memory host platform remote from an online software platform that hosts the computer system; causing the strings memory to be accessed includes at least: forming, by the computer system, a lookup query from at least one of a source location lookup code and a destination location lookup code; and causing, by the computer system, the lookup query to be transmitted over a network from the computer system to the strings memory host platform; the first code module is caused to be generated by causing a support computer system hosted by the strings memory host platform to generate the first code module; causing the first code module to be executed includes causing the support computer system to execute the first code module to produce the first resource; and the produced first resource is received by the computer system from the support computer system.
17. The method of claim 1, in which: the strings memory is partitioned according to different source location datapoints.
18. The method of claim 1, in which: the strings memory is partitioned according to different destination location datapoints.

19. The method of claim 1, in which: the strings memory is partitioned according to different item codes.

20. The method of claim 1, in which: the looking up is performed by applying to the strings memory a single query string that is derived by concatenating, in any order, at least two of: a first query made from the source location datapoint, a second query made from the destination location datapoint, and a third query made from the item code.

21. The method of claim 1, in which: the looking up is performed by applying to the strings memory a single query string that is derived by concatenating, in any order, at least two of: the source location datapoint, the destination location datapoint, and the item code.

22. The method of claim 1, in which: the first code module is the first code string.

23. The method of claim 1, in which: the first code module references the base value as a variable.

24. The method of claim 1, in which: the first code module includes a logical "IF" statement.

25. The method of claim 1, further including: generating, by the computer system, the first code module from the first code string.

26. The method of claim 25, in which: the first code module is generated from a first code kernel of the first code string.

27. The method of claim 26, in which: the first code kernel is the first code string.

28. The method of claim 26, in which: the first code kernel is a subset of the first code string.

29. The method of claim 26, in which: the first code kernel includes a logical "IF" statement.

30. The method of claim 26, in which: the first code module is generated by further altering the first code kernel.

31. The method of claim 1, in which: the first code module includes the base value as a variable.

32. The method of claim 1, in which: the first code module is executed by a subroutine that calls the base value as a variable.

33. The method of claim 1, further including: causing, by the computer system, a second code string to be looked up from the code strings stored in the strings memory, in which the second code string is associated with the one or more of: i) the defined source location, ii) the defined destination location, and iii) the defined item, in which the second code string is configured to implement a second rule of the domain about the one or more of: i) the defined source location, ii) the defined destination location, and iii) the defined item transitioning from the defined source location and/or to the defined destination location, in which the second rule of the domain is distinct from the first rule of the domain, in which the first code module is also generated from the second code string, and in which the first resource also complies with the second rule of the domain.

34. The method of claim 33, in which: the first code module is generated from a first code kernel of the first code string and from a second code kernel of the second code string.

35. The method of claim 33, in which: the first code module is generated from a first code kernel of the first code string, from a plus sign, and from a second code kernel of the second code string.

36. The method of claim 1, further including: causing, by the computer system, a second code string to be looked up from the code strings stored in the strings memory, in which the second code string is associated with the one or more of: i) the defined source location, ii) the defined destination location, and iii) the defined item, in which the second code string is configured to implement a second rule of the domain about the one or more of: i) the defined source location, ii) the defined destination location, and iii) the defined item transitioning from the defined source location and/or to the defined destination location, and in which the second rule of the domain is distinct from the first rule of the domain; causing, by the computer system, a second code module that is generated from the second code string to be executed, in which the executing of the second code module is in conjunction with the base value, and in which the executing of the second code module produces a second resource that complies with the second rule of the domain; and summing a numerical value of the first resource and a numerical value of the second resource to produce a

composite resource, and in which the notification is about an aspect of the composite resource instead of about an aspect of the first resource.

37. The method of claim 36, in which: the computer system includes a records memory, and the method further includes: storing, by the computer system, the first resource in the records memory in association with the first rule of the domain; and storing, by the computer system, the second resource in the records memory in association with the second rule of the domain.

38. The method of claim 36, in which: the computer system includes a records memory, the strings memory further stores, in association with the first code string, a first rule id that identifies an aspect of the first rule of the domain, the strings memory further stores, in association with the second code string, a second rule id that identifies an aspect of the second rule of the domain, and the method further includes: storing, by the computer system, the first resource in the records memory in association with the first rule id; and storing, by the computer system, the second resource in the records memory in association with the second rule id.
