

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12384695
B2
August 12, 2025
Jung; Hee Do et al.

Water purifier

Abstract

A water purifier may include: a filter filtering raw water to provide purified water; a discharge port through which the purified water is discharged outside; water pipes providing a flow space for the purified water to flow; a flow path module including a body part supporting the water pipes; and a tubing assembly detachably connected to the water pipes to selectively open and close at least a portion of the water pipes when connected thereto. The tubing assembly has one side connected to the filter and the other side connected to the flow path module, and the flow path module receives the purified water filtered by the filter through the tubing assembly. The flow path module may be placed above the tubing assembly, and disposed between the filter and the discharge port while overlapping at least a portion of the tubing assembly without overlapping the filter when viewed from above.

Inventors: Jung; Hee Do (Gwanak-gu, KR), Lee; Jong Hwan (Gwanak-gu, KR), Kim; Hyun Goo (Gwanak-gu, KR), Oh; Yoo Won (Gwanak-gu, KR), Park; Chan Jung (Gwanak-gu, KR), Jung; Woong (Gwanak-gu, KR)

Applicant: COWAY CO., LTD. (Chungcheongnam-do, KR)

Family ID: 1000008750704

Assignee: COWAY CO., LTD. (Chungcheongnam-do, KR)

Appl. No.: 18/247954

Filed (or PCT Filed): October 08, 2021

PCT No.: PCT/KR2021/013945

PCT Pub. No.: WO2022/075819

PCT Pub. Date: April 14, 2022

Prior Publication Data

Foreign Application Priority Data

KR	10-2020-0130279	Oct. 08, 2020
KR	10-2020-0130280	Oct. 08, 2020
KR	10-2020-0130281	Oct. 08, 2020

Publication Classification

Int. Cl.: C02F1/00 (20230101); B01D35/04 (20060101); B01D35/157 (20060101); B01D35/30 (20060101)

U.S. Cl.:

CPC C02F1/003 (20130101); B01D35/04 (20130101); B01D35/157 (20130101); B01D35/306 (20130101); C02F2201/004 (20130101); C02F2209/00 (20130101); C02F2303/04 (20130101)

Field of Classification Search

CPC: C02F (1/003); C02F (2201/004); C02F (2209/00); C02F (2303/04); C02F (2201/006); C02F (2307/10); B01D (35/04); B01D (35/157); B01D (35/306); B67D (1/00); B67D (1/08); B67D (1/12)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4741823	12/1987	Olsen	210/96.2	B01D 61/10
6436282	12/2001	Gundrum	210/257.2	B01D 65/00
9914096	12/2017	Sun	N/A	B01D 61/025

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
105879459	12/2017	CN	N/A
2537569	12/2011	EP	B01D 35/00
10-2019-0024760	12/2018	KR	N/A
10-1987942	12/2018	KR	N/A
10-2019-0108381	12/2018	KR	N/A
10-2020-0075166	12/2019	KR	N/A

OTHER PUBLICATIONS

Primary Examiner: Cecil; Terry K

Attorney, Agent or Firm: Oblon, McClelland, Maier & Neustadt, L.L.P.

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates to a water purifier.

BACKGROUND ART

(2) In general, a water purifier is a device that receives raw water from a raw water source such as tap water, filters the raw water into purified water, and then provides the purified water to a user. Such purified water may be immediately provided to the user, but may be provided as cold water after being cooled to a predetermined temperature or lower, or as hot water heated to a preset temperature or higher. In addition, the water purifier includes a plurality of flow paths through which purified water, cold water, and hot water respectively flow to provide the purified water, the cold water, and the hot water to the user.

(3) Meanwhile, when the water purifier is used for a long time, the flow path needs to be replaced due to water stains. Conventionally, in order to replace the flow path, a cover is separated from a main body, and then the flow path is replaced after separating the flow path from components such as a filter. However, in order to replace the flow path by separating it from the filter, it is necessary to clearly know the internal structure of the water purifier, which makes it difficult for a user to replace the flow path. In addition, in order to replace a plurality of flow paths in the water purifier, it is inconvenient to separate each of the plurality of flow paths from the filter and replace them. Accordingly a water purifier for a user to easily replace a flow path has been developed.

(4) Korean Patent Application Publication No. 10-2019-0020540 of the present applicant "Water filter connection module and water treatment device including the same" discloses a water filter connection module provided to be separable from a water filter and a water treatment device. However, according to the conventional water filter connection module, in order to replace the water filter connection module, it is required to separate the water filter connection module from a plurality of peripheral components such as a water filter, a water supply source, a drain pipe, and a storage tank. As such, in order to replace the water filter connection module, it is necessary to know the connection relationships between the connection module and the plurality of peripheral components, and the inconvenience of separating the plurality of peripheral components from the connection module still exists.

(5) In addition, in the conventional water treatment device, a configuration for guiding a position where the water filter connection module is placed is not disclosed, and thus it is difficult for a user to place the water filter connection module in an accurate position. Further, when the direction in which the water filter connection module is placed is incorrect, it may be incorrectly connected to the plurality of peripheral components such as the water filter, the water supply source, the drain pipe, and the storage tank. In this case, it is required to release the connection and rearrange the connection module.

(6) Accordingly, there is a need for a module which allows a general user, who does not specifically know the internal structure of the water purifier to easily replace a flow path inside the water purifier. In addition, there is a need for a device capable of guiding the position of the module so

that the user can place the module in an accurate position.

(7) In addition, the water purifier includes a circuit board that controls operation of the water purifier, and when the circuit board is in poor operation or used for a long time, maintenance of the circuit board is required. However, in the conventional water purifier, since the circuit board is disposed inside the water purifier, all peripheral components need to be separated in order to expose the circuit board to the outside. Due to this, it takes a lot of effort and time for an operator to maintain or replace the circuit board.

(8) Accordingly, there is a need for a device that allows a user to easily maintain and repair the circuit board and that reduces the time required for maintenance.

(9) In addition, the conventional water treatment device does not disclose a configuration for preventing the connection module from being separated from the placed portion when the water filter connection module is placed, so there is a risk of the connection module being separated from its correct position. Moreover, when the water filter connection module is separated from its original position, some connections between the connection module and the water filter, the water supply source, the drain pipe, and the storage tank may be disconnected, resulting in a risk of water leakage.

(10) Accordingly, there is a need for a device capable of preventing the connection module from being separated from its correct position, and water leakage due to disconnection with the peripheral components.

PRIOR ART DOCUMENT

(11) (Patent Document 1) Korean Patent Application Publication No. 10-2019-0020540 (published on Mar. 4, 2019) (Patent Document 2) US Patent Application Publication 2018-0078884 (published on Mar. 22, 2018)

DETAILED DESCRIPTION OF INVENTION

Technical Problems

(12) In view of the above, embodiments of the present disclosure provide a water purifier which allows a general user who does not specifically know the internal structure of the water purifier to easily replace a flow path inside the water purifier.

(13) In addition, embodiments of the present disclosure provide a water purifier capable of replacing a plurality of flow paths at once by separating one flow path module from a main body.

(14) Further, embodiments of the present disclosure provide a water purifier capable of connecting each of the plurality of flow paths with other components simply by mounting the flow path module in a correct position on a bracket.

(15) Furthermore, embodiments of the present disclosure provide a water purifier in which a cover frame can be fixedly supported on a main frame while the cover frame is separated from the bracket to prevent the cover frame from arbitrarily covering an upper side of the bracket.

(16) In addition, embodiments of the present disclosure provide a water purifier in which a circuit board including a plurality of boards and wires can be separated from the bracket while being supported on the cover frame, so the user can easily replace the flow path module without interference between the cover frame and the circuit board while replacing the flow path module.

(17) Further, embodiments of the present disclosure provide a water purifier in which the circuit board can be easily maintained by being fixedly supported on the main frame while the circuit board is separated from the cover frame.

(18) Embodiments of the present disclosure provide a water purifier capable of preventing the cover frame from being closed when the flow path module is in a state in which it can be separated from the bracket.

(19) Further, embodiments of the present disclosure provide a water purifier which makes the user aware that the flow path module is in the separable state, so that the user can confirm once again whether a separation preventing member is engaged with the flow path module.

(20) In addition, embodiments of the present disclosure provide a water purifier capable of

preventing leakage of water between the flow path module and a tubing assembly by preventing the flow path module from being separated from its correct position.

Technical Solution

(21) In accordance with an aspect of the present disclosure, there is provided a filter for filtering raw water to provide purified water; a discharge port through which the purified water is discharged to an outside; a plurality of water pipes providing a flow space for the purified water to flow; a flow path module including a body part supporting the plurality of water pipes; and a tubing assembly detachably connected to the plurality of water pipes, the tubing assembly serving to selectively open and close at least a portion of the plurality of water pipes when connected to the plurality of water pipes, wherein the tubing assembly has one side connected to the filter and the other side connected to the flow path module, and the flow path module receives the purified water filtered by the filter through the tubing assembly, wherein the flow path module is placed above the tubing assembly, and is disposed between the filter and the discharge port while overlapping at least a portion of the tubing assembly without overlapping the filter when viewed from above, wherein each of the plurality of water pipes includes a passage part through which the purified water flows, an inlet part provided on one side of the passage part through which the purified water flows in and including an inlet, and an outlet part provided on the other side of the passage part through which the purified water is discharged and including an outlet, and wherein the inlet and the outlet provided in each of the plurality of water pipes are exposed to the outside of the body part and opened downward.

(22) Further, the inlet part and the outlet part provided in each of the plurality of water pipes may be extended downward.

(23) Further, the body part may support the passage part, and have a plurality of through holes, the inlet part and the outlet part may protrude outward from the body through the plurality of through holes, and the plurality of through holes may be formed on a same surface of the body part.

(24) Further, at least a portion of the passage parts of the plurality of water pipes may extend in different directions, and each of the plurality of water pipes may be configured such that the flow space does not communicate with each other in the body part.

(25) Further, the inlet and the outlet provided in at least one of the plurality of water pipes may have different sizes from each other

(26) Further, at least one of the plurality of water pipes may have a different shape from another one thereof.

(27) Further, the tubing assembly may include a plurality of connectors which are selectively engaged with the inlet parts and the outlet parts of the plurality of water pipes, respectively, each of the inlet parts and the outlet parts of the plurality of water pipes may have a predetermined rigidity so that a shape thereof does not change when engaged with the connector.

(28) Further, the inlet and the outlet provided in at least one of the plurality of water pipes may have different sizes from each other, and each of the plurality of connectors may have a size corresponding to the inlet and the outlet provided in each of the plurality of water pipes.

(29) Further, an orientation determination portion having a protrusion or recess shape may be provided on an outer surface of the body part so that the body part has an asymmetrical shape, and the orientation determination portion may have a shape protruding or depressed laterally from the outer surface of the body part.

(30) Further, the water purifier may further include: a cooler for cooling the purified water to provide cold water; and a cold water flow part through which the cold water obtained by the cooler flows, wherein the flow path module may be disposed above the cooler and the cold water flow part.

(31) Further, the water purifier may further include: a frame including a main frame and a cover frame, wherein the cover frame may be configured such that the cover frame is placed in a cover position where the cover frame covers the flow path module or separated from the cover position so

that the flow path module is exposed to the outside.

(32) Further, the water purifier may further include: a circuit board, for controlling operation of the water purifier, supported by the cover frame, wherein when the cover frame is separated from the cover position, the circuit board may be separated from the cover position together with the cover frame.

(33) Further, the water purifier may further include: a bracket having a seating portion on which the body part is seated when the flow path module is connected to the tubing assembly, wherein the seating portion is a hole concavely formed in the bracket to surround at least a portion of a lower surface and at least a portion of a side surface of the flow path module, wherein when placed in the cover position, the cover frame is disposed above the bracket to cover an upper surface of the flow path module, wherein an orientation determination portion, having a protrusion or recess shape, for guiding a direction in which the flow path module is seated in the seating portion is provided on an outer surface of the body part, wherein the seating portion is provided with an engaging part having a shape corresponding to the orientation determination portion, and wherein the orientation determination portion engages with the engaging part when the flow path module is seated in a predetermined direction on the seating portion, and when the flow path module is seated in the seating portion in a direction different from the predetermined direction, the orientation determination portion does not engage with the engaging part and interferes with the bracket.

(34) Further, the water purifier may further include: a bracket having a seating portion on which the body part is seated when the flow path module is connected to the tubing assembly; and a separation preventing member for preventing the flow path module from being separated from the bracket when the flow path module is connected to the tubing assembly, wherein the separation preventing member may be supported by the bracket and selectively interferes with an upper side of the body part of the flow path module to prevent separation of the flow path module.

(35) The water purifier may further include: a cover frame that covers the flow path module when a position of the cover frame relative to the bracket is a cover position, wherein the separation preventing member may allow the cover frame to be placed in the cover position when selectively interfering with the flow path module to prevent separation of the flow path module, and wherein the separation preventing member may interfere with the cover frame to prevent the cover frame from being placed in the cover position when allowing the flow path module to be separated from the seating portion.

(36) The water purifier may further include: a main frame that accommodates the filter and the tubing assembly, wherein the cover frame may be placed in an open fixed position where the cover frame is engaged and fixed to the main frame in an inclined state with respect to the cover frame in the cover position, or the cover position.

(37) The body part may be provided with a protruding hook, and when engaged with the hook, the separation preventing member may selectively interfere with the flow path module to prevent separation of the flow path module and allows the cover frame to be placed in the cover position.

Effect of Invention

(38) According to embodiments of the present disclosure, even a general user who does not specifically know the internal structure of the water purifier can easily replace the flow path inside the water purifier.

(39) In addition, the user can replace the plurality of flow paths at once by separating one flow path module from the main body.

(40) Further, each of the plurality of flow paths can be connected with other components only by mounting the flow path module at the correct position on the bracket.

(41) Furthermore, the cover frame can be fixedly supported on the main frame while being separated from the bracket to prevent the cover frame from arbitrarily covering the upper side of the bracket.

(42) In addition, since the circuit board including the plurality of boards and wires is separated

from the bracket while being supported on the cover frame, the user can easily replace the flow path module without interference between the cover frame and the circuit board while replacing the flow path module.

(43) Further, since the circuit board is fixedly supported on the main frame while being separated from the cover frame, the circuit board can be easily maintained.

(44) Furthermore, the cover frame can be prevented from being closed when the flow path module is in the state in which it can be separated from the bracket.

(45) In addition, it is possible to make the user aware that the flow path module is in the state in which it can be separated, and thus, the user can confirm once again whether the separation preventing member is engaged with the flow path module.

(46) Further, it is possible to prevent water leakage between the flow path module and the tubing assembly by preventing the flow path module from being separated from its correct position.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a perspective view showing a water purifier according to one embodiment of the present disclosure.

(2) FIG. 2 is a perspective view of the water purifier of FIG. 1 in which an upper cover is separated.

(3) FIG. 3 is a perspective view showing a state in which a cover frame of FIG. 2 is placed in an open and fixed position.

(4) FIG. 4 is a perspective view of a flow path module of FIG. 3.

(5) FIG. 5 is an exploded perspective view of the flow path module of FIG. 4.

(6) FIG. 6 is a bottom perspective view of the flow path module of FIG. 4.

(7) FIG. 7 is a partial perspective view showing an exploded state of the flow path module of FIG. 3.

(8) FIG. 8 is a plan view in which the flow path module is omitted in FIG. 7.

(9) FIG. 9 is an enlarged view of part A of FIG. 3.

(10) FIG. 10 is a perspective view illustrating a state in which the flow path module of FIG. 3 and a tubing assembly are connected.

(11) FIG. 11 is a perspective view showing an exploded state of a body part of FIG. 10.

(12) FIG. 12 is a partially exploded perspective view of the flow path module and the tubing assembly of FIG. 10.

(13) FIG. 13 is a conceptual diagram schematically illustrating a flow of water in the water purifier according to one embodiment of the present disclosure.

(14) FIG. 14 is a partial cross-sectional view of a first purified water pipe and a first purified water inlet connector of FIG. 11 taken in a longitudinal direction.

(15) FIG. 15 is a partial cross-sectional view and an enlarged view when the cover frame of FIG. 2 is placed in the open and fixed position.

BEST MODE FOR CARRYING OUT THE INVENTION

(16) A preferred embodiment of the present disclosure for implementing the spirit of the present disclosure will be described in more detail with reference to the accompanying drawings.

(17) However, in describing the present disclosure, detailed descriptions of known configurations or functions may be omitted to clarify the present disclosure.

(18) When an element is referred to as being 'connected' to, 'supported' by, 'flowed' into, 'supplied' to, 'floated' in, 'fastened' with, 'flowed' out, 'discharged' out, or 'accessed' by another element, it should be understood that the element may be directly connected to, supported by, flowed into, supplied to, floated in, fastened with, flowed out, discharged out, or accessed by the

other element, but that other elements may exist in the middle.

(19) The terms used in the present disclosure are only used for describing specific embodiments, and are not intended to limit the present disclosure. Singular expressions include plural expressions unless the context clearly indicates otherwise.

(20) Terms including ordinal numbers, such as first and second, may be used for describing various elements, but the corresponding elements are not limited by these terms. These terms are only used for the purpose of distinguishing one element from another element.

(21) In the present specification, it is to be understood that the terms such as “including” are intended to indicate the existence of the certain features, areas, integers, steps, actions, elements and/or combinations thereof disclosed in the specification, and are not intended to preclude the possibility that one or more other certain features, areas, integers, steps, actions, elements and/or combinations thereof may exist or may be added.

(22) In addition, in the present specification, expressions for directions such as upward and downward are described based on the drawings, and it is said in advance that they may be expressed differently when the direction of the object is changed. Meanwhile, in the present specification, a left-right direction may be the x-axis direction of FIGS. 1 to 3 and 7, and a front-rear direction may be the y-axis direction of FIGS. 1 to 3 and 7. In addition, an up-down direction may be the z-axis direction of FIGS. 1 to 3 and 7.

(23) Hereinafter, a specific configuration of a water purifier **1** according to one embodiment of the present disclosure will be described with reference to the drawings.

(24) Hereinafter, referring to FIGS. 1, 4 and 13, the water purifier **1** according to one embodiment of the present disclosure can provide clean water to users by filtering water supplied from the outside. For example, the water purifier **1** can receive water from a water supply source (not shown) such as tap water, and filter the supplied water into clean water. The water purifier **1** may include a frame **100**, a flow path module **200**, a bracket **300**, a separation preventing member **400**, a filter **500**, a tubing assembly **600**, a cooler **700**, a heater **800**, a cold water flow unit **900**, a NOS valve **1000**, and a circuit board **1100**.

(25) Meanwhile, water introduced into the water purifier **1** from the outside may be classified into raw water, purified water, cold water, and hot water. Hereinafter, among water introduced into the water purifier **1** from the outside, water that has not passed through the filter **500** is defined as raw water, and water filtered through the filter **500** is defined as purified water. In addition, among the water filtered by the filter **500**, the water cooled to a predetermined temperature or less in the cooler **700** is defined as cold water, and among the water filtered by the filter **500**, the water heated by the heater **800** to a predetermined temperature or more is defined as hot water.

(26) Referring to FIGS. 2 and 3, the frame **100** may provide a space where the flow path module **200**, the bracket **300**, the separation preventing member **400**, the filter **500**, the tubing assembly **600**, the cooler **700**, and the heater **800**, the cold water flow unit **900**, the NOS valve **1000** and the circuit board **1100** are accommodated. For example, the frame **100** may extend in the up-down direction and may have a shape in which a part of an upper portion thereof protrudes forward. The frame **100** may include a main frame **110** and a cover frame **120**.

(27) The main frame **110** may be provided to surround at least a portion of the flow path module **200** the bracket **300**, the separation preventing member **400**, the filter **500**, the tubing assembly **600**, the cooler **700**, the heater **800** the cold water flow unit **900**, the NOS valve **1000**, and the circuit board **1100**. For example, the main frame **110** may be formed by coupling a plurality of covers to each other with bolts or the like. In addition, the upper cover of the main frame **110** may be selectively separated. However, this is only an example, and other than the bolts, well-known means for coupling the plurality of covers to each other may be used, and the side or bottom cover may be selectively separated.

(28) Meanwhile, the main frame **110** may be provided with a rib **111** that can be engaged with a fixture **121** to be described later when the cover frame **120** is rotated to an open position to be

described later. For example, the rib **111** may be formed on an upper portion of a rear side of the main frame **110** and may be provided to correspond to a shape of the fixture **121** so as to be selectively engaged with the fixture **121**. As such, as the rib **111** engages with the fixture **121**, the open fixed position of the cover frame **120** can be maintained.

(29) In addition, the main frame **110** may be provided with a discharge port **112** for discharging purified water to the outside. The discharge port **112** may communicate with the tubing assembly **600** and may be configured to discharge purified water, cold water, and hot water flowing in the tubing assembly **600** to the outside. For example, the discharge port **112** may be configured to discharge one of purified water, cold water, and hot water to the outside according to a user's selection. In addition, the discharge port **112** may be provided on a front side of the main frame **110** and may be open downward.

(30) Referring again to FIGS. **2** and **3**, the cover frame **120** may be supported by the bracket **300** to cover the flow path module **200** seated on the bracket **300**. In addition, the cover frame **120** may be separated from the bracket **300** so that the flow path module **200** is exposed to the outside. In this case, the cover frame **120** may be fixedly supported on the main frame **110**. However, this is only an example, and the cover frame **120** may be rotatably supported by the bracket **300** or the main frame **110**. Further, the cover frame **120** may support the circuit board **1100** and wires connected to the circuit board **1100**, and may be separated from the bracket **300** together with the circuit board **1100**.

(31) The cover frame **120** may be selectively placed in any one of a cover position and an open fixed position. For example, as shown in FIG. **2**, the cover frame **120** may be placed in the cover position. In this case, the cover frame **120** may be positioned above the bracket **300** and the flow path module **200**, and may block the flow path module **200** from the outside. As another example, as shown in FIGS. **3** and **15**, the cover frame **120** may be configured to be separable from the cover position so that the flow path module **200** is exposed to the outside. In other words, the cover frame **120** may be separated from the bracket **300**, and the separated cover frame **120** may be placed in the open fixed position. In this case upper portions of the bracket **300** and the flow path module **200** may be opened to the outside, and the flow path module **200** may be separated from the bracket **300** and replaced. In addition, the cover frame **120** placed in the open fixed position may be engaged and fixed to the main frame **110** in an inclined state with respect to the cover frame **120** in the cover position.

(32) The cover frame **120** may include the fixture **121**, a support **122**, and a cover frame body **123**.

(33) The fixture **121** may be engaged with the main frame **110** to maintain the position of the cover frame **120** when the cover frame **120** is placed in an open fixed position. The fixture **121** may be provided at one end of the cover frame body **123** and may be formed on a rear side of the cover frame **120**. For example, the fixture **121** may have a hook shape to be engaged with the rib **111**. However, this is just an example, and the fixture **121** may be formed on the main frame **110**. In addition, the fixture **121** may fix the cover frame **120** placed in the open fixed position to the main frame **110**. For example, when a user needs to replace the flow path module **200**, the cover frame **120** can be maintained in the open fixed position by the fixture **121** engaged with the rib **111**.

(34) In addition, the support **122** may be configured such that the cover frame **120** placed in the open fixed position is supported on the filter **500**. For example, the support **122** is supported on the filter **500** or the main frame **110** when the cover frame **120** is placed in the open fixed position. In this way, the cover frame **120** can be maintained in the open fixed position. Moreover, the support **122** may protrude downward from a lower surface of the cover frame body **123**, for example.

(35) The cover frame body **123** may cover the flow path module **200** and support the fixture **121** and the support **122**.

(36) As described above, by preventing the cover frame **120** from being arbitrarily placed in the cover position, the user can easily replace the flow path module **200** without interference with the cover frame **120** while replacing the flow path module **200**. In addition, the circuit board **1100**

including a plurality of boards and wires is placed in the open fixed position together with the cover frame **120**, and thus when the user replaces the flow path module **200**, inconvenience caused by interference with the circuit board **1100** can be eliminated.

(37) In addition, since the length of the wire connected to the circuit board **1100** is limited, the cover frame **120** and the circuit board **1100** have a limited range of movement. However, since the cover frame **120** is fixed to the main frame **110** even within the limited movement range, the open fixed position is maintained while the flow path module **200** is exposed to the outside.

(38) Referring to FIG. 4, the flow path module **200** may provide a passage through which purified water and cold water flow. The flow path module **200** can communicate with the tubing assembly **600** and is detachably connected to the tubing assembly **600**. For example, when the flow path module **200** is connected to the tubing assembly **600**, purified water and cold water may flow between the flow path module **200** and the tubing assembly **600**. In addition, when the flow path module **200** is connected to the tubing assembly **600**, the flow path module **200** may be supplied with purified water from the filter **500** through the tubing assembly **600**. That is, the flow path module **200** may be indirectly connected to the filter **500** through the tubing assembly **600** without being directly connected to the filter **500**. The flow path module **200** may include a body part **210** and a water pipe **220**.

(39) Referring to FIG. 5, the body part **210** may support a plurality of water pipes **220** and may be provided to surround at least a portion of the plurality of water pipes **220**. The body part **210** may be seated on a seating portion **310** of the bracket **300**, which will be described later, and when the body part **210** is seated to match the seating portion **310**, the water pipe **220** may be connected to the tubing assembly **600**. In addition, a shape of the body part **210** may be formed to correspond to a shape of the seating portion **310**. The body part **210** may include a first body **211**, a second body **212**, a hook **213**, and a support jaw **214**.

(40) The first body **211** may surround the water pipe **220** at an upper side, and the second body **212** may surround the water pipe **220** at a lower side. For example, when the first body **211** and the second body **212** are coupled to each other, at least a portion of the water pipe **220** may be disposed in an inner space between the first body **211** and the second body **212**.

(41) Meanwhile, an orientation determination portion **211a** may be formed on the first body **211** so that the first body **211** has an asymmetrical shape. When the body part **210** is seated on the seating portion **310**, the orientation determination portion **211a** may be provided on the first body **211** so as to be seated in a preset direction. The orientation determination portion **211a** may be provided to be engaged with an engaging portion **311** of the seating portion **310** to be described later. In addition, the orientation determination portion **211a** may be, for example, a protrusion protruding laterally from an outer surface of the first body **211**, and may be formed corresponding to a recess shape of the engaging portion **311**. However, this is only an example, and the orientation determination portion **211a** may have the shape of a recess shape depressed from the outer surface of the first body **211**, and the engaging portion **311** may have a protrusion shape, so that the orientation determination portion **211a** and the engaging portion **311** are engaged with each other.

(42) For example, the orientation determination portion **211a** is engaged with the engagement portion **311** when the body part **210** is seated on the seating portion **310** in the preset orientation. In this case, the body part **210** is placed so as to match the seating portion **310**. As another example, the orientation determination portion **211a** interferes with the bracket **300** without being engaged with the engagement portion **311** when the body part **210** is seated on the seating portion **310** in an orientation different from the preset direction. In this case, the body part **210** is not seated on the seating portion **310** and a portion of the body part **210** is placed at a position spaced apart from the seating portion **310**.

(43) As such, since the first body **211** is configured such that it has an asymmetrical shape and the orientation determination portion **211a** is engaged with the engaging portion **311**, the body part **210** can be prevented from being seated on the seating part **310** at a position other than the correct

position. In addition, the user can immediately recognize whether the body part **210** is seated in an orientation different from the preset orientation.

(44) In addition, a through-hole **212a** may be formed in the second body **212**. The through-hole **212a** may be formed through the second body **212**, and the water pipe **220** may extend from the inner space between the first body **211** and the second body **212** to the outside through the through-hole **212a**. For example, a plurality, of through-holes **212a** may be provided, and the plurality of through-holes **212a** may be formed on a same surface of the second body **212**.

(45) The hook **213** may prevent the separation, preventing member **400** from rotating beyond a predetermined range. The hook **213** may be engaged with the separation preventing member **400** and may be formed to protrude from an upper surface of the first body **211**. For example, the hook **213** may be formed such that a side portion is partially opened so that the separation preventing member **400** can be inserted. In addition, the hook **213** may be located on the rotation path of the separation preventing member **400** when the body part **210** is seated on the seating portion **310**.

(46) The support jaw **214** may support a plurality of water pipes **220**. The support jaw **214** may protrude upward from the second body **212**. In addition, a groove, which is a portion where the water pipe **220** is supported, may be formed in the support jaw **214**, and the groove may be formed to correspond to the shape of the water pipe **220**.

(47) Referring to FIGS. 5 and 6, the water pipe **220** may provide a flow space for water to flow. A plurality of water pipes **220** may be provided, and the plurality of water pipes **220** may provide flow spaces through which purified water or cold water flows. In addition, the plurality of water pipes **220** may include a first purified water pipe **221**, a second purified water pipe **222**, and a cold water pipe **223**, and at least a portion of the plurality of water pipes **220** may be disposed in an inner space of the body part **210**. The first purified water pipe **221**, the second purified water pipe **222**, and the cold water pipe **223** may be configured not to communicate with each other within the body part **210**. In other words, in the body part **210**, the purified, water flowing through the first purified water pipe **221**, the purified water flowing through the second purified water pipe **222**, and the cold water flowing through the cold water pipe **223** are not mixed with each other, and may flow along the respective flow paths. In addition, the first purified water pipe **221**, the second purified water pipe **222**, and the cold water pipe **223** may have different shapes.

(48) As such, since the first purified water pipe **221**, the second purified water purification pipe **222**, and the cold water pipe **223** have different shapes, the user can assemble the first purified water pipe **221**, the second purified, water pipe **222**, and the cold water pipe **223** in place without confusion. That is, when assembling the flow path module **200**, incorrect assembly of the first purified water pipe **221**, the second purified water pipe **222**, and the cold water pipe **223** can be prevented.

(49) Meanwhile, in the present specification, the water pipe **220** may be understood as a different configuration from water connectors **630**, **640**, and **650**. In other words, the water pipe **220** provides a flow space for purified water and cold water to flow, and may be distinguished from the water connectors **630**, **640**, and **650** that connect some of the plurality of water pipes **220**. In addition, the water pipe **220** can be distinguished from a valve that opens and closes a passage. Accordingly, the flow path module **200** includes the plurality of water pipes **220**, but does not include the plurality of water connectors **630**, **640**, and **650** and a feed valve **660**.

(50) The first purified water pipe **221** may provide a passage through which purified water flows. In addition, purified water filtered by the filter **500** may be introduced into the first purified water pipe **221**, and the first purified water pipe **221** may guide the introduced purified water to the feed valve **660** to be described later. The first purified water pipe **221** may include a first purified water inlet part **221a**, a first purified water outlet part **221b**, and a first purified water passage **221c**.

(51) Referring to FIGS. 6 and 12, the first purified water inlet part **221a** is a portion of the first purified water pipe **221** through which purified water is introduced, and may be provided on one side of the first purified water passage **221c**. The first purified water inlet part **221a** may be

selectively connected to a first purified water inlet connector **631** to be described later. For example, the first purified water inlet part **221a** may have a predetermined rigidity so that its shape does not change when engaged with a first purified water inlet connector port **631a** to be described later. In, addition, a first purified water inlet **221a-1** for introducing purified water may be formed at one end of the first purified water inlet part **221a**. The first purified water inlet **221a-1** may communicate with the first purified water inlet connector port **631a**.

(52) The first, purified water outlet part **221b** is a portion of the first purified water pipe **221** through which purified water is discharged, and may be provided on the other side of the first purified water passage **221c**. The first purified water outlet part **221b** may be selectively connected to a first purified water outlet connector **632** to be described later. For example, the first purified water outlet part **221b** may have a predetermined rigidity so that its shape does not change when engaged with a first purified water outlet connector port **632a** to be described later. In addition, a first purified water outlet **221b-1** through which purified water is discharged may be formed at one end of the first purified water outlet part **221b**. The first purified water outlet **221b-1** may communicate with the first purified water outlet connector port **632a**.

(53) The first purified water passage **221c** may provide a passage through which purified water flows. The first purified water passage **221c** may be provided such that one side thereof communicates with the first purified water inlet part **221a** and the other side thereof communicates with the first purified water outlet part **221b**. In addition, the first purified water passage **221c** may be extended in a different direction from at least one of a second purified water passage **222c** and a cold water passage **223c**.

(54) In this way, the purified water introduced into the first purified water inlet part **221a** may flow along the first purified water passage **221c** to be discharged through the first purified water outlet part **221b**. In addition, the purified water discharged through the first purified water outlet part **221b** may be divided in the tubing assembly **600** to be discharged to the outside or to flow into the second purified water pipe **222**.

(55) The second purified water pipe **222** may provide a passage for purified water flows. For example, the second purified water pipe **222** may guide purified water to the cooler **700**. In addition, in the second purified water pipe **222**, the purified water discharged from the first purified water pipe **221** to the tubing assembly **600** may flow, and the purified water discharged from the second purified water pipe **222** may flow to the cooler **700**. The second purified water pipe **222** may include a second purified water inlet part **222a**, a second purified water outlet **222b**, and a second purified water passage **222c**.

(56) The second purified water inlet part **222a** is a portion of the second water pipe **222** into which purified water is introduced, and may, be provided on one side of the second purified water passage **222c**. The second purified water inlet part **222a** may be selectively connected to a second purified water inlet connector **641** to be described later. For example, the second purified water inlet part **222a** may have a predetermined rigidity so that its shape does not change when engaged with a second purified water inlet connector port **641a** to be described later. In addition, a second purified water inlet **222a-1** for introducing purified water may be formed at one end of the second purified water inlet part **222a**. The second purified water inlet **222a-1** may communicate with the second purified water connector port **641a**.

(57) The second purified water outlet part **222b** is a portion of the second purified water pipe **222** through which purified water is discharged, and may be provided on the other side of the second purified water passage **222c**. The second purified water outlet part **222b** may be selectively connected to a second purified water outlet connector **642** to be described later. For example, the second purified water outlet part **222b** may have a predetermined rigidity so that its shape does not change when engaged, with a second purified water outlet connector port **642a** to be described later. In addition, a second purified water outlet **222b-1** through which purified water is discharged may be formed at one end of the second purified water outlet part **222b**. The second purified water

outlet **222b-1** may communicate with the second purified water outlet connector port **642a**.

(58) The second purified water passage **222c** may provide a passage through which purified water flows. The second purified water passage **222c** may be provided such that one side thereof communicates with the second purified water inlet part **222a** and the other side thereof communicates with the second purified water outlet part **222b**. In addition, the second purified water passage **222c** may be extended in a different direction from at least one of the first purified water passage **221c** and the cold water passage **223c**.

(59) In this way, the purified water introduced into the second purified water inlet part **222a** may flow along the second purified water passage **222c** to be discharged through the second purified water outlet part **222b**. In addition, the purified water discharged through the second purified water outlet part **222b** may flow toward the cooler **700**.

(60) The cold water pipe **223** may provide a passage through which cold water flows. For example, the cold water pipe **223** may guide cold water passing through the cooler **700** to an outlet part **670** to be described later. The cold water pipe **223** may include a cold water inlet part **223a**, a cold water outlet part **223b**, and a cold water passage **223c**.

(61) The cold water inlet part **223a** is a portion of the cold water pipe **223** into which cold water is introduced, and may be provided on one side of the cold water passage **223c**. The cold water inlet part **223a** may be selectively connected to a cold water inlet connector **651** to be described later. For example, the cold water inlet part **223a** may have a predetermined rigidity so that its shape does not change when engaged with a cold water inlet connector port **651a** to be described later. In addition, a cold water inlet **223a-1** for introducing cold water may be formed at one end of the cold water inlet part **223a**. The cold water inlet **223a-1** may communicate with the cold water inlet connector port **651a**.

(62) The cold water outlet part **223b** is a portion of the cold water pipe **223** through which cold water is discharged, and may be provided on the other side of the cold water passage **223c**. The cold water outlet part **223b** may be selectively connected to a cold water outlet connector **652** to be described later. For example, the cold water outlet part **223b** may have a predetermined rigidity so that its shape does not change when engaged with a cold water outlet connector port **652a** to be described later. In addition, a cold water outlet **223b-1** through which cold water is discharged may be formed at one end of the cold water outlet part **223b**. The cold water outlet **223b-1** may communicate with the cold water outlet connector port **652a**.

(63) The cold water passage **223c** may provide a passage through which cold water flows. The cold water passage **223c** may be provided such that one side thereof communicates with the cold water inlet part **223a** and the other side thereof communicates with the cold water outlet part **223b**. In addition, the cold water passage **223c** may be extended in a different direction from at least one of the first purified water passage part **221c** and the second purified water passage **222c**.

(64) In this way, the cold water introduced into the cold water inlet part **223a** may flow along the cold water passage **223c** to be discharged through the cold water outlet part **223b**. In addition, the cold water discharged through the cold water outlet part **223b** may be discharged to the outside through the outlet part **670** and the discharge port **112** sequentially.

(65) Meanwhile, in the present specification, the first purified water inlet part **221a**, the second purified water inlet part **222a**, and the cold water inlet part **223a** may be referred to as a plurality of inlet parts **221a**, **222a**, and **223a**, and the first purified water outlet part **221b**, the second purified water outlet part **222b**, and the cold water outlet part **223b** may be referred to as a plurality of outlet parts **221b**, **222b**, and **223b**. In addition, the first purified water inlet **221a-1**, the second purified water inlet **222a-1**, and the cold water inlet **223a-1** may be referred to as a plurality of inlets **221a-1**, **222a-1**, and **223a-1**. The first purified water outlet **221b-1**, the second purified water outlet **222b-1**, and the cold water outlet **223b-1** may be referred to as a plurality of outlets **221b-1**, **222b-1**, and **223b-1**.

(66) The plurality of inlet parts **221a**, **222a**, and **223a** and the plurality of outlet parts **221b**, **222b**,

and **223b** may extend from the inner space of the body part **210** through the plurality of through-holes **212a** to the outside of the body part **210**. For example, the plurality of inlet parts **221a**, **222a**, and **223a** and the plurality of outlet parts **221b**, **222b**, and **223b** may extend in one direction, that is, downward of the water purifier **1**. In this case, the plurality of inlet parts **221a**, **222a**, and **223a** and the plurality of outlet parts **221b**, **222b**, and **223b** extend in the same direction, but may also include extensions in one or more directions. For example, the plurality of inlet parts **221a**, **222a**, and **223a** and the plurality of outlet parts **221b**, **222b**, and **223b** may extend in the order of downward, sideward, and downward. In addition, when the flow path module **200** is seated on the seating part **310**, the plurality of inlet parts **221a**, **222a**, and **223a** and the plurality of outlet parts **221b**, **222b**, and **223b** may pass through bracket holes **320** to be engaged with a plurality of connectors **631a**, **632a**, **641a**, **642a**, **651a**, and **652a** of the tubing assembly **600**.

(67) In addition, the plurality of inlets **221a-1**, **222a-1**, and **223a-1** and the plurality of outlets **221b-1**, **222b-1**, and **223b-1** may be exposed to the outside of the body part **210**. For example, the plurality of inlets **221a-1**, **222a-1**, and **223a-1** and the plurality of outlets **221b-1**, **222b-1**, and **223b-1** may open in the same direction, that is, downward. In addition, at least one of the plurality of inlets **221a-1**, **222a-1**, and **223a-1** and the plurality of outlets **221b-1**, **222b-1**, and **223b-1** may be configured to have a different size from another one. For example, the first purified water inlet **221a-1** may have a larger diameter than the first purified water outlet **221b-1**. Due to this, the user can determine that the one having a larger diameter is the first purified water inlet **221a-1**, and determine the installation direction of the flow path module **200** without confusing the directions of the first purified water inlet **221a-1** and the first purified water outlet **221b-1**. Moreover, the flow path module **200** can be prevented from being installed in an orientation different from the preset orientation.

(68) Referring back to FIG. 3, the flow path module **200** may be seated on the seating portion **310** of the bracket **300**, which will be described later, and connected to the tubing assembly **600** when the flow path module **200** is seated in place. In this case, the water pipe **220** of the flow path module **200** is connected to the tubing assembly **600** through a bracket hole **320** to be described later. Here, the correct position of the flow path module **200** means a position where the flow path module **200** is placed in the preset orientation and is seated to match the seating portion **310**. Therefore, when the flow path module **200** is not seated in the correct position, that is, when the flow path module **200** is placed in an orientation different from the preset orientation or does not match the seating portion **310**, the flow path module **200** interferes with the bracket **300**. In this case, the flow path module **200** is not connected to the tubing assembly **600**.

(69) As described above, the flow path module **200** is configured to communicate with the tubing assembly **600** when the flow path module **200** is seated in the correct position, so that the user can easily connect the flow path module **200** and the tubing assembly **600**. In other words, when the user mounts the flow path module **200** in the correct position on the bracket **300**, the flow path module **200** and the tubing assembly **600** can be connected without separate connection with another component.

(70) In addition, when the flow path module **200** is seated in the correct position, the flow path module **200** may be placed on the upper side of the tubing assembly **600**. In other words, when viewed from above, at least a portion of the flow path module **200** may overlap with the tubing assembly **600**. In addition, when viewed from above, the flow path module **200** is disposed between the filter **500** and the discharge port **112**, but may be disposed so as not to overlap with the filter **500**. In this case, the arrangement in which the flow path module **200** is placed between the filter **500** and the discharge port **112** means that a central portion of the flow path module **200** is placed between the filter **500** and the discharge port **112** as well as that one end and the other end of the flow path module **200** are placed between the filter **500** and the discharge port **112**. In addition, when the flow path module **200** is seated in the correct position, the flow path module **200** may be placed higher than a temperature control unit. In this specification, it may be understood that the

temperature control unit includes the cooler **700**, the heater **800**, and the cold water flow part **900**.
(71) Meanwhile, referring to FIG. 7, the flow path module **200** seated on the seating portion **310** can be separated from the bracket **300**. Further, when the flow path module **200** is separated from the bracket **300**, the water pipe **220** of the flow path module **200** is separated from the tubing assembly **600**.

(72) As such, the user can separate the water pipe **220** from the tubing assembly **600** by separating the flow path module **200** from the bracket **300**, and can easily replace the water pipe **220**. In addition, the flow path module **200** is configured in a manner that the plurality of water pipes **220** are integrated in the body part **210**, so that the user can replace the plurality of water pipes **220** in one operation without separating the plurality of water pipes **220** from each other. In other words, since the plurality of water pipes **220** are provided as one module, the replacement of the plurality of water pipes **220** can be performed with easier.

(73) Meanwhile, purified water and cold water may flow through the plurality of water pipes **220** described above. In addition, a pipe through which hot water flows in the water purifier **1** may not be provided within the flow path module **200** but may be provided separately from the flow path module **200**. This is to prevent the user from being injured by hot water in the process of replacing the flow path module **200** since the user can easily replace the flow path module **200**. Accordingly, the pipe through which hot water flows is separately disposed inside the water purifier **1**, and the user can replace the flow path module **200** without risk of injury due to hot water.

(74) Referring to FIGS. 7 and 8, the bracket **300** may support the flow path module **200** and may provide a portion where the flow path module **200** is seated. The bracket **300** may be supported on the main frame **110** and may be disposed on the upper side of the tubing assembly **600**. In addition, a seating portion **310** and bracket holes **320** may be formed in the bracket **300**.

(75) The seating portion **310** may provide a portion where the body part **210** of the flow path module **200** is seated. For example, the seating portion **310** may be a recess depressed downward from the bracket **300**. In addition, the seating portion **310** may be formed to correspond to the shape of the body part **210**. As a more detailed example, the seating portion **310** may be formed to surround at least a portion of a lower surface and a side surface of the body part **210** when the body part **210** is seated on the seating portion **310**. The seating portion **310** may include the engaging portion **311**.

(76) The engaging portion **311** may be formed in the bracket **300** so that the body part **31** is seated in the preset orientation when the body part **311** is seated on the seating portion **310**. The engaging portion **311** may be provided to be engaged with the orientation determination portion **211a** of the body part **210**, and may be formed to correspond to the shape of the orientation determination portion **211a** as an example.

(77) The bracket hole **320** may be formed in the bracket **300** so that the water pipe **220** of the flow path module **200** penetrates therethrough. A plurality of bracket holes **320** may be provided, and the plurality, of bracket holes **320** may be formed to correspond to the positions of the plurality of water connectors **630**, **640**, and **650**. In addition, the plurality of bracket holes **320** may be formed to correspond to the position of the water pipe **220** when the flow path module **200** is seated to the seating portion **310**.

(78) Meanwhile, the plurality of water pipes **220** may penetrate through the plurality of bracket holes **320**, respectively. For example, when the flow path module **200** is seated in the correct position on the seating portion **310**, the plurality of water pipes **220** penetrate through the plurality of through-holes **212a** to be connected with the tubing assembly **600**. As another example, when the flow path module **200** is not seated in the correct position on the seating portion **310**, the plurality of water pipes **220** interferes with the bracket **300** without penetrating through the through-hole **212a**.

(79) Referring to FIG. 9, the separation preventing member **400** can prevent the flow path module **200** seated in the correct position on the seating portion **310** from being separated from the bracket

300. For example, the flow path module **200** seated in the correct position is connected to the tubing assembly **600**, and water may flow between the flow path module **200** and the tubing assembly **600**. As such, when the flow path module **200** is separated from the seating portion **310** while the water is flowing between the flow path module **200** and the tubing assembly **600**, the water leaks between the flow path module **200** and the tubing assembly **600**. Accordingly, the separation preventing member **400** may prevent the flow path module **200** from being separated from the seating portion **310** so that the connection between the flow path module **200** and the tubing assembly **600** is maintained.

(80) The separation preventing member **400** may be configured such that one end thereof is supported by the bracket **300** and the other end thereof selectively interferes with the upper side of the flow path module **200** seated in the correct position. For example, one end of the separation preventing member **400** may be rotatably supported by the bracket **300**, and the other end thereof is rotated to the upper side of the body part **210** seated in the correct position, so that the separation preventing member **400** can prevent the body part **210** from being separated from the seating portion **310**. As a more detailed example, the other end of the separation preventing member **400** may be formed to be inserted in the hook **213** of the body part **210**. Accordingly, the separation preventing member **400** may be engaged with the hook **213** to prevent the body part **210** from moving upward.

(81) Meanwhile, when the separation preventing member **400** is placed on the upper side of the flow path module **200** to prevent the flow path module **200** from being separated, the cover frame **120** may be allowed to be placed in the cover position. For example, when the separation preventing member **400** is engaged with the hook **213** or is placed on the upper side of the flow path module **200** (see the separation preventing member **400** shown in the solid line of FIG. 9), the cover frame **120** can be placed in the cover position. In addition, when the other end of the separation preventing member **400** is not placed on the upper side of the flow path module **200** and the flow path module **200** is allowed to be separated from the seating portion **310** (see the separation preventing member **400** shown in the dotted line of FIG. 9), the separation preventing member **400** may interfere with the cover frame **120** so that the cover frame **120** could not be placed in the cover position. For example, when the separation preventing member **400** is rotated and the flow path module **200** can be separated from the seating portion **310**, the cover frame **120** is caught by the separation preventing member **400** without being placed in the cover position.

(82) As described above, when the flow path module **200** is in a separable state from the bracket **300**, the separation preventing member **400** can allow the user to recognize that the flow path module **200** is in the separable state by preventing the cover frame **120** from being placed in the cover position. In this way, the user can check once again whether the separation preventing member **400** is not engaged with the flow path module **200**.

(83) In addition, the separation preventing member **400** can maintain the connection between the flow path module **200** and the tubing assembly **600** by preventing the flow path module **200** seated in the correct position from being separated. Accordingly, it is possible to prevent water from leaking between the flow path module **200** and the tubing assembly **600** connected to each other.

(84) Meanwhile, the water purifier **1** may further include a rotary actuator (not shown). The rotary actuator may be operated to rotate the separation preventing member **400** in one direction. For example, when the flow path module **200** is seated in the correct position on the bracket **300**, the rotary actuator may rotate the separation preventing member **400** to the upper side of the flow path module **200** to prevent the flow path module **200** from being separated from the bracket **300**. In addition, when the flow path module **200** needs to be replaced, the rotary actuator may rotate the separation preventing member **400** to allow the flow path module **200** to be separated from the bracket **300**. The operation of the rotary actuator may be controlled by the circuit board **1100**.

(85) The filter **500** may filter raw water introduced into the water purifier **1** to be purified water. Raw water passing through the NOS valve **1000** to be described later may flow into the filter **500**,

and purified water filtered by the filter **500** may flow into the first purified water, pipe **221** of the flow path module **200**. In addition, one or more filters **500** may be provided, and may be provided to the main frame **110** to be replaceable. For example, one or more filters **500** may be disposed on the rear side of the water purifier **1**.

(86) Referring to FIGS. **10** to **13**, the tubing assembly **600** may connect one or more of the discharge port **112**, the filter **500**, the cooler **700**, and the cold water flow part **900** to the flow path module **200**. For example, purified water filtered by the filter **500** may flow into the flow path module **200** through the tubing assembly **600**. As another example, cold water cooled in the cold water flow part **900** may flow into the flow path module **200** through the tubing assembly **600**. In addition, the tubing assembly **600** may connect some of the plurality of water pipes **220** of the flow path module **200** to each other. For example, in the tubing assembly **600**, purified water received from the first purified water pipe **221** may flow into the second purified water pipe **222**.

(87) As such, the tubing assembly **600** may connect the flow path module **200** to other components (e.g., the cold water flow part **900**). In addition, the tubing assembly **600** may connect some of the plurality of water pipes **220** of the flow path module **200**. In this way, even when the flow path module **200** is selectively connected to the tubing assembly **600**, the flow path module **200** may be connected to other components (e.g. the discharge port **112**) only by connecting the tubing assembly **600** and the flow path module **200**. In addition, since the flow path module **200** does not have to be directly connected to the discharge port **112**, the filter **500**, the cooler **700**, and the cold water flow part **900**, the plurality of water pipes **220** can be integrated and the size of the flow path module **200** can be miniaturized.

(88) In addition, the tubing assembly **600** may provide a passage through which water flows. For example, one or more of raw water, purified water, cold water, and hot water may flow through the tubing assembly **600**. The tubing assembly **600** may be disposed below the bracket **300** and may be selectively connected to the flow path module **200** seated on the bracket **300**. In addition, when connected to the flow path module **200**, the tubing assembly **600** may communicate with the plurality of water pipes **220**. In this case, the tubing assembly **600** may form a water flow path together with the flow path module **200**. For example, purified water and cold water may flow along the water flow path between the tubing assembly **600** and the flow path module **200** and alternately flow between the tubing assembly **600** and the flow path module **200**.

(89) In addition, when the tubing assembly **600** is connected to the flow path module **200**, at least a portion of the plurality of water pipes **220** can be selectively opened and closed. For example, the tubing assembly **600** may block the first purified water pipe **221**. In this case, purified water cannot flow from the first purified water pipe **221** to the first purified water outlet connector **632**.

(90) The tubing assembly **600** may include a support body **610**, a hot water valve **620**, a first purified water connector **630**, a second purified water connector **640**, a cold water connector **650**, a feed valve **660**, an outlet part **670**, and a sealing member **680**.

(91) The support body **610** may support at least a portion of the hot water part **620**, the first purified water connector **630**, the second purified water connector **640**, and the cold water connector **650**. In addition, the support **610** may support the NOS valve **1000** disposed adjacent thereto. The support **610** may be provided with a pipe to guide cold water cooled in the cooler **700** to the cold water inlet connector **651**.

(92) The hot water valve **620** may be operated to control the flow rate of purified water flowing toward the heater **800** or the flow rate of hot water discharged from the heater **800**. The hot water valve **620** may guide purified water to the heater **800** and guide hot water heated by, the heater **800** to the outlet part **660**. In addition, the hot water valve **620** may include a first hot water valve **621** which controls the flow rate of purified water flowing into the heater **800** and a second hot water valve **622** which controls the flow rate of hot water discharged from the heater **800**. The operations of the first hot water valve **621** and the second hot water valve **622** may be controlled by the circuit board **1100**.

(93) Referring back to FIG. 12, the first purified water connector **630** may provide a passage through which purified water flows. In addition, the first purified water connector **630** may be, selectively connected to the first purified water pipe **221**. The first purified water connector **630** may include a first purified water inlet connector **631** and a first purified water outlet connector **632**.

(94) The first purified water inlet connector **631** may provide a passage through which purified water flows. In addition, the first purified water inlet connector **631** may introduce purified water passing through the filter **500** and guide the introduced purified water to the first purified water pipe **221**. The first purified water inlet connector **631** may be selectively engaged with the first purified water inlet, part **221a** of the first purified water pipe **221**. In addition, a first purified water inlet connector port **631a** may be formed in the first purified water inlet connector **631**. The first purified water inlet connector port **631a** may communicate with the first purified water inlet **221a-1**.

(95) The first purified water outlet connector **632** may provide a passage through which purified water flows. In addition, the first, purified water outlet connector **632** may introduce purified water passing through the first purified water pipe **221** and guide the introduced purified water to the feed valve **660**. The first purified water outlet connector **632** may be selectively engaged with the first purified water outlet part **221b** of the first purified water pipe **221**. Moreover, a first purified water outlet connector port **632a** may be formed in the first purified water outlet connector **632**. The first purified water outlet connector port **632a** may communicate with the first purified water outlet **221b-1**.

(96) The second purified water inlet connector **641** may provide a passage through which purified water flows. In addition, the second purified water inlet connector **641** may introduce purified water passing through the feed valve **660** and guide the introduced purified water to the second purified water pipe **222**. The second purified water inlet connector **641** may be selectively engaged with the second purified water inlet part **222a** of the second purified water pipe **222**. Further, a second purified water inlet connector port **641a** may be formed in the second purified water inlet connector **641**. The second purified water inlet connector port **641a** may communicate with the second purified water inlet **222a-1**.

(97) The second purified water outlet connector **642** may provide a passage through which purified water flows. In addition, the second purified water outlet connector **642** may introduce purified water passing through the second purified water pipe **222** and guide the introduced purified water to the cooler **700**. The second purified water outlet connector **642** may be selectively engaged with the second purified water outlet part **222b** of the second purified water pipe **222**. Further, a second purified water outlet connector port **642a** may be formed in the second purified water outlet connector **642**. The second purified water outlet connector port **642a** may communicate with the second purified water outlet **222b-1**.

(98) The cold water inlet connector **651** may provide a passage through which cold water flows. In addition, the cold water inlet connector **651** may introduce cold water passing through the cooler **700** and guide the introduced cold water to the cold water pipe **223**. The cold water inlet connector **651** may be selectively engaged with the cold water inlet part **223a** of the cold water pipe **223**. Moreover, a cold water inlet connector port **651a** may be formed in the cold water inlet connector **651**. The cold water inlet connector port **651a** may communicate with the cold water inlet **223a-1**.

(99) The cold water outlet connector **652** may provide a passage through which cold outlet connector **652** may introduce cold water passing through the cold water pipe **223** and guide the introduced cold water to the discharge unit **660**. The cold water outlet connector **652** may be selectively engaged with the cold water outlet part **223b** of the cold water pipe **223**. Further, a cold water outlet connector port **652a** may be formed in the cold water outlet connector **652**. The cold water outlet connector port **652a** may communicate with the cold water outlet **223b-1**.

(100) Meanwhile, in the present specification, the first purified water connector **630** the second

purified water connector **640**, and the cold water connector **650** may be referred to as a plurality of water connectors **630**, **640**, and **650**. In addition, the first purified water inlet connector **631a**, the first purified water outlet connector **632a**, the second purified water inlet connector **641a**, the second purified water outlet connector **642a**, the cold water inlet connector **651a** and the cold water outlet connector **652a** may be referred to as a plurality of connectors **631a**, **632a**, **641a**, **642a**, **651a**, and **652a**.

(101) The plurality of connectors **631a**, **632a**, **641a**, **642a**, **651a**, and **652a** may be engaged with the plurality of inlet parts **221a**, **222a**, and **223a**, or the plurality of outlet parts **221b**, **222b**, and **223b**. In addition, the plurality of connectors **631a**, **632a**, **641a**, **642a**, **651a**, and **652a** may have sizes corresponding to the plurality of inlets **221a-1**, **222a-1**, and **223a-1** and the plurality of outlets **221b-1**, **222b-1**, and **223b-1** respectively. For example, the plurality of connectors **631a**, **632a**, **641a**, **642a**, **651a**, **652a** may open upward. In addition, since the plurality of connectors **631a**, **632a**, **641a**, **642a**, **651a**, **652a** are, opened upward, the plurality of connectors **631a**, **632a**, **641a**, **642a**, **651a**, and **652a** may communicate with the plurality of inlets **221a-1**, **222a-1**, and **223a-1** or the plurality of outlets **221b-1**, **222b-1**, and **223b-1** which are open downward.

(102) As such, the plurality of connectors **631a**, **632a**, **641a**, **642a**, **651a**, and **652a** are open upward, so that the plurality of inlet parts **221a**, **222a**, and **223a** or the plurality of outlet parts **221b**, **222b**, and **223b** extending downward can be easily inserted into the plurality of connectors **631a**, **632a**, **641a**, **642a**, **651a**, and **652a**. In other words, the flow path module **200** can be easily connected to the tubing assembly **600** by moving downward.

(103) The feed valve **660** may be operated to control the flow rate of purified water discharged from the first purified water pipe **221**. In addition, the feed valve **660** may flow purified water to the outlet part **670** or the second purified water pipe **222**. For example, purified water discharged from the first purified water pipe **221** may flow into the feed valve **660** to be divided. Further, some of the purified water divided by the feed valve **660** may flow to the outlet part **670** and the other purified water may flow to the second purified water pipe **222**. The feed valve **660** may be connected to the first purified water outlet connector **632** and the second purified water inlet connector **641**.

(104) Meanwhile, the feed valve **660** may block one end of the second purified water inlet connector **641** when the flow path module **200** is separated from the tubing assembly **600**. As a result, the purified water discharged from the first purified water pipe **221** does not flow to the second purified water pipe **222**. In addition, even while the flow path module **200** is connected to the tubing assembly **600**, when the separation preventing member **400** is placed in a position at which the separation of the flow path module **200** is allowed, the feed valve **660** may block one end of the second purified water inlet connector **641**. The operation of the feed valve **660** may be controlled by the circuit board **1100**.

(105) As such, even while the flow path module **200** is connected to the tubing assembly **600**, when the flow path module **200** can be separated from the bracket **300**, the feed valve **660** blocks the flow of purified water so that water leakage between the flow path module **200** and the tubing assembly **600** can be prevented.

(106) The outlet part **670** may discharge any one of purified water, cold water, and hot water through the discharge port **112**. In addition, the outlet part **670** may be connected to the hot water valve **620**, the cold water outlet connector port **652**, and the feed valve **660**. For example, the outlet part **670** may guide hot water introduced from the hot water valve **620** to the discharge port **112**, and may guide cold water introduced from the cold water outlet connector port **652** to the discharge port **112**. Moreover, the outlet part **670** may guide the purified water introduced from the feed valve **660** to the discharge port **112**.

(107) Referring to FIG. **14**, the sealing member **680** can prevent water from leaking between the first purified water inlet part **221a** and the first purified water inlet connector **631a** when the first purified water inlet part **221a** is inserted into the first purified water inlet connector **631a**. For

example, the sealing member **680** may be an O-ring inserted between the first purified water inlet part **221a** and the first purified water inlet connector **631a**. Meanwhile, in FIG. **14**, it has been described that the sealing member **680** is provided between the first purified water inlet part **221a** and the first purified water inlet connector **631a**, but this is only an example and a plurality of sealing members **680** may be provided. Accordingly, the plurality of sealing members **680** can seal between the plurality of inlet parts **221a**, **222a**, and **223a** or the plurality of outlet parts **221b**, **222b**, and **223b** and the plurality of connectors **631a**, **632a**, **641a**, **642a**, **651a**, and **652a**.

(108) The cooler **700** may provide cold water by cooling purified water to a predetermined temperature or less. The cooler **700** may be disposed above the cold water flow part **900**, and the cold water discharged from the cooler **700** may flow to the cold water flow part **900**.

(109) The heater **800** may provide hot water by heating purified water to a predetermined temperature or higher. The purified water may flow from the first hot water valve **621** to flow into the heater **800**, and the hot water provided from the heater **800** may flow into the second hot water valve **622**.

(110) The cold water flow part **900** may provide a space through which cold water supplied from the cooler **700** flows. In addition, the cold water flow part **900** may, provide a space for storing the cold water cooled by the cooler **700**. For example, the cold water flow part **900** may be configured in the form of a water tank to provide a space in which cold water flows and a space in which cold water is stored. In addition, as another example, the cold water flow part **900** may be configured in the form of a thin pipe or a water tank with partition walls installed therein to provide a space in which purified water flows as soon as it is cooled.

(111) The NOS valve **1000** may be operated to control the flow rate of raw water introduced from the outside. For example, the NOS valve **1000** may be a valve capable of opening and closing a passage through which raw water flows, and may control the flow rate of raw water by opening and closing the passage through which raw water flows. Driving of the NOS valve **1000** may be controlled by the circuit board **1100**. In addition, the NOS valve **1000** may guide raw water to the filter **500**. The NOS valve **1000** may be disposed adjacent to the tubing assembly **600**.

(112) The circuit board **1100** may control the operation of the tubing assembly **600**. For example, the circuit board **1100** may control the NOS valve **1000** to open the passage through which raw water flows. In addition, the circuit board **1100** may control the first hot water valve **621** to open a passage through which the purified water passing through the filter **500** flows, and control the second hot water valve **622** to open a passage through which hot water flows.

(113) As another example, the circuit board **1100** may control the feed valve **660** so that the purified water discharged from the first purified water pipe **221** flows to one or more of the outlet part **670** and the second purified water pipe **222**. In addition, the circuit board **1100** may control one or more of the NOS valve **1000** and the feed valve **660** so that no water flows when the flow path module **200** and the tubing assembly **600** are separated from each other. As a more specific example, the circuit board **1100** controls one or more of the NOS valve **1000** and the feed valve **660** so that no water flows when the flow path module **200** is not seated in the correct position, that is, when the plurality of water pipes **221**, **222**, and **223** are not connected to the plurality of water connectors **630**, **640**, and **650**. Here, the case where the flow module **200** is not seated in the correct position includes a case where any, one of the plurality of water pipes **221**, **222**, and **223** is not connected to the plurality of water connectors **630**, **640**, and **650**.

(114) As another example, the circuit board **1100** controls one or more of the NOS valve **1000** and the feed valve **660** so that no water flows when the separation preventing member **400** is placed in a position at which the separation of the flow path module **200** is allowed even while the flow path module **200** is seated in the correct position.

(115) Meanwhile, the circuit board **1100** may control the operation of the outlet part **670**. When a user's selection is input, the circuit board **1100** may control the outlet part **670** to discharge one of purified water, cold water, and hot water based on the user's selection. For example, when a user

inputs cold water discharge, the circuit board **1100** controls the outlet part **670** to discharge cold water.

(116) The circuit board **1100** may include a plurality of boards and a plurality of wires, and may be fixedly supported by the cover frame **120**. Accordingly, the circuit board **1100** may be separated from the bracket **300** together with the cover frame **120** when the cover frame **120** is separated from the bracket **300**.

(117) As such, the circuit board **1100** can be easily exposed to the outside by being separated together with the cover frame **120**. In addition, the maintenance of the circuit board **1100** can easily be performed since the circuit board **1100** is fixedly supported on the main frame **110** while being separated together with the cover frame **120**.

(118) The circuit board **1100** described above may be implemented by an arithmetic device including a microprocessor, a measurement device such as a sensor, and a memory, and since the implementation method thereof is obvious to those skilled in the art, further detailed descriptions are omitted.

(119) Hereinafter, referring to FIG. **13**, the flow of water inside the water purifier **1** will be described.

(120) Raw water supplied from the outside of the water purifier **1** passes through the NOS valve **1000** to flow to the filter **500**. Some of purified water filtered by the filter **500** flows to the hot water valve **620**, and the other part flows to the first purified water pipe **221** of the flow path module **200**. The purified water flowing into the hot water valve **620** is heated in the heater **800** and provided to the user as hot water through the outlet part **670** and the discharge port **112** sequentially.

(121) In addition, purified water flowing into the first purified water pipe **221** flows to the feed valve **660**. Some of the purified water flowing into the feed valve **660** is provided to the user as purified water through the outlet part **670** and the discharge port **112** sequentially.

(122) Further, the other part of the purified water flowing into the feed valve **660** flows into the cooler **700** through the second purified water pipe **222**. The purified water introduced into the cooler **700** is cooled and provided to the user as cold water through the cold water flow part **900**, the cold water pipe **223**, the outlet part **670**, and the discharge port **112** sequentially.

(123) Hereinafter, the operation of the water purifier **1** having the above configuration will be described.

(124) A user can use the water purifier **1** according to one embodiment of the present disclosure to filter water supplied from the outside. The water purifier **1** can provide purified water to the user by filtering raw water. In addition, the water purifier **1** can provide cold water or hot water to the user by cooling or heating the purified water according to the user's selection.

(125) Meanwhile, the plurality of water pipes **220** provided to allow water to flow in the water purifier **1** need to be replaced due to water stains when used for a long time. In this case, the user can separate the upper cover of the main frame **110** and separate the cover frame **120** from the bracket **300**. In addition, the cover frame **120** separated from the bracket **300** and placed in the open fixed position can be maintained in the open fixed position by, the fixture **121** being caught on the rib **111** of the main frame **110**. Then, the user rotates the separation preventing member **400** so that the flow path module **200** can be separated from the bracket **300**. As such, when the flow path module **200** is placed in a separable state, the user can separate the flow path module **200** from the bracket **300**.

(126) In addition, the user can replace the flow path module **200** with another flow path module **200** and mount it on the bracket **300**. In this case, the user can connect the flow path module **200** and the tubing assembly **600** by mounting the flow path module **200** to match the seating portion **310**. Moreover, when the user rotates the separation preventing member **400** to be engaged with the hook **213**, the connection between the flow path module **200** and the tubing assembly **600** can be maintained. Thereafter, the replacement of the flow path module **200** can be completed by moving

the cover frame **120** to the cover position.

(127) Although the embodiments of the present disclosure have been described as specific embodiments, these are merely examples. The present disclosure is not limited to the above, and should be construed as having the widest scope according to the technical idea disclosed herein. Those skilled in the art may combine/substitute the disclosed embodiments to implement a pattern of a shape not disclosed, but this also does not deviate from the scope of the present disclosure. In addition, those skilled in the art may easily change or modify the disclosed embodiments based on the present specification, and it is clear that such changes or modifications also fall within the scope of the present disclosure.

Claims

1. A water purifier comprising: a filter for filtering raw water to provide purified water; a discharge port through which the purified water is discharged to an outside; a plurality of water pipes providing a flow space for the purified water to flow; a flow path module including a body part supporting the plurality of water pipes; and a tubing assembly detachably connected to the plurality of water pipes, the tubing assembly serving to selectively open and close at least a portion of the plurality of water pipes when connected to the plurality of water pipes, wherein the tubing assembly has one side connected to the filter and the other side connected to the flow path module, and the flow path module receives the purified water filtered by the filter through the tubing assembly, wherein the flow path module is placed above the tubing assembly, and is disposed between the filter and the discharge port while overlapping at least a portion of the tubing assembly without overlapping the filter when viewed from above, wherein each of the plurality of water pipes includes a passage part through which the purified water flows, an inlet part provided on one side of the passage part through which the purified water flows in and including an inlet, and an outlet part provided on the other side of the passage part through which the purified water is discharged and including an outlet, and wherein the inlet and the outlet provided in each of the plurality of water pipes are exposed to the outside of the body part and opened downward.
2. The water purifier of claim 1, wherein the inlet part and the outlet part provided in each of the plurality of water pipes are extended downward.
3. The water purifier of claim 1, wherein the body part supports the passage part, and has a plurality of through holes, the inlet part and the outlet part protrude outward from the body through the plurality of through holes, and the plurality of through holes are formed on a same surface of the body part.
4. The water purifier of claim 1, wherein at least a portion of the passage parts of the plurality of water pipes extend in different directions, and each of the plurality of water pipes is configured such that the flow space does not communicate with each other in the body part.
5. The water purifier of claim 1, wherein the inlet and the outlet provided in at least one of the plurality of water pipes have different sizes from each other, and at least one of the plurality of water pipes has a different shape from another one thereof.
6. The water purifier of claim 1, wherein the tubing assembly includes a plurality of connectors which are selectively engaged with the inlet parts and the outlet parts of the plurality of water pipes, respectively, each of the inlet parts and the outlet parts of the plurality of water pipes has a predetermined rigidity so that a shape thereof does not change when engaged with the connector, the inlet and the outlet provided in at least one of the plurality of water pipes have different sizes from each other, and each of the plurality of connectors has a size corresponding to the inlet and the outlet provided in each of the plurality of water pipes.
7. The water purifier of claim 1, wherein an orientation determination portion having a protrusion or recess shape is provided on an outer surface of the body part so that the body part has an asymmetrical shape, and the orientation determination portion has a shape protruding or depressed

laterally from the outer surface of the body part.

8. The water purifier of claim 1, further comprising: a cooler for cooling the purified water to provide cold water; and a cold water flow part through which the cold water obtained by the cooler flows, wherein the flow path module is disposed above the cooler and the cold water flow part.
 9. The water purifier of claim 1, further comprising: a frame including a main frame and a cover frame, wherein the cover frame is configured such that the cover frame is placed in a cover position where the cover frame covers the flow path module or separated from the cover position so that the flow path module is exposed to the outside.
 10. The water purifier of claim 9, further comprising: a circuit board, for controlling operation of the water purifier, supported by the cover frame, wherein when the cover frame is separated from the cover position, the circuit board is separated from the cover position together with the cover frame.
 11. The water purifier of claim 9, further comprising: a bracket having a seating portion on which the body part is seated when the flow path module is connected to the tubing assembly, wherein the seating portion is a hole concavely formed in the bracket to surround at least a portion of a lower surface and at least a portion of a side surface of the flow path module, wherein when placed in the cover position, the cover frame is disposed above the bracket to cover an upper surface of the flow path module, wherein an orientation determination portion, having a protrusion or recess shape, for guiding a direction in which the flow path module is seated in the seating portion is provided on an outer surface of the body part, wherein the seating portion is provided with an engaging part having a shape corresponding to the orientation determination portion, and wherein the orientation determination portion engages with the engaging part when the flow path module is seated in a predetermined direction on the seating portion, and when the flow path module is seated in the seating portion in a direction different from the predetermined direction, the orientation determination portion does not engage with the engaging part and interferes with the bracket.
 12. The water purifier of claim 1, further comprising: a bracket having a seating portion on which the body part is seated when the flow path module is connected to the tubing assembly; and a separation preventing member for preventing the flow path module from being separated from the bracket when the flow path module is connected to the tubing assembly, wherein the separation preventing member is supported by the bracket and selectively interferes with an upper side of the body part of the flow path module to prevent separation of the flow path module.
 13. The water purifier of claim 12, further comprising: a cover frame that covers the flow path module when a position of the cover frame relative to the bracket is a cover position, wherein the separation preventing member allows the cover frame to be placed in the cover position when selectively interfering with the flow path module to prevent separation of the flow path module, and wherein the separation preventing member interferes with the cover frame to prevent the cover frame from being placed in the cover position when allowing the flow path module to be separated from the seating portion.
 14. The water purifier of claim 13, further comprising: a main frame that accommodates the filter and the tubing assembly, wherein the cover frame is placed in an open fixed position where the cover frame is engaged and fixed to the main frame in an inclined state with respect to the cover frame in the cover position, or the cover position.
 15. The water purifier of claim 13, wherein the body part is provided with a protruding hook, and wherein when engaged with the hook, the separation preventing member selectively interferes with the flow path module to prevent separation of the flow path module and allows the cover frame to be placed in the cover position.
-