US 20250259729A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2025/0259729 A1**

Gur et al. (43) **Pub. Date: Aug. 14, 2025**

(54) **HUMAN-ARTIFICIAL INTELLIGENCE INTERACTION FOR PHYSICAL THERAPY MEASUREMENTS**

(71) Applicants: **Amit Gur**, Zichron-Yaakov (IL); **Omer Achrack**, Jerusalem (IL); **Yael Yankelevsky**, Haifa (IL); **Ron Alfia**, Haifa (IL); **Alexandra Manevitch**, Jerusalem (IL); **Riki Sheinin**, Jerusalem (IL); **Mohr Wenger**, Gedera (IL); **Uzi Sarel**, Zichron-Yaakov (IL)

(72) Inventors: **Amit Gur**, Zichron-Yaakov (IL); **Omer Achrack**, Jerusalem (IL); **Yael Yankelevsky**, Haifa (IL); **Ron Alfia**, Haifa (IL); **Alexandra Manevitch**, Jerusalem (IL); **Riki Sheinin**, Jerusalem (IL); **Mohr Wenger**, Gedera (IL); **Uzi Sarel**, Zichron-Yaakov (IL)

(21) Appl. No.: **19/193,257**

(22) Filed: **Apr. 29, 2025**

Publication Classification

(51) **Int. Cl.**

G16H 20/30	(2018.01)
A61B 5/11	(2006.01)
G16H 40/67	(2018.01)

(52) **U.S. Cl.**

CPC ***G16H 20/30*** (2018.01); ***A61B 5/1128*** (2013.01); ***G16H 40/67*** (2018.01)

(57) **ABSTRACT**

Systems and methods for automatically analyzing movements to identify anomalies and incorrect actions. An artificial intelligence-based digital system is provided that can monitor exercises and automatically analyze movements to identify both anomalies and incorrect actions. The system includes a mobile device application that can serve as a user interface for the patient, a camera for streaming video of the patient performing the exercise in real-time, and an artificial intelligence-based system to analyze the patient's movements while performing the exercise and provide real time guidance and feedback to the patient. The system includes a video dataset including people performing a set a supported exercises. In some examples, the video dataset can be used to adjust checks of the artificial intelligence system for metric accuracy. The system can be used for physical therapy treatment tracking, ensuring patients are accurately performing exercises.

200




Deep Learning System
100
Interface Module
110
Human Activity
Detection Module
120
Training Module
130
Validation Module
140
Inference Module
150
Datastore
160

FIG. 1

200


CLINICIAN PORTAL 205
AI EXERCISE ANALYSIS 210
220
215
230
230
235
240

FIG. 2


300
310
CLOUD EXERCISE LIBRARY 315
DEEP-LEARNING 375
LOGIC DETERMINATIONS 380
CONFIGURATIONS 385
345
LIGHT CHECKS 320
INPUT VIDEO 305
PERSON DETECTION 325
PERSON OF INTEREST 330
SKELETON 335
2D-3D SKELETON 340
342
PRE-CHECKS 350
LIVE CHECKS 355
DEEP LEARNING CHECKS 360
OTHER FEATURES 365
METRICS REP COUNT 370
CLINICIAN PORTAL 390
PATIENT APPLICATION 395

FIG. 3


400
RECEIVE AN INPUT VIDEO FROM A USER
410
TRANSMIT EXERCISE INSTRUCTIONS INCLUDING A STARTING POSITION
420
PERSON IN VIDEO?
425
TRANSMIT INSTRUCTIONS FOR THE USER TO MOVE INTO THE CAMERA FIELD OF VIEW
430
PERSON IN CORRECT POSITION? 435
TRANSMIT INSTRUCTIONS FOR THE USER TO MOVE INTO THE STARTING POSITION
440
ANALYZING THE INPUT VIDEO STREAM TO DETERMINE PERFORMANCE ACCURACY OF THE EXERCISE
450
TRANSMITTING FEEDBACK TO THE PERSON BASED ON THE PERFORMANCE ACCURACY OF THE EXERCISE
460
MEASURING SELECTED PARAMETERS OF THE EXERCISE PERFORMANCE OVER MULTIPLE REPETITIONS OF THE EXERCISE
470
GENERATING MEASUREMENT RESULTS FOR TRANSMISSION TO A CLINICIAN
480

FIG. 4

500


Sets
STARTING POSITION
Left
Please turn and show left side of your body
Skip this exercise

FIG. 5A

530


Reps 3/10
Right
Knee Flexion
-10°
Please move right - relative to the camera
Skip this exercise

FIG. 5B

560



FIG. 5C


COMPUTING DEVICE
600
PROCESSING DEVICE
602
COMMUNICATION CHIP
612
MEMORY
604
BATTERY/POW6
614
DISPLAY DEVICE
606
GPS DEVICE
616
VIDEO OUTPUT DEVICE
608
VIDEO INPUT DEVICE
618
OTHER OUTPUT DEVICE
610
OTHER INPUT DEVICE
620
ANTENNA
622

FIG. 6

HUMAN-ARTIFICIAL INTELLIGENCE INTERACTION FOR PHYSICAL THERAPY MEASUREMENTS

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application is related to concurrently filed U.S. Application titled "Human Activity Analysis Based on Skeleton and Deep Learning Transformer", which is hereby incorporated by reference in its entirety.

TECHNICAL FIELD

[0002] This disclosure relates generally to object recognition, and in particular object recognition for movement analysis.

BACKGROUND

[0003] In Physical Therapy (PT) treatment, it is important to accurately identify when a patient performs an exercise incorrectly and provide corrective actions. Additionally, PT treatment plans are adjusted based on detected movement anomalies. The variety of exercises used by the Physical Therapy (PT) community is vast, ranging from 5,000 to 15,000 unique exercises. For each exercise, the number of potential incorrect movements or anomalies is also extensive and unpredictable. Furthermore, while performing their PT exercises, patients may also engage in many unrelated activities that are not part of the required exercise regimen. These factors present challenges to the development of automated systems for providing PT treatment.

BRIEF DESCRIPTION OF THE DRAWINGS

[0004] Embodiments will be readily understood by the following detailed description in conjunction with the accompanying drawings. To facilitate this description, like reference numerals designate like structural elements. Embodiments are illustrated by way of example, and not by way of limitation, in the figures of the accompanying drawings.

[0005] FIG. **1** illustrates a deep learning system, in accordance with various embodiments.

[0006] FIG. **2** illustrates an example overview of an exercise analysis system **200**, in accordance with various embodiments.

[0007] FIG. **3** illustrates an example of a pipeline for implementation of the AI-based exercise analysis module, in accordance with various embodiments.

[0008] FIG. **4** is a flowchart showing a method **400** of exercise analysis, in accordance with various embodiments.

[0009] FIGS. **5**A-**5**C illustrate examples of a user interface for an exercise analysis system, in accordance with various embodiments.

[0010] FIG. **6** is a block diagram of an example computing device, in accordance with various embodiments.

DETAILED DESCRIPTION

Overview

[0011] An artificial intelligence-based digital system is provided herein that can monitor PT exercises and automatically analyze movements to identify both anomalies and incorrect actions. The system includes a mobile device application that can serve as a user interface for the patient, a camera for streaming video of the patient performing the exercise in real-time, and an artificial intelligence-based system to analyze the patient's movements while performing the exercise and provide real time guidance and feedback to the patient. In some implementations, the system also includes a video dataset including people performing a set a supported exercises. In some examples, the video dataset can be used to adjust checks of the artificial intelligence system for metric accuracy.

[0012] In automated PT treatment tracking systems, and in particular in automated PT treatment tracking systems based on a single two-dimensional (2D) camera, measuring patient metrics across all possible human movements is very challenging. There are approximately 5,000 to 15,000 unique exercises that may be included in a PT treatment program, and the way a person performs each exercise in front of a camera can vary greatly. Additionally, in some examples, the patient may not even be performing the prescribed exercise, and may be engaging in a different activity. For effective development of an AI-based digital system to monitor PT activity, measurements collected when the patient is not performing the required exercise should disregarded, and focus should be on accurate measurement of the relevant metrics, such as repetition count and range of motion.

[0013] Many different issues that can arise while collecting measurements. For example, one potential issue is that the patient is performing an exercise in a way that is not well visible to the camera (e.g., with their back to the camera, too far from the camera, too close to the camera, partially obstructed by something in the scene, and/or partially obstructed by their own clothing). A second potential issue is that no person is detected in the scene (e.g., the patient leaves the area or the lighting conditions are poor). A third potential issue is that the patient performs the exercise in a plane that is harder to measure with a 2D camera (e.g., the person is standing facing the camera, in a frontal view, and moving their leg backward-standing sagittal to the camera would provide a better view of the movement). A fourth potential issue is that there is more than one person moving in the scene and it is difficult to identify the target patient. A fifth potential issue is that, for non-symmetric exercises, the patient performs the exercise with the incorrect body side or with the body side that is facing away from the camera, in a sagittal view. Another potential issue is that the patient is performing a different exercise altogether or not performing any exercise at all. Systems and methods are presented herein to use a deep learning system to guide the patient throughout the exercises and prevent or minimize the potential issues. If an issue does arise, the deep learning system can provide correction actions and/or instructions to the patient. Additionally, the deep learning system provides guidance and instructions that can enhance measurement accuracy for the system through corrective actions that can prevent and/or address issues. Providing real-time feedback improves treatment results by ensuring accurate performance of the exercise by the patient.

[0014] The guidance provided by the deep learning system can include pre-check feedback, in which guidance is provided before the patient begins the exercise. The guidance can include where to stand, how to stand, and how to start the exercise. The guidance can also include real-time feedback, in which guidance is provided while the patient is performing the exercise. Real-time feedback can be based on

identified conditions that are not optimal for performing measurements of the exercise. In some examples, the real-time feedback can include guidance to correct the exercise, correct the side performing the exercise, correct the location relative to the camera, and/or to remove an obstruction between the patient and the camera.

[0015] For purposes of explanation, specific numbers, materials, and configurations are set forth in order to provide a thorough understanding of the illustrative implementations. However, it will be apparent to one skilled in the art that the present disclosure may be practiced without the specific details or/and that the present disclosure may be practiced with only some of the described aspects. In other instances, well known features are omitted or simplified in order not to obscure the illustrative implementations.

[0016] Further, references are made to the accompanying drawings that form a part hereof, and in which is shown, by way of illustration, embodiments that may be practiced. It is to be understood that other embodiments may be utilized, and structural or logical changes may be made without departing from the scope of the present disclosure. Therefore, the following detailed description is not to be taken in a limiting sense.

[0017] Various operations may be described as multiple discrete actions or operations in turn, in a manner that is most helpful in understanding the claimed subject matter. However, the order of description should not be construed as to imply that these operations are necessarily order dependent. In particular, these operations may not be performed in the order of presentation. Operations described may be performed in a different order from the described embodiment. Various additional operations may be performed or described operations may be omitted in additional embodiments.

[0018] For the purposes of the present disclosure, the phrase "A and/or B" or the phrase "A or B" means (A), (B), or (A and B). For the purposes of the present disclosure, the phrase "A, B, and/or C" or the phrase "A, B, or C" means (A), (B), (C), (A and B), (A and C), (B and C), or (A, B, and C). The term "between," when used with reference to measurement ranges, is inclusive of the ends of the measurement ranges.

[0019] The description uses the phrases "in an embodiment" or "in embodiments," which may each refer to one or more of the same or different embodiments. The terms "comprising," "including," "having," and the like, as used with respect to embodiments of the present disclosure, are synonymous. The disclosure may use perspective-based descriptions such as "above," "below," "top," "bottom," and "side" to explain various features of the drawings, but these terms are simply for ease of discussion, and do not imply a desired or required orientation. The accompanying drawings are not necessarily drawn to scale. Unless otherwise specified, the use of the ordinal adjectives "first," "second," and "third," etc., to describe a common object, merely indicates that different instances of like objects are being referred to and are not intended to imply that the objects so described must be in a given sequence, either temporally, spatially, in ranking or in any other manner.

[0020] In the following detailed description, various aspects of the illustrative implementations will be described using terms commonly employed by those skilled in the art to convey the substance of their work to others skilled in the art.

[0021] The terms "substantially," "close," "approximately," "near," and "about," generally refer to being within +/−20% of a target value based on the input operand of a particular value as described herein or as known in the art. Similarly, terms indicating orientation of various elements, e.g., "coplanar," "perpendicular," "orthogonal," "parallel," or any other angle between the elements, generally refer to being within +/−5-20% of a target value based on the input operand of a particular value as described herein or as known in the art.

[0022] In addition, the terms "comprise," "comprising," "include," "including," "have," "having" or any other variation thereof, are intended to cover a non-exclusive inclusion. For example, a method, process, device, or system that comprises a list of elements is not necessarily limited to only those elements but may include other elements not expressly listed or inherent to such method, process, device, or systems. Also, the term "or" refers to an inclusive "or" and not to an exclusive "or."

[0023] The systems, methods, and devices of this disclosure each have several innovative aspects, no single one of which is solely responsible for all desirable attributes disclosed herein. Details of one or more implementations of the subject matter described in this specification are set forth in the description below and the accompanying drawings.

Example DNN System

[0024] FIG. **1** is a block diagram of an example DNN system **100**, in accordance with various embodiments. The DNN system **100** trains DNNs for various tasks, including physical therapy exercise analysis. The DNN system **100** includes an interface module **110**, a physical therapy exercise analysis module **120**, a training module **130**, a validation module **140**, an inference module **150**, and a datastore **160**. In other embodiments, alternative configurations, different or additional components may be included in the DNN system **100**. Further, functionality attributed to a component of the DNN system **100** may be accomplished by a different component included in the DNN system **100** or a different system. The DNN system **100** or a component of the DNN system **100** (e.g., the training module **130** or inference module **150**) may include the computing device **600** in FIG. **6**.

[0025] The interface module **110** facilitates communications of the DNN system **100** with other systems. As an example, the interface module **110** supports the DNN system **100** to distribute trained DNNs to other systems, e.g., computing devices configured to apply DNNs to perform tasks. As another example, the interface module **110** establishes communications between the DNN system **100** with an external database to receive data that can be used to train DNNs or input into DNNs to perform tasks. In some embodiments, data received by the interface module **110** may have a data structure, such as a matrix. In some embodiments, data received by the interface module **110** may be an image, a series of images, and/or a video stream.

[0026] The physical therapy exercise analysis module **120** identifies an exerciser, determines that selected measurement conditions are met, and analyzes the exercises. The physical therapy exercise analysis module **120** performs physical therapy exercise analysis in real-time and provides real-time guidance to the exerciser. In general, the physical therapy exercise analysis module **120** includes multiple components which can perform functions such as pre-

checks, providing pre-check guidance, live-checks, measuring and analyzing patient movement during exercises, and providing real-time guidance and feedback to the exerciser.

[0027] During training, the physical therapy exercise analysis module **120** can use a training data set including videos of an expert performing the exercises, with each video labeled with labels indicating which exercise is being performed, which side (if applicable), and how many repetitions are performed. In various examples, as described herein, the physical therapy exercise analysis module **120** includes one or more neural networks for processing input images and videos. In some examples, the physical therapy exercise analysis module **120** extracts skeleton sequences as described herein, and arranges the skeleton sequences in time as a 3D array. The physical therapy exercise analysis module **120** can arrange the joints from the skeleton sequence into multiple groups of joints, each representing a human body part that moves together when performing exercises. The movement of each group of joints over a selected time period (e.g., a few seconds) is represented in a matrix. In various implementations, the physical therapy exercise analysis module **120** includes a deep learning model for classifying the exercise based on the matrix data. In some examples, the deep learning model includes a transformer.

[0028] In various examples, as described herein, the physical therapy exercise analysis module **120** includes one or more neural networks for processing input videos. In some examples, the physical therapy exercise analysis module **120** includes one or more deep neural networks (DNN) for processing input images. The training module **130** trains DNNs using training datasets. In some embodiments, a training dataset for training a DNN may include one or more images and/or videos, each of which may be a training sample. In some examples, the training module **130** trains the physical therapy exercise analysis module **120**. The training module **130** may receive real-world video data for processing with the physical therapy exercise analysis module **120** as described herein. In some embodiments, the training module **130** may input different data into different layers of the DNN. For every subsequent DNN layer, the input data may be less than the previous DNN layer. The training module **130** may adjust internal parameters of the DNN to minimize a difference between training data output and the input data processed by the physical therapy exercise analysis module **120**.

[0029] In some embodiments, a part of the training dataset may be used to initially train the DNN, and the rest of the training dataset may be held back as a validation subset used by the validation module **140** to validate performance of a trained DNN. The portion of the training dataset not including the tuning subset and the validation subset may be used to train the DNN.

[0030] The training module **130** also determines hyperparameters for training the DNN. Hyperparameters are variables specifying the DNN training process. Hyperparameters are different from parameters inside the DNN (e.g., weights of filters). In some embodiments, hyperparameters include variables determining the architecture of the DNN, such as number of hidden layers, etc. Hyperparameters also include variables which determine how the DNN is trained, such as batch size, number of epochs, etc. A batch size defines the number of training samples to work through before updating the parameters of the DNN. The batch size is the same as or smaller than the number of samples in the training dataset. The training dataset can be divided into one or more batches. The number of epochs defines how many times the entire training dataset is passed forward and backwards through the entire network. The number of epochs defines the number of times that the deep learning algorithm works through the entire training dataset. One epoch means that each training sample in the training dataset has had an opportunity to update the parameters inside the DNN. An epoch may include one or more batches. The number of epochs may be 1, 10, 50, 100, or even larger.

[0031] The training module **130** defines the architecture of the DNN, e.g., based on some of the hyperparameters. The architecture of the DNN includes an input layer, an output layer, and a plurality of hidden layers. The input layer of an DNN may include tensors (e.g., a multidimensional array) specifying attributes of the input image, such as the height of the input image, the width of the input image, and the depth of the input image (e.g., the number of bits specifying the color of a pixel in the input image). The output layer includes labels of objects in the input layer. The hidden layers are layers between the input layer and output layer. The hidden layers include one or more convolutional layers and one or more other types of layers, such as pooling layers, fully connected layers, normalization layers, softmax or logistic layers, and so on. The convolutional layers of the DNN abstract the input image to a feature map that is represented by a tensor specifying the feature map height, the feature map width, and the feature map channels (e.g., red, green, blue images include 3 channels). A pooling layer is used to reduce the spatial volume of input image after convolution. It is used between 2 convolution layers. A fully connected layer involves weights, biases, and neurons. It connects neurons in one layer to neurons in another layer. It is used to classify images between different categories by training.

[0032] In the process of defining the architecture of the DNN, the training module **130** also adds an activation function to a hidden layer or the output layer. An activation function of a layer transforms the weighted sum of the input of the layer to an output of the layer. The activation function may be, for example, a rectified linear unit activation function, a tangent activation function, or other types of activation functions.

[0033] After the training module **130** defines the architecture of the DNN, the training module **130** inputs a training dataset into the DNN. The training dataset includes a plurality of training samples. An example of a training dataset includes a series of images of a video stream. Unlabeled, real-world video is input to the physical therapy exercise analysis module **120**, and processed using the physical therapy exercise analysis module **120** parameters of the DNN to produce two different model-generated outputs: a first time-forward model-generated output and a second time-reversed model-generated output. In the backward pass, the training module **130** modifies the parameters inside the DNN ("internal parameters of the DNN") to minimize the differences between the first model-generated output is and the second model generated output. The internal parameters include weights of filters in the convolutional layers of the DNN. In some embodiments, the training module **130** uses a cost function to minimize the differences.

[0034] The training module **130** may train the DNN for a predetermined number of epochs. The number of epochs is

a hyperparameter that defines the number of times that the deep learning algorithm will work through the entire training dataset. One epoch means that each sample in the training dataset has had an opportunity to update internal parameters of the DNN. After the training module **130** finishes the predetermined number of epochs, the training module **130** may stop updating the parameters in the DNN. The DNN having the updated parameters is referred to as a trained DNN.

[0035] The validation module **140** verifies accuracy of trained DNNs. In some embodiments, the validation module **140** inputs samples in a validation dataset into a trained DNN and uses the outputs of the DNN to determine the model accuracy. In some embodiments, a validation dataset may be formed of some or all the samples in the training dataset. Additionally or alternatively, the validation dataset includes additional samples, other than those in the training sets. In some embodiments, the validation module **140** may determine an accuracy score measuring the precision, recall, or a combination of precision and recall of the DNN. The validation module **140** may use the following metrics to determine the accuracy score: Precision=TP/(TP+FP) and Recall=TP/(TP+FN), where precision may be how many the reference classification model correctly predicted (TP or true positives) out of the total it predicted (TP+FP or false positives), and recall may be how many the reference classification model correctly predicted (TP) out of the total number of objects that did have the property in question (TP+FN or false negatives). The F-score (F-score=2*PR/(P+R)) unifies precision and recall into a single measure.

[0036] The validation module **140** may compare the accuracy score with a threshold score. In an example where the validation module **140** determines that the accuracy score of the augmented model is lower than the threshold score, the validation module **140** instructs the training module **130** to re-train the DNN. In one embodiment, the training module **130** may iteratively re-train the DNN until the occurrence of a stopping condition, such as the accuracy measurement indication that the DNN may be sufficiently accurate, or a number of training rounds having taken place.

[0037] The inference module **150** applies the trained or validated DNN to perform tasks. The inference module **150** may run inference processes of a trained or validated DNN. In some examples, inference makes use of the forward pass to produce model-generated output for unlabeled real-world data. For instance, the inference module **150** may input real-world data into the DNN and receive an output of the DNN. The output of the DNN may provide a solution to the task for which the DNN is trained for.

[0038] The inference module **150** may aggregate the outputs of the DNN to generate a final result of the inference process. In some embodiments, the inference module **150** may distribute the DNN to other systems, e.g., computing devices in communication with the DNN system **100**, for the other systems to apply the DNN to perform the tasks. The distribution of the DNN may be done through the interface module **110**. In some embodiments, the DNN system **100** may be implemented in a server, such as a cloud server, an edge service, and so on. The computing devices may be connected to the DNN system **100** through a network. Examples of the computing devices include edge devices.

[0039] The datastore **160** stores data received, generated, used, or otherwise associated with the DNN system **100**. For example, the datastore **160** stores video processed by the physical therapy exercise analysis module **120** or used by the training module **130**, validation module **140**, and the inference module **150**. The datastore **160** may also store other data generated by the training module **130** and validation module **140**, such as the hyperparameters for training DNNs, internal parameters of trained DNNs (e.g., values of tunable parameters of activation functions, such as Fractional Adaptive Linear Units (FALUs)), etc. In the embodiment of FIG. **1**, the datastore **160** is a component of the DNN system **100**. In other embodiments, the datastore **160** may be external to the DNN system **100** and communicate with the DNN system **100** through a network.

Example Exercise Analysis System

[0040] FIG. **2** illustrates an example overview of an exercise analysis system **200**, in accordance with various embodiments. In particular, various parts of an exercise analysis system **200** are illustrated in FIG. **2**. The exercise analysis system **200** includes an artificial intelligence (AI)-based exercise analysis module **210**, a clinician portal **205**, a patient application **215**, a cloud **220**, and a camera **230**. In some examples, the camera **230** is a mobile device **235** camera. A user can set up the system such that the camera **230** has a field of view **240** focused on the user. Recordings from the camera **230** can be shared with the AI-based exercise analysis module **210**, which can evaluate the recordings in real time and provide feedback and/or guidance to the user.

[0041] In some implementations, the exercise analysis system **200** can be used by physical therapists as an AI-guided physical therapy system. A mobile device application, such as on a tablet or phone, can provide the patient application **215** and serve as the user interface to the patient. The patient application **215** can communicate with the patient, the camera **230**, the AI-based exercise analysis module **210**, and the cloud **220**. The camera **230** is positioned in front of the patient and streams video in real time to the mobile device (e.g., mobile device **235**) and/or to the AI-based exercise analysis module **210**. At the AI-based exercise analysis module **210**, the patient movements and environment are analyzed, and guidance is generated to provide to the patient. In some examples, the patient can interact with the AI-based exercise analysis module **210** via the patient application **215**. For instance, the patient application **215** may guide the patient visually and/or audibly. The AI-based exercise analysis module **210** receives the video stream from the camera **230**, analyzes the video, extracts data from the video, and transmits instructions to the patient in real-time, including pre-checks and/or live-checks.

[0042] For physical therapists, clinicians, coaches, etc., the clinician portal **205** can present real-time and/or end-of-session measurement results and corresponding video or image frames. In particular, the clinician portal **205** receives the results from the AI-based exercise analysis module **210**. FIG. **3** illustrates an example of a pipeline for implementation of the AI-based exercise analysis module **210**.

[0043] In particular, as shown in FIG. **3**, an input video **305** is received at a human activity analysis system **310**. The human activity analysis system **310** includes an exercise library **315**, a light check module **320**, a person detection module **325**, a person-of-interest identification module **330**, a skeleton identification module **335**, a 2D-3D skeleton generation module **340**, an analysis module **345**, a deep-

learning module **375**, a logic determinations module **380**, and a configurations module **385**. The human activity analysis system **310** generates outputs to a clinician portal **390** and to a patient application **395**.

[0044] In various examples, the exercise library **315** includes a set of exercises that a user may be performing. The set of exercises can include PT exercises. The human activity analysis system **310** receives an input video **305**, and inputs the video to a light checks module **320**. The light checks module **320** determines whether the lighting in the video is sufficient for detection (and analysis) of the person in the video. If the lighting is insufficient, the human activity analysis system **310** can output an alert to the patient application **395** to adjust lighting in the area in which the patient is performing (and recording) the exercises. The patient can then turn on lights, open curtains, or otherwise adjust the lighting until the light check alert from the light checks module **320** of the human activity analysis system **310** is no longer activated.

[0045] The human activity analysis system **310** receives the input video **305** at a person detection module **325**, where any people present in the video are detected. At the person-of-interest module **330**, the person performing the exercises is identified. Thus, if there are any bystanders or others in the room with the person performing the exercises, the system will remove the other people from its subsequent analysis. At the skeleton module **335**, joints of the person performing the exercises are identified, and lines between the joints are generated to approximate a simplified skeleton. At the 2D-3D skeleton module **340**, a simplified skeleton of the person performing the exercises is generated, as illustrated in the skeleton line-drawing **342** of FIG. **3**. The 2D-3D skeleton module **340** saves the movement of the skeleton line-drawing **342** over time as skeleton sequences.

[0046] The skeleton sequences are output from the 2D-3D skeleton module **340** to an analysis module **345**. The analysis module **345** performs pre-checks at the pre-checks module **350**. The pre-checks can include checking where the exerciser is standing within the frame, how the exerciser is standing, lighting checks, and checks for obstructions. Pre-checks are discussed in greater detail below. The analysis module **345** performs live-checks at the live-checks module **355**. The live-checks can include checks while the patient is performing the exercise, and can include, for example, guidance to correct the exercise, correct the side performing the exercise, correct the location relative to the camera, correct lighting, and/or to remove an obstruction between the patient and the camera. In some examples, the deep learning checks module **360** performs AI-based exercise analysis, and can communicate with the live-checks module **355** to provide guidance and feedback on exercise movements. In some examples, the deep learning checks module **360** analyzes the skeleton sequences and identifies any anomalies. The analysis module **345** include a metric rep count module **370**, which can count the repetitions as the user performs the exercises. In various examples, the analysis module **345** can access the exercise library **315**, a deep-learning system **375**, logic determinations module **380**, and configurations module **385**. The analysis module **345** outputs its analysis to a clinician portal **390** and/or to a patient application **395**.

[0047] In some examples, the analysis module **345** analyzes video clips that are around a few seconds long. For instance, the analysis module **345** may analyze video clips that are between about two seconds long and about four seconds long. In one example, the analysis module **345** analyzes video clips that are about three seconds long. The video clips can be overlapping, such that, in one example, a first video clip includes image frames from time zero seconds to time three seconds, a second video clip includes image frames from time one second to time four seconds, and a third video clip includes image frames from time two seconds to time five seconds.

[0048] The clinician portal **390** can display a video of the patient performing the exercise and a graph illustrating movement over time. In some examples, the clinician portal **390** can display measurement results transmitted to the clinician during and/or after completion of the exercise. The patient application portal **395** can display a video of the real-time video stream transmitted as the input video to the exercise analysis system **310**. Instructions and/or guidance can be superimposed on the video image, where instructions and/or guidance can include feedback to the exerciser. The instructions and/or guidance are described in greater detail herein.

[0049] In various implementations, the human activity analysis system **310** is developed and fine-tuned to balance user experience, accuracy of exercise performance, and precision of physical therapy metrics. In some examples, the analysis module **345** determines when guiding conditions provided to the exerciser are met, and then determines measurements of various parameters. Thus, for instance, when exercise performance accuracy exceeds a selected threshold, the human activity analysis system **310** determines various exercise movement measurements. The measurements can include, for example, range of motion, repetition count, speed of each repetition, distance moved for one or more joints (average distance and/or distance for each repetition and/or change in distance moved with subsequent repetitions), and so on.

[0050] In some examples, the human activity analysis system **310** outputs a video of a person performed the selected exercise to the patient application **395**. The cloud exercise library **315** can include a video dataset of people performing the supported exercises. The video dataset can include examples of people performing each exercise accurately, including good start positions, and accurate movement, and the video dataset can include examples of people performing exercises poorly, including inaccurate start positions and/or inaccurate movement. The video dataset can be used to tune checks of the exerciser for best metric accuracy of the parameters measured.

Example Exercise Analysis Method

[0051] FIG. **4** is a flowchart showing a method **400** of exercise analysis, in accordance with various embodiments. The method **400** may be performed by the deep learning system **100** in FIG. **1**, the exercise analysis system **200** in FIG. **2**, and/or the. Although the method **400** is described with reference to the flowchart illustrated in FIG. **4**, many other methods for exercise analysis may alternatively be used. For example, the order of execution of the elements of FIG. **4** may be changed. As another example, some of the elements may be changed, eliminated, or combined.

[0052] In various implementations, the method **400** can be used for interaction between an AI system (the exercise analysis system) and a user (the exerciser) to increase measurement accuracy of exercises. The exercise analysis

system can provide guidance to the user to prevent measurement issues. For example, the exercise analysis system can suggest corrective actions when issues are identified. In some examples, the issues can include visual issues for video stream, such as position of the patient within the field of view (e.g., too far, too close, not centered, etc.), lighting issues, and obstructions between the patient and the camera. In some examples, the issues can include inaccuracies in exercise performance, such as incorrect exercise, incorrect movement of one or more body parts, incorrect side of body performing the movement, etc. In various examples, the exercise analysis system can perform pre-checks, completed before the user begins the exercise, as well as live-checks, completed while the user is performing the exercise.

[0053] Referring to the method **400** of FIG. **4**, at **410**, an input video is received from a user at an exercise analysis system. The input video can be a real-time video stream from a user device, such as a user tablet, phone, laptop, or other mobile device. At **420**, the exercise analysis system transmits exercise instructions to the user. The exercise instructions can include instructions to the patient on where to stand and how to start the exercise. At **425**, it is determined whether a person is in the video stream. If no person is found in the images of the video stream, at **430**, instructions are transmitted to the user to move into the camera field of view. In some examples, if multiple people are found in the video stream, instructions can be transmitted to the user to stand in a selected position and for other people to move out of a selected area in the video stream. In some examples, when multiple people are in the field of view of the camera, once the person of interest is identified and passed a pre-check, the exercise analysis system "locks" on the person of interest to ensure best accuracy during performance of the exercise.

[0054] If at **425**, a person is found in the video stream, at **435**, it is determined whether the person is standing (or otherwise positioned) in the correct position for the exercise. In some examples, it is determined whether the person is in the correct position within images of the input video. For instance, if can be determined whether the person is too far from the camera and/or whether the person is too close to the camera. Similarly, it can be determined whether the person is off to one side in the images captured in the input video. The exercise analysis system can provide feedback to the person to move closer to the camera, further from the camera, to the right, to the left, etc. In some examples, the exercise analysis system guides the person to a best location for the exercise analysis system to analyze the exercises and provide helpful results. In various examples, the best location can vary depending on the exercise and the depending on the height of the person. In some examples, the exercise analysis system records patient height at first login of the patient, and scales its analysis based on the patient's height. In some examples, the best location can be calibrated based on a test set and/or based on benchmark results.

[0055] In some examples, determining whether the person is in the correct position includes determining whether the person is in the correct starting posture and/or position for the selected exercise. Starting postures and/or positions can include standing, seated, quadruped, supine, and so on. Additionally starting postures and/or positions can include various limb positions. Accurate starting position is useful for accurate execution of the exercise analysis system. Providing feedback before the person begins the exercise increases exercise performance accuracy and hence increases measurement accuracy of the exercise analysis system.

[0056] In some examples, determining whether the person is in the correct position includes determining whether the person is starting in the correct view and/or plane relative to the camera (i.e., frontal, sagittal left/right, posterior or transverse).

[0057] In various examples, if the person is not in the correct position, at **440**, instructions are transmitted to the user to move to the starting position. FIG. **5**A shows an example image from a video stream illustrating an outline highlighting the user starting position, in accordance with various embodiments. As shown in FIG. **5**A, the outline is superimposed on the video stream. In FIG. **5**A, the outline illustrates a left side of the body, and guidance is provided to the person to turn and show the left side of their body. In some examples, the person can position themselves such that they appear in the outline superimposed on the screen.

[0058] Additionally, as shown in FIG. **5**A, a video is displayed in the top right of the image showing a person in the correct starting position. Ensuring the person starts the exercise from the correct starting position ensures that the patient plane shown to the camera (and displayed in the video stream) is the best plane for recording accurate measurements of the selected exercise. For example, when performing flexion/extension movements, the measurement is more accurate when seen in a sagittal view. In abduction/adduction movements, the measurement is more accurate in frontal view. For non-symmetric exercises, when the exercise is performed on the left body side, the measurement is more accurate when the left side is closer to the camera. Similarly, for non-symmetric exercises, when the exercise is performed on the right body side, the measurement is more accurate when the right side is closer to the camera. This check is performed for both 2D cameras and 3D cameras.

[0059] Another check that can be completed before the person begins performing the exercise is a lighting check. The lighting of the images in the video stream is checked for various issues, such as to ensure that the video is not too dark, not too bright, has no contrast issues such as high-dynamic range, and so on. Another check that may be completed is a human-equipment interaction test. In particular, if equipment is required to perform the exercise, an equipment check is performed to ensure the equipment is acceptable for the exercise. For example, if the exercise starts when the patient is standing on a box, the equipment check makes sure the person has an acceptable box and that the person is still in a good position relative to the camera when standing on the box. In another example, if a patient is lying on a physio ball for an exercise, the size and inflation of the physio ball can be checked.

[0060] Another check that can be completed before the person begins performing the exercise is to check for any obstructions between the person and the camera. For instance, exercise equipment may have been placed between the person and the camera, obstructing a view of the person. In another example, the person's clothing can be an obstruction. For instance, baggy clothes or a dress can obscure the movement.

[0061] When the pre-checks are completed and the person begins performing the exercise, additional checks are repeated during the exercise. The additional checks during

the exercise serve to identify sub-optimal conditions for measurements by the exercise analysis system.

[0062] Referring to FIG. **4**, at **450**, the input video stream is analyzed to determine performance accuracy of the exercise. Examples of exercise input that can be checked during the exercise include determining whether the patient is performing the correct exercise, determining whether the patient is exercising the correct side (for non-symmetric exercises), and determining whether the patient is still positioned in the correct location relative to the camera. In some examples, an exercise may instruct a patient to move from one side of the room to another side of the room, and the patient may move out of the field of view of the camera. At **460**, feedback can be transmitted to the person based on the checks and the identified performance accuracy of the exercise. Similar to the pre-checks, the input video stream can also be analyzed to identify any obstructions by objects, pets, equipment, clothing, etc., the lighting conditions can be checked, and the continued identification of the person-of-interest can be checked. Additional checks may include validating that the movement is performed in the expected plane (e.g., walking in a straight line and maintaining a fixed a distance from the camera throughout the exercise).

[0063] FIG. **5**B shows an example image **530** from a video stream illustrating an example in which the person is no longer positioned in the correct location relative to the camera, in accordance with various embodiments. As shown in FIG. **5**B, the exerciser is off to the left side of the image. Feedback is provided to the exerciser to move to the right relative to the camera, so that the exerciser will be back in the field of view of the camera.

[0064] FIG. **5**C is a schematic showing an example image **560** from a video stream illustrating an example in which the view of the person is obstructed, in accordance with various embodiments. In particular, as show in FIG. **5**C, a dog is sitting between the person and the camera, blocking the view of the person.

[0065] At **470**, selected parameters of the exercise performance are measured over multiple repetitions of the exercises. The measurements can include parameters related to, for example, range of motion, repetition count, speed of each repetition, distance moved for one or more joints (average distance and/or distance for each repetition and/or change in distance moved with subsequent repetitions), and so on.

[0066] At **480**, measurement results are generated for transmission to a clinician. In particular, if the person performing the exercises is working with a physical therapist, coach, personal trainer, clinician, etc., the measurement results for each exercise can be transmitted to that person for review and to provide further guidance to the exerciser. The measurement results can be used to correct accuracy of performance, to select future exercises, and/or to determine a next exercise protocol.

Example Computing Device

[0067] FIG. **6** is a block diagram of an example computing device **600**, in accordance with various embodiments. In some embodiments, the computing device **600** may be used for at least part of the deep learning system **100** in FIG. **1**. A number of components are illustrated in FIG. **6** as included in the computing device **600**, but any one or more of these components may be omitted or duplicated, as suitable for the application. In some embodiments, some or all of the components included in the computing device **600** may be attached to one or more motherboards. In some embodiments, some or all of these components are fabricated onto a single system on a chip (SoC) die. Additionally, in various embodiments, the computing device **600** may not include one or more of the components illustrated in FIG. **6**, but the computing device **600** may include interface circuitry for coupling to the one or more components. For example, the computing device **600** may not include a display device **606**, but may include display device interface circuitry (e.g., a connector and driver circuitry) to which a display device **606** may be coupled. In another set of examples, the computing device **600** may not include a video input device **618** or a video output device **608**, but may include video input or output device interface circuitry (e.g., connectors and supporting circuitry) to which a video input device **618** or video output device **608** may be coupled.

[0068] The computing device **600** may include a processing device **602** (e.g., one or more processing devices). The processing device **602** processes electronic data from registers and/or memory to transform that electronic data into other electronic data that may be stored in registers and/or memory. The computing device **600** may include a memory **604**, which may itself include one or more memory devices such as volatile memory (e.g., DRAM), nonvolatile memory (e.g., read-only memory (ROM)), high bandwidth memory (HBM), flash memory, solid state memory, and/or a hard drive. In some embodiments, the memory **604** may include memory that shares a die with the processing device **602**. In some embodiments, the memory **604** includes one or more non-transitory computer-readable media storing instructions executable for occupancy mapping or collision detection, e.g., the method **400** described above in conjunction with FIG. **4** or some operations performed by the DNN system **100** in FIG. **1**, the system **200** of FIG. **2**, and/or the system **300** of FIG. **3**. The instructions stored in the one or more non-transitory computer-readable media may be executed by the processing device **602**.

[0069] In some embodiments, the computing device **600** may include a communication chip **612** (e.g., one or more communication chips). For example, the communication chip **612** may be configured for managing wireless communications for the transfer of data to and from the computing device **600**. The term "wireless" and its derivatives may be used to describe circuits, devices, systems, methods, techniques, communications channels, etc., that may communicate data using modulated electromagnetic radiation through a nonsolid medium. The term does not imply that the associated devices do not contain any wires, although in some embodiments they might not.

[0070] The communication chip **612** may implement any of a number of wireless standards or protocols, including but not limited to Institute for Electrical and Electronic Engineers (IEEE) standards including Wi-Fi (IEEE 802.10 family), IEEE 802.16 standards (e.g., IEEE 802.16-2005 Amendment), Long-Term Evolution (LTE) project along with any amendments, updates, and/or revisions (e.g., advanced LTE project, ultramobile broadband (UMB) project (also referred to as "3GPP2"), etc.). IEEE 802.16 compatible Broadband Wireless Access (BWA) networks are generally referred to as WiMAX networks, an acronym that stands for worldwide interoperability for microwave access, which is a certification mark for products that pass conformity and interoperability tests for the IEEE 802.16 standards. The communication chip **612** may operate in accor-

dance with a Global System for Mobile Communication (GSM), General Packet Radio Service (GPRS), Universal Mobile Telecommunications System (UMTS), High Speed Packet Access (HSPA), Evolved HSPA (E-HSPA), or LTE network. The communication chip **612** may operate in accordance with Enhanced Data for GSM Evolution (EDGE), GSM EDGE Radio Access Network (GERAN), Universal Terrestrial Radio Access Network (UTRAN), or Evolved UTRAN (E-UTRAN). The communication chip **612** may operate in accordance with code-division multiple access (CDMA), Time Division Multiple Access (TDMA), Digital Enhanced Cordless Telecommunications (DECT), Evolution-Data Optimized (EV-DO), and derivatives thereof, as well as any other wireless protocols that are designated as 3G, 4G, 5G, and beyond. The communication chip **612** may operate in accordance with other wireless protocols in other embodiments. The computing device **600** may include an antenna **622** to facilitate wireless communications and/or to receive other wireless communications (such as AM or FM radio transmissions).

[0071] In some embodiments, the communication chip **612** may manage wired communications, such as electrical, optical, or any other suitable communication protocols (e.g., the Ethernet). As noted above, the communication chip **612** may include multiple communication chips. For instance, a first communication chip **612** may be dedicated to shorter-range wireless communications such as Wi-Fi or Bluetooth, and a second communication chip **612** may be dedicated to longer-range wireless communications such as global positioning system (GPS), EDGE, GPRS, CDMA, WiMAX, LTE, EV-DO, or others. In some embodiments, a first communication chip **612** may be dedicated to wireless communications, and a second communication chip **612** may be dedicated to wired communications.

[0072] The computing device **600** may include battery/power circuitry **614**. The battery/power circuitry **614** may include one or more energy storage devices (e.g., batteries or capacitors) and/or circuitry for coupling components of the computing device **600** to an energy source separate from the computing device **600** (e.g., AC line power).

[0073] The computing device **600** may include a display device **606** (or corresponding interface circuitry, as discussed above). The display device **606** may include any visual indicators, such as a heads-up display, a computer monitor, a projector, a touchscreen display, a liquid crystal display (LCD), a light-emitting diode display, or a flat panel display, for example.

[0074] The computing device **600** may include a video output device **608** (or corresponding interface circuitry, as discussed above). The video output device **608** may include any device that generates an audible indicator, such as speakers, headsets, or earbuds, for example.

[0075] The computing device **600** may include a video input device **618** (or corresponding interface circuitry, as discussed above). The video input device **618** may include any device that generates a signal representative of a sound, such as microphones, microphone arrays, or digital instruments (e.g., instruments having a musical instrument digital interface (MIDI) output).

[0076] The computing device **600** may include a GPS device **616** (or corresponding interface circuitry, as discussed above). The GPS device **616** may be in communication with a satellite-based system and may receive a location of the computing device **600**, as known in the art.

[0077] The computing device **600** may include another output device **610** (or corresponding interface circuitry, as discussed above). Examples of the other output device **610** may include a video codec, a video codec, a printer, a wired or wireless transmitter for providing information to other devices, or an additional storage device.

[0078] The computing device **600** may include another input device **620** (or corresponding interface circuitry, as discussed above). Examples of the other input device **620** may include an accelerometer, a gyroscope, a compass, an image capture device, a keyboard, a cursor control device such as a mouse, a stylus, a touchpad, a bar code reader, a Quick Response (QR) code reader, any sensor, or a radio frequency identification (RFID) reader.

[0079] The computing device **600** may have any desired form factor, such as a handheld or mobile computer system (e.g., a cell phone, a smart phone, a mobile internet device, a music player, a tablet computer, a laptop computer, a netbook computer, an ultrabook computer, a personal digital assistant (PDA), an ultramobile personal computer, etc.), a desktop computer system, a server or other networked computing component, a printer, a scanner, a monitor, a set-top box, an entertainment control unit, a vehicle control unit, a digital camera, a digital video recorder, or a wearable computer system. In some embodiments, the computing device **600** may be any other electronic device that processes data.

Selected Examples

[0080] The following paragraphs provide various examples of the embodiments disclosed herein.

[0081] Example 1 provides a computer-implemented method, including receiving a real-time input video stream; transmitting exercise instructions for a person to perform a selected exercise; determining the person is present in the real-time input video stream; analyzing a first video segment of the real-time input video stream, at a neural network, to determine performance of the selected exercise; transmitting feedback to the person based on the performance; measuring selected parameters of the performance of the selected exercise over a plurality of repetitions of the selected exercise; and generating measurement results.

[0082] Example 2 provides the computer-implemented method according to example 1, where transmitting exercise instructions includes transmitting an outline of a starting position for the selected exercise, and where the outline can be superimposed on the real-time input video stream.

[0083] Example 3 provides the computer-implemented method according to examples 1-2, further including identifying a present position of the person in the real-time input video stream and transmitting position instructions for the person to move to a best position based on selected exercise.

[0084] Example 4 provides the computer-implemented method according to example 1-3, further including identifying an obstruction in the real-time input video stream blocking a view of the person, and transmitting instructions to move the obstruction.

[0085] Example 5 provides the computer-implemented method according to example 1-4, where analyzing the first video segment of the real-time input video stream

includes identifying a side of the person performing the selected exercise, where the side is one of a right side, a left side, and both sides.

[0086] Example 6 provides the computer-implemented method according to example 5, further including determining the person is performing the selected exercise on a wrong side and transmitting feedback to switch sides.

[0087] Example 7 provides the computer-implemented method according to example 1-6, where the measurement results includes a total number of repetitions of the selected exercise performed.

[0088] Example 8 provides the computer-implemented method according to example 1-7, where transmitting exercise instructions includes transmitting a video of a person performing the selected exercise.

[0089] Example 9 provides one or more non-transitory computer-readable media storing instructions executable to perform operations, the operations including receiving a real-time input video stream; transmitting exercise instructions for a person to perform a selected exercise; determining the person is present in the real-time input video stream; analyzing a first video segment of the real-time input video stream, at a neural network, to determine performance of the selected exercise; transmitting feedback to the person based on the performance; measuring selected parameters of the performance of the selected exercise over a plurality of repetitions of the selected exercise; and generating measurement results.

[0090] Example 10 provides the one or more non-transitory computer-readable media according to example 9, where transmitting exercise instructions includes transmitting an outline of a starting position for the selected exercise, and where the outline can be superimposed on the real-time input video stream.

[0091] Example 11 provides the one or more non-transitory computer-readable media according to example 9-10, further including identifying a present position of the person in the real-time input video stream and transmitting position instructions for the person to move to a best position based on selected exercise.

[0092] Example 12 provides the one or more non-transitory computer-readable media according to example 9-11, further including identifying an obstruction in the real-time input video stream blocking a view of the person, and transmitting instructions to move the obstruction.

[0093] Example 13 provides the one or more non-transitory computer-readable media according to example 9-12, where analyzing the first video segment of the real-time input video stream includes identifying a side of the person performing the selected exercise, where the side is one of a right side, a left side, and both sides.

[0094] Example 14 provides the one or more non-transitory computer-readable media according to example 13, further including determining the person is performing the selected exercise on a wrong side and transmitting feedback to switch sides.

[0095] Example 15 provides the one or more non-transitory computer-readable media according to example 9-14, where the measurement results includes a total number of repetitions of the selected exercise performed.

[0096] Example 16 provides the one or more non-transitory computer-readable media according to example 9-15, where transmitting exercise instructions includes transmitting a video of a person performing the selected exercise.

[0097] Example 17 provides an apparatus, including a computer processor for executing computer program instructions; and a non-transitory computer-readable memory storing computer program instructions executable by the computer processor to perform operations including receiving a real-time input video stream; transmitting exercise instructions for a person to perform a selected exercise; determining the person is present in the real-time input video stream; analyzing a first video segment of the real-time input video stream, at a neural network, to determine performance of the selected exercise; transmitting feedback to the person based on the performance; measuring selected parameters of the performance of the selected exercise over a plurality of repetitions of the selected exercise; and generating measurement results.

[0098] Example 18 provides the apparatus according to example 17, where transmitting exercise instructions includes transmitting an outline of a starting position for the selected exercise, and where the outline can be superimposed on the real-time input video stream.

[0099] Example 19 provides the apparatus according to example 17-18, further including identifying a present position of the person in the real-time input video stream and transmitting position instructions for the person to move to a best position based on selected exercise.

[0100] Example 20 provides the apparatus according to example 17-19, where analyzing the first video segment of the real-time input video stream includes identifying a side of the person performing the selected exercise, where the side is one of a right side, a left side, and both sides.

[0101] The above description of illustrated implementations of the disclosure, including what is described in the Abstract, is not intended to be exhaustive or to limit the disclosure to the precise forms disclosed. While specific implementations of, and examples for, the disclosure are described herein for illustrative purposes, various equivalent modifications are possible within the scope of the disclosure, as those skilled in the relevant art will recognize. These modifications may be made to the disclosure in light of the above detailed description.

1. A computer-implemented method, comprising:

receiving a real-time input video stream;

transmitting exercise instructions for a person to perform a selected exercise;

determining the person is present in the real-time input video stream;

analyzing a first video segment of the real-time input video stream, at a neural network, to determine performance of the selected exercise;

transmitting feedback to the person based on the performance;

measuring selected parameters of the performance of the selected exercise over a plurality of repetitions of the selected exercise; and

generating measurement results.

2. The computer-implemented method according to claim **1**, wherein transmitting exercise instructions includes transmitting an outline of a starting position for the selected exercise, and wherein the outline can be superimposed on the real-time input video stream.

3. The computer-implemented method according to claim **1**, further comprising identifying a present position of the person in the real-time input video stream and transmitting position instructions for the person to move to a target position based on the selected exercise.

4. The computer-implemented method according to claim **1**, further comprising identifying an obstruction in the real-time input video stream blocking a view of the person, and transmitting instructions to move the obstruction.

5. The computer-implemented method according to claim **1**, wherein analyzing the first video segment of the real-time input video stream includes identifying a side of the person performing the selected exercise, wherein the side is one of a right side, a left side, and both sides.

6. The computer-implemented method according to claim **5**, further comprising determining the person is performing the selected exercise on a wrong side and transmitting feedback to switch sides.

7. The computer-implemented method according to claim **1**, wherein the measurement results includes a total number of repetitions of the selected exercise performed.

8. The computer-implemented method according to claim **1**, wherein transmitting exercise instructions includes transmitting a video of a person performing the selected exercise.

9. One or more non-transitory computer-readable media storing instructions executable to perform operations, the operations comprising:

receiving a real-time input video stream;

transmitting exercise instructions for a person to perform a selected exercise;

determining the person is present in the real-time input video stream;

analyzing a first video segment of the real-time input video stream, at a neural network, to determine performance of the selected exercise;

transmitting feedback to the person based on the performance;

measuring selected parameters of the performance of the selected exercise over a plurality of repetitions of the selected exercise; and

generating measurement results.

10. The one or more non-transitory computer-readable media according to claim **9**, wherein transmitting exercise instructions includes transmitting an outline of a starting position for the selected exercise, and wherein the outline can be superimposed on the real-time input video stream.

11. The one or more non-transitory computer-readable media according to claim **9**, further comprising identifying a present position of the person in the real-time input video stream and transmitting position instructions for the person to move to a target position based on the selected exercise.

12. The one or more non-transitory computer-readable media according to claim **9**, further comprising identifying an obstruction in the real-time input video stream blocking a view of the person, and transmitting instructions to move the obstruction.

13. The one or more non-transitory computer-readable media according to claim **9**, wherein analyzing the first video segment of the real-time input video stream includes identifying a side of the person performing the selected exercise, wherein the side is one of a right side, a left side, and both sides.

14. The one or more non-transitory computer-readable media according to claim **13**, further comprising determining the person is performing the selected exercise on a wrong side and transmitting feedback to switch sides.

15. The one or more non-transitory computer-readable media according to claim **9**, wherein the measurement results includes a total number of repetitions of the selected exercise performed.

16. The one or more non-transitory computer-readable media according to claim **9**, wherein transmitting exercise instructions includes transmitting a video of a person performing the selected exercise.

17. An apparatus, comprising:

a computer processor for executing computer program instructions; and

a non-transitory computer-readable memory storing computer program instructions executable by the computer processor to perform operations comprising:

receiving a real-time input video stream;

transmitting exercise instructions for a person to perform a selected exercise;

determining the person is present in the real-time input video stream;

analyzing a first video segment of the real-time input video stream, at a neural network, to determine performance of the selected exercise;

transmitting feedback to the person based on the performance;

measuring selected parameters of the performance of the selected exercise over a plurality of repetitions of the selected exercise; and

generating measurement results.

18. The apparatus according to claim **17**, wherein transmitting exercise instructions includes transmitting an outline of a starting position for the selected exercise, and wherein the outline can be superimposed on the real-time input video stream.

19. The apparatus according to claim **17**, further comprising identifying a present position of the person in the real-time input video stream and transmitting position instructions for the person to move to a target position based on the selected exercise.

20. The apparatus according to claim **17**, wherein analyzing the first video segment of the real-time input video stream includes identifying a side of the person performing the selected exercise, wherein the side is one of a right side, a left side, and both sides.

* * * * *