

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250253996

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

WANG; LILEI et al.

---

### BASE STATION, USER EQUIPMENT AND WIRELESS COMMUNICATION METHOD

---

#### Abstract

An integrated circuit includes generation circuitry and transmission circuitry. The generation circuitry uses a reference size for a search space to generate downlink control information (DCI) in a first DCI format used for sidelink communications. The transmission circuitry transmits the DCI in the first DCI format mapped on the search space. When a second DCI format used for base station communications is mapped on the search space and the second DCI format is larger than the first DCI format, the reference size for the search space is based on the second DCI format. When a third DCI format used for sidelink communications is mapped on the search space and the third DCI format is larger than the first DCI format, and the second DCI format larger than the third DCI format is not mapped on the search space, the reference size is based on the third DCI format.

---

**Inventors:** WANG; LILEI (Beijing, CN), SUZUKI; HIDETOSHI (Kanagawa, JP), GOLITSCHKE EDLER VON ELBWART; ALEXANDER (Hessen, DE)

**Applicant:** Panasonic Intellectual Property Corporation of America (Torrance, CA)

**Family ID:** 62076295

**Appl. No.:** 19/187636

**Filed:** April 23, 2025

#### Related U.S. Application Data

parent US continuation 18430452 20240201 parent-grant-document US 12309082 child US 19187636

parent US continuation 17974448 20221026 parent-grant-document US 11929949 child US 18430452

parent US continuation 16928631 20200714 parent-grant-document US 11516793 child US 17974448

## Publication Classification

**Int. Cl.:** **H04L5/00** (20060101); **H04L1/00** (20060101); **H04L27/26** (20060101); **H04W72/044** (20230101); **H04W72/0446** (20230101); **H04W72/12** (20230101); **H04W72/23** (20230101); **H04W92/18** (20090101)

**U.S. Cl.:**

**CPC** **H04L5/0046** (20130101); **H04L5/005** (20130101); **H04L5/0053** (20130101); **H04L27/2602** (20130101); **H04W72/0446** (20130101); **H04W72/046** (20130101); **H04W72/1215** (20130101); **H04W72/23** (20230101); **H04W92/18** (20130101); **H04L1/0008** (20130101)

---

## Background/Summary

### BACKGROUND

#### 1. Technical Field

[0001] The present disclosure relates to the field of wireless communication, and in particular, to a base station (eNodeB), a user equipment (UE) and wireless communication methods related to DCI (Downlink Control Information) design for blind detection.

#### 2. Description of the Related Art

[0002] Dynamic scheduling of sidelink (SL) transmission according to an eNodeB based scheduling resource allocation mode has been specified for V2V (Vehicle to Vehicle) communication so far and a sidelink DCI format has been designed for the dynamic scheduling of sidelink. FIG. 1 schematically shows an exemplary scenario in which sidelink resources are dynamically scheduled by an eNodeB for V2V communication. As shown in FIG. 1, communication may be performed between two vehicles **102** and **103** via sidelinks as shown by two thick arrows noted as “SL”. The resources for sidelink transmission between the vehicles **102** and **103** may be dynamically scheduled by eNodeB **101** through the sidelink DCI format as described above. Specifically, communication may also be performed between each of two vehicles **102** and **103** and eNodeB **101** as shown by respective thin arrows noted as “DL” or “UL”. For example, the vehicle **102** may receive the sidelink DCI from eNodeB **101** via downlink so as to perform the communication with the vehicle **103** via sidelinks based on the received sidelink DCI.

[0003] Based on latest 3GPP (The 3rd Generation Partnership Project) progress, semi-persistent scheduling (SPS) would be supported for V2V sidelink transmission in order to satisfy periodic traffic like CAM (Cooperative Awareness Message). Thus, sidelink SPS and the dedicated DCI format thereof are under discussion in 3GPP.

### SUMMARY

[0004] One non-limiting and exemplary embodiment provides DCI design to reduce blind detection times.

[0005] In a first general aspect of the present disclosure, there is provided a base station, comprising: circuitry operative to align, for each DCI (Downlink Control Information) of a first group of DCIs, one of the size of the DCI of the first group and the size of a selected DCI of a second group of DCIs with the other, if the size of the DCI of the first group is different from the size of each DCI of the second group of DCIs, wherein the selected DCI of the second group is a

DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes larger than the size of the DCI of the first group or a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes smaller than the size of the DCI of the first group; and a transmitter operative to transmit the first group of DCIs and the second group of DCIs after the size alignment by the circuitry to a user equipment, wherein the size alignment is based on a rule which is known by the base station and the user equipment beforehand.

[0006] In a second general aspect of the present disclosure, there is provided a user equipment, comprising: a receiver operative to receive a first group of DCIs and a second group of DCIs from a base station; and a circuitry operative to blindly detect the first group of DCIs and the second group of DCIs so as to perform transmission and/or reception based on a rule which is known by the base station and the user equipment beforehand, wherein said rule indicates that before being received by the user equipment, the first group of DCIs and the second group of DCIs has been subject to size alignment comprising: [0007] aligning, for each DCI of the first group of DCIs, one of the size of the DCI of the first group and the size of a selected DCI of the second group of DCIs with the other based on said rule, if the size of the DCI of the first group is different from the size of each DCI of the second group of DCIs, wherein the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes larger than the size of the DCI of the first group or a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes smaller than the size of the DCI of the first group.

[0008] In a third general aspect of the present disclosure, there is provided a wireless communication method for a base station, comprising: aligning, for each DCI (Downlink Control Information) of a first group of DCIs, one of the size of the DCI of the first group and the size of a selected DCI of a second group of DCIs with the other, if the size of the DCI of the first group is different from the size of each DCI of the second group of DCIs, wherein the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes larger than the size of the DCI of the first group or a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes smaller than the size of the DCI of the first group; and transmitting the first group of DCIs and the second group of DCIs after the size alignment to a user equipment, wherein the size alignment is based on a rule which is known by the base station and the user equipment beforehand.

[0009] It should be noted that general or specific embodiments may be implemented as a system, a method, an integrated circuit, a computer program, a storage medium, or any selective combination thereof.

[0010] Additional benefits and advantages of the disclosed embodiments will become apparent from the specification and drawings. The benefits and/or advantages may be individually obtained by the various embodiments and features of the specification and drawings, which need not all be provided in order to obtain one or more of such benefits and/or advantages.

---

## Description

### BRIEF DESCRIPTION OF DRAWINGS

[0011] The foregoing and other features of the present disclosure will become more fully apparent from the following description and appended claims, taken in conjunction with the accompanying drawings. Understanding that these drawings depict only several embodiments in accordance with the disclosure and are, therefore, not to be considered limiting of its scope, the disclosure will be described with additional specificity and detail through use of the accompanying drawings, in which:

[0012] FIG. 1 schematically shows an exemplary scenario in which sidelink resources are dynamically scheduled by an eNodeB for V2V communication;

[0013] FIG. 2 illustrates a flowchart of a wireless communication method for a base station according to an embodiment of the present disclosure;

[0014] FIG. 3 illustrates a flowchart of a wireless communication method for a user equipment according to another embodiment of the present disclosure;

[0015] FIG. 4 illustrates a block diagram of a base station according to a further embodiment of the present disclosure; and; and

[0016] FIG. 5 illustrates a block diagram of a user equipment according to another embodiment of the present disclosure.

## DETAILED DESCRIPTION

[0017] In the following detailed description, reference is made to the accompanying drawings, which form a part thereof. In the drawings, similar symbols typically identify similar components, unless context dictates otherwise. It will be readily understood that the aspects of the present disclosure can be arranged, substituted, combined, and designed in a wide variety of different configurations, all of which are explicitly contemplated and make part of this disclosure.

[0018] As described above, sidelink SPS and the dedicated DCI format thereof, which is also referred to be as sidelink SPS DCI format, are under discussion in 3GPP. Specifically, two additional fields are suggested to be added to the sidelink DCI format which is used for dynamic scheduling of V2V/V2X (Vehicle to anything) traffic. In the following, Table 1 shows detailed design of the suggested sidelink SPS DCI format with respect to different bandwidths of carriers to be scheduled. Here the assumption is SL SPS configuration index is 3 bits and Activation/release indication is 1 bit based on working assumption in 3GPP but in the end the size of these fields may be modified.

TABLE-US-00001

TABLE 1	The design of sidelink SPS DCI format	Bandwith	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	20 MHz	Carrier indicator	3	3	3	3	3	3	Lowest index of the subchannel allocation	0	2	3	4	4	5	Frequency resource location	0	3	4	6	7	8	Time gap between initial transmission and retransmission	4	4	4	4	4	4	SL SPS configuration index	3	3	3	3	3	3	Activation/release indication	1	1	1	1	1	1	Total payload size [bit]	11	16	18	21	22	24	Assumption on subchannel size in terms of PRB	6	5	5	5	5	5
---------	---------------------------------------	----------	---------	-------	-------	--------	--------	--------	-------------------	---	---	---	---	---	---	---	---	---	---	---	---	---	-----------------------------	---	---	---	---	---	---	--	---	---	---	---	---	---	----------------------------	---	---	---	---	---	---	-------------------------------	---	---	---	---	---	---	--------------------------	----	----	----	----	----	----	---	---	---	---	---	---	---

[0019] In Table 1, the first four table cells in the first column indicate contents (i.e. fields) contained in the existing sidelink DCI format used for dynamic scheduling based on 3GPP TS 36.312. Specifically, these contents are “Carrier indicator”, “Lowest index of the subchannel allocation”, “Frequency resource location” and “Time gap between initial transmission and retransmission”. For different bandwidths of carriers to be scheduled, sizes of some of these fields are different and sizes of others of these fields are the same. For example, Table 1 shows six different bandwidths, that is, 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz. The size of “Carrier indicator” is 3 bits for all of these six bandwidths, and the size of “Time gap between initial transmission and retransmission” is 4 bits for all of these six bandwidths. In contrast, the sizes of “Lowest index of the subchannel allocation” are 0 bits, 2 bits, 3 bits, 4 bits, 4 bits and 5 bits for bandwidths of 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz and 20 MHz respectively. Also, the size of “Frequency resource location” changes per bandwidth of the carrier to be scheduled as shown in Table 1.

[0020] In Table 1, the fifth and sixth table cells in the first column indicate the suggested two additional fields for sidelink (SL) SPS as described above. Specifically, these two additional fields are “SL SPS configuration index” and “Activation/release indication”. They both are assumed to have fixed sizes (3 bits and 1 bit respectively) for different bandwidths of carriers to be scheduled.

[0021] The last two rows in Table 1 respectively shows the total payloads sizes (i.e. the total number of bits) and assumed subchannel sizes (i.e. the number of PRBs (Physical Resource Blocks)) of the designed sidelink SPS DCI format for different bandwidths of carriers to be

scheduled. Apparently, due to the two additional fields, the total payload size of the sidelink SPS DCI will be larger than that of sidelink DCI for dynamical scheduling.

[0022] Although the above description is made by taking V2V/V2X communication, a vehicle may also be understood as a UE. That is to say, the direct communication between two UEs is performed via sidelink between them and may be scheduled by a base station/eNodeB through the sidelink DCI as described above. Simultaneously, there may be communication between the UE and the eNodeB and such communication is generally scheduled by the eNodeB via conventional DCI format such as DCI format 0, DCI format 1A and so on. For the purpose of explanation, these DCIs for scheduling transmission between the UE and the eNodeB are referred to be as Uu (User Equipment to Radio Network System) DCIs.

[0023] Since for a UE, sidelink communication with another UE and uplink/downlink communication with the eNodeB may both occurs, in a same search space, sidelink DCIs and Uu DCIs as described above may appear simultaneously and need to be blindly detected/decoded at the UE side. In this case, if the size of a sidelink DCI is different from each of Uu DCIs, the blind detection/decoding times at the UE side will be increased due to introducing SL DCIs. For example, Table 2 shows contents and DCI size of DCI format 0 with respect to different bandwidths of carriers to be scheduled.

TABLE-US-00002 TABLE 2 Contents and DCI size of DCI format 0

Bandwidth	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	20 MHz
Carrier indicator	3	3	3	3	3	3
Flag for format0/format1A	1	1	1	1	1	1
1 differentiation Hopping flag/RA Type 1 MSB	1	1	1	1	1	1
Resource block assignment and hopping resource allocation	5	7	9	11	12	13
Modulation and coding scheme	5	5	5	5	5	5
and redundancy version New data indicator	1	1	1	1	1	1
TPC command for scheduled PUSCH	2	2	2	2	2	2
Cyclic shift for DM RS and OCC index	3	3	3	3	3	3
UL index or Downlink Assignment Index (DAI)	0	0	0	0	0	0
CSI request	1	1	1	1	1	1
SRS request	0	0	0	0	0	0
Resource allocation type	1	1	1	1	1	1
Total payload size [bit]	23	25	27	29	30	31

[0024] Here, since fields contained in DCI format 0 and their respective sizes are well known for those skilled in the art, the details thereof is omitted for avoiding confusion of the inventive point of the present disclosure. In Table 2, the last row shows total payload sizes of DCI format 0 are 23 bits, 25 bits, 27 bits, 29 bits, 30 bits and 31 bits for different bandwidths of 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz and 20 MHz respectively.

[0025] Although not shown in Table 1, it can be derived from contents given in Table 1 that total payload sizes of sidelink DCI format for dynamical scheduling are 7 bits, 12 bits, 14 bits, 17 bits, 18 bits and 20 bits for different bandwidths of 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz and 20 MHz respectively. By comparison between DCI format 0 and the sidelink DCI format for dynamical scheduling, it can be seen that the size of the sidelink DCI format for dynamical scheduling is smaller than that of DCI format 0. Thus, based on the current specification and agreement, zero bits are padded to the sidelink DCI format for dynamical scheduling so as to align the size thereof to that of DCI format 0. Thereby, blind detection (decoding) times at UE side can be reduced.

[0026] However, as described above, due to two additional fields as shown in Table 1, the total payload size of the sidelink SPS DCI will be larger than that of sidelink DCI for dynamical scheduling by for example 4 bits for each bandwidth as shown in Table 1. Thus, by comparison between DCI format 0 and the sidelink SPS DCI format, there is possibility that the size of sidelink SPS DCI format is larger than that of DCI format 0. For the purpose of understanding easily, Table 3 shows size comparison between SL SPS DCI and DCI format 0.

TABLE-US-00003 TABLE 3 size comparison between SL SPS DCI and DCI format 0

DCI\DCI Bandwidth	format 0 1.4 MHz	format 0 3 MHz	format 0 5 MHz	format 0 10 MHz	format 0 15 MHz	format 0 20 MHz
SL SPS DCI	11\23	11\25	11\27	11\29	11\30	11\31
format 0 3 MHz	16\23	16\25	16\27	16\29	16\30	16\31
SL SPS DCI 5 MHz	18\23	18\25	18\27	18\29	18\30	18\31
format 0 10 MHz	21\23	21\25	21\27	21\29	21\30	21\31
SL SPS DCI 15 MHz	22\23	22\25	22\27	22\29	22\30	22\31
format 0 20 MHz	24\23	24\25	24\27			

[0027] As shown in Table 3, in each table cell containing two numbers, the number at left side of “\” indicates the size (total payload size) of SL SPS DCI for a certain bandwidth of carrier to be scheduled, and the number at right side of “\” indicates the size (total payload size) of DCI format 0 for the certain bandwidth of carrier to be scheduled. It can be seen from Table 3 that in a case that SL SPS DCI is used to schedule a carrier of bandwidth of 20 MHz and DCI format 0 is used to schedule a carrier of bandwidth of 1.4 MHz, the size (24 bits) of SL SPS DCI is larger than the size (23 bits) of DCI format 0, as shown in the table cell “24/23”. Since the current specification and agreement only consider the case that the size of the sidelink DCI format for dynamical scheduling is smaller than that of DCI format 0, UE behavior is unclear when the size of SL SPS DCI is larger than the size of DCI format 0.

[0028] Furthermore, in LTE (Long Term Evolution), it is known that DCI format 0 and DCI format 1A (as well as format 3/3A) are padded to each other in order for size alignment. However, DCI format 0 and DCI format 1A are only related to size alignment between two DCIs. Until now, it is unclear how to handle the size alignment in cases that there are more than two DCIs including at least one sidelink DCI and at least one Uu DCI. For example, the size of a sidelink DCI may be smaller than that of one Uu DCI but larger than that of another Uu DCI.

[0029] In addition, in NR (New Radio access technology) or 5G (The fifth Generation) system, sidelink DCIs and Uu DCIs may also appear in a same search space similarly as in cases described above, and how to implement the size alignment between DCIs needs to be considered too.

[0030] In an embodiment of the present disclosure, there is provided a wireless communication method **20** for a base station as shown in FIG. 2. FIG. 2 illustrates a flowchart of a wireless communication method **20** for a base station according to an embodiment of the present disclosure.

[0031] As shown in FIG. 2, the wireless communication method **20** starts at step **S201** in which, for each DCI of a first group of DCIs, one of the size of the DCI of the first group and the size of a selected DCI of a second group of DCIs is aligned with the other, if the size of the DCI of the first group is different from the size of each DCI of the second group of DCIs, wherein the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes larger than the size of the DCI of the first group or a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes smaller than the size of the DCI of the first group. Then, at step **S202**, the first group of DCIs and the second group of DCIs after the size alignment are transmitted to a user equipment. After step **S202**, the wireless communication method **20** ends. The size alignment is based on a rule which is known by the base station and the user equipment beforehand.

[0032] Specifically, for example, the base station may be eNodeB **101** as shown in FIG. 1 and the user equipment may be any one of vehicles **102** and **103** as shown in FIG. 1. That is to say, the wireless communication method **20** may be used by eNodeB **101** to schedule sidelink transmission and/or reception as well as uplink transmission and downlink reception of vehicles **102** and **103**.

[0033] For the purpose of explanation, it may be assumed that the first group of DCIs are DCIs for scheduling sidelink transmission between the user equipment and another user equipment and that the second group of DCIs are DCIs for scheduling transmission between the user equipment and the base station. As described above, the first group of DCIs may be referred simply to be as SL DCIs and the second group of DCIs may be referred simply to be as Uu DCIs.

[0034] As described above, in a same search space, there may be at least one SL DCI and at least one Uu DCI and the size of the SL DCI may be smaller or larger than the Uu DCI in one case. In another case, in a same search space, there may be more than one SL DCIs and more than one Uu DCIs and the size relationship between the SL DCIs and Uu DCIs may be very complicated. If no size alignment of these DCIs is performed, there will be many kinds of sizes of DCIs, blind detection of these DCIs needs to be performed too many times at the user equipment in order to correctly detect these DCIs, which will result in time consuming and system load increasing.

[0035] At step **S201**, for each SL DCI, if the size of the SL DCI is different from that of each Uu DCI, the size alignment is performed between the SL DCI and an Uu DCI whose size is smallest among Uu DCIs having sizes larger than the SL DCI or an Uu DCI whose size is largest among Uu DCIs having sizes smaller than the SL DCI. Thus, firstly, the blind detection times at UE side can be reduced. Secondly, since the selected Uu DCI is an Uu DCI whose size is smallest among Uu DCIs having sizes larger than the SL DCI or an Uu DCI whose size is largest among Uu DCIs having sizes smaller than the SL DCI, the minimum size change of DCIs can be kept.

[0036] In addition, since the rule on which the size alignment is based is known by the base station and the user equipment beforehand, UE may blindly detect these DCIs after the size alignment by the base station based on the rule. The rule may be predefined in a standard. Alternatively, the rule may also be defined by the base station, and the base station needs to notify UE of the rule for example via upper-layer signaling before UE performs the blind detection of DCIs. Apparently, the definition manner of the rule may also be any other suitable manner and the present disclosure is not limited to the above two manners.

[0037] When there are more than one SL DCIs and more than one Uu DCIs, different SL DCIs may be aligned with different Uu DCIs. Specific examples of the size alignment between SL DCIs and Uu DCIs will be further given later for facilitating understanding the wireless communication method **20**.

[0038] With the wireless communication method **20**, by performing the size alignment between each DCI of the first group of DCIs and the selected DCI of the second group whose size is closest to that of the each DCI of the first group, blind detection times at the user equipment can be reduced while minimizing the size change of DCIs.

[0039] According to an embodiment of the present disclosure, in the wireless communication method **20** as shown in FIG. 2, the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes larger than the size of the DCI of the first group. And, although not shown in FIG. 2, in step **S201**, aligning one of the size of the DCI of the first group and the size of the selected DCI of a second group of DCIs with the other may comprises a sub-step of increasing bits in the DCI of the first group, wherein the number of the increased bits equals to the difference between the size of the DCI of the first group and that of the selected DCI of the second group.

[0040] Specifically, in a first example, it is assumed that a UE is configured with TM (Transmission Mode) **10** and is expected to decode DCI format 0 and DCI format 2D for an Uu channel of bandwidth of 1.4 MHz and to decode SL SPS DCI for a sidelink channel of bandwidth of 20 MHz. That is to say, the first group of DCIs includes only one SL DCI, that is, SL SPS DCI as shown in Table 1, and the second group of DCIs includes two Uu DCIs, that is, DCI format 0 as shown in Table 2 and DCI format 2D. Table 4 shows the design (contents/fields and size) of DCI format 2D for the bandwidth of 1.4 MHz.

TABLE-US-00004 TABLE 4 The design of DCI format 2D

Total Field	Payload Size [bit]	Size [bit]	Field Name
Carrier indicator	3	35	Resource allocation header
Resource block assignment	6		TPC command for PUCCH
2			Downlink Assignment Index
0			HARQ process number
3			Antenna port(s), scrambling
3			identity and number of layers
SRS request	0		TB1 Modulation and coding scheme
5			TB1 New data indicator
1			TB1 Redundancy version
2			TB2 Modulation and coding scheme
5			TB2 New data indicator
1			TB2 Redundancy version
2			PDSCH RE Mapping and Quasi-Co-Location Indicator
			HARQ-ACK resource offset
0			

[0041] Based on Table 1, the size of SL SPS DCI is 24 bits for the bandwidth of 20 MHz. Based on Table 2, the size of DCI format 0 is 23 bits for the bandwidth of 1.4 MHz. In addition, based on Table 4, the size of DCI format 2D is 35 bits for the bandwidth of 1.4 MHz. Since DCI format 2D is well known by those skilled in the art, the detailed design thereof for other bandwidths will not be given here for avoiding confusion of the inventive point of the present disclosure. In this case, the size of SL SPS DCI is larger than that of DCI format 0 and smaller than that of DCI format 2D.

It is possible to increase bits in SL SPS DCI by 11 bits to align the size of SL SPS DCI with that of DCI format 2D. Thereby, blind detection times at UE side are not increased due to introducing SPS SL DCI, meanwhile the two Uu DCIs (DCI format 0 and DCI format 2D) are not impacted in all respects of size, content and coverage.

[0042] By increasing bits in the DCI of the first group to align the size of the DCI of the first group with the selected DCI of the second group, blind detection times at the user equipment can be reduced without impacting the second group of DCIs.

[0043] According to an embodiment of the present disclosure, in the wireless communication method **20** as shown in FIG. 2, although not shown in FIG. 2, the above sub-step may comprise: padding bits to the DCI of the first group or increasing CRC (Cyclic Redundancy Check) size in the DCI of the first group.

[0044] Specifically, in the first example, SL SPS DCI may be padded with 11 “0” bits to align with DCI format 2D. It is noted that the padded bits are not limited to “0”, and may be “1” or any other suitable bits.

[0045] Alternatively, it is also possible to increase CRC size in SL SPS DCI by 11 bits to align with DCI format 2D. In this case, by increasing CRC size, the accuracy and integrity of data transmission will be further improved while reducing blind detection times at UE side.

[0046] It is noted that, the above manners of increasing bits in the DCI of the first group so as to align with the selected DCI of the second group are only examples, the present disclosure is not limited thereto, and those skilled in the art may employ any other suitable manners.

[0047] According to an embodiment of the present disclosure, in the wireless communication method **20** as shown in FIG. 2, the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes smaller than the size of the DCI of the first group. And, although not shown in FIG. 2, in step **S201**, aligning one of the size of the DCI of the first group and the size of the selected DCI of a second group of DCIs with the other may comprises a sub-step of reducing bits in the DCI of the first group, wherein the number of the reduced bits equals to the difference between the size of the DCI of the first group and that of the selected DCI of the second group.

[0048] For convenience of understanding, the above first example is still taken as an example. Although the size of SL SPS DCI is aligned with that of DCI format 2D in the above description, the present disclosure is not limited thereto. It is also possible to align the size of SL SPS DCI with that of DCI format 0 by reducing 1 bit in SL SPS DCI. Similarly, blind detection times at UE side are not increased due to introducing SPS SL DCI, meanwhile the two Uu DCIs (DCI format 0 and DCI format 2D) are not impacted in all respects of size, content and coverage.

[0049] Thus, by reducing bits in the DCI of the first group to align the size of the DCI of the first group with the selected DCI of the second group, blind detection times at the user equipment can be reduced without impacting the second group of DCIs.

[0050] According to an embodiment of the present disclosure, in the wireless communication method **20** as shown in FIG. 2, although not shown in FIG. 2, the above sub-step may comprise: restricting the number of bits in at least one field in the DCI of the first group or by increasing the granularity of resource allocation in the DCI of the first group.

[0051] Specifically, it is possible to specify, for example in a standard, some restriction on field usage in SL DCI for some special case, for example, when SL refers to a larger bandwidth such as 20 MHz and Uu refers to a smaller bandwidth such as 1.4 MHz. More specifically, in the first example, since SL SPS DCI refers to sidelink channel of bandwidth of 20 MHz and two Uu DCIs refer to Uu channel of bandwidth of 1.4 MHz, it can be specified that the field of “SPS configuration index” in SL SPS DCI is squeezed to 2 bits from the default 3 bits as shown in Table 1. Thereby, the total payload size of SL SPS DCI can be reduced to be 23 bits which is equivalent to that of DCI format 0.

[0052] Alternatively, since the larger the granularity of resource allocation in DCI, the smaller the



size of the DCI, the granularity of resource allocation in SL SPS DCI may be increased to reduce 1 bit in SL SPS DCI. More specifically, the configured sub-channel size should be larger than 6 PRBs for SL SPS DCI in the first example for example.

[0053] It is noted that, the above manners of reducing bits in the DCI of the first group so as to align with the selected DCI of the second group are only examples, the present disclosure is not limited thereto, and those skilled in the art may employ any other suitable manners.

[0054] The above first example only gives a simple case in which there is only one SL DCI. In the following, a more complicated case is given by a second example. In the second example, it is assumed that a UE is to receive two Uu uplink DCIs in which one is used for CP-OFDM (Cyclic Prefix-Orthogonal Frequency Division Multiplexing) based uplink transmission and the other is used for DFT-S-OFDM (Discrete Fourier Transform-Spread-OFDM) based uplink transmission. And, the UE is also assumed to receive two SL DCIs in which one is used for dynamic scheduling and the other is used for SL SPS.

[0055] In order for convenience of explanation, the two Uu DCIs are represented by DCI1\_uu and DCI2\_uu and the two SL DCIs are indicated by DCI3\_SL and DCI4\_SL. In addition, the size relation of these four DCIs can be expressed as  $\text{DCI1\_uu} > \text{DCI4\_SL} > \text{DCI2\_uu} > \text{DCI3\_SL}$ . In this case, based on the wireless communication method **40** shown in FIG. 2, one option is to align the size of DCI4\_SL with that of DCI1\_uu by for example padding bits to DCI4\_SL and to align the size of DCI3\_SL with that of DCI2\_uu by for example padding bits to DCI3\_SL. Thereby, as described above, different SL DCIs are aligned with different Uu DCIs.

[0056] It is known that padding more bits will result in increased overhead and increased error rate. Since DCI4\_SL is aligned with its smallest larger Uu DCI (i.e. DCI1\_uu) meanwhile DCI3\_SL is aligned with its smallest larger Uu DCI (i.e. DCI2\_uu), minimum bits padded to each SL DCI can be kept. Thereby, the size increase of SL DCIs is minimized. Meanwhile, blind detection times at UE side are also not changed compared with the case without SL DCIs.

[0057] Similarly with the first example, in the second example, the another option may be to align DCI4\_SL with that of its largest smaller Uu DCI (i.e. DCI2\_uu) by reducing bits in DCI4\_SL and to align the size of DCI3\_SL with that of its smallest larger Uu DCI (i.e. DCI2\_uu) by increasing bits in DCI3\_SL.

[0058] In the above first and second examples, the size of SL DCI is aligned with that of Uu DCI by either increasing or reducing bits in SL DCI. However, the present disclosure is not limited thereto. In NR/5G cases, it is also possible to align the size of Uu DCI with that of SL DCI.

[0059] According to an embodiment of the present disclosure, in the wireless communication method **20** as shown in FIG. 2, the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes smaller than the size of the DCI of the first group. And, although not shown in FIG. 2, in step **S201**, aligning one of the size of the DCI of the first group and the size of the selected DCI of a second group of DCIs with the other may comprises a sub-step of adding bits to the selected DCI of the second group, wherein the number of the added bits equals to the difference between the size of the DCI of the first group and that of the selected DCI of the second group.

[0060] For convenience of understanding, the description is made based on a third example. In the third example, it is assumed that a UE is to receive two Uu DCIs in which one is TM specific DCI and the other is fallback DCI. And, the UE is also assumed to receive two SL DCIs in which one is used for dynamic scheduling and the other is used for SL SPS.

[0061] In order to convenience of explanation, as in the second example, the two Uu DCIs are also represented by DCI1\_uu and DCI2\_uu and the two SL DCIs are also indicated by DCI3\_SL and DCI4\_SL. Different from the second example, in the third example, the size relation of these four DCIs can be expressed as  $\text{DCI4\_SL} > \text{DCI3\_SL} > \text{DCI1\_uu} > \text{DCI2\_uu}$ . In this case, based on the above sub-step, firstly, for DCI4\_SL, since DCI1\_uu is the largest smaller Uu DCI, it is possible to align the size of DCI1\_uu with that of DCI4\_SL by adding bits to DCI1\_uu, which is different

from the above first and second examples. Secondly, for DCI3\_SL, since DCI1\_uu is also the largest smaller Uu DCI, the size alignment should also be performed between DCI3\_SL and DCI1\_uu, which is equivalent to that the size of DCI3\_SL is aligned with that of DCI4\_SL by increasing bits in DCI3\_SL. In summary, both the size of DCI1\_uu and the size of DCI3\_SL are aligned with that of DCI4\_SL. Thereby, the fallback DCI (DCI2\_uu) keeps unchanged, that is to say, the content, size and coverage thereof is kept. Meanwhile, by aligning both the size of DCI1\_uu and the size of DCI3\_SL with that of DCI4\_SL, blind detection times at UE side can be reduced.

[0062] Alternatively, another option for the third example may be aligning the sizes of all of DCI3\_SL, DCI1\_uu and DCI2\_uu with that of DCI4\_SL. In this case, the blind detection times at UE side may be smallest.

[0063] Based on the third example, it can be seen that all of Uu DCIs or at least TM specific Uu DCIs is aligned in size with the largest SL DCI if none of Uu DCIs has larger size than that of any SL DCI. However, this is only two possible manner of size alignment of DCIs, the present disclosure is not limited thereto, and those skilled in the art may employ any other suitable manner size alignment of DCIs. For example, both the size of DCI1\_uu and the size of DCI2\_uu or only the size of DCI1\_uu may be aligned with DCI3\_SL by adding bits thereto, meanwhile the size of DCI4\_SL may be aligned with that of DCI3\_SL by reducing bits in DCI4\_SL.

[0064] Thus, by adding bits to the selected DCI of the second group to align the size of the selected DCI of the second group with the DCI of the first group, blind detection times at the user equipment can be reduced.

[0065] According to an embodiment of the present disclosure, in the wireless communication method **20** as shown in FIG. 2, although not shown in FIG. 2, the above sub-step may comprise: padding bits to the selected DCI of the second group or increasing the number of bits in at least one field in the selected DCI.

[0066] For example, in the third example, it is possible to pad bits such as “0”, “1” or any other bits to DCI1\_uu so as to align the size of DCI1\_uu with that of DCI4\_uu. Also, for the another option as described above, it is possible to pad bits such as “0”, “1” or any other bits to DCI2\_uu so as to align the size of DCI2\_uu with that of DCI4\_uu.

[0067] Alternatively, as for SL DCI, it is also possible to specify, for example in a standard, some restriction on field usage in Uu DCI for some special case, for example, when SL refers to larger bandwidth such as 20 MHz and Uu refers to smaller bandwidth such as 1.4 MHz. More specifically, it can be specified that only 2 or 3 bits instead of default 1 bit can be configured for the field of “CSI request” in this case. Thereby, the number of bits in Uu DCI may be increased. Also, similarly with SL DCI, it is also possible to increase CRC size in Uu DCI so as to add bits to Uu DCI.

[0068] Furthermore, a fourth example as an extension to the first example and a general case is further described below for facilitating understanding of the present disclosure. In the fourth example, a UE is assumed to receive at least two Uu DCIs represented as DCI1\_uu and DCI2\_uu, and to receive at least one SL DCI indicated by DCI3\_SL. there are at least three possible size relations among these three DCIs. The first size relation is assumed to be  $DCI1\_uu > DCI3\_SL > DCI2\_uu$ , which corresponds to the case in the first example for instance. In this case, as described above, one option is to align the size of DCI3\_SL with that of DCI1\_uu by increasing bits in DCI3\_SL. Another option is to align the size of DCI3\_SL with that of DCI2\_uu by reducing bits in DCI3\_SL. A further option is to align the size of DCI2\_uu with that of DCI3\_SL by adding bits to DCI2\_uu.

[0069] The second size relation is assumed to be  $DCI1\_uu > DCI2\_uu > DCI3\_SL$ . In this case, the size of DCI3\_SL is aligned with that of DCI2\_uu by increasing bits in DCI3\_SL.

[0070] The third size relation is assumed to be  $DCI3\_SL > DCI1\_uu > DCI2\_uu$ . In this case, one option is to align the size of DCI1\_uu with that of DCI3\_SL by adding bits to DCI1\_uu. Another

option is to align the size of DCI3\_SL with that of DCI1\_uu by reducing bits in DCI3\_SL. For the one option, it is also possible to further align the size of DCI2\_uu with that of DCI3\_SL by adding bits to DCI2\_uu, which will result in smallest times of blind detection at UE side.

[0071] It is noted that, although SL DCIs and Uu DCIs are described in the above examples, the present disclosure is not limited thereto, the first group of DCIs can be other types of DCIs than SL DCIs and the second group of DCIs can be other types of DCIs than Uu DCIs. Also, although not given in the above, the selected DCI of the second group may also be aligned with that of the DCI of the first group by reducing bits depending on specific cases.

[0072] In the above, the wireless communication method **20** is described in detail with reference to FIGS. **1-2**. With the wireless communication method **20**, by performing the size alignment between each DCI of the first group of DCIs and the selected DCI of the second group whose size is closest to that of each DCI of the first group, blind detection times at the user equipment can be reduced while minimizing the size change of DCIs.

[0073] In another embodiment of the present disclosure, there is provided a wireless communication method **30** for a user equipment as shown in FIG. **3**. FIG. **3** illustrates a flowchart of a wireless communication method **30** for a user equipment according to another embodiment of the present disclosure.

[0074] As shown in FIG. **3**, the wireless communication method **30** starts at step **S301** in which a first group of DCIs and a second group of DCIs is received from a base station. Then, at step **S302**, the first group of DCIs and the second group of DCIs is detected blindly so as to perform transmission and/or reception based on a rule which is known by the base station and the user equipment beforehand. After step **S702**, the wireless communication method **30** ends. Said rule indicates that before being received by the user equipment, the first group of DCIs and the second group of DCIs has been subject to size alignment comprising: aligning, for each DCI of the first group of DCIs, one of the size of the DCI of the first group and the size of a selected DCI of the second group of DCIs with the other based on said rule, if the size of the DCI of the first group is different from the size of each DCI of the second group of DCIs, wherein the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes larger than the size of the DCI of the first group or a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes smaller than the size of the DCI of the first group. For example, the wireless communication method **30** may be applied to vehicles **102** and **130** as shown in FIG. **1**.

[0075] According to an embodiment of the present disclosure, in the wireless communication method **30** as shown in FIG. **3**, the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes larger than the size of the DCI of the first group, and said aligning one of the size of the DCI of the first group and the size of the selected DCI of a second group of DCIs with the other comprises: increasing bits in the DCI of the first group, and the number of the increased bits equals to the difference between the size of the DCI of the first group and that of the selected DCI of the second group.

[0076] According to an embodiment of the present disclosure, in the wireless communication method **30** as shown in FIG. **3**, said increasing bits in the DCI of the first group comprises: padding bits to the DCI of the first group or increasing CRC size in the DCI of the first group.

[0077] According to an embodiment of the present disclosure, in the wireless communication method **30** as shown in FIG. **3**, the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes smaller than the size of the DCI of the first group, and said aligning one of the size of the DCI of the first group and the size of the selected DCI of a second group of DCIs with the other comprises: reducing bits in the DCI of the first group, and the number of the reduced bits equals to the difference between the size of the DCI of the first group and that of the selected DCI of the second group.

[0078] According to an embodiment of the present disclosure, in the wireless communication

method **30** as shown in FIG. 3, said reducing bits in the DCI of the first group comprises: restricting the number of bits in at least one field in the DCI of the first group or increasing the granularity of resource allocation in the DCI of the first group.

[0079] According to an embodiment of the present disclosure, in the wireless communication method **30** as shown in FIG. 3, the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes smaller than the size of the DCI of the first group, and said aligning one of the size of the DCI of the first group and the size of the selected DCI of a second group of DCIs with the other comprises: adding bits to the selected DCI of the second group, wherein the number of the added bits equals to the difference between the size of the DCI of the first group and that of the selected DCI of the second group.

[0080] According to an embodiment of the present disclosure, in the wireless communication method **30** as shown in FIG. 3, said adding bits to the selected DCI of the second group comprising: padding bits to the selected DCI of the second group or increasing the number of bits in at least one field in the selected DCI.

[0081] According to an embodiment of the present disclosure, in the wireless communication method **30** as shown in FIG. 3, the first group of DCIs are DCIs for scheduling sidelink transmission between the user equipment and another user equipment, and the second group of DCIs are DCIs for scheduling transmission between the user equipment and the base station.

[0082] With the wireless communication method **30**, by performing the size alignment between each DCI of the first group of DCIs and the selected DCI of the second group whose size is closest to that of the each DCI of the first group, blind detection times at the user equipment can be reduced while minimizing the size change of DCIs.

[0083] In a further embodiment of the present disclosure, there is provided a base station **400** as shown in FIG. 4. FIG. 4 illustrates a block diagram of a base station **400** according to a further embodiment of the present disclosure.

[0084] As shown in FIG. 4, the base station **400** includes: a circuitry **401** operative to align, for each DCI (Downlink Control Information) of a first group of DCIs, one of the size of the DCI of the first group and the size of a selected DCI of a second group of DCIs with the other, if the size of the DCI of the first group is different from the size of each DCI of the second group of DCIs, wherein the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes larger than the size of the DCI of the first group or a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes smaller than the size of the DCI of the first group; and a transmitter **402** operative to transmit the first group of DCIs and the second group of DCIs after the size alignment by the circuitry to a user equipment. The size alignment is based on a rule which is known by the base station and the user equipment beforehand.

[0085] The base station **400** according to the present embodiment may further include a CPU (Central Processing Unit) **410** for executing related programs to process various data and control operations of respective units in the base station **400**, a ROM (Read Only Memory) **413** for storing various programs required for performing various process and control by the CPU **410**, a RAM (Random Access Memory) **415** for storing intermediate data temporarily produced in the procedure of process and control by the CPU **410**, and/or a storage unit **417** for storing various programs, data and so on. The above circuitry **401**, transmitter **402**, CPU **410**, ROM **413**, RAM **415** and/or storage unit **417** etc. may be interconnected via data and/or command bus **420** and transfer signals between one another.

[0086] Respective units as described above do not limit the scope of the present disclosure. According to one embodiment of the disclosure, the functions of the above circuitry **401** and transmitter **402** may be implemented by hardware, and the above CPU **410**, ROM **413**, RAM **415** and/or storage unit **417** may not be necessary. Alternatively, part or all of functions of the above circuitry **401** or transmitter **402** may also be implemented by functional software in combination

with the above CPU **410**, ROM **413**, RAM **415** and/or storage unit **417** etc.

[0087] Specifically, the base station **400** may be eNodeB **101** shown in FIG. **1** and may perform the wireless communication method **20** as described above in conjunction with FIG. **2**.

[0088] With the base station **400**, by performing the size alignment between each DCI of the first group of DCIs and the selected DCI of the second group whose size is closest to that of the each DCI of the first group, blind detection times at the user equipment can be reduced while minimizing the size change of DCIs.

[0089] Note that, the other technical features in the above wireless communication method **20** can also be incorporated in the base station **400** and will not be described here for avoid redundancy.

[0090] In another embodiment of the present disclosure, there is provided a user equipment **500** as shown in FIG. **5**. FIG. **5** illustrates a block diagram of a user equipment **500** according to another embodiment of the present disclosure.

[0091] As shown in FIG. **5**, the user equipment **500** includes: a receiver **501** operative to receive a first group of DCIs and a second group of DCIs from a base station; and a circuitry **302** operative to blindly detect the first group of DCIs and the second group of DCIs so as to perform transmission and/or reception based on a rule which is known by the base station and the user equipment beforehand. And, said rule indicates that before being received by the user equipment, the first group of DCIs and the second group of DCIs has been subject to size alignment comprising: aligning, for each DCI of the first group of DCIs, one of the size of the DCI of the first group and the size of a selected DCI of the second group of DCIs with the other based on said rule, if the size of the DCI of the first group is different from the size of each DCI of the second group of DCIs, wherein the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes larger than the size of the DCI of the first group or a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes smaller than the size of the DCI of the first group.

[0092] The user equipment **500** according to the present embodiment may further include a CPU (Central Processing Unit) **510** for executing related programs to process various data and control operations of respective units in the user equipment **500**, a ROM (Read Only Memory) **513** for storing various programs required for performing various process and control by the CPU **510**, a RAM (Random Access Memory) **515** for storing intermediate data temporarily produced in the procedure of process and control by the CPU **510**, and/or a storage unit **517** for storing various programs, data and so on. The above receiver **501**, circuitry **502**, CPU **510**, ROM **513**, RAM **515** and/or storage unit **517** etc. may be interconnected via data and/or command bus **520** and transfer signals between one another.

[0093] Respective units as described above do not limit the scope of the present disclosure.

According to one embodiment of the disclosure, the functions of the above receiver **501** and circuitry **502** may be implemented by hardware, and the above CPU **510**, ROM **513**, RAM **515** and/or storage unit **517** may not be necessary. Alternatively, part or all of functions of the above receiver **501** and/or circuitry **502** may also be implemented by functional software in combination with the above CPU **510**, ROM **513**, RAM **515** and/or storage unit **517** etc.

[0094] Specifically, the user equipment **500** may be vehicles **102** and **103** shown in FIG. **1** and may perform the wireless communication method **30** as described above in conjunction with FIG. **3**.

[0095] With the user equipment **500**, by performing the size alignment between each DCI of the first group of DCIs and the selected DCI of the second group whose size is closest to that of the each DCI of the first group, blind detection times at the user equipment can be reduced while minimizing the size change of DCIs.

[0096] Note that, the other technical features in the above wireless communication method **30** can also be incorporated in the user equipment **500** and will not be described here for avoid redundancy.

[0097] The present disclosure can be realized by software, hardware, or software in cooperation

with hardware. Each functional block used in the description of each embodiment described above can be realized by an LSI as an integrated circuit, and each process described in the each embodiment may be controlled by LSI. They may be individually formed as chips, or one chip may be formed so as to include a part or all of the functional blocks. They may include a data input and output coupled thereto. The LSI here may be referred to as an IC, a system LSI, a super LSI, or an ultra LSI depending on a difference in the degree of integration. However, the technique of implementing an integrated circuit is not limited to the LSI and may be realized by using a dedicated circuit or a general-purpose processor. In addition, a FPGA (Field Programmable Gate Array) that can be programmed after the manufacture of the LSI or a reconfigurable processor in which the connections and the settings of circuits cells disposed inside the LSI can be reconfigured may be used.

[0098] It is noted that the present disclosure intends to be variously changed or modified by those skilled in the art based on the description presented in the specification and known technologies without departing from the content and the scope of the present disclosure, and such changes and applications fall within the scope that claimed to be protected.

[0099] Furthermore, in a range not departing from the content of the disclosure, the constituent elements of the above-described embodiments may be arbitrarily combined.

[0100] Embodiments of the present disclosure can at least provide the following subject matters.

[0101] (1). A Base Station, Comprising: [0102] circuitry operative to align, for each DCI (Downlink Control Information) of a first group of DCIs, one of the size of the DCI of the first group and the size of a selected DCI of a second group of DCIs with the other, if the size of the DCI of the first group is different from the size of each DCI of the second group of DCIs, wherein the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes larger than the size of the DCI of the first group or a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes smaller than the size of the DCI of the first group; and [0103] a transmitter operative to transmit the first group of DCIs and the second group of DCIs after the size alignment by the circuitry to a user equipment, [0104] wherein the size alignment is based on a rule which is known by the base station and the user equipment beforehand.

[0105] (2). The base station according to (1), wherein the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes larger than the size of the DCI of the first group, and [0106] wherein the circuitry further increases bits in the DCI of the first group, and the number of the increased bits equals to the difference between the size of the DCI of the first group and that of the selected DCI of the second group.

[0107] (3). The base station according to (2), wherein the circuitry increases bits in the DCI of the first group by padding bits or increasing CRC (Cyclic Redundancy Check) size.

[0108] (4). The base station according to (1), wherein the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes smaller than the size of the DCI of the first group, and wherein the circuitry further reduces bits in the DCI of the first group, and the number of the reduced bits equals to the difference between the size of the DCI of the first group and that of the selected DCI of the second group.

[0109] (5). The base station according to (4), wherein the circuitry reduces bits in the DCI of the first group by restricting the number of bits in at least one field in the DCI of the first group or by increasing the granularity of resource allocation in the DCI of the first group.

[0110] (6). The base station according to (1), wherein the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes smaller than the size of the DCI of the first group, and [0111] wherein the circuitry further adds bits to the selected DCI of the second group, and the number of the added bits equals

to the difference between the size of the DCI of the first group and that of the selected DCI of the second group.

[0112] (7). The base station according to (6), wherein the circuitry adds bits to the selected DCI of the second group by padding bits or by increasing the number of bits in at least one field in the selected DCI.

[0113] (8). The base station according to (1), wherein the first group of DCIs are DCIs for scheduling sidelink transmission between the user equipment and another user equipment, and the second group of DCIs are DCIs for scheduling transmission between the user equipment and the base station.

[0114] (9). A user equipment, comprising: [0115] a receiver operative to receive a first group of DCIs and a second group of DCIs from a base station; and [0116] a circuitry operative to blindly detect the first group of DCIs and the second group of DCIs so as to perform transmission and/or reception based on a rule which is known by the base station and the user equipment beforehand, [0117] wherein said rule indicates that before being received by the user equipment, the first group of DCIs and the second group of DCIs has been subject to size alignment comprising: aligning, for each DCI of the first group of DCIs, one of the size of the DCI of the first group and the size of a selected DCI of the second group of DCIs with the other based on said rule, if the size of the DCI of the first group is different from the size of each DCI of the second group of DCIs, wherein the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes larger than the size of the DCI of the first group or a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes smaller than the size of the DCI of the first group.

[0118] (10). The user equipment according to (9), wherein the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes larger than the size of the DCI of the first group, and [0119] wherein said aligning one of the size of the DCI of the first group and the size of the selected DCI of a second group of DCIs with the other comprises: [0120] increasing bits in the DCI of the first group, and the number of the increased bits equals to the difference between the size of the DCI of the first group and that of the selected DCI of the second group.

[0121] (11). The user equipment according to (10), wherein said increasing bits in the DCI of the first group comprises: [0122] padding bits to the DCI of the first group or increasing CRC size in the DCI of the first group.

[0123] (12). The user equipment according to (9), wherein the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes smaller than the size of the DCI of the first group, and [0124] wherein said aligning one of the size of the DCI of the first group and the size of the selected DCI of a second group of DCIs with the other comprises: [0125] reducing bits in the DCI of the first group, and the number of the reduced bits equals to the difference between the size of the DCI of the first group and that of the selected DCI of the second group.

[0126] (13). The user equipment according to (12), wherein said reducing bits in the DCI of the first group comprises: [0127] restricting the number of bits in at least one field in the DCI of the first group or increasing the granularity of resource allocation in the DCI of the first group.

[0128] (14). The user equipment according to (9), wherein the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes smaller than the size of the DCI of the first group, and [0129] wherein said aligning one of the size of the DCI of the first group and the size of the selected DCI of a second group of DCIs with the other comprises: [0130] adding bits to the selected DCI of the second group, wherein the number of the added bits equals to the difference between the size of the DCI of the first group and that of the selected DCI of the second group.

[0131] (15). The user equipment according to (14), wherein said adding bits to the selected DCI of

the second group comprising: [0132] padding bits to the selected DCI of the second group or increasing the number of bits in at least one field in the selected DCI.

[0133] (16). The user equipment according to (9), wherein the first group of DCIs are DCIs for scheduling sidelink transmission between the user equipment and another user equipment, and the second group of DCIs are DCIs for scheduling transmission between the user equipment and the base station.

[0134] (17). A wireless communication method for a base station, comprising: [0135] aligning, for each DCI (Downlink Control Information) of a first group of DCIs, one of the size of the DCI of the first group and the size of a selected DCI of a second group of DCIs with the other, if the size of the DCI of the first group is different from the size of each DCI of the second group of DCIs, wherein the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes larger than the size of the DCI of the first group or a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes smaller than the size of the DCI of the first group; and [0136] transmitting the first group of DCIs and the second group of DCIs after the size alignment to a user equipment, [0137] wherein the size alignment is based on a rule which is known by the base station and the user equipment beforehand.

[0138] (18). The wireless communication method according to (17), wherein the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes larger than the size of the DCI of the first group, and [0139] wherein said aligning one of the size of the DCI of the first group and the size of the selected DCI of a second group of DCIs with the other comprises: [0140] increasing bits in the DCI of the first group, wherein the number of the increased bits equals to the difference between the size of the DCI of the first group and that of the selected DCI of the second group.

[0141] (19). The wireless communication method according to (18), wherein said increasing bits in the DCI of the first group comprises: [0142] padding bits to the DCI of the first group or increasing CRC (Cyclic Redundancy Check) size in the DCI of the first group.

[0143] (20). The wireless communication method according to (17), wherein the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes smaller than the size of the DCI of the first group, and [0144] wherein said aligning one of the size of the DCI of the first group and the size of the selected DCI of a second group of DCIs with the other comprises: [0145] reducing bits in the DCI of the first group, wherein the number of the reduced bits equals to the difference between the size of the DCI of the first group and that of the selected DCI of the second group.

[0146] (21). The wireless communication method according to (20), wherein said reducing bits in the DCI of the first group comprises: [0147] restricting the number of bits in at least one field in the DCI of the first group or increasing the granularity of resource allocation in the DCI of the first group.

[0148] (22). The wireless communication method according to (17), wherein the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes smaller than the size of the DCI of the first group, and [0149] wherein said aligning one of the size of the DCI of the first group and the size of the selected DCI of a second group of DCIs with the other comprises: [0150] adding bits to the selected DCI of the second group, wherein the number of the added bits equals to the difference between the size of the DCI of the first group and that of the selected DCI of the second group.

[0151] (23). The wireless communication method according to (22), wherein said adding bits to the selected DCI of the second group comprising: [0152] padding bits to the selected DCI of the second group or increasing the number of bits in at least one field in the selected DCI.

[0153] (24). The wireless communication method according to (17), wherein the first group of DCIs are DCIs for scheduling sidelink transmission between the user equipment and another user



equipment, and the second group of DCIs are DCIs for scheduling transmission between the user equipment and the base station.

[0154] (25). A wireless communication method for a user equipment, comprising: [0155] receiving a first group of DCIs and a second group of DCIs from a base station; and [0156] detecting blindly the first group of DCIs and the second group of DCIs so as to perform transmission and/or reception based on a rule which is known by the base station and the user equipment beforehand, [0157] wherein said rule indicates that before being received by the user equipment, the first group of DCIs and the second group of DCIs has been subject to size alignment comprising: aligning, for each DCI of the first group of DCIs, one of the size of the DCI of the first group and the size of a selected DCI of the second group of DCIs with the other based on said rule, if the size of the DCI of the first group is different from the size of each DCI of the second group of DCIs, wherein the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes larger than the size of the DCI of the first group or a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes smaller than the size of the DCI of the first group.

[0158] (26). The wireless communication method according to (25), wherein the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes larger than the size of the DCI of the first group, and [0159] wherein said aligning one of the size of the DCI of the first group and the size of the selected DCI of a second group of DCIs with the other comprises: [0160] increasing bits in the DCI of the first group, and the number of the increased bits equals to the difference between the size of the DCI of the first group and that of the selected DCI of the second group.

[0161] (27). The wireless communication method according to (26), wherein said increasing bits in the DCI of the first group comprises: [0162] padding bits to the DCI of the first group or increasing CRC size in the DCI of the first group.

[0163] (28). The wireless communication method according to (25), wherein the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes smaller than the size of the DCI of the first group, and [0164] wherein said aligning one of the size of the DCI of the first group and the size of the selected DCI of a second group of DCIs with the other comprises: [0165] reducing bits in the DCI of the first group, and the number of the reduced bits equals to the difference between the size of the DCI of the first group and that of the selected DCI of the second group.

[0166] (29). The wireless communication method according to (28), wherein said reducing bits in the DCI of the first group comprises: [0167] restricting the number of bits in at least one field in the DCI of the first group or increasing the granularity of resource allocation in the DCI of the first group.

[0168] (30). The wireless communication method according to (25), wherein the selected DCI of the second group is a DCI whose size is closest to the size of the DCI of the first group among DCIs of the second group having sizes smaller than the size of the DCI of the first group, and [0169] wherein said aligning one of the size of the DCI of the first group and the size of the selected DCI of a second group of DCIs with the other comprises: [0170] adding bits to the selected DCI of the second group, wherein the number of the added bits equals to the difference between the size of the DCI of the first group and that of the selected DCI of the second group.

[0171] (31). The wireless communication method according to (30), wherein said adding bits to the selected DCI of the second group comprising: [0172] padding bits to the selected DCI of the second group or increasing the number of bits in at least one field in the selected DCI.

[0173] (32). The wireless communication method according to (25), wherein the first group of DCIs are DCIs for scheduling sidelink transmission between the user equipment and another user equipment, and the second group of DCIs are DCIs for scheduling transmission between the user equipment and the base station.

## Claims

1. An integrated circuit, comprising: reception circuitry, which, in operation, control receiving in a search space, downlink control information (DCI) with a first DCI format used for sidelink communications; and decoding circuitry, which, in operation, controls a decoding process of the DCI by using a reference size; wherein, when a second DCI format used for base station communications is mapped on the search space and the second DCI format is larger than the first DCI format, the reference size for the search space is based on the second DCI format, and when a third DCI format used for sidelink communications is mapped on the search space and the third DCI format is larger than the first DCI format, and the second DCI format larger than the third DCI format is not mapped on the search space, the reference size for the search space is based on the third DCI format.
  2. The integrated circuit according to claim 1, wherein one of the first DCI format and the third DCI format is used for a dynamic scheduling and the other of the first DCI format and the third DCI format is used for a semi-persistent scheduling (SPS).
  3. The integrated circuit according to claim 1, wherein a size of the second DCI format is a nearest size to a size of the first DCI format, the nearest size being equal to or greater than the size of the first DCI format.
  4. The integrated circuit according to claim 1, wherein a size of the third DCI format is a nearest size to a size of the first DCI format, the nearest size being equal to or greater than the size of the first DCI format.
  5. The integrated circuit according to claim 1, wherein zeros of padding bits are added to the first DCI format until a size of the first DCI format with the padding bits equals the reference size.
-