

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12386285
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Sato; Shougo

Image forming apparatus capable of facilitating toner replenishment to toner supply unit

Abstract

An image forming apparatus includes a main casing, a developing roller, a connecting tube, and a toner container. The main casing includes a sheet supply tray. The developing roller is provided in the main casing. The connecting tube has one end portion and another end portion inside the main casing. The toner container is for accommodating toner. The one end portion of the connecting tube is connected to the toner container. The toner container has an inlet opening for replenishing toner. The toner container is pivotally movable between a first position and a second position about the connecting tube. A position of the inlet opening at the second position is higher than a position of the inlet opening at the first position.

Inventors:	Sato; Shougo (Seto, JP)
Applicant:	Brother Kogyo Kabushiki Kaisha (Nagoya, JP)
Family ID:	1000008749715
Assignee:	Brother Kogyo Kabushiki Kaisha (Nagoya, JP)
Appl. No.:	18/739005
Filed:	June 10, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240329565 A1	Oct. 03, 2024

Foreign Application Priority Data

JP	2016-017928	Feb. 02, 2016
----	-------------	---------------

Related U.S. Application Data

continuation parent-doc US 17942290 20220912 US 12044985 child-doc US 18739005
continuation parent-doc US 16810327 20200305 US 11487223 20221101 child-doc US 17942290
continuation parent-doc US 16048543 20180730 US 10599069 20200324 child-doc US 16810327
continuation parent-doc US 15408525 20170118 US 10061230 20180828 child-doc US 16048543

Publication Classification

Int. Cl.: G03G15/08 (20060101)

U.S. Cl.:

CPC G03G15/0891 (20130101); G03G15/0879 (20130101); G03G15/0886 (20130101);

Field of Classification Search

CPC: G03G (15/0891); G03G (15/0822); G03G (15/0874); G03G (15/0886)

USPC: 399/252; 399/258

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4142655	12/1978	Fantuzzo	N/A	N/A
4367954	12/1982	Ganz et al.	N/A	N/A
4641945	12/1986	Ikesue et al.	N/A	N/A
5329340	12/1993	Fukuchi et al.	N/A	N/A
8417160	12/2012	Ishiguro et al.	N/A	N/A
9176425	12/2014	Takami et al.	N/A	N/A
9229422	12/2015	Yamamoto	N/A	G03G 15/0881
9436125	12/2015	Fukushima	N/A	G03G 15/0886
2002/0009310	12/2001	Kabumoto et al.	N/A	N/A
2003/0118368	12/2002	Saito et al.	N/A	N/A
2005/0207797	12/2004	Fujita et al.	N/A	N/A
2007/0223947	12/2006	Ohkawa et al.	N/A	N/A
2008/0170889	12/2007	Eto et al.	N/A	N/A
2010/0272477	12/2009	Nishikawa	N/A	N/A
2011/0064482	12/2010	Ishiguro et al.	N/A	N/A
2014/0248061	12/2013	Takami et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1427312	12/2002	CN	N/A
2681175	12/2004	CN	N/A
101046657	12/2006	CN	N/A
101226363	12/2007	CN	N/A
102023522	12/2010	CN	N/A
104020653	12/2013	CN	N/A
S59-188678	12/1983	JP	N/A

S61-004960	12/1985	JP	N/A
S61-085865	12/1985	JP	N/A
H01-222276	12/1988	JP	N/A
H05-204244	12/1992	JP	N/A
H10-055100	12/1997	JP	N/A
2003-084517	12/2002	JP	N/A
2003-312624	12/2002	JP	N/A
2006-154875	12/2005	JP	N/A
2012-071585	12/2011	JP	N/A
2021250983	12/2020	WO	N/A

OTHER PUBLICATIONS

Oct. 24, 2017—(US) Non-final Office Action—U.S. Appl. No. 15/408,525. cited by applicant
May 2, 2018—(US) Notice of Allowance—U.S. Appl. No. 15/408,525. cited by applicant
Dec. 3, 2018—(US) Non-Final Office Action—U.S. Appl. No. 16/048,543. cited by applicant
May 3, 2019—(US) Final Office Action—U.S. Appl. No. 16/048,543. cited by applicant
Aug. 13, 2019—(US) Final Office Action—U.S. Appl. No. 16/048,543. cited by applicant
Nov. 12, 2019—(US) Notice of Allowance—U.S. Appl. No. 16/048,543. cited by applicant
Nov. 19, 2019—(JP) Office Action—App 2016-017928. cited by applicant
May 12, 2020—(JP) Notice of Reasons for Refusal—App 2016-017928, Eng Tran. cited by applicant
Jul. 1, 2020—(CN) First Office Action—App 201710058468.X. cited by applicant
Aug. 25, 2020—(US) Non-Final Office Action—U.S. Appl. No. 16/810,327. cited by applicant
Apr. 12, 2021—(US) Final Office Action—U.S. Appl. No. 16/810,327. cited by applicant
Mar. 24, 2021—(CN) The Second Office Action—App 201710058468.X. cited by applicant
Aug. 12, 2021—(US) Non-final Office Action—U.S. Appl. No. 16/810,327. cited by applicant
Feb. 18, 2022—(US) Notice of Allowance—U.S. Appl. No. 16/810,327. cited by applicant
Feb. 24, 2022—(CN) The First Office Action—App 202010156129.7. cited by applicant
Jun. 13, 2022—(US) Notice of Allowance—U.S. Appl. No. 16/810,327. cited by applicant
Aug. 9, 2022—(CN) The Second Office Action—App 202010156129.7. cited by applicant
Oct. 31, 2023—(US)—Non-final Office Action—U.S. Appl. No. 17/942,290. cited by applicant
Mar. 13, 2024—(US)—Notice of Allowance—U.S. Appl. No. 17/942,290. cited by applicant

Primary Examiner: Tran; Hoan H

Attorney, Agent or Firm: Banner & Witcoff, Ltd.

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION (1) This application is a continuation of U.S. patent application Ser. No. 17/942,290 filed Sep. 12, 2022 which is a continuation of U.S. patent application Ser. No. 16/810,327 filed Mar. 5, 2020, issued as U.S. Pat. No. 11,487,223 on Nov. 1, 2022, which is a continuation of U.S. patent application Ser. No. 16/048,543 filed Jul. 30, 2018, issued as U.S. Pat. No. 10,599,069 on Mar. 24, 2020, which is a continuation of U.S. patent application Ser. No. 15/408,525 filed Jan. 18, 2017, issued as U.S. Pat. No. 10,061,230 on Aug. 28, 2018, which claims priority from Japanese Patent Application No. 2016-017928 filed Feb. 2, 2016. The entire contents of the priority applications are incorporated herein by reference.

TECHNICAL FIELD

(1) The present disclosure relates to an electrophotographic type image forming apparatus.

BACKGROUND

(2) An ink jet type image forming apparatus having an ejection head for ejecting ink to form an image is known in the art.

(3) According to one kind of the ink jet type image forming apparatus, an ink cartridge system is provided such that a cartridge can be replaced by a new cartridge to replenish ink to a main body of the apparatus. According to another kind of the ink jet type image forming apparatus as described in Japanese Patent Application Publication No. 2012-71585, a liquid supply system is provided in which a user replenishes ink to an ink tank provided at an outside of the image forming apparatus, and the ink replenished in the ink tank is sucked at negative pressure and is supplied to the main body of the image forming apparatus.

SUMMARY

(4) In an electrophotographic type image forming apparatus, similar to the ink jet type image forming apparatus as described in the Japanese Patent Application Publication No. 2012-71585, a demand has been made to provide a toner container to which a user can replenish toner. The replenished toner in the toner container is supplied to a developing device.

(5) It is therefore an object of the disclosure to provide an electrophotographic type image forming apparatus capable of facilitating toner replenishment to a toner supply unit.

(6) In order to attain the above and other objects, according to one aspect, the disclosure provides an image forming apparatus including: a main casing, a developing roller, a connecting tube, and a toner container. The main casing includes a sheet supply tray. The developing roller is provided in the main casing. The connecting tube has one end portion and another end portion inside the main casing. The toner container is for accommodating toner. The one end portion of the connecting tube is connected to the toner container. The toner container has an inlet opening for replenishing toner. The toner container is pivotally movable between a first position and a second position about the connecting tube. A position of the inlet opening at the second position is higher than a position of the inlet opening at the first position.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The particular features and advantages of the disclosure will become apparent from the following description taken in connection with the accompanying drawings, in which:

(2) FIG. 1 is a central cross-sectional view of an image forming apparatus according to a first embodiment;

(3) FIG. 2 is a cross-sectional view taken along a line A-A of FIG. 1;

(4) FIG. 3A is a central cross-sectional view of a process cartridge illustrated in FIG. 1;

(5) FIG. 3B is a cross-sectional view of the process cartridge illustrated in FIG. 3A taken along a plane positioned more rightward of the process cartridge in comparison with the cross-sectional view of FIG. 3A;

(6) FIG. 4 is a cross-sectional side view of a toner supply unit of the image forming apparatus illustrated in FIG. 1 and illustrating a toner container at its first position;

(7) FIG. 5 is a view illustrating the toner container at its second position of the image forming apparatus illustrated in FIG. 4;

(8) FIG. 6 is a view for description of toner replenishment to the toner container positioned at the second position illustrated in FIG. 5;

(9) FIG. 7 is a cross-sectional view of the image forming apparatus illustrated in FIG. 1 and illustrating a connection between the process cartridge and the toner supply unit;

(10) FIG. 8 is a view for description of attachment and detachment of the process cartridge with respect to the image forming apparatus illustrated in FIG. 7, and particularly illustrating grooves formed in an inner wall;

(11) FIG. 9 is a cross-sectional view of an image forming apparatus according to a second embodiment and taken along a plane passing through a toner supply unit and illustrating a toner container at its first position;

(12) FIG. 10 is a view of the image forming apparatus according to the second embodiment, and illustrating the toner container at its second position;

(13) FIG. 11 is a cross-sectional view taken along a line B-B of FIG. 9;

(14) FIG. 12 is a central cross-sectional view of an image forming apparatus according to a third embodiment;

(15) FIG. 13 is a view illustrating the image forming apparatus according to the third embodiment in a state where a drawer is pulled out; and

(16) FIG. 14 is a cross-sectional view taken along a line C-C of FIG. 12.

DETAILED DESCRIPTION

First Embodiment

(17) An image forming apparatus 1 according to a first embodiment will be described with reference to FIGS. 1 through 8. Throughout the description, the reference to “direction” is based on the directions as indicated by arrows in the drawings.

(18) 1. Outline of Image Forming Apparatus

(19) As illustrated in FIGS. 1 and 2, the image forming apparatus 1 is a laser printer including a main casing 2 formed with an opening 7, a process cartridge 3, a toner supply unit 101, a scanner 4, a fixing unit 5, and a reading unit 35.

(20) The main casing 2 is box-shaped and includes a cover 8, a sheet supply tray 9, and a manual insertion tray 22.

(21) The opening 7 is positioned at an upper end portion of the main casing 2. That is, the main casing 2 has an upper wall through which the opening 7 extends vertically. The opening 7 allows the process cartridge 3 to pass therethrough.

(22) The cover 8 is positioned at the upper end portion of the main casing 2, and extends in a frontward/rearward direction. The cover 8 is plate-like shaped, and is pivotally movable about a rear end portion thereof between a closed position (see FIG. 1) closing the opening 7 and an open position (see FIGS. 7 and 8) opening the opening 7. Sheets P discharged from the main casing 2 are loaded onto the cover 8.

(23) The sheet supply tray 9 is positioned at a lower end portion of the main casing 2. The sheet supply tray 9 is adapted to accommodate the sheets P.

(24) The manual insertion tray 22 is positioned at a front end portion of the main casing 2. The manual insertion tray 22 is adapted to support sheet(s) P mounted by a user. The sheet P supplied from the manual insertion tray 22 is conveyed to a portion between a photosensitive drum 13 and a transfer roller 15 through a conveying route different from that from the sheet supply tray 9. The manual insertion tray 22 is pivotally movable about a lower end portion thereof between a support position (see FIG. 7) and an accommodated position (see FIG. 1). The manual insertion tray 22 is foldable at its center portion. As illustrated in FIG. 7, the manual insertion tray 22 extends diagonally upward and frontward from the lower end portion at its support position, so that the sheet(s) P can be mounted on the manual insertion tray 22. As illustrated in FIG. 1, the manual insertion tray 22 is folded rearward so as to cover the upper wall of the main casing 2 when the manual insertion tray 22 is at the accommodated position. The manual insertion tray 22 also covers a front end portion of the cover 8 at its accommodated position.

(25) The process cartridge 3 is mounted to a central portion of the main casing 2. As illustrated in FIG. 8, the process cartridge 3 is attachable to and detachable from the main casing 2 through the opening 7. As illustrated in FIG. 1, the process cartridge 3 includes a drum unit 11 and a developing

unit **12**.

(26) The drum unit **11** includes the photosensitive drum **13**, a charge roller **14** adapted to charge a surface of the photosensitive drum **13**, a charge cleaning roller **20** adapted to remove deposited material such as residual toner and paper dust on the surface of the charge roller **14**, and the transfer roller **15** in contact with the photosensitive drum **13**.

(27) The photosensitive drum **13** is positioned at a rear end portion of the drum unit **11**. The photosensitive drum **13** is cylindrical extending in a leftward/rightward direction.

(28) The developing unit **12** is positioned frontward of the photosensitive drum **13**, and includes a developing roller **16**, a supply roller **17**, and a blade **18**.

(29) The developing roller **16** is positioned at a rear end portion of the developing unit **12**, and is in contact with the surface of the photosensitive drum **13**. The developing roller **16** is adapted to supply toner to the photosensitive drum **13**.

(30) The supply roller **17** is positioned frontward of the developing roller **16** and is in contact with the developing roller **16**. The supply roller **17** is adapted to supply toner to the developing roller **16**.

(31) The blade **18** is positioned frontward of the developing roller **16**. A lower end portion of the blade **18** is positioned above the supply roller **17** so as to contact the developing roller **16**. The blade **18** is adapted to regulate thickness of a toner layer formed on a surface of the developing roller **16**.

(32) As illustrated in FIG. **2**, the toner supply unit **101** is positioned rightward of the process cartridge **3**, and is not detachable from the main casing **2**. The toner supply unit **101** is adapted to supply toner to the developing unit **12** of the process cartridge **3**.

(33) The scanner **4** is positioned frontward of the process cartridge **3**. The scanner **4** is adapted to irradiate laser beam **L** based on image data toward the photosensitive drum **13** to expose the surface of the photosensitive drum **13** to light.

(34) The fixing unit **5** is positioned rearward of the process cartridge **3**, and includes a heat roller **5A** and a pressure roller **5B** in contact with the heat roller **5A**.

(35) The reading unit **35** is positioned above the cover **8** with a space therebetween. The reading unit **35** is a flat-bed type image scanner adapted to read image on an original document. The reading unit **35** is pivotally movable about a rear end portion thereof between a reading position (see FIG. **1**) and a retracted position (see FIG. **7**) retracted upward from the reading position.

(36) **2. Process Cartridge**

(37) **(1) Drum Unit**

(38) As illustrated in FIGS. **3A** and **3B**, the drum unit **11** includes a first side wall **67L**, a second side wall **67R**, a handle **68**, a connecting portion **69**, a drum cleaning unit **65**, and a protruding sleeve **77** formed with a hole **82**.

(39) The first and second side walls **67L** and **67R** are spaced away from each other in the leftward/rightward direction. The first and second side walls **67L**, **67R** are plate shaped extending in the frontward/rearward direction and an upward/downward direction.

(40) The handle **68** is positioned at a front end portion of the drum unit **11**. The handle **68** is pivotally movable relative to the first and second side walls **67L**, **67R**.

(41) The connecting portion **69** is positioned at the front end portion of the drum unit **11**, and includes a connection sleeve **72** formed with a hole **74**, and an engagement portion **73**.

(42) The connection sleeve **72** protrudes rightward from a right surface of the second side wall **67R**, and extends in the leftward/rightward direction. The connection sleeve **72** is generally cylindrical having a closed right end portion.

(43) The hole **74** penetrates a rear end portion of the connection sleeve **72** in the frontward/rearward direction.

(44) The engagement portion **73** extends upward from the connection sleeve **72** at a position above the hole **74**. The engagement portion **73** is curved rearward toward its tip end such that the engagement portion **73** extends along an outer peripheral surface of a connecting tube body **118** of

a connecting tube **116** described later and as illustrated in FIG. 7.

(45) As illustrated in FIGS. 3A and 3B, the drum cleaning unit **65** includes a cleaning member **78**, a waste toner accommodating portion **76** formed with an opening **81**, and a screw **79**.

(46) The cleaning member **78** has a rear end portion in contact with an upper end portion of the peripheral surface of the photosensitive drum **13**.

(47) The waste toner accommodating portion **76** is a hollow tubular shaped extending in the leftward/rightward direction. Each end portion of the waste toner accommodating portion **76** in the leftward/rightward direction is closed. The left end portion and right end portion of the waste toner accommodating portion **76** are connected to the first side wall **67L**, and the second side wall **67R**, respectively.

(48) The opening **81** is positioned at a bottom wall of the waste toner accommodating portion **76**, and extends through a thickness of the bottom wall in the upward/downward direction.

(49) The screw **79** is positioned in the waste toner accommodating portion **76**. The screw **79** is in confrontation with the cleaning member **78** through the opening **81**. The screw **79** is an auger screw extending in the leftward/rightward direction. The screw **79** has a left end portion rotatably supported to the first side wall **67L**, and a right end portion positioned rightward of the second side wall **67R**. The right end portion of the screw **79** is rotatably supported to a right end portion of the protruding sleeve **77**.

(50) The protruding sleeve **77** protrudes rightward from the right surface of the second side wall **67R**, and extends in the leftward/rightward direction. The protruding sleeve **77** extends through the second side wall **67R** in the leftward/rightward direction, and is generally hollow cylindrical having a closed right end portion.

(51) The hole **82** extends through a rear end portion of the protruding sleeve **77** in the frontward/rearward direction.

(52) (2) Developing Unit

(53) As illustrated in FIG. 3A, the developing unit **12** includes a developing frame **86**, a shaft **88**, a first screw **90**, and a second screw **91**.

(54) The developing frame **86** is generally box-shaped extending in the leftward/rightward direction. The developing frame **86** includes a conveying chamber **94** and a developing chamber **95**.

(55) The conveying chamber **94** is positioned at a front end portion of the developing frame **86**, and extends through a right wall of the developing frame **86**. As illustrated in FIGS. 3A and 3B, the conveying chamber **94** is aligned with the connection sleeve **72** of the connecting portion **69** in the leftward/rightward direction. The conveying chamber **94** is in communication with the connecting sleeve **72**. A seal member **97** (see FIG. 2) is interposed between the conveying chamber **94** and the connecting sleeve **72**, i.e., between the developing frame **86** and the second side wall **67R** of the drum unit **11**.

(56) The seal member **97** is generally hollow cylindrical and is adapted to prevent toner from leaking from a portion between the conveying chamber **94** and the connecting sleeve **72**. The seal member **97** is also adapted to connect the conveying chamber **94** and the connecting sleeve **72** to restrain toner leakage from the portion between the conveying chamber **94** and the connecting sleeve **72**, even if the conveying chamber **94** is displaced from the connecting sleeve **72** as viewed in the leftward/rightward direction as a result of pivotal movement of the developing unit **12** relative to the drum unit **11**.

(57) The developing chamber **95** is positioned rearward of the conveying chamber **94**. The developing chamber **95** is in communication with the conveying chamber **94** through a communication opening **96**.

(58) The developing frame **86** supports the developing roller **16**, the supply roller **17**, and the blade **18**. The developing roller **16** has a rear end portion exposed to an outside through the developing frame **86**.

(59) The shaft **88** is positioned at an upper end portion of developing unit **12**, and extends through the developing frame **86** in the leftward/rightward direction. The shaft **88** has a left end portion rotatably supported to the first side wall **67L** of the drum unit **11**, and has a right end portion rotatably supported to the second side wall **67R** of the drum unit **11** as illustrated in FIG. 2.

(60) With this structure, the developing unit **12** is pivotally movable about the shaft **88** relative to the drum unit **11**.

(61) As illustrated in FIGS. 3A and 3B, the first screw **90** is positioned in the conveying chamber **94** of the developing frame **86**. The first screw **90** is an auger screw extending in the leftward/rightward direction. As illustrated in FIG. 2, the first screw **90** has a left end portion rotatably supported to a left wall of the developing frame **86**, and has a right end portion protruding rightward through the right wall of the developing frame **86**. That is, a distal right end of the first screw **90** is positioned rightward of the right wall of the developing frame **86**. The right end portion of the first screw **90** extends through the second side wall **67R** of the drum unit **11**, and is positioned in the connecting sleeve **72** of the drum unit **11**. The right end portion of the first screw **90** is rotatably supported to the right end portion of the connecting sleeve **72**.

(62) As illustrated in FIGS. 3A and 3B, the second screw **91** is positioned in the developing chamber **95** of the developing frame **86**. The second screw **91** is an auger screw extending in the leftward/rightward direction. The second screw **91** has a left end portion rotatably supported to the left wall of the developing frame **86**, and has a right end portion rotatably supported to the right wall of the developing frame **86**.

(63) 3. Main Casing

(64) As illustrated in FIGS. 2 and 8, the main casing **2** includes a first accommodation wall **40L**, a second accommodation wall **40R** formed with holes **42**, a first inner wall **41L** formed with a groove **48**, and a second inner wall **41R** formed with grooves **48**, **49**, and **50**.

(65) The first accommodation wall **40L** constitutes a left wall of the main casing **2**, and extends in the frontward/rearward direction and the upward/downward direction. The first accommodation wall **40L** provides an internal space in which a driving portion **44** for inputting driving force to the photosensitive drum **13**, etc. is accommodated.

(66) As illustrated in FIGS. 2 and 4, the second accommodation wall **40R** constitutes a right wall of the main casing **2**. That is, the second accommodation wall **40R** is positioned rightward of and spaced away from the first accommodation wall **40L**. The second accommodation wall **40R** extends in the frontward/rearward direction and the upward/downward direction. The second accommodation wall **40R** provides an internal space in which a circuit board **45** formed with a hole **46** is accommodated.

(67) As illustrated in FIG. 2, the holes **42** are positioned at a generally center portion of the second accommodation wall **40R** in the frontward/rearward direction. The holes **42** extend through left and right walls of the second accommodation wall **40R** in the leftward/rightward direction. The holes **42** are adapted to allow the connecting tube body **118** of the connecting tube **116** described later to extend therethrough such that the connecting tube body **118** is fitted with the holes **42**.

(68) The circuit board **45** is positioned between the developing unit **12** and a toner container **117** of the toner supply unit **101** described later in the leftward/rightward direction.

(69) The hole **46** extends through the thickness of the circuit board **45**, and is positioned at a position in alignment with the holes **42** of the second accommodation wall **40R** in the leftward/rightward direction. The hole **46** is adapted to allow the connecting tube body **118** of the connecting tube **116** described later to extend therethrough such that the connecting tube body **118** is fitted with the hole **46**.

(70) The first inner wall **41L** is positioned inward of and adjacent to the first accommodation wall **40L** in the leftward/rightward direction.

(71) The groove **48** is recessed outward from an inner surface of the first inner wall **41L** in the leftward/rightward direction. Incidentally, the groove **48** of the first inner wall **41L** is identical to

the groove **48** of the second inner wall **41R**. Therefore, the groove **48** will be further described in detail in the description of the groove **48** of the second inner wall **41R**.

(72) The second inner wall **41R** is positioned leftward of and adjacent to the second accommodation wall **40R**. As illustrated in FIG. **8**, the second inner wall **41R** is plate shaped extending in the frontward/rearward direction and the upward/downward direction.

(73) The groove **48** is adapted to guide a shaft of the photosensitive drum **13** of the process cartridge **3**. The groove **48** is recessed outward from an inner surface of the second inner wall **41R** in the leftward/rightward direction. The groove **48** extends diagonally downward and rearward from a generally center portion of the opening **7** in the frontward/rearward direction. The groove **48** has a rear end portion positioned at a generally center portion of the second inner groove **41R** in the upward/downward direction.

(74) The groove **49** is adapted to guide the connecting portion **69** of the process cartridge **3**. The groove **49** is positioned frontward of the groove **48**, and is recessed outward from the inner surface of the second inner wall **41R** in the leftward/rightward direction. The groove **49** extends downward from a front end portion of the groove **48** and is then curved rearward.

(75) The groove **50** is adapted to guide the protruding sleeve **77** of the process cartridge **3**. The groove **50** is positioned rearward of the groove **48**. The groove **50** is recessed outward from the inner surface of the second inner wall **41R** in the leftward/rightward direction. The groove **50** extends diagonally downward and rearward from a rear end portion of the opening **7**. The groove **50** has a rear end portion positioned rearward of the rear end portion of the opening **7**, and rearward and upward of the rear end portion of the groove **48**.

(76) 4. Accommodation Box, Toner Supply Unit and Waste Toner Collecting Portion

(77) As illustrated in FIGS. **2** and **4**, the image forming apparatus **1** includes an accommodation box **100** formed with openings **103** and **104**, the toner supply unit **101**, and a waste toner collection unit **102** for collecting waste toner removed from the photosensitive drum **13**.

(78) (1) Accommodation Box

(79) The accommodation box **100** is positioned rightward of the second accommodation wall **40R**, and is generally box shaped. The accommodation box **100** is adapted to accommodate the toner supply unit **101** and the waste toner collection unit **102**. The accommodation box **100** includes a protruding portion **106**, an upper cover **109**, a side cover **110**, a boss **111** formed with a hole **112**, and a boss **113** formed with a recessed portion **114**.

(80) The opening **103** is positioned at an upper portion of the toner supply unit **101**. The opening **103** extends through a thickness of an upper wall of the accommodation box **100** in the upward/downward direction.

(81) The opening **104** is positioned rightward of the waste toner collection unit **102**. The opening **104** extends through a thickness of a right side wall of the accommodation box **100** in the leftward/rightward direction.

(82) The protruding portion **106** constitutes a front end portion of the accommodation box **100**. The protruding portion **106** protrudes frontward from an upper portion of a front wall of the accommodation box **100**. The protruding portion **106** includes a support portion **107**.

(83) The support portion **107** protrudes upward from a lower wall of the protruding portion **106**. The support portion **107** is adapted to support a reception sleeve **132** of the toner container **117** described later. The support portion **107** supports the reception sleeve **132** at its first position.

(84) The upper cover **109** constitutes an upper end portion of the accommodation box **100**. The upper cover **109** is fixed to a body portion **130** of a container body **124** of the toner container **117**. The upper cover **109** is plate shaped extending in the frontward/rearward direction and the leftward/rightward direction. The upper cover **109** has a front end portion positioned frontward of the protruding portion **106**. The upper cover **109** is pivotally movable together with the toner container **117** about the connecting tube **116** described later. The upper cover **109** is pivotally movable between a closed position closing the opening **103** and an open position opening the

opening **103**.

(85) As illustrated in FIG. 2, the side cover **110** is positioned rightward of a waste toner box **149** of the waste toner collection unit **102** described later. The side cover **110** is plate shaped extending in the frontward/rearward direction and the upward/downward direction. The side cover **110** is pivotally movable about a rear end portion thereof between a closed position closing the opening **104** and an open position opening the opening **104**.

(86) The boss **111** is positioned rightward of the hole **46** of the circuit board **45**, and is positioned at a right surface of the second accommodation wall **40R**. The boss **111** is generally cylindrical extending in the leftward/rightward direction.

(87) The boss **111** is formed with the hole **112** at a radially center portion thereof. The hole **112** extends through a length of the boss **111**, and in alignment with the holes **42** of the second accommodation wall **40R** in the leftward/rightward direction.

(88) The boss **113** is positioned rightward of the boss **111**, and is spaced away from and in alignment with the boss **111** in the leftward/rightward direction. The boss **113** is positioned at a left surface of a right wall of the accommodation box **100**. The boss **113** is generally cylindrical extending in the leftward/rightward direction.

(89) The recessed portion **114** is recessed rightward from a left surface of the boss **113**. The recessed portion **114** is adapted to receive a right end portion of the connecting tube **116**, preventing rotation of the connecting tube **116**.

(90) (2) Toner Supply Unit

(91) The toner supply unit **101** includes the connecting tube **116** and the toner container **117**.

(92) The connecting tube **116** extends in the leftward/rightward direction, and having one end portion fitted with the boss **113**. The connecting tube **116** extends through the hole **112** of the boss **111**, the holes **42** of the second accommodation wall **40R**, and the hole **46** of the circuit board **45**. The connecting tube **116** has another end portion positioned inside the main casing **2**. Thus, the connecting tube **116** cannot be detached from the main casing **2**. As illustrated in FIG. 7, the left end portion of the connecting tube **116** is positioned rearward of the connecting portion **69**. As illustrated in FIGS. 2 and 7, the connecting tube **116** includes the connecting tube body **118** formed with an inlet opening **121** and an outlet opening **122**, and an auger screw **119**.

(93) The connecting tube body **118** is generally hollow cylindrical extending in the leftward/rightward direction, and each end portion of the connecting tube body **118** in the leftward/rightward direction is closed.

(94) As illustrated in FIG. 4, the inlet opening **121** is positioned at the right end portion of the connecting tube body **118**. The inlet opening **121** extends through a thickness of the front end portion of the connecting tube body **118** in the frontward/rearward direction.

(95) The outlet opening **122** is positioned at the left end portion of the connecting tube body **118**. The outlet opening **122** extends through the thickness of the front end portion of the connecting tube body **118** in the frontward/rearward direction, and is in communication with the hole **74** of the connecting portion **69**.

(96) The auger screw **119** is positioned in the connecting tube body **118**, and extends in the leftward/rightward direction. The auger screw **119** has a right end portion rotatably supported to a right wall of the connecting tube body **118**. The auger screw **119** has a left end portion rotatably supported to a left wall of the connecting tube body **118**.

(97) The toner container **117** is a container for accommodating toner therein. The toner container **117** is pivotally movable about the connecting tube **116** between a first position (FIGS. 2 and 4) and a second position (FIGS. 5 and 6). In the first position, the toner container **117** extends frontward from the connecting tube **116**, and in the second position, the toner container **117** extends upward from the connecting tube **116**. The toner container **117** has one end portion connected to the connecting tube **116** and another end portion positioned away from the connecting tube **116**.

Incidentally, the following description regarding the toner container **117** will be based on the first

position of the toner container **117**. As illustrated in FIGS. 2 and 4, the toner container **117** includes the container body **124** formed with an inlet opening **137**, a lid **125**, a filter **126**, and three conveying members **127**.

(98) The container body **124** is a hollow sleeve-like member extending between one end and another end of the toner container **117**. The container body **124** also extends in an extending direction of the connecting tube **116**. As illustrated in FIG. 2, a length of the container body **124** between the one end and the other end is greater than a length in the extending direction of the connecting tube **116**. The container body **124** includes the body portion **130** formed with a hole **134**, a shutter **131** formed with a communication opening **136**, and the reception sleeve **132**.

(99) The body portion **130** is generally rectangular cylindrical. The body portion **130** includes a first wall **130A** and a second wall **130B**.

(100) The first wall **130A** is positioned above the conveying members **127** when the toner container **117** is at the first position.

(101) The second wall **130B** is positioned below the conveying members **127** when the toner container **117** is at the first position.

(102) The hole **134** is positioned closer to the reception sleeve **132** than the frontmost rotation shaft **142** of the conveying member **127** to the reception sleeve **132** in the extending direction of the toner container **117**. Further, the hole **134** is positioned closer to the first wall **130A** than the rotation shafts **142** to the first wall **130A** in a facing direction between the first wall **130A** and the second wall **130B**. The hole **134** extends through a left wall of the body portion **130** in the leftward/rightward direction.

(103) The shutter **131** is positioned at one end portion of the toner container **117**. The shutter **131** is continuous with one end portion of the container body **124**. The shutter **131** is generally hollow cylindrical extending in the leftward/rightward direction. The connecting tube body **118** is positioned inside of and inseparably fitted with the shutter **131**. Thus, the toner container **117** is inseparable from the accommodation box **100**.

(104) The communication opening **136** extends through a front end portion of the shutter **131** and a rear end portion of the body portion **130** in the frontward/rearward direction. The communication opening **136** is adapted to provide communication between the shutter **131** and the container body **124**. The communication opening **136** can be communicated with the inlet opening **121** of the connecting tube **116** when the toner container **117** is positioned at the first position.

(105) The reception sleeve **132** is positioned at the other end portion of the toner container **117**. The reception sleeve **132** is generally hollow cylindrical extending frontward from the other end portion of the container body **124**. The reception sleeve **132** is supported to the support portion **107** of the protruding portion **106** of the accommodation box **100** when the toner container **117** is at the first position.

(106) The inlet opening **137** is positioned at the other end portion of the container body **124**. The inlet opening **137** extends through the other end portion of the container body **124** in the extending direction of the toner container **117**. The inlet opening **137** is a hollow space of the reception sleeve **132**.

(107) The lid **125** is attachable to and detachable from the inlet opening **137** of the reception sleeve **132**.

(108) The filter **126** is fitted in the hole **134**. The filter **126** is adapted to allow air to pass therethrough, but prevent toner from passing therethrough. The filter **126** is made from urethane foam, for example.

(109) The three conveying members **127** are positioned between the shutter **131** and the reception sleeve **132**. The three conveying members **127** are arrayed in the extending direction of the toner container **117**, such that a space is provided between neighboring conveyor members **127**. Each conveying member **127** includes the rotation shaft **142** and a blade **143**.

(110) Each of the rotation shafts **142** is generally solid cylindrical extending in the

leftward/rightward direction. Each rotation shaft **142** is positioned below the filter **126**. Each rotation shaft **142** has a left end portion rotatably supported to the left wall of the container body **124**, and has a right end portion rotatably supported to the right wall of the container body **124**.
(111) Each of the blades **143** extends radially outward from each of the rotation shafts **142**. Each blade **143** is rotatable about an axis of each rotation shaft **142**, so that the conveying members **127** agitate the toner in the container body **124** and conveys the toner to the connecting tube **116**.

(112) (3) Waste Toner Collecting Unit

(113) The waste toner collection unit **102** is positioned rearward of the toner supply unit **101**. As illustrated in FIGS. **4** and **8**, the waste toner collection unit **102** includes a conveying tube **145** formed with holes **151**, **152**, a support portion **146**, a screw **147**, and the waste toner box **149**.

(114) As illustrated in FIG. **2**, the conveying tube **145** is generally hollow cylindrical extending in the leftward/rightward direction. Each end of the conveying tube **145** in the leftward/rightward direction is closed. The conveying tube **145** extends through the second accommodation wall **40R** of the main casing **2** in the leftward/rightward direction. The conveying tube **145** has a right end portion positioned inside the accommodation box **100**. As illustrated in FIG. **8**, the conveying tube **145** has a left end portion positioned rearward of the rear end portion of the groove **50** of the second inner wall **41R** of the main casing **2**. That is, as illustrated in FIG. **7**, the protruding sleeve **77** of the process cartridge **3** is positioned frontward of the conveying tube **145**.

(115) The hole **151** is positioned at the left end portion of the conveying tube **145**, and extends through a front end portion of the conveying tube **145** in the frontward/rearward direction. The hole **151** is in communication with the hole **82** of the protruding sleeve **77** of the drum cleaning unit **65**.

(116) As illustrated in FIG. **4**, the hole **152** is positioned at the right end portion of the conveying tube **145**. The hole **152** extends through a lower end portion of the conveying tube **145** in the upward/downward direction.

(117) As illustrated in FIGS. **2** and **8**, the support portion **146** is positioned at the left end portion of the conveying tube **145**. The support portion **146** extends upward from an upper edge of the hole **151** of the conveying tube **145**, and also extends frontward from a lower edge of the hole **151**. The support portion **146** is curved along a circumferential surface of the waste toner accommodating portion **76** of the drum cleaning unit **65** of the process cartridge **3**.

(118) The screw **147** is positioned in the conveying tube **145**, and extends in the leftward/rightward direction. The screw **147** has a right end portion rotatably supported to a right wall of the conveying tube **145**. The screw **147** has a left end portion rotatably supported to a left wall of the conveying tube **145**.

(119) As illustrated in FIGS. **2** and **4**, the waste toner box **149** is positioned at a rear end portion of the accommodation box **100**. The waste toner box **149** is generally box shaped. The waste toner box **149** has an upper end portion through which the right end portion of the conveying tube **145** extends. The waste toner box **149** is adapted to receive waste toner conveyed by the conveying tube **145**. The waste toner box **149** can be attached to and detached from the accommodation box **100** by opening the side cover **110** of the accommodation box **100**.

(120) 5. Replenishment of Toner

(121) Toner replenishment to the toner container **117** will next be described.

(122) For replenishment of toner with respect to the toner container **117**, the user moves the toner container **117** from the first position to the second position as illustrated in FIGS. **4** and **5**.

(123) For moving the toner container **117** from the first position to the second position, the user grips and lifts upward the front end portion of the upper cover **109** of the accommodation box **100**. Accordingly, the toner container **117** is pivotally moved upward about the connecting tube **116** such that the inlet opening **137** is directed upward. Thus, the toner container **117** extends upward from the connecting tube **116** to be positioned at the second position.

(124) When the toner container **117** is at the second position, the filter **126** of the body portion **130** is positioned above the rotation shafts **142** of the conveying members **127**.

(125) Further, the communication opening **136** is positioned above the inlet opening **121** of the connecting tube body **118**. Accordingly, an inner surface of the shutter **131** is brought into confrontation with the inlet opening **121**. Thus, the shutter **131** closes the inlet opening **121** of the connecting tube body **118**.

(126) Further, an outer surface of the connecting tube body **118** is brought into confrontation with the communication opening **136**. Thus, the connecting tube body **118** closes the communication opening **136** of the container body **124**.

(127) Then, the user removes the lid **125** from the inlet opening **137** of the toner container **117**.

(128) Then, the user inserts a toner replenishment vessel **170** into the inlet opening **137** to replenish toner to the toner container **117**.

(129) Upon completion of the toner replenishment, the user attaches the lid **125** to the inlet opening **137** of the toner container **117**.

(130) Then, the user moves the toner container **117** from the second position to the first position.

(131) For moving the container from the second position to the first position, the user grips the upper cover **109**, and lays the toner container **117** frontward about the connecting tube **116**. Then, the user permits the reception sleeve **132** to be seated on the support portion **107** of the protruding portion **106** as illustrated in FIG. 4. Thus, the toner container **117** can be positioned at the first position.

(132) In this case, the filter **126** is positioned above the rotation shafts **142** of the conveying members **127**.

(133) 6. Image Forming Operation

(134) After start of image forming operation in the image forming apparatus **1**, the three conveying members **127** convey toner in the toner container **117** into the connecting tube body **118** of the connecting tube **116** through the communication opening **136** and the inlet opening **121** as illustrated in FIG. 4.

(135) Then, the auger screw **119** conveys the toner in the connecting tube body **118** leftward as illustrated in FIG. 2.

(136) The toner conveyed to a left portion of the connecting tube body **118** is conveyed to the right end portion of the connection sleeve **72** through the outlet opening **122** of the connecting tube body **118** and the hole **74** of the connection sleeve **72**.

(137) Then, the first screw **90** of the developing unit **12** conveys the toner conveyed to the right end portion of the connection sleeve **72** toward the conveying chamber **94**. The first screw **90** conveys the toner conveyed to the conveying chamber **94** leftward, and supplies toner to the developing chamber **95** through the communication opening **96**.

(138) The toner in the developing chamber **95** is supplied to the supply roller **17**.

(139) Then, the supply roller **17** supplies toner in the developing chamber **95** to the developing roller **16**. In this case, the toner is subjected to triboelectric charging with positive polarity between the developing roller **16** and the supply roller **17**, and is carried on the developing roller **16**. The blade **18** regulates a thickness of the toner layer carried on the developing roller **16**.

(140) The toner carried on the developing roller **16** is supplied to the electrostatic latent image formed on the surface of the photosensitive drum **13**. Thus, the toner image is carried on the surface of the photosensitive drum **13**.

(141) As illustrated in FIG. 1, the sheet P is supplied one by one to the portion between the photosensitive drum **13** and the transfer roller **15** at a prescribed timing. Thus, the toner image on the surface of the photosensitive drum **13** is transferred to the sheet P when the sheet P passes through the portion between the photosensitive drum **13** and the transfer roller **15**.

(142) Then, the sheet P is heated and pressed when the sheet P passes through a portion between the heat roller **5A** and the pressure roller **5B**. Thus, the toner image on the sheet P is thermally fixed to the sheet P. Then, the sheet P is delivered onto the cover **8**.

(143) Incidentally, in the image forming operation, the developing unit **12** is displaced relative to

the photosensitive drum **13** due to the rotation of the photosensitive drum **13** and the developing roller **16**. The developing unit **12** is slightly moved in the frontward/rearward direction about the shaft **88** as a fulcrum as illustrated in FIG. **1**.

(144) Further, waste toner remaining on the surface of the photosensitive drum **13** is scraped and removed by the cleaning member **78** of the drum cleaning unit **65**, and is accommodated in the waste toner accommodating portion **76**.

(145) The screw **79** conveys the waste toner in the waste toner accommodating portion **76** rightward as illustrated in FIG. **2**.

(146) The waste toner conveyed to a right portion of the waste toner accommodating portion **76** is flowed into the conveying tube **145** through the holes **82**, **151** as illustrated in FIG. **7**.

(147) The screw **147** conveys the waste toner in the conveying tube **145** toward the waste toner box **149**.

(148) **7. Attachment and Detachment of Process Cartridge**

(149) For detaching the process cartridge **3** from the main casing **2**, the user positions the manual insertion tray **22** at the support position as illustrated in FIG. **7**.

(150) Then, the user positions the cover **8** at its open position, and grips the handle **68** to pull out the process cartridge **3** upward. Accordingly, each end portion of the photosensitive drum **13** in the leftward/rightward direction is guided by each groove **48** of each of the first and second inner walls **41L**, **41R**. Further, the connecting portion **69** of the process cartridge **3** is guided by the groove **49**, and the protruding sleeve **77** of the drum cleaning unit **65** is guided by the groove **50**. As a result, the process cartridge **3** can be detached from the main casing **2**.

(151) For attaching the process cartridge **3** to the main casing **2**, the user positions the manual insertion tray **22** at the support position, and pushes the process cartridge **3** through the opening **7** while the cover **8** is maintained at its open position. Then, the user positions the cover **8** at its closed position, and positions the manual insertion tray **22** at its accommodated position. Thus, the process cartridge **3** can be attached to the main casing **2**.

(152) **8. Function and Effect**

(153) (1) According to the image forming apparatus **1**, toner accommodated in the toner container **117** is supplied to the developing unit **12** through the connecting tube **116** as illustrated in FIGS. **2** and **4**.

(154) When the toner is to be replenished into the toner container **117** in accordance with the decrease in toner amount in the toner container **117**, the toner container **117** is pivotally moved about the connecting tube **116** to the second position as illustrated in FIGS. **5** and **6**, so that the inlet opening **137** is positioned above the position of the inlet opening **137** at the first position of the toner container **117**.

(155) Therefore, the user can easily replenish toner into the toner container **117** through the inlet opening **137**.

(156) (2) According to the image forming apparatus **1**, the user positions the toner container **117** to the second position at which the inlet opening **137** is positioned above the inlet opening **137** at the first position, and a longitudinal direction of the toner container **117** is directed in the upward/downward direction as illustrated in FIGS. **5** and **6**.

(157) Therefore, the user can replenish the toner through the inlet opening **137** such that the toner is successively increased upward in a direction from the bottom of the toner container **117** without scattering of the toner.

(158) Further, as illustrated in FIG. **4**, the toner container **117** is to be positioned at the first position which the inlet opening **137** is positioned below the inlet opening **137** at the second position. Thus, a compact image forming apparatus in the upward/downward direction can be obtained.

(159) (3) According to the image forming apparatus **1**, as illustrated in FIG. **4**, toner in the toner container **117** can be stably conveyed to the connecting tube **116** by the conveying member **127**.

(160) (4) According to the image forming apparatus **1**, as illustrated in FIG. **6**, the filter **126** can

allow air pushed by toner to pass therethrough when the toner is replenished into the toner container **117**.

(161) Therefore, the user can efficiently replenish toner into the toner container **117** through the inlet opening **137**.

(162) Further, the image forming apparatus **1** can restrain toner from reaching the filter **126**, because the filter **126** is positioned above the rotation shafts **142** of the conveying members **127** as illustrated in FIGS. **4** and **5** not only in the first position but also in the second position of the toner container **117**.

(163) As a result, clogging of the filter **126** by the toner can be restrained.

(164) (5) According to the image forming apparatus **1**, the toner container **117** is pivotally movably supported to the main casing **2** through the connecting tube **116** as illustrated in FIGS. **4** and **5**.

(165) Therefore, toner in the toner container **117** can be stably supplied to the developing unit **12**.

(166) (6) According to the image forming apparatus **1**, the circuit board **45** is positioned between the toner container **117** and the developing unit **12** as illustrated in FIG. **2**.

(167) Therefore, effective layout of the circuit board **45**, the toner container **117**, and the developing unit **12** with respect to the main casing **2** can be obtained.

(168) (7) According to the image forming apparatus **1**, toner in the connecting tube **116** can be reliably conveyed to the developing unit **12** by the auger screw **119** as illustrated in FIG. **2**.

(169) (8) According to the image forming apparatus **1**, the inlet opening **121** of the connecting tube **116** is closed when the user positions the toner container **117** at the second position for toner replenishment as illustrated in FIG. **6**.

(170) Therefore, the shutter **131** prevents toner from being flowed into the connecting tube **116** during replenishment of toner into the toner container **117**. After completion of replenishment of toner into the toner container **117**, toner in the toner container **117** is supplied to the connecting tube **116** when the toner container **117** is moved to the first position to open the inlet opening **121** of the connecting tube **116**.

(171) (9) According to the image forming apparatus **1**, as illustrated in FIG. **4**, the lid **125** closes the inlet opening **137** so that the lid **125** can prevent the toner from leaking from the inlet opening **137** during pivotal movement of the toner container **117**.

(172) Further, as illustrated in FIG. **6**, the inlet opening **137** can be opened by removing the lid **125** by the user for replenishing the toner into the toner container **117**.

(173) (10) According to the image forming apparatus **1**, the inlet opening **137** is positioned higher than the main casing **2** and the reading unit **35** when the toner container **117** is at the second position as illustrated in FIGS. **5** and **6**. Therefore, the user can easily replenish toner into the toner container **117** through the inlet opening **137**.

Second Embodiment

(174) 1. Outline of Image Forming Apparatus

(175) An image forming apparatus **1A** according to a second embodiment will next be described with reference to FIGS. **9** through **11** wherein like parts and components are designated by the same reference numerals as those shown in the first embodiment to avoid duplicating description.

(176) In the first embodiment, as illustrated in FIGS. **4** and **5**, the communication opening **136** and the inlet opening **121** are communicated with each other when the toner container **117** is at the first position, and the communication opening **136** is not communicated with the inlet opening **121** when the toner container **117** is at the second position.

(177) In contrast, in the second embodiment, an inlet opening **193** of a connecting tube **180** and a communication opening **209** of a toner container **181** are communicated with each other as illustrated in FIG. **11** at both a first position and a second position of the toner container **181** as illustrated in FIGS. **9** and **10**. Further, in the second embodiment, the toner container **181** has a bottom wall **205** positioned below the connecting tube **180** when the toner container **181** is at its second position.

(178) 2. Structure

(179) (1) Accommodation Box

(180) In the first embodiment, the upper cover **109** of the accommodation box **100** is fixed to the container body **124**. In contrast, in the second embodiment, an upper cover **109A** is not fixed to a container body **200** but is pivotally movable about a left end portion of the upper cover **109A**. FIG. **10** illustrates an open position of the upper cover **109A** and FIG. **9** illustrates a closed position thereof.

(181) (2) Toner Supply Unit

(182) In the second embodiment, a toner supply unit **101A** includes the connecting tube **180** and the toner container **181** as illustrated in FIGS. **9** and **11**.

(183) The connecting tube **180** extends in the leftward/rightward direction. The connecting tube **180** has one end portion fitted with the hole **42** of the right wall of the second accommodation wall **40R**, and has another end portion positioned inside the main casing **2** and extending through the hole **42** of the left wall of the second accommodation wall **40R**. Thus, the connecting tube **180** cannot be detached from the main casing **2**. The connecting tube **180** includes a connecting tube body **190** formed with the inlet opening **193**, a boss **195** formed with a recessed portion **196**, and an auger screw **191**.

(184) The connecting tube body **190** is generally hollow cylindrical extending in the leftward/rightward direction. The connecting tube body **190** has a closed left end portion and an open right end portion. The connecting tube body **190** extends through the hole **42** of the left wall of the second accommodation wall **40R** and the hole **46** of the circuit board **45**.

(185) The inlet opening **193** is positioned at the right end portion of the connecting tube body **190**. The inlet opening **193** is a hollow space in the connecting tube body **190** extending in an extending direction of the connecting tube **180**.

(186) The boss **195** is positioned rightward of the connecting tube body **190**, and is integral with the right end portion of the connecting tube body **190**. The boss **195** is generally cylindrical extending in the leftward/rightward direction. The boss **195** has an outer diameter greater than that of the connecting tube body **190**, and is fitted with the hole **42** formed in the right wall of the second accommodation wall **40R**. The boss **195** has a right end portion positioned rightward of the second accommodation wall **40R**. The boss **195** is in continuous with the connecting tube body **190**, and extends through the holes **42** of the second accommodation wall **40R** and the hole **46** of the circuit board **45** in the leftward/rightward direction.

(187) The recessed portion **196** is recessed leftward from a right surface of the boss **195**. The recessed portion **196** has an inner diameter greater than that of the connecting tube body **190**. The recessed portion **196** is adapted to receive a first engagement portion **207** of the toner container **181** such that the first engagement portion **207** is rotatable relative to the recessed portion **196**.

(188) The auger screw **191** is positioned in the connecting tube body **190**, and extends in the leftward/rightward direction. The auger screw **191** has a right end portion positioned at the right end portion of the connecting tube body **190**. More specifically, the right end portion of the auger screw **191** is positioned in the communication opening **209** of the toner container **181**. The auger screw **191** has a left end portion rotatably supported to a left wall of the connecting tube body **190**.

(189) The toner container **181** is pivotally movable about the connecting tube **180** between the first position (FIGS. **9** and **11**) where the toner container **181** extends frontward from the connecting tube **180** and the second position (FIG. **10**) where the toner container **181** extends upward from the connecting tube **180**. The toner container **181** has one end portion connected to the connecting tube **180** and another end portion remote from the connecting tube **180**. Incidentally, the following description is based on the first position of the toner container **181**. As illustrated in FIGS. **9** and **11**, the toner container **181** includes the container body **200**, a conveying member **201**, and the lid **125**.

(190) The container body **200** is a hollow cylindrical extending between one end portion and another end portion of the toner container **181**. The container body **200** includes a body portion

204, the bottom wall **205**, a support portion **206** formed with a hole **211**, the first engagement portion **207** formed with the communication opening **209**, a second engagement portion **208**, and the reception sleeve **132**.

(191) The body portion **204** is generally hollow cylindrical. The conveying member **201** is accommodated in the body portion **204**.

(192) The bottom wall **205** is provided at one end portion of the body portion **204** to constitute one end portion of the container body **200**, and is hollow semi-spherical. The bottom wall **205** closes the one end of the body portion **204**.

(193) The support portion **206** is positioned at another end portion of the body portion **204** as illustrated in FIGS. **9** and **11**. The support portion **206** is curved toward the one end of the container body **200** from a peripheral end portion of the inlet opening **137**.

(194) The hole **211** extends through a central portion of the support portion **206** in a longitudinal direction of the container body **200**.

(195) As illustrated in FIG. **11**, the first engagement portion **207** is positioned at a left end portion of the body portion **204**, and protrudes leftward from the left end portion of the body portion **204**. The first engagement portion **207** is generally cylindrical, and is rotatably fitted with the recessed portion **196** of the boss **195** of the connecting tube **180**.

(196) The communication opening **209** extends through the first engagement portion **207** in the leftward/rightward direction. Thus, the communication opening **209** provides communication between the container body **200** and the connecting tube **180**.

(197) The second engagement portion **208** is positioned at a right end portion of the body portion **204**. The second engagement portion **208** is aligned with the first engagement portion **207** in the leftward/rightward direction. The second engagement portion **208** protrudes rightward from the right end portion of the body portion **204**. The second engagement portion **208** is generally cylindrical, and is rotatably fitted with a recessed portion **114A** of a boss **113A**.

(198) With this structure, the toner container **181** is pivotally movable about the first engagement portion **207** and the second engagement portion **208** as fulcrums relative to the connecting tube **180** and an accommodation box **100A**.

(199) The conveying member **201** is positioned inside the container body **200** and extends between the inlet opening **137** and the bottom wall **205**. The conveying member **201** has one end portion rotatably supported to the bottom wall **205**, and has another end portion rotatably supported to the hole **211** of the support portion **206**.

(200) A drive gear **215** is fixed to the one end portion of the conveying member **201** at a position rearward of the bottom wall **205**.

(201) A main gear **216** is positioned rightward of the second accommodation wall **40R**. As illustrated in FIG. **11**, the main gear **216** is meshed with the drive gear **215** when the toner container **181** is at its first position.

(202) 3. Toner Replenishment

(203) Next, toner replenishment to the toner container **181** will be described.

(204) For replenishing toner to the toner container **181**, a user positions the upper cover **109A** of the accommodation box **100A** to its open position as illustrated in FIG. **10**. Then, the user grips the toner container **181** and pivotally moves the toner container **181** about the connecting tube **180** as the fulcrum so as to direct the inlet opening **137** upward. As a result, the toner container **181** extends upward from the connecting tube **180** to be positioned at the second position.

(205) Then, similar to the first embodiment, the user removes the lid **125** from the inlet opening **137** of the toner container **181**, and inserts the toner replenishing vessel **170** into the inlet opening **137** to replenish toner into the toner container **181**.

(206) Toner replenished through the inlet opening **137** is accumulated on the bottom wall **205** positioned below the connecting tube **180**.

(207) Toner is successively stacked, and is flowed into the connecting tube **180** through the

communication opening **209**.

(208) Then, the user moves the toner container **181** to the first position, and moves the upper cover **109A** to its closed position.

(209) Thus, toner replenishment is completed.

(210) Toner replenished into the container body **200** of the toner container **181** is supplied to the developing unit **12** by the auger screw **191**.

(211) 4. Function and Effect

(212) In the image forming apparatus **1A** according to the second embodiment, toner replenished through the inlet opening **137** is accumulated on the bottom wall **205** positioned below the connecting tube **180**.

(213) The toner is successively stacked, and is flowed into the connecting tube **180**.

(214) Therefore, the structure can prevent the toner replenished through the inlet opening **137** of the toner container **181** from immediately flowing into the connecting tube **180**.

(215) Further, the second embodiment provides the function and effect similar to those of the first embodiment.

Third Embodiment

(216) 1. Outline of Image Forming Apparatus

(217) An image forming apparatus **1B** according to a third embodiment will be described with reference to FIGS. **12** through **14**, wherein like parts and components are designated by the same reference numerals as those shown in the first embodiment to avoid duplicating description.

(218) In the first embodiment, the image forming apparatus **1** is a monochromatic printer provided with the single process cartridge **3**. On the other hand, in the third embodiment, the image forming apparatus **1B** is a direct tandem type color laser printer provided with four process units **230** as illustrated in FIGS. **12** and **13**.

(219) A user can replenish toner to each of toner containers **241** of each of four process units **230**.

(220) 2. Structure

(221) As illustrated in FIGS. **12** and **13**, the image forming apparatus **1B** includes a drawer **231**, the four process units **230**, a scanner **4B**, and a reading unit **35B**.

(222) The drawer **231** is generally box shaped, and is adapted to be pulled out of and pushed into a main casing **2B** of the image forming apparatus **1B**. The drawer **231** is adapted to support the four process units **230**. The main casing **2B** includes a sheet supply tray **9B**.

(223) The four process units **230** are supported to the drawer **231** and are arrayed in the frontward/rearward direction with a space between neighboring process units **230**. Each process unit **230** includes a drum unit **11B** supporting a photosensitive drum **13B**, a developing unit **12B**, and a toner supply unit **235** for supplying toner to the developing unit **12B**. The developing unit **12B** includes the developing roller **16**, the supply roller **17**, the blade **18**, a developing frame **86B**, and a screw **90B**.

(224) The toner supply unit **235** includes a connecting tube **240** and the toner container **241** as illustrated in FIG. **14**.

(225) The connecting tube **240** is positioned at a right end portion of the developing unit **12B**, and includes a connecting tube body **244** formed with an inlet opening **246** and an outlet opening **247**.

(226) The connecting tube body **244** is generally hollow cylindrical extending in the frontward/rearward direction.

(227) The inlet opening **246** extends through an upper end portion of the connecting tube body **244** in the upward/downward direction.

(228) The outlet opening **247** is positioned below the inlet opening **246**, and extends through a lower end portion of the connecting tube body **244** in the upward/downward direction. Thus, the outlet opening **247** provides communication between the connecting tube body **244** and the developing frame **86B** of the developing unit **12B**.

(229) The toner container **241** is pivotally movable about the connecting tube **240** as a fulcrum

between a first position as illustrated in FIG. 12 and a solid line in FIG. 14, and a second position as illustrated in FIG. 13 and a two dotted chain line in FIG. 14. In the first position, the toner container **241** extends leftward from the connecting tube **240**, and in the second position the toner container **241** extends upward from the connecting tube **240**. The toner container **241** has one end portion connected to the connecting tube **240** and another end portion remote from the connecting tube **240**. Incidentally, the following description as to the toner container **241** is based on a situation where the toner container **241** is at its first position. As illustrated in FIG. 14, the toner container **241** includes a container body **250** and an auger screw **251**.

(230) The container body **250** is hollow cylindrical extending between one end and another end of the toner container **241**. The container body **250** includes an engagement sleeve **255** and a reception sleeve **132B** similar to the reception sleeve **132** of the first embodiment.

(231) The engagement sleeve **255** is provided at one end portion of the container body **250** positioned closer to the connecting tube **240** than the other end portion to the connecting tube **240**. The engagement sleeve **255** is generally hollow cylindrical extending in the frontward/rearward direction. The engagement sleeve **255** and the container body **250** are communicated with each other by a communication opening **256**. The engagement sleeve **255** receives therein the connecting tube body **244** of the connecting tube **240**.

(232) The communication opening **256** extends through an upper end portion of the engagement sleeve **255** and one end portion of the container body **250** in the upward/downward direction. The communication opening **256** is brought into communication with the inlet opening **246** of the connecting tube **240** when the toner container **241** is positioned at its first position.

(233) The auger screw **251** extends between one end portion and another end portion of the container body **250**, and is rotatably supported to the one end portion and another end portion of the container body **250**. Incidentally, a lid **125B**, a filter **126B**, an inlet opening **137B**, and a hole **134B** are provided in the third embodiment those similar to the lid **125**, the filter **126**, the inlet opening **137**, and the hole **134** in the first embodiment.

(234) 3. Toner Replenishment

(235) Replenishment of toner to the toner container **241** will next be described.

(236) As illustrated in FIG. 13, the drawer **231** is pulled out from the main casing **2B** for replenishing toner to the toner container **241**. Then, the user grips the toner container **241** of the toner supply unit **235**, and pivotally moves the toner container **241** about the connecting tube **240** so as to position the inlet opening **137B** upward. Thus, the toner container **241** extends upward from the connecting tube **240** to be positioned at the second position.

(237) At the second position of the toner container **241**, the communication opening **256** is moved rightward relative to the inlet opening **246**.

(238) Thus, an inner surface of the engagement sleeve **255** is brought into confrontation with the inlet opening **246**, so that the engagement sleeve **255** closes the inlet opening **246** of the connecting tube body **244**.

(239) Further, the communication opening **256** is brought into confrontation with an outer surface of the connecting tube body **244**, so that the connecting tube body **244** closes the communication opening **256** of the container body **250**.

(240) Then, similar to the first embodiment, the user removes the lid **125B** from the inlet opening **137B** of the toner container **241**, and inserts the toner replenishing vessel **170** into the inlet opening **137B** to replenish toner to the toner container **241**.

(241) After completion of the toner replenishment into the toner container **241**, the user attaches the lid **125B** to the inlet opening **137B** of the toner container **241**.

(242) Then, the user pivotally moves the toner container **241** from the second position to the first position similar to the first embodiment.

(243) Thus, the toner container **241** can be positioned at the first position.

(244) Then, the toner in the toner container **241** is conveyed to the communication opening **256** by

the auger screw **251**, and is supplied into the developing unit **12** through the connecting tube **240**.

(245) 4. Function and Effect

(246) In the image forming apparatus **1B** according to the third embodiment, function and effect those similar to the first embodiment can be obtained with respect to the tandem type color printer instead of the monochromatic printer.

MODIFICATION

(247) According to the first embodiment, the three conveying members **127** are provided in the toner container **117**. However, numbers of the conveying members **127** is not limited to three, and one, two or not less than four conveying member(s) can be provided in the toner container **117**.

(248) Further, in the first embodiment, the shutter **131** is generally hollow cylindrical. However, a shutter having an arcuate shape is also available.

(249) While the description has been made in detail with reference to the embodiment(s) thereof, it would be apparent to those skilled in the art that many modifications and variations may be made therein without departing from the spirit of the disclosure.

Claims

1. An image forming apparatus comprising: a main casing; a photosensitive drum; a developing roller; a scanner configured to expose the photosensitive drum to light; a toner container configured to accommodate toner therein, the toner container having an inlet opening to replenish toner to the toner container; and a cover pivotable between a closed position, at which the cover closes the inlet opening, and an open position, at which the cover exposes the inlet opening to an outside, wherein the main casing includes a front wall and a rear wall spaced apart from each other in a front-rear direction, wherein the toner container is movable together with the inlet opening relative to the main casing between a first position and a second position, wherein the toner container is at the first position during an image forming operation, and wherein toner is replenished by a user to the toner container through the inlet opening in a state where the toner container is at the second position, and wherein a position of the inlet opening when the toner container is at the second position is higher than a position of the inlet opening when the toner container is at the first position.
2. The image forming apparatus according to claim 1, wherein a distance from the front wall of the main casing to the inlet opening in the front-rear direction is smaller than a distance from the front wall of the main casing to the photosensitive drum in the front-rear direction.
3. The image forming apparatus according to claim 1, wherein the cover covers the inlet opening from above.
4. The image forming apparatus according to claim 3, wherein the cover is pivotable about a cover axis extending in a horizontal direction.
5. The image forming apparatus according to claim 4, wherein the cover includes a rectangular-shaped plate having a first side and a second side shorter than the first side, the cover being pivotable about a cover axis that extends along the first side of the cover.
6. The image forming apparatus according to claim 4, wherein the photosensitive drum is rotatable about a drum axis, and wherein a distance from the front wall of the main casing to the cover axis in the front-rear direction is smaller than a distance from the front wall of the main casing to the drum axis.
7. The image forming apparatus according to claim 4, wherein a distance from the front wall of the main casing to the cover axis in the front-rear direction is greater than a distance from the front wall of the main casing to the scanner.
8. The image forming apparatus according to claim 1, wherein the toner container includes a lid movable relative to the main casing between a closed position at which the lid closes the inlet opening and an open position at which the lid opens the inlet opening.

9. The image forming apparatus according to claim 8, wherein the lid is detachably attached to the inlet opening.

10. The image forming apparatus according to claim 8, wherein the inlet opening is configured to allow a toner replenishing vessel accommodating toner therein to be attached by the user in a case where the lid is at the open position.

11. The image forming apparatus according to claim 10, wherein the inlet opening is positioned above the developing roller in a state where the toner replenishing vessel is attached to the inlet opening.

12. The image forming apparatus according to claim 10, wherein the inlet opening is positioned above the photosensitive drum in a state where the toner replenishing vessel is attached to the inlet opening.
