

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12385941
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Gilchrist; Ulysses

Automatic assaying system and methods therefor

Abstract

An automatic assaying system having a multiplex pipette cartridge section in which pipette cartridges are docked. At least one pipette cartridge has a different pipetting characteristic from another corresponding pipette cartridge, the different pipetting characteristic being selectable from a number of different pipetting characteristics. A multiplexing work item holder has an array of work item holder docks that dock corresponding work item holders selectable from pipette trays and pipette tip set racks that define the selectable different pipetting characteristic. One or more of the work item holder docks are indexed to selectably multiplex both the different interchangeable pipette trays and the at least one pipette set rack. A carrier moves the pipette cartridge or a work item holder carriage and a controller selects the at least one pipette tip set rack corresponding to a work item holder dock so as to effect automatic selection of the different pipetting characteristic.

Inventors:	Gilchrist; Ulysses (Reading, MA)
Applicant:	HighRes Biosolutions, Inc. (Beverly, MA)
Family ID:	1000008752293
Assignee:	HighRes Biosolutions, Inc. (Beverly, MA)
Appl. No.:	18/337633
Filed:	June 20, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230333135 A1	Oct. 19, 2023

Related U.S. Application Data

continuation parent-doc US 16900468 20200612 US 11680954 child-doc US 18337633

Publication Classification

Int. Cl.: **G01N35/10** (20060101); **B01L3/02** (20060101); **G01N35/00** (20060101); **G01N35/04** (20060101)

U.S. Cl.:

CPC **G01N35/1074** (20130101); **B01L3/021** (20130101); B01L2200/04 (20130101); B01L2200/14 (20130101); B01L2300/021 (20130101); B01L2300/0829 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5055263	12/1990	Meltzer	N/A	N/A
5306510	12/1993	Meltzer	N/A	N/A
5512247	12/1995	Bonacina et al.	N/A	N/A
5948359	12/1998	Kalra et al.	N/A	N/A
5958342	12/1998	Gamble et al.	N/A	N/A
6299840	12/2000	Watanabe et al.	N/A	N/A
6325114	12/2000	Bevirt et al.	N/A	N/A
7858041	12/2009	Muraishi et al.	N/A	N/A
7968060	12/2010	Van Tuyl	N/A	N/A
8211301	12/2011	Safar et al.	N/A	N/A
8282895	12/2011	Miller et al.	N/A	N/A
8404492	12/2012	Bladassari et al.	N/A	N/A
8638509	12/2013	Blasenheim et al.	N/A	N/A
8865474	12/2013	Paschetto et al.	N/A	N/A
9028754	12/2014	Winter et al.	N/A	N/A
2003/0215357	12/2002	Malterer et al.	N/A	N/A
2004/0005714	12/2003	Safar et al.	N/A	N/A
2004/0081583	12/2003	Berndt et al.	N/A	N/A
2004/0096360	12/2003	Toi et al.	N/A	N/A
2004/0112978	12/2003	Reichel et al.	N/A	N/A
2006/0188409	12/2005	Chang et al.	N/A	N/A
2008/0254545	12/2007	Kitaoka	N/A	N/A
2009/0155123	12/2008	Williams et al.	N/A	N/A
2010/0105074	12/2009	Covey et al.	N/A	N/A
2012/0291872	12/2011	Brady et al.	N/A	N/A
2013/0017535	12/2012	Frey et al.	N/A	N/A
2013/0151004	12/2012	Winter et al.	N/A	N/A
2013/0280145	12/2012	West et al.	N/A	N/A
2013/0295597	12/2012	Dewitte et al.	N/A	N/A
2014/0045186	12/2013	Gubatayao et al.	N/A	N/A
2014/0154043	12/2013	Hofstadler et al.	N/A	N/A

2014/0193826	12/2013	Gajewski et al.	N/A	N/A
2014/0260696	12/2013	Criswell	N/A	N/A
2014/0338430	12/2013	Theodorsen	N/A	N/A
2015/0127270	12/2014	Thoss et al.	N/A	N/A
2015/0260747	12/2014	Samsoondar	N/A	N/A
2016/0256866	12/2015	Nichols et al.	N/A	N/A
2017/0142945	12/2016	Demetrescu et al.	N/A	N/A
2017/0219614	12/2016	Cook et al.	N/A	N/A
2019/0227091	12/2018	Park et al.	N/A	N/A
2019/0250181	12/2018	Seeber	N/A	N/A
2020/0200779	12/2019	Sigler et al.	N/A	N/A
2020/0319222	12/2019	Vansickler et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1363736	12/2002	EP	N/A
2016141000	12/2015	WO	N/A

OTHER PUBLICATIONS

International Search Report, International Application No. PCT/US2016/020326, dated Jun. 13, 2016. cited by applicant

Primary Examiner: Robinson; Elizabeth A

Assistant Examiner: Fisher; Brittany I

Attorney, Agent or Firm: Perman & Green, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation of U.S. patent application Ser. No. 16/900,468, filed Jun. 12, 2020, (Now U.S. Pat. No. 11,680,954), and are hereby incorporated by reference in their entireties.

BACKGROUND

1. Field

(1) The exemplary embodiments generally relate to life sciences equipment, and more particularly, to pipetting equipment for use in the life sciences industry.

2. Brief Description of Related Developments

(2) Pipettors, also referred to as chemical droppers, are laboratory tools commonly used in the life sciences industry to dispense a volume of liquid. As life sciences equipment has advanced, many pipettors have been integrated into automated systems. While these automated systems have improved the accuracy and control of pipetting procedures, these conventional automated systems can be less than dynamic in their ability to handle distinct pipetting procedures.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The foregoing aspects and other features of the disclosed embodiment are explained in the

following description, taken in connection with the accompanying drawings, wherein:

- (2) FIG. 1 is a schematic block diagram of an automatic assaying system incorporating aspects of the present disclosure;
- (3) FIG. 2 illustrates non-limiting examples of work item holders of the automatic assaying system of FIG. 1 in accordance with aspects of the present disclosure;
- (4) FIG. 3 is a side perspective illustration of the automatic assaying system of FIG. 1 in accordance with aspects of the present disclosure;
- (5) FIG. 4 is a side perspective illustration of the automatic assaying system of FIG. 1 in accordance with aspects of the present disclosure;
- (6) FIG. 5A is a top perspective illustration of portions of the automatic assaying system of FIG. 1 in accordance with aspects of the present disclosure;
- (7) FIG. 5B is a schematic diagram illustrating portions of the automatic assaying system of FIG. 5A in accordance with aspects of the present disclosure;
- (8) FIG. 6A is a schematic illustration of an non-limiting exemplary multiplexed/sequenced workflow through the automatic assaying system of FIG. 1 in accordance with aspects of the present disclosure;
- (9) FIG. 6B is a schematic illustration of an non-limiting exemplary multiplexed/sequenced workflow from a storage section of the automatic assaying system to a work section of the automatic assaying system to effect the non-limiting exemplary multiplexed/sequenced workflow of FIG. 6A in accordance with aspects of the present disclosure;
- (10) FIG. 7 is a block diagram of an exemplary method incorporating aspects of the present disclosure;
- (11) FIG. 8 is a block diagram of an exemplary method incorporating aspects of the present disclosure; and
- (12) FIG. 9 is a block diagram of an exemplary method incorporating aspects of the present disclosure.

DETAILED DESCRIPTION

(13) Referring to FIG. 1 an exemplary automatic assaying system **100** is illustrated in accordance with aspects of the present disclosure. Although the aspects of the present disclosure will be described with reference to the drawings, it should be understood that the aspects of the present disclosure can be embodied in many forms. In addition, any suitable size, shape or type of elements or materials could be used.

(14) The automatic assaying system **100** is configured to provide a substantially continuous uninterrupted flow of work item holders **118** between a storage section **106** of the automatic assaying system **100** and a work section **104** of the automatic assaying system **100**. The work item holders **118** are transferred in the substantially continuous uninterrupted flow from the storage section **106** to the work section **104** in any suitable multiplexed order (e.g., forming the substantially continuous uninterrupted flow) so that when the work item holders **118** are presented to a carrier **130** of the automatic assaying system **100** (i.e., that effects pipetting operations), at least a predetermined pipetting protocol can be performed on predetermined groups of work item holders **118** belonging to a respective pipetting protocol. The term multiplexed as used herein refers to the insertion of work item holders **118** corresponding or belonging to different pipetting protocols into the (single) substantially continuous uninterrupted flow of work item holders **118** between the storage section **106** and the work section **104** in a manner similar to that in which communication signals are combined for transmission over a single shared medium (the substantially continuous uninterrupted flow of work item holders **118** being the shared medium as effected by one or more of the articulated bot arm **122**, the indexing section **120**, and the carrier **130** as described herein and work item holders **118** of different pipetting protocols may be inter-mixed with each other in the substantially continuous uninterrupted flow of work item holders **118**).

(15) The number of pipetting protocols that are performed in, for example, life sciences assays is large. The aspects of the present disclosure provide for the flexible loading of work item holders **118** to the automatic assaying system **100**, where flexible refers the ability to load and unload work item holders from the automatic assaying system substantially without interrupting work flow through the automatic assaying system. In some aspects, the flexibility of the automatic assaying system **100** is effected at least in part by loading generic work item holders that are useful for more than one pipetting protocol, reagents, compounds, pipette tip set racks, etc. in advance (e.g., prior to a desired pipetting operation) to the storage section **106** (e.g., an unused supply of these work items are continuously stored in the storage section and used as desired in an opportunistic manner depending on a desired pipetting protocol) or as needed in a just-in-time manner (e.g., the work items are loaded to the storage section when requested or immediately prior to a pipetting protocol) for random access of the work item holders **118** to effect completion (or partial completion) of a pipetting protocol in accordance with desired pipetting protocols to be performed by the automatic assaying system **100**.

(16) The predetermined pipetting protocols that are performed on respective groups of work item holders **118** include, but are not limited to, pipette tray (also referred to as sample holder tray) replication, pipette tray reformatting (e.g., expansion and/or compression), reagent addition, compound addition, and serial dilution. Pipette tray replication is the replication of the contents of a source pipette tray to one or more destination pipette trays (i.e., the contents of each destination pipette tray replicates the contents of the source pipette tray). Pipette tray reformatting involves moving samples between pipette trays having a different number of sample wells. Tray expansion reformatting is an operation that spreads the contents of sample wells of a source pipette tray having a first number of sample wells to more than one destination pipette tray each having a second number of sample wells that is different than the first number of sample wells of source pipette tray (e.g., the contents of a source pipette tray having 384 sample wells is expanded to four destination pipette trays each having 96 sample wells). Tray compression reformatting is an operation that spreads the contents of sample wells of more than one source pipette tray each having a first number of sample wells to a destination pipette tray having a second number of sample wells that is different than the first number of samples wells of each source tray (e.g., the contents of four source pipette trays each having 96 sample wells is compressed to one destination pipette tray having 384 sample wells). Reagent addition refers to the addition of any suitable liquid from a source pipette tray (or any other suitable reservoir) that is added to the sample wells of a destination pipette tray. Compound addition is the transfer of a set of compounds, or samples, from a source pipette tray to a destination pipette tray. Serial dilution is used to set up different sample concentrations for an experiment where a measured amount of high concentration sample is transferred from a source pipette tray to a destination pipette where that high concentration sample is mixed with a dilution solvent creating a lower concentration sample.

(17) In accordance with the aspects of the present disclosure the storage section **106** includes a reader **198** that is configured to identify each work item holder **118** within the storage section **106** so as to effect the multiplexed or otherwise sequenced ordered transfer of the work item holders **118** from the storage section **106** to the work section **104** for performing a predetermined work/pipetting protocol. As will be described herein, the reader **198** is configured to, with a controller **199** of the automatic assaying system **100**, resolve a sequence of pipette trays **201A-201B** and/or pipette tip set racks **211A-211n** (referred to herein as work item holders **118**), from the storage section **106**, and sequence (e.g., multiplex) the work item holders **118** with automation within the work section **104** according to the predetermined pipetting protocol, and further resolve automatically any blockages in work item multiplexing/sequencing that may exist in the transfer of the work item holders **118** from the storage section **106** to the work section **104** and/or the multiplexing/sequencing within the work section **104**.

(18) Referring to FIGS. **1**, **3**, and **4**, a user of the automatic assaying system **100** initializes a

sequence corresponding to multiple pipetting protocols (or in some aspects one or more pipetting protocols) where, for example, the user enters or selects in a controller **199** of the automatic assaying system **100**, through a user interface **308** of the automatic assaying system **100**, multiple predetermined pipetting/work protocols based on source pipette trays (i.e., pipette trays having a source of specimens on which assays are to be performed) and/or pipette tip set rack holders **211A-211n** held in the storage section **106**. The controller **199** registers (or saves) the user selection of the multiple predetermined pipetting/work protocols in the controller **199** (e.g., the controller includes any suitable memory) or in any suitable memory accessible by the controller **199**. As described herein, the controller **199** is configured to automatically effect the registered more than one predetermined work protocols in a substantially continuous series, wherein for each different predetermined work protocol the controller **199** resolves, based on the respective different predetermined pipetting characteristic, a different corresponding sequence of the pipette trays **201A-201n** and at least one pipette tip set rack **211A-211n** in and with the multiplexing/sequencing work item holder **116** (that determines sequence location and indexing for each pipette tray **201A-201n** and the at least one pipette tip set rack **211A-211n**) for the corresponding sequence and sequence transition between different registered predetermined pipetting/work protocols to effect the different registered predetermined pipetting/work protocols substantially continuously.

(19) As will be described in further detail herein, the source pipette trays, pipette tip set racks **211A-211n**, and/or destination pipette trays (i.e., pipette trays into which a portion of the source of specimen in the source pipette tray is transferred) are manually loaded into the storage section **106** or loaded into the storage section **106** with any suitable automation. A reader **198** of the automatic assaying system **100** reads or otherwise identifies the contents of the storage section **106** so as to map locations of the work item holders **118** in the storage section, characterize and identify the work item holders **118** in the storage section **106**, and/or identify missing or miss-loaded work item holders in the storage section **106**. The controller **199** is configured to sequence the registered predetermined pipetting/work protocols in series dependent on map info of the pipette trays **201A-201n** and the at least one pipette tip set rack **211A-211n** in store (e.g., in the storage section **106**). Based on the reading of the work item holders **118** in the storage section **106** by the reader **198**, the controller **199** is configured to compare each of the user selected pipetting protocols (and desired work item holders for performing those selected pipetting protocols) with the contents of the storage section **106** to verify that the selected pipetting protocols can be performed using the work item **118** stored in the storage section **106**. For each selected pipetting protocol that can be performed using the work item holders **118** stored in the storage section **106**, for each of the selected pipetting protocols the controller **199** is configured to present verification to the user through the user interface **308** that the selected pipetting protocol will be performed. If a work item **118** desired for a selected pipetting protocol is missing, miss-loaded or is otherwise unselectable, the controller **199** is configured to present a notification to the user, for each pipetting protocol that cannot be performed, through the user interface **308** that the selected pipetting protocol is unselectable or cannot be performed until the missing, miss-loaded or is otherwise unselectable work item holder **118** is remedied. As described herein, remedying of the missing, miss-loaded or is otherwise unselectable work item holder **118** may be performed while the automatic assaying system **100** is performing work/pipetting operations.

(20) The controller **199** is configured to, based on the selected pipetting protocols, identify and determine (from the map of the storage locations noted above) locations of the source pipette tray(s), the destination pipette tray(s), and/or the pipetting tip set rack(s) desired for each of the selected pipetting protocols. The controller **199** generates a multiplexing/sequencing of the desired work item holders **118** to move the desired work item holders automatically from the storage section **106** to the work section **104**, and then back to the storage section **106** or to any suitable output of the automatic assaying system **100** (where output of the work item holder **118** effects transfer of the work item holder **118** to the user). The multiplexing/sequencing of the desired work

item holders **118** provides for the segway/switching (e.g., in the multiplexing/sequencing) from a terminus sequence/multiplex of one pipetting protocol to a start multiplex/sequence of another pipetting protocol so that a substantially continuous uninterrupted flow of work item holders is maintained between the storage section **106** and the work section **104**. For example, the controller **199**, when nearing the terminus multiplex/sequence of the one pipetting protocol, determines which of the selected pipetting protocols to perform next (i.e., the sequence in which the selected pipetting protocols is effected automatically by the controller as described herein), where the controller **199** effects pre-loading of work item holders **118** for the next/following pipetting protocol in the work section **104** prior to the terminus multiplex/sequence of the one/previous pipetting protocol.

(21) To resolve any blockages in the multiplexing/sequencing of a predetermined pipetting protocol, the controller, in one aspect, re-sequences the predetermined pipetting protocol in its entirety (e.g., a different pipetting protocol unaffected by the blockage is performed instead of the pipetting protocol affected by the blockage) and/or partially re-sequences the predetermined pipetting protocol so as to be performed in multiple steps (e.g., a first pipetting protocol unaffected by the blockage is partially performed, at least a second pipetting protocol is performed, and then first pipetting protocol is completed once the blockage is remedied) to maintain the substantially continuous uninterrupted flow of work item holders **118**. Such blockages may be a result of a predetermined work item holder **118** not be loaded into (i.e., present/stored within) the storage section **106**, the predetermined work item holder **118** being incorrectly loaded in the storage section **106**, or any other circumstance where a predetermined work item holder **118** cannot be transferred from the storage section **106** to the work section **104**. As may be realized, in some aspects, the system and method described herein provide for execution of a variety of pipetting operations (such as those described above and referred to herein as work protocols or pipetting protocols) within the automatic assaying system **100** substantially without manual intervention.

(22) Still referring to FIG. **1** and also to FIGS. **2**, **3**, **4**, and **5A**, the automatic assaying system **100** includes a frame **101**, a multiplex pipette cartridge section **138**, a multiplexing work item holder **116** (also referred to herein as a sequencing work item holder), a carrier **130**, and a controller **199**. The multiplex pipette cartridge section **138** is connected to the frame **101** and has an array of multiple pipette cartridge docks **139A-139n** (where *n* is an integer that denotes an upper numerical limit to the number of multiple pipette cartridge docks) arrayed along an array axis **590** (FIG. **5A**). Each multiple pipette cartridge dock **139A-139n** of the multiple pipette cartridge docks **139A-139n** is configured to dock a corresponding pipette cartridge **114A-114n** (where *n* is an integer that denotes an upper numerical limit to the number of pipette cartridges), where at least one pipette cartridge **114A-114n** of the corresponding pipette cartridges **114A-114n** has a different pipetting characteristic from another corresponding pipette cartridge **114A-114n**. The different pipetting characteristic is selectable from a number of different pipetting characteristics that include, but are not limited to, a number of pipetting tips (e.g., a single row of pipetting tips, an array of tips corresponding to standard SBS tray types such as 96 well trays, 384 well trays, 1536 well trays, 6144 well trays or any other tray having any suitable number of wells), a type of pipetting tip(s) (e.g., disposable tips made of various types of plastics that are designed to be discarded and replaced after each pipetting action, or fixed tips made of stainless steel tube (or other suitable material) that are used repeatedly and washed between pipetting actions), and/or any other suitable pipetting characteristic.

(23) In accordance with aspects of the present disclosure, the pipette cartridges **114A-114n** have interchangeable pipette tip set racks **211A-211n** that can reconfigure a pipette cartridge **114A-114n** from having a first pipetting characteristic to a second different pipetting characteristic. As described herein, the different pipette tip set racks **211A-211n** are transferred from the storage section **106** to the work section **104** for coupling with a predetermined pipette cartridge **114A-114n** so as to change the pipetting characteristic of the predetermined pipette cartridge. As may be realized, the pipette cartridge **114A-114n** (and/or the pipette tip set racks **211A-211n** of one or more

the pipette cartridges **114A-114n**) are automatically changed so as to change the different pipetting characteristic to effect a pipetting protocol as described herein and maintain a substantially continuous uninterrupted flow of work item holders **118** and a substantially continuous uninterrupted execution of more than one pipetting protocol by the automatic assaying system **100**.

(24) The multiplexing work item holder **116** is connected to the frame and includes an array of work item holder docks **121A-121n** (where n is an integer that denotes an upper numerical limit to the number of work item holder docks) that are disposed facing the array of multiple pipette cartridge docks **139A-139n** and are substantially aligned with the array axis **590** (FIG. 5A). Each work item holder dock **121A-121n** of the array of work item holder docks **121A-121n** is configured to dock a corresponding work item holder **118A-118n** (where n is an integer that denotes an upper numerical limit to the number of work item holders). The work item holders **118A-118n** are generally referred to as work item holders **118** and are selectable from a number of different interchangeable pipette trays **201A-201n** (where n is an integer that denotes an upper numerical limit to the number of different interchangeable pipette trays) and at least one pipette tip set rack **211A-211n** (where n is an integer that denotes an upper numerical limit to the number of pipette tip set racks) that defines the selectable different pipetting characteristic. In accordance with aspects of the present disclosure, each of the different interchangeable pipette trays **201A-201n** has a different work characteristic. For example, the number of different interchangeable pipette trays **201A-201n** comprise pipette trays with different work sample wells or receptacles capacities. Where the different work characteristic is a number of sample wells, the different interchangeable pipette trays **201A-201n** include 96 well trays **201A**, 384 well trays **201B**, 1536 well trays **201C**, 6144 well trays **201D**, trays with less than 96 wells, and/or trays with more than 6144 wells. In accordance with aspects of the present disclosure each of the 96 well trays **201A**, 384 well trays **201B**, 1536 well trays **201C**, 6144 well trays **201D**, trays with less than 96 wells, and/or trays with more than 6144 wells may also have varying receptacle capacities (e.g., the volume of each well may vary for the same type of tray such as a volume of the wells of one 96 well tray may be greater than a volume of the wells of another 96 well tray). The different interchangeable pipette trays **201A-201n** are standardized so as to have a SBS-format footprint (e.g., the base of the tray has a standardized length and width, i.e., footprint) or any other suitable standardized footprint that facilitates the interchangeability of the pipette trays **201A-201n**.

(25) As noted above, the at least one pipette tip set rack **211A-211n** defines the selectable different pipetting characteristic of the pipette cartridge **114A-114n** to which it is coupled/connected. Here, the at least one pipette tip set rack **211A-211n** is interchangeable from a number of different pipette tip set racks **211A-211n**, each having a different set of (or type of) a different predetermined number of one of more pipette tips. For example, the selectable different pipetting characteristic is a 96 pipette tip set rack **211A** (e.g., having 96 pipette tips), a 384 pipette tip set rack **211B** (e.g., having 384 pipette tips), a 1536 pipette tip set rack **211C** (e.g., having 1536 pipette tips), a 6144 pipette tip set rack **211D** (e.g., having 6144 pipette tips), a pipette tip set rack having less than 96 pipette tips, and a pipette tip set rack having more than 6144 pipette tips, where the pipette tips of the selectable pipette tip set racks **211A-211n** are either fixed (e.g., reusable) or disposable as described herein.

(26) Referring to FIGS. 1, 5A and 5B, the multiplexing work item holder **116** has indexing sections **120** indexing one or more of the work item holder docks **121A-121n** relative to the frame **101** between different positions so as to selectably multiplex both the different interchangeable pipette trays **201A-201n** and the at least one pipette set rack **211A-211n** corresponding to the work item holder dock **121A-121n**. For example, the work section **104** includes a set of pipette cartridges **114A-114n** docked in the multiplex pipette cartridge section **138** (e.g., at a respective multiple pipette cartridge dock **139A-139n**). The work section **104** further includes at least one indexing section **120A-120n** holding a respective set (e.g., at least one) of work item holders **118A-118n**. The work section **104** includes any suitable drive section to effect movement of the at least one

indexing section **120A-120n** as described herein. Each of the indexing sections **120A-120n** includes distinct work item holder docks **121A-121n**, which include at least one static nest position **118** (such as for example, indexing section **120A**), and at least one dynamic nest position **520** (such as for example, tray docks **120B-120n**). In one or more aspects of the present disclosure, the dynamic nest positions **520** are at distinct heights (Z-direction) within the work section **104**, and are adjustable horizontally (X-direction) within the work section **104**. In one or more aspects, one indexing section can be loaded/unloaded onto/off-of the static nest position **118** from one of the dynamic nest positions **520** by an articulated bot (or robot) arm **122**, which is movable in the X-direction, Y-direction and Z-direction.

(27) The carrier **130** is connected to the frame **101** and includes a gantry **131** arranged so as move, with a gripper **133** (also referred to as a cartridge carriage) of the gantry **131**, the at least one pipette cartridge **114A-114n** or a work item holder carriage **132** (e.g., which may be integrated with or in addition to the gripper **133** and transports the work item holders **118**), of the carrier **130**, relative to the frame **101** between the array of multiple pipette cartridge docks **139A-139n** and the array of work item holder docks **121A-121n** multiplexing the at least one pipette cartridge **114A-114n** and interfacing the at least one pipette cartridge **114A-114n** with multiplexing one of the different interchangeable pipette trays **201A-201n** and the at least one pipette tip set rack **211A-211n** at the array of work item holder docks **121A-121n**.

(28) Referring to FIGS. **1** and **5B**, the carrier **130** is coupled to frame **101** within the work section **104** above the multiplex pipette cartridge section **138** and the multiplexing work item holder **116** so that the gantry **131** moves relative to the frame for transporting/moving the at least one pipette cartridge **114A-114n** or a work item holder carriage **132** within the work section **104**. The gantry **131** is mounted to the frame **101** in any suitable manner, and includes at least two distinct tracks, e.g., at least one stationary track **532** (two shown) aligned in a first direction (X-direction), and a movable track **534** aligned in a second direction (Y-direction) distinct from the first direction. The movable track **534** can be coupled to the stationary track(s) **532**, e.g., by complementary track integration, meaning that the movable track **534** can move within the stationary track(s) **532**, such that the movable track **534** remains perpendicular to the stationary track(s) **532**. In the aspect illustrated in FIG. **5B** the at least one stationary track **532** includes two distinct stationary tracks **532** aligned in parallel with each other, where the two distinct stationary tracks **532** are aligned perpendicular to the movable track **534**; however, in other aspects the carrier **130** may have any suitable configuration that provides three dimensional movement to the gripper **133** and/or work item holder carriage **132** for transporting the at least one pipette cartridge **114A-114n** or a work item holder carriage **132** within the work section **104**. As may be realized, the carrier **130** includes any suitable drive section for effecting the movement of the gantry **130** as described herein.

(29) As shown in FIGS. **5A** and **5B**, the carrier **130** is configured to transport each of the set of pipette cartridges **114A-114n** to a pipetting location, e.g., a location of at least one of the pipette trays **201A-201n** within a work item holder dock **121A-121n** in the work section **104**. As described herein, the carrier **130** is configured to move each pipette cartridge **114A-114n** (e.g., held by the carrier **130**) in a third direction (Z-direction) perpendicular to both the first (X) and second (Y) directions. In one or more aspects, the gantry **131** is configured to rotate the gripper **133** about a primary axis A_{cp} (i.e., of the gripper **133** and/or work item holder carriage **132**) such that the carrier **130** can circumferentially navigate about one or more of the pipette cartridges **114A-114n**. Further, the carrier **130**, when engaged with a pipette cartridge **114A-114n**, can rotate that pipette cartridge **114A-114n** about the primary axis A_{cp} , which may facilitate pipetting operations, as well as facilitates loading and/or unloading of pipette cartridges **114A-114n** to and from the multiple pipette cartridge dock **139A-139n** and/or pipette tip set rack **211A-211n** loading and/or unloading to and from the pipette cartridges **114A-114n** at the work item holder docks **121A-121n** of the indexing sections **120**.

(30) In one or more aspects, for example, as shown in FIG. **5A**, the pipette cartridges **114A-114n**

are docked in respective multiple pipette cartridge docks **139A-139n** which are coupled to a sidewall **555** of the interior of the work section **104**. The multiple pipette cartridge docks **139A-139n** can be located in such a manner that the carrier **130** engages the pipette cartridges **114A-114n** from a top surface **542** of the pipette cartridges **114A-114n**. However, in aspects, the pipette cartridges **114A-114n** are docked in multiple pipette cartridge docks **139A-139n** that are coupled to a ceiling of the work section **104**, such that the pipette cartridges **114A-114n** hang from overhead mounts in the work section **104**. In these aspects, the carrier **130** can be configured to engage a side of the pipette cartridges **114A-114n** and transport the pipette cartridges **114A-114n** to/from the work item holders **118A-118n** located at the work item holder docks **121A-121n** and the multiple pipette cartridge docks **139A-139n**.

(31) In accordance with the aspects of the present disclosure, and referring again to FIGS. **1**, **3**, **4**, **5A** and **5B**, the frame **101** is arranged so that the multiplex pipette cartridge section **138**, the multiplexing work item holder **116**, and the carrier **130** are disposed in the work section of the frame **104**. The automatic assaying system **100** further comprises the storage section **106** connected to the frame **101**. In the aspects illustrated in the Figs. the storage section **106** is located beneath the work section **104**; however, in other aspects the storage section **106** may be located above the work section **104** or to a side of the work section **104** (e.g., in the same horizontal plane as the work section **104**). The storage section **106** has an automated random access storage array **107** configured for storing therein work item holders **118**. For example, the automated random access storage array **107** is configured to store each pipette tray **201A-201n** of the number of different interchangeable pipette trays **201A-201n** and each of the at least one pipette tip set rack **211A-211n** isolated from the work section **104** where the pipette trays **201A-201n** and the at least one pipette tip rack set **211A-211n** are loaded and unloaded from at least one of the work item holder docks **121A-121n**. As illustrated in FIGS. **3**, **4**, and **5A**, the automated random access storage array **107** is in the form of a rotatable carousel that has stacked holding locations **366** arranged radially about an axis of rotation of the carousel. The stacked holding locations **366** include holding locations **366A** for holding the pipette trays **201A-201n** and holding locations **366B** for holding the pipette tip set racks **211A-211n**.

(32) Referring to FIGS. **1**, **3**, and **5A**, the automatic assaying system **100** includes the articulated bot arm **122** which is movably connected to the frame **101**. The articulated bot arm **122** is illustrated as a SCARA (Selective Compliant Articulated Robot Arm) type arm; however, in other aspects the articulated bot arm **122** has any suitable configuration for transporting work item holders **118** as described herein. In one aspect, the articulated bot arm may be substantially similar to that described in U.S. patent application Ser. No. 16/653,537 filed on Oct. 15, 2019 and titled "Pipettor System" (now U.S. Pat. No. 10,613,110 issued on Apr. 7, 2020), the disclosure of which is incorporated herein by reference in its entirety. The articulated bot arm **122** is configured to automatically transport each of at least one of the number of different interchangeable pipette trays **201A-201n** and the at least one pipette tip set rack **211A-211n** from respective holding locations **366** of storage section **106** to and from the work section **104** and loading and unloading a corresponding work item dock **121A-121n** with the at least one of the number of different interchangeable pipette trays **201A-201n** and the at least one pipette tip set rack **211A-211B** being transported. For example, the storage section **106** and the work section **104** are fluidly connected (such that a fluid, e.g., air, water, etc. may pass between) such that the pipette trays **201A-201n** and the pipette tip set racks **211A-211n** can be passed between the work section **104** and the storage section **106** (and vice versa) with the articulated bot arm **122** (or other suitable lift system). The storage section **106** stores pipette trays **201A-201n** and pipette tip set racks **211A-211n** when not in use in the work section **104**.

(33) The articulated bot arm **122** is configured to move the pipette trays **201A-201n** and the pipette tip set racks **211A-211n** along the Z direction between the work section **104** and the storage section **106** (see FIG. **5A**). For example, the work section **104** and the storage section **106** are separated by

a partition wall **575**. The partition wall **575** includes a passage **576** that is shaped and sized to provide passage of the articulated bot arm **122** between the work section **104** and the storage section **106**. In one or more aspects the passage **576** is a sealable passage. In addition to movement in the Z direction (e.g., for transport of work item holders **118** between the work section **104** and the storage section **106**) the articulated bot arm **122** is also configured to move in the X-Y plane to move the work item holders **118** (e.g., such as the pipette trays **201A-201n** and the pipette tip set racks **211A-211n**) in the X and Y directions within each of the work section **104** and the storage section **106**. Movement of the work item holders **118** in at least the X-Y plane within the storage section **106** facilitates insertion and removal of the work item holders **118** to and from the automated random access storage array **107**. Movement of the work item holders **118** in at least the X-Y plane within the work section **104** facilitates insertion and removal of the work item holders **118** to and from the work item holder docks **121A-121n** of the indexing sections **120**.

(34) In accordance with the aspects of the present disclosure, referring to FIGS. **1** and **4**, the automatic assaying system **100** includes the reader **198** which is connected to the frame **101** and is communicably coupled to the controller **199**. The reader **198** is disposed to read identification (ID) indicia **119A-119n** identifying a tray characteristic and rack characteristic related to the different pipetting characteristic, of each pipette tray **201A-201n** and each of the at least one pipette tip set rack **211A-211n** stored in the automated random access storage array **107** of the storage section **106**. The tray characteristic corresponds to at least one of the selectable different pipetting characteristic, and the rack characteristic is determinative of at least one of the selectable different pipetting characteristic. For example, in one or more aspects aspect, the reader includes a reader housing **410**, a scanner **411**, and any suitable drive system **412** (e.g., linear actuator, ball screw drive, etc.). The housing is mounted or otherwise coupled to the frame **101** so that the scanner **411** faces the automated random access storage array **107**. The work item holders **118** are positioned within the automated random access storage array **107** so that the identification indicia **119A-119n** of each work item holder **118** is visible (i.e., within a field of view FOV) of the scanner **411**. The scanner **411** is any suitable scanner such as one or more of a barcode reader, a laser scanner, a charged coupled device (CCD) sensor, a complementary metal oxide semiconductor (CMOS) sensor, or any other suitable optical sensor configured to read the identification indicia **119A-119n**. The scanner **411** is connected to the drive system **412** so that the drive system **412** drives the scanner in the Z direction to read the identification indicia **119A-119n** of each work item holder **118** in the stacks of stacked holding locations **366**, where rotation of the automated random access storage array facilitates scanning of each stack of the stacked holding locations **366** by the reader **198**. In other aspects, the automated random access storage array **107** and reader **198** have any suitable configurations for holding and scanning the work item holders **118** in the storage section **106**. For example, the reader **198R** (FIGS. **1** and **3**), in some aspects, is located on the articulated bot arm **122** (but is otherwise similar to reader **198**) where the articulated bot arm **122** positions the reader in the X, Y, and/or Z directions to read the identification indicia **119A-119n** of each work item holder **118** in the stacks of stacked holding locations **366**, where rotation of the automated random access storage array facilitates scanning of each stack of the stacked holding locations **366** by the reader **198**. In still other aspects, the automatic assaying system **100** both reader **198** and reader **198R**.

(35) As noted above, the identification indicia **119A-119n** identifies a tray characteristic and rack characteristic related to the different pipetting characteristic of the pipette trays **201A-201n** and the pipette tip set rack **211A-211B**. For example, with respect to the pipette trays **201A-201n**, the identification indicia **119A-119n** identifies one or more of the number of wells in a respective pipette tray **201A-201n**, a volume of each well of a respective pipette tray **201A-201n** or any other suitable characteristic. The identification indicia **119A-119n** identify, in one or more aspects, a tray characteristic relating one pipette tray **201A-201n** to other pipette trays **201A-201n** of a set of pipette trays **665, 666** (see FIG. **6A**) with the different pipetting characteristic being common to

each pipette tray **201A-201n** of the set **665, 666**. For exemplary purposes only, each pipette tray in the set **665** has the common characteristic of each pipette tray having 384 wells; while each pipette tray in the set **666** has the common characteristic of each pipette tray having 96 wells. The identifying indicia also identify the work item holders **118** (e.g., such as through assignment and registering of the pipette trays with the controller **199**) associated with (or otherwise part of) a pipetting protocol. For example, still referring to FIG. 6A, the work item holders associated with each of the pipetting protocols are associated with each other in the controller **199** to identify which work item holders **118** are related to each other via a common (i.e., the same) pipetting protocol. Here, for exemplary purposes only, the work item holders **118** (i.e., the 96 pipette rack, the 384 well tray, and the four 96 well trays) corresponding to the expansion tray reformatting shown in FIG. 6A are related to/associated with each other in the controller **199** (or any suitable memory accessible by the controller) through the respective identification indicia **119A-119n** of the respective work item holders **118**.

(36) The controller **199** is communicably coupled (e.g., via a wired or wireless communication connection) to the multiplexing work item holder **116** and the carrier **130**. The controller **199** is configured to select the at least one pipette tip set rack **211A-211n** corresponding to a work item holder dock **121A-121n** so as to effect automatic selection of the different pipetting characteristic of the at least one pipette cartridge **114A-114n** via the interface between the at least one pipette cartridge **114A-114n** and the multiplexed one of the corresponding pipette trays **201A-201n** and pipette tip set rack **211A-211n** at the array of work item holder docks **118A-118n**. For example, the controller **199** is programmed to perform one or more predetermined pipetting protocols (such as those illustrated in FIG. 6B), where a user selects the predetermined pipetting protocols. The controller **199** is programmed in any suitable manner such as through a user interface **308** (see FIGS. 3 and 4) of the automatic assaying system **100** or through any other user interface coupled to the controller **199**. The work item holders **118** for completing the selected one or more pipetting protocols are loaded into the storage section **106** in any suitable manner. In one aspect the work item holders **118** are loaded (and/or unloaded) into the automated random access storage array **107** manually; while in other aspects, the work item holders **118** are loaded (and/or unloaded) into the automated random access storage array **107** with any suitable automation, such as where the automatic assaying system **100** is part of a larger automated system. For example, the articulated robot arm **122** may transfer the work item holders **118** from (or to) a cart or storage located outside the frame **101**, and accessible to the articulated robot arm **122**, to (or from) the automated random access storage array **107**. In other aspects, any suitable robot arm or transfer device located on a cart or other suitable location/equipment interfaced with the automatic assaying system **100** may extend into the frame **101** for placing (or removing) the work item holders **118** to (or from) the automated random access storage array **107**).

(37) In one or more aspects, the reader **198** identifies the work item holders loaded into the automated random access storage array **107** and the controller **199** receives the identification information from the reader **198**. The controller **199** is configured to register the identifications of the work item holders **118** within the automated random access storage array **107** in a memory of or accessible by the controller **199**. The controller **199** is configured to compare the contents of the random access storage array **107** (as determined by the reader **198**) with desired work item holders for completing the selected one or more pipetting protocols to verify that the desired work item holders **118** for completing the selected one or more pipetting protocols are present in the random access storage array **107**. Where all of the work item holders **118** are not present the controller **199** causes an alert (e.g., aural or visual) to be presented to an operator of the automatic assaying system **100** through, for example the user interface **308** (see FIGS. 3 and 4).

(38) The controller **199** is configured to issue control commands to the articulated bot arm **122**, the automated random access storage array **107**, and the multiplexing work item holder **116** so that the desired work item holders **118** for completing the selected one or more pipetting protocols are

transferred in the substantially continuous uninterrupted flow from the storage section **106** to the work section **104** in any suitable multiplexed order (e.g., forming the substantially continuous uninterrupted flow). The multiplexed order is such that the work item holders **118** are presented to the carrier **130** (i.e., holding a pipette cartridge **114A-114n** that effects pipetting operations of a predetermined one of the selected pipetting protocols) so that at least the predetermined pipetting protocol can be performed on predetermined groups of work item holders **118** belonging to/corresponding with the respective pipetting protocol as determined by the pipette characteristic of the at least one pipette cartridge **114A-114n** used to complete the predetermined pipetting protocol.

(39) Referring to FIGS. **1**, **3**, **4**, and **6A**, in accordance with the aspects of the present disclosure, an order in which the selected pipetting protocols is performed is automatically selected by the controller **199**. The respective different interchangeable pipetting characteristic of the at least one pipette cartridge **114A-114n** for each pipetting protocol is automatically selected by the controller **199** with the ordering of the selected pipetting protocols. In one or more aspects the order in which the selected pipetting protocols is performed is a dynamic order in that the order may be modified or changed so that the sequencing of the selected pipetting protocols can be rearranged during operation. For example, referring to FIG. **6A**, the controller **199** determines a predetermined order of performing the pipetting protocols based on, e.g., data entered (e.g., the protocols to be performed) by an operator through the user interface **308** (see FIGS. **3** and **4**) is shown where the protocols are performed in the order of tray replication, tray reformatting (expansion), tray reformatting (compression), reagent addition, compound addition, and serial dilution. As noted above, the reader **198** verifies the presence or absence (e.g., physically not present, inserted incorrectly in a storage location, or any other miss-insertion of the work item holder that prevents reading the identification indicia or automated transport within the automatic assaying system **100**) of the pipette set tip racks **211A-211n** and the pipette trays **201A-201n** corresponding to the pipetting protocols within the automated random access storage array **107**.

(40) The absence of a work item holder **118** may be referred to herein as a blockage in sequencing of the desired pipetting protocols where the controller **199** is configured to resolve (e.g., find a solution to) the blockage so as to maintain the substantially continuous uninterrupted flow of work item holders **118** between the storage section **106** and the work section **104**. For example, where one or more of the pipette set tip racks **211A-211n** and the pipette trays **201A-201n** are determined to be absent from the automated random access storage array **107**, rather than halt operations of the automatic assaying system **100**, the controller **199** is configured to rearrange the pipetting protocol order in any suitable manner so that pipetting protocols (or portions thereof) with the desired work item holders **118** present in the automated random access storage array **107** are performed while, in an aspect where the work item holders **118** are provided to the storage section **106** manually, an alert (e.g., aural or visual) is presented to an operator through the user interface **308** to rectify the absence of the one or more of the pipette set tip racks **211A-211n** and the pipette trays **201A-201n**; while in other aspects where the work item holders **118** are provided to the storage section **106** with any suitable automation, a request or a command for the desired work item holders to be transferred to the storage section **106** may be made by the controller **199** to any suitable automation to effect transfer of the desired work item holders **118** to the storage section **106**. For example, where one or more of the 96 pipette rack, 384 well tray, or 96 well tray for the expansion tray reformatting is/are determined to be absent the expansion tray reformatting protocol may be moved to the end of the protocol performance order/sequence so that the expansion tray reformatting protocol is performed last; while in other aspects a portion of the expansion tray reformatting protocol for which the work item holders **118** are present may be performed where a remaining portion of the expansion tray reformatting protocol is performed at a later time in the protocol performance order/sequence when the work item holders **118** become available. In this manner, the substantially continuous uninterrupted flow of work item holders **118** between the

storage section **106** of the automatic assaying system **100** and the work section **104** of the automatic assaying system **100** is effected.

(41) In providing the substantially continuous uninterrupted flow of work item holders **118** between the storage section **106** and the work section **104** the controller **199** is configured to operate the storage section **106**, the work section **104**, and the articulated bot arm **122** so as to multiplex or sequence the number of different interchangeable pipette trays **201A-201n** with the multiplexing work item holder **116** according to the different pipette characteristic of the at least one pipette cartridge **114A-114n**. The number of different pipette trays **201A-201n** multiplexing corresponds respectively with the different interchangeable pipetting characteristic, of the at least one pipette cartridge **114A-114n**, ahead of automatic selection and behind automatic selection of the different pipetting characteristic. For example, still referring to FIGS. **1** and **6A** and also to FIG. **6B**, the controller **199** automatically selects (such as when dynamically determining a processing order of the pipetting protocols) the different interchangeable pipetting characteristics of the 6144 pipette rack, the 96 pipette rack, and the 384 pipette rack to effect the pipetting operations of, for example, any suitable desired pipetting protocol in the sequence of pipetting protocols, such as tray replication, expansion tray reformatting, and compression tray reformatting. In one or more aspects, the 6144 pipette rack, the 96 pipette rack, and the 384 pipette rack are provided as disposable pipette tip rack sets from the storage section **106** and are associated with one or more of the pipette cartridge **114A-114n**, where one of the pipette cartridges **114A-114n** picks up a respective one of the 6144 pipette rack, the 96 pipette rack, and the 384 pipette rack from the multiplexing work item holder **116**; however in other aspects the pipette tip set racks may be fixed pipette set tip rack that are coupled to a respective pipette cartridge **114A-114n** in any suitable manner (e.g., provided directly to the work section **104** with a respective pipette cartridge **114A-114n** or transferred to and coupled with the respective pipette cartridge **114A-114n** from the storage section **106**) and cleaned as desired for reuse in multiple pipetting protocols.

(42) The pipette tip set racks **211A-211n** (such as the 6144 pipette rack, the 96 pipette rack, and the 384 pipette rack noted above) and the pipette trays **201A-201n** of the respective pipetting protocols are transferred to the work area **104** from the storage area **106** in any suitable manner so that the desired work item holders **118** are presented to the carrier **130** for executing/performing the desired pipetting protocol. For example, the work item holders **118** need not be transferred from the storage area **106** to the work area **104** in a predetermined sequence (e.g., all work items **118** for the tray replication pipetting protocol are transferred to the work area prior to the work items of the expansion tray reformatting pipetting protocol, etc.) but rather, the work items may be transferred in an optimized manner (e.g., shortest transfer times, etc.) as determined by the controller **199** to effect the substantially continuous uninterrupted flow of work item holders **118**. For example, the controller **199** is communicably coupled to the multiplexing/sequencing work item holder **116** and the carrier **130** and is configured to select the at least one pipette tip set rack **211A-211n** corresponding to the work item holder dock and effect, via random access sequencing of each corresponding pipette cartridge **114A-114n**, automatic selection of the different pipetting characteristic of at least one pipette cartridge. In one or more aspects, the controller **199** is configured to select the at least one pipette tip set rack **211A-211n** corresponding to the work item holder dock **121A-121n** and effect, via random access sequencing of each corresponding pipette cartridge **114A-114n**, automatic selection of the different pipetting characteristic of at least one pipette cartridge **114A-114n** based on the rack characteristic identified by the reader **198**.

(43) Referring to FIG. **6B** the pipetting protocols of FIG. **6A** are shown alongside an exemplary order in which the work items **118** of those pipetting protocols are randomly accessed by the articulated bot arm **122** from the automated random access storage array **107** and transferred to the indexing sections **120A-120C** of the multiplexing/sequencing work item holder **116**. For exemplary purposes only and referring to the pipetting protocol sequence illustrated in FIG. **6A**, an exemplary random access loading of the indexing sections **120** will be described. In the random access

sequencing example shown in FIG. 6B, the 384 well tray and 96 pipette rack of the expansion tray reformatting pipetting protocol are placed on indexing section **120A** ahead of (i.e., multiplexed with) the 6144 well trays and the 6144 pipette rack of the tray replication pipetting protocol. The remaining 96 well trays of the expansion tray reformatting pipetting protocol are placed on indexing section **120B** followed by a 384 well tray of the compression tray reformatting pipetting operation. In this manner, referring to FIGS. 5A and 5B, indexing section **120A**, once loaded as noted above, is presented to the carrier **130** by moving the indexing sections **120A-120C** in one or more of the Z, X, and Y directions to the carrier **130** so that the desired work item holders **118** for the tray replication pipetting protocol are presented to the carrier, along with a portion of the work item holders for the expansion tray reformatting pipetting protocol (noting that indexing section **120B** may continue to be loaded with the work item holders **118** noted above).

(44) As can be seen in FIGS. 5A and 5B, multiple indexing section **120A-120C** can be simultaneously presented to the carrier **130**. Here the indexing section **120B** is also presented to the carrier so that in combination with indexing section **120A** the desired work item holders **118** for the expansion tray reformatting pipetting operation along with some of the work item holders **118** for the compression tray reformatting pipetting operation are presented to the carrier **130**. The controller **199** issues commands to the carrier **130** so that the tray replication pipetting protocol and the expansion tray reformatting are executed using indexing section **120A** and **120B** while indexing section **120C** is loaded with the 1536 well tray, the remaining 384 well trays, and the 384 pipette tip set rack of the compression tray reformatting pipetting operation. The indexing sections **120A-120C** are multiplexed so that indexing section **120A** is presented to the articulated bot arm **122** for unloading/returning the work items **118** thereon to the storage section **106**, while indexing sections **120B**, **120C** are presented to the carriage **130** for execution of the compression tray reformatting. During the compression tray reformatting, the indexing section **120A** is loaded with the desired work items **118** for the reagent addition and compound addition pipetting protocols in the order of the 96 well tray (of the compound addition pipetting protocol), the 96 well tray (containing reagent) (of the reagent addition pipetting protocol), the 96 pipette tip set rack, the 96 well tray (of the reagent addition pipetting protocol), and the 384 well tray (containing compound) (of the compound addition pipetting protocol). The indexing sections **120A-120C** are multiplexed so that indexing section **120B** is presented to the articulated bot arm **122** for unloading/returning the work items **118** thereon to the storage section **106**, while indexing sections **120C**, **120A** are presented to the carriage **130** for execution of at least the reagent addition pipetting protocol. Once unloaded, the remaining 384 pipette rack of the compound addition pipetting protocol is loaded on indexing section **120B** along with the 384 pipette tip set rack, the 384 well tray, and the 384 well tray (containing dilution solvent) of the serial dilution pipetting protocol. The indexing sections **120A-120C** are again multiplexed so that indexing sections **120A**, **120B** are presented to the carrier for completion of the compound addition pipetting protocol and the serial dilution pipetting protocol.

(45) As can be seen above, while pipetting protocol operations are being performed by the carrier **130** in the work section **104** on work item holders **118** disposed in the work item holder docks **121A-121n** of one or more indexing sections **120A-120n**, work item holders **118** are transferred from the storage section **106** by the articulated bot arm **122** to other indexing sections **120A-120n** to provide for the substantially continuous uninterrupted flow of work item holders **118**. As also described above, the operations of the carrier **130** and the articulated bot arm **122** are coordinated by the controller **199** so that work items are randomly accessed by both the articulated bot arm **122** (from the automated random access storage array **107**) and the carrier (from the indexing sections) for performing one or more desired pipetting protocols, such as those described herein, and maintaining the substantially continuous uninterrupted execution of pipetting protocols.

(46) Referring to FIGS. 1, 5A, 5B, and 7, an exemplary method **700** will be described in accordance with one or more aspects of the present disclosure. The method **700** includes providing the frame **101** (FIG. 7, Block **701**). A multiplex pipette cartridge section **138** is provided (FIG. 7,

Block 705). As described herein, the multiplex pipette cartridge section 138 is connected to the frame 101 and has the array of multiple pipette cartridge docks 139A-139n arrayed along the array axis 590. Each multiple pipette cartridge dock 139A-139n of the multiple pipette cartridge docks 139A-139n is configured to dock a corresponding pipette cartridge 114A-114n, where at least one pipette cartridge 114A-114n of the corresponding pipette cartridge 114A-114n has a different pipetting characteristic from another corresponding pipette cartridge 114A-114n, and the different pipetting characteristic is selectable from a number of different pipetting characteristics, such as described above.

(47) The multiplexing work item holder 116 is provided (FIG. 7, Block 710). The multiplexing work item holder 116 is connected to the frame 101 and has the array of work item holder docks 121A-121n disposed facing the array of multiple pipette cartridge docks 139A-139n. The multiplexing work item holder 116 is substantially aligned with the array axis 590, where each work item holder dock 121A-121n of the array of work item holder docks 121A-121n is configured to dock the corresponding work item holder 118 selectable from the number of different interchangeable pipette trays 201A-201n (each having a different work characteristic), and the at least one pipette tip set rack 211A-211n that defines the selectable different pipetting characteristic. The multiplexing work item holder 116 has indexing sections 120 indexing one or more of the work item holder docks 121A-121n relative to the frame 101 between different positions so as to selectably multiplex both the different interchangeable pipette trays 201A-201n and the at least one pipette tip set rack 211A-211n corresponding to the work item holder dock 121A-121n.

(48) The carrier 130, which is connected to the frame 101 and including the gantry 131, moves the at least one pipette cartridge 114A-114n or the work item holder carriage 132, of the carrier 130, relative to the frame 101 (FIG. 7, Block 715) between the array of multiple pipette cartridge docks 139A-139n and the array of work item holder docks 121A-121n multiplexing the at least one pipette cartridge 114A-114n and interfacing the at least one pipette cartridge 114A-114n with multiplexing one of the different interchangeable pipette trays 201A-201n and the at least one pipette tip set rack 211A-211n at the array of work item holder docks 121A-121n. The controller 199, which is communicably coupled to the multiplexing work item holder 116 and the carrier 130, selects (as described above) the at least one pipette tip set rack 211A-211n (FIG. 7, Block 720) corresponding to the work item holder dock 121A-121B so as to effect automatic selection of the different pipetting characteristic of the at least one pipette cartridge 114A-114n via the (multiplexed) interface between the at least one pipette cartridge 114A-114n and the at least one pipette tip set rack 211A-211n at the array of work item holder docks 121A-121n.

(49) As described above, the controller 199 controls multiplexing of the number of different interchangeable pipette trays 201A-201n (FIG. 7, Block 725) with the multiplexing work item holder 116 according to the different pipette characteristic of the at least one pipette cartridge 114A-114n. In accordance with the method 700, the user enters or selects in the controller 199, through a user interface 308 of the automatic assaying system 100, multiple predetermined pipetting/work protocols based on source pipette trays (i.e., pipette trays having a source of specimens on which assays are to be performed) and/or pipette tip set rack holders 211A-211n held in the storage section 106 as described herein and the locations of the corresponding work item holders 118 are mapped within the storage section 106, as also described herein. The controller 199 is configured to, based on the selected pipetting protocols, identify and determine (from the map of the storage locations noted above) locations of the source pipette tray(s), the destination pipette tray(s), and/or the pipetting tip set rack(s) desired for each of the selected pipetting/work protocols as described herein. The controller 199 generates a multiplexing/sequencing of the desired work item holders 118 to move the desired work item holders automatically from the storage section 106 to the work section 104, and then back to the storage section 106 or to any suitable output of the automatic assaying system 100 (where output of the work item holder 118 effects transfer of the work item holder 118 to the user). The articulated bot arm 122 automatically transports (i.e., in

accordance with the multiplexing/sequencing of the desired work item holders **118**) each of at least one of the number of different interchangeable pipette trays **201A-201n** and the at least one pipette tip set rack **211A-211n** from the storage section **106** (FIG. 7, Block **730**) to and from the storage section **106** and loading and unloading a corresponding work item holder dock **121A-121n** with the at least one of the number of different interchangeable pipette trays **201A-201n** and the at least one pipette tip set rack **211A-211n** transported. To identify which work item holders **118** are to be transferred, the reader **198** reads identification indicia (FIG. 7, Block **735**) identifying a tray characteristic and rack characteristic related to the different pipetting characteristic, of each pipette tray **201A-201n** and each of the at least one pipette tip set rack **211A-211n** stored in the automated random access storage array **107** of the storage section **106**.

(50) As described above, the work item holders **118** are transferred from the storage section **106** to the work section **104** to effect pipetting protocols. In one or more aspects, one of the number of different interchangeable pipette trays **201A-201n** is a source tray and another of the different interchangeable pipette trays is a destination tray (See FIG. 6A), and the method **700** includes, with the at least one pipette cartridge **114A-114n**, replicating contents of the source tray to the destination tray (FIG. 7, Block **740**). In one or more aspects, one of the number of different interchangeable pipette trays **201A-201n** is a source tray and another of the different interchangeable pipette trays is a destination tray, where the method includes, with the at least one pipette cartridge **114A-114n**, tray reformatting (FIG. 7, Block **745**). Where there are multiple destination trays and the tray reformatting comprises a tray expansion, samples are moved with the at least one pipette cartridge **114A-114n**, from a single source tray to the multiple destination trays (see FIG. 6A). Where there are multiple source trays and the tray reformatting comprises a tray compression, samples are moved with the at least one pipette cartridge **114A-114n**, from the multiple source trays to a single destination tray (see FIG. 6A). In one or more aspects, the method **700** includes, with the at least one pipette cartridge **114A-114n**, adding a reagent (FIG. 7, Block **750**) to at least one of the different interchangeable pipette trays **201A-201n** docked in the array of work item holder docks **121A-121n**. In one or more aspects, one of the number of different interchangeable pipette trays **201A-201n** is a source tray and another of the different interchangeable pipette trays is a destination tray, and the method **700** includes, with the at least one pipette cartridge **114A-114n**, a compound addition (FIG. 7, Block **755**) where a set of compounds or samples are moved from the source tray to the destination tray (see FIG. 6A). In one or more aspects, a serial dilution of samples in at least one of the different interchangeable pipette trays **201A-201n** docked in the array of work item holder docks **121A-121n** is performed with the at least one pipette cartridge **114A-114n** (FIG. 7, Block **760**).

(51) Referring to FIGS. 1, 5A, 5B, and 8, an exemplary method **800** will be described in accordance with one or more aspects of the present disclosure. The method **800** includes providing a frame **101** (FIG. 8, Block **801**). A multiplex pipette cartridge section **138** is provided (FIG. 8, Block **805**). As described herein, the multiplex pipette cartridge section **138** is connected to the frame **101** and has an array of multiple pipette cartridge docks **139A-139n** arrayed along the array axis **590**. Each respective multiple pipette cartridge dock **139A-139n** is configured to dock the corresponding pipette cartridge **114A-114n**, where at least one pipette cartridge **114A-114n** of the corresponding pipette cartridge **114A-114n** has a selectably variable pipetting characteristic selectable from a number of different pipetting characteristics, such as described above.

(52) The sequencing work item holder **116** is provided (FIG. 8, Block **810**). The sequencing work item holder **116** is connected to the frame **101** and has the array of work item holder docks **121A-121n** disposed substantially juxtaposed from and substantially aligned with the array axis **590**, where each work item holder dock **121A-121n** of the array of work item holder docks **121A-121n** is configured to dock a corresponding work item holder **118A-118n** selectable from a number of different interchangeable pipette trays **201A-201n** (each having a different work characteristic) and at least one pipette tip set rack **211A-211n** that defines the selectable different pipetting

characteristic. The sequencing work item holder **116** has indexing sections **120** indexing one or more of the work item holder docks **121A-121n** relative to the frame **101** between different position so as to selectably sequence both the different interchangeable pipette trays **201A-201n** and the at least one pipette set rack **211A-211n** corresponding to the work item holder dock **121A-121n**.

(53) The cartridge carriage (or gripper) **133** is moved (FIG. 8, Block **815**), with the carrier **130** connected to the frame **101** and including the gantry **131**, relative to the frame **101** so as to transport each corresponding pipette cartridge **114A-114n** from the respective multiple pipette cartridge dock **139A-139n** effecting random access sequencing of each corresponding pipette cartridge **114A-114n** relative to the corresponding pipette trays **201A-201n** and pipette tip set rack **211A-211n** at each work item holder dock **121A-121n**. The controller **199** selects, as described herein, the at least one pipette tip set rack **211A-211n** (FIG. 8, Block **820**) corresponding to the work item holder dock **121A-121n** and effecting, via random access sequencing of each corresponding pipette cartridge **114A-114n**, automatic selection of the different pipetting characteristic of at least one pipette cartridge **114A-114n**.

(54) As described above, the controller **199** controls sequencing the number of different interchangeable pipette trays **201A-201n** (FIG. 8, Block **825**) with the sequencing work item holder **116** according to the different pipette characteristic of the at least one pipette cartridge **114A-114n**. In accordance with the method **800**, the user enters or selects in the controller **199**, through a user interface **308** of the automatic assaying system **100**, multiple predetermined pipetting/work protocols based on source pipette trays (i.e., pipette trays having a source of specimens on which assays are to be performed) and/or pipette tip set rack holders **211A-211n** held in the storage section **106** as described herein and the locations of the corresponding work item holders **118** are mapped within the storage section **106**, as also described herein. The controller **199** is configured to, based on the selected pipetting protocols, identify and determine (from the map of the storage locations noted above) locations of the source pipette tray(s), the destination pipette tray(s), and/or the pipetting tip set rack(s) desired for each of the selected pipetting/work protocols as described herein. The controller **199** generates a multiplexing/sequencing of the desired work item holders **118** to move the desired work item holders automatically from the storage section **106** to the work section **104**, and then back to the storage section **106** or to any suitable output of the automatic assaying system **100** (where output of the work item holder **118** effects transfer of the work item holder **118** to the user). The articulated bot arm **122** automatically transports (in accordance with the multiplexing/sequencing of the desired work item holders **118**) each of at least one of the number of different interchangeable pipette trays **201A-201n** and the at least one pipette tip set rack **211A-211n** from the storage section **106** (FIG. 9, Block **830**) to and from the storage section **106** and loading and unloading a corresponding work item holder dock **121A-121n** with the at least one of the number of different interchangeable pipette trays **201A-201n** and the at least one pipette tip set rack **211A-211n** transported. To identify which work item holders **118** are to be transferred, the reader **198** reads identification indicia **199A-119n** (FIG. 8, Block **835**) identifying a tray characteristic and rack characteristic related to the different pipetting characteristic, of each pipette tray **201A-201n** and each of the at least one pipette tip set rack **211A-211n** stored in the automated random access storage array **107** of the storage section **106**.

(55) As described above, the work item holders **118** are transferred from the storage section **106** to the work section **104** to effect pipetting protocols. In one or more aspects, one of the number of different interchangeable pipette trays **201A-201n** is a source tray and another of the different interchangeable pipette trays is a destination tray (See FIG. 6A), and the method **800** includes, with the at least one pipette cartridge **114A-114n**, replicating contents of the source tray to the destination tray (FIG. 8, Block **840**). In one or more aspects, one of the number of different interchangeable pipette trays **201A-201n** is a source tray and another of the different interchangeable pipette trays is a destination tray, where the method includes, with the at least one

pipette cartridge **114A-114n**, tray reformatting (FIG. 8, Block **845**). Where there are multiple destination trays and the tray reformatting comprises a tray expansion, samples are moved with the at least one pipette cartridge **114A-114n**, from a single source tray to the multiple destination trays (see FIG. 6A). Where there are multiple source trays and the tray reformatting comprises a tray compression, samples are moved with the at least one pipette cartridge **114A-114n**, from the multiple source trays to a single destination tray (see FIG. 6A). In one or more aspects, the method **800** includes, with the at least one pipette cartridge **114A-114n**, adding a reagent (FIG. 8, Block **850**) to at least one of the different interchangeable pipette trays **201A-201n** docked in the array of work item holder docks **121A-121n**. In one or more aspects, one of the number of different interchangeable pipette trays **201A-201n** is a source tray and another of the different interchangeable pipette trays is a destination tray, and the method **800** includes, with the at least one pipette cartridge **114A-114n**, a compound addition (FIG. 8, Block **855**) where a set of compounds or samples are moved from the source tray to the destination tray (see FIG. 6A). In one or more aspects, a serial dilution of samples in at least one of the different interchangeable pipette trays **201A-201n** docked in the array of work item holder docks **121A-121n** is performed with the at least one pipette cartridge **114A-114n** (FIG. 8, Block **860**).

(56) Referring to FIGS. 1, 5A, 5B, and 9, an exemplary method **900** will be described in accordance with one or more aspects of the present disclosure. The method **900** includes providing a frame **101** (FIG. 9, Block **901**). A multiplex pipette cartridge section **138** is provided (FIG. 9, Block **905**). As described herein the multiplex pipette cartridge section **138** is connected to the frame and has the array of multiple pipette cartridge docks **139A-139n** arrayed along the array axis **590**. Each respective multiple pipette cartridge dock **139A-139n** is configured to dock a corresponding pipette cartridge **114A-114n**, where at least one pipette cartridge **114A-114n** of the corresponding pipette cartridge **114A-114n** has a selectably variable pipetting characteristic selectable from a number of different pipetting characteristics, such as describe above.

(57) The sequencing work item holder **116** is provided (FIG. 9, Block **910**). As described herein, the sequencing work item holder **116** is connected to the frame and has the array of work item holder docks **121A-121n** disposed substantially juxtaposed from and substantially aligned with the array axis **590**, where each work item holder dock **121A-121n** of the array of work item holder docks **121A-121n** is configured to dock a corresponding work item holder **118A-118n** selectable from a number of different interchangeable pipette trays **201A-201n** (each having a different work characteristic) and at least one pipette tip set rack **211A-211n** that defines the selectable different pipetting characteristic. The sequencing work item holder **116** has indexing sections **120** indexing the one or more of the work item holder docks relative to the frame between different positions so as to selectably sequence both the different interchangeable pipette trays and the at least one pipette tip set rack corresponding to the holder dock;

(58) The cartridge carrier (or gripper) **133** is moved (FIG. 9, Block **915**), with the carrier **130** connected to the frame **101** and including the gantry **131**, relative to the frame **101** so as to transport each corresponding pipette cartridge **114A-114n** from the respective multiple pipette cartridge dock **139A-139n** effecting random access sequencing of each corresponding pipette cartridge **114A-114n** relative to the corresponding pipette trays **201A-201n** and pipette tip set rack **211A-211n** at each work item holder dock **121A-121n**.

(59) In accordance with the method **900**, the controller **199** is provided (FIG. 9, Block **920**) and is connected to the reader **198**. The method **900** includes reading, with the reader **198**, the identification indicia **119A-119n** (FIG. 9, Block **925**) identifying a tray characteristic and a rack characteristic of each pipette tray **201A-201n** and each of the at least one pipette tip set rack **211A-211n** loaded in the corresponding work item holder dock **121A-121n**, wherein the tray characteristic corresponds to at least one of the selectable different pipetting characteristic, and the rack characteristic is determinative of at least one of the selectable different pipetting characteristic. The method **900** includes selecting, with the controller **199**, the at least one pipette tip set rack

211A-211n (FIG. 9, Block **930**) corresponding to the work item holder dock **121A-121n** and effecting, via random access sequencing of each corresponding pipette cartridge **114A-114n**, automatic selection of the different pipetting characteristic of at least one pipette cartridge **114A-114n** based on the rack characteristic identified by the reader **198**.

(60) As described above, the controller **199** sequences the number of different interchangeable pipette trays **201A-201n** with the sequencing work item holder **116** (FIG. 9, Block **935**) according to the different pipette characteristic of the at least one pipette cartridge **114A-114n**. In accordance with the method **900**, the user enters or selects in the controller **199**, through a user interface **308** of the automatic assaying system **100**, multiple predetermined pipetting/work protocols based on source pipette trays (i.e., pipette trays having a source of specimens on which assays are to be performed) and/or pipette tip set rack holders **211A-211n** held in the storage section **106** as described herein and the locations of the corresponding work item holders **118** are mapped within the storage section **106**, as also described herein. The controller **199** is configured to, based on the selected pipetting protocols, identify and determine (from the map of the storage locations noted above) locations of the source pipette tray(s), the destination pipette tray(s), and/or the pipetting tip set rack(s) desired for each of the selected pipetting/work protocols as described herein. The controller **199** generates a multiplexing/sequencing of the desired work item holders **118** to move the desired work item holders automatically from the storage section **106** to the work section **104**, and then back to the storage section **106** or to any suitable output of the automatic assaying system **100** (where output of the work item holder **118** effects transfer of the work item holder **118** to the user). The articulated bot arm **122** automatically transports (in accordance with the multiplexing/sequencing of the desired work item holders **118**) each of at least one of the number of different interchangeable pipette trays **201A-201n** and the at least one pipette tip set rack **211A-211n** from the storage section **106** (FIG. 9, Block **940**) to and from the storage section **106** and loading and unloading a corresponding work item holder dock **121A-121n** with the at least one of the number of different interchangeable pipette trays **201A-201n** and the at least one pipette tip set rack **211A-211n** transported. As described herein, to identify which work item holders **118** are to be transferred, the reader **198** reads identification indicia **199A-119n** identifying a tray characteristic and rack characteristic related to the different pipetting characteristic, of each pipette tray **201A-201n** and each of the at least one pipette tip set rack **211A-211n** stored in the automated random access storage array **107** of the storage section **106**.

(61) As described above, the work item holders **118** are transferred from the storage section **106** to the work section **104** to effect pipetting protocols. In one or more aspects, one of the number of different interchangeable pipette trays **201A-201n** is a source tray and another of the different interchangeable pipette trays is a destination tray (See FIG. **6A**), and the method **900** includes, with the at least one pipette cartridge **114A-114n**, replicating contents of the source tray to the destination tray (FIG. 9, Block **945**). In one or more aspects, one of the number of different interchangeable pipette trays **201A-201n** is a source tray and another of the different interchangeable pipette trays is a destination tray, where the method **900** includes, with the at least one pipette cartridge **114A-114n**, tray reformatting (FIG. 9, Block **950**). Where there are multiple destination trays and the tray reformatting comprises a tray expansion, samples are moved with the at least one pipette cartridge **114A-114n**, from a single source tray to the multiple destination trays (see FIG. **6A**). Where there are multiple source trays and the tray reformatting comprises a tray compression, samples are moved with the at least one pipette cartridge **114A-114n**, from the multiple source trays to a single destination tray (see FIG. **6A**). In one or more aspects, the method **900** includes, with the at least one pipette cartridge **114A-114n**, adding a reagent (FIG. 9, Block **955**) to at least one of the different interchangeable pipette trays **201A-201n** docked in the array of work item holder docks **121A-121n**. In one or more aspects, one of the number of different interchangeable pipette trays **201A-201n** is a source tray and another of the different interchangeable pipette trays is a destination tray, and the method **900** includes, with the at least

one pipette cartridge **114A-114n**, a compound addition (FIG. 9, Block **960**) where a set of compounds or samples are moved from the source tray to the destination tray (see FIG. 6A). In one or more aspects, a serial dilution of samples in at least one of the different interchangeable pipette trays **201A-201n** docked in the array of work item holder docks **121A-121n** is performed with the at least one pipette cartridge **114A-114n** (FIG. 9, Block **965**).

(62) In accordance with one or more aspects of the present disclosure an automatic assaying system comprises: a frame; a multiplex pipette cartridge section, connected to the frame, having an array of multiple pipette cartridge docks arrayed along an array axis, each multiple pipette cartridge dock of the multiple pipette cartridge docks is configured to dock a corresponding pipette cartridge, at least one pipette cartridge of the corresponding pipette cartridges having a different pipetting characteristic from another corresponding pipette cartridge, the different pipetting characteristic being selectable from a number of different pipetting characteristics; a multiplexing work item holder, connected to the frame, with an array of work item holder docks disposed facing the array of multiple pipette cartridge docks and substantially aligned with the array axis, each work item holder dock of the array of work item holder docks is configured to dock a corresponding work item holder selectable from: a number of different interchangeable pipette trays, each having a different work characteristic, and at least one pipette tip set rack that defines the selectable different pipetting characteristic, wherein the multiplexing work item holder has indexing sections indexing one or more of the work item holder docks relative to the frame between different positions so as to selectably multiplex both the different interchangeable pipette trays and the at least one pipette set rack corresponding to the work item holder dock; a carrier connected to the frame including a gantry arranged so as move the at least one pipette cartridge or a work item holder carriage, of the carrier, relative to the frame between the array of multiple pipette cartridge docks and the array of work item holder docks multiplexing the at least one pipette cartridge and interfacing the at least one pipette cartridge with multiplexing one of the different interchangeable pipette trays and the at least one pipette tip set rack at the array of work item holder docks; and a controller communicably coupled to the multiplexing work item holder and the carrier and configured to select the at least one pipette tip set rack corresponding to a work item holder dock so as to effect automatic selection of the different pipetting characteristic of the at least one pipette cartridge via the interface.

(63) In accordance with one or more aspects of the present disclosure the number of different interchangeable pipette trays comprise pipette trays with different work sample wells or receptacles capacities.

(64) In accordance with one or more aspects of the present disclosure the at least one pipette tip set rack is interchangeable from a number of different pipette tip set racks, each having a different set of a different predetermined number of one of more pipette tips.

(65) In accordance with one or more aspects of the present disclosure the controller is configured so as to multiplex the number of different interchangeable pipette trays with the multiplexing work item holder according to the different pipette characteristic of the at least one pipette cartridge.

(66) In accordance with one or more aspects of the present disclosure the number of different pipette trays multiplexing corresponds respectively with the different interchangeable pipetting characteristic, of the at least one pipette cartridge, ahead of automatic selection and behind automatic selection of the different pipetting characteristic.

(67) In accordance with one or more aspects of the present disclosure the frame is arranged so that the multiplex pipette cartridge section, the multiplexing work item holder, and the carrier are disposed in a work section of the frame, and the system further comprises a storage section connected to the frame, having an automated random access storage array configured for storing therein each pipette tray of the number of different interchangeable pipette trays and each of the at least one pipette tip set rack isolated from the work section, where the number of different interchangeable pipette trays and the at least one pipette tip rack set are loaded and unloaded from at least one of the work item holder docks.

(68) In accordance with one or more aspects of the present disclosure the automatic assaying system further comprises an articulated bot arm movably connected to the frame and configured for automatically transporting each of at least one of the number of different interchangeable pipette trays and the at least one pipette tip set rack from the storage section to and from the work section and loading and unloading a corresponding work item dock with the at least one of the number of different interchangeable pipette trays and the at least one pipette tip set rack transported.

(69) In accordance with one or more aspects of the present disclosure the automatic assaying system further comprises a reader connected to the frame and communicably coupled to the controller, the reader being disposed to read identification indicia identifying a tray characteristic and rack characteristic related to the different pipetting characteristic, of each pipette tray and each of the at least one pipette tip set rack stored in the automated random access storage array of the storage section.

(70) In accordance with one or more aspects of the present disclosure the identification indicia further identify a tray characteristic relating the pipette tray to other pipette trays of a set of pipette trays with the different pipetting characteristic common to each pipette tray of the set.

(71) In accordance with one or more aspects of the present disclosure the automatic assaying system comprises: a frame; a multiplex pipette cartridge section, connected to the frame, having an array of multiple pipette cartridge docks arrayed along an array axis, each respective multiple pipette cartridge dock is configured to dock a corresponding pipette cartridge, at least one pipette cartridge of the corresponding pipette cartridge having a selectably variable pipetting characteristic selectable from a number of different pipetting characteristics; a sequencing work item holder, connected to the frame, with an array of work item holder docks disposed substantially juxtaposed from and substantially aligned with the array axis, each work item holder dock of the array of work item holder docks is configured to dock a corresponding work item holder selectable from: a number of different interchangeable pipette trays, each having a different work characteristic, and at least one pipette tip set rack that defines the selectable different pipetting characteristic, wherein the sequencing work item holder has indexing sections indexing one or more of the work item holder docks relative to the frame between different positions so as to selectably sequence both the different interchangeable pipette trays and the at least one pipette set rack corresponding to the work item holder dock; a carrier connected to the frame including a gantry arranged so as move a cartridge carriage, of the carrier, relative to the frame so as to transport each corresponding pipette cartridge from the respective multiple pipette cartridge dock effecting random access sequencing of each corresponding pipette cartridge relative to the corresponding pipette trays and pipette tip set rack at each work item holder dock; and a controller communicably coupled to the sequencing work item holder and the carrier and configured to select the at least one pipette tip set rack corresponding to the work item holder dock and effect, via random access sequencing of each corresponding pipette cartridge, automatic selection of the different pipetting characteristic of at least one pipette cartridge.

(72) In accordance with one or more aspects of the present disclosure the number of different interchangeable pipette trays comprise pipette trays with different work sample wells or receptacles capacities.

(73) In accordance with one or more aspects of the present disclosure the at least one pipette tip set rack is interchangeable from a number of different pipette tip set racks, each having a different set of a different predetermined number of one of more pipette tips.

(74) In accordance with one or more aspects of the present disclosure the controller is configured so as to sequence the number of different interchangeable pipette trays with the sequencing work item holder according to the different pipette characteristic of the at least one pipette cartridge.

(75) In accordance with one or more aspects of the present disclosure the number of different interchangeable pipette trays sequencing corresponds respectively with the different pipetting characteristic, of the at least one pipette cartridge, ahead of automatic selection and behind

automatic selection of the different pipetting characteristic.

(76) In accordance with one or more aspects of the present disclosure the frame is arranged so that the multiplex pipette cartridge section, the sequencing work item holder, and the carrier are disposed in a work section of the frame, and the system further comprises a storage section connected to the frame, having an automated random access storage array configured for storing therein each pipette tray of the number of different interchangeable pipette trays and each of the at least one pipette tip set rack isolated from the work section loaded and unloaded from at least one of the work item holder docks.

(77) In accordance with one or more aspects of the present disclosure the automatic assaying system further comprises an articulated bot arm movably connected to the frame and configured for automatically transporting each of at least one of the number of different interchangeable pipette trays and the at least one pipette tip set rack from the storage section to and from the storage section and loading and unloading a corresponding work item holder dock with the at least one of the number of different interchangeable pipette trays and the at least one pipette tip set rack transported.

(78) In accordance with one or more aspects of the present disclosure the automatic assaying system further comprises a reader connected to the frame and communicably coupled to the controller, the reader being disposed to read identification indicia identifying a tray characteristic and rack characteristic related to the different pipetting characteristic, of each pipette tray and each of the at least one pipette tip set rack stored in the automated random access storage array of the storage section.

(79) In accordance with one or more aspects of the present disclosure the identification indicia further identify a tray characteristic relating the pipette tray to other pipette trays of a set of pipette trays with the different pipetting characteristic common to each pipette tray of the set.

(80) In accordance with one or more aspects of the present disclosure an automatic assaying system comprises: a frame; a multiplex pipette cartridge section, connected to the frame, having an array of multiple pipette cartridge docks arrayed along an array axis, each respective multiple pipette cartridge dock is configured to dock a corresponding pipette cartridge, at least one pipette cartridge of the corresponding pipette cartridge having a selectably variable pipetting characteristic selectable from a number of different pipetting characteristics; a sequencing work item holder, connected to the frame, with an array of work item holder docks disposed substantially juxtaposed from and substantially aligned with the array axis, each work item holder dock of the array of work item holder docks is configured to dock a corresponding work item holder selectable from: a number of different interchangeable pipette trays, each having a different work characteristic, and at least one pipette tip set rack that defines the selectable different pipetting characteristic, wherein the sequencing work item holder has indexing sections indexing the one or more of the work item holder docks relative to the frame between different positions so as to selectably sequence both the different interchangeable pipette trays and the at least one pipette set rack corresponding to the holder dock; a carrier connected to the frame including a gantry arranged so as move a cartridge carriage, of the carrier, relative to the frame so as to transport each corresponding pipette cartridge from the respective multiple pipette cartridge dock effecting random access sequencing of each corresponding pipette cartridge relative to the corresponding pipette trays and pipette tip set rack at each work item holder dock; a controller communicably coupled to the sequencing work item holder and the carrier; and a reader connected to the frame and communicably coupled to the controller, the reader being disposed to read identification indicia identifying a tray characteristic and a rack characteristic of each pipette tray and each of the at least one pipette tip set rack loaded in the corresponding work item holder dock, wherein the tray characteristic corresponds to at least one of the selectable different pipetting characteristic, and the rack characteristic is determinative of at least one of the selectable different pipetting characteristic.

(81) In accordance with one or more aspects of the present disclosure the controller is configured to

select the at least one pipette tip set rack corresponding to the work item holder dock and effect, via random access sequencing of each corresponding pipette cartridge, automatic selection of the different pipetting characteristic of at least one pipette cartridge based on the rack characteristic identified by the reader.

(82) In accordance with one or more aspects of the present disclosure the number of different interchangeable pipette trays comprise pipette trays with different work sample wells or receptacles capacities.

(83) In accordance with one or more aspects of the present disclosure the at least one pipette tip set rack is interchangeable from a number of different pipette tip set racks, each having a different set of a different predetermined number of one of more pipette tips.

(84) In accordance with one or more aspects of the present disclosure the controller is configured so as to sequence the number of different interchangeable pipette trays with the sequencing work item holder according to the different pipette characteristic of the at least one pipette cartridge.

(85) In accordance with one or more aspects of the present disclosure the number of different interchangeable pipette trays sequencing corresponds respectively with the different pipetting characteristic, of the at least one pipette cartridge, ahead of automatic selection and behind automatic selection of the different pipetting characteristic.

(86) In accordance with one or more aspects of the present disclosure the frame is arranged so that the multiplex pipette cartridge section, the sequencing work item holder, and the carrier are disposed in a work section of the frame, and the system further comprises a storage section connected to the frame, having an automated random access storage array configured for storing therein each pipette tray of the number of different interchangeable pipette trays and each of the at least one pipette tip set rack isolated from the work section loaded and unloaded from at least one of the work item holder docks.

(87) In accordance with one or more aspects of the present disclosure the automatic assaying system further comprises an articulated bot arm movably connected to the frame and configured for automatically transporting each of at least one of the number of different interchangeable pipette trays and the at least one pipette tip set rack from the storage section to and from the storage section and loading and unloading a corresponding work item holder dock with the at least one of the number of different interchangeable pipette trays and the at least one pipette tip set rack transported.

(88) In accordance with one or more aspects of the present disclosure the identification indicia further identify a tray characteristic relating the pipette tray to other pipette trays of a set of pipette trays with the different pipetting characteristic common to each pipette tray of the set.

(89) In accordance with one or more aspects of the present disclosure a method in an automatic assaying system is provided. The method comprises: providing a frame; providing a multiplex pipette cartridge section, connected to the frame, having an array of multiple pipette cartridge docks arrayed along an array axis, each multiple pipette cartridge dock of the multiple pipette cartridge docks is configured to dock a corresponding pipette cartridge, at least one pipette cartridge of the corresponding pipette cartridge having a different pipetting characteristic from another corresponding pipette cartridge, the different pipetting characteristic being selectable from a number of different pipetting characteristics; providing a multiplexing work item holder, connected to the frame, with an array of work item holder docks disposed facing the array of multiple pipette cartridge docks and substantially aligned with the array axis, each work item holder dock of the array of work item holder docks is configured to dock a corresponding work item holder selectable from: a number of different interchangeable pipette trays, each having a different work characteristic, and at least one pipette tip set rack that defines the selectable different pipetting characteristic, wherein the multiplexing work item holder has indexing sections indexing one or more of the work item holder docks relative to the frame between different positions so as to selectably multiplex both the different interchangeable pipette trays and the at least one pipette set

rack corresponding to the work item holder dock; moving, with a carrier connected to the frame and including a gantry, the at least one pipette cartridge or a work item holder carriage, of the carrier, relative to the frame between the array of multiple pipette cartridge docks and the array of work item holder docks multiplexing the at least one pipette cartridge and interfacing the at least one pipette cartridge with multiplexing one of the different interchangeable pipette trays and the at least one pipette tip set rack at the array of work item holder docks; and selecting, with a controller communicably coupled to the multiplexing work item holder and the carrier, the at least one pipette tip set rack corresponding to a work item holder dock so as to effect automatic selection of the different pipetting characteristic of the at least one pipette cartridge via the interface.

(90) In accordance with one or more aspects of the present disclosure the number of different interchangeable pipette trays comprise pipette trays with different work sample wells or receptacles capacities.

(91) In accordance with one or more aspects of the present disclosure the at least one pipette tip set rack is interchangeable from a number of different pipette tip set racks, each having a different set of a different predetermined number of one of more pipette tips.

(92) In accordance with one or more aspects of the present disclosure the method further comprises, with the controller, multiplexing the number of different interchangeable pipette trays with the multiplexing work item holder according to the different pipette characteristic of the at least one pipette cartridge.

(93) In accordance with one or more aspects of the present disclosure the number of different pipette trays multiplexing corresponds respectively with the different interchangeable pipetting characteristic, of the at least one pipette cartridge, ahead of automatic selection and behind automatic selection of the different pipetting characteristic.

(94) In accordance with one or more aspects of the present disclosure the frame is arranged so that the multiplex pipette cartridge section, the multiplexing work item holder, and the carrier are disposed in a work section of the frame, and the system further comprises a storage section connected to the frame, having an automated random access storage array configured for storing therein each pipette tray of the number of different interchangeable pipette trays and each of the at least one pipette tip set rack isolated from the work section loaded and unloaded from at least one of the work item holder docks.

(95) In accordance with one or more aspects of the present disclosure the method further comprises, with an articulated bot arm movably connected to the frame, automatically transporting each of at least one of the number of different interchangeable pipette trays and the at least one pipette tip set rack from the storage section to and from the storage section and loading and unloading a corresponding work item holder dock with the at least one of the number of different interchangeable pipette trays and the at least one pipette tip set rack transported.

(96) In accordance with one or more aspects of the present disclosure the method further comprises, with a reader connected to the frame and communicably coupled to the controller, reading identification indicia identifying a tray characteristic and rack characteristic related to the different pipetting characteristic, of each pipette tray and each of the at least one pipette tip set rack stored in the automated random access storage array of the storage section.

(97) In accordance with one or more aspects of the present disclosure the identification indicia further identify a tray characteristic relating the pipette tray to other pipette trays of a set of pipette trays with the different pipetting characteristic common to each pipette tray of the set.

(98) In accordance with one or more aspects of the present disclosure one of the number of different interchangeable pipette trays is a source tray and another of the different interchangeable pipette trays is a destination tray, the method further comprising, with the at least one pipette cartridge, replicating contents of the source tray to the destination tray.

(99) In accordance with one or more aspects of the present disclosure one of the number of different interchangeable pipette trays is a source tray and another of the different interchangeable

pipette trays is a destination tray, the method further comprising, with the at least one pipette cartridge, tray reformatting.

(100) In accordance with one or more aspects of the present disclosure the destination tray includes a greater number of work sample wells than the source tray and the tray reformatting comprises a tray expansion where samples are moved with the at least one pipette cartridge, from a lesser number of work sample wells of the source tray to the greater number of work sample wells of the destination tray.

(101) In accordance with one or more aspects of the present disclosure the source tray includes a greater number of work sample wells than the destination tray and the tray reformatting comprises a tray compression where samples are moved with the at least one pipette cartridge, from the greater number of work sample wells of the source tray to a lesser number of work sample wells of the destination tray.

(102) In accordance with one or more aspects of the present disclosure the method further comprises, with the at least one pipette cartridge, adding a reagent to at least one of the different interchangeable pipette trays docked in the array of work item holder docks.

(103) In accordance with one or more aspects of the present disclosure one of the number of different interchangeable pipette trays is a source tray and another of the different interchangeable pipette trays is a destination tray, the method further comprising, with the at least one pipette cartridge, a compound addition where a set of compounds or samples are moved from the source tray to the destination tray.

(104) In accordance with one or more aspects of the present disclosure the method further comprises, with the at least one pipette cartridge, a serial dilution of samples in at least one of the different interchangeable pipette trays docked in the array of work item holder docks.

(105) In accordance with one or more aspects of the present disclosure a method in an automatic assaying system is provided. The method comprises: providing a frame; providing a multiplex pipette cartridge section, connected to the frame, having an array of multiple pipette cartridge docks arrayed along an array axis, each respective multiple pipette cartridge dock is configured to dock a corresponding pipette cartridge, at least one pipette cartridge of the corresponding pipette cartridge having a selectably variable pipetting characteristic selectable from a number of different pipetting characteristics; providing a sequencing work item holder, connected to the frame, with an array of work item holder docks disposed substantially juxtaposed from and substantially aligned with the array axis, each work item holder dock of the array of work item holder docks is configured to dock a corresponding work item holder selectable from: a number of different interchangeable pipette trays, each having a different work characteristic, and at least one pipette tip set rack that defines the selectable different pipetting characteristic, wherein the sequencing work item holder has indexing sections indexing one or more of the work item holder docks relative to the frame between different position so as to selectably sequence both the different interchangeable pipette trays and the at least one pipette set rack corresponding to the work item holder dock; moving, with a carrier connected to the frame and including a gantry, a cartridge carriage, of the carrier, relative to the frame so as to transport each corresponding pipette cartridge from the respective multiple pipette cartridge dock effecting random access sequencing of each corresponding pipette cartridge relative to the corresponding pipette trays and pipette tip set rack at each work item holder dock; and selecting, with a controller communicably coupled to the sequencing work item holder and the carrier, the at least one pipette tip set rack corresponding to the work item holder dock and effecting, via random access sequencing of each corresponding pipette cartridge, automatic selection of the different pipetting characteristic of at least one pipette cartridge.

(106) In accordance with one or more aspects of the present disclosure the number of different interchangeable pipette trays comprise pipette trays with different work sample wells or receptacles capacities.

(107) In accordance with one or more aspects of the present disclosure the at least one pipette tip set rack is interchangeable from a number of different pipette tip set racks, each having a different set of a different predetermined number of one of more pipette tips.

(108) In accordance with one or more aspects of the present disclosure the method further comprises, with the controller, sequencing the number of different interchangeable pipette trays with the sequencing work item holder according to the different pipette characteristic of the at least one pipette cartridge.

(109) In accordance with one or more aspects of the present disclosure the number of different interchangeable pipette trays sequencing corresponds respectively with the different pipetting characteristic, of the at least one pipette cartridge, ahead of automatic selection and behind automatic selection of the different pipetting characteristic.

(110) In accordance with one or more aspects of the present disclosure the frame is arranged so that the multiplex pipette cartridge section, the sequencing work item holder, and the carrier are disposed in a work section of the frame, and the system further comprises a storage section connected to the frame, having an automated random access storage array configured for storing therein each pipette tray of the number of different interchangeable pipette trays and each of the at least one pipette tip set rack isolated from the work section loaded and unloaded from at least one of the work item holder docks.

(111) In accordance with one or more aspects of the present disclosure the method further comprises, with an articulated bot arm movably connected to the frame, automatically transporting each of at least one of the number of different interchangeable pipette trays and the at least one pipette tip set rack from the storage section to and from the storage section and loading and unloading a corresponding work item holder dock with the at least one of the number of different interchangeable pipette trays and the at least one pipette tip set rack transported.

(112) In accordance with one or more aspects of the present disclosure the method further comprises, with a reader connected to the frame and communicably coupled to the controller, reading identification indicia identifying a tray characteristic and rack characteristic related to the different pipetting characteristic, of each pipette tray and each of the at least one pipette tip set rack stored in the automated random access storage array of the storage section.

(113) In accordance with one or more aspects of the present disclosure the identification indicia further identify a tray characteristic relating the pipette tray to other pipette trays of a set of pipette trays with the different pipetting characteristic common to each pipette tray of the set.

(114) In accordance with one or more aspects of the present disclosure one of the number of different interchangeable pipette trays is a source tray and another of the different interchangeable pipette trays is a destination tray, the method further comprising, with the at least one pipette cartridge, replicating contents of the source tray to the destination tray.

(115) In accordance with one or more aspects of the present disclosure one of the number of different interchangeable pipette trays is a source tray and another of the different interchangeable pipette trays is a destination tray, the method further comprising, with the at least one pipette cartridge, tray reformatting.

(116) In accordance with one or more aspects of the present disclosure the destination tray includes a greater number of work sample wells than the source tray and the tray reformatting comprises a tray expansion where samples are moved with the at least one pipette cartridge, from a lesser number of work sample wells of the source tray to the greater number of work sample wells of the destination tray.

(117) In accordance with one or more aspects of the present disclosure the source tray includes a greater number of work sample wells than the destination tray and the tray reformatting comprises a tray compression where samples are moved with the at least one pipette cartridge, from the greater number of work sample wells of the source tray to a lesser number of work sample wells of the destination tray.

(118) In accordance with one or more aspects of the present disclosure the method further comprises, with the at least one pipette cartridge, adding a reagent to at least one of the different interchangeable pipette trays docked in the array of work item holder docks.

(119) In accordance with one or more aspects of the present disclosure one of the number of different interchangeable pipette trays is a source tray and another of the different interchangeable pipette trays is a destination tray, the method further comprising, with the at least one pipette cartridge, a compound addition where a set of compounds or samples are moved from the source tray to the destination tray.

(120) In accordance with one or more aspects of the present disclosure the method further comprises, with the at least one pipette cartridge, a serial dilution of samples in at least one of the different interchangeable pipette trays docked in the array of work item holder docks.

(121) In accordance with one or more aspects of the present disclosure a method in an automatic assaying system is provided. The method comprises: providing a frame; providing a multiplex pipette cartridge section, connected to the frame, having an array of multiple pipette cartridge docks arrayed along an array axis, each respective multiple pipette cartridge dock is configured to dock a corresponding pipette cartridge, at least one pipette cartridge of the corresponding pipette cartridge having a selectably variable pipetting characteristic selectable from a number of different pipetting characteristics; providing a sequencing work item holder, connected to the frame, with an array of work item holder docks disposed substantially juxtaposed from and substantially aligned with the array axis, each work item holder dock of the array of work item holder docks is configured to dock a corresponding work item holder selectable from: a number of different interchangeable pipette trays, each having a different work characteristic, and at least one pipette tip set rack that defines the selectable different pipetting characteristic, wherein the sequencing work item holder has indexing sections indexing the one or more of the work item holder docks relative to the frame between different positions so as to selectably sequence both the different interchangeable pipette trays and the at least one pipette set rack corresponding to the holder dock; moving, with a carrier connected to the frame and including a gantry, a cartridge carriage, of the carrier, relative to the frame so as to transport each corresponding pipette cartridge from the respective multiple pipette cartridge dock effecting random access sequencing of each corresponding pipette cartridge relative to the corresponding pipette trays and pipette tip set rack at each work item holder dock; providing a controller communicably coupled to the sequencing work item holder and the carrier; and reading, with a reader connected to the frame and communicably coupled to the controller, identification indicia identifying a tray characteristic and a rack characteristic of each pipette tray and each of the at least one pipette tip set rack loaded in the corresponding work item holder dock, wherein the tray characteristic corresponds to at least one of the selectable different pipetting characteristic, and the rack characteristic is determinative of at least one of the selectable different pipetting characteristic.

(122) In accordance with one or more aspects of the present disclosure the method further comprises selecting, with the controller, the at least one pipette tip set rack corresponding to the work item holder dock and effecting, via random access sequencing of each corresponding pipette cartridge, automatic selection of the different pipetting characteristic of at least one pipette cartridge based on the rack characteristic identified by the reader.

(123) In accordance with one or more aspects of the present disclosure the number of different interchangeable pipette trays comprise pipette trays with different work sample wells or receptacles capacities.

(124) 6 In accordance with one or more aspects of the present disclosure the at least one pipette tip set rack is interchangeable from a number of different pipette tip set racks, each having a different set of a different predetermined number of one of more pipette tips.

(125) In accordance with one or more aspects of the present disclosure the method further comprises, with the controller, sequencing the number of different interchangeable pipette trays

with the sequencing work item holder according to the different pipette characteristic of the at least one pipette cartridge.

(126) In accordance with one or more aspects of the present disclosure the number of different interchangeable pipette trays sequencing corresponds respectively with the different pipetting characteristic, of the at least one pipette cartridge, ahead of automatic selection and behind automatic selection of the different pipetting characteristic.

(127) In accordance with one or more aspects of the present disclosure the frame is arranged so that the multiplex pipette cartridge section, the sequencing work item holder, and the carrier are disposed in a work section of the frame, and the system further comprises a storage section connected to the frame, having an automated random access storage array configured for storing therein each pipette tray of the number of different interchangeable pipette trays and each of the at least one pipette tip set rack isolated from the work section loaded and unloaded from at least one of the work item holder docks.

(128) In accordance with one or more aspects of the present disclosure the method further comprises, with an articulated bot arm movably connected to the frame, automatically transporting each of at least one of the number of different interchangeable pipette trays and the at least one pipette tip set rack from the storage section to and from the storage section and loading and unloading a corresponding work item holder dock with the at least one of the number of different interchangeable pipette trays and the at least one pipette tip set rack transported.

(129) In accordance with one or more aspects of the present disclosure the identification indicia further identify a tray characteristic relating the pipette tray to other pipette trays of a set of pipette trays with the different pipetting characteristic common to each pipette tray of the set.

(130) In accordance with one or more aspects of the present disclosure one of the number of different interchangeable pipette trays is a source tray and another of the different interchangeable pipette trays is a destination tray, the method further comprising, with the at least one pipette cartridge, replicating contents of the source tray to the destination tray.

(131) In accordance with one or more aspects of the present disclosure one of the number of different interchangeable pipette trays is a source tray and another of the different interchangeable pipette trays is a destination tray, the method further comprising, with the at least one pipette cartridge, tray reformatting.

(132) In accordance with one or more aspects of the present disclosure the destination tray includes a greater number of work sample wells than the source tray and the tray reformatting comprises a tray expansion where samples are moved with the at least one pipette cartridge, from a lesser number of work sample wells of the source tray to the greater number of work sample wells of the destination tray.

(133) In accordance with one or more aspects of the present disclosure the source tray includes a greater number of work sample wells than the destination tray and the tray reformatting comprises a tray compression where samples are moved with the at least one pipette cartridge, from the greater number of work sample wells of the source tray to a lesser number of work sample wells of the destination tray.

(134) In accordance with one or more aspects of the present disclosure the method further comprises, with the at least one pipette cartridge, adding a reagent to at least one of the different interchangeable pipette trays docked in the array of work item holder docks.

(135) In accordance with one or more aspects of the present disclosure one of the number of different interchangeable pipette trays is a source tray and another of the different interchangeable pipette trays is a destination tray, the method further comprising, with the at least one pipette cartridge, a compound addition where a set of compounds or samples are moved from the source tray to the destination tray.

(136) In accordance with one or more aspects of the present disclosure the method further comprises, with the at least one pipette cartridge, a serial dilution of samples in at least one of the

different interchangeable pipette trays docked in the array of work item holder docks.

(137) In accordance with one or more aspects of the present disclosure an automatic assaying system comprises: a frame; a multiplex pipette cartridge section, connected to the frame, having an array of multiple pipette cartridge docks arrayed along an array axis, each respective multiple pipette cartridge dock is configured to dock a corresponding pipette cartridge, at least one pipette cartridge of the corresponding pipette cartridge having a selectably variable pipetting characteristic selectable from a number of different pipetting characteristics; a sequencing work item holder, connected to the frame, with an array of work item holder docks disposed substantially juxtaposed from and substantially aligned with the array axis, each work item holder dock is configured to dock a corresponding work item holder selectable from: a number of different interchangeable pipette trays, each having a different work characteristic, and at least one pipette tip set rack that defines the selectable different pipetting characteristic, wherein the sequencing work item holder has indexing sections indexing one or more of the work item holder docks relative to the frame between different position so as to selectably sequence both the pipette trays and the at least one pipette tip set rack corresponding to the work item holder dock; a carrier connected to the frame including a gantry arranged so as move a cartridge carriage, of the carrier, relative to the frame so as to transport each corresponding pipette cartridge from the respective multiple pipette cartridge dock effecting random access sequencing of each corresponding pipette cartridge relative to the corresponding pipette trays and the at least one pipette tip set rack at each work item holder dock; and a controller communicably coupled to the sequencing work item holder and the carrier and configured to register user selection of more than one predetermined work protocols, each based on a respective one of the different predetermined pipetting characteristics; wherein the controller is configured to automatically effect the registered more than one predetermined work protocols in a substantially continuous series, wherein for each different predetermined work protocol the controller resolves, based on the respective different predetermined pipetting characteristic, a different corresponding sequence of the pipette trays and the at least one pipette tip set rack in and with the sequencing work item holder (that determines sequence locations and indexing for each pipette tray and the at least one pipette tip set rack) for the corresponding sequence and sequence transition between different registered predetermined work protocols to effect the different registered predetermined work protocols substantially continuously.

(138) In accordance with one or more aspects of the present disclosure the controller is configured to sequence the registered predetermined work protocols in series dependent on map info of the pipette trays and the at least one pipette tip set rack in store.

(139) In accordance with one or more aspects of the present disclosure the number of different interchangeable pipette trays comprise pipette trays with different work sample wells or receptacles capacities.

(140) In accordance with one or more aspects of the present disclosure the at least one pipette tip set rack is interchangeable from a number of different pipette tip set racks, each having a different set of a different predetermined number of one of more pipette tips.

(141) In accordance with one or more aspects of the present disclosure the controller is configured so as to sequence the number of different interchangeable pipette trays with the sequencing work item holder according to the different pipette characteristic of the at least one pipette cartridge.

(142) In accordance with one or more aspects of the present disclosure the number of different interchangeable pipette trays sequencing corresponds respectively with the different pipetting characteristic, of the at least one pipette cartridge, ahead of automatic selection and behind automatic selection of the different pipetting characteristic.

(143) In accordance with one or more aspects of the present disclosure the frame is arranged so that the multiplex pipette cartridge section, the sequencing work item holder, and the carrier are disposed in a work section of the frame, and the system further comprises a storage section connected to the frame, having an automated random access storage array configured for storing

therein each pipette tray of the number of different interchangeable pipette trays and each of the at least one pipette tip set rack isolated from the work section loaded and unloaded from at least one of the work item holder docks.

(144) In accordance with one or more aspects of the present disclosure the automatic assaying system further comprises an articulated bot arm movably connected to the frame and configured for automatically transporting each of at least one of the number of different interchangeable pipette trays and the at least one pipette tip set rack from the storage section to and from the storage section and loading and unloading a corresponding work item holder dock with the at least one of the number of different interchangeable pipette trays and the at least one pipette tip set rack transported.

(145) In accordance with one or more aspects of the present disclosure the automatic assaying system further comprises a reader connected to the frame and communicably coupled to the controller, the reader being disposed to read identification indicia identifying a tray characteristic and rack characteristic related to the different pipetting characteristic, of each pipette tray and each of the at least one pipette tip set rack stored in the automated random access storage array of the storage section.

(146) In accordance with one or more aspects of the present disclosure the identification indicia further identify a tray characteristic relating the pipette tray to other pipette trays of a set of pipette trays with the different pipetting characteristic common to each pipette tray of the set.

(147) It should be understood that the foregoing description is only illustrative of the aspects of the present disclosure. Various alternatives and modifications can be devised by those skilled in the art without departing from the aspects of the present disclosure. Accordingly, the aspects of the present disclosure are intended to embrace all such alternatives, modifications and variances that fall within the scope of any claims appended hereto. Further, the mere fact that different features are recited in mutually different dependent or independent claims does not indicate that a combination of these features cannot be advantageously used, such a combination remaining within the scope of the aspects of the present disclosure.

Claims

1. An automatic assaying system comprising: a frame; a multiplex pipette cartridge section, connected to the frame, having an array of multiple pipette cartridge docks arrayed along an array axis, each respective multiple pipette cartridge dock is configured to dock a corresponding pipette cartridge, at least one pipette cartridge of the corresponding pipette cartridge having a selectably variable pipetting characteristic selectable from a number of different pipetting characteristics; a sequencing work item holder, connected to the frame, with an array of work item holder docks disposed substantially juxtaposed from and substantially aligned with the array axis, each work item holder dock of the array of work item holder docks is configured to dock a corresponding work item holder selectable from: a number of different interchangeable pipette trays, each having a different work characteristic, and at least one pipette tip set rack that defines the selectable different pipetting characteristic, wherein the sequencing work item holder has indexing sections indexing one or more of the work item holder docks relative to the frame between different positions so as to selectably sequence both the different interchangeable pipette trays and the at least one pipette set rack corresponding to the one or more work item holder dock; a carrier connected to the frame including a gantry arranged so as to move a cartridge carriage, of the carrier, relative to the frame so as to transport each corresponding pipette cartridge from the respective multiple pipette cartridge dock effecting random access sequencing of each corresponding pipette cartridge relative to the corresponding different interchangeable pipette trays and pipette tip set rack at each work item holder dock; and a controller communicably coupled to the sequencing work item holder and the carrier and configured to select the at least one pipette tip

set rack corresponding to the one or more work item holder docks and effect, via random access sequencing of each corresponding pipette cartridge, automatic selection of the different pipetting characteristic of at least one pipette cartridge.

2. The automatic assaying system of claim 1, wherein the number of different interchangeable pipette trays comprise pipette trays with different work sample wells or receptacles capacities.

3. The automatic assaying system of claim 1, wherein the at least one pipette tip set rack is interchangeable from a number of different pipette tip set racks, each having a different set of a different predetermined number of one of more pipette tips.

4. The automatic assaying system of claim 1, wherein the controller is configured so as to sequence the number of different interchangeable pipette trays with the sequencing work item holder according to the different pipette characteristic of the at least one pipette cartridge.

5. The automatic assaying system of claim 1, wherein the number of different interchangeable pipette trays sequencing corresponds respectively with the different pipetting characteristic, of the at least one pipette cartridge, ahead of automatic selection and behind automatic selection of the different pipetting characteristic.

6. The automatic assaying system of claim 1, wherein the frame is arranged so that the multiplex pipette cartridge section, the sequencing work item holder, and the carrier are disposed in a work section of the frame, and the system further comprises a storage section connected to the frame, having an automated random access storage array configured for storing therein each pipette tray of the number of different interchangeable pipette trays and each of the at least one pipette tip set rack isolated from the work section loaded and unloaded from at least one of the work item holder docks.

7. The automatic assaying system of claim 6, further comprising an articulated bot arm movably connected to the frame and configured for automatically transporting each of at least one of the number of different interchangeable pipette trays and the at least one pipette tip set rack from the storage section to and from the storage section and loading and unloading a corresponding work item holder dock with the at least one of the number of different interchangeable pipette trays and the at least one pipette tip set rack transported.

8. The automatic assaying system of claim 6, further comprising a reader connected to the frame and communicably coupled to the controller, the reader being disposed to read identification indicia identifying a tray characteristic and rack characteristic related to the different pipetting characteristic, of each pipette tray and each of the at least one pipette tip set rack stored in the automated random access storage array of the storage section.

9. The automatic assaying system of claim 8, wherein the identification indicia further identify a tray characteristic relating the pipette tray to other pipette trays of a set of pipette trays with the different pipetting characteristic common to each pipette tray of the set.

10. A method comprising: providing a frame; providing a multiplex pipette cartridge section, connected to the frame, having an array of multiple pipette cartridge docks arrayed along an array axis, each respective multiple pipette cartridge dock docking a corresponding pipette cartridge, at least one pipette cartridge of the corresponding pipette cartridge having a selectably variable pipetting characteristic selectable from a number of different pipetting characteristics; providing a sequencing work item holder, connected to the frame, with an array of work item holder docks disposed substantially juxtaposed from and substantially aligned with the array axis, each work item holder dock of the array of work item holder docks docking a corresponding work item holder selectable from: a number of different interchangeable pipette trays, each having a different work characteristic, and at least one pipette tip set rack defining the selectable different pipetting characteristic, wherein the sequencing work item holder has indexing sections indexing one or more of the work item holder docks relative to the frame between different positions, selectably sequencing both the different interchangeable pipette trays and the at least one pipette set rack corresponding to the work item holder dock; effecting random access sequencing of pipette

cartridges relative to the corresponding different interchangeable pipette trays and pipette tip set rack at each work item holder dock by transporting each corresponding pipette cartridge from the respective multiple pipette cartridge dock with a carrier connected to the frame including a gantry arranged for moving a cartridge carriage, of the carrier, relative to the frame; and selecting, with a controller communicably coupled to the sequencing work item holder and the carrier the at least one pipette tip set rack corresponding to the one or more work item holder docks and effecting, via random access sequencing of each corresponding pipette cartridge, automatic selection of the different pipetting characteristic of at least one pipette cartridge.

11. The method of claim 10, wherein the number of different interchangeable pipette trays comprise pipette trays with different work sample wells or receptacles capacities.

12. The method of claim 10, wherein the at least one pipette tip set rack is interchangeable from a number of different pipette tip set racks, each having a different set of a different predetermined number of one of more pipette tips.

13. The method of claim 10, further comprising sequencing, with the controller, the number of different interchangeable pipette trays with the sequencing work item holder according to the different pipette characteristic of the at least one pipette cartridge.

14. The method of claim 10, wherein the number of different interchangeable pipette trays sequencing corresponds respectively with the different pipetting characteristic, of the at least one pipette cartridge, ahead of automatic selection and behind automatic selection of the different pipetting characteristic.

15. The method of claim 10, wherein the frame is arranged so that the multiplex pipette cartridge section, the sequencing work item holder, and the carrier are disposed in a work section of the frame, and the system further comprises a storage section connected to the frame, having an automated random access storage array configured for storing therein each pipette tray of the number of different interchangeable pipette trays and each of the at least one pipette tip set rack isolated from the work section loaded and unloaded from at least one of the work item holder docks.

16. The method of claim 15, further comprising automatically transporting, with an articulated bot arm movably connected to the frame, each of at least one of the number of different interchangeable pipette trays and the at least one pipette tip set rack from the storage section to and from the storage section and loading and unloading a corresponding work item holder dock with the at least one of the number of different interchangeable pipette trays and the at least one pipette tip set rack transported.

17. The method of claim 15, further comprising reading, with a reader connected to the frame and communicably coupled to the controller, identification indicia identifying a tray characteristic and rack characteristic related to the different pipetting characteristic, of each pipette tray and each of the at least one pipette tip set rack stored in the automated random access storage array of the storage section.

18. The method of claim 17, wherein the identification indicia further identify a tray characteristic relating the pipette tray to other pipette trays of a set of pipette trays with the different pipetting characteristic common to each pipette tray of the set.
