

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250258666

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Hua; Song

FIRMWARE UPGRADE METHOD FOR EMBEDDED COMBINATION APPARATUS AND FIRMWARE UPGRADE DEVICE THEREOF

Abstract

The present invention provides a firmware upgrade method and a firmware upgrade device thereof for an embedded combination apparatus. A main device is first connected to a computer for firmware upgrade, and then a firmware version of a slave device is checked to determine whether to match a firmware version of the main device. If they match, the slave device does not need to be upgraded. If any slave device has a mismatched firmware version, the main device sends an upgrade command and data of a matching firmware version to the slave device individually. The slave device receives a corresponding firmware upgrade package for firmware upgrade. The firmware upgrade method of the present invention complete a firmware upgrade process of the embedded combination apparatus without detaching the main device from the slave device, which is convenient and fast with a lower error rate.

Inventors: Hua; Song (Suzhou, CN)

Applicant: QISDA (SUZHOU) CO., Ltd. (Suzhou, CN)

Family ID: 1000008396683

Assignee: QISDA (SUZHOU) CO., Ltd. (Suzhou, CN)

Appl. No.: 19/010181

Filed: January 06, 2025

Foreign Application Priority Data

CN 202410176137.6

Feb. 08, 2024

Publication Classification

Int. Cl.: G06F8/654 (20180101); G06F8/658 (20180101); H04L67/00 (20220101)

U.S. Cl.:

CPC G06F8/654 (20180201); G06F8/658 (20180201); H04L67/34 (20130101);

Background/Summary

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0001] The present invention relates to an embedded combination apparatus, and more specifically, to a firmware upgrade method for an embedded combination apparatus and a firmware upgrade device thereof.

2. Description of the Prior Art

[0002] An embedded combination apparatus generally consists of a main device and one or more slave devices, which are connected via USB or serial port cables. Firmware upgrades during the lifecycle of the embedded combination apparatus are performed on the main device and the slave device separately. For example, in a combination apparatus like a tablet computer and a docking station, the tablet computer and the docking station need to be detached from each other first if a firmware upgrade process needs to be performed. Subsequently, the tablet computer is upgraded by OTA technology (Over the Air Technology), or is coupled to a PC (Personal Computer) via a data cable and upgraded via a specific software executed by the PC. The docking station is also coupled to the PC via the data cable and upgraded by the PC. During the aforesaid firmware upgrade process, the main device and the slave device do not communicate with each other, and firmware version numbers of the main device and the slave device are only known when the main device is reassembled with the slave device and restarts again.

[0003] Current firmware upgrades for the embedded combination apparatus are performed separately. Sometimes the embedded combination apparatus needs to be disassembled and coupled to the PC via the data cable for firmware burning and assembly of the embedded combination apparatus is then performed after the firmware upgrade process is completed, which is strenuous and time-consuming. For avoiding firmware incompatibility between combined devices of the embedded combination apparatus, an operator needs to know the firmware version compatibility of each combined device and manually selects an appropriate firmware version for each combined device before the aforesaid firmware upgrade process is performed, thereby increasing the error rate of the firmware upgrade process.

SUMMARY OF THE INVENTION

[0004] The present invention provides a firmware upgrade method and a firmware upgrade device thereof for an embedded combination apparatus, for solving the prior art problem that the embedded combination apparatus needs to be disassembled and then performs firmware upgrades on the combined devices in the embedded combination apparatus separately checking after the firmware version compatibility.

[0005] For achieving the aforesaid purpose, the present invention adopts the following technical solutions.

[0006] A firmware upgrade method for an embedded combination apparatus is disclosed. The embedded combination apparatus includes a main device and a slave device. The slave device is coupled to the main device. The firmware upgrade method includes: [0007] Step S1: connecting the main device to a computer to receive a first firmware upgrade package for upgrading a firmware of the main device and restarting the main device, wherein the first firmware upgrade

package includes a second firmware upgrade package for upgrading the slave device; [0008] Step S2: the main device reading a firmware version information of the slave device; [0009] Step S3: comparing a firmware version information of the main device with the firmware version information of the slave device to determine whether the slave device needs to be upgraded; [0010] Step S4: if it is determined that the slave device needs to be upgraded, the main device sending an upgrade command and the second firmware upgrade package to the slave device; and [0011] Step S5: the slave device receiving the upgrade command and the second firmware upgrade package to upgrade a firmware of the slave device and restart according to the upgrade command.

[0012] Preferably, after Step S3 is completed, if it is determined that the slave device does not need to be upgraded, Step S4 and Step S5 are skipped, and a firmware upgrade process of the embedded combination apparatus is completed.

[0013] Preferably, connection between the main device and the computer is wireless or wired, and/or connection between the slave device and the main device is wireless or wired.

[0014] Preferably, when connection between the main device and the computer is wireless, OTA technology (Over the Air Technology) is used to receive the first firmware upgrade package in Step S1.

[0015] Preferably, the main device corresponds to at least two types of slave devices, and in Step S2, the main device determines a type of the slave device by reading a hardware ID of the slave device.

[0016] Preferably, in Step S4, the main device obtains a current firmware version number matching the slave device according to a current firmware version number of the main device, and sends a corresponding firmware version to the slave device.

[0017] A firmware upgrade device for an embedded combination apparatus is disclosed. The embedded combination apparatus includes a main device and a slave device. The slave device is coupled to the main device. The firmware upgrade device includes: [0018] a main upgrade module connecting the main device to a computer to receive a first firmware upgrade package for upgrading a firmware of the main device and restarting the main device, wherein the first firmware upgrade package includes a second firmware upgrade package for upgrading the slave device; [0019] a reading module utilizing the main device to read a firmware version information of the slave device; [0020] a comparison module comparing a firmware version information of the main device with the firmware version information of the slave device to determine whether the slave device needs to be upgraded; [0021] a sending module utilizing the main device to send an upgrade command and the second firmware upgrade package to the slave device if it is determined that the slave device needs to be upgraded; and [0022] a slave upgrade module utilizing the slave device to receive the upgrade command and the second firmware upgrade package for upgrading a firmware of the slave device and restarting the slave device according to the upgrade command.

[0023] Preferably, connection between the main device and the computer is wireless or wired, and/or connection between the slave device and the main device is wireless or wired.

[0024] Preferably, when connection between the main device and the computer is wireless, OTA technology is used to receive the first firmware upgrade package in Step S1.

[0025] Preferably, the main device corresponds to at least two types of slave devices, and in Step S2, the main device determines a type of the slave device by reading a hardware ID of the slave device.

[0026] Compared with the prior art, the present invention has the following advantages.

[0027] When the firmware upgrade process of the embedded combination apparatus is performed, there is no need to detach the main device from the slave device, select the appropriate firmware version for each device to burn the firmware separately, and then reassemble the main device with the slave device. Instead, the main device can be directly connected to a PC for upgrading the firmware of the main device, wherein the firmware upgrade package of the main device includes the firmware upgrade package of the slave device. When the main device is running, the main

device checks the firmware version of the slave device and determines whether the slave device firmware needs to be upgraded. If the slave device needs to be upgraded, the main device can directly send the upgrade command and data to the slave device for upgrading the firmware of the slave device.

[0028] The present invention can complete the firmware upgrade process of the embedded combination apparatus without networking and without separating the main device from the slave device, which is convenient and fast with low error rate.

[0029] These and other objectives of the present invention will no doubt become obvious to those of ordinary skill in the art after reading the following detailed description of the preferred embodiment that is illustrated in the various figures and drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0030] FIG. 1 is a flowchart of a firmware upgrade method for an embedded combination apparatus according to an embodiment of the present invention.

[0031] FIG. 2 is a diagram showing connection between the embedded combination apparatus and a computer.

[0032] FIG. 3 is a functional block diagram of a firmware upgrade device according to an embodiment of the present invention.

DETAILED DESCRIPTION

[0033] To further understand objectives, structures, features, and functions of the present invention, the following detailed description is provided in conjunction with embodiments.

[0034] In the description of the present invention, it should be noted that terms such as “center”, “up”, “down”, “left”, “right”, “vertical”, “horizontal”, “inner”, “outer”, etc., indicate directions or positional relationships based on directions or positional relationships shown in the accompanying drawings. These terms are only for the convenience of describing the present invention and simplifying the description, and do not indicate or imply that the referred device or element must have a specific direction or be constructed and operated in a specific direction. Thus, these terms cannot be understood as limiting the present invention.

[0035] An embedded combination apparatus includes a main device **100** and one or more slave devices **200**. The slave device **200** is coupled to the main device **100**. When the embedded combination apparatus needs to be upgraded, the main device **100** and the slave device **200** need to be detached from each other, individually connected to a PC, and upgraded via a specific software run by the PC, and it is necessary to ensure the firmware version compatibility between the main device **100** and the slave device **200**. After the aforesaid firmware upgrade process is completed, the main device **100** and the slave device **200** are combined for operation again. This process is not only strenuous and time-consuming, but also easily causes errors due to the firmware version incompatibility between the main device **100** and the slave device **200**.

[0036] To solve the above problems, please refer to FIGS. 1 and 2. The present invention provides a firmware upgrade method for the embedded combination apparatus and a firmware upgrade device, wherein the main device **100** is responsible for the entire firmware upgrade process of the embedded combination apparatus. During the firmware upgrade process, an operator does not need to disassemble the embedded combination apparatus for performing firmware upgrades of devices in the embedded combination apparatus individually. Instead, only a firmware of the main device **100** needs to be upgraded. While running, the main device **100** checks a firmware version of the slave device **200**, compares a firmware version of the main device **100** with the firmware version of the slave device **200** to determine whether a firmware of the slave device **200** needs to be upgraded. If a firmware upgrade is needed, the main device **100** sends an upgrade command and a

corresponding firmware to upgrade the slave device **200**.

[0037] Please refer to FIGS. **1** and **2**. The present invention provides the firmware upgrade method for the embedded combination apparatus. The embedded combination apparatus includes the main device **100** and the slave device **200**, wherein the slave device **200** is coupled to the main device **100** for signal communication. The firmware upgrade method includes the following steps.

[0038] Step **S1**: Connect the main device **100** to the computer **300** to receive a first firmware upgrade package for upgrading and restarting the main device **100**, wherein the first firmware upgrade package includes a second firmware upgrade package for the slave device **200**.

[0039] Step **S2**: The main device **100** reads a firmware version information of the slave device **200**.

[0040] Step **S3**: Compare a firmware version information of the main device **100** with the firmware version information of the slave device **200** to determine whether the slave device **200** needs to be upgraded.

[0041] Step **S4**: If it is determined that the slave device **200** needs to be upgraded, the main device **100** sends the upgrade command and the second firmware upgrade package to the slave device **200**.

[0042] Step **S5**: The slave device **200** receives the upgrade command and the second firmware upgrade package and upgrades a firmware of the slave device **200** and restarts according to the upgrade command.

[0043] After Step **S3** is completed, if it is determined that the slave device **200** does not need to be upgraded, Step **S4** and Step **S5** are skipped, and the firmware upgrade process of the embedded combination apparatus is completed.

[0044] In this embodiment, signal connection is established between the main device **100** and the computer **300** and between the slave device **200** and the main device **100**. The slave device **200** does not need to connect to the computer **300**. That is, the firmware upgrade of the slave device **200** could be completed without the signal connection between the slave device **200** and the computer **300** or information transmission in a local area network where the slave device **200** is located. The firmware upgrade of the slave device **200** is entirely dependent on a signal connection channel with the main device **100**. In different embodiments, the main device **100** and the computer **300** could be connected in a wireless or wired manner, and/or the slave device **200** and the main device **100** could be connected in a wireless or wired manner.

[0045] Wireless connection methods include, but are not limited thereto, one or more of WiFi modules, 2G/3G/4G/5G communication modules, Zigbee modules, and Bluetooth modules. Wired connection methods include, but are not limited thereto, one or more of USB connections, serial port connections, and other data cable connections.

[0046] When the main device **100** is wirelessly connected to the computer **300**, in Step **S1**, OTA technology is used to receive the first firmware upgrade package and upgrade the firmware of the main device **100**. Implementation methods of OTA technology could include download based on HTTP or FTP protocol, download based on Bluetooth, download based on mobile network, and download based on multicast or broadcast.

[0047] In a preferred embodiment, the main device **100** corresponds to at least two types of slave devices **200**. The main device **100** is connected to one or more slave devices **200**, and each slave device **200** has multiple types that can be selected according to actual needs. Furthermore, in Step **S2**, the main device **100** determines a type of the slave device **200** by reading a hardware ID of the slave device **200**.

[0048] In one embodiment, different types of slave devices **200** are provided as follows: [0049] a slave device **200A** only has a basic configuration, and a hardware ID of the slave device **200A** is 0x20000; [0050] a slave device **200B** has a display screen, and a hardware ID of the slave device **200B** is 0x20001; [0051] a slave device **200C** has a display screen and a touch screen, and a hardware ID of the slave device **200C** is 0x20011; [0052] whether the last two digits of the hardware ID are 1 indicates whether a display touch function is configured.

[0053] The main device **100** could match a corresponding firmware for the slave device **200** by

reading the hardware ID of the slave device **200**. For example, the hardware ID 0x20001 indicates that the slave device **200** needs a firmware upgrade package corresponding to the display screen, and the hardware ID 0x20011 indicates that the slave device **200** needs a firmware upgrade package corresponding to the display screen and the touch screen.

[0054] In Step S3, the main device **100** compares the firmware version of the main device **100** with the firmware version of the slave device **200**. More specifically, the main device **100** stores a matching table of the firmware versions of the main device **100** and the slave device **200** for comparing the firmware version of the slave device **200** with the current firmware version of the main device **100**. If the firmware version of the slave device **200** matches the current firmware version of the main device **100**, it is determined that the slave device **200** does not need to be upgraded. If the firmware version of the slave device **200** does not match the current firmware version of the main device **100**, it is determined that the slave device **200** needs to be upgraded.

[0055] In Step S4, the main device **100** obtains a firmware version number of the slave device **200** based on the current firmware version number of the main device **100**, and sends a corresponding upgrade firmware to the slave device **200**. Since the firmware upgrade package of the main device **100** includes the firmware upgrade package of the slave device **200**, the firmware upgrade of the slave device **200** could be performed after receiving the corresponding upgrade firmware.

[0056] Thus, the firmware upgrade method according to an embodiment of the present invention includes upgrading the firmware of the main device **100** first, and then checking whether the firmware version of the slave device **200** matches the upgraded firmware version of the main device **100**. If the firmware version of the slave device **200** matches the upgraded firmware version of the main device **100**, the slave device **200** does not need to be upgraded, and the firmware upgrade process of the embedded combination apparatus is completed. If any slave device **200** has a mismatched firmware version, the main device **100** sends the upgrade command and data of the matching firmware version to the slave device **200** individually. The slave device **200** receives the corresponding firmware upgrade package from the main device **100** and upgrades the firmware of the slave device **200**, thereby completing the firmware upgrade process of the embedded combination apparatus. The firmware upgrade method of the present invention can complete the firmware upgrade process of the embedded combination apparatus without detaching the main device **100** from the slave device **200**, which is convenient and fast with a lower error rate.

[0057] Please refer to FIG. 3. The present invention provides a firmware upgrade device for upgrading the firmware of the embedded combination apparatus. The embedded combination apparatus includes the main device **100** and the slave device **200**. The slave device **200** is connected to the main device **100** for signal communication. The firmware upgrade device includes a main upgrade module **11**, a reading module **12**, a comparison module **13**, a sending module **14**, and a slave upgrade module **15**.

[0058] The main upgrade module **11** connects the main device **100** to the computer **300** for receiving the first firmware upgrade package. The main device **100** upgrades the firmware of the main device **100** and restarts. The first firmware upgrade package includes the second firmware upgrade package for the slave device **200**.

[0059] The reading module **12** utilizes the main device **100** to read the firmware version information of the slave device **200**.

[0060] The comparison module **13** compares the firmware version information of the main device **100** with the firmware version information of the slave device **200** and determines whether the slave device **200** needs to be upgraded.

[0061] The sending module **14** sends the upgrade command and the second firmware upgrade package to the slave device **200** if it is determined that the slave device **200** needs to be upgraded.

[0062] The slave upgrade module **15** utilizes the slave device **200** to receive the upgrade command and the second firmware upgrade package for upgrading the firmware of the slave device **200** and restarts the slave device **200** according to the upgrade command.

[0063] The main upgrade module **11**, the reading module **12**, the comparison module **13**, and the sending module **14** are disposed inside the main device **100** and connected by 12C connections, serial port connections, USB connections or other wired connections. The main device **100** and the slave device **200** are coupled through the sending module **14** and the slave upgrade module **15**, which could be achieved by 12C connections, serial port connections, USB connections or other wired connections, or by WiFi wireless connections, BT wireless connections or other wireless connections.

[0064] In this embodiment, signal connection is established between the main device **100** and the computer **300** and between the slave device **200** and the main device **100**. The slave device **200** does not need to connect to the computer **300**. That is, the firmware upgrade of the slave device **200** could be completed without signal connection between the slave device **200** and the computer **300** or information transmission in a local area network where the slave device **200** is located. The firmware upgrade of the slave device **200** is entirely dependent on a signal connection channel with the main device **100**. In different embodiments, the main device **100** and the computer **300** could be connected in a wireless or wired manner, and/or the slave device **200** and the main device **100** could be connected in a wireless or wired manner.

[0065] The wireless connection methods include, but are not limited thereto, one or more of WiFi modules, 2G/3G/4G/5G communication modules, Zigbee modules, Bluetooth modules. The wired connection methods include, but are not limited thereto, one or more of USB connections, serial port connections, and other data cable connections.

[0066] When the main device **100** is wirelessly connected to the computer **300**, OTA technology is used to receive the first firmware upgrade package and upgrade the firmware of the main device **100**. The implementation methods of OTA technology could include download based on HTTP or FTP protocol, download based on Bluetooth, download based on mobile network, and download based on multicast or broadcast.

[0067] In a preferred embodiment, the main device **100** corresponds to at least two types of slave devices **200**. The main device **100** is connected to one or more slave devices **200**, and each slave device **200** has multiple types that can be selected according to actual needs. The reading module **12** utilizes the main device **100** determines a type of the slave device **200** by reading a hardware ID of the slave device **200**.

[0068] In a preferred embodiment, the comparison module **13** utilizes the main device **100** to obtain the firmware version number matching the current firmware version of the slave device **200** based on the current firmware version number of the main device **100** and send a corresponding upgrade firmware to the slave device **200**.

[0069] In summary, the firmware upgrade device for upgrading the firmware of the embedded combination apparatus according to an embodiment of the present invention utilizes USB or other connection methods to achieve connection between the main device and the slave device and is not networked. In this case, the main device **100** is first connected to the computer **300** for firmware upgrade, and then the firmware version of the slave device **200** is checked to determine whether to match the upgraded firmware version of the main device **100**. If the firmware version of the slave device **200** matches the upgraded firmware version of the main device **100**, the slave devices **200** do not need to be upgraded, thereby completing the firmware upgrade process of the embedded combination apparatus. If any slave device **200** has a mismatched firmware version, the main device **100** sends the upgrade command and data of the matching firmware version to the slave device **200** individually. The slave device **200** receives the corresponding firmware upgrade package from the main device **100** and upgrades the firmware of the slave device **200**, thereby completing the firmware upgrade process of the embedded combination apparatus. The firmware upgrade device of the present invention can complete the firmware upgrade process of the embedded combination apparatus without detaching the main device **100** from the slave device **200**, which is convenient and fast with a lower error rate.

[0070] Those skilled in the art will readily observe that numerous modifications and alterations of the device and method may be made while retaining the teachings of the invention. Accordingly, the above disclosure should be construed as limited only by the metes and bounds of the appended claims.

Claims

1. A firmware upgrade method for an embedded combination apparatus, the embedded combination apparatus comprising a main device and a slave device, the slave device being coupled to the main device, the firmware upgrade method comprising: Step S1: connecting the main device to a computer to receive a first firmware upgrade package for upgrading a firmware of the main device and restarting the main device, wherein the first firmware upgrade package comprises a second firmware upgrade package for upgrading the slave device; Step S2: the main device reading a firmware version information of the slave device; Step S3: comparing a firmware version information of the main device with the firmware version information of the slave device to determine whether the slave device needs to be upgraded; Step S4: if it is determined that the slave device needs to be upgraded, the main device sending an upgrade command and the second firmware upgrade package to the slave device; Step S5: the slave device receiving the upgrade command and the second firmware upgrade package to upgrade a firmware of the slave device and restart according to the upgrade command.
2. The firmware upgrade method of claim 1, wherein after Step S3 is completed, if it is determined that the slave device does not need to be upgraded, Step S4 and Step S5 are skipped, and a firmware upgrade process of the embedded combination apparatus is completed.
3. The firmware upgrade method of claim 1, wherein connection between the main device and the computer is wireless or wired, and/or connection between the slave device and the main device is wireless or wired.
4. The firmware upgrade method of claim 1, wherein when connection between the main device and the computer is wireless, OTA technology (Over the Air Technology) is used to receive the first firmware upgrade package in Step S1.
5. The firmware upgrade method of claim 1, wherein the main device corresponds to at least two types of slave devices, and in Step S2, the main device determines a type of the slave device by reading a hardware ID of the slave device.
6. The firmware upgrade method of claim 1, wherein in Step S4, the main device obtains a current firmware version number matching the slave device according to a current firmware version number of the main device, and sends a corresponding firmware version to the slave device.
7. A firmware upgrade device for an embedded combination apparatus, the embedded combination apparatus comprising a main device and a slave device, the slave device being coupled to the main device, the firmware upgrade device comprising: a main upgrade module connecting the main device to a computer to receive a first firmware upgrade package for upgrading a firmware of the main device and restarting the main device, wherein the first firmware upgrade package comprises a second firmware upgrade package for upgrading the slave device; a reading module utilizing the main device to read a firmware version information of the slave device; a comparison module comparing a firmware version information of the main device with the firmware version information of the slave device to determine whether the slave device needs to be upgraded; a sending module utilizing the main device to send an upgrade command and the second firmware upgrade package to the slave device if it is determined that the slave device needs to be upgraded; and a slave upgrade module utilizing the slave device to receive the upgrade command and the second firmware upgrade package for upgrading a firmware of the slave device and restarting the slave device according to the upgrade command.
8. The firmware upgrade device of claim 7, wherein connection between the main device and the

computer is wireless or wired, and/or connection between the slave device and the main device is wireless or wired.

9. The firmware upgrade device of claim 8, wherein when connection between the main device and the computer is wireless, OTA technology is used to receive the first firmware upgrade package in Step S1.

10. The firmware upgrade device of claim 7, wherein the main device corresponds to at least two types of slave devices, and in Step S2, the main device determines a type of the slave device by reading a hardware ID of the slave device.
