

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250258291

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Steenstrup; Jens et al.

MULTI-PERSPECTIVE ENSONIFICATION SYSTEM AND METHOD

Abstract

A survey system and method to improve one or more of survey quality, efficiency, and utility for example by utilizing a vessel mounted MBES and a selected survey plan to check sound speed(s) via eliciting echoes from reflectors in colocated groups of reflectors using multi-perspective ensonification.

Inventors: Steenstrup; Jens (B'Kara, MT), Tiemann; Christopher (Austin, TX), Bilodeau; Peter (Austin, TX), Chun; Mark (Austin, TX), Hobart; Kirk (Austin, TX)

Applicant: R3Vox LTD (B'Kara, MT)

Family ID: 1000008561533

Appl. No.: 19/192672

Filed: April 29, 2025

Related U.S. Application Data

parent US continuation 17874895 20220727 parent-grant-document US 12313739 child US 19192672

parent US continuation 16516084 20190718 parent-grant-document US 11428810 child US 17874895

Publication Classification

Int. Cl.: G01S15/89 (20060101); G01S7/53 (20060101); G01S7/54 (20060101)

U.S. Cl.:

CPC G01S15/89 (20130101); G01S7/53 (20130101); G01S7/54 (20130101);

Background/Summary

PRIORITY CLAIM, BENEFIT CLAIM AND INCORPORATION BY REFERENCE [0001] This application is a continuation of U.S. patent application Ser. No. 17/874,895 filed Jul. 27, 2022 which is a continuation of U.S. patent application Ser. No. 16/516,084 filed Jul. 18, 2019 now U.S. Pat. No. 11,428,810 which is a continuation of U.S. patent application Ser. No. 16/016,632 filed Jun. 24, 2018 now U.S. Pat. No. 10,429,505 and claims the benefit of U.S. Provisional Pat. App. No. 62/528,354 filed Jul. 3, 2017, the content of these applications being incorporated herein in their entireties and for all purposes. This application incorporates by reference, in their entireties and for all purposes, the disclosures of U.S. Pat. No. 3,144,631 concerning Mills Cross sonar, U.S. Pat. No. 8,305,841 concerning sonar used for mapping seafloor topography, U.S. Pat. No. 7,092,440 concerning spread spectrum communications techniques, U.S. Pat. No. 5,483,499 concerning Doppler frequency estimation, and U.S. Pat. No. 9,244,168 concerning frequency burst sonar.

BACKGROUND OF THE INVENTION

Field of the Invention

[0002] The present invention relates to underwater acoustical systems, methods of using underwater acoustical systems, and methods for processing and using the data they produce. In particular, the invention relates to survey systems including multibeam sonar systems capable of obtaining multi-perspective ensonification data.

Discussion of the Related Art

[0003] A month after the Titanic struck an iceberg in 1912, English meteorologist Lewis Richardson filed a patent at the British Patent Office for an underwater ranging device. Modern day successors to Richardson's invention are often referred to as SONAR (sound navigation and ranging) devices. Among these devices are ones using transducer arrays to project sound or pressure waves through a liquid medium and transducer arrays to receive corresponding echoes from features that scatter and/or reflect impinging waves.

[0004] Information about these features and their environment can be derived from the echoes. For example, bathymetric surveys provide information about the depth of scattering centers, water column surveys provide information about scattering centers in the water column, and seafloor characterization surveys provide information about scattering centers at the seafloor surface and below the seafloor surface. The diversity and quality of the information returned in echoes may be determined in part by the characteristics of the signal used to excite the projector transducers.

[0005] The cost of obtaining this information is strongly influenced by the timeframe during which manpower and equipment is required to acquire the information.

[0006] Although some progress towards improving data quality and diversity while reducing the time required to perform an underwater survey has been made, particularly through the use of multibeam echo sounders, long standing technological challenges and risks associated with building and testing costly new survey equipment present significant obstacles to further similar improvements.

SUMMARY OF THE INVENTION

[0007] The present invention provides a multi-perspective ensonification system and method. In an embodiment, a multi-perspective ensonification method comprising the steps of: installing a multibeam echo sounder system ("MBES") on a water going vehicle such that one or more transducers in a single MBES projector array and plural transducers in a single MBES hydrophone array are in a Mills Cross arrangement; modeling a waterbody with a plurality of "j" superposed layers (l.sub.1 . . . l.sub.j) having respective layer thicknesses (t.sub.1 . . . t.sub.j), each of the j layers having a layer entry sound speed and a layer exit sound speed such that a set of (j+1) sound

speed values (c.sub.1, c.sub.2 . . . c.sub.j+1) characterize the sound speed profile through the layers; designing a vehicle route and traversing the route such that during MBES operation along the route i) plural primary areas are ensonified, ii) plural secondary areas are ensonified, iii) each primary area is overlapped by a respective secondary area, and iv) for each overlap a first echo originating therein traverses a first path to the MBES and a second echo originating therein traverses a second path to the MBES at a location different from the first; via a travel time corresponding to each echo, modeling the propagation of sound through the waterbody to locate in three dimensions a reflector that returned the echo; one of the dimensions indicating a waterbody depth and the other two dimensions indicating coordinates in a reflector plane parallel to the waterbody free surface; selecting a colocation metric and using the metric to identify groups of reflectors that are colocated in the reflector plane; for each group of colocated reflectors, quantifying disagreements in the waterbody depths corresponding to the reflectors in the group; and, determining a set of adjusted sound speed values that tends to simultaneously reduce the disagreement within each group of depth estimates.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] The present invention is described with reference to the accompanying figures. These figures, incorporated herein and forming part of the specification, illustrate embodiments of the invention and, together with the description, further serve to explain its principles enabling a person skilled in the relevant art to make and use the invention.

[0009] FIG. 1A shows a survey system including a multibeam echo sounder system (“MBES”) of the present invention.

[0010] FIG. 1B shows an embodiment of at least portions of the MBES of FIG. 1A.

[0011] FIG. 2A shows a vessel equipped with a Mills Cross type arrangement of transducer arrays for use with the MBES of FIG. 1A.

[0012] FIG. 2B shows schematically an MBES fan such as a fan resulting from operation of the echo sounder system of FIG. 1A.

[0013] FIGS. 2C-D show an antiparallel track survey plan carried out using the MBES of FIG. 1A.

[0014] FIGS. 2E-F show a cross track survey plan carried out using the MBES of FIG. 1A.

[0015] FIGS. 2G-H show a same track survey plan carried out using the MBES of FIG. 1A.

[0016] FIGS. 2I-J show an exemplary waterbody model for use with the surveys of FIGS. 2B-H.

[0017] FIGS. 3A-G show a process using the MBES of FIG. 1A for testing sound speeds used in depth estimates.

[0018] FIG. 4 shows a method using the MBES of FIG. 1A for synthesizing a sound speed profile using the MBES of FIG. 1A.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0019] The disclosure provided in the following pages describes examples of some embodiments of the invention. The designs, figures, and description are non-limiting examples of the embodiments they disclose. For example, other embodiments of the disclosed device and/or method may or may not include the features described herein. Moreover, described features, advantages or benefits may apply to only certain embodiments of the invention and should not be used to limit the disclosed invention.

[0020] As used herein, the term “coupled” includes direct and indirect connections. Moreover, where first and second devices are coupled, intervening devices including active devices may be located therebetween.

Survey System

[0021] FIG. 1A shows a survey system **100A**. The survey system includes an echo sounder system

such as a multibeam echo sounder system **102** which may be mounted on a surface vehicle or vessel, a remotely operated vehicle, an autonomous underwater vehicle, or the like. As is further described below, echo sounder and/or survey system outputs **114** may be contemporaneous with echo sounder processing of hydrophone data as in some embodiments for bathymetry or non-contemporaneous with processing of hydrophone data as in some embodiments for waterbody bottom classification.

[0022] Data acquired by multibeam echo sounder systems **104** includes data from echo sounder listening devices such as hydrophones (e.g., transducers) that receive echoes which are related to the acoustic/pressure waves emanating from the echo sounder projectors but have returned by virtue of an interaction with inhomogeneities of many kinds. The interactions may take the form of reflection or scattering. The inhomogeneities, also known as reflectors and/or scattering centers, represent discontinuities in the physical properties of the medium. Exemplary scattering centers may be found in one or more of i) an ensonified volume of the waterbody such as a water column, ii) upon the ensonified surface of the bottom, or iii) within the ensonified volume of the sub-bottom.

[0023] Scattering centers of a biological nature may be present in the water column, as they are a part of the marine life. Scattering centers of a nonbiological nature may be present in the water column in the form of bubbles, dust and sand particles, thermal microstructure, and turbulence of natural or human origin, such as ships' wakes. Scattering centers on the surface of the bottom may be due to the mechanical roughness of the bottom, such as ripples, or be due to the inherent size, shape and physical arrangement of the bottom constituents, such as mud, sand, shell fragments, cobbles and boulders, or due to both factors. Scattering centers in the sub-bottom may be due to bioturbation of the sediments, layering of different sediment materials within the bottom, or buried manmade structures such as pipelines.

[0024] Data processing within the echo sounder system may include contemporaneous processing of hydrophone data **106**, for example to obtain bathymetric and/or backscatter data. Data processing may also include non-contemporaneous processing of multibeam echo sounder system data **108**, for example to characterize the environment including bottom conditions or the water column.

[0025] Data processing may include utilization of complementary or other data. For example, contemporaneous processing of hydrophone data **106** may utilize contemporaneous **110** and/or non-contemporaneous **112** data such as contemporaneously collected global positioning system ("GPS") data, sound speed measurements, attitude, and navigational information. For example, non-contemporaneous processing of echo sounder system data may utilize contemporaneous **110** and/or non-contemporaneous **112** data such as non-contemporaneously collected waterbody bottom composition data and tidal records.

[0026] FIG. **1B** shows portions of an exemplary multibeam echo sounder system ("MBES") **100B**. The echo sounder system includes a transducer section **120** and an acoustic transceiver **122**. The echo sounder system may include a transceiver interface such as an interface module **124** and/or a workstation computer **126** for one or more of data processing, data storage, and interfacing man and machine. Exemplary transducers, shown here in a Mills Cross arrangement **120**, include a transmitter or projector array **130** and a receiver or hydrophone array **140**. Projectors in the projector array may be spaced along a line that is parallel with a keel line or track of a vehicle or vessel to which they are mounted which may be referred to as an along track arrangement. In some embodiments, a receiver of the transceiver **122** has an operating frequency range matched with that of the projectors and/or the hydrophones.

[0027] During echo sounder operation, sound or pressure waves emanating from the projector array travel within a body of water and possibly within the bottom beneath the body of water and in doing so may undergo interactions, such as reflections or scattering, which disturb the propagation trajectory of the pressure waves. Some of the reflections or echoes are "heard" by the hydrophone

array. See for example the disclosure of Etal, U.S. Pat. No. 3,144,631, which is included herein by reference, in its entirety and for all purposes.

[0028] The acoustic transceiver **122** includes a transmitter section **150** and a receiver section **170**. The acoustic transceiver may be configured to transmit to a single projector array **130** and to receive from a single hydrophone array **140**. In some embodiments, such a transceiver may be said to operate with a single transmitter array and a single receiver array. Unless otherwise noted, the term transceiver does not require common transmitter and receiver packaging.

[0029] In various embodiments, a single projector array ensonifies the entirety of a swath on a single ping. Here, a projector array may be a single projector array regardless of the geometry, arrangement, or quantity of devices employed. For example, where a plurality of projectors forms a plurality of spatially distinct projector groups, the plural projectors are a single projector array if they are operated to ensonify the entirety of a swath on a single ping.

[0030] The echo sounder may further include a means such as an interface module **124** for interconnection with the transceiver **122**. This interface module may provide, among other things, a power supply for the transceiver, communications with the transceiver, communications with the workstation computer **126**, and communications with other sources of data such as a source of contemporaneous GPS data.

[0031] The workstation computer **126** may provide for one or more of data processing such as data processing for visualization of survey results, for data storage such as storage of bathymetry data and backscatter data, for user inputs, and for display of any of inputs, system status, and survey results.

Mills Cross Transducer Arrangement

[0032] FIGS. 2A-B show an exemplary vessel equipped with a multibeam echo sounder **200A**. See for example the echo sounders of FIGS. 1A-B. As seen in FIG. 2A, an MBES array package **204** is affixed to a vessel **202**, for example to a bottom of the vessel.

[0033] Within the array package **204** is an along track array of projectors **208** and a cross track array of hydrophones **210**. The projector array is for excitation by an echo sounder transmitter message. The hydrophone array is for receiving echoes of the transmitted message.

[0034] As explained below, a crossed array arrangement such as a Mills Cross arrangement of the projector and hydrophone arrays enables the echo sounder to operate with crossed transmit and receive beams wherein the cross intersection identifies a particular waterbody location, area, or cell. The crossed arrays may be in a perpendicular or a substantially perpendicular arrangement. Substantially perpendicular refers to generally small deviations from perpendicular caused by any of array assembly tolerances, mounting tolerances, adjustment tolerances, and the like.

Echoes Returned From Particular Locations

[0035] FIG. 2B shows bottom ensonification **200B**. In particular, an across track strip or fan of a waterbody bottom **212** is ensonified by the projector array **208**. Note the along track projector array **208** ensonifies an across track fan **212**. As shown, the projected beam **211** has a wide across track aperture angle $\theta_{sub.t1}$ as compared with a relatively narrow along track aperture angle $\theta_{sub.t2}$. Echoes from this ensonified fan are received by the hydrophone array **210**.

[0036] In various embodiments, MBES receiver beam steering enables subdivision of the fan **212** into a series of zones. This subdivision into zones enables identification of an echo returned from a particular zone or location **213** on the waterbody bottom **215**.

Survey Perspectives

[0037] Notably, when the fan **212** is ensonified, the vessel is in a particular position relative to the waterbody bottom **215**. As such, the echo returned from the waterbody bottom location **213** may be said to have been acquired from a particular perspective with the MBES in a particular position relative to the waterbody bottom location.

[0038] As discussed below, when echo data for a particular waterbody bottom location includes data from multiple different perspectives, this data can be used to test assumptions made about the

environment that propagates the echoes.

Echoes From Multiple Perspectives

[0039] Multi-perspective ensonification includes a process of operating MBES projectors at multiple vessel locations such that a site on the waterbody bottom is ensonified multiple times from multiple different perspectives.

[0040] For example, when the MBES projectors are operated at location (longitude 1, latitude 1), echo data ed1 from a zone z1 within the ensonified area is acquired. Later in time, when the MBES projectors are operated at location (longitude 2, latitude 2), echo data ed2 from a zone z2 that overlaps zone z1 may be acquired.

[0041] Where zones z.sub.1 and z.sub.2 are at least partially superimposed, an overlap is defined. The site may be ensonified from multiple perspectives and echo data may be acquired from multiple perspectives. In some embodiments, different perspectives result when the MBES pitch angles ensonifying zones z.sub.1 and z.sub.2 differ.

[0042] Various terminology may be used to refer to this and similar processes. For example, acquiring multiple echoes from the same site may be referred to as a part of a multi-perspective survey, multi-echo ray tracing, multi-look echo sounding, and/or multi-perspective ensonification, echoes, or queries.

Survey Plans

[0043] FIGS. 2C-D show an antiparallel track survey plan aimed at acquiring multi-perspective survey data 200C-D.

[0044] As shown in FIG. 2C, an MBES transducer plane x-z is at level yt and a waterbody bottom 215 plane x'-z' is at level yb. Survey vessel tracks are located in the upper x-z plane. As shown, the survey vessel movement along a first track Track 1 is parallel to and opposite of survey vessel movement along a second track Track 2. In some embodiments, deviations from parallel tracks arise from vessel instrument measurement inaccuracies, course and or heading errors arising from sea conditions, and the like. In some embodiments similar multi-perspective survey results are provided by non-opposed track directions.

[0045] Operation of MBES projectors on a vessel traversing Track 1 may, with a beam angle of $\theta t1$, ensonify a first waterbody bottom fan f1. And, operation of the MBES projectors while traversing Track 2 may, with a beam angle of $\theta t11$, ensonify a second waterbody bottom fan f2. The beam angles may be equal or not.

[0046] Notably, when fan f1 overlaps fan f2 a portion of the waterbody bottom is ensonified twice. As explained below, a first ensonification from Track 1 is from a first perspective and a second ensonification from Track 2 is from a second perspective.

[0047] As shown in FIGS. 2C-D, MBES operation on Track 1 results in ensonification of fan f1 which includes ensonification of cell c1 and ensonification Ap of a site within cell c1. In similar fashion, MBES operation on Track 2 results in ensonification of fan f2 which includes ensonification Bp of the same site within cell c2. Temporally, ensonification A.sub.p and its echo A.sub.h may precede ensonification B.sub.p and its echo B.sub.h.

[0048] This example shows an antiparallel track survey plan where a site defined by an overlap (an overlap, site, or overlap site) is ensonified from a first perspective on Track 1 and from a second perspective on Track 2. In particular, the first perspective is the location of g1 on Track 1 relative to the overlap site and the second perspective is the location of g2 on Track 2 relative to the overlapped.

[0049] FIGS. 2E-F show a cross track survey plan aimed at acquiring multi-perspective survey data 200E-F.

[0050] As shown in FIG. 2E, an MBES transducer plane x-z is at level yt and a waterbody bottom 215 plane x'-z' is at level yb. Survey vessel tracks, Track 1 and Track 2, are located in the upper x-z plane. As shown, the tracks cross at an angle α . In some embodiments, angle α is about a right angle with deviations subject to vessel instrument measurement inaccuracies, course and or

heading errors arising from sea conditions, and the like. In various embodiments the survey vessel direction of movement along either track may be reversed.

[0051] Operation of MBES projectors on a vessel traversing Track **1** may, with a beam angle of $\theta t1$, ensonify a first waterbody bottom fan **f1**. And, operation of the MBES projectors while traversing Track **2** may, with a beam angle of $\theta t11$, ensonify a second waterbody bottom fan **f2**. The beam angles may be equal or not.

[0052] Notably, when fan **f1** overlaps fan **f2** a portion of the waterbody bottom is ensonified twice. As explained below, a first ensonification from Track **1** is from a first perspective and a second ensonification from Track **2** is from a second perspective.

[0053] As shown in FIGS. 2E-F, MBES operation on Track **1** results in ensonification of fan **f1** which includes ensonification of cell **c1** and ensonification **Ap** of a site within cell **c1** and a corresponding echo **Ah**. In similar fashion, MBES operation on Track **2** results in ensonification of fan **f2** which includes ensonification **Bp** of the same site within cell **c2** and a corresponding echo **Bh**. Temporally, ensonification **A.sub.p** and its echo **A.sub.h** may precede ensonification **B.sub.p** and its echo **B.sub.h**.

[0054] This example shows a cross track survey plan where an overlap site is ensonified from a first perspective on Track **1** and from a second perspective on Track **2**. In particular, the first perspective is the location of **g1** on Track **1** relative to the overlap site and the second perspective is the location of **g2** on Track **2** relative to the overlap site.

[0055] FIGS. 2G-H show a same track survey plan aimed at acquiring multi-perspective survey data **200G-H**.

[0056] As shown in FIG. 2G, an MBES transducer plane **x-z** is at level **yt** and a waterbody bottom **215** plane **x'-z'** is at level **yb**. Survey vessel Track **1** is located in the upper **x-z** plane. In some embodiments, Track **1** is a straight line. And, in some embodiments Track **1** deviates from a straight line. For example, where Track **1** is about a straight line, deviations from a straight line path include deviations due to vessel instrument measurement inaccuracies, course and or heading errors arising from sea conditions, and the like. In various embodiments the survey vessel direction of movement along the track may be reversed.

[0057] An early operation of MBES projectors on a vessel traversing Track **1** may, with a cross track beam angle of $\theta t1$, ensonify a first plurality of waterbody bottom fans **f1-f5**. As shown, the fans **f1-f5** extend between an along track angle $\beta t1$.

[0058] A later operation of the MBES projectors while traversing Track **1** may, with a beam angle of $\theta t11$, ensonify a second plurality of waterbody bottom fans **f1'-f5'**. As shown, the fans **f1'-f5'** extend between an along track angle $\beta t11$. The angles $\theta t1$, $\theta t11$ may be equal or not. The angles $\beta t1$, $\beta t11$ may be equal or not.

[0059] As shown, the early MBES projector operation produces a grid of cells located by fan **f1-f5** and by zone **k1-k4**. For example a cell **f1**, **k1** is ensonified by early MBES operation while a cell **f5'**, **k1** is ensonified by later MBES operation. These cells do not overlap.

[0060] In another example a cell **f4**, **k1** is ensonified by early MBES operation while the same cell **f1'**, **k1** is ensonified by later MBES operation. These cells overlap. As explained below, early MBES operation and later MBES operation provides ensonification of cell **f4**, **k1** from a first perspective at **g1** along Track **1** and ensonification of overlapping cell **f1'**, **k1** from a second perspective at **g2** along Track **1**.

[0061] As shown in FIG. 2H, early MBES operation on Track **1** at **g1** results in ensonification of fans **f1-f5** which includes ensonification **Ap** of cell **f4**, **k1** and a corresponding echo **Ah**. Later MBES operation on Track **1** at **g2** results in ensonification of fans **f1'-f5'** which includes ensonification **Bp** of cell **f1'**, **k1** and a corresponding echo **Bh**. Temporally, ensonification **A.sub.p** and echo **A.sub.h** may precede ensonification **B.sub.p** and echo **B.sub.h**.

[0062] This example shows a same track survey plan where a site is ensonified from a first and a second perspective along Track **1**. In particular, the first perspective is the location of **g1** on Track **1**

relative to the overlap site and the second perspective is the location of g2 on Track 1 relative to the overlap site.

Waterbody Model

[0063] Estimating the propagation path(s) of acoustic energy through a waterbody may be referred to as ray tracing. This ray tracing may involve dividing the waterbody into layers. Tracing sound rays through a body of water may involve dividing the waterbody into layers. With defined layers, physical properties such as the speed of sound may be measured, estimated, or otherwise made available for one or more layers. The value of a particular media property may be held constant or varied, such as linearly varied, within a layer. For example, in a multi-layer media model the speed of sound may be constant within a layer or change with a constant gradient within a layer provided the speed of sound is continuous from layer to layer.

[0064] FIGS. 2I-J show an exemplary waterbody model 200I-J. As seen, the waterbody includes three layers (l1, l2, l3), each layer having a corresponding thickness (t1, t2, t3). In each of the figures, four interfaces with corresponding sound speeds (c1, c2, c3, c4) and (c1', c2', c3', c4') demarcate the layers.

[0065] FIG. 2I shows a first echo from a point on a waterbody bottom 283 that is traced with three ray segments. In accordance with Snell's law of refraction ($\sin \theta_x / c_x = \sin \theta_y / c_y$), a first ray segment ra exits layer l3 at an angle θ_3 , a second ray segment rb exits layer l2 at an angle θ_2 , and a third ray segment rc exits layer l1 at an angle θ_1 . In various embodiments, the third ray segment rc leaves layer l1 at or near an MBES hydrophone array.

[0066] As skilled artisans will appreciate, ray segments like those of FIGS. 2I-J may travel through a layer and/or be modeled as traveling through a layer with no change in sound speed or with various changes in sound speed. For example, sound may travel through a layer with a constant sound speed and experience no change of ray path angle resulting in a straight ray segment. For example, sound may travel through a layer with a constant sound speed gradient and experience a gradual change of ray path angle resulting in a curved ray segment. Notably, the figures do not attempt to replicate curved ray segments. For example, in some embodiments ray angles at layer interfaces may change abruptly with gradual continuous changes thereafter as in a prior layer. For example, in some embodiments the slopes of adjoining rays at layer interfaces may be equal or about equal, for example within 1 to 10 percent difference.

[0067] FIG. 2J shows a second echo from the point 283 on the waterbody bottom. Here, a first ray segment ra' exits layer l3 at an angle θ_3' , a second ray segment rb' exits layer l2 at an angle θ_2' , and a third ray segment rc' exits layer l1 at an angle θ_1' . In various embodiments, the third ray segment leaves layer l1 at or near an MBES hydrophone array.

[0068] As will be noted, the ray segments tracing the first echo are characterized by a more severe slope than those tracing the second echo. This shows, among other things, that the first and second echoes from the point on the waterbody bottom 283 correspond to ensonifications from different perspectives as discussed above.

[0069] It should be noted that FIGS. 2I-J are based on a particular waterbody model and are merely illustrative. For example, the number of layers used in the model may be 2, 3, 4, 5 or more. For example, the value of the speed of sound may vary with depth.

Testing Sound Speeds

[0070] FIGS. 3A-3G show a process for testing sound speeds used in depth estimates 300A-G.

[0071] FIG. 3A provides an overview of the process 300A. In a first step, a model of the waterbody where sound speeds at various depths will be estimated is constructed. See for example the models of FIGS. 2I-J. In a second step, a survey path is selected. See for example the survey paths of FIGS. 2A-H and in particular survey paths that provide multi-perspective ensonifications of individual overlap sites. In the third step 330, survey data is acquired when an MBES is operated on board a vessel that follows the selected survey path. From this data, waterbody bottom reflectors are located in a fourth step.

[0072] Because it is unlikely that multiple echoes will emanate from the same reflector, groups of reflectors in relatively small areas on the waterbody bottom are assumed to be colocated and to provide multi-perspective echoes from the same location. For example, the waterbody bottom may be divided using a square grid into colocation areas that are one meter on a side. Notably, grid size may vary with water depth owing to beam footprints that vary with depth.

[0073] In step **350**, colocated reflectors are identified using a method such as the one just described. Because colocated reflectors are found in a small area on the waterbody bottom, the depth estimate made for each of the reflectors should be closely similar or, perhaps within measurement accuracy, the same. Notably, reducing the grid size reduces the variation in actual depths among a group of colocated reflectors.

[0074] With the assumption that depths among colocated reflectors should be the same, in a sixth step **360** disagreements in depth estimates are characterized in a quantitative manner. In step seven **370**, the sensitivity in depth disagreements to sound speed perturbations is quantified. In step eight **380**, the depth estimate disagreements are reduced or minimized by selecting speed of sound values that achieve this result. In an embodiment, the process ends thereafter at step **390**.

[0075] FIGS. **3B-3G** which follow provide a flowchart with process step details **300B-G**.

Modeling the Environment

[0076] In FIG. **3B**, the flowchart starts with modeling the environment in step **310**. As shown alongside the flowchart, a waterbody model **312** provides four layers **l1-l4** with respective layer thicknesses **t1-t4**. The sound speeds entering and leaving the waterbody are **c1** and **c5** while the sound speeds at layer boundaries are **c2-c4**. Angles of refraction entering each layer are **θ1-θ4** and the angle of refraction leaving layer **l4** is **θ5**.

[0077] As skilled artisans will appreciate, ray segments like those of the waterbody model **312** may travel through a layer and/or be modeled as traveling through a layer with no change in sound speed or with various changes in sound speed. For example, sound may travel through a layer with a constant sound speed and experience no change of ray path angle resulting in a straight ray segment. For example, sound may travel through a layer with a constant sound speed gradient and experience a gradual change of ray path angle resulting in a curved ray segment. Notably, the figures do not attempt to replicate curved ray segments. For example, in some embodiments ray angles at layer interfaces may change abruptly with gradual continuous changes thereafter as in a prior layer. For example, in some embodiments the slopes of adjoining rays at layer interfaces may be equal or about equal, for example within 1 to 10 percent difference.

[0078] A table alongside the flowchart **314** includes selected variables and their descriptions.

[0079] Known variables in the table are travel time **tt** for an acoustic message emitted by the projectors **208** and received by the hydrophones **210**, sound speed at the launch **c1**, launch angle **θ1**. User defined variables are the thicknesses **t1-t3** of layers of waterbody layers **l1-l3**.

[0080] Initially estimated variables in the table are sound speeds **c2-c5** and angles of refraction **θ2-θ5**. The unknown variable in the table is the thickness of layer **l4**.

Selecting Survey Path

[0081] FIG. **3C** is a continuation **300C** of the flowchart of FIG. **3B** as indicated by link **f1**. In step **320** a survey path is selected. As shown alongside the flowchart, the survey path selected is an antiparallel track path **322**. Track B overlaps Track A, the direction of Track B being opposite the direction of Track A.

[0082] As discussed above, with this survey path the ensonification of a Track A cell **325** and the subsequent ensonification of an overlapping Track B cell **327** is intended to provide echoes from multiple perspectives. In particular, echoes resulting from the first ensonification of colocated reflectors are from a perspective other than that of echoes resulting from the second ensonification of the colocated reflectors.

[0083] Concerning selection of an antiparallel tracks survey path, the discussion above shows any of several survey paths might be selected including parallel tracks in the same or opposed

directions, cross tracks in similar or opposed directions, and same track forward and backward look directions. Further, any combinations of these paths may be chosen to provide multiple echoes from differing perspectives from each of plural reflectors.

[0084] Notably, while this discussion speaks of echoes from multiple, e.g., two different, perspectives, a group of colocated reflectors may return echoes from many different perspectives.

Acquiring Data

[0085] An acquired data step **330** includes an ensonification step **332** where multiple “i” areas ($A_1, A_2 \dots A_i$) are ensonified with “i” pings ($P_1, P_2 \dots P_i$) to obtain echoes from “i” perspectives. Also included is a receive returns step **334** where waterbody bottom reflectors return echoes from these pings and round trip travel times of those echoes are measured for all beams, fans, and pings.

[0086] As shown alongside the flowchart, an example with $i=3$ is shown. For illustrative purposes the waterbody bottom areas **A1**, **A2**, **A3** are shown as circles. Reflectors located in the common area “Z” where the three circles overlap will return echoes from three different perspectives.

[0087] Notably, what is presented here is exemplary. For example, just as two areas may provide an intersecting zone z, so too may many more than two or three overlapping areas provide an intersecting zone.

Ray Tracing to Determine Reflector Locations

[0088] Given measured travel time information and the modeled sound speed profile, in step **340** acoustic paths through the layers of the waterbody model **312** between the MBES and ensonified reflectors are modeled. Within each of the areas **A1**, **A2**, **A3** ray tracing to reflectors provides coordinates x, y, z specific to each reflector. As shown, matrices **326** for respective areas **PA1**, **PA2**, **PA3** provide coordinates for reflectors therein. Here, seven or more sets of reflector coordinates appear in each matrix and indicate returns from corresponding reflectors in each of the areas. Coordinate indicia indicate a reflector number (e.g., 1-7) and an area that confines the reflector (e.g., **A1**, **A2**, **A3**).

Finding Colocated Reflectors

[0089] FIG. **3D** is a continuation **300D** of the flowchart of FIG. **3C** as indicated by link **f2**. Here, groups of reflectors may be considered as “colocated” or as representative of a single location on a waterbody bottom such as a location having a single or substantially invariant depth such as a depth that varies within a survey map tolerance, survey instrument tolerance, selected tolerance, or similar industry tolerance.

[0090] A step of finding colocated reflectors **350** includes an identification step **352**, a collection step **354**, and a rewrite step **356**.

[0091] In the identification step **352**, colocated reflectors are identified as reflectors having the same or similar x, y coordinates across all three of the matrices **PA1**, **PA2**, **PA3** are marked **353**.

[0092] In particular, as shown by the dotted box outlines, coordinate pairs $x_{sub.2,A1}, y_{sub.2,A1}$ and $x_{sub.5,A2}, y_{sub.5,A2}$ and $x_{sub.1,A3}, y_{sub.1,A3}$ identify a 1.^{sup}st same or similar waterbody bottom location. As shown by dashed box outlines, coordinate pairs $x_{sub.6,A1}, y_{sub.6,A1}$ and $x_{sub.7,A2}, y_{sub.7,A2}$ and $x_{sub.4,A3}, y_{sub.4,A3}$ identify a 2.^{sup}nd same or similar waterbody bottom location. And, as shown by dashed and dotted box outlines, coordinate pairs $x_{sub.4,A1}, y_{sub.4,A1}$ and $x_{sub.3,A2}, y_{sub.3,A2}$ and $x_{sub.6,A3}, y_{sub.6,A3}$ identify a 3.^{sup}rd same or similar waterbody bottom location.

[0093] Reflector coordinates may be said to identify a similar location when they are situated within a selected colocation area, for example within an area of one square meter. Reflector coordinates may be said to identify a similar location when they lie within a colocation circle, for example a circle having a diameter of one meter. Similarly located reflectors may be identified by overlaying and dividing the waterbody bottom with a pattern such as a grid, regular grid, or square grid and designating each area so identified as a colocation area. For example, where a regular grid such as a square grid is used, areas identified within the grid may be colocation areas such that reflectors falling within a particular grid defined area are colocated reflectors with similar x, y

coordinates.

[0094] In the collection step **354**, the coordinates of similarly located reflectors are collected **355** in three matrices CP1, CP2, CP3. As suggested by the coordinate indices below the matrices, a simplification in matrix presentation results from rewriting the indices in a manner suggesting that for a given matrix the x,y coordinates are the same or similar.

[0095] In the rewriting step **356** illustrated by three matrices **357**, the multiple colocated x and y coordinates of the matrices **355** are assigned a single x and y value to represent the group, for example using an average, grid center or area center. See in particular indices of x, y, z, are rewritten in matrices CPT1, CPT2, CPT3 that correspond to matrices CP1, CP2, CP3. Here, remarking the indices of x and y to be the same within a given matrix emphasizes the equality or similarity of the x, y pairs in the matrix, for example x.sub.1, y.sub.1 for all of the x, y pairs in matrix CPT1.

[0096] Notably, the z coordinates are not necessarily equal or similar. As such, they are remarked as z.sub.a,b where “a” is constant in a particular matrix and “b” varies from row to row in the matrix. For example, in the first matrix CPT1 the z coordinates by row are z.sub.1,1, z.sub.1,2, z.sub.1,3.

[0097] In each of the rewritten matrices CPT1, CPT2, CPT3 a respective location x, y corresponds with three different depth estimates. For example, in CPT1 the location x1,y1 corresponds with depth estimates z.sub.a,1, z.sub.a,2, z.sub.a,3.

Solution Paradigms

[0098] In various embodiments, we may assume the depth estimates in each matrix **357** should be the same even though they are not. Equality may be assumed because, for each matrix, the depth estimates correspond with a group of colocated reflectors. As such, the depth estimates in a particular matrix may be viewed as samples or sample values “s” of the same environmental variable at a particular location.

[0099] The goodness of this same matrix/same depth assumption depends on variables including the regularity of the waterbody bottom and the characteristic dimension(s) and/or pattern(s) used to identify colocated reflectors.

[0100] Whatever the case, various methodologies for testing and/or improving depth estimates may manipulate variables such as sound speed(s) to reduce the variability in depth estimates for each group and/or multiple groups of colocated reflectors.

Characterizing Disagreements in Depth Estimates

[0101] FIG. **3E** is a continuation **300E** of the flowchart of FIG. **3D** as indicated by link f3. Here, a step of characterizing disagreement in depth estimates includes a step establishing a basis to characterize differences **360** and the step of characterizing the disagreement **362**.

[0102] In particular, step **360** establishes a basis for characterizing differences in depth estimates. For each group of colocated reflectors a mean value matrix z as shown below expresses this basis. TABLE-US-00001 Mean Value Equation Variables Variable description [00001]

$$\bar{z}_x = (\overset{\bar{z}_1}{\underset{\bar{z}_3}{\text{.Math.}}}_{y=1}^s z_{x,y}) / s \text{ .Math. } \bar{z}_2 \text{ .Math. } z_{\text{sub.x}} \text{ mean depth for each group x of colocated}$$

reflectors z.sub.x,y depth at y.sup.th reflector in group x of colocated reflectors s number of samples

[0103] Given a basis for characterizing differences in depth estimates, step **364** provides for each group of colocated reflectors a measure of the disagreement among depth estimates as expressed by vector d shown in the equation below.

TABLE-US-00002 Disagreement Equation Variables Variable description [00002]

$$d_x = (\text{Math}.\bar{z}_x - z_{x,y} \text{Math}.) / s \text{Math}.$$

$$d_1$$

$$d_2$$

$$d_3$$

estimate for each group x of colocated reflectors (residuals) z.sub.x mean depth for each group x of colocated reflectors z.sub.x,y depth at y.sup.th reflector in group x of colocated reflectors s number of samples

Constructing a Gradient Matrix

[0104] FIG. 3F is a continuation 300F of the flowchart of FIG. 3E as indicated by link f4. The gradient matrix is a metric of the sensitivity of depth estimates to modeled sound speeds and is constructed by first perturbing the values of sound speed c.sub.2 . . . c.sub.p by a positive increment and then by a negative increment. Then, for each perturbation, steps are repeated including the steps of determining reflector locations 340, finding colocated reflectors 350, and characterizing disagreements in depth estimates 360 with vectors d.sub.+ and d.sub.-.

[0105] In step 371, a counter p counts from 2 to 5 indicating values of the speed of sound c.sub.2 . . . c.sub.5 consistent with a four layer waterbody model having five corresponding values of the speed of sound c.sub.1 . . . c.sub.5 where c.sub.1 is a known value of the speed of sound at the launch.

[0106] In step 372, a positive perturbation (+Δ) is applied to a p.sup.th sound speed value c.sub.p. Steps 340-364 are repeated and vector d.sub.p+ is populated 376. The p.sup.th sound speed value c.sub.p is then reset.

[0107] In step 373, a negative perturbation (-Δ) is applied to the p.sup.th sound speed value c.sub.p. Steps 340-364 are repeated and vector d.sub.p- is populated 377. The p.sup.th sound speed value c.sub.p is then reset.

[0108] In step 374, a p.sup.th row of the gradient matrix G is populated. In particular, G.sub.p,i= (d.sub.p+,i-d.sub.p-,i)/2 mag (Δ) where counter i varies from 1 to n to populate 378 the columns of the matrix G, each value of i representing the i.sup.th group of colocated reflectors. When the last column is populated, counter p indexes to the next value in step 375 and steps 372-374 are repeated. When the last row of the matrix G is populated, the process proceeds to step 382 of the minimize disagreement block 380.

Minimizing Depth Estimate Disagreement

[0109] FIG. 3G is a continuation 300G of the flowchart of FIG. 3F as indicated by link f5. In this figure, disagreements among depth estimates in each group of colocated reflectors are simultaneously minimized utilizing conventional least-squares techniques associated with linear algebra.

[0110] In step 382, an equation utilizing the gradient matrix G and disagreement in depth estimates vector d provides a vector of corrections mhat to be applied to sound speed values to reduce or minimize depth disagreements. The equation presented 382 is a well-known least-squares minimizing solution whose derivation is available in academic texts such as the text by Munk, Walter, et al., *Ocean Acoustic Tomography*, Cambridge University Press, 1995. The equation provides two terms for conveying prior information, if known, about the noise or solutions. The diagonal of matrix R can be populated with the relative sizes of noise variance associated with each observation in vector d. The diagonal of matrix S can be populated with the relative sizes of the elements of mhat.

TABLE-US-00003 Overdetermined Variable System Equation Variables description {circumflex over (m)} Vector of corrections to (mhat) be applied to sound speed values c.sub.2 . . . c.sub.5. G.sup.T Transpose of gradient matrix G (interchange of rows and columns) {circumflex over (m)} = (G.sup.TR.sup.-1G + S.sup.-1).sup.-1G.sup.TR.sup.-1d R Matrix conveying information about data uncertainty. R.sup.-1 Inverse of R matrix G Gradient matrix. S Matrix conveying information about model parameter sizes. S.sup.-1 Inverse of S matrix d disagreement in depth estimate for

each group x of colocated reflectors (residuals)

[0111] In step **384**, each of the sound speed values $c_2 \dots c_5$ is corrected using the correction vector \hat{m} .

TABLE-US-00004 Sound Speed Estimates Variables Variable description $c_{sub.2est} = c_{sub.2} - \{\text{circumflex over (m)}\}_{sub.2}$ c sound speed $c_{sub.3est} = c_{sub.3} - \{\text{circumflex over (m)}\}_{sub.3}$ \hat{m} sound speed correction $c_{sub.4est} = c_{sub.4} - \{\text{circumflex over (m)}\}_{sub.4}$ $c_{sub.5est} = c_{sub.5} - \{\text{circumflex over (m)}\}_{sub.5}$

Synthesizing a Sound Speed Profile

[0112] The above solution procedure is based on a multilayer waterbody model with a known sound speed $c_{sub.1}$ at launch and initial estimates or otherwise available values of sound speed at the layer interfaces and at the waterbody bottom.

[0113] Notably, cases may arise where the only available value(s) of sound speed are sound speed value(s) at launch. For example, a survey conducted with equipment malfunction(s) or human error(s) may result in such a case. For example, a survey conducted with the intent to estimate sound speed values after the survey is conducted may result in such a case.

[0114] In some embodiments, the system and method of the present invention may be used to synthesize a sound speed profile. For example, where sound speed at launch is known, the system and method of the present invention may be used to synthesize a sound speed profile through a waterbody modeled with a plurality of layers.

[0115] FIG. 4 shows a method for synthesizing a sound speed profile where a waterbody is modeled with multiple layers **400**. Steps in this synthesis method corresponding to those mentioned above (see e.g., FIGS. 3A-G) may be carried out in a similar manner.

[0116] In a first step **410** the need for synthesizing a sound speed profile is evaluated. Where there is a need, the process proceeds to a second step **420**.

[0117] In the second step **420**, known variables are identified. In particular, knowns may be sound speed at a Mills Cross transducer array, launch angle, travel time, GPS data, and vessel heading/tilt/roll data. In a third step **430**, the environment is modeled. Here, $c_{sub.1}$ is known and for j layers the sound speed is set to $c_{sub.1}$ such that in each layer the speed of sound is the same.

[0118] With a multilayer model, ray tracing locates reflectors in a fourth step **440**. And, finding groups of colocated reflectors follows in a fifth step **450**.

[0119] In step **460**, i) disagreements in depth estimates are characterized in a manner similar to that described in step **360** above, ii) a gradient matrix is constructed in a manner similar to that described in step **370** above, iii) disagreements among depth estimates in each group of colocated reflectors are reduced in a manner similar to that described in step **380** above, iv) sound speed adjustments are calculated in a manner similar to that described in step **380** above, and v) sound speed adjustments are applied as suggested above. Using the adjusted values of sound speed, a survey may be created in step **470**. Following step **470** is an end step **480**.

[0120] In an embodiment, a threshold value that when compared to a function of the measured depth disagreements indicates whether the assumed sound speed profile differs from the real environment.

[0121] While various embodiments of the present invention have been described above, it should be understood that they have been presented by way of example only, and not limitation. It will be apparent to those skilled in the art that various changes in the form and details can be made without departing from the spirit and scope of the invention. As such, the breadth and scope of the present invention should not be limited by the above-described exemplary embodiments, but should be defined only in accordance with the following claims and equivalents thereof.

Claims

- 1.** A multi-perspective sonar method comprising the steps of: ensonifying from different perspectives each of multiple areas ($A_1 \dots A_n$) having a zone Z in common; locating reflectors in Z and their estimated depths via ray tracing; using locations of the reflectors to find collocated groups ($g_1 \dots g_n$) of reflectors; for each group g_x of collocated reflectors, characterizing disagreement among the group's reflector depth estimates; and, utilizing a numerical minimization technique to find one or more sound speeds that minimize reflector depth estimate disagreements.
- 2.** The method of claim 1 wherein data is acquired from the intersections of a single beam emitted by projectors with a plurality of beams emitted by hydrophones.
- 3.** The method of claim 1 wherein the reflectors are located on a waterbody bottom divided into areas, a collocated group of reflectors being those reflectors found in the same area.
- 4.** The method of claim 1 wherein the disagreements in reflector depth estimates are used to construct a system of simultaneous equations that is overdetermined, plural adjustments to respective sound speed values being indicated by a solution to the simultaneous equations.
- 5.** The method of claim 1 wherein estimates of sound speed as a function of depth are perturbed, the effects of the perturbations on travel times used in derivation of plural sound speed values.
- 6.** The method of claim 1 wherein ray tracing along non-intersecting first and second routes results in ensonifications from different perspectives when (i) at least partially superimposed first and second waterbody fans overlap at a site and (ii) there are multiple echoes from multiple collocated reflectors at the site.
- 7.** The method of claim 1 wherein ray tracing along intersecting first and second routes results in ensonifications from different perspectives when (i) at least partially superimposed first and second waterbody fans overlap at a site and (ii) there are multiple echoes from multiple collocated reflectors at the site.
- 8.** The method of claim 1 wherein ensonifications from different perspectives occur while ray tracing along a single route when (i) at least partially superimposed first and second waterbody fans overlap at a site and (ii) there are multiple echoes from multiple collocated reflectors at the site.
- 9.** The method of claim 1 wherein at least partially superimposed first and second waterbody fans overlap, the first waterbody fan resulting from a forwardly pitched fan at time₁ and the second waterbody fan resulting from a rearwardly pitched fan at time₂ where time₂>time₁.
- 10.** The method of claim 1 wherein the ray tracing is from a water going vehicle and the result of the survey is a bathymetric survey.
- 11.** A multi-perspective sonar comprising: from different perspectives, projectors for ensonifying each of multiple areas ($A_1 \dots A_n$) having a common zone Z; hydrophones for receiving echoes from reflectors in Z and ray tracing using one or more sound speed estimates for locating these reflectors and their estimated depths; reflector locations used to find ($g_1 \dots g_n$) groups of collocated reflectors; for each group g_x the disagreement among depth estimates is characterized; and, a numerical minimization technique used to find one or more sound speeds that minimize depth disagreements.
- 12.** The sonar of claim 11 wherein data is acquired from the intersections of a single beam emitted by projectors with a plurality of beams emitted by hydrophones.
- 13.** The sonar of claim 12 wherein the reflectors are located on a waterbody bottom divided into areas, a collocated group of reflectors being those found in the same area.
- 14.** The sonar of claim 11 wherein the disagreements in reflector depth estimates are used to construct a system of simultaneous equations that is overdetermined, plural adjustments to respective sound speed values being indicated by a solution to the simultaneous equations.
- 15.** The sonar of claim 11 wherein estimates of sound speed as a function of depth are perturbed, the effects of the perturbations on travel times used in derivation of plural sound speed values.
- 16.** The sonar of claim 11 wherein ray tracing along non-intersecting first and second routes results in ensonifications from different perspectives when (i) at least partially superimposed first and

second waterbody fans overlap at a site and (ii) there are multiple echoes from multiple collocated reflectors at the site.

17. The sonar of claim 11 wherein ray tracing along intersecting first and second routes results in ensonifications from different perspectives when (i) at least partially superimposed first and second waterbody fans overlap at a site and (ii) there are multiple echoes from multiple collocated reflectors at the site.

18. The sonar of claim 11 wherein ensonifications from different perspectives occur while ray tracing along a single route when (i) at least partially superimposed first and second waterbody fans overlap at a site and (ii) there are multiple echoes from multiple collocated reflectors at the site.

19. The sonar of claim 11 wherein at least partially superimposed first and second waterbody fans overlap, the first waterbody fan resulting from a forwardly pitched fan at time1 and the second waterbody fan resulting from a rearwardly pitched fan at time2 where $\text{time2} > \text{time1}$.

20. The sonar of claim 11 wherein the ray tracing is from a water going vehicle and the result of the survey is a bathymetric survey.
