

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250251775

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

Bell; Debra M. et al.

MEMORY DEVICE SENSORS

Abstract

Systems, apparatuses, and methods related to using memory device sensors are described. Some memory system or device types include sensors embedded in their circuitry. For instance, a device can be coupled to a memory device with an embedded sensor. The memory device can transmit the data generated by the embedded sensor using a sensor output coupled to the device. The memory device may generate, based at least in part on a characteristic of a memory device, a signal from a sensor embedded in the memory device and transmit the signal generated by the sensor from the memory device to another device coupled to the memory device.

Inventors: Bell; Debra M. (Boise, ID), Baghi; Roya (Boise, ID), Gove; Erica M. (Boise, ID), Hosseinimakarem; Zahra (Boise, ID), O'Donnell; Cheryl M. (Boise, ID)

Applicant: Micron Technology, Inc. (Boise, ID)

Family ID: 76209100

Appl. No.: 19/185656

Filed: April 22, 2025

Related U.S. Application Data

parent US continuation 18379440 20231012 parent-grant-document US 12298835 child US 19185656

parent US continuation 17892629 20220822 parent-grant-document US 11789519 child US 18379440

parent US continuation 16707488 20191209 parent-grant-document US 11435811 child US 17892629

Publication Classification

Int. Cl.: G06F1/3234 (20190101); G11C11/56 (20060101); G11C16/26 (20060101)

Background/Summary

PRIORITY INFORMATION [0001] This application is a Continuation of U.S. application Ser. No. 18/379,440 filed on Oct. 12, 2023, which is a Continuation of U.S. application Ser. No. 17/892,629 filed on Aug. 22, 2022, which issued as U.S. Pat. No. 11,789,519 on Oct. 17, 2023, which is a Continuation of U.S. application Ser. No. 16/707,488 filed on Dec. 9, 2019, which issued as U.S. Pat. No. 11,435,811 on Sep. 6, 2022, the contents of which are herein incorporated by reference.

TECHNICAL FIELD

[0002] The present disclosure relates generally to semiconductor memory and methods, and more particularly, to apparatuses, systems, and methods for memory device sensors.

BACKGROUND

[0003] Memory devices are typically provided as internal, semiconductor, integrated circuits in computers or other electronic systems. There are many different types of memory including volatile and non-volatile memory. Volatile memory can require power to maintain its data (e.g., host data, error data, etc.) and includes random access memory (RAM), dynamic random access memory (DRAM), static random access memory (SRAM), synchronous dynamic random access memory (SDRAM), and thyristor random access memory (TRAM), among others. Non-volatile memory can provide persistent data by retaining stored data when not powered and can include NAND flash memory, NOR flash memory, and resistance variable memory such as phase change random access memory (PCRAM), resistive random access memory (RRAM), and magnetoresistive random access memory (MRAM), such as spin torque transfer random access memory (STT RAM), among others.

[0004] Memory devices can be coupled to another device (e.g., a computing device, a processing resource, etc.) to store data, commands, and/or instructions for use by the device while the computer or electronic system is operating. For example, data, commands, and/or instructions can be transferred between the other device and the memory device(s) during operation of a computing or other electronic system.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] FIG. 1 is a functional block diagram of an apparatus in the form of a computing system including memory device sensors in accordance with a number of embodiments of the present disclosure.

[0006] FIG. 2 is a functional block diagram in the form of a computing system including device sensors in accordance with a number of embodiments of the present disclosure.

[0007] FIG. 3 is flow diagram including examples of memory device sensors in accordance with a number of embodiments of the present disclosure.

[0008] FIG. 4 is a flow diagram representing an example method for memory device sensors in accordance with a number of embodiments of the present disclosure.

[0009] FIG. 5 is a flow diagram representing another example method for memory device sensors in accordance with a number of embodiments of the present disclosure.

DETAILED DESCRIPTION

[0010] Systems, apparatuses, and methods related to using memory device sensors are described.

Some memory system or device types include sensors embedded in their circuitry. For instance, a device can be coupled to a memory device with an embedded sensor. The memory device can transmit the data generated by the embedded sensor using a sensor output coupled to the device. For instance, the memory device may generate, based at least in part on a characteristic of a memory device, a signal from a sensor embedded in the memory device and transmit the signal generated by the sensor from the memory device to another device coupled to the memory device. [0011] Utilizing sensors embedded in memory devices to obtain information generated by the embedded sensor can conserve resources (e.g., space, money, power, etc.) by removing the need to include hardware for an external sensor. For instance, another device can be coupled to a memory device including an embedded sensor. The memory device can transmit the signal generated by the embedded sensor using a dedicated sensor output coupled to the other device.

[0012] A computing system including memory devices can include one or more different memory media types which can be used to store (e.g., write) data in a computing system. Such data can be transferred between the computing system and the memory system. The data stored in the memory media of the memory device can be important or even critical to operation of the computing system and/or another device connected to the memory device. There are various types of memory devices including memory media. Some examples of memory media include non-volatile memory and volatile memory.

[0013] Non-volatile memory can provide persistent data by retaining stored data when not powered and can include NAND flash memory, NOR flash memory, read only memory (ROM), Electrically Erasable Programmable ROM (EEPROM), Erasable Programmable ROM (EPROM), and Storage Class Memory (SCM) that can include resistance variable memory, such as phase change random access memory (PCRAM), three-dimensional cross-point memory (e.g., 3D X Point™), resistive random access memory (RRAM), ferroelectric random access memory (FeRAM), magnetoresistive random access memory (MRAM), and programmable conductive memory, among other types of memory. Volatile memory can require power to maintain its data (e.g., error data, etc.) and includes random-access memory (RAM), dynamic random access memory (DRAM), and static random access memory (SRAM), among others. Some types of memory devices can include sensors embedded in the circuitry of the memory device.

[0014] For example, DRAM can include one or more sensors (e.g., a temperature sensor) that are embedded in circuitry. The embedded sensors can be programmable to generate a signal. The signal can represent sensor data and the memory device (e.g., including DRAM) can receive the signals and store the data associated with the sensors (e.g., sensor data). The signal can represent data related to an environment where the DRAM is located and/or related to another device that is coupled to the DRAM. Computing devices can frequently include DRAM as memory media. As other devices such as, wireless communication devices, mobile devices, semi-autonomous vehicles, fully autonomous vehicles, Internet of Things (IoT) devices, mobile artificial intelligence systems, etc. become more prevalent, sensors and other devices related to computing systems are also increasingly needed to generate information about the surroundings of the computing device. As such, there is a growing need for information gathered by sensors coupled to computing devices.

[0015] In some approaches, external sensors can be coupled to a host and transmit a signal including sensor data to a memory device coupled to another device that can be included in a host. This approach can provide a signal generated from the sensor to the host. This approach can be slow, costly, and the sensors can occupy space that may not be readily available, consume excess power, and/or otherwise waste resources of the computing system (e.g., host).

[0016] Hosts can include processors, a central processing unit (CPU), and/or be another device connected to the memory device. Such hosts include edge computing devices, computing devices within a mobile device, computing devices within vehicles (e.g., autonomous or semi-autonomous vehicles, etc.) and can use memory devices such as DRAM to execute applications and may benefit from the use of sensors. In some examples herein, memory devices including memory media such

as DRAM may include sensors on-board (e.g., embedded in circuitry of the memory device). For example, a vehicle can include a device (e.g., a computing device, a processor, a CPU, etc.) to execute instructions stored in a memory device coupled to the device within the vehicle. The sensors may be intermittently or consistently generating signals including sensor data to be written (e.g., stored) in the DRAM, however, end application access to the sensor data stored in DRAM is not always possible or efficient. As more devices (e.g., edge computing devices, vehicles, etc.) utilize DRAM, and storage capability of memory systems increase, the volume of sensor data generated by embedded sensors increases, and the effects of the inability to access sensor data stored in DRAM become more pronounced. These effects can be further exacerbated by the limitations of some approaches to read and interpret sensor data from external sensors such that the contents can be effective, especially as the amount of sensor data stored in memory systems and the speed at which sensor data retrieval is expected.

[0017] In contrast, embodiments herein are directed to enabling end application, user applications, and/or host applications, access to sensors embedded in memory devices such that the devices coupled to the memory device can conserve resources by refraining from the installation of external sensors thus saving power, unnecessary hardware, cost, etc. Hosts can take advantage of already existing embedded sensors included in memory devices coupled to the host. For example, in a context of mobile devices and/or partially or fully autonomous vehicles, decisions related to signals received from sensors may require end-user access such that actions can be taken quickly, efficiently, or otherwise interpreted. Enabling the use of sensors already existing on DRAM can increase the availability of such sensor data from sensors.

[0018] In another embodiment, sensors described herein can be located and/or exist near and/or on a scribe line in semiconductor memory devices. A scribe line can be located on a semiconductor wafer between dies such that the dies can be separated. In some examples, sensors are integrated on a semiconductor wafer near and/or on the scribe line during manufacturing. Enabling the use of these integrated (e.g., embedded) sensors post-manufacturing can increase the availability of data collected by the sensors without the need of extra and/or external hardware.

[0019] Embodiments herein describe another device coupled to a memory device that can be configured by a controller e.g., a processor, control circuitry, hardware, firmware, and/or software and a number of memory devices each including control circuitry. The controller can include a command decoder to output a value to another device included on the host. As used herein, the term “value” refers to an output from a sensor embedded in a memory device. Some examples of values can include a temperature value e.g., a temperature in Fahrenheit, Celsius, Kelvin, or any other unit used to measure thermodynamic temperature. The temperature value can be transmitted as an encoded 8-bit binary string. Another examples of a value can be a unit of time (e.g., microseconds (μ s), seconds, minutes, etc.), or a quantity of detection events. A detection event can be a quantity of motion events detected by a motion sensor embedded in a memory device and a motion value and/or a motion sensor value can be a quantity of motion events detected.

[0020] The output can be transmitted from the memory device using a sensor output. As used herein, the term “sensor output” refers to an output component that is configured to transfer sensor data (e.g., a value) from an embedded sensor to another device and/or a host. For example, a sensor output can be separate from a data output generally included on a bus. The sensor output can be used to transmit an indication about the signal that represents sensor data to another device and/or the host. The sensor output can be dedicated to the sensor such that it is configured to transmit the signal that represents sensor data and/or an indication to the other device.

[0021] In some examples, a sensor output described herein can be a value generated as an average of more than one embedded sensor. In some examples, the sensor output can be a weighted average of more than one embedded sensor where the weight is based on the location of the embedded sensor relative to the area where the sensor is generating a signal that represent sensor data. For example, more than one embedded temperature sensor can be located in various positions on a host

to monitor the temperature of the interior of the host. The temperature value generated by an embedded sensor located nearest to the interior sensor can be weighted higher than a different embedded sensor generating a signal representing temperature data from farther away from the interior of the host.

[0022] In another embodiment described herein, memory devices including memory media such as DRAM having an embedded sensor can be configured to transmit a signal that represents sensor data from the embedded sensor to another device coupled to the memory device using standard I/O lines included in a bus. For example, a controller (e.g., a command decoder) can receive a command (e.g., a multi-purpose register read command), and the memory device can be configured to map each embedded sensor output to a corresponding multi-purpose register. In this example, existing bandwidth of the memory device can be used to conserve the need for a dedicated sensor output.

[0023] In the following detailed description of the present disclosure, reference is made to the accompanying drawings that form a part hereof, and in which is shown by way of illustration how one or more embodiments of the disclosure can be practiced. These embodiments are described in sufficient detail to enable those of ordinary skill in the art to practice the embodiments of this disclosure, and it is to be understood that other embodiments can be utilized and that process, electrical, and structural changes can be made without departing from the scope of the present disclosure.

[0024] As used herein, designators such as “N,” “M,” “P”, etc., particularly with respect to reference numerals in the drawings, indicate that a number of the particular feature so designated can be included. It is also to be understood that the terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting. As used herein, the singular forms “a,” “an,” and “the” can include both singular and plural referents, unless the context clearly dictates otherwise. In addition, “a number of,” “at least one,” and “one or more” (e.g., a number of memory devices) can refer to one or more memory devices, whereas a “plurality of” is intended to refer to more than one of such things. Furthermore, the words “can” and “may” are used throughout this application in a permissive sense (i.e., having the potential to, being able to), not in a mandatory sense (i.e., must). The term “include,” and derivations thereof, means “including, but not limited to.” The terms “coupled,” and “coupling” mean to be directly or indirectly connected physically or for access to and movement (transmission) of commands and/or data, as appropriate to the context, and, unless stated otherwise, can include a wireless connection. The terms “data” and “data values” are used interchangeably herein and can have the same meaning, as appropriate to the context.

[0025] The figures herein follow a numbering convention in which the first digit or digits correspond to the figure number and the remaining digits identify an element or component in the figure. Similar elements or components between different figures can be identified by the use of similar digits. For example, **106** can reference element “**06**” in FIG. **1**, and a similar element can be referenced as **206** in FIG. **2**. A group or plurality of similar elements or components can generally be referred to herein with a single element number. For example, a plurality of reference elements **230-1**, . . . , **230-P** (e.g., **230-1** to **230-P**) can be referred to generally as **230**. As will be appreciated, elements shown in the various embodiments herein can be added, exchanged, and/or eliminated so as to provide a number of additional embodiments of the present disclosure. In addition, the proportion and/or the relative scale of the elements provided in the figures are intended to illustrate certain embodiments of the present disclosure and should not be taken in a limiting sense.

[0026] FIG. **1** is a functional block diagram of an apparatus in the form of a computing system **100** including memory device sensors in accordance with a number of embodiments of the present disclosure. As used herein, an “apparatus” can refer to, but is not limited to, any of a variety of structures or combinations of structures, such as a circuit or circuitry, a die or dice, a module or modules, another device or devices, or a system or systems, for example. The computing system

100 can include memory device **112**. The memory device **112** can include memory array **104-1** and memory array **104-M** which may be collectively referred to herein as the memory array **104**. The memory device **112** can include a controller **102** coupled to a multiplexer (MUX) **106**. The MUX **106** can be coupled to one or more sensors embedded in circuitry of the memory device **112**. For example, the MUX **106** can be coupled to a temperature sensor **130-1**, a timer **130-2** (e.g., for self-refresh control), an oscillator **130-3**, a counter **130-4**, and/or a motion sensor **130-P**, which may be collectively referred to as the sensor or the sensors **130**. A motion sensor can include integrated orientation sensors such as accelerometers and/or gyroscopes (e.g., microelectromechanical system gyroscope). Although specific types of sensors are mentioned herein, embodiments are not so limited and other sensors can be used (e.g., a pressure sensor and/or a random number generator). [0027] The memory device **112** can include volatile or non-volatile memory. For example, the memory media of the memory device **112** can be volatile memory media such as DRAM. DRAM can include a plurality of sensors which can be at least one of a temperature sensor, a motion sensor, an oscillator, a timer, or a combination thereof. The memory device **112** can be coupled to another device **120** via a bus **105**. The bus **105** can include a clock line (CLK) **108**, a command line **110** to transmit commands, an address line **114** to determine where commands should be sent, and a data input/output (data I/O) **116**. The other device **120** can be a CPU, a graphics processing unit (GPU), an application specific integrated circuit (ASIC), an edge computing device, etc. The device **120** can be a host (e.g., a processor) and/or included as part of a host (e.g., a computing device within another device).

[0028] For example, a host can be a host system (e.g., a computing system within a larger device) such as a computing device within a wireless connected device, a computing device within a personal laptop computer, a computing device within a vehicle, a CPU and/or processor within a desktop computer, a computing device within a digital camera, a computing device within a mobile telephone, an internet-of-things (IoT) enabled device, or a computing device within a memory card reader, a computing device within graphics processing unit (e.g., a video card), among various other types of hosts. As used herein an “IoT enabled device” can refer to devices embedded with electronics, software, sensors, actuators, and/or network connectivity which enable such devices to connect to a network and/or exchange data. Examples of IoT enabled devices include mobile phones, smart phones, tablets, phablets, computing devices, implantable devices, vehicles, home appliances, smart home devices, monitoring devices, wearable devices, devices enabling intelligent shopping systems, among other cyber-physical systems.

[0029] The host and/or the other device **120** can include a system motherboard and/or backplane and can include a number of memory access devices, e.g., a number of processing resources (e.g., one or more processors, microprocessors, or some other type of controlling circuitry). One of ordinary skill in the art will appreciate that “a processor” can intend one or more processors, such as a parallel processing system, a number of coprocessors, etc. The device **120** can be coupled to memory device **112** by the bus **105**.

[0030] The controller **102** can include a command decoder which can receive commands from the command line **110** of the bus **105**. The command to read data from a sensor **130** can be received by the controller **102**. The command can be a mode register type command from the other device **120** which can include information related to which sensor needs to output a signal representing sensor data using the sensor output **118**. The MUX can be a device that selects between analog and digital input signals received from selection pins and forward the signal to the sensor output **118**.

[0031] As mentioned, the computing system **100** includes a sensor **130** embedded in circuitry the memory device **112**. The sensor **130** can be configured to collect data related to the other device **120** connected to the memory device **112**. For example, the other device **120** can be a part of and/or coupled to a host. The sensor **130** can be embedded in the memory device **112** such as including memory such as DRAM and collect data corresponding to an environment of the other device **120**. Said differently, the embedded sensor **130** can be a temperature sensor **130-1** which can generate a

signal representing sensor data (e.g., a particular temperature value) in the form of a temperature of the host and/or an environment of the host.

[0032] The memory device **112** can be configured to transmit the sensor **130** signal that represents sensor data to the other device **120** using the sensor output **118**. For example, the sensor output **118** coupled can be coupled to one or more of the sensors **130** and to the other device **120** to transmit the signal that represents sensor data collected by the sensor **130** to the other device **120**. The sensor output can be dedicated to the sensor embedded in the memory device **112**. In this way, embedded sensors **130** can be accessible by end applications (e.g., users, hosts, etc.) to provide sensor generated data.

[0033] In some embodiments, the MUX **106** can receive signals that represent sensor data from multiple sensors **130** responsive to receiving a command from the controller **106**. For example, the controller **106** can receive a request from the other device **120** via the bus **105** to read sensor data from one or more sensors **130**. Responsive to receiving the request, the controller **102** can transmit a command to the MUX **106** to select and forward signals that represent sensor data from the temperature sensor **130-1** and the motion sensor **130-P**, where the motion sensor **130-P** and the temperature sensor **130-1** are both embedded in circuitry of the of the memory device **112**. The MUX **106** can transmit the signal that represents sensor data from the temperature sensor **130-1** and the motion sensor **130-P** to the other device **120** via the sensor output **118**.

[0034] FIG. **2** is a functional block diagram in the form of a computing system **200** including memory device sensors **230** in accordance with a number of embodiments of the present disclosure. The computing system **200** can include memory device **212** and be analogous to the memory device **112** of FIG. **1**. The memory device **212** can include memory array **204-1** and memory array **204-M** which may be collectively referred to herein as the memory array **204** and be analogous to the memory array **104** of FIG. **1**.

[0035] The memory device **212** can include controller **202** which can be analogous to controller **102** of FIG. **1**. The controller **202** can be coupled to registers **224-1**, **224-2**, **224-3**, and **224-N** and be collectively referred to herein as registers **224**. The registers **224** can each be coupled to one or more sensors embedded in circuitry of the memory device **212**. For example, the register **224-1** can be coupled to a temperature sensor **230-1**, the register **224-2** can be coupled to a motion sensor **230-P**, the register **224-3** and **224-N** can be coupled to a timer **230-2** via an oscillator **230-3** and/or a counter **230-4**, which may be collectively referred to as the sensor or the sensors **230**. Although specific types of sensors are mentioned herein, embodiments are not so limited and other sensors can be used (e.g., a pressure sensor and/or a random number generator).

[0036] The memory device **212** can be coupled to device **220** via a bus **205**. The bus **205** can include a clock line (CLK) **208**, a command line **210** to transmit commands, an address line **214** to determine where commands should be sent, and a data input/output (data I/O) **216**. The other device **220** can be a CPU, a graphics processing unit (GPU), an application specific integrated circuit (ASIC), an edge computing device, etc. The other device **220** can be included as part of a host (not illustrated as to not obscure examples of the disclosure).

[0037] The bus **205** can be coupled to an input/output logic (IO logic) **219**. The IO logic **219** can be a communication between the memory device **212** and the other device **220**. The I/O logic **219** can include hardware to perform input and output operations for the memory device **212**. The I/O logic **219** can receive information from the imbedded sensors **230** and transmit them to the other device **220** via the bus **205**.

[0038] FIG. **2** illustrates an example of a device **220** and memory device **212** coupled to the other device **220**. The memory device **212** includes a plurality of sensors **230** embedded in the memory device **212**, and a plurality of registers **224** each respectively coupled to one of the plurality of sensors **230**, the controller **202** (e.g., a command decode) to transmit commands to read one or more of the plurality of registers, and a data output (Data/IO) **216** coupled to the plurality of registers **224** (e.g., via the IO logic **219**) to transmit the sensor data from the plurality of registers

224 to the other device **220**.

[0039] The signal that represents sensor data transmitted from the sensors **230** to respective registers **224** can be sensor data of an operation of the sensor **230**. For example, the temperature sensor **230-1** can generate a temperature value and transmit a signal representing a temperature value to the register **224-1**, the embedded timer **230-2** can include an oscillator **230-3** and/or a counter **230-4** which can transmit a signal representing sensor data to register **224-3** and/or **224-N**, the embedded motion sensor **230-P** can transmit a signal that represents motion sensor data to the register **224-2**.

[0040] The embedded timer can include the oscillator **230-3** which can produce a periodic signal to transmit to the register **224-3** and/or to the counter **230-4**. The counter **230-4** can (independently or concurrently with the oscillator **230-3**) transmit a quantity of incidences of data collected by one or more of the sensors **230**. Said differently, the oscillator **230-3** can work with the counter **230-4** to periodically generate a signal which can report a quantity of signals generated from any of the sensors **230**. In contrast, the oscillator **230-3** and the counter **230-4** can operate independently to transmit respective signals that represent sensor data to respective registers.

[0041] In some embodiments, the controller **202** can configure the sensors **230** to generate signals that represent sensor data based on parameters. For example, the controller **202** can configure the sensors **230** to generate signals that represent sensor data to the respective registers **224** when the other device **220** is located in a particular environment. The controller **202** can generate a register read command **222** to read the sensor data stored in the respective registers and the I/O logic **219** can transmit the sensor data from the registers **224** to the other device **220**.

[0042] The environment can be a location of the other device **220** (e.g., a location of the host coupled to the other device). The controller **202** can receive an indication from the other device **220** related to the environment, and the controller **202** can configure the sensors **230** to generate signals that represent sensor data about the environment. For example, the controller **202** can receive an indication that the other device **220** (e.g., a host coupled to the other device **220**) is located in an environment. The controller **202** can configure the temperature sensor **230-1** to generate a temperature value (e.g., an encoded 8-bit binary string) and transmit the temperature value to the register **224-1**. Responsive to a register read command **222** transmitted from the controller **202**, the I/O logic **219** can transmit the signal that represents sensor data from the register **224-1** including the temperature value to the other device **220**. Said differently, the I/O logic **219** can transmit the values related to the respective operations of the plurality of sensors **230** to the other device **220**. Using these methods, the temperature value generated by the embedded temperature sensor **230-1** can be accessible to the other device **220** and/or the host/user.

[0043] In some embodiments, the embedded timer **230-2** (using an embedded oscillator **230-3** and/or an embedded counter **230-4**) can produce a timer output with a fixed period such as 1 μ s. In other embodiments, the timer output can be a flag, where the controller **202** is configured to generate a register read command **222** when a quantity of seconds have elapsed. The controller **202** can program the memory device **212** to generate sensor outputs to the respective registers **224** based on the quantity of seconds that have elapsed.

[0044] As mentioned, the motion sensor **230-P** can be embedded in the circuitry of the memory device **212** and can detect a change in motion within an environment. For example, the environment can be a location of the other device **220** (e.g., a location of the host coupled to the other device). The controller **202** can receive an indication from the other device **220** related to the environment and the controller **202** can configure the sensors **230** to generate signals that represent sensor data about the environment. For example, the controller **202** can receive an indication that the other device **220** (e.g., a host coupled to the other device **220**) is located in an environment. The controller **202** can configure the motion sensor **230-P** to generate a flag if motion is detected in the environment. Responsive to a register read command **222** transmitted from the controller **202**, the I/O logic **219** can transmit the sensor data from the register **224-2** including the motion sensor flag

to the other device **220**.

[0045] In some embodiments, multiple embedded sensors **230** can be used in combination to provide information to the host/user via the other device **220**. For example, the other device **220** can be coupled to an IoT device (e.g., a host) and the IoT device can initiate an operation responsive to transmission of the signals that represent sensor data (e.g., from one or more of the sensors **230**) from the plurality of registers **224** to the other device **220**. The IoT device can include the other device **220** and can make decisions based on the received sensor data. For example, the IoT device may be a mobile phone, and the other device **220** coupled to the mobile phone may receive a temperature value from the temperature sensor **230-1**, and the motion sensor **230-P** embedded in the memory device **212** of the mobile phone. Based on the receipt of the temperature value and the motion sensor value, the other device **220** may initiate the mobile phone to change an operation (e.g., switch from “on” to “off”). Using these methods, hosts/users can gain access to sensor data generated by the embedded sensors and avoid the need for external sensor installations.

[0046] FIG. **3** is flow diagram including an example of memory device sensors in accordance with a number of embodiments of the present disclosure. The flow diagram **301** of FIG. **3** describes a memory device (e.g., the memory device **112** of FIG. **1**) programming, via a controller (e.g., the controller **102** of FIG. **1**), sensors (e.g., the sensors **130** of FIG. **1**) embedded in circuitry of the memory device, to generate signals that represent sensor data about a host coupled to another device (e.g., the device **120** of FIG. **1**). At block **340** the memory device can configure, via the controller, the sensors embedded in the circuitry of the memory device to generate signals that represent sensor data to be externally accessible to another device. For example, the memory device can be configured to generate signals that represent sensor data from the embedded sensors. In some embodiments, the memory device can be configured to generate the signal that represents sensor data from the respective embedded sensors at predetermined intervals, when the other device is operating, and/or when the sensors detect a value that is greater than or less than a predetermined threshold.

[0047] At block **342**, one or more of the embedded sensors can collect data values. For example, a temperature sensor (e.g., the temperature sensor **130-1** of FIG. **1**) can collect a temperature (e.g., the data value) from an environment of which the other device and/or the memory device is located. The sensors embedded in the circuitry of the memory device may collect data intermittently, responsive to a command, and/or continuously, etc. In some embodiments, the data collected by the sensors can be transmitted as signals that represent sensor data (the data value) to the other device via a dedicated output (e.g., the sensor output **118** of FIG. **1**). The sensor output can be directly coupled to the sensors embedded in the memory device. In other embodiments, the sensor data can be transmitted to a register as a signal (e.g., the registers **224** of FIG. **2**) that is mapped to each embedded sensor.

[0048] For example, at block **344**, the memory device can transmit the signals that represent sensor data (e.g., the data value) to a corresponding register. At block **346** the sensor data (e.g., data value) from the embedded sensor can be stored in its corresponding register until it is transmitted to the other device. In some examples, the register can store the sensor data until it is retrieved by an I/O logic (e.g., the I/O logic **207** of FIG. **2**). At block **348**, the I/O logic can receive the sensor data (e.g., the data value) from the register. The I/O logic can receive the sensor data value responsive to a register read command (e.g., the register read command **222** of FIG. **2**) generated by the controller of the memory device. The register read command can be generated responsive to the other device being in an environment, changing an environment, and/or requested by a user and/or host.

[0049] At block **350** the signal that represents sensor data (e.g., the data value) can be transmitted to the other device. As mentioned herein, the other device can be coupled to, a part of, or the entirety of a host. The host can conserve resources, time, and power by utilizing sensors that are embedded in the memory device. The signals that represent sensor data collected from the sensors

embedded in the memory device can be analyzed by the other device. At block 352, the other device can analyze the signals that represent the sensor data (e.g., the data value) received from the embedded sensors. In some examples, the other device can cause the host coupled to the other device to change an operation based at least in part on the signals that represent sensor data received from the memory device.

[0050] FIG. 4 is a flow diagram representing an example method 489 for memory device sensors in accordance with a number of embodiments of the present disclosure. At block 490, the method 489 includes generating, based at least in part on a characteristic of a memory device (e.g., the memory device 112 of FIG. 1), a signal from a sensor (e.g., the sensors 130 of FIG. 1) embedded in the memory device. The sensor can be embedded in the circuitry of the memory device. In some examples, the memory device can be configured to request signals that represent sensor data at intervals using an embedded timer (e.g., the timer 130-2 of FIG. 1) which can include an embedded oscillator (e.g., the oscillator 130-3 of FIG. 1) and/or an embedded counter (e.g., the counter 130-4 of FIG. 1). The memory device can be configured to transmit a request (e.g., a command) to a controller (e.g., the controller 102 of FIG. 1) at predetermined intervals such that signals that represent sensor data from the embedded sensors is generated at continuous intervals. In other embodiments a command is generated responsive to or following a request received by the controller.

[0051] For example, in some embodiments, a command can be generated by the controller, responsive to a request from the other device for the signals that represent sensor data from the sensor embedded in the memory device. For example, the sensor may be a temperature sensor embedded in the memory device, the other device may be an IoT device and/or a portion of an IoT device. A component of the IoT device can request temperature sensor data from the embedded sensor. The IoT device can request the sensor data from the controller of the memory device, and, responsive to the request, the controller can generate the command for the sensor data of the temperature sensor. Embodiments are not limited to a temperature sensor embedded in the memory device.

[0052] In other embodiments, the command can be generated by the controller, responsive to a request from the other device for the sensor data from the sensor embedded in the memory device. For example, the sensor may be a motion sensor embedded in the memory device, and the other device may be an IoT device. A component of the IoT device can request motion sensor data from the embedded motion sensor. The IoT device can request the sensor data from the controller of the memory device, and responsive to the request, the controller can generate the command for the sensor data of the motion sensor.

[0053] In other embodiments, the command can be generated by the controller, responsive to a request from the other device for the sensor data from the sensor embedded in the memory device. For example, the sensor may be a timer embedded in the memory device, and the other device may be an IoT device. A component of the IoT device can request timer data from the embedded timer. The IoT device can request the timer data from the controller of the memory device, and responsive to the request, the controller can generate the command for the timer data of the timer. The memory device can transmit the timer data to the other device via a dedicated sensor output (e.g., the sensor output 118). The sensor output can be directly coupled to the embedded sensors. Using this method, the embedded sensor data can be directly accessible to the other device (and/or hosts or users).

[0054] At block 492, the method 489 includes transmitting the signal generated by the sensor from the memory device to another device coupled to the memory device. In the example above where the sensor is an embedded temperature sensor, the transmitted signal that represents sensor data can be a temperature value indicating an environment of the other device. For example, the temperature value can be a value indicating the temperature of the environment where the other device is physically located.

[0055] In the example above where the sensor is an embedded motion sensor, the transmitted signal

that represents sensor data can be a value indicating a motion in an environment of the other device. For example, the motion value can be a value indicating motion related to the environment of the other device (e.g., the other device is a vehicle and the motion is detected inside the vehicle). In the example above where the sensor is an embedded timer, the transmitted signal that represents sensor data can be a value indicating a time corresponding to another device. For example, the time value can be a value indicating a time corresponding to the other device (e.g., a timestamp). In some examples, various embedded sensors can generate signals that represent sensor data to be transmitted together. For example, the time value can be paired with a temperature value and/or a motion sensor value.

[0056] In another embodiment, the other device can transmit a command to the controller for sensor data from the embedded sensors responsive to a change of environment of the other device. In a different embodiment, the memory device can be configured to detect changes in the environment of the other device and prompt the other device to transmit a request to the controller and/or automatically transmit a command to the embedded sensors. In other words, receiving the command from the controller to transmit the signal that represents sensor data from the sensor can be responsive to the controller detecting a change in an environment of the other device.

[0057] For example, the memory device can be coupled to another device in the form of a vehicle. The vehicle may move from a garage location to an outdoor location. The controller of the memory device can be configured to detect this change in environment and transmit a signal that represents sensor data from embedded sensors responsive to the change in environment. The change in environment may change a frequency at which the sensor data is generated, and/or a configured threshold of the sensor data.

[0058] For example, embodiments herein can include receiving, by the other device, the data from the sensor embedded in the memory device and initiating an indication that a value included in the data is greater than or less than a predetermined threshold. In some embodiments, the other device may be an IoT device that is configured to take an action (e.g., a preventative measure, initiate an alarm, etc.) responsive to a value generated by an embedded sensor. For example, the other device can receive a temperature value from an embedded sensor via the sensor output and take an action if the temperature value is greater than or less than (e.g., above or below) a predetermined threshold temperature.

[0059] FIG. 5 is a flow diagram representing another example method **593** for memory device sensors in accordance with a number of embodiments of the present disclosure. At block **594**, the method **593** includes reading sensor data included in a signal from one or more of a plurality of registers (e.g., the registers **224** of FIG. 2) each respectively coupled to a plurality of sensors (e.g., the sensors **230** of FIG. 2) embedded in a memory device (e.g., the memory device **112** of FIG. 1), wherein the sensor data is generated by one or more of the plurality of sensors. In some examples a command (e.g., the register read command **222**) to read sensor data from one or more of the plurality of registers can be transmitted by a controller (e.g., the controller **102** of FIG. 1). Responsive to the transmitted command, the signal that represents sensor data can be transmitted via a bus (e.g., the bus **205** of FIG. 2) to another device.

[0060] For example, at block **596**, the method **593** can include transmitting the sensor data, via a data output (e.g., the data output **216** of FIG. 2) coupled to the plurality of registers, to another device (e.g., the device **220** of FIG. 2) coupled to the memory device. In some embodiments described herein, multiples sensors can be used to transmit a signal that represents sensor data to another device such that it is accessible for a host and/or a user of the other device.

[0061] For example, the method **593** can include configuring the controller to transmit a signal that represents sensor data from a first sensor at a predetermined interval initiated by a second sensor, where the first sensor is an embedded temperature sensor (e.g., the temperature sensor **230-1** of FIG. 2) and the second sensor is an embedded timer (e.g., the timer **230-2**) and the signal that represents sensor data transmitted at the predetermined interval is a temperature value. The timer

can include an oscillator (e.g., the oscillator **230-3** of FIG. 2) and/or a counter (e.g., the counter **230-4** of FIG. 2) to transmit the signal that represents sensor data at the predetermined intervals. The sensor data from the one or more sensors can be written, respectively, to one or more registers. [0062] For example, in the above example, where the transmitted signal that represents sensor data is from an embedded temperature sensor and a timer, the method **593** can include writing the temperature value to a first register (e.g., the register **224-1** of FIG. 2) of the plurality of registers at each of the predetermined intervals and writing a time indicator, from the embedded timer, corresponding to each temperature value to a second register (e.g., register **224-3** and register **224-N** of FIG. 2). Such that the embedded sensor data is accessible to the other device (e.g., and/or hosts/users of the other device) the memory device can transmit the signal that represents sensor data from the one or more registers to the other device.

[0063] The method **593** can include receiving, by the other device, the temperature value from the first register corresponding to the embedded temperature sensor, and receiving, by the other device, the time value from the second register corresponding to the embedded temperature sensor. Embodiments are not so limited to an embedded temperature sensor.

[0064] The method **593** can include configuring the controller to transmit a signal that represents sensor data from a first sensor at predetermined intervals initiated by a second sensor, wherein the first sensor is an embedded motion sensor (e.g., the motion sensor **230-P**) and the second sensor is an embedded timer; and the signal that represents sensor data transmitted at the predetermined intervals is a motion value. The motion value is an indication of motion in the other device. The sensor data from the one or more sensors can be written, respectively, to one or more registers.

[0065] In the above example, where the transmitted signal that represents sensor data is from an embedded motion sensor, the method **593** can include writing the motion value to a first register (e.g., the register **224-2** of FIG. 2) of the plurality of registers at each of the predetermined intervals, and writing a time value, from the embedded timer, corresponding to each motion value to a second register (e.g., register **224-3** and register **224-N** of FIG. 2). Such that the embedded sensor data is accessible to the other device (e.g., and/or hosts/users of the other device) the memory device can transmit the sensor data from the one or more registers to the other device.

[0066] The method **593** can include receiving, by the other device, the motion value from the first register corresponding to the embedded motion sensor, and receiving, by the other device, the time value from the second register corresponding to the embedded temperature sensor.

[0067] Although specific embodiments have been illustrated and described herein, those of ordinary skill in the art will appreciate that an arrangement calculated to achieve the same results can be substituted for the specific embodiments shown. This disclosure is intended to cover adaptations or variations of one or more embodiments of the present disclosure. It is to be understood that the above description has been made in an illustrative fashion, and not a restrictive one. Combination of the above embodiments, and other embodiments not specifically described herein will be apparent to those of skill in the art upon reviewing the above description. The scope of the one or more embodiments of the present disclosure includes other applications in which the above structures and processes are used. Therefore, the scope of one or more embodiments of the present disclosure should be determined with reference to the appended claims, along with the full range of equivalents to which such claims are entitled.

[0068] In the foregoing Detailed Description, some features are grouped together in a single embodiment for the purpose of streamlining the disclosure. This method of disclosure is not to be interpreted as reflecting an intention that the disclosed embodiments of the present disclosure have to use more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive subject matter lies in less than all features of a single disclosed embodiment. Thus, the following claims are hereby incorporated into the Detailed Description, with each claim standing on its own as a separate embodiment.

Claims

1. A method, comprising: generating, based at least in part on a characteristic of a memory device, sensor data by a sensor embedded in the memory device, wherein the memory device includes a memory array and the sensor; and transmitting a signal representing the sensor data generated by the sensor from the memory device to another device coupled to the memory device.
2. The method of claim 1, further comprising receiving, by a controller coupled to the memory device, a request from the another device for the signal from the sensor embedded in the memory device.
3. The method of claim 1, wherein the sensor comprises a temperature sensor and further comprising transmitting, from the temperature sensor, the signal indicating a temperature of an environment of the another device.
4. The method of claim 1, wherein the sensor comprises a motion sensor and further comprising transmitting, from the motion sensor, the signal indicating a motion in an environment of the another device.
5. The method of claim 1, wherein the sensor comprises a timer and further comprising transmitting, from the timer, the signal indicating a time corresponding to the another device.
6. The method of claim 1, further including transmitting the signal representing the sensor data generated by the sensor from the memory device to the another device via a sensor output coupled to the sensor and the another device.
7. The method of claim 1, further including transmitting the signal representing the sensor data generated by the sensor from the memory device to the another device via a data output.
8. The method of claim 1, further comprising generating a command from a controller coupled to the memory device to transmit the signal from the sensor responsive to the controller detecting a change in an environment of the another device.
9. The method of claim 1, further comprising: receiving, by the another device, the signal from the sensor embedded in the memory device; and initiating, by the another device, an indication that a value included in the signal is greater than or equal to a threshold.
10. A memory device, comprising: a sensor embedded in the memory device, wherein the memory device includes a memory array and the sensor and wherein the sensor is configured to generate, based at least in part on a characteristic of the memory device, a signal from the sensor embedded in the memory device; and a sensor output coupled to the sensor and to another device to transmit data represent signal generated by the sensor to the another device.
11. The memory device of claim 10, wherein the sensor embedded in the memory device includes volatile memory media, and collects data corresponding to an environment of the another device.
12. The memory device of claim 10, wherein the sensor output is dedicated to the sensor embedded in the memory device.
13. The memory device of claim 10, wherein the sensor comprises a temperature sensor and wherein the sensor output is configured to transfer the signal indicating a temperature of an environment of the another device from the sensor to the another device.
14. The memory device of claim 10, wherein the sensor comprises a motion sensor and wherein the sensor output is configured to transfer the signal indicating a motion in an environment of the another device from the sensor to the another device.
15. The memory device of claim 10, wherein the sensor comprises a timer and wherein the sensor output is configured to transfer the signal indicating a time corresponding to the another device from the sensor to the another device.
16. A system, comprising: a device; and a memory device coupled to the device, the memory device comprising: a memory array; a number of sensors embedded in the memory device; a number of registers each respectively coupled to one of the number of sensors to collect data from

one or more of the plurality of sensors; a controller to transmit a command to read one or more of the plurality of registers; and a data output coupled to the number of registers to transmit the data from the number of registers to the device.

17. The system of claim 16, wherein the memory device includes Dynamic Random Access Memory (DRA M) and the plurality of sensors are at least one of a temperature sensor, a motion sensor, an oscillator, a timer, or a combination thereof.

18. The system of claim 16, wherein the data collected from the one or more plurality of sensors are values related to respective operations of respective sensors of the plurality of sensors.

19. The system of claim 18, further comprising an input/output logic to transmit the values related to the respective operations of respective sensors of the plurality of sensors to the device.

20. The system of claim 16, wherein: the device is coupled to an Internet of Things (IoT) device; and the IoT device initiates an operation responsive to the transmission of the data from the plurality of registers to the device.
