

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250248831

Kind Code

A1

Publication Date

August 07, 2025

Inventor(s)

Parsons; Dennis et al.

---

### **DURABLE STENT GRAFT WITH TAPERED STRUTS AND STABLE DELIVERY METHODS AND DEVICES**

---

#### **Abstract**

Some embodiments relate in part to endovascular prostheses and methods of deploying same. Embodiments may be directed more specifically to stent grafts and methods of making and deploying same within the body of a patient. Stent embodiments may include tapered struts for an even distribution of strain. Stent embodiments may also include portions which are enlarged in a circumferential direction which may be configured to stabilize the stent in a constrained state.

---

**Inventors:** Parsons; Dennis (Santa Rosa, CA), Staudenmayer; Christopher L. (Santa Rosa, CA), Watson; James R. (Santa Rosa, CA)

**Applicant:** TriVascular, Inc. (Santa Rosa, CA)

**Family ID:** 49292934

**Appl. No.:** 19/172387

**Filed:** April 07, 2025

#### **Related U.S. Application Data**

parent US continuation 17465751 20210902 parent-grant-document US 12268621 child US 19172387

parent US continuation 14615337 20150205 parent-grant-document US 11109989 child US 17465751

parent US continuation 13799207 20130313 parent-grant-document US 8992595 child US 14615337

us-provisional-application US 61620362 20120404

---

#### **Publication Classification**

**Int. Cl.: A61F2/90 (20130101); A61F2/06 (20130101); A61F2/07 (20130101); A61F2/82 (20130101); A61F2/848 (20130101); A61F2/88 (20060101); A61F2/89 (20130101); A61F2/91 (20130101); A61F2/95 (20130101); A61F2/966 (20130101)**

**U.S. Cl.:**

**CPC A61F2/90 (20130101); A61F2/07 (20130101); A61F2/82 (20130101); A61F2/848 (20130101); A61F2/91 (20130101); A61F2002/065 (20130101); A61F2002/067 (20130101); A61F2002/072 (20130101); A61F2002/075 (20130101); A61F2002/825 (20130101); A61F2/88 (20130101); A61F2/89 (20130101); A61F2/95 (20130101); A61F2002/9665 (20130101); A61F2210/0014 (20130101); A61F2220/0016 (20130101); A61F2220/005 (20130101); A61F2220/0058 (20130101); A61F2220/0075 (20130101); A61F2230/0006 (20130101); A61F2230/0008 (20130101); A61F2230/0013 (20130101); A61F2230/0019 (20130101); A61F2230/0026 (20130101); A61F2230/0078 (20130101); A61F2250/0003 (20130101); A61F2250/0036 (20130101); Y10T29/49863 (20150115)**

---

## **Background/Summary**

**RELATED APPLICATIONS [0001]** This application is a continuation of U.S. patent application Ser. No. 17/465,751, filed Sep. 2, 2021, which is a continuation of U.S. patent application Ser. No. 14/615,337, filed Feb. 5, 2015, which is a continuation of U.S. patent application Ser. No. 13/799,207, filed Mar. 13, 2013, by D. Parsons et al., titled Durable Stent Graft with Tapered Struts and Stable Delivery Methods and Devices, which claims priority under 35 U.S.C. 119(e) from U.S. Provisional Patent Application No. 61/620,362, filed Apr. 4, 2012, by D. Parsons et al., titled Durable Stent Graft with Tapered Struts and Stable Delivery Methods and Devices, each of which is incorporated by reference herein in its entirety.

## **FIELD OF THE INVENTION**

**[0002]** Some embodiments relate in part to endovascular prostheses and methods of deploying same. Embodiments may be directed more specifically to stent grafts and methods of making and deploying same within the body of a patient.

## **BACKGROUND**

**[0003]** An aneurysm is a medical condition indicated generally by an expansion and weakening of the wall of an artery of a patient. Aneurysms can develop at various sites within a patient's body. Thoracic aortic aneurysms (TAAs) or abdominal aortic aneurysms (AAAs) are manifested by an expansion and weakening of the aorta which is a serious and life threatening condition for which intervention is generally indicated. Existing methods of treating aneurysms include invasive surgical procedures with graft replacement of the affected vessel or body lumen or reinforcement of the vessel with a graft.

**[0004]** Surgical procedures to treat aortic aneurysms can have relatively high morbidity and mortality rates due to the risk factors inherent to surgical repair of this disease as well as long hospital stays and painful recoveries. This is especially true for surgical repair of TAAs, which is generally regarded as involving higher risk and more difficulty when compared to surgical repair of AAAs. An example of a surgical procedure involving repair of a AAA is described in a book titled Surgical Treatment of Aortic Aneurysms by Denton A. Cooley, M.D., published in 1986 by W. B. Saunders Company.

**[0005]** Due to the inherent risks and complexities of surgical repair of aortic aneurysms, endovascular repair has become a widely-used alternative therapy, most notably in treating AAAs. Early work in this field is exemplified by Lawrence, Jr. et al. in "Percutaneous Endovascular Graft:

Experimental Evaluation”, Radiology (May 1987) and by Mirich et al. in “Percutaneously Placed Endovascular Grafts for Aortic Aneurysms: Feasibility Study,” Radiology (March 1989).

Commercially available endoprostheses for the endovascular treatment of AAAs include the AneuRx® stent graft manufactured by Medtronic, Inc. of Minneapolis, MN, the Zenith® stent graft system sold by Cook, Inc. of Bloomington, IN, the PowerLink® stent-graft system manufactured by Endologix, Inc. of Irvine, CA, and the Excluder® stent graft system manufactured by W.L. Gore & Associates, Inc. of Newark, DE. A commercially available stent graft for the treatment of TAAs is the TAG™ system manufactured by W.L. Gore & Associates, Inc.

[0006] When deploying devices by catheter or other suitable instrument, it is advantageous to have a flexible and low profile stent graft and delivery system for passage through the various guiding catheters as well as the patient's sometimes tortuous anatomy. Many of the existing endovascular devices and methods for treatment of aneurysms, while representing significant advancement over previous devices and methods, use systems having relatively large transverse profiles, often up to 24 French. Also, such existing systems have greater than desired lateral stiffness, which can complicate the delivery process. In addition, the sizing of stent grafts may be important to achieve a favorable clinical result. In order to properly size a stent graft, the treating facility typically must maintain a large and expensive inventory of stent grafts in order to accommodate the varied sizes of patient vessels due to varied patient sizes and vessel morphologies. Alternatively, intervention may be delayed while awaiting custom size stent grafts to be manufactured and sent to the treating facility. As such, minimally invasive endovascular treatment of aneurysms is not available for many patients that would benefit from such a procedure and can be more difficult to carry out for those patients for whom the procedure is indicated.

[0007] What have been needed are stent graft systems and methods that are adaptable to a wide range of patient anatomies and that can be safely and reliably deployed using a flexible low profile system.

## SUMMARY

[0008] Some embodiments are directed to a self-expanding cylindrical stent which has a constrained state and a relaxed expanded state. The stent may also include a longitudinal axis, a proximal end, a distal end, and a plurality of resilient struts configured to exert an outward radial force in the constrained state. At least one of the resilient struts may include a longitudinal section which is enlarged in a circumferential orientation relative to a longitudinal axis of the stent and configured to stabilize the at least one strut relative to the position of adjacent struts while the stent is in a constrained state. At least some of the enlarged longitudinal sections may be in axial alignment with each other. In some cases, the enlarged longitudinal sections of the struts may be enlarged in one transverse dimension of the struts. In some cases, the enlarged longitudinal sections may be enlarged along a circumferential direction about the longitudinal axis of the stent and the struts may have a substantially constant thickness in a radial direction relative to the longitudinal axis of the stent. The enlarged longitudinal section may have an enlarged transverse dimension that is about 1.5 times to about 3 times the nominal transverse dimension of the strut in a direction of the enlargement for some embodiments.

[0009] Certain embodiments are directed to an endovascular stent graft, having a main body portion including at least one tubular portion made from at least one layer of flexible material and a self-expanding cylindrical stent which has a constrained state and a relaxed expanded state. The stent may also include a longitudinal axis, a proximal end, a distal end, a plurality of resilient struts configured to exert an outward radial force in the constrained state. At least one of the resilient struts may include a longitudinal section which is enlarged in a circumferential orientation relative to a longitudinal axis of the stent and configured to stabilize the at least one strut relative to the position of adjacent struts while the stent is in a constrained state. All resilient struts may include a longitudinal section which is enlarged in a circumferential orientation relative to a longitudinal axis of the stent and configured to stabilize at least one strut relative to the position of adjacent struts

while the stent is in a constrained state in some embodiments. In some cases, at least some of the enlarged longitudinal sections may be in axial alignment with each other. In some instances, the enlarged longitudinal sections of the struts may be enlarged in one transverse dimension of the struts. In some instances, the enlarged longitudinal sections may be enlarged along a circumferential direction about the longitudinal axis of the stent and the struts may have a substantially constant thickness in a radial direction relative to the longitudinal axis of the stent. The enlarged longitudinal section may have an enlarged transverse dimension that is about 1.5 times to about 3 times the nominal transverse dimension of the strut in a direction of the enlargement in some embodiments.

[0010] Some embodiments are directed to a method of loading a delivery catheter system with an endovascular stent graft. The endovascular stent graft may have a main body portion including at least one tubular portion made from at least one layer of flexible material, and a self-expanding cylindrical stent which has a constrained state and a relaxed expanded state. The self-expanding cylindrical stent may include a longitudinal axis, a proximal end, a distal end, a plurality of resilient struts configured to exert an outward radial force in the constrained state. At least one of the resilient struts may include a longitudinal section which is enlarged in a circumferential orientation relative to a longitudinal axis of the stent and configured to separate and stabilize the at least one strut relative to the position of adjacent struts while the stent is in a constrained state. In some cases, the self-expanding cylindrical stent of the stent graft may be constrained about a bushing of the delivery system such that the enlarged longitudinal section of the at least one resilient strut stabilizes the position of the at least one strut relative to the position of adjacent struts in the constrained state. In some instances, the stent may be releasably secured in the constrained stabilized state.

[0011] Some embodiments of an endovascular stent graft may include a main body portion having at least one tubular portion made from at least one layer of flexible material and a self-expanding anchor member. The self-expanding anchor member may include a constrained state, a relaxed expanded state, a proximal stent portion, and a distal stent portion. In some cases, the endovascular stent graft may be configured such that a proximal end of the distal stent portion is secured to a distal end of the proximal stent portion and a distal end of the distal stent portion is secured to a proximal end of the main body portion. The endovascular stent graft may also be configured such that the axial length of the self-expanding anchor member as a whole divided by the axial length of the proximal stent portion is a ratio of about 1.75 to about 2.0.

[0012] Some embodiments of a self-expanding anchor member include a constrained state, a relaxed expanded state, a proximal stent portion, and a distal stent portion. In some cases, the anchor member may be configured such that a proximal end of the distal stent portion is secured to a distal end of the proximal stent portion and the axial length of the self-expanding anchor member as a whole divided by the axial length of the proximal stent portion is a ratio of about 1.75 to about 2.0.

[0013] Some embodiments of an endovascular stent graft may include a main body portion including at least one tubular portion made from at least one layer of flexible material and a self-expanding cylindrical stent which has a constrained state and a relaxed expanded state. The self-expanding cylindrical stent may include a longitudinal axis, a proximal end, a distal end, and a plurality of resilient struts configured to exert an outward radial force in the constrained state. At least one of the resilient struts may have a longitudinal section which is enlarged in a circumferential orientation relative to a longitudinal axis of the stent and be configured to stabilize the at least one strut relative to the position of adjacent struts while the stent is in a constrained state. For such an embodiment, all of the resilient struts of the stent may include a longitudinal section which is enlarged in a circumferential orientation relative to a longitudinal axis of the stent and be configured to stabilize the at least one strut relative to the position of adjacent struts while the stent is in a constrained state. In some cases at least some of the enlarged longitudinal sections

may be in axial alignment with each other. In some instances, the enlarged longitudinal sections of the struts may be enlarged in one transverse dimension of the struts or the enlarged longitudinal sections may be enlarged along a circumferential direction about the longitudinal axis of the stent and the struts may have a substantially constant thickness in a radial direction relative to the longitudinal axis of the stent. For some embodiments, the enlarged longitudinal section may have an enlarged transverse dimension that is about 1.5 times to about 3 times the nominal transverse dimension of the strut in a direction of the enlargement. In some cases, the enlarged longitudinal section includes an undulating configuration of the nominal strut or an oval enlargement of the nominal strut. In some instances, each strut of the stent may include an enlarged longitudinal section with only one enlarged longitudinal section or an enlarged longitudinal section with a plurality of enlarged longitudinal sections. For some embodiments, the struts having enlarged longitudinal sections may be disposed in a substantially longitudinal orientation between the proximal end and distal end of the stent when the stent is in the constrained state. In some cases, the struts may be disposed in an undulating pattern. In some instances, the self-expanding cylindrical stent of the stent graft may include a superelastic alloy such as NiTi alloy.

[0014] Certain embodiments are described further in the following description, examples, claims and drawings.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0015] FIG. 1 illustrates an elevation view of an embodiment of an endoluminal prosthesis in the form of a stent graft for treatment of a patient's vessel.

[0016] FIG. 1A is an enlarged view of the encircled portion 1A of FIG. 1 including a proximal self-expanding stent member and proximal connector ring of the stent graft embodiment of FIG. 1.

[0017] FIG. 2 illustrates the stent graft embodiment of FIG. 1 in a constrained configuration disposed on a distal section of a delivery catheter within a lumen of a patient's vessel.

[0018] FIG. 3 shows an enlarged view of the encircled portion 3 of the stent graft of FIG. 2 including the proximal self-expanding stent member in a constrained configuration but without the constraining releasable belts for clarity of illustration.

[0019] FIG. 3A is a transverse cross sectional view of the proximal self-expanding stent member and delivery catheter system of FIG. 3 taken along lines 3A-3A of FIG. 3.

[0020] FIG. 4 illustrates the stent graft of FIG. 2 in a deployed unconstrained state.

[0021] FIG. 5 is a schematic view of an embodiment of a section of a stent that illustrates features of struts of the stent.

[0022] FIGS. 6A and 6AA illustrate paired transverse cross section views of a strut embodiment of FIG. 5 taken along the lines 6A-6A and 6AA-6AA of FIG. 5.

[0023] FIGS. 6B and 6BB illustrate paired transverse cross section views of another strut embodiment of FIG. 5.

[0024] FIGS. 6C and 6CC illustrate paired transverse cross section views of another strut embodiment of FIG. 5.

[0025] FIGS. 6D and 6DD illustrate paired transverse cross section views of another strut embodiment of FIG. 5.

[0026] FIGS. 6E and 6EE illustrate paired transverse cross section views of another strut embodiment of FIG. 5.

[0027] FIG. 7A illustrates a strut embodiment in longitudinal section taken along lines 7A-7A of the stent embodiment in FIG. 5.

[0028] FIG. 7B illustrates another strut embodiment in longitudinal section.

[0029] FIG. 7C illustrates another strut embodiment in longitudinal section.

[0030] FIG. **8** illustrates a portion of an embodiment of a stent including struts having a stepped taper configuration.

[0031] FIG. **9** illustrates a portion of an embodiment of a stent including struts having a continuous taper, barbs, and tuck pads with tuck slots.

[0032] FIG. **10A** illustrates a portion of a cylindrical stent embodiment in a constrained configuration including struts having coaxial enlarged portion embodiments.

[0033] FIG. **10B** illustrates a portion of a cylindrical stent embodiment in a constrained configuration including struts having coaxial enlarged portion embodiments.

[0034] FIG. **10C** illustrates a portion of a cylindrical stent embodiment in a constrained configuration including struts having undulating deflected portions configured to physically separate adjacent struts in a circumferential direction.

[0035] FIG. **11** illustrates a portion of a cylindrical stent embodiment in a constrained configuration shown flattened including struts having coaxial enlarged portion embodiments and undulating deflected portions.

[0036] FIG. **12** is a transverse cross section view of the stent portion of FIG. **11** taken along lines **12-12** of FIG. **11**.

[0037] FIG. **13** is an elevation view of a bifurcated stent graft embodiment.

[0038] FIG. **14** illustrates an embodiment of the stent graft of FIG. **13** partially deployed within a patient's aorta.

[0039] FIG. **15** is a perspective view of a proximal anchor member embodiment.

[0040] FIG. **16** is an elevation view of a cut away portion of the proximal anchor member embodiment of FIG. **15**.

[0041] FIG. **17** is an elevation view of a cut away portion of the proximal anchor member embodiment of FIG. **16**.

[0042] FIG. **18** shows a distal portion of the cut away portion of the proximal anchor member of FIG. **16**.

[0043] FIG. **19** is an enlarged view of the encircled portion **19-19** in FIG. **18**.

[0044] The drawings illustrate embodiments of the invention and are not limiting. For clarity and ease of illustration, the drawings are not made to scale and, in some instances, various aspects may be shown exaggerated or enlarged to facilitate an understanding of particular embodiments.

#### DETAILED DESCRIPTION

[0045] Embodiments of the invention are directed generally to methods and devices for treatment of fluid flow vessels with the body of a patient. Treatment of blood vessels may be specifically indicated for some embodiments, and, more specifically, treatment of aneurysms, such as abdominal aortic aneurysms. Devices for such treatment modalities may include stents, grafts and stent graft assemblies that include at least one stent secured to a graft member.

[0046] For some embodiments, the modular graft assembly may be bifurcated for treatment of an abdominal aortic aneurysm. Such a graft assembly embodiment may include a bifurcated main body member, an ipsilateral graft extension and contralateral graft extension. The main body may have a wall portion that binds a main fluid flow lumen disposed therein. An ipsilateral leg of the main body may have an ipsilateral port and an ipsilateral fluid flow lumen that is in fluid communication with the main fluid flow lumen and the ipsilateral port. A contralateral leg of the main body may have a contralateral port and a contralateral fluid flow lumen that is in fluid communication with the main fluid flow lumen and the contralateral port. The main body, ipsilateral leg, and contralateral leg may form a bifurcated “Y” shaped configuration.

[0047] For some bifurcated embodiments, the main fluid flow lumen of the main body generally may have a larger transverse dimension and area than a transverse dimension and area of either of the fluid flow lumens of the ipsilateral leg or contralateral leg. A proximal anchor member may be disposed at a proximal end of the main body. The proximal anchor member may include a proximal self-expanding stent that is formed from an elongate element having a generally serpentine shape

with four crowns or apices at either end. Each proximal apex or crown of the proximal stent may be coupled to alternating distal crowns or apices of an eight crown distal self-expanding stent. The distal self-expanding stent may be formed from an elongate element having a generally serpentine shape. A distal end of the distal stent may be mechanically coupled to a connector ring which may be embedded in graft material of the proximal end of the main body, or directly coupled to perforations in the proximal edge region of the main body. Embodiments of the connector ring may be generally circular in shape having regular undulations about the circumference that may be substantially sinusoidal in shape. The proximal stent may include outwardly extending barbs, that may be integrally formed with the struts of the stent for some embodiments, having sharp tissue penetrating tips that are configured to penetrate into tissue of an inside surface of a lumen within which the proximal stent is deployed in an expanded state. Although the proximal anchor member may include self-expanding stents, similar stents may be used that are configured to be inelastically expanded with outward radial pressure as might be generated by the expansion of an expandable balloon from within either or both stents. The connector ring coupled to the proximal stent may also be inelastically expandable.

[0048] With regard to graft embodiments discussed herein, such as graft assembly, and components thereof, as well as graft extensions and, the term “proximal” refers to a location towards a patient's heart and the term “distal” refers to a location away from the patient's heart. With regard to delivery system catheters and components thereof discussed herein, the term “distal” refers to a location that is disposed away from an operator who is using the catheter and the term “proximal” refers to a location towards the operator.

[0049] FIGS. 1-4 illustrate an embodiment of a stent graft assembly **150** which may include a main graft member or main body portion **152** which is not bifurcated. The main body **152** may be tubular in shape and have a wall portion **153** that bounds a main fluid flow lumen **155** disposed therein. The main body **152** may include a proximal end **154**, a distal end **156** and an inflatable portion **158**. The main body **152** of the stent graft assembly **150** may include at least one flexible layer of material such as PTFE, polymer meshes, composites of same or the like. A proximal anchor member or stent may be disposed at the proximal end **154** of the main body **152**. The proximal anchor member embodiment shown in FIG. 1 includes a single proximal self-expanding stent member **160** disposed about a proximal end **154** of the main body **152**. In some embodiments, the proximal self-expanding stent member **160** may be formed from an elongate element having a generally serpentine shape with eight crowns or apices at either end. A distal end **162** of the proximal self-expanding stent member **160** may be mechanically coupled to a proximal connector ring **164** which may be embedded in graft material generally about the proximal end **154** of the main body **152**, or directly coupled to perforations in the proximal end **154** region of the main body **152**.

[0050] A distal self-expanding stent member **170** may be disposed at the distal end **156** of the main body **152** and may be configured to engage an interior luminal surface **132** within the patient's vasculature **130**. The distal self-expanding stent member **170** shown in FIG. 1 includes a single self-expanding stent member disposed along the distal end **156** of the main body **152** of the stent graft assembly **152**. The distal self-expanding stent member **170** may be formed from a resilient elongate element having a generally serpentine shape with eight crowns or apices at either end. A proximal end **172** of the distal self-expanding stent member **170** may be mechanically coupled to a distal connector ring **174** which may be embedded in graft material generally about the distal end **156** of the main body **152**, or directly coupled to perforations in the distal end **156** region of the main body **152**.

[0051] Embodiments of either the proximal connector ring **164** or distal connector ring **174** may be generally circular or cylindrical in shape with regular undulations about the circumference that may be substantially sinusoidal or zig-zag in shape. Some embodiments of either the proximal or distal self-expanding stent members **160**, **170** may include outwardly extending barbs **165** (see FIG. 1A).

Such barbs **165** may be integrally formed with the struts **168** of either the proximal self-expanding stent member **160** or distal self-expanding member **170**. Furthermore, the barbs **165** may have sharp tissue penetrating tips that may be configured to penetrate into tissue of an inside surface of a lumen within which either the proximal self-expanding stent member **160** or distal self-expanding member **170** may be deployed into an expanded state.

[0052] Although the proximal and distal self-expanding stent members **160** and **170** of the stent graft **150** has generally been described as including self-expanding stents, the proximal and distal self-expanding stent members **160** and **170** may also include similar stents that are configured to be inelastically expanded with outward radial pressure as might be generated by the expansion of an expandable balloon from within either the proximal self-expanding stent member **160** or distal self-expanding stent member **170**. Additionally, at least one of the proximal self-expanding stent member **160** and distal self-expanding stent member **170** may be made from or include a superelastic alloy, such as NiTi alloy.

[0053] The stent graft **150** may further include an optional inflation conduit (not shown) which may serve as a fill manifold for inflation of the inflatable portion **158** of the stent graft **150**. The inflation conduit may include a distal end with an inflation port in fluid communication with an exterior portion of the main body **152** and extending from the distal end **156** into an interior volume of the inflatable portion **158** of the stent graft **150**.

[0054] Some embodiments of the stent graft **150** may include radiopaque markers **116** that may be used to facilitate alignment of the stent graft **150**. A radiopaque marker **116** configuration and imaging system may be used for alignment during positioning of the stent graft **150** in a patient. FIG. **1A** illustrates an enlarged view of a portion of the stent graft **150** with portions of the stent graft **150** not shown for clarity of illustration. The stent graft **150** embodiment shown in FIG. **1A** illustrates the proximal end **154** of the main body **152**, the proximal self-expanding stent member **160**, and a plurality of radiopaque markers **116** disposed about a circumference of a distal end **162** of the proximal self-expanding stent member **160**. Furthermore, the plurality of radiopaque markers **116** may include helically wound wire members which may be disposed about connector members **216**, as shown in FIG. **1A**. In general, the connector members **216** may be configured to mechanically couple the proximal self-expanding stent member **160** to the proximal connector ring **164** disposed within the proximal end **154** of the main body **152** of the stent graft **150**. Some embodiments of the stent graft **150** may additionally or alternatively include a plurality of radiopaque markers **116** circumferentially disposed about a tubular portion of the endovascular stent graft **150**. For example, the radiopaque markers **116** may lie in a plane that is substantially orthogonal or parallel to a longitudinal axis **186** of the tubular main body **152** of the stent graft **150**. Additionally, the distal self-expanding member **170** may include one or more radiopaque markers **116**.

[0055] Furthermore, any number of features may be incorporated into the stent graft **150** which may enable detection of all or part of the stent graft **150** under fluoroscopy or other suitable forms of imaging. For example, in general, the radiopaque markers **116**, or other detection features, may be used to facilitate orthogonal orientation of the imaging axis or view. Once a substantially orthogonal view angle is achieved, an accurate axial position of the partially deployed stent graft **150** relative to the patient's vasculature may be achieved, avoiding parallax, ensuring precise placement of the stent graft **150** relative to significant branch vessels or other anatomic reference points. Parallax in some circumstances may cause error in axial placement of the stent graft **150** relative to the intended target site. Accurate positioning may be achieved with axial movement and adjustment of the stent graft **150** by manual manipulation of a proximal portion of the delivery catheter **100**.

[0056] As shown in FIG. **2**, the stent graft **150** may be positioned such that the proximal end **154** of the main body **152** of the stent graft **150** is aligned distal of the ostium of the renal arteries. Once the delivery catheter **100** system has been positioned at the treatment site an outer sheath **102** of the



delivery catheter **100** may be proximally retracted. Though the outer sheath **102** may have been proximally retracted, thus exposing the stent graft **150**, the stent graft **150** may remain in a partially constrained state with the proximal self-expanding stent member **160** restrained by a pair of proximal releasable belts **104** and **106** releasably disposed about the proximal self-expanding stent member **160**. The distal self-expanding stent member **170** may be constrained by another set of distal releasable belts **108** and **110** which may be releasably disposed about the distal self-expanding stent member **170**.

[0057] Each of the releasable belts **104**, **106**, **108** and **110** may be configured to be independently released by retraction of one or more respective release wires **120**. Release wires **120** may be disposed within an end loop or loops of the releasable belts **104**, **106**, **108** and **110** with the one or more release wires **120** holding the loops in fixed relation to each other. For this arrangement, retraction of one or more release wires **120** from the end loops releases the loops to allow them to move relative to each other which in turn removes the constraint of the belt members **104**, **106**, **108** and **110** about the respective proximal and distal self-expanding stent members **160** and **170**. After at least partial deployment of the proximal stent member **160**, finalizing the axial position of the stent graft **150** relative to the anatomy of the patient's vasculature **130** and treatment site may then be made. The axial positioning may be accomplished in some embodiments with the use of one or more radiopaque marker devices **116**, as described above. Once the partially radially constrained stent graft **150** is axially aligned, the proximal self-expanding stent member **160** may then be fully deployed in order to engage and become secured to the luminal wall or interior luminal surface **132** of the patient's vasculature **130**, as shown by way of example in FIG. 4. Once the proximal anchor member **160** is fully deployed, the inflatable portion **158** of the stent graft **150**, including the network of inflatable channels, may be inflated with a fill material. For some embodiments, the network of inflatable channels may be filled from a desired site within the inflatable portion **158**. More specifically, the inflatable portion **158** may be inflated with fill material from a proximal end **154** of the main body **152**.

[0058] The proximal self-expanding stent member **160** may be disposed at and secured to a proximal end **154** of the main body **152**. For example, the proximal self-expanding stent member **160** may have a first self-expanding stent member **200** secured to a second self-expanding stent member **202**. Both the first and second self-expanding stent members **200** and **202** may have a somewhat tubular shape and may be secured together by one or more struts **168**. Some embodiments of the struts **168** may have one or more cross sectional areas **169** that vary along the length of the strut **168**. Such a configuration may be useful in avoiding points of concentrated stress in, for example, the proximal self-expanding stent member **160** or struts **168**. The proximal self-expanding stent member **160** may include at least one barb **165** and/or enlarged portion **180** on each strut **168**, every other strut **168** or combinations thereof. One proximal self-expanding stent member **160** embodiment may have a repeated strut **168** pattern having a more proximally placed barb **165** on one strut **168**, an adjacent neighbor strut **168** with a more distally placed barb **165**, and a following adjacent strut **168** with a centrally placed enlarged portion **180**, as shown in FIG. 3. Another enlarged portion embodiment **180** may have enlarged portions **180** on every strut **168**, as shown in FIG. 5. Additionally, a proximal self-expanding stent member **160** embodiment may have a first self-expanding stent member **200** secured to a second self-expanding stent member **202** where the first self-expanding stent member **200** (or more proximal stent) may have alternating more distally placed barbs **165** along the struts **168** with more proximally placed barbs **165** along the struts **168**, as shown in FIG. 9. Another proximal self-expanding stent member **160** embodiment may include one or more struts **168** having enlarged portions **180** generally centrally placed along the length of the struts **168**, followed by alternating more distally placed barbs **165** with more proximally placed barbs **165** along the struts **168**, as shown in FIG. 11.

[0059] For some embodiments, the first self-expanding member **200** of the proximal self-expanding stent member **160** may further include a plurality of barbs **165** having sharp tissue

engaging tips that are configured to extend radially outward and distally in a deployed expanded state. This configuration may be useful in order to engage tissue of an inner luminal surface **132** of a patient's vasculature **130** and mechanically anchor the stent graft **150** to the vasculature **130**, in addition to the anchoring function provided by the outward radial force of the proximal self-expanding stent member **160** against the inner luminal surface **132** of the patient's vasculature **130** when the stent graft **150** is in a deployed state. The second self-expanding member **202** of the proximal self-expanding stent member **160** may be secured to the proximal end **154** of the main body **152** of the stent graft **150** with one or more struts **168** and/or connector members **216** mechanically coupled to a proximal connector ring **164**.

[0060] When loaded on the delivery catheter **100**, the first and second self-expanding members **200**, **202** of the proximal self-expanding stent member **160** may be radially constrained by releasable belts **104** and **106** which may be releasably held in a constraining configuration by a release member, such as a release wire **120**. FIG. 2 shows an embodiment of the proximal self-expanding stent member **160** where the first self-expanding member **200** is being radially constrained by a first releasable belt **104** and the second self-expanding member **202** is being radially constrained by a second releasable belt **106**. The first releasable belt **104** may be released by a first release wire **120** and the second releasable belt **106** may be deployed by the second release wire **120**. The first and second self-expanding members **200** and **202** of the proximal anchor member may only be released after the outer sheath **102** has been retracted, as shown in FIG. 2, in order to expose the stent graft **150**.

[0061] The strut **168** structure of the proximal self-expanding stent member **160** and/or distal self-expanding stent member **170** may be formed from a cylindrical metal tube structure which is carved or bore by laser or other cutting device. Thereafter, the cut tube may be heat set into two separate forms or states such as an expanded state and non-expanded/contracted state. FIG. 3 shows an example of a non-expanded state. The proximal self-expanding stent member **160** and/or distal self-expanding stent member **170** may include one or more barbs **165**. A barb **165** may be any outwardly directed protuberance, typically terminating in a sharp point that is capable of at least partially penetrating a body passageway in which the stent graft **150** is deployed (typically the initial and medial layers of a blood vessel such as the abdominal aorta). The number of barbs **165**, the length of each barb **165**, each barb **165** angle, and the barb **165** orientation may vary from barb **165** to barb **165** within a single anchor member or between multiple anchor members (i.e., proximal self-expanding stent member **160** and/or distal self-expanding stent member **170**) within a single stent graft **150**. Although the various barbs **165** (and tuck pads **166**, as will be discussed below) may be attached to or fixed on the struts **168**, it may be preferred that they are integrally formed as part of the struts **168**. When either the proximal self-expanding stent member **160** and/or distal self-expanding stent member **170** is deployed in the abdominal aorta, for example, typically in a location proximal to the aneurysm and any diseased tissue, barbs **165** may be designed to work in conjunction with the distally-oriented blood flow field. In this location, the barbs **165** may penetrate the tissue and prevent axial migration of the stent graft **150**. As such, the barbs **165** may be oriented proximally with respect to the main body **152** section. However, the number, dimensions, configuration and orientation of barbs **165** may vary significantly, yet be within the scope of the present invention.

[0062] The staged deployment of the proximal self-expanding stent member **160** may also facilitate self-alignment of the stent graft **150**. For instance, upon deployment of the proximal self-expanding stent member **160**, the graft may be free to expand and enable distal fluid flow to flow through the stent graft **150** and create a “windsock” effect. That is, the distal fluid flow may apply a slight distal force generally upon the main body **152**. This distal force may help to align at least the main body **152** and proximal self-expanding stent member **160** within the patient's vasculature **130**, which may be particularly advantageous during deployment of the stent graft **150** within the angulated vasculature **130**, for example.

[0063] In some embodiments of the stent graft **150**, one or more struts **168** may include tuck pads **166**. Additionally, the one or more struts **168** may have tuck pads **166** positioned such that the tuck pads **166** are generally aligned with a barb **165** extending from an adjacent strut **168**, as shown in FIG. **11**. As such, during preparation of the stent graft **150** into its reduced diameter delivery configuration (or non-expanded/contracted state), each barb **165** may be placed, for example, behind an adjacent strut **168** and/or tuck pad **166** in order to prevent the barbs **165** from radially extending and contacting the inside of a outer sheath **102** or delivery catheter **100** during delivery of the stent graft **150**, as well as to prevent undesired contact of the barbs **165** with the inside luminal surface **132** of a patient's vasculature **130**.

[0064] As illustrated in FIG. **3A**, the struts **168** may have various circumferential dimensions and/or cross sectional areas **169**. Enlarged portions **180** of a strut **168** may also include varying radial lengths generally along a longitudinal axis of the strut **168**. Enlarged portions **180** may be aligned with barbs **165** and/or located at a generally unstable portion of a strut **168**. In some stent graft **150** embodiments, when the stent (i.e., proximal self-expanding member **169**) is in a compressed state, enlarged portions **180** may abut each other and may have one or more flat sides which prevent slippage by each other. Adjacent enlarged portions **180** that abut each other and circumferentially interfere with each other may be axially coextensive. In a radially compressed state, for example, the one or more enlarged portions **180** may be compressed to a radial diameter that is no greater than the remaining part of the strut **168**.

[0065] In some embodiments, one or more struts **168** may have a tapered section **300**. For example, one or more struts **168** may have a tapered section **300** in order to evenly distribute strain induced at least when the stent is in a constrained state. The strut **168** may taper from a first end portion of the strut **168** to a smaller transverse cross section towards a middle portion of the strut **168**. As shown in FIG. **7B**, a strut **168** embodiment may taper from a proximal end **400** portion towards a respective middle portion **402** and taper to a reduced transverse cross section from a distal end portion **404** towards a respective middle portion **402**. The strut **168** may taper over half or approximately half of the length of the strut **168**. In addition, the strut **168** may taper generally over the entire length of the strut **168**, such as from the apex or crown of the anchor member or stent to the middle of the strut or to the first discontinuity feature (i.e., an enlarged portion **180**, barb **165**, tuck pad **166** and the like). The struts **168** may taper in at least one transverse dimension of the strut **168**. Additionally, the struts **168** may taper along a circumferential direction about the longitudinal axis of the struts **168** may have a substantially constant thickness in a radial direction relative to the longitudinal axis of the stent, such as the proximal self-expanding stent member **160**. The struts **168** may taper along a radial direction relative to the longitudinal axis of the anchor member or stent and the struts **168** may have a substantially constant thickness in a circumferential direction about the longitudinal axis of the anchor member or stent. The taper angle of a tapered section **300** of a strut **168** may be about 1 degree to about 3 degrees inclusive, about 1.5 degree to about 2.5 degrees inclusive, or about 1.75 degree to about 2.25 degrees inclusive. The strut **168** embodiments may taper continuously from each end portion to the respective middle portions, such as is shown by way of example in FIG. **9**. The struts may include a stepped taper embodiment **302** which tapers in discrete steps rather than a smooth continuous taper from the distal and proximal end portions **404** and **400** of the respective middle portions **402** in either radial direction about the longitudinal axis. Such an embodiment is shown by way of example in FIG. **7C**. The struts may also taper in a circumferential direction about the longitudinal axis, as shown in FIG. **8**. The tapered sections **300** of the struts **168** may extend from proximal and distal end portions **400** and **404** of the struts **168** to respective strut structures (i.e., enlarged portions **180**) disposed in, for example, the middle portion **402** of the respective strut **168**, as shown by way of example in FIG. **8**.

[0066] FIG. **5** illustrates a portion of a stent **500** embodiment which may function as a proximal self-expanding stent member **160**. The stent **500** may include a plurality of struts **168** extending axially between the proximal end **402** and distal end **404** thereof. The stent **500** may be oriented in

either direction, depending on the application. Both the proximal and distal ends **400** and **404** may have a plurality of crowns adjoining adjacent struts **168**. The distal end **404** may have a plurality of connecting members **216** configured to connect the stent **500** to the main body **152** or other structure. The stent **500** embodiment may have various features (i.e., tuck pads **166**, etc.) and structures and is not limited to the strut **168** features and structures illustrated herein. For example, the stent **500** may have a body defined by a lattice structure or a helical structure.

[0067] Optional taper (or tapers) may be incorporated into one or more of the struts **168** of the various stent **500** embodiments, as well as the various connector members **216**. In general, incorporating one or more tapers into one or more of the struts **168** in one or more stents **500** may provide greater space in the tapered section **300** to accommodate alternative features such as barbs **165** and tuck pads **166**. In addition, it may allow for a smaller deployment profile when the components are in a radially collapsed delivery configuration. When configuring the various stents **500** into this reduced diameter delivery profile (non-expanded/constrained state), the stents **500** may experience a large degree of bending strain that may be poorly distributed. Tapering certain stent **500** struts **168** in particular locations may help to distribute this strain more evenly throughout the stent **500** and/or strut **168** which may assist in preventing strain damage to the stent **500**.

[0068] FIG. **5** illustrates a section of a stent **500**, such as a proximal self-expanding stent member **160**, in which the struts **168** taper from a proximal end **400** width to a minimum width about the middle portion **402** of the strut **168**. An example transverse cross-section of the strut **168** taken along line **6AA-6AA**, which is generally located in the proximal end **400** region of a strut **168**, of FIG. **5** is shown in FIG. **6AA** (which may or may not equal a width of strut **168** in the apex region or distal end **404**). Another example transverse cross-section of the strut **168** taken along line **6A-6A**, which is generally located in the minimum width, or near the middle portion **402** region of the strut **168**, of FIG. **5** is shown in FIG. **6A**. The optional taper, which may be expressed as the taper ratio, is the ratio of the maximum width (as shown, for example, in FIG. **6AA**) to the minimum width (as shown in FIG. **6A**) of a cross sectional area **169**. The taper ratio may vary widely depending on, for example, the particular region of the strut **168** or connector member **216**, the material used, and other factors. Taper ratios ranging from about 1 to about 10 or greater may be within the scope of the present invention. It may also be within the scope of the present invention for the struts **168** to have no taper (as shown by way of example in FIG. **7A**).

[0069] FIGS. **6A-6EE**, illustrate a variety of examples of varying transverse cross-sectional views taken at two different locations along a single strut **168**. These figures illustrate examples of the different shapes and sizes a single cross sectional area **169** of a strut **168** may have. For instance, as described above, FIGS. **6A** and **6AA** show a pair of transverse cross section views of the strut **168** embodiment of FIG. **5** taken along the lines **6A-6A** and **6AA-6AA** which illustrates the rectangular shape of the cross sectional area **169** and the change in size of the cross sectional area **169** at two different locations along the strut **168**. FIGS. **6B** and **6BB** illustrate another example embodiment of paired transverse cross section views of another strut **168** embodiment which illustrates the trapezoidal shape of the cross sectional area **169** and the change in size of the cross sectional area **169** at two different locations along the strut **168**. FIGS. **6C** and **6CC** illustrate another example embodiment of paired transverse cross section views of another strut **168** embodiment which illustrates the inverse trapezoidal shape of the cross sectional area **169** and the change in size of the cross sectional area **169** at two different locations along the strut **168**. FIGS. **6D** and **6DD** illustrate another example embodiment of paired transverse cross section views of another strut **168** embodiment which illustrates the elliptical shape of the cross sectional area **169** and the change in size of the cross sectional area **169** at two different locations along the strut **168**. FIGS. **6E** and **6EE** illustrate another example embodiment of paired transverse cross section views of another strut **168** embodiment which illustrates the circular shape of the cross sectional area **169** and the change in size of the cross sectional area **169** at two different locations along the strut **168**. The transverse cross sectional area **169** of one or more locations along a strut **168** are not limited to the sizes and

shapes disclosed herein, and may be any number of sizes and shapes that may be incorporated in a strut **168** and/or stent **500** configuration.

[0070] A proximal self-expanding stent member **160** may have, for example, one or more struts **168** having a proximal end **400** portion and/or distal end **404** portion which may be made from NiTi and an effective maximum strut **168** width ranging from about 0.016 to about 0.032 inch; particularly from about 0.022 inch and about 0.028 inch, and a minimum strut **168** width between about 0.010 inch and about 0.026 inch; particularly from about 0.012 inch and about 0.022 inch. Additional tapered strut **168** embodiments are described and shown herein in the figures which may be used in other anchor members (such as the proximal and distal self-expanding stent members **160** and **170**), stent **500** embodiments or connector members **216** described herein, and may be incorporated in any number of components and made from any number of materials. For example, tapering of the struts **168** in any configuration described herein may improve the strain distribution at least between the proximal end **400** portions and distal end **404** portions of the struts **168**.

[0071] Various types of taper features or configurations may be implemented in any number of struts **168** for achieving a variety of strut **168** characteristics. For example, one or more struts **168** may include a taper having an offset radii and/or combinations of elliptical and/or circular apex radii in order to further cause the desired behavior during assembly into a reduced-diameter delivery configuration as well as effective delivery and performance in vivo. For example, the proximal end **400** portion, or apex, width may be the minimum width of the strut **168** which untapers towards the middle portion **402** of the strut **168**, which may have the maximum width of the strut **168**. The tapering from the proximal end **400** portion to the middle portion **402** of the strut **168** may be continuous, stepped in discrete steps **410** with straight untapered portions between each discrete step (as shown by way of example in FIGS. 7C and 8) or a combination thereof. Furthermore, untapering of the strut **168** may be in the radial and/or circumferential direction along the longitudinal length of the strut **168**.

[0072] The strut **168** may include an enlarged portion **180** located in about the middle portion **402** of one or more of the struts **168**, as shown by way of example in FIG. 5. By way of further example, one or more enlarged portions **180** may be located along every other strut **168** of the stent **500**. The one or more enlarged portion **180** may be located along a strut **168** in various locations, such as near or at the proximal end **400** portion, middle portion **402**, and/or distal end **404** portion of the strut **168**. Additionally, the one or more enlarged portions **180** may be located at offset locations relative to enlarged portions **180** (or other features) along neighboring struts **168**.

[0073] In some cases, the one or more enlarged longitudinal sections or enlarged portions **180** may have an enlarged transverse dimension that is about 1.5 times to about 3 times the nominal transverse dimension of the strut **168** in a direction of the enlargement. Additionally, the enlarged portions **180** may have an undulating configuration of the nominal strut **168**. Furthermore, the enlarged portion **180** may have an oval enlargement of the nominal strut. Each strut **168** of the stent **500** having an enlarged portion **168** along the length of the strut **168** may have only one enlarged portion **180**. Alternatively, each strut **168** of the stent **500** having an enlarged portion **180** along the length of the strut **168** may have more than one enlarged portion **180**. The enlarged portions **180** are not limited to what are described and shown herein, and may be sized, featured, shaped, and proportioned in any number of ways that may assist in assembly or use of the stent **500**.

Additionally, any number of materials may be used and may vary between struts **168**, anchor members (such as the proximal and distal self-expanding strut members **160** and **170**), and/or stents **500**.

[0074] FIG. 10A shows an example portion of a cylindrical stent embodiment **500** in a constrained configuration including struts **168** having generally coaxially aligned enlarged portion **180** embodiments having circular or oval features. FIG. 10B shows an example portion of a cylindrical stent embodiment **500** in a constrained configuration having struts **168** with generally coaxially

aligned enlarged portion **180** embodiments having square or rectangular features. FIG. **10C** shows a portion of a cylindrical stent embodiment **500** in a constrained configuration including struts **168** having undulating deflected portions **182** which may be configured to physically separate adjacent struts **168** in a circumferential direction.

[0075] One or more struts **168** of a stent embodiment **500** may have a stepped taper **302** feature generally along the length of the strut **168**. For example, one or more struts **168** may have a stepped taper **302** from the proximal end **400** to the respective middle portion **402** of the strut **168** and/or a stepped taper **302** from the distal end **404** to the middle portion **402** of the strut **168**, wherein the stepped taper **302** may be in either radial direction about the longitudinal axis of the strut **168**, as shown by way of example in FIG. **7C**, or the circumferential direction about the longitudinal axis, as shown by way of example in FIG. **8**. The taper characteristics of a strut **168** may be continuous, stepped or any other shape configured to evenly distribute strain induced by the constraint of the constrained non-expanded stent **500**.

[0076] FIG. **7A** illustrates an example longitudinal section view taken along line **7A-7A** of the strut **168** in FIG. **5** which shows a generally rectangular cross sectional area **169** having no radial tapering about the longitudinal axis. FIG. **7B** illustrates another example of a longitudinal section view of a strut **168** which shows a generally tapered cross sectional area **169** due to radial tapering about the longitudinal axis of the strut **168**. In FIG. **7B**, the strut **168** tapers continuously from each end portion (the proximal and distal ends **400** and **404**) to the middle portion **402** such that the middle portion **402** generally has the minimum strut **168** width in the radial direction. FIG. **7C** shows another example strut **168** embodiment in longitudinal section including a radial stepped tapering **302** about the longitudinal axis of the strut **168**. In FIG. **7C**, the strut **168** generally tapers in steps continuously from each end portion (the proximal and distal ends **400** and **404**) to the middle portion **402** such that the middle portion **402** generally has the minimum strut **168** width in the radial direction.

[0077] FIG. **8** shows a portion of an embodiment of a stent **500** including struts **168** having a circumferential stepped taper **302** configuration about the longitudinal axis of the strut **168**. The middle portion **402** of each strut **168** may also include an enlarged portion **180** extending, for example, in a circumferential direction. Portions of the stepped taper **302** of a strut **168** that may be directly adjacent an enlarged portion **180** may have the minimum strut **168** width in the circumferential direction. However, any number of combinations of tapering in any direction may be used.

[0078] FIG. **9** shows a stent embodiment **500** where the proximal self-expanding stent member **160** has a first self-expanding member **200** secured to a second self-expanding member **202** where the first self-expanding member **200** has alternating more proximally placed barbs **165** along the struts **168** with more distally placed barbs **165** along the struts **168**. In addition, the stent embodiment **500** may have a continuous taper in the second self-expanding member **202**, which is the portion of the proximal self-expanding stent member **160** adjacent the main body **152**. Each strut **168** on the first self-expanding member **168** may have a barb **165** in a different location relative to a neighboring strut **168**. The barbs **165** may be formed integrally with the struts **168**, but may otherwise be manufactured, for example, as a separate component attached to the struts **168**. In general, the struts **168** and the barbs **165** of the stent embodiments **500** and anchor members may be self-expanding, that is, upon release of a constraining force, the struts **168** may move radially apart and the barbs **165** may extend radially outward. Other configurations, such as balloon expansion, are also contemplated within the present invention.

[0079] In addition, stent embodiments **500** may include struts **168** including tuck pads **166**, which may be positioned along a strut **168** such that the tuck pads **166** are axially aligned with a barb **165** positioned on a neighboring strut **168**. Similar to the barbs **165** and enlarged portions **180**, the number, dimensions, configurations and orientations of the tuck pads **166** may vary between struts **168**, stent embodiments **500** and anchor members (such as the proximal and distal self-expanding

stent members **160** and **170** described herein).

[0080] During preparation of a stent graft embodiment **150** (and therefore one or more proximal self-expanding stent members **160**) into a reduced diameter delivery configuration, one or more barbs **165** may be placed behind a corresponding strut **168** and/or tuck pad **166**, if present, in order to prevent the barbs **165** from contacting the inside of a outer sheath **102** or delivery catheter **100** during delivery of the stent graft **150** and from undesired contact with the interior luminal surface **132** of the patient's vasculature **130**. As described in copending U.S. patent application Ser. No. 09/917,371 to Chobotov et al., now U.S. Pat. No. 6,761,733, and which is incorporated by reference herein in its entirety, a release belt may be disposed in one or more grooves (not shown) disposed on one or more struts **168** which may assist in retaining the proximal self-expanding stent member **160** in the reduced diameter delivery configuration.

[0081] For example, upon deployment of stent graft **150**, and more particularly the proximal self-expanding stent member **160**, (typically accomplished, at least in part, by release of one or more belts, such as the proximal releasable belts **104** and **106**), the radial expansion of the proximal self-expanding stent member **160** results in a displacement of struts **168** so that the distance between them increases. Eventually, the displacement between the struts **168** become large enough to enable the barbs **165** to be released from behind the adjacent strut **168** and/or tuck pad **166** and engage the interior luminal surface **132** of the patient's vasculature **130**. In general, the barbs **165** may release into a position suitable for engaging the interior luminal surface **132** of a patient's vasculature with a time constant that is generally an order of magnitude lower than the time constant associated with the radial expansion of the stent **500** embodiment or anchor member (such as the proximal self-expanding stent member **160**). In other words, during the stent **500** or anchor member deployment process, the one or more barbs **165** may complete their deployment before the stent **500** or anchor member is fully expanded so that the barbs **165** may engage the interior luminal surface **132** of the vasculature **130** with maximum effectiveness.

[0082] Referring again to FIG. **9**, the proximal self-expanding stent member **160** may include struts **168**, any one of which may further comprise one or more barbs **165**. In addition, optional tuck pads **166** may be positioned along a strut **168** such that the tuck pad **166** is coaxially aligned with a barb **165** on a neighboring strut **168** in order to shield the neighboring barb **165** at least when the stent graft **150** is in its reduced diameter delivery configuration. Struts **168** and/or tuck pads **166** may also include a tuck slot **167** which may assist in retaining a barb **165** while the stent graft **150** (and consequently the proximal self-expanding stent member **160**) is in its reduced diameter delivery configuration. Upon deployment of a stent graft **150** embodiment, the one or more barbs **165** may be released from respective tuck slots **167** and thereafter placed in an operational or deployed configuration for engaging a patient's vasculature **130**.

[0083] FIG. **11** shows a portion of a cylindrical stent embodiment **500** in a generally constrained and flattened configuration having struts **168** with a coaxial enlarged portion **180** embodiments and undulating deflected portions **182**. The undulating deflected portions **182** may have barbs **165** positioned at offset proximal and distal locations along neighboring struts **168** which may aid in efficiently compacting the struts **168** and barbs **165** in a constrained configuration for delivery into a patient's body. By alternating axial location of the barbs **165** and/or enlarged portions **180** along neighboring struts **168**, the stent **500** may be optimally compressed. The undulating deflected portions **182** of a strut **168** may enable multiple lateral contact points within the stent **500**. Such multiple contact points may aid in restraining or compacting the stent **500** in a constrained/non-expanded state. In some embodiments, one or more struts **168** may have enlarged longitudinal sections or enlarged portions **180** that may be disposed in a substantially longitudinal orientation between the proximal end and distal end of the stent **500** when the stent **500** is in the constrained state. Additionally, the one or more struts **168** may be disposed in an undulating pattern. FIG. **12** shows a transverse cross section view of the stent **500** portion of FIG. **11** taken along lines **12-12** of FIG. **11**. FIG. **12** illustrates an example of the varying circumferential cross sectional areas **169** of

the struts **168** along a transverse cross section of the strut **500**.

[0084] As discussed above, some embodiments of a modular endovascular stent graft assembly may include a bifurcated graft member **600** with a proximal stent or anchor member **602** secured thereto. In some cases, the main body member **604** may be formed from a supple graft material, such as ePTFE, having a main fluid flow lumen **606** therein. FIG. **13** illustrates such an embodiment. Referring to this figure, the main graft portion **604** may include an ipsilateral leg **608** with an ipsilateral fluid flow lumen **610** in communication with the main fluid flow lumen **606**, a contralateral leg **612** with a contralateral fluid flow lumen **614** in communication with the main fluid flow lumen **606** and a network of inflatable channels **616** disposed on the main graft member **604**. For some embodiments, the main graft or main body member **604** may have an axial length of about 5 cm to about 10 cm, more specifically, about 6 cm to about 8 cm in order to span an aneurysm **622** of a patient's aorta **618** without engaging the patient's iliac arteries **620** directly with the legs **608** and **612** of the main graft member **604** (see FIG. **14**).

[0085] The inflatable channels of the network of inflatable channels **616** may be disposed on any portion of the main graft or main body member **604** including the ipsilateral and contralateral legs **608** and **612**. The network of inflatable channels **616** may be configured to accept a hardenable fill material to provide structural rigidity to the main body **604** member when the network of inflatable channels **616** are in an inflated state and the inflation material has been cured or hardened.

Radiopaque inflation material may be used to facilitate monitoring of the fill process and subsequent engagement of graft extensions. The network of inflatable channels **616** may also include at least one inflatable cuff **624** disposed on a proximal portion of the main body member which may be configured to seal against an inside surface of a patient's vessel, such as the aorta.

[0086] The proximal anchor member **626**, which may have a substantially tubular or cylindrical configuration, may be disposed at a proximal end **628** of the main body member **604** and secured to the main body member **604** in any suitable manner including stitching, adhesive bonding, welding, and the like. The proximal anchor member **626** may also be secured to the main body **604** with a resilient connector ring (not shown) which may be embedded in a proximal end or portion **628** the main body **604**. The proximal anchor member **626** may have a self-expanding proximal stent portion **630** secured to a self-expanding distal stent portion **632**. Each of these stent portions **630** and **632** may include an undulating elongate stent element that may be disposed in a somewhat serpentine or sinusoidal configuration, as shown above with regard to stent members **160** and **170**. Each of the stent portions **630** and **632** of the proximal anchor member **626** of the stent graft **600** in FIG. **13** may share any or all of the features, dimensions or materials of stent members **160** and **170** discussed above. For example, the proximal and distal stent portions **630** and **632** of the proximal anchor member **626** may include tapered struts **634** that extend between crown portions **636** of each respective stent portion **630** or **632**. Such tapered struts **634** may have any or all of the features, dimensions, and materials of the struts discussed above and include a tapered strut configuration that allows for the strain imposed on the strut structure to be evenly distributed through the structure of the stent portion or portions **630** and **632**.

[0087] In some cases, the proximal stent portion **630** may be secured to the distal stent portion **632** with one or more struts or strut segments **638** disposed between the respective proximal and distal stent sections **630** and **632**. Some embodiments of such interconnecting struts **638** may have a cross sectional area that is substantially the same as or greater than a cross sectional area of proximal stent portions **630** or distal stent portions **632** adjacent the strut **638**. Such configurations may be useful in avoiding points of concentrated stress in the proximal anchor member **602** or struts **638** which couple components thereof. For some embodiments, the proximal stent portion **630** of the proximal anchor member **602** may further include a plurality of barbs **640** having sharp tissue engaging tips **642** that are configured to extend in a radial outward direction in a deployed expanded state (see FIG. **15**). For some embodiments, each stent portion **630** and **632** of the proximal anchor member **602** may include about 5 crowns **636** to about 8 crowns **636** at either end



of the respective section **630** or **632** and may be made from a superelastic alloy such as superelastic NiTi alloy.

[0088] At least one tubular ipsilateral graft extension **644** having a fluid flow lumen **646** disposed therein may be deployed with the fluid flow lumen **646** of the graft extension **644** sealed to and in fluid communication with the fluid flow lumen **610** of the ipsilateral leg **608** of the main body member **604**. In addition, at least one tubular contralateral graft extension **648** having a fluid flow lumen **650** disposed therein may be deployed with the fluid flow lumen **650** of the graft extension **648** sealed to and in fluid communication with the fluid flow lumen **614** of the contralateral leg **612** of the main body member **604**. For some embodiments, the graft extensions **644** and **648** may include an interposed self-expanding stent **652** disposed between at least one outer layer and at least one inner layer of supply layers of graft material. The interposed stent disposed between the outer layer and inner layer of graft material may be formed from an elongate resilient element helically wound with a plurality of longitudinally spaced turns into an open tubular configuration. For some embodiments, the interposed stent **652** may include a superelastic alloy such as superelastic NiTi alloy. In addition, the graft material of each graft extension **644** and **648** may further include at least one axial zone of low permeability for some embodiments.

[0089] For some embodiments, an outside surface of the graft extension **648** may be sealed to an inside surface of the contralateral leg **612** of the main body **604** when the graft extension **648** is in a deployed state. For some embodiments, the axial length of the ipsilateral and contralateral legs **608** and **612** may be sufficient to provide adequate surface area contact with outer surfaces of graft extensions **644** and **648** to provide sufficient friction to hold the graft extensions **644** and **648** in place. For some embodiments, the ipsilateral and contralateral legs **608** and **612** may have an axial length of at least about 2 cm. For some embodiments, the ipsilateral and contralateral legs **608** and **612** may have an axial length of about 2 cm to about 6 cm, more specifically, about 3 cm to about 5 cm.

[0090] For the bifurcated stent graft embodiment **600** discussed above or any other suitable stent graft embodiment discussed herein that includes a proximal self-expanding anchor member **602**, it may be desirable in some cases to constrain each of the proximal and distal stent portions **630** and **632** separately so that each of the proximal and distal stent portions **630** and **632** of the proximal anchor member **602** can be deployed from a radially constrained state independent of each other. FIG. 14 shows the stent graft **600** having an 8 crown distal stent portion **632** with marker elements **654** disposed at a distal end **656** of the distal stent portion **632**. Other than this variation in the proximal anchor configuration, the stent graft of FIG. 14 may have the same features, dimensions and materials as those of the stent graft **600** shown in FIG. 13.

[0091] The stent graft **600** of FIG. 14 is shown in a partially deployed state within an abdominal aorta **618** of a patient with the proximal end **628** of the main body **604** disposed just below and in a non-interfering relationship with the renal arteries **658** which extend from and are in communication with the patient's aorta. The main body **604** of the stent graft **600** also extends substantially across the aneurysm **622** of the aorta **618**, however, this relationship may vary depending on the size of the graft **600** used and the morphology of the aneurysm **632**. The proximal stent portion **630** of the proximal anchor member **602** is still constrained by a releasable member or belt **660** such that it has an outer dimension or profile suitable for delivery within a catheter assembly within the patient's vasculature. The distal stent portion **632**, however, has been released from a constrained state and has expanded radially such that the distal end **656** of the distal stent portion **632** has expanded outwardly in approximation to the inner surface **662** of the patient's aorta **618**.

[0092] In such cases, a proximal anchor member **602** configured to allow the distal end **656** of the distal stent portion **632** to so expand may be desirable. For example, the markers **654** disposed at the distal end **656** of the distal stent portion **632** are substantially open and are close to or in contact with the inner wall **662** of the patient's aorta **68** providing good visualization of the position of the

partially deployed stent graft **600** under fluoroscopy. This configuration may allow the physician deploying the stent graft **600** to visualize the position of the stent graft **600** and accurately predict what the final position of the stent graft **600** will be after complete deployment. However, such a configuration may also allow the physician to adjust the position of the stent graft **600** prior to full deployment of the proximal anchor member **602**. In other words, the stent graft **600** and markers **654** at the distal end **656** of the distal stent portion **632** are sufficiently expanded so that the physician can easily see how the stent graft **600** will be positioned when fully deployed before the physician has deployed the proximal stent portion **630** in which case the barbs **640** or other tissue engaging members of the proximal stent portion **630** engage the tissue of the inner wall **662** of the patient's aorta **618**.

[0093] We have found that in some instances, in order to configure an anchor member **602** such that the distal end **656** of the distal stent portion **632** opens or radially expands sufficiently upon release from a constrained state, that certain design parameters or criteria may be desirable. In particular, such a stent portion **632** may benefit from a configuration that produces a good distal opening force or maximum opening force in an outward radial direction. In order to produce a generous opening force in an outward radial direction, the section of the struts **634** and crowns **636** of the proximal and distal stent portions **630** and **632** may be increased, however, it may also be desirable to adjust the tapering profile of the struts **634** in order to maintain a substantially even distribution of strain throughout the structure of the stent portions **630** and **632**. For some embodiments, a useful outward opening force may include about 0.5 to about 0.75 lbf of force for a stent embodiment that is about 14 mm to about 16 mm in outer diameter in a relaxed unconstrained state.

[0094] In cases such as the stent graft embodiment **600** of FIG. **13** wherein the proximal anchor member **602** includes both a proximal stent portion **630** and a distal stent portion **632**, it may be useful to vary the axial lengths of the respective proximal and distal portions **630** and **632** of the anchor member **602**. Such an unsymmetric arrangement may be beneficial in cases such as the partial deployment sequence step shown in FIG. **14** wherein the constraint on the distal stent portion **632** has been released so as to allow radial expansion of the distal portion **632** but the proximal stent portion **630** remains constrained.

[0095] FIG. **15** illustrates an embodiment of the proximal anchor member **602** having a 5 crown proximal stent portion **630** and a five crown distal stent portion **632**. An attachment ring **664** is secured to each crown **636** of the distal end **656** of the distal stent portion **632**. Such attachment rings **664** may be secured to the proximal end **628** of main body **604** by stitching the ring **664** to the flexible material of the main body portion **604** with suture or any other suitable material. Such attachment rings **664** may also be secured to the main body **604** by any other suitable method including any of the attachment methods and devices discussed above. A cutaway portion **668** of the proximal anchor member **602** is shown at the ends of arrows **665** to illustrate an element of the proximal anchor member **602** for further discussion. The cutaway portion **668** includes a distal crown **670** and respective stent struts **634** attached thereto from the distal stent portion **632** and a proximal crown **672** and respective stent struts **634** attached thereto from the proximal stent portion **630**. The proximal end of the distal stent portion **632** is secured to the distal end **676** of the proximal stent portion **630** by strut segments **638**.

[0096] FIG. **16** illustrates the cutaway portion **668** of the proximal anchor member **602** of FIG. **15** with an adjacent arrow **678** that indicates the axial length of the proximal stent portion **630** and an arrow **680** that indicates the axial length of the proximal stent portion **630** together with the distal stent portion **632** or, in other words, the axial length of the proximal anchor member **602** as a whole. For some embodiments, it has been determined that one or more of the design parameters discussed above may be optimized by use of a proximal anchor member **602** having a proximal stent portion **630** and a distal stent portion **632** wherein the axial length of the proximal anchor member **602** as a whole (L.sub.stent) divided by the axial length of the proximal stent portion **630**

(L.sub.proximal) is a ratio of about 1.75 to about 2.5, more specifically, about 1.75 to about 2.1, and even more specifically, about 1.75 to about 1.9. Such a configuration may be useful for a multi-element stent or proximal anchor member **602** in order to maximize opening force and minimize peak strain within the proximal anchor member **602**.

[0097] It has also been discovered that for such proximal anchor member embodiments **600** as shown in FIG. **16** including unsymmetric axial lengths of the proximal stent portion **630** and distal stent portion **632**, that it may also be useful to include unsymmetric taper lengths. FIG. **17** illustrates the cutaway portion **668** of the proximal anchor member **602** of FIG. **15** with an arrow **682** that indicates the axial length of the tapered portion **684** of the strut **634** that tapers from the proximal end **674** of the distal stent portion **632** towards the distal end **656** of the distal stent portion **632**. Such a tapered portion **684** extends from the crown **686** of the distal stent portion **632** at a proximal end thereof to an axial position of minimum strut cross section **688** between the proximal crown **686** and distal crown **670** of the distal stent portion **632**. Distal of the position of minimum section **688** on the strut **634**, the strut **634** may begin to flare and increase in section towards the distal crown **670**. Thus, the point of minimum section **688** on the strut **634** represents the endpoint of the tapered portions **684** of the strut **634** which begin at each respective crown **670** and **686** of the distal stent portion **632**. For some stent embodiments **602**, a strut taper configuration wherein the axial length of the proximal anchor member as a whole **602** or L.sub.stent divided by the axial length of the tapered strut **634** from the crown **686** of the distal stent portion **632** at a proximal end **674** thereof to an axial position of minimum strut cross section **688** between the proximal crown **686** and distal crown **670** of the distal stent portion **632** (L.sub.taper) is about 3.0 to about 4.5, may be particularly useful in order to maximize opening force and reduce or minimize peak strains within the structure of the proximal anchor member **602**. It should also be noted that such unsymmetric taper lengths may also be used for multi-element stents or proximal anchor members **602** having stent portions **630** and **632** of equal axial length.

[0098] Another design parameter that may be useful when maximizing opening force and minimizing peak strain within a proximal anchor member **602** is selection of the inner crown radius of the crowns **636** at each end of the respective proximal and distal stent portions **630** and **632**. FIGS. **18** and **19** illustrate an inner crown radius R of a distal crown **670** of the distal stent portion **632** of the proximal anchor member **602**. For some embodiments, it may be useful to have an inner crown radius R of about 0.001 inches to about 0.005 inches, more specifically, about 0.001 inches to about 0.004 inches. It should be noted that such inner crown radii dimensions R may also be used for single element stents or proximal anchor members **160** and **170**, particularly in embodiments where it is desirable to maximize opening force and minimize peak strains within the proximal anchor member.

[0099] For some particular stent graft embodiments **600** having a bifurcated main body **604** and a multi-element proximal anchor member **602**, the proximal anchor member **602** may be configured to open to a maximum diameter of about 29 mm to about 31 mm, more specifically, about 30 mm, the proximal anchor member may have an overall axial length L.sub.stent of about 35 mm to about 37 mm, more specifically, about 36 mm, an opening force of about 0.5 lbf to about 0.7 lbf, more specifically, about 0.6 lbf, and a ratio of the axial length **680** of the anchor member **602** L.sub.stent divided by the axial length **678** of the proximal stent portion **630** L.sub.proximal of about 2.0 to about 2.2, more specifically, about 2.1. Such an embodiment **600** may also have a distal stent portion **632** with a strut taper configuration wherein the length **680** of the proximal anchor member **602** as a whole L.sub.stent divided by the length **682** of the tapered strut **639** from the crown **686** of the distal stent portion **632** at a proximal end thereof to an axial position of minimum strut cross section **688** between the proximal crown **686** and distal crown **670** of the distal stent portion **632** (L.sub.taper) is about 3.0 to about 3.2, more specifically, about 3.1. Many other embodiments following the design parameters discussed above may also be used in order to maximize opening force and minimize peak strain within the proximal anchor member **602**. As discussed above, these

design parameters may also be used singly or in any combination in order to achieve the desired results in either single element stents **160** and **170** or multi-element stents **600** having a proximal stent portion **630**, distal stent portion **632** or any other number of stent portions.

[0100] While preferred embodiments of the invention have been shown and described herein, it will be understood that such embodiments are provided by way of example only. Numerous variations, changes and substitutions will occur to those skilled in the art without departing from the spirit of the invention. Accordingly, it is intended that the appended claims cover all such variations as fall within the spirit and scope of the invention.

[0101] The number of barbs, enlarged portions or tapers per strut, the length of each barb, enlarged portions or tapers, each of the barb angles or tapered angle described above, and the barb, enlarged portion or tapered orientation may vary from barb to barb, enlarged portion to enlarged portion, strut to strut within a single stent or between multiple stents within a single graft.

[0102] The entirety of each patent, patent application, publication and document referenced herein hereby is incorporated by reference. Citation of the above patents, patent applications, publications and documents is not an admission that any of the foregoing is pertinent prior art, nor does it constitute any admission as to the contents or date of these publications or documents.

[0103] Modifications may be made to the foregoing without departing from the basic aspects of the invention. Although embodiments of the invention have been described in substantial detail with reference to one or more specific embodiments, those of ordinary skill in the art will recognize that changes may be made to the embodiments specifically disclosed in this application, yet these modifications and improvements are within the scope and spirit of the invention.

[0104] Embodiments illustratively described herein suitably may be practiced in the absence of any element(s) not specifically disclosed herein. Thus, for example, in each instance herein any of the terms “comprising,” “consisting essentially of,” and “consisting of” may be replaced with either of the other two terms. The terms and expressions which have been employed are used as terms of description and not of limitation and use of such terms and expressions do not exclude any equivalents of the features shown and described or portions thereof and various modifications are possible within the scope of the invention claimed. The term “a” or “an” can refer to one of or a plurality of the elements it modifies (e.g., “a reagent” can mean one or more reagents) unless it is contextually clear either one of the elements or more than one of the elements is described. Thus, it should be understood that although embodiments have been specifically disclosed by representative embodiments and optional features, modification and variation of the concepts herein disclosed may be resorted to by those skilled in the art, and such modifications and variations are considered within the scope of this invention.

[0105] Certain embodiments of the invention are set forth in the claim(s) that follow(s).

## Claims

**1-30.** (canceled)

**31.** A self-expanding cylindrical stent having a constrained state and a relaxed expanded state, comprising: a proximal end; a distal end; and a plurality of first resilient struts configured to exert an outward radial force in the constrained state, each of the plurality of first resilient struts comprising an enlarged longitudinal section which is enlarged in a circumferential orientation relative to a longitudinal axis of the stent and configured to stabilize the plurality of first resilient struts, wherein the enlarged longitudinal sections of two adjacent resilient struts of the plurality of first resilient struts contact each other in the constraint state.

**32.** The stent of claim 31, wherein the enlarged longitudinal section of a first resilient strut of the plurality of first resilient struts contacts the enlarged longitudinal sections of two second resilient struts of the plurality of resilient struts in the constraint state.

**33.** The stent of claim 31, wherein the enlarged longitudinal section of one of the plurality of first

resilient struts comprises one or more flat sides.

**34.** The stent of claim 31, wherein the enlarged longitudinal sections of the two adjacent resilient struts circumferentially interfere with each other as the enlarged longitudinal sections of the two adjacent resilient struts contact each other in the constraint state.

**35.** The stent of claim 31, wherein the enlarged longitudinal sections of the two adjacent resilient struts are axially coextensive.

**36.** The stent of claim 31, wherein in the constraint state, the enlarged longitudinal sections of the plurality of first resilient struts are compressed to a radial diameter that is no greater than a radial diameter of a remaining part of the stent.

**37.** The stent of claim 31, further comprising a plurality of second resilient struts configured to exert an outward radial force in the constrained state, each of the plurality of second resilient struts comprising a body and a barbed section that extends from the body.

**38.** The stent of claim 37, wherein locations and orientations of the barbed sections of two adjacent resilient struts of the plurality of second resilient struts are asymmetric about a dimension that extends across the plurality of second resilient struts.

**39.** The stent of claim 37, wherein each of the plurality of second resilient struts comprises a section, wherein the barbed section has a first flat surface, and the enlarged section comprises a second flat surface.

**40.** The stent of claim 39, wherein a first flat surface of a first resilient strut of the plurality of second resilient struts faces a second flat surface of a second resilient strut of the plurality of second resilient struts.

**41.** The stent of claim 37, wherein locations of the barbed sections of the plurality of second resilient struts are alternating across the plurality of second resilient struts.

**42.** The stent of claim 37, wherein one of the plurality of first resilient struts is adjacent to one of the plurality of second resilient struts.

**43.** The stent of claim 31, wherein the plurality of first resilient struts do not comprise barbed portion.

**44.** The stent of claim 31, wherein a transverse dimension of the enlarged longitudinal section of one of the plurality of first resilient struts is 1.5 times to 3 times a nominal transverse dimension of the one of the plurality of first resilient struts in the circumferential orientation.

**45.** The stent of claim 31, wherein each of the plurality of first resilient struts comprises two or more of the enlarged longitudinal sections; each of the plurality of first resilient struts comprises only one of the enlarged longitudinal section.

**46.** The stent of claim 31, wherein a location of the enlarged longitudinal section of a first one of the two adjacent resilient struts of the plurality of first resilient struts is offset from a location of the enlarged longitudinal section of a second one of the two adjacent resilient struts of the plurality of first resilient struts, along an axial dimension of the two adjacent resilient struts.

**47.** The stent of claim 31, wherein a cross-section of a body of one of the plurality of first resilient struts has a trapezoidal shape.

**48.** The stent of claim 31, wherein a cross-section of a body of one of the plurality of first resilient struts has an oval or round shape.

**49.** The stent of claim 31, wherein a cross-section of a body of one of the two adjacent resilient struts and a cross-section of a body of another one of the two adjacent resilient struts are complementary.

**50.** The stent of claim 31, wherein at least one of the plurality of first resilient struts comprises a taper having an offset radius, an elliptical apex radius, or a circular apex radius.

---