

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12386869
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Williams; Frank John et al.

---

### Image processing utilizing an antigen construct

---

#### Abstract

A method performed by a computing device includes determining a set of identigens for each word of a query of a topic to produce sets of identigens. Each set of identigens represents one or more different meanings of a word of the query. The method further includes interpreting, using identigen pairing rules, the sets of identigens to determine a most likely meaning interpretation of the query and produce an excluding query antigen group with an excluding antigen. The method further includes recovering a response antigen group for the query from a knowledge database utilizing the excluding query antigen group. The response antigen group provides a response to the query.

---

**Inventors:** Williams; Frank John (Rossmoor, CA), Lazzara; David Ralph (Huntington Beach, CA), Sundberg; Stephen Emerson (Chicago, IL), Reed; Ameeta Vasant (Deerfield, IL), Roberson; Dennis Arlen (Chapin, SC), MacTavish; Thomas James (Inverness, IL), Knutson; Karl Olaf (Palatine, IL), Thomas; Jessy (Palatine, IL), MacTavish; Niklas Josiah (Inverness, IL), Corns, II; David Michael (Elgin, IL), Chu; Andrew (St. Charles, IL), Mazurkiewicz; Theodore (Lake Zurich, IL), Grube; Gary W. (Barrington Hills, IL)

**Applicant:** entigenlogic LLC (Schaumburg, IL)

**Family ID:** 1000008751410

**Assignee:** entigenlogic LLC (Schaumburg, IL)

**Appl. No.:** 17/970112

**Filed:** October 20, 2022

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20230043805 A1	Feb. 09, 2023

## Related U.S. Application Data

continuation-in-part parent-doc US 16696114 20191126 US 11544320 child-doc US 17970112  
us-provisional-application US 62772655 20181129

---

## Publication Classification

**Int. Cl.:** **G06V10/00** (20220101); **G06F16/332** (20190101); **G06F40/247** (20200101); **G06N5/04** (20230101)

**U.S. Cl.:**

**CPC** **G06F16/3322** (20190101); **G06F40/247** (20200101); **G06N5/04** (20130101);

## Field of Classification Search

**CPC:** G06F (16/3322); G06F (40/247); G06F (40/30); G06N (5/022); G06N (5/04)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4538188	12/1984	Barker	N/A	N/A
6021220	12/1999	Anderholm	N/A	N/A
6076088	12/1999	Paik	N/A	N/A
6175834	12/2000	Cai	N/A	N/A
8645991	12/2013	Mcintire	N/A	N/A
9286938	12/2015	Tseytlin	N/A	N/A
10108600	12/2017	Williams	N/A	G06F 40/242
10110544	12/2017	Kozareva	N/A	G06N 5/048
10163011	12/2017	Kaehler	N/A	N/A
10390055	12/2018	Wilms	N/A	N/A
10943075	12/2020	Williams	N/A	G06F 16/313
11100324	12/2020	Williams	N/A	G06T 7/11
11232260	12/2021	Williams	N/A	G06F 16/3344
11288583	12/2021	Williams	N/A	G06F 16/9035
11544320	12/2022	Williams	N/A	G06V 10/764
11748563	12/2022	Grube	707/758	G06F 40/237
12019628	12/2023	Williams	N/A	G06F 16/90344
12050869	12/2023	Williams	N/A	G06N 5/04
12147908	12/2023	Williams	N/A	G06N 5/041
12182188	12/2023	Williams	N/A	G06F 16/338
2003/0097251	12/2002	Yamada	N/A	N/A
2008/0208569	12/2007	Simpson	N/A	N/A
2016/0147979	12/2015	Kato	N/A	N/A
2019/0362145	12/2018	Williams	N/A	N/A
2020/0034358	12/2019	Wurzel	N/A	N/A
2020/0175064	12/2019	Williams	N/A	N/A

2021/0182604	12/2020	Anthony	N/A	N/A
2021/0287012	12/2020	Li	N/A	N/A

---

*Primary Examiner:* Alavi; Amir

---

## Background/Summary

CROSS REFERENCE TO RELATED PATENTS (1) The present U.S. Utility Patent Applications claims priority pursuant to 35 U.S.C. § 120 as a continuation in part of U.S. Utility application Ser. No. 16/696,114, entitled “IMAGE PROCESSING UTILIZING AN ENTIGEN CONSTRUCT” filed Nov. 26, 2019, allowed, which claims priority pursuant to 35 U.S.C. § 119(e) to U.S. Provisional Application No. 62/772,655, entitled “IMAGE PROCESSING UTILIZING AN ENTIGEN CONSTRUCT” filed Nov. 29, 2018, all of which are hereby incorporated herein by reference in their entirety and made part of the present U.S. Utility Patent Application for all purposes.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

(1) Not Applicable

INCORPORATION-BY-REFERENCE OF MATERIAL SUBMITTED ON A COMPACT DISC

(2) Not Applicable

BACKGROUND OF THE INVENTION

Technical Field of the Invention

(3) This invention relates to computing systems and more particularly to generating data representations of data and analyzing the data utilizing the data representations.

Description of Related Art

(4) It is known that data is stored in information systems, such as files containing text. It is often difficult to produce useful information from this stored data due to many factors. The factors include the volume of available data, accuracy of the data, and variances in how text is interpreted to express knowledge. For example, many languages and regional dialects utilize the same or similar words to represent different concepts.

(5) Computers are known to utilize pattern recognition techniques and apply statistical reasoning to process text to express an interpretation in an attempt to overcome ambiguities inherent in words. One pattern recognition technique includes matching a word pattern of a query to a word pattern of the stored data to find an explicit textual answer. Another pattern recognition technique classifies words into major grammatical types such as functional words, nouns, adjectives, verbs and adverbs. Grammar based techniques then utilize these grammatical types to study how words should be distributed within a string of words to form a properly constructed grammatical sentence where each word is forced to support a grammatical operation without necessarily identifying what the word is actually trying to describe.

---

## Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING(S)

(1) FIG. 1 is a schematic block diagram of an embodiment of a computing system in accordance with the present invention;

(2) FIG. 2 is a schematic block diagram of an embodiment of various servers of a computing system in accordance with the present invention;

(3) FIG. 3 is a schematic block diagram of an embodiment of various devices of a computing

system in accordance with the present invention;

(4) FIGS. 4A and 4B are schematic block diagrams of another embodiment of a computing system in accordance with the present invention;

(5) FIG. 4C is a logic diagram of an embodiment of a method for interpreting content to produce a response to a query within a computing system in accordance with the present invention;

(6) FIG. 5A is a schematic block diagram of an embodiment of a collections module of a computing system in accordance with the present invention;

(7) FIG. 5B is a logic diagram of an embodiment of a method for obtaining content within a computing system in accordance with the present invention;

(8) FIG. 5C is a schematic block diagram of an embodiment of a query module of a computing system in accordance with the present invention;

(9) FIG. 5D is a logic diagram of an embodiment of a method for providing a response to a query within a computing system in accordance with the present invention;

(10) FIG. 5E is a schematic block diagram of an embodiment of an identigen entigen intelligence (IEI) module of a computing system in accordance with the present invention;

(11) FIG. 5F is a logic diagram of an embodiment of a method for analyzing content within a computing system in accordance with the present invention;

(12) FIG. 6A is a schematic block diagram of an embodiment of an element identification module and an interpretation module of a computing system in accordance with the present invention;

(13) FIG. 6B is a logic diagram of an embodiment of a method for interpreting information within a computing system in accordance with the present invention;

(14) FIG. 6C is a schematic block diagram of an embodiment of an answer resolution module of a computing system in accordance with the present invention;

(15) FIG. 6D is a logic diagram of an embodiment of a method for producing an answer within a computing system in accordance with the present invention;

(16) FIG. 7A is an information flow diagram for interpreting information within a computing system in accordance with the present invention;

(17) FIG. 7B is a relationship block diagram illustrating an embodiment of relationships between things and representations of things within a computing system in accordance with the present invention;

(18) FIG. 7C is a diagram of an embodiment of a synonym words table within a computing system in accordance with the present invention;

(19) FIG. 7D is a diagram of an embodiment of a polysemous words table within a computing system in accordance with the present invention;

(20) FIG. 7E is a diagram of an embodiment of transforming words into groupings within a computing system in accordance with the present invention;

(21) FIG. 8A is a data flow diagram for accumulating knowledge within a computing system in accordance with the present invention;

(22) FIG. 8B is a diagram of an embodiment of a groupings table within a computing system in accordance with the present invention;

(23) FIG. 8C is a data flow diagram for answering questions utilizing accumulated knowledge within a computing system in accordance with the present invention;

(24) FIG. 8D is a data flow diagram for answering questions utilizing interference within a computing system in accordance with the present invention;

(25) FIG. 8E is a relationship block diagram illustrating another embodiment of relationships between things and representations of things within a computing system in accordance with the present invention;

(26) FIGS. 8F and 8G are schematic block diagrams of another embodiment of a computing system in accordance with the present invention;

(27) FIG. 8H is a logic diagram of an embodiment of a method for processing content to produce

knowledge within a computing system in accordance with the present invention;

(28) FIGS. **8J** and **8K** are schematic block diagrams another embodiment of a computing system in accordance with the present invention;

(29) FIG. **8L** is a logic diagram of an embodiment of a method for generating a query response to a query within a computing system in accordance with the present invention;

(30) FIGS. **9A** and **9B** are schematic block diagrams of another embodiment of a computing system illustrating an embodiment of a method for interpreting an image within the computing system in accordance with the present invention;

(31) FIG. **10A** is a schematic block diagram of another embodiment of a computing system in accordance with the present invention;

(32) FIGS. **10B** and **10C** are schematic block diagrams of an embodiment of a portion of knowledge base within a computing system in accordance with the present invention;

(33) FIG. **10D** is a logic diagram of an embodiment of a method for processing a query within a computing system in accordance with the present invention;

(34) FIGS. **10E** and **10F** are schematic block diagrams of another embodiment of a computing system illustrating an embodiment of a method for generating a response to a query within the computing system in accordance with the present invention;

(35) FIG. **11A** is a schematic block diagram of another embodiment of a computing system in accordance with the present invention;

(36) FIGS. **11B** and **11C** are schematic block diagrams of another embodiment of a portion of knowledge base within a computing system in accordance with the present invention;

(37) FIG. **11D** is a logic diagram of an embodiment of another method for processing a query within a computing system in accordance with the present invention;

(38) FIG. **12A** is a schematic block diagram of another embodiment of a computing system in accordance with the present invention;

(39) FIGS. **12B** and **12C** are schematic block diagrams of another embodiment of a portion of knowledge base within a computing system in accordance with the present invention;

(40) FIG. **12D** is a logic diagram of an embodiment of another method for processing a query within a computing system in accordance with the present invention;

(41) FIG. **13A** is a schematic block diagram of another embodiment of a computing system in accordance with the present invention;

(42) FIG. **13B** is schematic block diagram of another embodiment of a portion of knowledge base within a computing system in accordance with the present invention; and

(43) FIG. **13C** is a logic diagram of an embodiment of another method for processing an image within a computing system in accordance with the present invention.

#### DETAILED DESCRIPTION OF THE INVENTION

(44) FIG. **1** is a schematic block diagram of an embodiment of a computing system **10** that includes a plurality of user devices **12-1** through **12-N**, a plurality of wireless user devices **14-1** through **14-N**, a plurality of content sources **16-1** through **16-N**, a plurality of transactional servers **18-1** through **18-N**, a plurality of artificial intelligence (AI) servers **20-1** through **20-N**, and a core network **24**. The core network **24** includes at least one of the Internet, a public radio access network (RAN), and any private network. Hereafter, the computing system **10** may be interchangeably referred to as a data network, a data communication network, a system, a communication system, and a data communication system. Hereafter, the user device and the wireless user device may be interchangeably referred to as user devices, and each of the transactional servers and the AI servers may be interchangeably referred to as servers.

(45) Each user device, wireless user device, transactional server, and AI server includes a computing device that includes a computing core. In general, a computing device is any electronic device that can communicate data, process data, and/or store data. A further generality of a computing device is that it includes one or more of a central processing unit (CPU), a memory

system, a sensor (e.g., internal or external), user input/output interfaces, peripheral device interfaces, communication elements, and an interconnecting bus structure.

(46) As further specific examples, each of the computing devices may be a portable computing device and/or a fixed computing device. A portable computing device may be an embedded controller, a smart sensor, a smart pill, a social networking device, a gaming device, a cell phone, a smart phone, a robot, a personal digital assistant, a digital music player, a digital video player, a laptop computer, a handheld computer, a tablet, a video game controller, an engine controller, a vehicular controller, an aircraft controller, a maritime vessel controller, and/or any other portable device that includes a computing core. A fixed computing device may be security camera, a sensor device, a household appliance, a machine, a robot, an embedded controller, a personal computer (PC), a computer server, a cable set-top box, a satellite receiver, a television set, a printer, a fax machine, home entertainment equipment, a camera controller, a video game console, a critical infrastructure controller, and/or any type of home or office computing equipment that includes a computing core. An embodiment of the various servers is discussed in greater detail with reference to FIG. 2. An embodiment of the various devices is discussed in greater detail with reference to FIG. 3.

(47) Each of the content sources **16-1** through **16-N** includes any source of content, where the content includes one or more of data files, a data stream, a tech stream, a text file, an audio stream, an audio file, a video stream, a video file, etc. Examples of the content sources include a weather service, a multi-language online dictionary, a fact server, a big data storage system, the Internet, social media systems, an email server, a news server, a schedule server, a traffic monitor, a security camera system, audio monitoring equipment, an information server, a service provider, a data aggregator, and airline traffic server, a shipping and logistics server, a banking server, a financial transaction server, etc. Alternatively, or in addition to, one or more of the various user devices may provide content. For example, a wireless user device may provide content (e.g., issued as a content message) when the wireless user device is able to capture data (e.g., text input, sensor input, etc.).

(48) Generally, an embodiment of this invention presents solutions where the computing system **10** supports the generation and utilization of knowledge extracted from content. For example, the AI servers **20-1** through **20-N** ingest content from the content sources **16-1** through **16-N** by receiving, via the core network **24** content messages **28-1** through **28-N** as AI messages **32-1** through **32-N**, extract the knowledge from the ingested content, and interact with the various user devices to utilize the extracted knowledge by facilitating the issuing, via the core network **24**, user messages **22-1** through **22-N** to the user devices **12-1** through **12-N** and wireless signals **26-1** through **26-N** to the wireless user devices **14-1** through **14-N**.

(49) Each content message **28-1** through **28-N** includes a content request (e.g., requesting content related to a topic, content type, content timing, one or more domains, etc.) or a content response, where the content response includes real-time or static content such as one or more of dictionary information, facts, non-facts, weather information, sensor data, news information, blog information, social media content, user daily activity schedules, traffic conditions, community event schedules, school schedules, user schedules airline records, shipping records, logistics records, banking records, census information, global financial history information, etc. Each AI message **32-1** through **32-N** includes one or more of content messages, user messages (e.g., a query request, a query response that includes an answer to a query request), and transaction messages (e.g., transaction information, requests and responses related to transactions). Each user message **22-1** through **22-N** includes one or more of a query request, a query response, a trigger request, a trigger response, a content collection, control information, software information, configuration information, security information, routing information, addressing information, presence information, analytics information, protocol information, all types of media, sensor data, statistical data, user data, error messages, etc.

(50) When utilizing a wireless signal capability of the core network **24**, each of the wireless user

devices **14-1** through **14-N** encodes/decodes data and/or information messages (e.g., user messages such as user messages **22-1** through **22-N**) in accordance with one or more wireless standards for local wireless data signals (e.g., Wi-Fi, Bluetooth, ZigBee) and/or for wide area wireless data signals (e.g., 2G, 3G, 4G, 5G, satellite, point-to-point, etc.) to produce wireless signals **26-1** through **26-N**. Having encoded/decoded the data and/or information messages, the wireless user devices **14-1** through **14-N** and/or receive the wireless signals to/from the wireless capability of the core network **24**.

(51) As another example of the generation and utilization of knowledge, the transactional servers **18-1** through **18-N** communicate, via the core network **24**, transaction messages **30-1** through **30-N** as further AI messages **32-1** through **32-N** to facilitate ingesting of transactional type content (e.g., real-time crypto currency transaction information) and to facilitate handling of utilization of the knowledge by one or more of the transactional servers (e.g., for a transactional function) in addition to the utilization of the knowledge by the various user devices. Each transaction message **30-1** through **30-N** includes one or more of a query request, a query response, a trigger request, a trigger response, a content message, and transactional information, where the transactional information may include one or more of consumer purchasing history, crypto currency ledgers, stock market trade information, other investment transaction information, etc.

(52) In another specific example of operation of the generation and utilization of knowledge extracted from the content, the user device **12-1** issues a user message **22-1** to the AI server **20-1**, where the user message **22-1** includes a query request and where the query request includes a question related to a first domain of knowledge. The issuing includes generating the user message **22-1** based on the query request (e.g., the question), selecting the AI server **20-1** based on the first domain of knowledge, and sending, via the core network **24**, the user message **22-1** as a further AI message **32-1** to the AI server **20-1**. Having received the AI message **32-1**, the AI server **20-1** analyzes the question within the first domain, generates further knowledge, generates a preliminary answer, generates a quality level indicator of the preliminary answer, and determines to gather further content when the quality level indicator is below a minimum quality threshold level.

(53) When gathering the further content, the AI server **20-1** issues, via the core network **24**, a still further AI message **32-1** as a further content message **28-1** to the content source **16-1**, where the content message **28-1** includes a content request for more content associated with the first domain of knowledge and in particular the question. Alternatively, or in addition to, the AI server **20-1** issues the content request to another AI server to facilitate a response within a domain associated with the other AI server. Further alternatively, or in addition to, the AI server **20-1** issues the content request to one or more of the various user devices to facilitate a response from a subject matter expert.

(54) Having received the content message **28-1**, the contents or **16-1** issues, via the core network **24**, a still further content message **28-1** to the AI server **20-1** as a yet further AI message **32-1**, where the still further content message **28-1** includes requested content. The AI server **20-1** processes the received content to generate further knowledge. Having generated the further knowledge, the AI server **20-1** re-analyzes the question, generates still further knowledge, generates another preliminary answer, generates another quality level indicator of the other preliminary answer, and determines to issue a query response to the user device **12-1** when the quality level indicator is above the minimum quality threshold level. When issuing the query response, the AI server **20-1** generates an AI message **32-1** that includes another user message **22-1**, where the other user message **22-1** includes the other preliminary answer as a query response including the answer to the question. Having generated the AI message **32-1**, the AI server **20-1** sends, via the core network **24**, the AI message **32-1** as the user message **22-1** to the user device **12-1** thus providing the answer to the original question of the query request.

(55) FIG. 2 is a schematic block diagram of an embodiment of the AI servers **20-1** through **20-N** and the transactional servers **18-1** through **18-N** of the computing system **10** of FIG. 1. The servers

include a computing core **52**, one or more visual output devices **74** (e.g., video graphics display, touchscreen, LED, etc.), one or more user input devices **76** (e.g., keypad, keyboard, touchscreen, voice to text, a push button, a microphone, a card reader, a door position switch, a biometric input device, etc.), one or more audio output devices **78** (e.g., speaker(s), headphone jack, a motor, etc.), and one or more visual input devices **80** (e.g., a still image camera, a video camera, photocell, etc.). (56) The servers further include one or more universal serial bus (USB) devices (USB devices **1-U**), one or more peripheral devices (e.g., peripheral devices **1-P**), one or more memory devices (e.g., one or more flash memory devices **92**, one or more hard drive (HD) memories **94**, and one or more solid state (SS) memory devices **96**, and/or cloud memory **98**). The servers further include one or more wireless location modems **84** (e.g., global positioning satellite (GPS), Wi-Fi, angle of arrival, time difference of arrival, signal strength, dedicated wireless location, etc.), one or more wireless communication modems **86-1** through **86-N** (e.g., a cellular network transceiver, a wireless data network transceiver, a Wi-Fi transceiver, a Bluetooth transceiver, a 315 MHz transceiver, a zig bee transceiver, a 60 GHz transceiver, etc.), a telco interface **102** (e.g., to interface to a public switched telephone network), and a wired local area network (LAN) **88** (e.g., optical, electrical), and a wired wide area network (WAN) **90** (e.g., optical, electrical).

(57) The computing core **52** includes a video graphics module **54**, one or more processing modules **50-1** through **50-N** (e.g., which may include one or more secure co-processors), a memory controller **56** and one or more main memories **58-1** through **58-N** (e.g., RAM serving as local memory). The computing core **52** further includes one or more input/output (I/O) device interfaces **62**, an input/output (I/O) controller **60**, a peripheral interface **64**, one or more USB interfaces **66**, one or more network interfaces **72**, one or more memory interfaces **70**, and/or one or more peripheral device interfaces **68**.

(58) The processing modules may be a single processing device or a plurality of processing devices where the processing device may further be referred to as one or more of a “processing circuit”, a “processor”, and/or a “processing unit”. Such a processing device may be a microprocessor, microcontroller, digital signal processor, microcomputer, central processing unit, field programmable gate array, programmable logic device, state machine, logic circuitry, analog circuitry, digital circuitry, and/or any device that manipulates signals (analog and/or digital) based on hard coding of the circuitry and/or operational instructions.

(59) The processing module, module, processing circuit, and/or processing unit may be, or further include, memory and/or an integrated memory element, which may be a single memory device, a plurality of memory devices, and/or embedded circuitry of another processing module, module, processing circuit, and/or processing unit. Such a memory device may be a read-only memory, random access memory, volatile memory, non-volatile memory, static memory, dynamic memory, flash memory, cache memory, and/or any device that stores digital information. Note that if the processing module, module, processing circuit, and/or processing unit includes more than one processing device, the processing devices may be centrally located (e.g., directly coupled together via a wired and/or wireless bus structure) or may be distributedly located (e.g., cloud computing via indirect coupling via a local area network and/or a wide area network).

(60) Further note that if the processing module, module, processing circuit, and/or processing unit implements one or more of its functions via a state machine, analog circuitry, digital circuitry, and/or logic circuitry, the memory and/or memory element storing the corresponding operational instructions may be embedded within, or external to, the circuitry comprising the state machine, analog circuitry, digital circuitry, and/or logic circuitry. Still further note that, the memory element may store, and the processing module, module, processing circuit, and/or processing unit executes, hard coded and/or operational instructions corresponding to at least some of the steps and/or functions illustrated in one or more of the Figures. Such a memory device or memory element can be included in an article of manufacture.

(61) Each of the interfaces **62**, **66**, **68**, **70**, and **72** includes a combination of hardware (e.g.,



connectors, wiring, etc.) and may further include operational instructions stored on memory (e.g., driver software) that are executed by one or more of the processing modules **50-1** through **50-N** and/or a processing circuit within the interface. Each of the interfaces couples to one or more components of the servers. For example, one of the TO device interfaces **62** couples to an audio output device **78**. As another example, one of the memory interfaces **70** couples to flash memory **92** and another one of the memory interfaces **70** couples to cloud memory **98** (e.g., an on-line storage system and/or on-line backup system). In other embodiments, the servers may include more or less devices and modules than shown in this example embodiment of the servers.

(62) FIG. **3** is a schematic block diagram of an embodiment of the various devices of the computing system **10** of FIG. **1**, including the user devices **12-1** through **12-N** and the wireless user devices **14-1** through **14-N**. The various devices include the visual output device **74** of FIG. **2**, the user input device **76** of FIG. **2**, the audio output device **78** of FIG. **2**, the visual input device **80** of FIG. **2**, and one or more sensors **82**.

(63) The sensor may be implemented internally and/or externally to the device. Example sensors includes a still camera, a video camera, servo motors associated with a camera, a position detector, a smoke detector, a gas detector, a motion sensor, an accelerometer, velocity detector, a compass, a gyro, a temperature sensor, a pressure sensor, an altitude sensor, a humidity detector, a moisture detector, an imaging sensor, and a biometric sensor. Further examples of the sensor include an infrared sensor, an audio sensor, an ultrasonic sensor, a proximity detector, a magnetic field detector, a biomaterial detector, a radiation detector, a weight detector, a density detector, a chemical analysis detector, a fluid flow volume sensor, a DNA reader, a wind speed sensor, a wind direction sensor, and an object detection sensor.

(64) Further examples of the sensor include an object identifier sensor, a motion recognition detector, a battery level detector, a room temperature sensor, a sound detector, a smoke detector, an intrusion detector, a motion detector, a door position sensor, a window position sensor, and a sunlight detector. Still further sensor examples include medical category sensors including: a pulse rate monitor, a heart rhythm monitor, a breathing detector, a blood pressure monitor, a blood glucose level detector, blood type, an electrocardiogram sensor, a body mass detector, an imaging sensor, a microphone, body temperature, etc.

(65) The various devices further include the computing core **52** of FIG. **2**, the one or more universal serial bus (USB) devices (USB devices **1-U**) of FIG. **2**, the one or more peripheral devices (e.g., peripheral devices **1-P**) of FIG. **2**, and the one or more memories of FIG. **2** (e.g., flash memories **92**, HD memories **94**, SS memories **96**, and/or cloud memories **98**). The various devices further include the one or more wireless location modems **84** of FIG. **2**, the one or more wireless communication modems **86-1** through **86-N** of FIG. **2**, the telco interface **102** of FIG. **2**, the wired local area network (LAN) **88** of FIG. **2**, and the wired wide area network (WAN) **90** of FIG. **2**. In other embodiments, the various devices may include more or less internal devices and modules than shown in this example embodiment of the various devices.

(66) FIGS. **4A** and **4B** are schematic block diagrams of another embodiment of a computing system that includes one or more of the user device **12-1** of FIG. **1**, the wireless user device **14-1** of FIG. **1**, the content source **16-1** of FIG. **1**, the transactional server **18-1** of FIG. **1**, the user device **12-2** of FIG. **1**, and the AI server **20-1** of FIG. **1**. The AI server **20-1** includes the processing module **50-1** (e.g., associated with the servers) of FIG. **2**, where the processing module **50-1** includes a collections module **120**, an identigen entigen intelligence (IEI) module **122**, and a query module **124**. Alternatively, the collections module **120**, the IEI module **122**, and the query module **124** may be implemented by the processing module **50-1** (e.g., associated with the various user devices) of FIG. **3**. The computing system functions to interpret content to produce a response to a query.

(67) FIG. **4A** illustrates an example of the interpreting of the content to produce the response to the query where the collections module **120** interprets (e.g., based on an interpretation approach such as rules) at least one of a collections request **132** from the query module **124** and a collections

request within collections information **130** from the IEI module **122** to produce content request information (e.g., potential sources, content descriptors of desired content). Alternatively, or in addition to, the collections module **120** may facilitate gathering further content based on a plurality of collection requests from a plurality of devices of the computing system **10** of FIG. **1**.

(68) The collections request **132** is utilized to facilitate collection of content, where the content may be received in a real-time fashion once or at desired intervals, or in a static fashion from previous discrete time frames. For instance, the query module **124** issues the collections request **132** to facilitate collection of content as a background activity to support a long-term query (e.g., how many domestic airline flights over the next seven days include travelers between the age of 18 and 35 years old). The collections request **132** may include one or more of a requester identifier (ID), a content type (e.g., language, dialect, media type, topic, etc.), a content source indicator, security credentials (e.g., an authorization level, a password, a user ID, parameters utilized for encryption, etc.), a desired content quality level, trigger information (e.g., parameters under which to collect content based on a pre-event, an event (i.e., content quality level reaches a threshold to cause the trigger, trueness), or a timeframe), a desired format, and a desired timing associated with the content.

(69) Having interpreted the collections request **132**, the collections module **120** selects a source of content based on the content request information. The selecting includes one or more of identifying one or more potential sources based on the content request information, selecting the source of content from the potential sources utilizing a selection approach (e.g., favorable history, a favorable security level, favorable accessibility, favorable cost, favorable performance, etc.). For example, the collections module **120** selects the content source **16-1** when the content source **16-1** is known to provide a favorable content quality level for a domain associated with the collections request **132**.

(70) Having selected the source of content, the collections module **120** issues a content request **126** to the selected source of content. The issuing includes generating the content request **126** based on the content request information for the selected source of content and sending the content request **126** to the selected source of content. The content request **126** may include one or more of a content type indicator, a requester ID, security credentials for content access, and any other information associated with the collections request **132**. For example, the collections module **120** sends the content request **126**, via the core network **24** of FIG. **1**, to the content source **16-1**. Alternatively, or in addition to, the collections module **120** may send a similar content request **126** to one or more of the user device **12-1**, the wireless user device **14-1**, and the transactional server **18-1** to facilitate collecting of further content.

(71) In response to the content request **126**, the collections module **120** receives one or more content responses **128**. The content response **128** includes one or more of content associated with the content source, a content source identifier, security credential processing information, and any other information pertaining to the desired content. Having received the content response **128**, the collections module **120** interprets the received content response **128** to produce collections information **130**, where the collections information **130** further includes a collections response from the collections module **120** to the IEI module **122**.

(72) The collections response includes one or more of transformed content (e.g., completed sentences and paragraphs), timing information associated with the content, a content source ID, and a content quality level. Having generated the collections response of the collections information **130**, the collections module **120** sends the collections information **130** to the IEI module **122**. Having received the collections information **130** from the collections module **120**, the IEI module **122** interprets the further content of the content response to generate further knowledge, where the further knowledge is stored in a memory associated with the IEI module **122** to facilitate subsequent answering of questions posed in received queries.

(73) FIG. **4B** further illustrates the example of the interpreting of the content to produce the

response to the query where, the query module **124** interprets a received query request **136** from a requester to produce an interpretation of the query request. For example, the query module **124** receives the query request **136** from the user device **12-2**, and/or from one or more of the wireless user device **14-2** and the transactional server **18-2**. The query request **136** includes one or more of an identifier (ID) associated with the request (e.g., requester ID, ID of an entity to send a response to), a question, question constraints (e.g., within a timeframe, within a geographic area, within a domain of knowledge, etc.), and content associated with the question (e.g., which may be analyzed for new knowledge itself).

(74) The interpreting of the query request **136** includes determining whether to issue a request to the IEI module **122** (e.g., a question, perhaps with content) and/or to issue a request to the collections module **120** (e.g., for further background content). For example, the query module **124** produces the interpretation of the query request to indicate to send the request directly to the IEI module **122** when the question is associated with a simple non-time varying function answer (e.g., question: “how many hydrogen atoms does a molecule of water have?”).

(75) Having interpreted the query request **136**, the query module **124** issues at least one of an IEI request as query information **138** to the IEI module **122** (e.g., when receiving a simple new query request) and a collections request **132** to the collections module **120** (e.g., based on two or more query requests **136** requiring more substantive content gathering). The IEI request of the query information **138** includes one or more of an identifier (ID) of the query module **124**, an ID of the requester (e.g., the user device **12-2**), a question (e.g., with regards to content for analysis, with regards to knowledge minded by the AI server from general content), one or more constraints (e.g., assumptions, restrictions, etc.) associated with the question, content for analysis of the question, and timing information (e.g., a date range for relevance of the question).

(76) Having received the query information **138** that includes the IEI request from the query module **124**, the IEI module **122** determines whether a satisfactory response can be generated based on currently available knowledge, including that of the query request **136**. The determining includes indicating that the satisfactory response cannot be generated when an estimated quality level of an answer falls below a minimum quality threshold level. When the satisfactory response cannot be generated, the IEI module **122** facilitates collecting more content. The facilitating includes issuing a collections request to the collections module **120** of the AI server **20-1** and/or to another server or user device, and interpreting a subsequent collections response **134** of collections information **130** that includes further content to produce further knowledge to enable a more favorable answer.

(77) When the IEI module **122** indicates that the satisfactory response can be generated, the IEI module **122** issues an IEI response as query information **138** to the query module **124**. The IEI response includes one or more of one or more answers, timing relevance of the one or more answers, an estimated quality level of each answer, and one or more assumptions associated with the answer. The issuing includes generating the IEI response based on the collections response **134** of the collections information **130** and the IEI request, and sending the IEI response as the query information **138** to the query module **124**. Alternatively, or in addition to, at least some of the further content collected by the collections module **120** is utilized to generate a collections response **134** issued by the collections module **120** to the query module **124**. The collections response **134** includes one or more of further content, a content availability indicator (e.g., when, where, required credentials, etc.), a content freshness indicator (e.g., timestamps, predicted time availability), content source identifiers, and a content quality level.

(78) Having received the query information **138** from the IEI module **122**, the query module **124** issues a query response **140** to the requester based on the IEI response and/or the collections response **134** directly from the collections module **120**, where the collection module **120** generates the collections response **134** based on collected content and the collections request **132**. The query response **140** includes one or more of an answer, answer timing, an answer quality level, and

answer assumptions.

(79) FIG. 4C is a logic diagram of an embodiment of a method for interpreting content to produce a response to a query within a computing system. In particular, a method is presented for use in conjunction with one or more functions and features described in conjunction with FIGS. 1-3, 4A-4B, and also FIG. 4C. The method includes step **150** where a collections module of a processing module of one or more computing devices (e.g., of one or more servers) interprets a collections request to produce content request information. The interpreting may include one or more of identifying a desired content source, identifying a content type, identifying a content domain, and identifying content timing requirements.

(80) The method continues at step **152** where the collections module selects a source of content based on the content request information. For example, the collections module identifies one or more potential sources based on the content request information and selects the source of content from the potential sources utilizing a selection approach (e.g., based on one or more of favorable history, a favorable security level, favorable accessibility, favorable cost, favorable performance, etc.). The method continues at step **154** where the collections module issues a content request to the selected source of content. The issuing includes generating a content request based on the content request information for the selected source of content and sending the content request to the selected source of content.

(81) The method continues at step **156** where the collections module issues collections information to an identigen entigen intelligence (IEI) module based on a received content response, where the IEI module extracts further knowledge from newly obtained content from the one or more received content responses. For example, the collections module generates the collections information based on newly obtained content from the one or more received content responses of the selected source of content.

(82) The method continues at step **158** where a query module interprets a received query request from a requester to produce an interpretation of the query request. The interpreting may include determining whether to issue a request to the IEI module (e.g., a question) or to issue a request to the collections module to gather further background content. The method continues at step **160** where the query module issues a further collections request. For example, when receiving a new query request, the query module generates a request for the IEI module. As another example, when receiving a plurality of query requests for similar questions, the query module generates a request for the collections module to gather further background content.

(83) The method continues at step **162** where the IEI module determines whether a satisfactory query response can be generated when receiving the request from the query module. For example, the IEI module indicates that the satisfactory query response cannot be generated when an estimated quality level of an answer is below a minimum answer quality threshold level. The method branches to step **166** when the IEI module determines that the satisfactory query response can be generated. The method continues to step **164** when the IEI module determines that the satisfactory query response cannot be generated. When the satisfactory query response cannot be generated, the method continues at step **164** where the IEI module facilitates collecting more content. The method loops back to step **150**.

(84) When the satisfactory query response can be generated, the method continues at step **166** where the IEI module issues an IEI response to the query module. The issuing includes generating the IEI response based on the collections response and the IEI request, and sending the IEI response to the query module. The method continues at step **168** where the query module issues a query response to the requester. For example, the query module generates the query response based on the IEI response and/or a collections response from the collections module and sends the query response to the requester, where the collections module generates the collections response based on collected content and the collections request.

(85) The method described above in conjunction with the processing module can alternatively be

performed by other modules of the computing system **10** of FIG. **1** or by other devices. In addition, at least one memory section (e.g., a computer readable memory, a non-transitory computer readable storage medium, a non-transitory computer readable memory organized into a first memory element, a second memory element, a third memory element, a fourth element section, a fifth memory element etc.) that stores operational instructions can, when executed by one or more processing modules of one or more computing devices (e.g., one or more servers, one or more user devices) of the computing system **10**, cause the one or more computing devices to perform any or all of the method steps described above.

(86) FIG. **5A** is a schematic block diagram of an embodiment of the collections module **120** of FIG. **4A** that includes a content acquisition module **180**, a content selection module **182**, a source selection module **184**, a content security module **186**, an acquisition timing module **188**, a content transformation module **190**, and a content quality module **192**. Generally, an embodiment of this invention presents solutions where the collections module **120** supports collecting content.

(87) In an example of operation of the collecting of the content, the content acquisition module **180** receives a collections request **132** from a requester. The content acquisition module **180** obtains content selection information **194** based on the collections request **132**. The content selection information **194** includes one or more of content requirements, a desired content type indicator, a desired content source identifier, a content type indicator, a candidate source identifier (ID), and a content profile (e.g., a template of typical parameters of the content). For example, the content acquisition module **180** receives the content selection information **194** from the content selection module **182**, where the content selection module **182** generates the content selection information **194** based on a content selection information request from the content acquisition module **180** and where the content acquisition module **180** generates the content selection information request based on the collections request **132**.

(88) The content acquisition module **180** obtains source selection information **196** based on the collections request **132**. The source selection information **196** includes one or more of candidate source identifiers, a content profile, selected sources, source priority levels, and recommended source access timing. For example, the content acquisition module **180** receives the source selection information **196** from the source selection module **184**, where the source selection module **184** generates the source selection information **196** based on a source selection information request from the content acquisition module **180** and where the content acquisition module **180** generates the source selection information request based on the collections request **132**.

(89) The content acquisition module **180** obtains acquisition timing information **200** based on the collections request **132**. The acquisition timing information **200** includes one or more of recommended source access timing, confirmed source access timing, source access testing results, estimated velocity of content update's, content precious, timestamps, predicted time availability, required content acquisition triggers, content acquisition trigger detection indicators, and a duplicative indicator with a pending content request. For example, the content acquisition module **180** receives the acquisition timing information **200** from the acquisition timing module **188**, where the acquisition timing module **188** generates the acquisition timing information **200** based on an acquisition timing information request from the content acquisition module **180** and where the content acquisition module **180** generates the acquisition timing information request based on the collections request **132**.

(90) Having obtained the content selection information **194**, the source selection information **196**, and the acquisition timing information **200**, the content acquisition module **180** issues a content request **126** to a content source utilizing security information **198** from the content security module **186**, where the content acquisition module **180** generates the content request **126** in accordance with the content selection information **194**, the source selection information **196**, and the acquisition timing information **200**. The security information **198** includes one or more of source priority requirements, requester security information, available security procedures, and security

credentials for trust and/or encryption. For example, the content acquisition module **180** generates the content request **126** to request a particular content type in accordance with the content selection information **194** and to include security parameters of the security information **198**, initiates sending of the content request **126** in accordance with the acquisition timing information **200**, and sends the content request **126** to a particular targeted content source in accordance with the source selection information **196**.

(91) In response to receiving a content response **128**, the content acquisition module **180** determines the quality level of received content extracted from the content response **128**. For example, the content acquisition module **180** receives content quality information **204** from the content quality module **192**, where the content quality module **192** generates the quality level of the received content based on receiving a content quality request from the content acquisition module **180** and where the content acquisition module **180** generates the content quality request based on content extracted from the content response **128**. The content quality information includes one or more of a content reliability threshold range, a content accuracy threshold range, a desired content quality level, a predicted content quality level, and a predicted level of trust.

(92) When the quality level is below a minimum desired quality threshold level, the content acquisition module **180** facilitates acquisition of further content. The facilitating includes issuing another content request **126** to a same content source and/or to another content source to receive and interpret further received content. When the quality level is above the minimum desired quality threshold level, the content acquisition module **180** issues a collections response **134** to the requester. The issuing includes processing the content in accordance with a transformation approach to produce transformed content, generating the collections response **134** to include the transformed content, and sending the collections response **134** to the requester. The processing of the content to produce the transformed content includes receiving content transformation information **202** from the content transformation module **190**, where the content transformation module **190** transforms the content in accordance with the transformation approach to produce the transformed content. The content transformation information includes a desired format, available formats, recommended formatting, the received content, transformation instructions, and the transformed content.

(93) FIG. 5B is a logic diagram of an embodiment of a method for obtaining content within a computing system. In particular, a method is presented for use in conjunction with one or more functions and features described in conjunction with FIGS. 1-3, 4A-4C, 5A, and also FIG. 5B. The method includes step **210** where a processing module of one or more processing modules of one or more computing devices of the computing system receives a collections request from the requester. The method continues at step **212** where the processing module determines content selection information. The determining includes interpreting the collections request to identify requirements of the content.

(94) The method continues at step **214** where the processing module determines source selection information. The determining includes interpreting the collections request to identify and select one or more sources for the content to be collected. The method continues at step **216** where the processing module determines acquisition timing information. The determining includes interpreting the collections request to identify timing requirements for the acquisition of the content from the one or more sources. The method continues at step **218** where the processing module issues a content request utilizing security information and in accordance with one or more of the content selection information, the source selection information, and the acquisition timing information. For example, the processing module issues the content request to the one or more sources for the content in accordance with the content requirements, where the sending of the request is in accordance with the acquisition timing information.

(95) The method continues at step **220** where the processing module determines a content quality level for received content area the determining includes receiving the content from the one or more

sources, obtaining content quality information for the received content based on a quality analysis of the received content. The method branches to step **224** when the content quality level is favorable and the method continues to step **222** when the quality level is unfavorable. For example, the processing module determines that the content quality level is favorable when the content quality level is equal to or above a minimum quality threshold level and determines that the content quality level is unfavorable when the content quality level is less than the minimum quality threshold level.

(96) When the content quality level is unfavorable, the method continues at step **222** where the processing module facilitates acquisition and further content. For example, the processing module issues further content requests and receives further content for analysis. When the content quality level is favorable, the method continues at step **224** where the processing module issues a collections response to the requester. The issuing includes generating the collections response and sending the collections response to the requester. The generating of the collections response may include transforming the received content into transformed content in accordance with a transformation approach (e.g., reformatting, interpreting absolute meaning and translating into another language in accordance with the absolute meaning, etc.).

(97) The method described above in conjunction with the processing module can alternatively be performed by other modules of the computing system **10** of FIG. **1** or by other devices. In addition, at least one memory section (e.g., a computer readable memory, a non-transitory computer readable storage medium, a non-transitory computer readable memory organized into a first memory element, a second memory element, a third memory element, a fourth element section, a fifth memory element etc.) that stores operational instructions can, when executed by one or more processing modules of one or more computing devices (e.g., one or more servers, one or more user devices) of the computing system **10**, cause the one or more computing devices to perform any or all of the method steps described above.

(98) FIG. **5C** is a schematic block diagram of an embodiment of the query module **124** of FIG. **4A** that includes an answer acquisition module **230**, a content requirements module **232**, a source requirements module **234**, a content security module **236**, an answer timing module **238**, an answer transformation module **240**, and an answer quality module **242**. Generally, an embodiment of this invention presents solutions where the query module **124** supports responding to a query.

(99) In an example of operation of the responding to the query, the answer acquisition module **230** receives a query request **136** from a requester. The answer acquisition module **230** obtains content requirements information **248** based on the query request **136**. The content requirements information **248** includes one or more of content parameters, a desired content type, a desired content source if any, a content type if any, candidate source identifiers, a content profile, and a question of the query request **136**. For example, the answer acquisition module **230** receives the content requirements information **248** from the content requirements module **232**, where the content requirements module **232** generates the content requirements information **248** based on a content requirements information request from the answer acquisition module **230** and where the answer acquisition module **230** generates the content requirements information request based on the query request **136**.

(100) The answer acquisition module **230** obtains source requirements information **250** based on the query request **136**. The source requirements information **250** includes one or more of candidate source identifiers, a content profile, a desired source parameter, recommended source parameters, source priority levels, and recommended source access timing. For example, the answer acquisition module **230** receives the source requirements information **250** from the source requirements module **234**, where the source requirements module **234** generates the source requirements information **250** based on a source requirements information request from the answer acquisition module **230** and where the answer acquisition module **230** generates the source requirements information request based on the query request **136**.

(101) The answer acquisition module **230** obtains answer timing information **254** based on the query request **136**. The answer timing information **254** includes one or more of requested answer timing, confirmed answer timing, source access testing results, estimated velocity of content updates, content freshness, timestamps, predicted time available, requested content acquisition trigger, and a content acquisition trigger detected indicator. For example, the answer acquisition module **230** receives the answer timing information **254** from the answer timing module **238**, where the answer timing module **238** generates the answer timing information **254** based on an answer timing information request from the answer acquisition module **230** and where the answer acquisition module **230** generates the answer timing information request based on the query request **136**.

(102) Having obtained the content requirements information **248**, the source requirements information **250**, and the answer timing information **254**, the answer acquisition module **230** determines whether to issue an IEI request **244** and/or a collections request **132** based on one or more of the content requirements information **248**, the source requirements information **250**, and the answer timing information **254**. For example, the answer acquisition module **230** selects the IEI request **244** when an immediate answer to a simple query request **136** is required and is expected to have a favorable quality level. As another example, the answer acquisition module **230** selects the collections request **132** when a longer-term answer is required as indicated by the answer timing information to before and/or when the query request **136** has an unfavorable quality level.

(103) When issuing the IEI request **244**, the answer acquisition module **230** generates the IEI request **244** in accordance with security information **252** received from the content security module **236** and based on one or more of the content requirements information **248**, the source requirements information **250**, and the answer timing information **254**. Having generated the IEI request **244**, the answer acquisition module **230** sends the IEI request **244** to at least one IEI module.

(104) When issuing the collections request **132**, the answer acquisition module **230** generates the collections request **132** in accordance with the security information **252** received from the content security module **236** and based on one or more of the content requirements information **248**, the source requirements information **250**, and the answer timing information **254**. Having generated the collections request **132**, the answer acquisition module **230** sends the collections request **132** to at least one collections module. Alternatively, the answer acquisition module **230** facilitate sending of the collections request **132** to one or more various user devices (e.g., to access a subject matter expert).

(105) The answer acquisition module **230** determines a quality level of a received answer extracted from a collections response **134** and/or an IEI response **246**. For example, the answer acquisition module **230** extracts the quality level of the received answer from answer quality information **258** received from the answer quality module **242** in response to an answer quality request from the answer acquisition module **230**. When the quality level is unfavorable, the answer acquisition module **230** facilitates obtaining a further answer. The facilitation includes issuing at least one of a further IEI request **244** and a further collections request **132** to generate a further answer for further quality testing. When the quality level is favorable, the answer acquisition module **230** issues a query response **140** to the requester. The issuing includes generating the query response **140** based on answer transformation information **256** received from the answer transformation module **240**, where the answer transformation module **240** generates the answer transformation information **256** to include a transformed answer based on receiving the answer from the answer acquisition module **230**. The answer transformation information **250 6A** further include the question, a desired format of the answer, available formats, recommended formatting, received IEI responses, transformation instructions, and transformed IEI responses into an answer.

(106) FIG. 5D is a logic diagram of an embodiment of a method for providing a response to a query within a computing system. In particular, a method is presented for use in conjunction with



one or more functions and features described in conjunction with FIGS. 1-3, 4A-4C, 5C, and also FIG. 5D. The method includes step **270** where a processing module of one or more processing modules of one or more computing devices of the computing system receives a query request (e.g., a question) from a requester. The method continues at step **272** where the processing module determines content requirements information. The determining includes interpreting the query request to produce the content requirements. The method continues at step **274** where the processing module determines source requirements information. The determining includes interpreting the query request to produce the source requirements. The method continues at step **276** where the processing module determines answer timing information. The determining includes interpreting the query request to produce the answer timing information.

(107) The method continues at step **278** the processing module determines whether to issue an IEI request and/or a collections request. For example, the determining includes selecting the IEI request when the answer timing information indicates that a simple one-time answer is appropriate. As another example, the processing module selects the collections request when the answer timing information indicates that the answer is associated with a series of events over an event time frame.

(108) When issuing the IEI request, the method continues at step **280** where the processing module issues the IEI request to an IEI module. The issuing includes generating the IEI request in accordance with security information and based on one or more of the content requirements information, the source requirements information, and the answer timing information.

(109) When issuing the collections request, the method continues at step **282** where the processing module issues the collections request to a collections module. The issuing includes generating the collections request in accordance with the security information and based on one or more of the content requirements information, the source requirements information, and the answer timing information. Alternatively, the processing module issues both the IEI request and the collections request when a satisfactory partial answer may be provided based on a corresponding IEI response and a further more generalized and specific answer may be provided based on a corresponding collections response and associated further IEI response.

(110) The method continues at step **284** where the processing module determines a quality level of a received answer. The determining includes extracting the answer from the collections response and/or the IEI response and interpreting the answer in accordance with one or more of the content requirements information, the source requirements information, the answer timing information, and the query request to produce the quality level. The method branches to step **288** when the quality level is favorable and the method continues to step **286** when the quality level is unfavorable. For example, the processing module indicates that the quality level is favorable when the quality level is equal to or greater than a minimum answer quality threshold level. As another example, the processing module indicates that the quality level is unfavorable when the quality level is less than the minimum answer quality threshold level.

(111) When the quality level is unfavorable, the method continues at step **286** where the processing module obtains a further answer. The obtaining includes at least one of issuing a further IEI request and a further collections request to facilitate obtaining of a further answer for further answer quality level testing as the method loops back to step **270**. When the quality level is favorable, the method continues at step **288** where the processing module issues a query response to the requester. The issuing includes transforming the answer into a transformed answer in accordance with an answer transformation approach (e.g., formatting, further interpretations of the virtual question in light of the answer and further knowledge) and sending the transformed answer to the requester as the query response.

(112) The method described above in conjunction with the processing module can alternatively be performed by other modules of the computing system **10** of FIG. **1** or by other devices. In addition, at least one memory section (e.g., a computer readable memory, a non-transitory computer readable storage medium, a non-transitory computer readable memory organized into a first memory

element, a second memory element, a third memory element, a fourth element section, a fifth memory element etc.) that stores operational instructions can, when executed by one or more processing modules of one or more computing devices (e.g., one or more servers, one or more user devices) of the computing system **10**, cause the one or more computing devices to perform any or all of the method steps described above.

(113) FIG. 5E is a schematic block diagram of an embodiment of the identigen entigen intelligence (IEI) module **122** of FIG. 4A that includes a content ingestion module **300**, an element identification module **302**, and interpretation module **304**, and answer resolution module **306**, and an IEI control module **308**. Generally, an embodiment of this invention presents solutions where the IEI module **122** supports interpreting content to produce knowledge that may be utilized to answer questions.

(114) In an example of operation of the producing and utilizing of the knowledge, the content ingestion module **300** generates formatted content **314** based on question content **312** and/or source content **310**, where the IEI module **122** receives an IEI request **244** that includes the question content **312** and the IEI module **122** receives a collections response **134** that includes the source content **310**. The source content **310** includes content from a source extracted from the collections response **134**. The question content **312** includes content extracted from the IEI request **244** (e.g., content paired with a question). The content ingestion module **300** generates the formatted content **314** in accordance with a formatting approach (e.g., creating proper sentences from words of the content). The formatted content **314** includes modified content that is compatible with subsequent element identification (e.g., complete sentences, combinations of words and interpreted sounds and/or inflection cues with temporal associations of words).

(115) The element identification module **302** processes the formatted content **314** based on element rules **318** and an element list **332** to produce identified element information **340**. Rules **316** includes the element rules **318** (e.g., match, partial match, language translation, etc.). Lists **330** includes the element list **332** (e.g., element ID, element context ID, element usage ID, words, characters, symbols etc.). The IEI control module **308** may provide the rules **316** and the lists **330** by accessing stored data **360** from a memory associated with the IEI module **122**. Generally, an embodiment of this invention presents solutions where the stored data **360** may further include one or more of a descriptive dictionary, categories, representations of element sets, element list, sequence data, pending questions, pending request, recognized elements, unrecognized elements, errors, etc.

(116) The identified element information **340** includes one or more of identifiers of elements identified in the formatted content **314**, may include ordering and/or sequencing and grouping information. For example, the element identification module **302** compares elements of the formatted content **314** to known elements of the element list **332** to produce identifiers of the known elements as the identified element information **340** in accordance with the element rules **318**. Alternatively, the element identification module **302** outputs un-identified element information **342** to the IEI control module **308**, where the un-identified element information **342** includes temporary identifiers for elements not identifiable from the formatted content **314** when compared to the element list **332**.

(117) The interpretation module **304** processes the identified element information **340** in accordance with interpretation rules **320** (e.g., potentially valid permutations of various combinations of identified elements), question information **346** (e.g., a question extracted from the IEI request to hundred **44** which may be paired with content associated with the question), and a groupings list **334** (e.g., representations of associated groups of representations of things, a set of element identifiers, valid element usage IDs in accordance with similar, an element context, permutations of sets of identifiers for possible interpretations of a sentence or other) to produce interpreted information **344**. The interpreted information **344** includes potentially valid interpretations of combinations of identified elements. Generally, an embodiment of this invention

presents solutions where the interpretation module **304** supports producing the interpreted information **344** by considering permutations of the identified element information **340** in accordance with the interpretation rules **320** and the groupings list **334**.

(118) The answer resolution module **306** processes the interpreted information **344** based on answer rules **322** (e.g., guidance to extract a desired answer), the question information **346**, and inferred question information **352** (e.g., posed by the IEI control module or analysis of general collections of content or refinement of a stated question from a request) to produce preliminary answers **354** and an answer quality level **356**. The answer generally lies in the interpreted information **344** as both new content received and knowledge based on groupings list **334** generated based on previously received content. The preliminary answers **354** includes an answer to a stated or inferred question that subject further refinement. The answer quality level **356** includes a determination of a quality level of the preliminary answers **354** based on the answer rules **322**. The inferred question information **352** may further be associated with time information **348**, where the time information includes one or more of current real-time, a time reference associated with entity submitting a request, and a time reference of a collections response.

(119) When the IEI control module **308** determines that the answer quality level **356** is below an answer quality threshold level, the IEI control module **308** facilitates collecting of further content (e.g., by issuing a collections request **132** and receiving corresponding collections responses **134** for analysis). When the answer quality level **356** compares favorably to the answer quality threshold level, the IEI control module **308** issues an IEI response **246** based on the preliminary answers **354**. When receiving training information **358**, the IEI control module **308** facilitates updating of one or more of the lists **330** and the rules **316** and stores the updated list **330** and the updated rules **316** in the memories as updated stored data **360**.

(120) FIG. 5F is a logic diagram of an embodiment of a method for analyzing content within a computing system. In particular, a method is presented for use in conjunction with one or more functions and features described in conjunction with FIGS. 1-3, 4A-4C, 5E, and also FIG. 5F. The method includes step **370** where a processing module of one or more processing modules of one or more computing devices of the computing system facilitates updating of one or more rules and lists based on one or more of received training information and received content. For example, the processing module updates rules with received rules to produce updated rules and updates element lists with received elements to produce updated element lists. As another example, the processing module interprets the received content to identify a new word for at least temporary inclusion in the updated element list.

(121) The method continues at step **372** where the processing module transforms at least some of the received content into formatted content. For example, the processing module processes the received content in accordance with a transformation approach to produce the formatted content, where the formatted content supports compatibility with subsequent element identification (e.g., typical sentence structures of groups of words).

(122) The method continues at step **374** where the processing module processes the formatted content based on the rules and the lists to produce identified element information and/or an identified element information. For example, the processing module compares the formatted content to element lists to identify a match producing identifiers for identified elements or new identifiers for unidentified elements when there is no match.

(123) The method continues at step **376** with a processing module processes the identified element information based on rules, the lists, and question information to produce interpreted information. For example, the processing module compares the identified element information to associated groups of representations of things to generate potentially valid interpretations of combinations of identified elements.

(124) The method continues at step **378** where the processing module processes the interpreted information based on the rules, the question information, and inferred question information to

produce preliminary answers. For example, the processing module matches the interpreted information to one or more answers (e.g., embedded knowledge based on a fact base built from previously received content) with highest correctness likelihood levels that is subject to further refinement.

(125) The method continues at step **380** where the processing module generates an answer quality level based on the preliminary answers, the rules, and the inferred question information. For example, the processing module predicts the answer correctness likelihood level based on the rules, the inferred question information, and the question information. The method branches to step **384** when the answer quality level is favorable and the method continues to step **382** when the answer quality level is unfavorable. For example, the generating of the answer quality level further includes the processing module indicating that the answer quality level is favorable when the answer quality level is greater than or equal to a minimum answer quality threshold level. As another example, the generating of the answer quality level further includes the processing module indicating that the answer quality level is unfavorable when the answer quality level is less than the minimum answer quality threshold level.

(126) When the answer quality level is unfavorable, the method continues at step **382** where the processing module facilitates gathering clarifying information. For example, the processing module issues a collections request to facilitate receiving further content and or request question clarification from a question requester. When the answer quality level is favorable, the method continues at step **384** where the processing module issues a response that includes one or more answers based on the preliminary answers and/or further updated preliminary answers based on gathering further content. For example, the processing module generates a response that includes one or more answers and the answer quality level and issues the response to the requester.

(127) The method described above in conjunction with the processing module can alternatively be performed by other modules of the computing system **10** of FIG. **1** or by other devices. In addition, at least one memory section (e.g., a computer readable memory, a non-transitory computer readable storage medium, a non-transitory computer readable memory organized into a first memory element, a second memory element, a third memory element, a fourth element section, a fifth memory element etc.) that stores operational instructions can, when executed by one or more processing modules of one or more computing devices (e.g., one or more servers, one or more user devices) of the computing system **10**, cause the one or more computing devices to perform any or all of the method steps described above.

(128) FIG. **6A** is a schematic block diagram of an embodiment of the element identification module **302** of FIG. **5A** and the interpretation module **304** of FIG. **5A**. The element identification module **302** includes an element matching module **400** and an element grouping module **402**. The interpretation module **304** includes a grouping matching module **404** and a grouping interpretation module **406**. Generally, an embodiment of this invention presents solutions where the element identification module **302** supports identifying potentially valid permutations of groupings of elements while the interpretation module **304** interprets the potentially valid permutations of groupings of elements to produce interpreted information that includes the most likely of groupings based on a question.

(129) In an example of operation of the identifying of the potentially valid permutations of groupings of elements, when matching elements of the formatted content **314**, the element matching module **400** generates matched elements **412** (e.g., identifiers of elements contained in the formatted content **314**) based on the element list **332**. For example, the element matching module **400** matches a received element to an element of the element list **332** and outputs the matched elements **412** to include an identifier of the matched element. When finding elements that are unidentified, the element matching module **400** outputs un-recognized words information **408** (e.g., words not in the element list **332**, may temporarily add) as part of un-identified element information **342**. For example, the element matching module **400** indicates that a match cannot be

made between a received element of the formatted content **314**, generates the unrecognized words info **408** to include the received element and/or a temporary identifier, and issues and updated element list **414** that includes the temporary identifier and the corresponding unidentified received element.

(130) The element grouping module **402** analyzes the matched elements **412** in accordance with element rules **318** to produce grouping error information **410** (e.g., incorrect sentence structure indicators) when a structural error is detected. The element grouping module **402** produces identified element information **340** when favorable structure is associated with the matched elements in accordance with the element rules **318**. The identified element information **340** may further include grouping information of the plurality of permutations of groups of elements (e.g., several possible interpretations), where the grouping information includes one or more groups of words forming an associated set and/or super-group set of two or more subsets when subsets share a common core element.

(131) In an example of operation of the interpreting of the potentially valid permutations of groupings of elements to produce the interpreted information, the grouping matching module **404** analyzes the identified element information **340** in accordance with a groupings list **334** to produce validated groupings information **416**. For example, the grouping matching module **404** compares a grouping aspect of the identified element information **340** (e.g., for each permutation of groups of elements of possible interpretations), generates the validated groupings information **416** to include identification of valid permutations aligned with the groupings list **334**. Alternatively, or in addition to, the grouping matching module **404** generates an updated groupings list **418** when determining a new valid grouping (e.g., has favorable structure and interpreted meaning) that is to be added to the groupings list **334**.

(132) The grouping interpretation module **406** interprets the validated groupings information **416** based on the question information **346** and in accordance with the interpretation rules **320** to produce interpreted information **344** (e.g., most likely interpretations, next most likely interpretations, etc.). For example, the grouping interpretation module **406** obtains context, obtains favorable historical interpretations, processes the validated groupings based on interpretation rules **320**, where each interpretation is associated with a correctness likelihood level.

(133) FIG. 6B is a logic diagram of an embodiment of a method for interpreting information within a computing system. In particular, a method is presented for use in conjunction with one or more functions and features described in conjunction with FIGS. 1-3, 4A-4C, 5E-5F, 6A, and also FIG. 6B. The method includes step **430** where a processing module of one or more processing modules of one or more computing devices of the computing system analyzes formatted content. For example, the processing module attempt to match a received element of the formatted content to one or more elements of an elements list. When there is no match, the method branches to step **434** and when there is a match, the method continues to step **432**. When there is a match, the method continues at step **432** where the processing module outputs matched elements (e.g., to include the matched element and/or an identifier of the matched element). When there is no match, the method continues at step **434** where the processing module outputs unrecognized words (e.g., elements and/or a temporary identifier for the unmatched element).

(134) The method continues at step **436** where the processing module analyzes matched elements. For example, the processing module attempt to match a detected structure of the matched elements (e.g., chained elements as in a received sequence) to favorable structures in accordance with element rules. The method branches to step **440** when the analysis is unfavorable and the method continues to step **438** when the analysis is favorable. When the analysis is favorable matching a detected structure to the favorable structure of the element rules, the method continues at step **438** where the processing module outputs identified element information (e.g., an identifier of the favorable structure, identifiers of each of the detected elements). When the analysis is unfavorable matching a detected structure to the favorable structure of the element rules, the method continues

at step **440** where the processing module outputs grouping error information (e.g., a representation of the incorrect structure, identifiers of the elements of the incorrect structure, a temporary new identifier of the incorrect structure).

(135) The method continues at step **442** where the processing module analyzes the identified element information to produce validated groupings information. For example, the processing module compares a grouping aspect of the identified element information and generates the validated groupings information to include identification of valid permutations that align with the groupings list. Alternatively, or in addition to, the processing module generates an updated groupings list when determining a new valid grouping.

(136) The method continues at step **444** where the processing module interprets the validated groupings information to produce interpreted information. For example, the processing module obtains one or more of context and historical interpretations and processes the validated groupings based on interpretation rules to generate the interpreted information, where each interpretation is associated with a correctness likelihood level (e.g., a quality level).

(137) The method described above in conjunction with the processing module can alternatively be performed by other modules of the computing system **10** of FIG. **1** or by other devices. In addition, at least one memory section (e.g., a computer readable memory, a non-transitory computer readable storage medium, a non-transitory computer readable memory organized into a first memory element, a second memory element, a third memory element, a fourth element section, a fifth memory element etc.) that stores operational instructions can, when executed by one or more processing modules of one or more computing devices (e.g., one or more servers, one or more user devices) of the computing system **10**, cause the one or more computing devices to perform any or all of the method steps described above.

(138) FIG. **6C** is a schematic block diagram of an embodiment of the answer resolution module **306** of FIG. **5A** that includes an interim answer module **460**, and answer prioritization module **462**, and a preliminary answer quality module **464**. Generally, an embodiment of this invention presents solutions where the answer resolution module **306** supports producing an answer for interpreted information **344**.

(139) In an example of operation of the providing of the answer, the interim answer module **460** analyzes the interpreted information **344** based on question information **346** and inferred question information **352** to produce interim answers **466** (e.g., answers to stated and/or inferred questions without regard to rules that is subject to further refinement). The answer prioritization module **462** analyzes the interim answers **466** based on answer rules **322** to produce preliminary answer **354**. For example, the answer prioritization module **462** identifies all possible answers from the interim answers **466** that conform to the answer rules **322**.

(140) The preliminary answer quality module **464** analyzes the preliminary answers **354** in accordance with the question information **346**, the inferred question information **352**, and the answer rules **322** to produce an answer quality level **356**. For example, for each of the preliminary answers **354**, the preliminary answer quality module **464** may compare a fit of the preliminary answer **354** to a corresponding previous answer and question quality level, calculate the answer quality level **356** based on a level of conformance to the answer rules **322**, calculate the answer quality level **356** based on alignment with the inferred question information **352**, and determine the answer quality level **356** based on an interpreted correlation with the question information **346**.

(141) FIG. **6D** is a logic diagram of an embodiment of a method for producing an answer within a computing system. In particular, a method is presented for use in conjunction with one or more functions and features described in conjunction with FIGS. **1-3**, **4A-4C**, **5E-5F**, **6C**, and also FIG. **6D**. The method includes step **480** where a processing module of one or more processing modules of one or more computing devices of the computing system analyzes received interpreted information based on question information and inferred question information to produce one or more interim answers. For example, the processing module generates potential answers based on

patterns consistent with previously produced knowledge and likelihood of correctness.

(142) The method continues at step **482** where the processing module analyzes the one or more interim answers based on answer rules to produce preliminary answers. For example, the processing module identifies all possible answers from the interim answers that conform to the answer rules. The method continues at step **484** where the processing module analyzes the preliminary answers in accordance with the question information, the inferred question information, and the answer rules to produce an answer quality level. For example, for each of the elementary answers, the processing module may compare a fit of the preliminary answer to a corresponding previous answer-and-answer quality level, calculate the answer quality level based on performance to the answer rules, calculate answer quality level based on alignment with the inferred question information, and determine the answer quality level based on interpreted correlation with the question information.

(143) The method described above in conjunction with the processing module can alternatively be performed by other modules of the computing system **10** of FIG. **1** or by other devices. In addition, at least one memory section (e.g., a computer readable memory, a non-transitory computer readable storage medium, a non-transitory computer readable memory organized into a first memory element, a second memory element, a third memory element, a fourth element section, a fifth memory element etc.) that stores operational instructions can, when executed by one or more processing modules of one or more computing devices (e.g., one or more servers, one or more user devices) of the computing system **10**, cause the one or more computing devices to perform any or all of the method steps described above.

(144) FIG. **7A** is an information flow diagram for interpreting information within a computing system, where sets of entigens **504** are interpreted from sets of identigens **502** which are interpreted from sentences of words **500**. Such identigen entigen intelligence (IP processing of the words (e.g., to IEI process) includes producing one or more of interim knowledge, a preliminary answer, and an answer quality level. For example, the IEI processing includes identifying permutations of identigens of a phrase of a sentence (e.g., interpreting human expressions to produce identigen groupings for each word of ingested content), reducing the permutations of identigens (e.g., utilizing rules to eliminate unfavorable permutations), mapping the reduced permutations of identigens to at least one set of entigens (e.g., most likely identigens become the entigens) to produce the interim knowledge, processing the knowledge in accordance with a knowledge database (e.g., comparing the set of entigens to the knowledge database) to produce a preliminary answer, and generating the answer quality level based on the preliminary answer for a corresponding domain.

(145) Human expressions are utilized to portray facts and fiction about the real world. The real-world includes items, actions, and attributes. The human expressions include textual words, textual symbols, images, and other sensorial information (e.g., sounds). It is known that many words, within a given language, can mean different things based on groupings and orderings of the words. For example, the sentences of words **500** can include many different forms of sentences that mean vastly different things even when the words are very similar.

(146) The present invention presents solutions where the computing system **10** supports producing a computer-based representation of a truest meaning possible of the human expressions given the way that multitudes of human expressions relate to these meanings. As a first step of the flow diagram to transition from human representations of things to a most precise computer representation of the things, the computer identifies the words, phrases, sentences, etc. from the human expressions to produce the sets of identigens **502**. Each identigen includes an identifier of their meaning and an identifier of an instance for each possible language, culture, etc. For example, the words car and automobile share a common meaning identifier but have different instance identifiers since they are different words and are spelled differently. As another example, the word duck is associated both with a bird and an action to elude even though they are spelled the same. In

this example the bird duck has a different meaning than the elude duck and as such each has a different meaning identifier of the corresponding identigens.

(147) As a second step of the flow diagram to transition from human representations of things to the most precise computer representation of the things, the computer extracts meaning from groupings of the identified words, phrases, sentences, etc. to produce the sets of entigens **504**. Each entigen includes an identifier of a single conceivable and perceivable thing in space and time (e.g., independent of language and other aspects of the human expressions). For example, the words car and automobile are different instances of the same meaning and point to a common shared entigen. As another example, the word duck for the bird meaning has an associated unique entigen that is different than the entigen for the word duck for the elude meaning.

(148) As a third step of the flow diagram to transition from human expressions of things to the most precise computer representation of the things, the computer reasons facts from the extracted meanings. For example, the computer maintains a fact-based of the valid meanings from the valid groupings or sets of entigens so as to support subsequent inferences, deductions, rationalizations of posed questions to produce answers that are aligned with a most factual view. As time goes on, and as an entigen has been identified, it can encounter an experience transformations in time, space, attributes, actions, and words which are used to identify it without creating contradictions or ever losing its identity.

(149) FIG. 7B is a relationship block diagram illustrating an embodiment of relationships between things **510** and representations of things **512** within a computing system. The things **510** includes conceivable and perceivable things including actions **522**, items **524**, and attributes **526**. The representation of things **512** includes representations of things used by humans **514** and representation of things used by of computing devices **516** of embodiments of the present invention. The things **510** relates to the representations of things used by humans **514** where the invention presents solutions where the computing system **10** supports mapping the representations of things used by humans **514** to the representations of things used by computing devices **516**, where the representations of things used by computing devices **516** map back to the things **510**.

(150) The representations of things used by humans **514** includes textual words **528**, textual symbols **530**, images (e.g., non-textual) **532**, and other sensorial information **534** (e.g., sounds, sensor data, electrical fields, voice inflections, emotion representations, facial expressions, whistles, etc.). The representations of things used by computing devices **516** includes identigens **518** and entigens **520**. The representations of things used by humans **514** maps to the identigens **518** and the identigens **518** map to the entigens **520**. The entigens **520** uniquely maps back to the things **510** in space and time, a truest meaning the computer is looking for to create knowledge and answer questions based on the knowledge.

(151) To accommodate the mapping of the representations of things used by humans **514** to the identigens **518**, the identigens **518** is partitioned into actenymys **544** (e.g., actions), itenymys **546** (e.g., items), attrenymys **548** (e.g., attributes), and functionals **550** (e.g., that join and/or describe). Each of the actenymys **544**, itenymys **546**, and attrenymys **548** may be further classified into singulatums **552** (e.g., identify one unique entigen) and pluratums **554** (e.g., identify a plurality of entigens that have similarities).

(152) Each identigen **518** is associated with an identigens identifier (IDN) **536**. The IDN **536** includes a meaning identifier (ID) **538** portion, an instance ID **540** portion, and a type ID **542** portion. The meaning ID **538** includes an identifier of common meaning. The instance ID **540** includes an identifier of a particular word and language. The type ID **542** includes one or more identifiers for actenymys, itenymys, attrenymys, singulatums, pluratums, a time reference, and any other reference to describe the IDN **536**. The mapping of the representations of things used by humans **514** to the identigens **518** by the computing system of the present invention includes determining the identigens **518** in accordance with logic and instructions for forming groupings of words.



(153) Generally, an embodiment of this invention presents solutions where the identigens **518** map to the entigens **520**. Multiple identigens may map to a common unique antigen. The mapping of the identigens **518** to the entigens **520** by the computing system of the present invention includes determining entigens in accordance with logic and instructions for forming groupings of identigens.

(154) FIG. 7C is a diagram of an embodiment of a synonym words table **570** within a computing system, where the synonym words table **570** includes multiple fields including textual words **572**, identigens **518**, and entigens **520**. The identigens **518** includes fields for the meaning identifier (ID) **538** and the instance ID **540**. The computing system of the present invention may utilize the synonym words table **570** to map textual words **572** to identigens **518** and map the identigens **518** to entigens **520**. For example, the words car, automobile, auto, bil (Swedish), carro (Spanish), and bil (Danish) all share a common meaning but are different instances (e.g., different words and languages). The words map to a common meaning ID but to individual unique instant identifiers. Each of the different identigens map to a common antigen since they describe the same thing.

(155) FIG. 7D is a diagram of an embodiment of a polysemous words table **576** within a computing system, where the polysemous words table **576** includes multiple fields including textual words **572**, identigens **518**, and entigens **520**. The identigens **518** includes fields for the meaning identifier (ID) **538** and the instance ID **540**. The computing system of the present invention may utilize the polysemous words table **576** to map textual words **572** to identigens **518** and map the identigens **518** to entigens **520**. For example, the word duck maps to four different identigens since the word duck has four associated different meanings (e.g., bird, fabric, to submerge, to elude) and instances. Each of the identigens represent different things and hence map to four different entigens.

(156) FIG. 7E is a diagram of an embodiment of transforming words into groupings within a computing system that includes a words table **580**, a groupings of words section to validate permutations of groupings, and a groupings table **584** to capture the valid groupings. The words table **580** includes multiple fields including textual words **572**, identigens **518**, and entigens **520**. The identigens **518** includes fields for the meaning identifier (ID) **538**, the instance ID **540**, and the type ID **542**. The computing system of the present invention may utilize the words table **580** to map textual words **572** to identigens **518** and map the identigens **518** to entigens **520**. For example, the word pilot may refer to a flyer and the action to fly. Each meaning has a different antigen and different antigen.

(157) The computing system the present invention may apply rules to the fields of the words table **580** to validate various groupings of words. Those that are invalid are denoted with a “X” while those that are valid are associated with a check mark. For example, the grouping “pilot Tom” is invalid when the word pilot refers to flying and Tom refers to a person. The antigen combinations for the flying pilot and the person Tom are denoted as invalid by the rules. As another example, the grouping “pilot Tom” is valid when the word pilot refers to a flyer and Tom refers to the person. The antigen combinations for the flyer pilot and the person Tom are denoted as valid by the rules.

(158) The groupings table **584** includes multiple fields including grouping ID **586**, word strings **588**, identigens **518**, and entigens **520**. The computing system of the present invention may produce the groupings table **584** as a stored fact base for valid and/or invalid groupings of words identified by their corresponding identigens. For example, the valid grouping “pilot Tom” referring to flyer Tom the person is represented with a grouping identifier of 3001 and identity and identifiers 150.001 and 457.001. The antigen field **520** may indicate associated entigens that correspond to the identigens. For example, antigen e717 corresponds to the flyer pilot meaning and antigen e61 corresponds to the time the person meaning. Alternatively, or in addition to, the antigen field **520** may be populated with a single antigen identifier (ENI).

(159) The word strings field **588** may include any number of words in a string. Different ordering of the same words can produce multiple different strings and even different meanings and hence entigens. More broadly, each entry (e.g., role) of the groupings table **584** may refer to groupings of words, two or more word strings, an idiom, just identigens, just entigens, and/or any combination

of the preceding elements. Each entry has a unique grouping identifier. An idiom may have a unique grouping ID and include identifiers of original word identigens and replacing identigens associated with the meaning of the idiom not just the meaning of the original words. Valid groupings may still have ambiguity on their own and may need more strings and/or context to select a best fit when interpreting a truest meaning of the grouping.

(160) FIG. 8A is a data flow diagram for accumulating knowledge within a computing system, where a computing device, at a time= $t_0$ , ingests and processes facts **598** at a step **590** based on rules **316** and fact base information **600** to produce groupings **602** for storage in a fact base **592** (e.g., words, phrases, word groupings, identigens, entigens, quality levels). The facts **598** may include information from books, archive data, Central intelligence agency (CIA) world fact book, trusted content, etc. The ingesting may include filtering to organize and promote better valid groupings detection (e.g., considering similar domains together). The groupings **602** includes one or more of groupings identifiers, identigen identifiers, entigen identifiers, and estimated fit quality levels. The processing step **590** may include identifying identigens from words of the facts **598** in accordance with the rules **316** and the fact base info **600** and identifying groupings utilizing identigens in accordance with rules **316** and fact base info **600**.

(161) Subsequent to ingestion and processing of the facts **598** to establish the fact base **592**, at a time= $t_1+$ , the computing device ingests and processes new content **604** at a step **594** in accordance with the rules **316** and the fact base information **600** to produce preliminary grouping **606**. The new content may include updated content (e.g., timewise) from periodicals, newsfeeds, social media, etc. The preliminary grouping **606** includes one or more of preliminary groupings identifiers, preliminary identigen identifiers, preliminary entigen identifiers, estimated fit quality levels, and representations of unidentified words.

(162) The computing device validates the preliminary groupings **606** at a step **596** based on the rules **316** and the fact base info **600** to produce updated fact base info **608** for storage in the fact base **592**. The validating includes one or more of reasoning a fit of existing fact base info **600** with the new preliminary grouping **606**, discarding preliminary groupings, updating just time frame information associated with an entry of the existing fact base info **600** (e.g., to validate knowledge for the present), creating new entigens, and creating a median entigen to summarize portions of knowledge within a median indicator as a quality level indicator (e.g., suggestive not certain).

(163) Storage of the updated fact base information **608** captures patterns that develop by themselves instead of searching for patterns as in prior art artificial intelligence systems. Growth of the fact base **592** enables subsequent reasoning to create new knowledge including deduction, induction, inference, and inferential sentiment (e.g., a chain of sentiment sentences). Examples of sentiments includes emotion, beliefs, convictions, feelings, judgments, notions, opinions, and views.

(164) FIG. 8B is a diagram of an embodiment of a groupings table **620** within a computing system. The groupings table **620** includes multiple fields including grouping ID **586**, word strings **588**, an IF string **622** and a THEN string **624**. Each of the fields for the IF string **622** and the THEN string **624** includes fields for an identigen (IDN) string **626**, and an entigen (ENI) string **628**. The computing system of the present invention may produce the groupings table **620** as a stored fact base to enable IF THEN based inference to generate a new knowledge inference **630**.

(165) As a specific example, grouping **5493** points out the logic of IF someone has a tumor, THEN someone is sick and the grouping **5494** points of the logic that IF someone is sick, THEN someone is sad. As a result of utilizing inference, the new knowledge inference **630** may produce grouping **5495** where IF someone has a tumor, THEN someone is possibly sad (e.g., or is sad).

(166) FIG. 8C is a data flow diagram for answering questions utilizing accumulated knowledge within a computing system, where a computing device ingests and processes question information **346** at a step **640** based on rules **316** and fact base info **600** from a fact base **592** to produce preliminary grouping **606**. The ingesting and processing questions step **640** includes identifying

identigens from words of a question in accordance with the rules **316** and the fact base information **600** and may also include identifying groupings from the identified identigens in accordance with the rules **316** and the fact base information **600**.

(167) The computing device validates the preliminary grouping **606** at a step **596** based on the rules **316** and the fact base information **600** to produce identified element information **340**. For example, the computing device reasons fit of existing fact base information with new preliminary groupings **606** to produce the identified element information **340** associated with highest quality levels. The computing device interprets a question of the identified element information **340** at a step **642** based on the rules **316** and the fact base information **600**. The interpreting of the question may include separating new content from the question and reducing the question based on the fact base information **600** and the new content.

(168) The computing device produces preliminary answers **354** from the interpreted information **344** at a resolve answer step **644** based on the rules **316** and the fact base information **600**. For example, the computing device compares the interpreted information **344** two the fact base information **600** to produce the preliminary answers **354** with highest quality levels utilizing one or more of deduction, induction, inferencing, and applying inferential sentiments logic. Alternatively, or in addition to, the computing device may save new knowledge identified from the question information **346** to update the fact base **592**.

(169) FIG. **8D** is a data flow diagram for answering questions utilizing interference within a computing system that includes a groupings table **648** and the resolve answer step **644** of FIG. **8C**. The groupings table **648** includes multiple fields including fields for a grouping (GRP) identifier (ID) **586**, word strings **588**, an identigen (IDN) string **626**, and an entigen (ENI) **628**. The groupings table **648** may be utilized to build a fact base to enable resolving a future question into an answer. For example, the grouping **8356** notes knowledge that Michael sleeps eight hours and grouping **8357** notes that Michael usually starts to sleep at 11 PM.

(170) In a first question example that includes a question “Michael sleeping?”, the resolve answer step **644** analyzes the question from the interpreted information **344** in accordance with the fact base information **600**, the rules **316**, and a real-time indicator that the current time is 1 AM to produce a preliminary answer of “possibly YES” when inferring that Michael is probably sleeping at 1 AM when Michael usually starts sleeping at 11 PM and Michael usually sleeps for a duration of eight hours.

(171) In a second question example that includes the question “Michael sleeping?”, the resolve answer step **644** analyzes the question from the interpreted information **344** in accordance with the fact base information **600**, the rules **316**, and a real-time indicator that the current time is now 11 AM to produce a preliminary answer of “possibly NO” when inferring that Michael is probably not sleeping at 11 AM when Michael usually starts sleeping at 11 PM and Michael usually sleeps for a duration of eight hours.

(172) FIG. **8E** is a relationship block diagram illustrating another embodiment of relationships between things and representations of things within a computing system. While things in the real world are described with words, it is often the case that a particular word has multiple meanings in isolation. Interpreting the meaning of the particular word may hinge on analyzing how the word is utilized in a phrase, a sentence, multiple sentences, paragraphs, and even whole documents or more. Describing and stratifying the use of words, word types, and possible meanings help in interpreting a true meaning.

(173) Humans utilize textual words **528** to represent things in the real world. Quite often a particular word has multiple instances of different grammatical use when part of a phrase of one or more sentences. The grammatical use **649** of words includes the nouns and the verbs, and also includes adverbs, adjectives, pronouns, conjunctions, prepositions, determiners, exclamations, etc.

(174) As an example of multiple grammatical use, the word “bat” in the English language can be utilized as a noun or a verb. For instance, when utilized as a noun, the word “bat” may apply to a

baseball bat or may apply to a flying “bat.” As another instance, when utilized as a verb, the word “bat” may apply to the action of hitting or batting an object, i.e., “bat the ball.”

(175) To stratify word types by use, the words are associated with a word type (e.g., type identifier **542**). The word types include objects (e.g., items **524**), characteristics (e.g., attributes **526**), actions **522**, and the functionals **550** for joining other words and describing words. For example, when the word “bat” is utilized as a noun, the word is describing the object of either the baseball bat or the flying bat. As another example, when the word “bat” is utilized as a verb, the word is describing the action of hitting.

(176) To determine possible meanings, the words, by word type, are mapped to associative meanings (e.g., identigens **518**). For each possible associative meaning, the word type is documented with the meaning and further with an identifier (ID) of the instance (e.g., an identigen identifier).

(177) For the example of the word “bat” when utilized as a noun for the baseball bat, a first identigen identifier **536-1** includes a type ID **542-1** associated with the object **524**, an instance ID **540-1** associated with the first identigen identifier (e.g., unique for the baseball bat), and a meaning ID **538-1** associated with the baseball bat. For the example of the word “bat” when utilized as a noun for the flying bat, a second identigen identifier **536-2** includes a type ID **542-1** associated with the object **524**, an instance ID **540-2** associated with the second identigen identifier (e.g., unique for the flying bat), and a meaning ID **538-2** associated with the flying bat. For the example of the word “bat” when utilized as a verb for the bat that hits, a third identigen identifier **536-2** includes a type ID **542-2** associated with the actions **522**, an instance ID **540-3** associated with the third identigen identifier (e.g., unique for the bat that hits), and a meaning ID **538-3** associated with the bat that hits.

(178) With the word described by a type and possible associative meanings, a combination of full grammatical use of the word within the phrase etc., application of rules, and utilization of an ever-growing knowledge database that represents knowledge by linked entigens, the absolute meaning (e.g., entigen **520**) of the word is represented as a unique entigen. For example, a first entigen e1 represents the absolute meaning of a baseball bat (e.g., a generic baseball bat not a particular baseball bat that belongs to anyone), a second entigen e2 represents the absolute meaning of the flying bat (e.g., a generic flying bat not a particular flying bat), and a third entigen e3 represents the absolute meaning of the verb bat (e.g., to hit).

(179) An embodiment of methods to ingest text to produce absolute meanings for storage in a knowledge database are discussed in greater detail with reference to FIGS. **8F-H**. Those embodiments further discuss the discerning of the grammatical use, the use of the rules, and the utilization of the knowledge database to definitively interpret the absolute meaning of a string of words.

(180) Another embodiment of methods to respond to a query to produce an answer based on knowledge stored in the knowledge database are discussed in greater detail with reference to FIGS. **8J-L**. Those embodiments further discuss the discerning of the grammatical use, the use of the rules, and the utilization of the knowledge database to interpret the query. The query interpretation is utilized to extract the answer from the knowledge database to facilitate forming the query response.

(181) FIGS. **8F** and **8G** are schematic block diagrams of another embodiment of a computing system that includes the content ingestion module **300** of FIG. **5E**, the element identification module **302** of FIG. **5E**, the interpretation module **304** of FIG. **5E**, the IEI control module **308** of FIG. **5E**, and the SS memory **96** of FIG. **2**. Generally, an embodiment of this invention provides presents solutions where the computing system **10** supports processing content to produce knowledge for storage in a knowledge database.

(182) The processing of the content to produce the knowledge includes a series of steps. For example, a first step includes identifying words of an ingested phrase to produce tokenized words.

As depicted in FIG. 8F, a specific example of the first step includes the content ingestion module **300** comparing words of source content **310** to dictionary entries to produce formatted content **314** that includes identifiers of known words. Alternatively, when a comparison is unfavorable, the temporary identifier may be assigned to an unknown word. For instance, the content ingestion module **300** produces identifiers associated with the words “the”, “black”, “bat”, “eats”, and “fruit” when the ingested phrase includes “The black bat eats fruit”, and generates the formatted content **314** to include the identifiers of the words.

(183) A second step of the processing of the content to produce the knowledge includes, for each tokenized word, identifying one or more identigens that correspond the tokenized word, where each identigen describes one of an object, a characteristic, and an action. As depicted in FIG. 8F, a specific example of the second step includes the element identification module **302** performing a look up of identigen identifiers, utilizing an element list **332** and in accordance with element rules **318**, of the one or more identigens associated with each tokenized word of the formatted content **314** to produce identified element information **340**.

(184) A unique identifier is associated with each of the potential object, the characteristic, and the action (OCA) associated with the tokenized word (e.g. sequential identigens). For instance, the element identification module **302** identifies a functional symbol for “the”, identifies a single identigen for “black”, identifies two identigens for “bat” (e.g., baseball bat and flying bat), identifies a single identigen for “eats”, and identifies a single identigen for “fruit.” When at least one tokenized word is associated with multiple identigens, two or more permutations of sequential combinations of identigens for each tokenized word result. For example, when “bat” is associated with two identigens, two permutations of sequential combinations of identigens result for the ingested phrase.

(185) A third step of the processing of the content to produce the knowledge includes, for each permutation of sequential combinations of identigens, generating a corresponding equation package (i.e., candidate interpretation), where the equation package includes a sequential linking of pairs of identigens (e.g., relationships), where each sequential linking pairs a preceding identigen to a next identigen, and where an equation element describes a relationship between paired identigens (OCAs) such as describes, acts on, is a, belongs to, did, did to, etc. Multiple OCAs occur for a common word when the word has multiple potential meanings (e.g., a baseball bat, a flying bat).

(186) As depicted in FIG. 8F, a specific example of the third step includes the interpretation module **304**, for each permutation of identigens of each tokenized word of the identified element information **340**, the interpretation module **304** generates, in accordance with interpretation rules **320** and a groupings list **334**, an equation package to include one or more of the identifiers of the tokenized words, a list of identifiers of the identigens of the equation package, a list of pairing identifiers for sequential pairs of identigens, and a quality metric associated with each sequential pair of identigens (e.g., likelihood of a proper interpretation). For instance, the interpretation module **304** produces a first equation package that includes a first identigen pairing of a black bat (e.g., flying bat with a higher quality metric level), the second pairing of bat eats (e.g., the flying bat eats, with a higher quality metric level), and a third pairing of eats fruit, and the interpretation module **304** produces a second equation package that includes a first pairing of a black bat (e.g., baseball bat, with a neutral quality metric level), the second pairing of bat eats (e.g., the baseball bat eats, with a lower quality metric level), and a third pairing of eats fruit.

(187) A fourth step of the processing of the content to produce the knowledge includes selecting a surviving equation package associated with a most favorable confidence level. As depicted in FIG. 8F, a specific example of the fourth step includes the interpretation module **304** applying interpretation rules **320** (i.e., inference, pragmatic engine, utilizing the identifiers of the identigens to match against known valid combinations of identifiers of entigens) to reduce a number of permutations of the sequential combinations of identigens to produce interpreted information **344** that includes identification of at least one equation package as a surviving interpretation SI (e.g.,

higher quality metric level).

(188) Non-surviving equation packages are eliminated that compare unfavorably to pairing rules and/or are associated with an unfavorable quality metric levels to produce a non-surviving interpretation NSI 2 (e.g., lower quality metric level), where an overall quality metric level may be assigned to each equation package based on quality metric levels of each pairing, such that a higher quality metric level of an equation package indicates a higher probability of a most favorable interpretation. For instance, the interpretation module **304** eliminates the equation package that includes the second pairing indicating that the “baseball bat eats” which is inconsistent with a desired quality metric level of one or more of the groupings list **334** and the interpretation rules **320** and selects the equation package associated with the “flying bat eats” which is favorably consistent with the one or more of the quality metric levels of the groupings list **334** and the interpretation rules **320**.

(189) A fifth step of the processing of the content to produce the knowledge utilizing the confidence level includes integrating knowledge of the surviving equation package into a knowledge database. For example, integrating at least a portion of the reduced OCA combinations into a graphical database to produce updated knowledge. As another example, the portion of the reduced OCA combinations may be translated into rows and columns entries when utilizing a rows and columns database rather than a graphical database. When utilizing the rows and columns approach for the knowledge database, subsequent access to the knowledge database may utilize structured query language (SQL) queries.

(190) As depicted in FIG. **8G**, a specific example of the fifth step includes the IEI control module **308** recovering fact base information **600** from SS memory **96** to identify a portion of the knowledge database for potential modification utilizing the OCAs of the surviving interpretation SI **1** (i.e., compare a pattern of relationships between the OCAs of the surviving interpretation SI **1** from the interpreted information **344** to relationships of OCAs of the portion of the knowledge database including potentially new quality metric levels).

(191) The fifth step further includes determining modifications (e.g., additions, subtractions, further clarifications required when information is complex, etc.) to the portion of the knowledge database based on the new quality metric levels. For instance, the IEI control module **308** causes adding the element “black” as a “describes” relationship of an existing bat OCA and adding the element “fruit” as an eats “does to” relationship to implement the modifications to the portion of the fact base information **600** to produce updated fact base information **608** for storage in the SS memory **96**.

(192) FIG. **8H** is a logic diagram of an embodiment of a method for processing content to produce knowledge for storage within a computing system. In particular, a method is presented for use in conjunction with one or more functions and features described in conjunction with FIGS. **1-8E**, **8F**, and also FIG. **8G**. The method includes step **650** where a processing module of one or more processing modules of one or more computing devices of the computing system identifies words of an ingested phrase to produce tokenized words. The identified includes comparing words to known words of dictionary entries to produce identifiers of known words.

(193) For each tokenized word, the method continues at step **651** where the processing module identifies one or more identigens that corresponds to the tokenized word, where each identigen describes one of an object, a characteristic, and an action (e.g., OCA). The identifying includes performing a lookup of identifiers of the one or more identigens associated with each tokenized word, where the different identifiers associated with each of the potential object, the characteristic, and the action associated with the tokenized word.

(194) The method continues at step **652** where the processing module, for each permutation of sequential combinations of identigens, generates a plurality of equation elements to form a corresponding equation package, where each equation element describes a relationship between sequentially linked pairs of identigens, where each sequential linking pairs a preceding identigen to

a next identigen. For example, for each permutation of identigens of each tokenized word, the processing module generates the equation package to include a plurality of equation elements, where each equation element describes the relationship (e.g., describes, acts on, is a, belongs to, did, did too, etc.) between sequentially adjacent identigens of a plurality of sequential combinations of identigens. Each equation element may be further associated with a quality metric to evaluate a favorability level of an interpretation in light of the sequence of identigens of the equation package. (195) The method continues at step **653** where the processing module selects a surviving equation package associated with most favorable interpretation. For example, the processing module applies rules (i.e., inference, pragmatic engine, utilizing the identifiers of the identigens to match against known valid combinations of identifiers of entigens), to reduce the number of permutations of the sequential combinations of identigens to identify at least one equation package, where non-surviving equation packages are eliminated the compare unfavorably to pairing rules and/or are associated with an unfavorable quality metric levels to produce a non-surviving interpretation, where an overall quality metric level is assigned to each equation package based on quality metric levels of each pairing, such that a higher quality metric level indicates an equation package with a higher probability of favorability of correctness.

(196) The method continues at step **654** where the processing module integrates knowledge of the surviving equation package into a knowledge database. For example, the processing module integrates at least a portion of the reduced OCA combinations into a graphical database to produce updated knowledge. The integrating may include recovering fact base information from storage of the knowledge database to identify a portion of the knowledge database for potential modifications utilizing the OCAs of the surviving equation package (i.e., compare a pattern of relationships between the OCAs of the surviving equation package to relationships of the OCAs of the portion of the knowledge database including potentially new quality metric levels). The integrating further includes determining modifications (e.g., additions, subtractions, further clarifications required when complex information is presented, etc.) to produce the updated knowledge database that is based on fit of acceptable quality metric levels, and implementing the modifications to the portion of the fact base information to produce the updated fact base information for storage in the portion of the knowledge database.

(197) The method described above in conjunction with the processing module can alternatively be performed by other modules of the computing system **10** of FIG. **1** or by other devices. In addition, at least one memory section (e.g., a computer readable memory, a non-transitory computer readable storage medium, a non-transitory computer readable memory organized into a first memory element, a second memory element, a third memory element, a fourth element section, a fifth memory element etc.) that stores operational instructions can, when executed by one or more processing modules of one or more computing devices (e.g., one or more servers, one or more user devices) of the computing system **10**, cause the one or more computing devices to perform any or all of the method steps described above.

(198) FIGS. **8J** and **8K** are schematic block diagrams of another embodiment of a computing system that includes the content ingestion module **300** of FIG. **5E**, the element identification module **302** of FIG. **5E**, the interpretation module **304** of FIG. **5E**, the answer resolution module **306** of FIG. **5E**, and the SS memory **96** of FIG. **2**. Generally, an embodiment of this invention provides solutions where the computing system **10** supports for generating a query response to a query utilizing a knowledge database.

(199) The generating of the query response to the query includes a series of steps. For example, a first step includes identifying words of an ingested query to produce tokenized words. As depicted in FIG. **8J**, a specific example of the first step includes the content ingestion module **300** comparing words of query info **138** to dictionary entries to produce formatted content **314** that includes identifiers of known words. For instance, the content ingestion module **300** produces identifiers for each word of the query “what black animal flies and eats fruit and insects?”

(200) A second step of the generating of the query response to the query includes, for each tokenized word, identifying one or more identigens that correspond the tokenized word, where each identigen describes one of an object, a characteristic, and an action (OCA). As depicted in FIG. 8J, a specific example of the second step includes the element identification module **302** performing a look up of identifiers, utilizing an element list **332** and in accordance with element rules **318**, of the one or more identigens associated with each tokenized word of the formatted content **314** to produce identified element information **340**. A unique identifier is associated with each of the potential object, the characteristic, and the action associated with a particular tokenized word. For instance, the element identification module **302** produces a single identigen identifier for each of the black color, an animal, flies, eats, fruit, and insects.

(201) A third step of the generating of the query response to the query includes, for each permutation of sequential combinations of identigens, generating a corresponding equation package (i.e., candidate interpretation). The equation package includes a sequential linking of pairs of identigens, where each sequential linking pairs a preceding identigen to a next identigen. An equation element describes a relationship between paired identigens (OCAs) such as describes, acts on, is a, belongs to, did, did to, etc.

(202) As depicted in FIG. 8J, a specific example of the third step includes the interpretation module **304**, for each permutation of identigens of each tokenized word of the identified element information **340**, generating the equation packages in accordance with interpretation rules **320** and a groupings list **334** to produce a series of equation elements that include pairings of identigens. For instance, the interpretation module **304** generates a first pairing to describe a black animal, a second pairing to describe an animal that flies, a third pairing to describe flies and eats, a fourth pairing to describe eats fruit, and a fifth pairing to describe eats fruit and insects.

(203) A fourth step of the generating the query response to the query includes selecting a surviving equation package associated with a most favorable interpretation. As depicted in FIG. 8J, a specific example of the fourth step includes the interpretation module **304** applying the interpretation rules **320** (i.e., inference, pragmatic engine, utilizing the identifiers of the identigens to match against known valid combinations of identifiers of entigens) to reduce the number of permutations of the sequential combinations of identigens to produce interpreted information **344**. The interpreted information **344** includes identification of at least one equation package as a surviving interpretation SI **10**, where non-surviving equation packages, if any, are eliminated that compare unfavorably to pairing rules to produce a non-surviving interpretation.

(204) A fifth step of the generating the query response to the query includes utilizing a knowledge database, generating a query response to the surviving equation package of the query, where the surviving equation package of the query is transformed to produce query knowledge for comparison to a portion of the knowledge database. An answer is extracted from the portion of the knowledge database to produce the query response.

(205) As depicted in FIG. 8K, a specific example of the fifth step includes the answer resolution module **306** interpreting the surviving interpretation SI **10** of the interpreted information **344** in accordance with answer rules **322** to produce query knowledge QK **10** (i.e., a graphical representation of knowledge when the knowledge database utilizes a graphical database). For example, the answer resolution module **306** accesses fact base information **600** from the SS memory **96** to identify the portion of the knowledge database associated with a favorable comparison of the query knowledge QK **10** (e.g., by comparing attributes of the query knowledge QK **10** to attributes of the fact base information **600**), and generates preliminary answers **354** that includes the answer to the query. For instance, the answer is “bat” when the associated OCAs of bat, such as black, eats fruit, eats insects, is an animal, and flies, aligns with OCAs of the query knowledge.

(206) FIG. 8L is a logic diagram of an embodiment of a method for generating a query response to a query utilizing knowledge within a knowledge database within a computing system. In particular,



a method is presented for use in conjunction with one or more functions and features described in conjunction with FIGS. 1-8D, 8J, and also FIG. 8K. The method includes step 655 where a processing module of one or more processing modules of one or more computing devices of the computing system identifies words of an ingested query to produce tokenized words. For example, the processing module compares words to known words of dictionary entries to produce identifiers of known words.

(207) For each tokenized word, the method continues at step 656 where the processing module identifies one or more identigens that correspond to the tokenized word, where each identigen describes one of an object, a characteristic, and an action. For example, the processing module performs a lookup of identifiers of the one or more identigens associated with each tokenized word, where different identifiers associated with each permutation of a potential object, characteristic, and action associated with the tokenized word.

(208) For each permutation of sequential combinations of identigens, the method continues at step 657 where the processing module generates a plurality of equation elements to form a corresponding equation package, where each equation element describes a relationship between sequentially linked pairs of identigens. Each sequential linking pairs a preceding identigen to a next identigen. For example, for each permutation of identigens of each tokenized word, the processing module includes all other permutations of all other tokenized words to generate the equation packages. Each equation package includes a plurality of equation elements describing the relationships between sequentially adjacent identigens of a plurality of sequential combinations of identigens.

(209) The method continues at step 658 where the processing module selects a surviving equation package associated with a most favorable interpretation. For example, the processing module applies rules (i.e., inference, pragmatic engine, utilizing the identifiers of the identigens to match against known valid combinations of identifiers of entigens) to reduce the number of permutations of the sequential combinations of identigens to identify at least one equation package. Non-surviving equation packages are eliminated the compare unfavorably to pairing rules.

(210) The method continues at step 659 where the processing module generates a query response to the surviving equation package, where the surviving equation package is transformed to produce query knowledge for locating the portion of a knowledge database that includes an answer to the query. As an example of generating the query response, the processing module interprets the surviving the equation package in accordance with answer rules to produce the query knowledge (e.g., a graphical representation of knowledge when the knowledge database utilizes a graphical database format).

(211) The processing module accesses fact base information from the knowledge database to identify the portion of the knowledge database associated with a favorable comparison of the query knowledge (e.g., favorable comparison of attributes of the query knowledge to the portion of the knowledge database, aligning favorably comparing entigens without conflicting entigens). The processing module extracts an answer from the portion of the knowledge database to produce the query response.

(212) The method described above in conjunction with the processing module can alternatively be performed by other modules of the computing system 10 of FIG. 1 or by other devices. In addition, at least one memory section (e.g., a computer readable memory, a non-transitory computer readable storage medium, a non-transitory computer readable memory organized into a first memory element, a second memory element, a third memory element, a fourth element section, a fifth memory element etc.) that stores operational instructions can, when executed by one or more processing modules of one or more computing devices (e.g., one or more servers, one or more user devices) of the computing system 10, cause the one or more computing devices to perform any or all of the method steps described above.

(213) FIGS. 9A and 9B are schematic block diagrams of another embodiment of a computing

system illustrating an embodiment of a method for interpreting an image within the computing system. The computing system includes the content ingestion module **300** of FIG. 5E, the element identification module **302** of FIG. 5E, the interpretation module **304** of FIG. 5E, the answer resolution module **306** of FIG. 5E, and a knowledge database **664**. The knowledge database **664** may be implemented utilizing one or more of the memories of FIG. 2.

(214) FIG. 9A illustrates an example of operation of the method for interpreting the image where the interpretation module **304** obtains a set of image segment identigens for each of a plurality of image segments of an image to produce a plurality of sets of image segment identigens. A first set of image segment identigens is a set of possible interpretations of a first image segment of the plurality of image segments. The obtaining of the set of image segment identigens for each of the plurality of image segments of the image to produce the plurality of sets of image segment identigens includes a variety of approaches.

(215) A first approach includes the interpretation module **304** receiving the plurality of sets of image segment identigens with the image. For instance, the interpretation module **304** receives sets of image segment identigens **674** along with image **660**.

(216) A second approach includes the interpretation module **304** accessing, using an identifier of the image, the knowledge database **664** to recover the plurality of sets of image segment identigens. For instance, the interpretation module **304** utilizes the identifier of the image **660** to access the knowledge database **664** to recover the sets of image segment identigens **674** when the knowledge database **664** stores the sets of image segment identigens **674** indexed by the identifier of the image.

(217) A third approach includes the interpretation module **304** interpreting a response message to produce the plurality of sets of image segment identigens. The response message is in response to a query that includes a representation of the image. For instance, the interpretation module **304** generates the query to include the identifier of the image **660**, sends the query to the knowledge database **664**, receives the response message, and extracts the sets of image segment identigens **674** from the response message. Alternatively, the interpretation module **304** sends the query to another computing device.

(218) A fourth approach includes interpreting the image to identify the plurality of image segments and accessing, for each image segment of the plurality of image segments, the knowledge database **664** to recover a corresponding set of image segment identigens. For instance, the content ingestion module **300** partitions the image **660** to produce image segments **662** (e.g., of a television, a bed, and an elephant). The element identification module **302** compares (e.g., substantially matches) the image segments **662** to image segment information **668** from the knowledge database **664** to produce identified image segments **670** (e.g., representing the television, the bed, and the elephant). The image segment information **668** includes representations of stored images.

(219) The interpretation module accesses the knowledge database **664** utilizing the identified image segment **670** to recover image segment identigens **672** to produce the sets of image segment identigens **674**. The image segment identigens **672** includes a list of one or more identigens that is associated with each of the identified image segments. For example, the first set of image segment identigens includes identigen #1 for the television, the second set of image segment identigens includes identigen #4 for the bad, and the third set of image segment identigens includes identigen #7 for the elephant.

(220) FIG. 9B further illustrates the example of operation of the method for interpreting the image where the answer resolution module **306** identifies a subset of valid image segment identigens of each set of image segment identigens of the plurality of sets of image segment identigens by applying identigen rules to the plurality of sets of image segment identigens to produce a plurality of subsets of valid image segment identigens. As an example, each valid image segment identigen of a first subset of valid image segment identigens represents a most likely interpretation of the first image segment of the plurality of image segments.

(221) The identifying the subset of valid image segment identigens of each set of image segment identigens of the plurality of sets of image segment identigens includes selecting a first image segment identigen of a first set of image segment identigens of the plurality of sets of image segment identigens for inclusion in the first subset of valid image segment identigens when the identigen rules indicates favorable association between the first image segment identigen and a second image segment identigen of a second set of image segment identigens of the plurality of sets of image segment identigens. For example, the answer resolution module **306** accesses the knowledge database **664** to recover identigen rules **676** and applies the rules to image segment identigens of adjacent sets of image segment identigens to identify valid combinations of the image segment identigens. For instance, the answer resolution module **306** identifies identigen #1 for the television as valid and identifies identigen #4 for the bed as valid when the identigen rule **676** include a favorable association between identigens #1 and #4.

(222) Having identified the subset of valid image segment identigens for each set of image segment identigens, the answer resolution module **306** generates an image entigen group **678** utilizing the plurality of subsets of valid image segment identigens. The image entigen group **678** represents a most likely interpretation of the image **660**.

(223) The generating the image entigen group **678** utilizing the plurality of subsets of valid image segment identigens includes selecting at least one plurality of valid image segment identigens from the plurality of subsets of valid image segment identigens to produce at least one permutation of a plurality of image entigens of the image entigen group. One valid image segment identigen is selected from each subset of valid image segment identigens to produce each of the at least one permutation of the plurality of image entigens of the image entigen group. For instance, the answer resolution module **306** generates the image entigen group **678** to include entigens #1 and #4 when the permutation of entigens #1 and #4 compares favorably to the identigen rule **676**. Having produced the image entigen group **678**, the answer resolution module **306** identifies an invalid set of image segment identigens of the plurality of sets of image segment identigens by applying the identigen rules **676** to the plurality of sets of image segment identigens. For instance, the answer resolution module **306** identifies the third identigen set as invalid when the image segment identigen #7 for the elephant does not favorably pair with any of the other image segment identigens of the other sets of image segment identigens as indicated by the identigen rule **676** (e.g., an elephant is generally not found with a bed or a television).

(224) Having identified the invalid set of image segment identigens, the answer resolution module **306** generates an updated image **680** based on the image **660** and in accordance with the invalid set of image segment identigens. The updated image **680** excludes an image segment that corresponds to the invalid set of image segment identigens. For example, the answer resolution module **306** excludes the third image segment of the elephant from the image **660** to produce an output the updated image **680**.

(225) The method described above can alternatively be performed by other modules of the computing system **10** of FIG. **1** or by other devices. In addition, at least one memory section (e.g., a computer readable memory, a non-transitory computer readable storage medium, a non-transitory computer readable memory organized into a first memory element, a second memory element, a third memory element, a fourth element section, a fifth memory element etc.) that stores operational instructions can, when executed by one or more processing modules of one or more computing devices (e.g., one or more servers, one or more user devices) of the computing system **10**, cause the one or more computing devices to perform any or all of the method steps described above.

(226) FIG. **10A** is a schematic block diagram of another embodiment of a computing system in accordance that includes query content sources **700**, the AI server **20-1** of FIG. **1**, and the user device **12-1** of FIG. **1**. The query content sources **700** include the content sources **16-1** through **16-N** of FIG. **1**. The AI server **20-1** includes the processing module **50-1** of FIG. **2** and the SS memory

**96** of FIG. 2. The processing module **50-1** includes the collections module **120** of FIG. 4A, the IEI module **122** of FIG. 4A, and the query module **124** of FIG. 4A. Generally, this invention presents solutions where the computing system **10** supports processing a query.

(227) The processing of the query includes a series of steps. For example, a first step includes IEI processing an exclusion statement associated with the query to produce a knowledge base restriction when subsequently utilizing a knowledge base to produce a query response to the query. The query is with regards to a question and/or a search request. For instance, find drone sightings near a military base.

(228) The exclusion statement includes a sentence that describes at least one parent attribute to exclude from the query response to the query. For instance, exclude military unmanned aircraft vehicles (UAVs) from the finding of the drone sightings. The knowledge base restriction excludes one or more of identifying attributes of entigens of the knowledge base when subsequently producing the query response. Alternatively, the knowledge base restriction identifies of a portion of the knowledge base to exclude. Further alternatively, the knowledge base restriction generates an updated knowledge base that excludes the portion of the knowledge base to exclude, identifying another portion of the knowledge base that is associated with the query and is not excluded based on the exclusion statement.

(229) The example of the first step further includes IEI processing the exclusion statement to produce an exclusion entigen group (e.g., associated with exclude military UAVs), comparing the exclusion entigen group to groups of entigens in the knowledge base to locate a portion of the knowledge base for exclusion, and identifying each entigen of the portion of the knowledge base for exclusion to produce the knowledge base restriction. As illustrated in FIG. 10A, a specific example includes the IEI module **122** receiving an IEI request **244** from the query module **124**, where the query module **124** receives a query with exclusion request **703** from the user device **12-1** that includes the query and the exclusion statement.

(230) The query module **124** issues the IEI request **244** to the IEI module **122**, where the IEI request **244** includes content of the query with exclusion request **703**. The IEI module **122** IEI processes the exclusion statement utilizing fact base information **600** (e.g., knowledge base) from the SS memory **96** to produce the exclusion entigen group, compares the exclusion entigen group to groups of entigens of the knowledge base by accessing the fact base information **600** to locate the portion of the knowledge base for exclusion, and identifies each entigen of the portion of the knowledge base for exclusion to produce the knowledge base restriction.

(231) A second step of the processing of the query includes obtaining sufficient knowledge to produce the query response with favorable results. For example, determine that the knowledge base has insufficient knowledge to facilitate producing the query response with favorable results (i.e., produce a preliminary query response, determine that a quality level of the preliminary query response falls below a minimum quality threshold level, the query is with respect to a future time frame thus requiring new knowledge). The obtaining the sufficient knowledge further includes identifying a content source, obtaining further content from the content sources, IEI processing the further content to produce incremental knowledge, and integrating the incremental knowledge with the knowledge base to produce an updated knowledge base.

(232) As illustrated in FIG. 10A, a specific example of the second step includes, the IEI module **122** determining that the query is associated with a subsequent time frame, identifying content sources **16-1** through **16-N** of the query content sources **700**, and causing gathering of further content that is not excluded to produce further knowledge. The IEI module **122** issues a collections request **132** to the collections module **120** (e.g., including the knowledge base restriction), where the collections module **120** issues a query with exclusion content request **705** (e.g., to request content that is not restricted) to the query content sources **700**.

(233) The collections module **120** receives a query with exclusion content response **707**, and issues a collections response **134** to the IEI module **122** including the further content. The IEI module **122**

IEI processes the further content to produce the incremental knowledge and integrates the incremental knowledge with the fact base information **600** for storage in the SS memory **96**.

(234) A third step of the processing of the query includes IEI processing the query utilizing the knowledge base to produce the query response to the query in accordance with the knowledge base restriction. For example, IEI module **122** processes the query to produce a query entigen group, compares the query entigen group to the groups of entigens in the updated knowledge base in accordance with the knowledge base restriction to locate an unrestricted portion of the knowledge base associated with the query, and generates the query response based on the unrestricted portion of the knowledge base.

(235) As illustrated in FIG. **10A**, a specific example of the third step includes the IEI module **122** IEI processing the query to produce the query entigen group and accessing the fact base information **600** from the SS memory **96** to facilitate comparing the query entigen group to the groups of entigens in the updated knowledge base in accordance with the knowledge base restriction to locate the unrestricted portion of the knowledge base associated with the query. The IEI processing further includes generating the query response based on the unrestricted portion of the knowledge base and issuing an IEI response **246** to the query module **124** that includes the query response. The query module **124** issues a query with exclusion response **709** to the user device **12-1** that includes the query response (e.g., and further includes identifiers of the portions of the knowledge base, etc.).

(236) FIGS. **10B** and **10C** are schematic block diagrams of an embodiment of a portion of knowledge base that includes the fact base information **600** before processing the exclusion statement and the effective knowledge base entigen group **712** after processing the exclusion statement based on the query with exclusion request **703** (e.g., find UAV sightings around a military base that excludes military UAVs). With the military UAVs of the fact base information **600** of FIG. **10B** excluded to produce the effective knowledge base entigen group **712** of FIG. **10C**, the finding of the UAV sightings around the military base enjoys a performance enhancement by excluding a portion of the fact base information **600** associated with military UAVs.

(237) FIG. **10D** is a logic diagram of an embodiment of a method for processing a query within a computing system. In particular, a method is presented for use in conjunction with one or more functions and features described in conjunction with FIGS. **1-8D**, **10A**, and also FIGS. **10B-10C**. The method includes step **720** where a processing module of one or more processing modules of one or more computing devices of the computing system IEI processes an exclusion statement associated with a query to produce a knowledge base restriction when subsequently utilizing a knowledge base to produce a query response to the query. For example, the processing module IEI processes the exclusion statement to produce an exclusion entigen group (e.g., associated with excluded military UAVs), compares the exclusion entigen group to groups of entigens in the knowledge base to locate a portion of the knowledge base for exclusion, and identifies each entigen of the portion of the knowledge base for exclusion to produce the knowledge base restriction.

(238) The method continues at step **722** where the processing module obtains sufficient knowledge to enable producing the query response with favorable results. For example, the processing module determines that the knowledge base has insufficient knowledge to facilitate producing the query response with favorable results (i.e., produce a preliminary query response, determine that a quality level of the preliminary query response falls below a minimum quality threshold level, the query is with respect to a future time frame thus requiring new knowledge). The processing module identifies a content source, causes gathering the further content that is not excluded to produce further knowledge that is not excluded, IEI processes the further content to produce incremental knowledge, and integrates the incremental knowledge with the knowledge base to produce an updated knowledge base.

(239) The method continues at step **724** where the processing module IEI processes the query utilizing the knowledge base to produce the query response to the query in accordance with the

knowledge base restriction. For example, the processing module IEI processes the query to produce a query antigen group, compares the query antigen group to the groups of antigens in the updated knowledge base in accordance with the knowledge base restriction to locate an unrestricted portion of the knowledge base associated with the query. The processing module generates the query response based on the unrestricted portion of the knowledge base.

(240) The method described above in conjunction with the processing module can alternatively be performed by other modules of the computing system **10** of FIG. **1** or by other devices. In addition, at least one memory section (e.g., a computer readable memory, a non-transitory computer readable storage medium, a non-transitory computer readable memory organized into a first memory element, a second memory element, a third memory element, a fourth element section, a fifth memory element etc.) that stores operational instructions can, when executed by one or more processing modules of one or more computing devices (e.g., one or more servers, one or more user devices) of the computing system **10**, cause the one or more computing devices to perform any or all of the method steps described above.

(241) FIGS. **10E** and **10F** are schematic block diagrams of another embodiment of a computing system illustrating an embodiment of a method for generating a response to a query within the computing system. The computing system includes the content ingestion module **300** of FIG. **5E**, the element identification module **302** of FIG. **5E**, the interpretation module **304** of FIG. **5E**, the answer resolution module **306** of FIG. **5E**, and a knowledge database **701**. The knowledge database **701** may be implemented utilizing one or more of the memories of FIG. **2**.

(242) FIG. **10E** illustrates an example of operation of the method for generating the response to the query where a first step includes the content ingestion module **300** obtaining a query **1000**. The query includes a question associated with an exclusion such as in Boolean logic “not” something. The obtaining includes at least one of receiving the query **1000** from a requesting entity (e.g., a user interface associated with the user, a computing device operably coupled to the computing system, etc.) and recovering the query **1000** from the knowledge database **701**. For example, the content ingestion module **300** receives the query **1000** from the requesting entity, where the query **1000** includes a string of words: “UAV-sightings exclude military-UAV-sightings?” In this example the requesting entity is inquiring about sightings of unmanned aerial vehicles that are not military style unmanned aerial vehicles. Asking the question this way utilizes the exclusion rather than specifically asking for alternative UAVs such as commercial and consumer models.

(243) Having obtained the query **1000**, a second step of the example method of operation includes the content ingestion module **300** parsing the string of words of the query **1000** to produce words **1002** of the query. For example, the content ingestion module **300** produces the words **1002** to include the words: “UAV-sightings”, “exclude”, and “military-UAV-sightings” when the query **1000** includes “UAV-sightings exclude military-UAV-sightings?”

(244) With the query **1000** parsed into words **1002**, a third step of the example method of operation includes the element identification module **302** determining a set of identigens for each word of a plurality of words **1002** of the query of a topic to produce a plurality of sets of identigens **708**. A set of identigens of the plurality of sets of identigens represents one or more different meanings of a word of the plurality of words. Each identigen of the set of identigens includes a meaning identifier, an instance identifier, and a time reference. Each meaning identifier associated with the set of identigens represents a different meaning of the one or more different meanings of the word of the plurality of words. Each time reference provides time information when a corresponding different meaning of the one or more different meanings is valid. A first set of identigens of the plurality of sets of identigens is produced for a first word of the plurality of words.

(245) As an example of the producing of the sets of identigens **708**, the element identification module **302** recovers identigen information **706** from the knowledge database **701** based on the words **1002**. For example, the element identification module **302** recovers identigen group #10-11 associated with a “UAV-sightings” meaning of the word “UAV-sightings” to form a first identigen

set. The element identification module **302** further recovers identigens #7 and #8 associated with a “exclude” meaning of the word “exclude” to form a second identigen set. The element identification module **302** further recovers identigen group #9-10-11 associated with a “military-UAV-sightings” meaning of the word “military-UAV-sightings” to form a third identigen set.

(246) Having produced the plurality of sets of identigens **708**, a fourth step of the example method of operation includes the interpretation module **304** identifying an excluding entigen **1008** of an excluding query entigen group **1009**. The excluding entigen **1008** is associated with the excluded entigen group **1009** to be disassociated with the topic with regards to a response to the query. The identifying the excluding entigen **1008** of the excluding query entigen group **1009** includes one or more approaches.

(247) A first approach includes matching a first query entigen of the excluding query entigen group to list of excluding category entigens. For example, the interpretation module **304** matches entigen #8 for the meaning “rule out” to an entry of the list of excluding category entigens to produce the excluding entigen **1008**.

(248) A second approach includes detecting an indication of an excluding category from the knowledge database for the first query entigen of the excluding query entigen group. For example, the interpretation module **304** interprets a record recovered from the knowledge database **701** with regards to the entigen #8 that indicates the excluding category to produce the excluding entigen **1008**.

(249) A third approach includes identifying a set of characteristics from the knowledge database for the first query entigen of the excluding query entigen group. At least one characteristic of the set of characteristics is associated with the excluding category. For example, the interpretation module **304** interprets the record recovered from the knowledge database **701** with regards to the entigen #8 that indicates the characteristic associated with the excluding category.

(250) Having produced the sets of identigens **708** and identified the excluding entigen, a fifth step of the example method of operation includes the interpretation module **304** interpreting, in accordance with identigen pairing rules **710** of the knowledge database **701**, the plurality of sets of identigens **708** to determine a most likely meaning interpretation of the query **1000** and produce an excluding query entigen group **1006** comprising the excluding entigen **1008** of a plurality of query entigens. The knowledge database includes a multitude of entigen groups associated with a multitude of topics. The multitude of topics includes the topic.

(251) Each entigen group of the multitude of entigen groups includes a corresponding plurality of entigens and one or more entigen relationships between at least some of the corresponding plurality of entigens. The excluding query entigen group **1006** represents the most likely meaning interpretation of the query. The excluding entigen **1008** functions to exclude at least a portion of an excluded entigen group to be disassociated with the topic with regards to a response to the query. Each query entigen of the excluding query entigen group corresponds to a selected identigen of the set of identigens having a selected meaning of the one or more different meanings of each word of the plurality of words.

(252) Each query entigen of the excluding query entigen group **1006** represents a single conceivable and perceivable thing in space and time that is independent of language and corresponds to a time reference of the selected identigen associated with the excluding query entigen group. The selected identigen favorably pairs with at least one corresponding sequentially adjacent identigen of another set of identigens of the plurality of sets of identigens based on the identigen pairing rules of the knowledge database.

(253) In an example of the interpreting the plurality of sets of identigens **708** to produce the excluding query entigen group **1006**, the interpretation module **304** receives identigen rules **710** from the knowledge database **7** one with regards to permutations of combinations of the identigens of each of the sets of identigens **708**. For instance, the interpretation module **304** pairs the identigen group #10-11 with identigen #8 in pairs the identigen #8 with the identigen group #9-10-11 in

accordance with the identifying rules **710** to produce the excluding query entigen group **1006**. (254) FIG. **10F** further illustrates the example of operation of the method for generating the response to the query where a sixth step includes the answer resolution module **306** recovering a response entigen group **1010** for the query **1000** from the knowledge database **7** one utilizing the excluding query entigen group **1006** and based on the excluding entigen **1008** and the excluded entigen group **1009**. The response entigen group **1010** includes one or more response entigens and one or more response entigen relationships between at least some of the one or more response entigens. The set of response entigens includes a portion of the excluding query entigen group. The response entigen group provides the response to the query.

(255) The recovering the response entigen group for the query from the knowledge database utilizing the excluding query entigen group and based on the excluding entigen and the excluded entigen group includes a series of sub-steps. A first sub-step includes eliminating the excluding entigen and the excluded entigen group from the excluding query entigen group to produce a remaining subset of query entigens of the excluding query entigen group. For example, the answer resolution module **306** eliminates the entigen #8 for the meaning “rule out” and the entigen group #9-10-11 for the meaning “military-UAV-sightings” from the excluding query entigen group **1006** to produce the remaining subset of query entigens (e.g., entigen group #10-11 for UAV sightings).

(256) A second sub-step includes accessing the knowledge database utilizing the remaining subset of query entigens to identify a superset of response entigens of the response entigen group. For example, the interpretation module **306** interprets entigen information **716** received from the knowledge database **701** with regards to all UAV sightings (e.g., nonmilitary and military) as the superset of response entigens in accordance with the remaining subset of query entigens.

(257) A third sub-step includes removing conflicting response entigens associated with the excluded entigen group in accordance with the excluding entigen from the superset of response entigens to produce the response entigen group. For example, the interpretation module **306** eliminates conflicting entigens associated with sightings of military UAVs in accordance with the excluding entigen to exclude from the superset of response entigens conflicting entigens associated with military UAV sightings.

(258) Alternatively, or in addition to, the recovering the response entigen group for the query from the knowledge database utilizing the excluding query entigen group and based on the excluding entigen and the excluded entigen group further includes a series of alternate sub-steps. A first alternate sub-step includes accessing the knowledge database utilizing the excluded entigen group and in accordance with the excluding entigen to produce a search entigen group. For example, the answer resolution module **306** produces the search entigen group to include non-military UAV sightings. A second alternate sub-step includes accessing the knowledge database utilizing the search entigen group to identify the response entigen group. For example, the answer resolution module **306** interprets further entigen information **716** from the knowledge database **701** with regards to non-military UAV sightings (e.g., sightings 1-3).

(259) Having produced the response entigen group **1010**, a seventh step of the example method of operation includes the answer resolution module **306** generating a query response phrase utilizing the response entigen group as a representation of the response entigen group. For example, the answer resolution module **306** generates the query response phrase to include “non-military UAV sightings include #1 and #2 of tello and #3 of dracon”.

(260) Having generated the query response phrase, the seventh step further includes the answer resolution module **306** outputting at least one of the response entigen group **1010** and the query response phrase to a requesting entity associated with the query.

(261) Alternately, or in addition to, the seventh step further includes the answer resolution module **306** combining the excluding query entigen group with the response entigen group to produce an incremental entigen group associated with the topic. Having produced the incremental entigen group, the answer resolution module **306** facilitates storage of the incremental entigen group in the



knowledge database **701** to provide expanded knowledge of the topic.

(262) The method described above in conjunction with the processing module can alternatively be performed by other modules of the computing system **10** of FIG. **1** or by other devices. In addition, at least one memory section (e.g., a computer readable memory, a non-transitory computer readable storage medium, a non-transitory computer readable memory organized into a first memory element, a second memory element, a third memory element, a fourth element section, a fifth memory element etc.) that stores operational instructions can, when executed by one or more processing modules of one or more computing devices (e.g., one or more servers, one or more user devices) of the computing system **10**, cause the one or more computing devices to perform any or all of the method steps described above.

(263) FIG. **11A** is a schematic block diagram of another embodiment of a computing system that includes query content sources **730**, the AI server **20-1** of FIG. **1**, and the user device **12-1** of FIG. **1**. The query content sources **730** include the content sources **16-1** through **16-N** of FIG. **1**. The AI server **20-1** includes the processing module **50-1** of FIG. **2** and the SS memory **96** of FIG. **2**. The processing module **50-1** includes the collections module **120** of FIG. **4A**, the IEI module **122** of FIG. **4A**, and the query module **124** of FIG. **4A**. Generally, an embodiment of this invention presents solutions where the computing system **10** supports processing a query.

(264) The processing of the query includes a series of steps. For example, a first step includes IEI processing an expansion statement associated with a query to produce a knowledge focus when subsequently utilizing a knowledge base to produce a query response to the query (e.g., locate an unnamed the bomber suspect). The expansion statement includes a sentence that describes at least one attribute to expand upon when searching content and/or knowledge to produce the query response to the query (e.g., utilizing alias names connected to the unnamed bomber suspect).

(265) The knowledge focus includes one or more of identified attributes of entigens of the knowledge base to include when subsequently producing the query response, identity of a portion of the knowledge base to include, generating an updated knowledge base that includes the portion of the knowledge base to include, and identifying further content to acquire to produce knowledge related to the expansion statement. For example, IEI process the expansion statement to produce an expansion entigen group (e.g., associated with alias names connected to the suspect), compare the expansion entigen group to groups of entigens in the knowledge base to locate a portion of the knowledge base for inclusion, and identify each entigen of the portion of the knowledge base for inclusion to produce the knowledge focus.

(266) As a specific example of the first step, the IEI module **122** receives an IEI request **244** from the query module **124**. The query module **124** receives a query with expansion request **732** from the user device **12-1** that includes the query and the expansion statement and issues the IEI request **244** to the IEI module **122**. The IEI request **244** includes the query with expansion request **732**.

(267) The IEI module **122** IEI processes the expansion statement utilizing fact base information **600** (e.g., knowledge base) from the SS memory **96** to produce the expansion entigen group, compares the expansion entigen group to groups of entigens of the knowledge base by accessing the fact base information **600** to locate the portion of the knowledge base for expansion. Having located the portion, the IEI module **122** identifies each entigen of the portion of the knowledge base for expansion to produce the knowledge base focus.

(268) A second step of the processing of the query includes obtaining further knowledge to produce the query response with favorable results. For example, determine that the knowledge base has insufficient knowledge to facilitate producing the query response with favorable results (i.e., produce a preliminary query response, determine that a quality level of the preliminary query response falls below a minimum quality threshold level; the query is with respect to a future time frame thus requiring new knowledge). Having identified the insufficient knowledge, content sources are identified, a content requirement is generated (e.g., hit on alias names from IEI processing the expansion statement), further content is obtained from the content sources utilizing

the content requirement (e.g., alias trigger), the further content is IEI processed to produce incremental knowledge for integration with the knowledge base to produce an updated knowledge base.

(269) As a specific example of the second step, the IEI module **122** determines that the query is associated with a trigger on substantially live content, identifies content sources **16-1** through **16-N** of the query content sources **730**, causes gathering of further content that is associated with the knowledge focus to produce further knowledge. The causing includes the IEI module **122** issuing a collections request **132** to the collections module **120** (e.g., including the knowledge focus of specific alias names). The collections module **120** issues a query with expansion content request **734** (e.g., to request content that is associated with aliases) to the query content sources **730**, receives a query with expansion content response **736**, and issues a collections response **134** to the IEI module **122** including the further content. The IEI module **122** IEI processes the further content to produce the incremental knowledge and integrates the incremental knowledge with the fact base information **600** for storage in the SS memory **96** as the updated knowledge base.

(270) A third step of processing the query includes IEI processing the query utilizing the knowledge base to produce the query response to the query in accordance with the knowledge focus. For example, IEI process the query to produce a query entigen group, compare the query entigen group to the groups of entigens in the updated knowledge base in accordance with the knowledge base focus to locate an area of focus portion of the knowledge base associated with the query, and generate the query response based on the area of focus portion of the knowledge base (e.g., put the puzzle together with inference and deduction rules).

(271) As a specific example of the third step, the IEI module **122** IEI processes the query to produce the query entigen group, accesses the fact base information **600** from the SS memory **96** to facilitate comparing the query entigen group to the groups of entigens in the updated knowledge base in accordance with the knowledge base restriction to locate the unrestricted portion of the knowledge base associated with the query. The IEI module **122** generates the query response based on the unrestricted portion of the knowledge base and issues and IEI response **246** to the query module **124** that includes the query response. The query module **124** issues a query with exclusion response **708** to the user device **12-1** that includes the query response (e.g., and further includes identifiers of the portions of the knowledge base, etc.).

(272) FIGS. **11B** and **11C** are schematic block diagrams of another embodiment of a portion of knowledge base that includes the fact base information **600** before processing the expansion statement and an effective knowledge base entigen group **742** after processing the expansion statement based on the query with expansion request **732** (e.g., locate a main bomber suspect utilizing alias names). With the alias name portions of the fact base information **600** of FIG. **11B** expanded to produce the effective knowledge base entigen group **742** of FIG. **11C**, the finding of the unnamed bomber suspect enjoys a performance enhancement by expanding upon the alias name portion of the fact base information **600** associated with the unnamed bomber suspect.

(273) FIG. **11D** is a logic diagram of an embodiment of another method for processing a query within a computing system. In particular, a method is presented for use in conjunction with one or more functions and features described in conjunction with FIGS. **1-8D**, **11A**, and also FIGS. **11B-11C**. The method includes step **750** where a processing module of one or more processing modules of one or more computing devices of the computing system IEI processes and expansion statement associated with a query to produce a knowledge base focus when subsequently utilizing a knowledge base to produce a query response to the query. For example, the processing module IEI processes the expansion statement to produce an expansion entigen group (e.g., associated with alias names connected to an unnamed bomber suspect), compares the expansion entigen group to groups of entigens in the knowledge base to locate a portion of the knowledge base for inclusion, and identifies each entigen of the portion of the knowledge base for inclusion to produce the knowledge focus.

(274) The method continues at step **752** where the processing module obtains further knowledge to enable producing the query response with favorable results. For example, the processing module determines that the knowledge base has insufficient knowledge to facilitate producing the query response with favorable results (i.e., produce a preliminary query response, determine that a quality level of the pulmonary query response falls below a minimum quality threshold level; the query is with respect to a future time frame thus requiring new knowledge). The processing module further identifies content sources, generates a content requirement (e.g., hit on alias names from IEI processing expansion statement), obtains further content from the content sources utilizing the content requirement (e.g., alias trigger), IEI processes the further content to produce incremental knowledge, and integrates the incremental knowledge with the knowledge base to produce an updated knowledge base.

(275) The method continues at step **754** with a processing module IEI processes the query utilizing the knowledge base to produce the query response to the query in accordance with the knowledge focus. For example, the processing module IEI processes the query to produce a query entigen group, compares the query entigen group to the groups of identigens of the updated knowledge base in accordance with the knowledge base focus to locate an area of focus portion of the knowledge base associated with the query. The processing module generates the query response based on the area focus portion of the knowledge base (e.g., put the puzzle together with inference and deduction rules).

(276) The method described above in conjunction with the processing module can alternatively be performed by other modules of the computing system **10** of FIG. **1** or by other devices. In addition, at least one memory section (e.g., a computer readable memory, a non-transitory computer readable storage medium, a non-transitory computer readable memory organized into a first memory element, a second memory element, a third memory element, a fourth element section, a fifth memory element etc.) that stores operational instructions can, when executed by one or more processing modules of one or more computing devices (e.g., one or more servers, one or more user devices) of the computing system **10**, cause the one or more computing devices to perform any or all of the method steps described above.

(277) FIG. **12A** is a schematic block diagram of another embodiment of a computing system that includes the AI server **20-1** of FIG. **1** and the user device **12-1** of FIG. **1**. The AI server **20-1** includes the processing module **50-1** of FIG. **2** and the SS memory **96** of FIG. **2**. The processing module **50-1** includes the IEI module **122** of FIG. **4A** and the query module **124** of FIG. **4A**. Generally, an embodiment of this invention presents solutions where the computing system **10** supports processing a query.

(278) The processing of the query includes a series of steps. For example, a first step includes determining mandatory inclusive and exclusive attributes associated with a query for subsequent processing with a knowledge base to produce a query response. Mandatory inclusive attributes include descriptors and values of characteristics of an entigen that must be present to satisfy the query. Mandatory exclusive attributes include descriptors and values of characteristics of an entigen that must not be present to satisfy the query. The determining includes extracting from the query and IEI processing the query utilizing the knowledge base to identify the mandatory inclusive and exclusive attributes.

(279) As a specific example of the first step, the IEI module **122** receives an IEI request **244** from the query module **124** that includes a query with inclusive and exclusive attributes request **770** from the user device **12-1**. For instance, the request **770** includes a text string “identify a car line with a high-performance model that does not require all changes.” The IEI module **122** extracts the query (e.g., identify a car line) from the request and extracts a mandatory attribute statement from the request. The mandatory attribute statement identifies the mandatory inclusive attribute (e.g., a performance model) and the mandatory exclusive attribute (e.g., not associated with oil changes).

(280) A second step of processing the query includes IEI processing the query utilizing the

knowledge base to produce a query entigen group. For example, identify a plurality of permutations of identigen groupings. Each permutation pairs sequential identigens associated with possible interpretations of sequential words of the query. The example further includes applying entigen pairing rules, in accordance with the knowledge base, to the plurality of permutations to identify a surviving interpretation to produce the query antigen group.

(281) As a specific example of the second step, the IEI module **122** IEI processes the query utilizing fact base information **600** from the SS memory **96** to produce the query entigen group that will be utilized in a subsequent search for a car line. For instance, the IEI module **122** extracts the query (e.g., identify the car line) from the query and IEI processes the text string of the query to produce the query entigen group.

(282) A third step of the processing of the query includes identifying a portion of the knowledge base associated with the query entigen group. For example, compare the query entigen group to entigens of the knowledge base to identify a portion of the knowledge base associated with the query entigen group. As a specific example of the third step, the IEI module **122** recovers entigen groupings from the fact base information **600** of the SS memory **96** for comparison to the query entigen group and indicates a portion when the recovered entigen substantially matches at least some of the entigens of the query entigen group (e.g., entigens of car lines and attributes).

(283) A fourth step of the processing of the query includes interpreting the portion of the knowledge base associated with the query entigen group in accordance with the mandatory inclusive and exclusive attributes to produce the query response. For example, apply logic (e.g., induction, deduction, inference, etc.) to the entigens of the portion of the knowledge base to locate an answer entigen as the query response. The locating includes excluding entigens and linked entigens associated with the exclusive attribute. The locating further includes including entigens and linked entigens associated with the inclusive attribute.

(284) As a specific example of the fourth step, the IEI module **122** applies the logic to the entigens of the fact base information **600** from the SS memory **96** in accordance with the mandatory inclusive and exclusive attributes to identify the entigen associated with the query response and issues an IEI response **246** to the query module **124** that includes the query response. The query module **124** issues a query with inclusive and exclusive attributes response **772** to the user device **12-1**. For instance, the query response, as depicted in FIG. **12C**, identifies Tessy as a car line with the model that has high performance and does not require oil changes.

(285) FIGS. **12B** and **12C** are schematic block diagrams of another embodiment of a portion of knowledge base within a computing system that includes the fact base information **600** before processing the mandatory attribute statement and an effective knowledge base entigen group **782** after processing the mandatory attribute statement based on the query with inclusive and exclusive attributes request **770** (e.g., identify a car line with a high-performance model that does not require oil changes). With the high-performance and oil requirement portions of the fact base information **600** of FIG. **12B** expanded to produce the effective knowledge base entigen group **782** of FIG. **12C**, the finding of the car line enjoys a performance enhancement by expanding upon the high-performance and oil requirement portions of the fact base information **600** associated with the car line. For instance, while Tessy and Shevy both have high-performance cars, only Tessy as a high-performance model that does not require oil.

(286) FIG. **12D** is a logic diagram of an embodiment of another method for processing a query within a computing system. In particular, a method is presented for use in conjunction with one or more functions and features described in conjunction with FIGS. **1-8D**, **12A**, and also FIGS. **12B-12C**. The method includes step **800** where a processing module of one or more processing modules of one or more computing devices of the computing system determines mandatory inclusive and exclusive attributes associated with the query for subsequent processing utilizing a knowledge base to produce a query response. The determining includes one or more of extracting the mandatory inclusive and exclusive attributes from the query and IEI processing the query utilizing the

knowledge base to identify the mandatory inclusive and exclusive attributes.

(287) The method continues at step **802** where the processing module IEI processes the query utilizing the knowledge base to produce a query entigen group. For example, the processing module identifies a plurality of permutations of identigen groupings, where each permutation pairs sequential identigens associated with possible interpretations of sequential words of the query, and applies entigen pairing rules, in accordance with the knowledge base, to the plurality of permutations to identify a surviving interpretation. The processing module further transforms the surviving interpretation into the query entigen group.

(288) The method continues at step **804** where the processing module identifies a portion of the knowledge base associated with the query entigen group. For example, the processing module compares the query entigen group to entigens of the knowledge base to identify a portion of the knowledge base associated with the query entigen group.

(289) The method continues at step **806** where the processing module interprets a portion of the knowledge base associated with the query entigen group in accordance with the mandatory inclusive and exclusive attributes to produce the query response. For example, the processing module applies logic (e.g., induction, deduction, inference, etc.) to the entigens of the portion of the knowledge base to locate an answer entigen as the query response. The locating further includes excluding of exclusive entigens (e.g., associated with the mandatory exclusive attribute) and other related entigens linked to the exclusive entigens. The locating further includes including of inclusive entigens (e.g., associated with the mandatory inclusive attributes) and other related entigens linked to the inclusive entigens.

(290) The method described above in conjunction with the processing module can alternatively be performed by other modules of the computing system **10** of FIG. **1** or by other devices. In addition, at least one memory section (e.g., a computer readable memory, a non-transitory computer readable storage medium, a non-transitory computer readable memory organized into a first memory element, a second memory element, a third memory element, a fourth element section, a fifth memory element etc.) that stores operational instructions can, when executed by one or more processing modules of one or more computing devices (e.g., one or more servers, one or more user devices) of the computing system **10**, cause the one or more computing devices to perform any or all of the method steps described above.

(291) FIG. **13A** is a schematic block diagram of another embodiment of a computing system that includes the content ingestion module **300** of FIG. **5E**, the element identification module **302** of FIG. **5E**, the interpretation module **304** of FIG. **5E**, and the SS memory **96** of FIG. **2**. Generally, an embodiment of this invention presents solutions where the computing system **10** supports processing an image.

(292) The processing of the image includes a series of steps. For example, a first step includes identifying image elements of an ingested image to produce tokenized image elements. As a specific example of the first step, the content ingestion module **300** processes an image **830** of source content **310** in accordance with element rules **318** and an element list **332** (of images) to produce formatted content **314**, where the image **830** includes a plurality of image elements.

(293) As an instance of the identifying of the image elements, the content ingestion module **300** identifies the source content **310** as a face image (e.g., based on a file name, based on a quick interpretation), selects facial image related element rules **318** and a facial image related element list **332**, partitions the image into the plurality of image elements (e.g., pixel mapping, element identification rules), identifies element relationships between the plurality of image elements (e.g., proximity, relationship, orientation, actions, etc.) for each image element, and compares the image element to image elements of the element list **332** in accordance with the image element rules **318** to produce an identified image element.

(294) In the instance, an image element **832-1** is produced when matching an image element of the image to a stored image of a pair of eyes, an image element **832-2** is produced when matching

another image element of the image to a stored image of a nose, and an image element **832-3** is produced when matching another image element of the image to a stored image of a mouth. In addition, the content ingestion module **300** produces an image element related to the face itself (e.g., all other areas of the face, positioning information of the other image elements with respect to the other areas of the face).

(295) A second step of the processing of the image includes, for each tokenized image element, identifying one or more identigens that correspond the tokenized image element including characteristics of each image element objects and characteristics describing relationships between the objects (e.g., distance between nose and mouth, position on the face itself). Each Identigen describes one of an object, a characteristic, and an action.

(296) As a specific example of the second step to identify the one or more identigens, the element identification module **302** performs a look up of identifiers, utilizing an element list **332** and in accordance with element rules **318**, of the one or more identigens associated with each tokenized image element of the formatted content **314** to produce identified element information **340**. A unique identifier is associated with each of the potential object.

(297) The element identification module **300** further performs estimations to produce the characteristic associated with a particular tokenized image element. For instance, the identified element information **340** is produced to include an eyes identigen **834-1** for the eyes image element **832-1**, a nose identigen **834-2** for the nose image element **832-2**, a mouth identigen **834-3** for the mouth image element **832-3**, an eyes dimension identigen **834-4** is estimated for a distance between the eyes, a nose dimension identigen **834-5** is estimated for a width of the nose, a mouth dimension identigen **834-6** is estimated for a width of the mouth, and further characteristic identigens are produced for further dimensions (e.g., between objects, etc.), colors, shapes, skin texture, blemishes, facial lines, or any other distinguishing facial characteristic. There could be hundreds or more.

(298) A third step of the processing of the image includes, for each permutation of sequential combinations of identigens (e.g., generally just one in this example, but dimensions could have ranges), generating a corresponding equation package (i.e., candidate interpretation). The equation package includes a sequential linking of pairs of the identigens. Each sequential linking pairs a preceding identigen to a next identigen. An equation element describes a relationship between paired identigens (OCA's) such as describes, acts on, is a, belongs to, did, did to, etc. Multiple OCAs occur for a common word when the word has multiple meanings (e.g., a baseball bat, a flying bat).

(299) As a specific example of the third step, for each permutation of identigens of each tokenized image element of the identified element information **340**, the interpretation module **304** includes all other permutations of all other tokenized image elements to generate the equation packages in accordance with interpretation rules **320** and a groupings list **334**. For instance, the interpretation module **304** produces a first pairing of the eyes and nose identigens, a second pairing of the nose and mouth identigens, and further pairings to link dimensions and other characteristics. The fourth step of the processing of the image include selecting a surviving equation package associated with a most favorable interpretation as a surviving interpretation **836**. As a specific example of the fourth step, the interpretation module **304** applies the interpretation rules **320** (i.e., inference, pragmatic engine, utilizing the identifiers of the identigens to match against known valid combinations of identifiers of entigens and characteristics of identigens and relationships of identigens) to reduce the number of permutations of the sequential combinations of identigens to produce interpreted information **344**.

(300) The interpreted information **344** includes identification of at least one equation package as the surviving interpretation **836**, where non-surviving equation packages are eliminated that compare unfavorably to pairing rules and/or are associated with an unfavorable confidence level to produce a non-surviving interpretation. A confidence level may be assigned to each equation

package such that a higher confidence level indicates that equation package with equation elements that are substantially the same in other equation packages, i.e., more consistency.

(301) A fifth step of the processing of the image includes integrating the surviving interpretation **836** into a knowledge base to facilitate subsequent matching of a subject image to the ingested image. As a specific example of the first step, the interpretation module **304**, or another module, locates a portion of the knowledge base that compares favorably to the surviving interpretation **836**, interprets the surviving interpretation **836** (e.g., entigens, links based on characteristics), and updates the portion of the knowledge base with the interpretation to produce an updated knowledge base.

(302) FIG. **13B** is schematic block diagram of another embodiment of a portion of knowledge base that pertains to the processing of the image to produce an effective knowledgebase entigen grouping **840** from the interpreted information **344**, when the interpreted information **344** includes an example text string of “a face with objects: to eyes, nose, a mouth, with characteristics (e.g., dimensions, color, etc.)” The effective knowledgebase entigen group **840** provides a portion of the updated knowledge base to enable subsequent matching of another image of the same face to the stored representation of the face. The matching includes creating an entigen group for the other image in a similar manner as described and comparing the entigen group for the other image to the effective knowledgebase entigen group **840** to produce a positive match (e.g., matching when a substantial number of the characteristics of each object of the face are within a positive match tolerance).

(303) FIG. **13C** is a logic diagram of an embodiment of another method for processing an image within a computing system. In particular, a method is presented for use in conjunction with one or more functions and features described in conjunction with FIGS. **1-8D**, **13A**, and also FIG. **13B**. The method includes step **850** where a processing module of one or more processing modules of one or more computing devices of the computing system identifies image elements of an ingested image to produce tokenized image elements. For example, the processing module processes an ingested image as source content in accordance with element rules and an element list (of images) to produce formatted content.

(304) The image includes a plurality of image elements. The processing module identifies the source content as a face image (e.g., based on a file name, based on an interpretation of the image), select facial image related element rules and a facial image related element list, partition the image into the plurality of image elements (e.g., pixel mapping, element identification rules). The processing module identifies element relationships between the plurality of image elements (e.g., proximity, relationship, orientation, actions, etc.) for each image element and compares the image element to image elements of the element list in accordance with the image element rules to produce an identified image element. For example, a first image element is produced when matching an image element of the image to a stored image of a pair of eyes, a second image element is produced when matching another image element of the image to a stored image of a nose, and a third image element is produced when matching yet another image element of the image to a stored image of a mouth.

(305) For each tokenized image element, the method continues at step **852** where the processing module identifies one or more identigens that correspond to the tokenized image element including characteristics of the image element objects and characteristics describing relationships between the objects. For example, the processing module performs a look up of identifiers, utilizing an element list and in accordance with element rules, of the one or more identigens associated with each tokenized image element of the formatted content to produce identified element information.

(306) A unique identifier is associated with each of the potential object. The processing module performs estimations to produce the characteristic associated with a particular tokenized image element. For instance, the identified element information is produced to include an eyes entigen for the eyes image element, a nose entigen for the nose image element, a mouth entigen for the

mouth image element, an eyes dimension identigen is estimated for a distance between the eyes, a nose dimension identigen is estimated for a width of the nose, a mouth dimension identigen is estimated for a width of the mouth, and further characteristic identigens are produced for further dimensions (e.g., between objects, etc.), colors, shapes, skin texture, blemishes, facial lines, or any other distinguishing facial characteristic. There could be hundreds or more characteristic related identigens.

(307) For each permutation of sequential combinations of identigens, the method continues at step **854** where the processing module generates a corresponding equation package, where the equation package includes a sequential linking of pairs of identigens, where each sequential linking pairs a preceding identigen to a next identigen, and where the equation element describes a relationship between paired identigens. For example, the processing module, for each permutation of identigens of each tokenized image element of the identified element information, includes permutations of all other tokenized image elements to generate the equation packages in accordance with interpretation rules and the groupings list. For instance, the processing module produces a first pairing of the eyes and nose identigens, the second pairing of the nose and mouth identigens, and further pairings to link dimensions and other characteristics.

(308) The method continues at step **856** for the processing module selects a surviving equation package associated with a most favorable interpretation as a surviving interpretation. For example, the processing module applies interpretation rules (i.e., inference, pragmatic engine, utilizing the identifiers of the identigens to match against known valid combinations of identifiers of entigens and characteristics of identigens and relationships of identigens) to reduce the number of permutations of the sequential combinations of identigens to produce interpreted information that includes identification of at least one equation package as the surviving interpretation.

(309) Non-surviving equation packages are eliminated that compare unfavorably to pairing rules and/or are associated with an unfavorable confidence level to produce a non-surviving interpretation. For example, a confidence level may be assigned to each equation package such that a higher confidence level indicates that equation package with equation elements that are substantially the same in other equation packages, i.e., more consistency.

(310) The method continues at step **858** where the processing module integrates the surviving interpretation into a knowledge base to facilitate subsequent matching of a subject image (e.g., a new facial image of an unknown person) to the ingested image. For example, the processing module locates a portion of the knowledge base that compares favorably to the surviving interpretation. The processing module interprets the surviving interpretation (e.g., entigens, linkage between characteristic related entigens) to update the portion of the knowledge base with the interpretation (e.g., adding entigens to the knowledge base when new, replacing contradictory entigens associated with the knowledge base, etc.).

(311) The method described above in conjunction with the processing module can alternatively be performed by other modules of the computing system **10** of FIG. **1** or by other devices. In addition, at least one memory section (e.g., a computer readable memory, a non-transitory computer readable storage medium, a non-transitory computer readable memory organized into a first memory element, a second memory element, a third memory element, a fourth element section, a fifth memory element etc.) that stores operational instructions can, when executed by one or more processing modules of one or more computing devices (e.g., one or more servers, one or more user devices) of the computing system **10**, cause the one or more computing devices to perform any or all of the method steps described above.

(312) It is noted that terminologies as may be used herein such as bit stream, stream, signal sequence, etc. (or their equivalents) have been used interchangeably to describe digital information whose content corresponds to any of a number of desired types (e.g., data, video, speech, text, graphics, audio, etc. any of which may generally be referred to as 'data').

(313) As may be used herein, the terms "substantially" and "approximately" provides an industry-



accepted tolerance for its corresponding term and/or relativity between items. For some industries, an industry-accepted tolerance is less than one percent and, for other industries, the industry-accepted tolerance is 10 percent or more. Other examples of industry-accepted tolerance range from less than one percent to fifty percent. Industry-accepted tolerances correspond to, but are not limited to, component values, integrated circuit process variations, temperature variations, rise and fall times, thermal noise, dimensions, signaling errors, dropped packets, temperatures, pressures, material compositions, and/or performance metrics. Within an industry, tolerance variances of accepted tolerances may be more or less than a percentage level (e.g., dimension tolerance of less than  $\pm 1\%$ ). Some relativity between items may range from a difference of less than a percentage level to a few percent. Other relativity between items may range from a difference of a few percent to magnitude of differences.

(314) As may also be used herein, the term(s) “configured to”, “operably coupled to”, “coupled to”, and/or “coupling” includes direct coupling between items and/or indirect coupling between items via an intervening item (e.g., an item includes, but is not limited to, a component, an element, a circuit, and/or a module) where, for an example of indirect coupling, the intervening item does not modify the information of a signal but may adjust its current level, voltage level, and/or power level. As may further be used herein, inferred coupling (i.e., where one element is coupled to another element by inference) includes direct and indirect coupling between two items in the same manner as “coupled to”.

(315) As may even further be used herein, the term “configured to”, “operable to”, “coupled to”, or “operably coupled to” indicates that an item includes one or more of power connections, input(s), output(s), etc., to perform, when activated, one or more its corresponding functions and may further include inferred coupling to one or more other items. As may still further be used herein, the term “associated with”, includes direct and/or indirect coupling of separate items and/or one item being embedded within another item.

(316) As may be used herein, the term “compares favorably”, indicates that a comparison between two or more items, signals, etc., provides a desired relationship. For example, when the desired relationship is that signal **1** has a greater magnitude than signal **2**, a favorable comparison may be achieved when the magnitude of signal **1** is greater than that of signal **2** or when the magnitude of signal **2** is less than that of signal **1**. As may be used herein, the term “compares unfavorably”, indicates that a comparison between two or more items, signals, etc., fails to provide the desired relationship.

(317) As may be used herein, one or more claims may include, in a specific form of this generic form, the phrase “at least one of a, b, and c” or of this generic form “at least one of a, b, or c”, with more or less elements than “a”, “b”, and “c”. In either phrasing, the phrases are to be interpreted identically. In particular, “at least one of a, b, and c” is equivalent to “at least one of a, b, or c” and shall mean a, b, and/or c. As an example, it means: “a” only, “b” only, “c” only, “a” and “b”, “a” and “c”, “b” and “c”, and/or “a”, “b”, and “c”.

(318) As may also be used herein, the terms “processing module”, “processing circuit”, “processor”, “processing circuitry”, and/or “processing unit” may be a single processing device or a plurality of processing devices. Such a processing device may be a microprocessor, microcontroller, digital signal processor, microcomputer, central processing unit, field programmable gate array, programmable logic device, state machine, logic circuitry, analog circuitry, digital circuitry, and/or any device that manipulates signals (analog and/or digital) based on hard coding of the circuitry and/or operational instructions. The processing module, module, processing circuit, processing circuitry, and/or processing unit may be, or further include, memory and/or an integrated memory element, which may be a single memory device, a plurality of memory devices, and/or embedded circuitry of another processing module, module, processing circuit, processing circuitry, and/or processing unit. Such a memory device may be a read-only memory, random access memory, volatile memory, non-volatile memory, static memory, dynamic memory, flash

memory, cache memory, and/or any device that stores digital information. Note that if the processing module, module, processing circuit, processing circuitry, and/or processing unit includes more than one processing device, the processing devices may be centrally located (e.g., directly coupled together via a wired and/or wireless bus structure) or may be distributedly located (e.g., cloud computing via indirect coupling via a local area network and/or a wide area network). Further note that if the processing module, module, processing circuit, processing circuitry and/or processing unit implements one or more of its functions via a state machine, analog circuitry, digital circuitry, and/or logic circuitry, the memory and/or memory element storing the corresponding operational instructions may be embedded within, or external to, the circuitry comprising the state machine, analog circuitry, digital circuitry, and/or logic circuitry. Still further note that, the memory element may store, and the processing module, module, processing circuit, processing circuitry and/or processing unit executes, hard coded and/or operational instructions corresponding to at least some of the steps and/or functions illustrated in one or more of the Figures. Such a memory device or memory element can be included in an article of manufacture. One or more embodiments have been described above with the aid of method steps illustrating the performance of specified functions and relationships thereof. The boundaries and sequence of these functional building blocks and method steps have been arbitrarily defined herein for convenience of description. Alternate boundaries and sequences can be defined so long as the specified functions and relationships are appropriately performed. Any such alternate boundaries or sequences are thus within the scope and spirit of the claims. Further, the boundaries of these functional building blocks have been arbitrarily defined for convenience of description. Alternate boundaries could be defined as long as the certain significant functions are appropriately performed. Similarly, flow diagram blocks may also have been arbitrarily defined herein to illustrate certain significant functionality.

(319) To the extent used, the flow diagram block boundaries and sequence could have been defined otherwise and still perform the certain significant functionality. Such alternate definitions of both functional building blocks and flow diagram blocks and sequences are thus within the scope and spirit of the claims. One of average skill in the art will also recognize that the functional building blocks, and other illustrative blocks, modules and components herein, can be implemented as illustrated or by discrete components, application specific integrated circuits, processors executing appropriate software and the like or any combination thereof.

(320) In addition, a flow diagram may include a “start” and/or “continue” indication. The “start” and “continue” indications reflect that the steps presented can optionally be incorporated in or otherwise used in conjunction with one or more other routines. In addition, a flow diagram may include an “end” and/or “continue” indication. The “end” and/or “continue” indications reflect that the steps presented can end as described and shown or optionally be incorporated in or otherwise used in conjunction with one or more other routines. In this context, “start” indicates the beginning of the first step presented and may be preceded by other activities not specifically shown. Further, the “continue” indication reflects that the steps presented may be performed multiple times and/or may be succeeded by other activities not specifically shown. Further, while a flow diagram indicates a particular ordering of steps, other orderings are likewise possible provided that the principles of causality are maintained.

(321) The one or more embodiments are used herein to illustrate one or more aspects, one or more features, one or more concepts, and/or one or more examples. A physical embodiment of an apparatus, an article of manufacture, a machine, and/or of a process may include one or more of the aspects, features, concepts, examples, etc. described with reference to one or more of the embodiments discussed herein. Further, from figure to figure, the embodiments may incorporate the same or similarly named functions, steps, modules, etc. that may use the same or different reference numbers and, as such, the functions, steps, modules, etc. may be the same or similar functions, steps, modules, etc. or different ones.

(322) Unless specifically stated to the contra, signals to, from, and/or between elements in a figure of any of the figures presented herein may be analog or digital, continuous time or discrete time, and single-ended or differential. For instance, if a signal path is shown as a single-ended path, it also represents a differential signal path. Similarly, if a signal path is shown as a differential path, it also represents a single-ended signal path. While one or more particular architectures are described herein, other architectures can likewise be implemented that use one or more data buses not expressly shown, direct connectivity between elements, and/or indirect coupling between other elements as recognized by one of average skill in the art.

(323) The term “module” is used in the description of one or more of the embodiments. A module implements one or more functions via a device such as a processor or other processing device or other hardware that may include or operate in association with a memory that stores operational instructions. A module may operate independently and/or in conjunction with software and/or firmware. As also used herein, a module may contain one or more sub-modules, each of which may be one or more modules.

(324) As may further be used herein, a computer readable memory includes one or more memory elements. A memory element may be a separate memory device, multiple memory devices, or a set of memory locations within a memory device. Such a memory device may be a read-only memory, random access memory, volatile memory, non-volatile memory, static memory, dynamic memory, flash memory, cache memory, and/or any device that stores digital information. The memory device may be in a form a solid-state memory, a hard drive memory, cloud memory, thumb drive, server memory, computing device memory, and/or other physical medium for storing digital information.

(325) While particular combinations of various functions and features of the one or more embodiments have been expressly described herein, other combinations of these features and functions are likewise possible. The present disclosure is not limited by the particular examples disclosed herein and expressly incorporates these other combinations.

## Claims

1. A method for execution by a computing device, the method comprises: determining a set of identigens for each word of a plurality of words of a query of a topic to produce a plurality of sets of identigens, wherein a set of identigens of the plurality of sets of identigens represents one or more different meanings of a word of the plurality of words, wherein each identigen of the set of identigens includes a meaning identifier, an instance identifier, and a time reference, wherein each meaning identifier associated with the set of identigens represents a different meaning of the one or more different meanings of the word of the plurality of words, wherein each time reference provides time information when a corresponding different meaning of the one or more different meanings is valid, wherein a first set of identigens of the plurality of sets of identigens is produced for a first word of the plurality of words; interpreting, in accordance with identigen pairing rules of a knowledge database, the plurality of sets of identigens to determine a most likely meaning interpretation of the query and produce an excluding query entigen group comprising an excluding entigen of a plurality of query entigens, wherein the knowledge database includes a multitude of entigen groups associated with a multitude of topics, wherein the multitude of topics includes the topic, wherein each entigen group of the multitude of entigen groups includes a corresponding plurality of entigens and one or more entigen relationships between at least some of the corresponding plurality of entigens, wherein the excluding query entigen group represents the most likely meaning interpretation of the query, wherein the excluding entigen functions to exclude at least a portion of an excluded entigen group to be disassociated with the topic with regards to a response to the query, wherein each query entigen of the excluding query entigen group corresponds to a selected identigen of the set of identigens having a selected meaning of the one or

more different meanings of each word of the plurality of words, wherein each query entigen of the excluding query entigen group represents a single conceivable and perceivable thing in space and time that is independent of language and corresponds to a time reference of the selected identigen associated with the excluding query entigen group, wherein the selected identigen favorably pairs with at least one corresponding sequentially adjacent identigen of another set of identigens of the plurality of sets of identigens based on the identigen pairing rules of the knowledge database; and recovering a response entigen group for the query from the knowledge database utilizing the excluding query entigen group and based on the excluding entigen and the excluded entigen group, wherein the response entigen group includes one or more response entigens and one or more response entigen relationships between at least some of the one or more response entigens, wherein the set of response entigens includes a portion of the excluding query entigen group, wherein the response entigen group provides the response to the query.

2. The method of claim 1 further comprises: identifying the excluding entigen of the excluding query entigen group, wherein the excluding entigen functions is associated with the excluded entigen group to be disassociated with the topic with regards to the response to the query, wherein the identifying the excluding entigen of the excluding query entigen group includes one or more of: matching a first query entigen of the excluding query entigen group to list of excluding category entigens; detecting an indication of an excluding category from the knowledge database for the first query entigen of the excluding query entigen group; and identifying a set of characteristics from the knowledge database for the first query entigen of the excluding query entigen group, wherein at least one characteristic of the set of characteristics is associated with the excluding category.

3. The method of claim 1 further comprises: generating a query response phrase utilizing the response entigen group as a representation of the response entigen group; and outputting, via a user interface of the computing device, at least one of the response entigen group and the query response phrase to a requesting entity associated with the query.

4. The method of claim 1 further comprises: combining the excluding query entigen group with the response entigen group to produce an incremental entigen group associated with the topic; and storing the incremental entigen group in the knowledge database to provide expanded knowledge of the topic.

5. The method of claim 1, wherein the recovering the response entigen group for the query from the knowledge database utilizing the excluding query entigen group and based on the excluding entigen and the excluded entigen group comprises: eliminating the excluding entigen and the excluded entigen group from the excluding query entigen group to produce a remaining subset of query entigens of the excluding query entigen group; accessing the knowledge database utilizing the remaining subset of query entigens to identify a superset of response entigens of the response entigen group; and removing conflicting response entigens associated with the excluded entigen group in accordance with the excluding entigen from the superset of response entigens to produce the response entigen group.

6. The method of claim 1, wherein the recovering the response entigen group for the query from the knowledge database utilizing the excluding query entigen group and based on the excluding entigen and the excluded entigen group further comprises: accessing the knowledge database utilizing the excluded entigen group and in accordance with the excluding entigen to produce a search entigen group; and accessing the knowledge database utilizing the search entigen group to identify the response entigen group.

7. A computing device of a computing system, the computing device comprises: an interface; a local memory; and a processing module operably coupled to the interface and the local memory, wherein the processing module functions to: determine a set of identigens for each word of a plurality of words of a query of a topic to produce a plurality of sets of identigens, wherein a set of identigens of the plurality of sets of identigens represents one or more different meanings of a word of the plurality of words, wherein each identigen of the set of identigens includes a meaning

identifier, an instance identifier, and a time reference, wherein each meaning identifier associated with the set of identigens represents a different meaning of the one or more different meanings of the word of the plurality of words, wherein each time reference provides time information when a corresponding different meaning of the one or more different meanings is valid, wherein a first set of identigens of the plurality of sets of identigens is produced for a first word of the plurality of words; interpret, in accordance with identigen pairing rules of a knowledge database, the plurality of sets of identigens to determine a most likely meaning interpretation of the query and produce an excluding query entigen group comprising an excluding entigen of a plurality of query entigens, wherein the knowledge database includes a multitude of entigen groups associated with a multitude of topics, wherein the multitude of topics includes the topic, wherein each entigen group of the multitude of entigen groups includes a corresponding plurality of entigens and one or more entigen relationships between at least some of the corresponding plurality of entigens, wherein the excluding query entigen group represents the most likely meaning interpretation of the query, wherein the excluding entigen functions to exclude at least a portion of an excluded entigen group to be disassociated with the topic with regards to a response to the query, wherein each query entigen of the excluding query entigen group corresponds to a selected identigen of the set of identigens having a selected meaning of the one or more different meanings of each word of the plurality of words, wherein each query entigen of the excluding query entigen group represents a single conceivable and perceivable thing in space and time that is independent of language and corresponds to a time reference of the selected identigen associated with the excluding query entigen group, wherein the selected identigen favorably pairs with at least one corresponding sequentially adjacent identigen of another set of identigens of the plurality of sets of identigens based on the identigen pairing rules of the knowledge database; and recover, via the interface, a response entigen group for the query from the knowledge database utilizing the excluding query entigen group and based on the excluding entigen and the excluded entigen group, wherein the response entigen group includes one or more response entigens and one or more response entigen relationships between at least some of the one or more response entigens, wherein the set of response entigens includes a portion of the excluding query entigen group, wherein the response entigen group provides the response to the query.

8. The computing device of claim 7, wherein the processing module further functions to: identify the excluding entigen of the excluding query entigen group, wherein the excluding entigen functions is associated with the excluded entigen group to be disassociated with the topic with regards to the response to the query, wherein the processing module identifies the excluding entigen of the excluding query entigen group by one or more of: matching a first query entigen of the excluding query entigen group to list of excluding category entigens; detecting an indication of an excluding category from the knowledge database for the first query entigen of the excluding query entigen group; and identifying a set of characteristics from the knowledge database for the first query entigen of the excluding query entigen group, wherein at least one characteristic of the set of characteristics is associated with the excluding category.

9. The computing device of claim 7, wherein the processing module further functions to: generate a query response phrase utilizing the response entigen group as a representation of the response entigen group; and output, via the interface, at least one of the response entigen group and the query response phrase to a requesting entity associated with the query.

10. The computing device of claim 7, wherein the processing module further functions to: combine the excluding query entigen group with the response entigen group to produce an incremental entigen group associated with the topic; and store, via the interface, the incremental entigen group in the knowledge database to provide expanded knowledge of the topic.

11. The computing device of claim 7, wherein the processing module functions to recover the response entigen group for the query from the knowledge database utilizing the excluding query entigen group and based on the excluding entigen and the excluded entigen group by: eliminating

the excluding entigen and the excluded entigen group from the excluding query entigen group to produce a remaining subset of query entigens of the excluding query entigen group; accessing, via the interface, the knowledge database utilizing the remaining subset of query entigens to identify a superset of response entigens of the response entigen group; and removing conflicting response entigens associated with the excluded entigen group in accordance with the excluding entigen from the superset of response entigens to produce the response entigen group.

12. The computing device of claim 7, wherein the processing module further functions to recover the response entigen group for the query from the knowledge database utilizing the excluding query entigen group and based on the excluding entigen and the excluded entigen group by: accessing, via the interface, the knowledge database utilizing the excluded entigen group and in accordance with the excluding entigen to produce a search entigen group; and accessing, via the interface, the knowledge database utilizing the search entigen group to identify the response entigen group.

13. A non-transitory computer readable memory comprises: a first memory element that stores operational instructions that, when executed by a processing module, causes the processing module to: determine a set of identigens for each word of a plurality of words of a query of a topic to produce a plurality of sets of identigens, wherein a set of identigens of the plurality of sets of identigens represents one or more different meanings of a word of the plurality of words, wherein each identigen of the set of identigens includes a meaning identifier, an instance identifier, and a time reference, wherein each meaning identifier associated with the set of identigens represents a different meaning of the one or more different meanings of the word of the plurality of words, wherein each time reference provides time information when a corresponding different meaning of the one or more different meanings is valid, wherein a first set of identigens of the plurality of sets of identigens is produced for a first word of the plurality of words; a second memory element that stores operational instructions that, when executed by the processing module, causes the processing module to: interpret, in accordance with identigen pairing rules of a knowledge database, the plurality of sets of identigens to determine a most likely meaning interpretation of the query and produce an excluding query entigen group comprising an excluding entigen of a plurality of query entigens, wherein the knowledge database includes a multitude of entigen groups associated with a multitude of topics, wherein the multitude of topics includes the topic, wherein each entigen group of the multitude of entigen groups includes a corresponding plurality of entigens and one or more entigen relationships between at least some of the corresponding plurality of entigens, wherein the excluding query entigen group represents the most likely meaning interpretation of the query, wherein the excluding entigen functions to exclude at least a portion of an excluded entigen group to be disassociated with the topic with regards to a response to the query, wherein each query entigen of the excluding query entigen group corresponds to a selected identigen of the set of identigens having a selected meaning of the one or more different meanings of each word of the plurality of words, wherein each query entigen of the excluding query entigen group represents a single conceivable and perceivable thing in space and time that is independent of language and corresponds to a time reference of the selected identigen associated with the excluding query entigen group, wherein the selected identigen favorably pairs with at least one corresponding sequentially adjacent identigen of another set of identigens of the plurality of sets of identigens based on the identigen pairing rules of the knowledge database; and a third memory element that stores operational instructions that, when executed by the processing module, causes the processing module to: recover a response entigen group for the query from the knowledge database utilizing the excluding query entigen group and based on the excluding entigen and the excluded entigen group, wherein the response entigen group includes one or more response entigens and one or more response entigen relationships between at least some of the one or more response entigens, wherein the set of response entigens includes a portion of the excluding query entigen group, wherein the response entigen group provides the response to the query.

14. The non-transitory computer readable memory of claim 13 further comprises: a fourth memory

element stores operational instructions that, when executed by the processing module, causes the processing module to: identify the excluding entigen of the excluding query entigen group, wherein the excluding entigen functions is associated with the excluded entigen group to be disassociated with the topic with regards to the response to the query, wherein the processing module identifies the excluding entigen of the excluding query entigen group by one or more of: matching a first query entigen of the excluding query entigen group to list of excluding category entigens; detecting an indication of an excluding category from the knowledge database for the first query entigen of the excluding query entigen group; and identifying a set of characteristics from the knowledge database for the first query entigen of the excluding query entigen group, wherein at least one characteristic of the set of characteristics is associated with the excluding category.

15. The non-transitory computer readable memory of claim 13 further comprises: a fifth memory element stores operational instructions that, when executed by the processing module, causes the processing module to: generate a query response phrase utilizing the response entigen group as a representation of the response entigen group; and output at least one of the response entigen group and the query response phrase to a requesting entity associated with the query.

16. The non-transitory computer readable memory of claim 13 further comprises: a sixth memory element stores operational instructions that, when executed by the processing module, causes the processing module to: combine the excluding query entigen group with the response entigen group to produce an incremental entigen group associated with the topic; and store the incremental entigen group in the knowledge database to provide expanded knowledge of the topic.

17. The non-transitory computer readable memory of claim 13, wherein the processing module functions to execute the operational instructions stored by the third memory element to cause the processing module to recover the response entigen group for the query from the knowledge database utilizing the excluding query entigen group and based on the excluding entigen and the excluded entigen group by: eliminating the excluding entigen and the excluded entigen group from the excluding query entigen group to produce a remaining subset of query entigens of the excluding query entigen group; accessing the knowledge database utilizing the remaining subset of query entigens to identify a superset of response entigens of the response entigen group; and removing conflicting response entigens associated with the excluded entigen group in accordance with the excluding entigen from the superset of response entigens to produce the response entigen group.

18. The non-transitory computer readable memory of claim 13, wherein the processing module further functions to execute the operational instructions stored by the third memory element to cause the processing module to recover the response entigen group for the query from the knowledge database utilizing the excluding query entigen group and based on the excluding entigen and the excluded entigen group by: accessing the knowledge database utilizing the excluded entigen group and in accordance with the excluding entigen to produce a search entigen group; and accessing the knowledge database utilizing the search entigen group to identify the response entigen group.

---