

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250261073

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

AIO; Kosuke

---

### **WIRELESS DEVICE, AND WIRELESS COMMUNICATION METHOD OF WIRELESS DEVICE, WIRELESS TERMINAL, AND WIRELESS COMMUNICATION METHOD OF WIRELESS TERMINAL, AND WIRELESS BASE STATION, AND WIRELESS COMMUNICATION METHOD OF WIRELESS BASE STATION**

---

#### **Abstract**

A communication device determines a communication quality with a base station, requests a neighboring base station for a transition judgment information to transmit information to become a judgment criterion of the communication quality to be included in a Beacon signal at a stage before the communication quality degrades to an extent that the base station is immediately switched, and selects a base station with which a communication connection should be established on the basis of the transition judgment information included in the Beacon signal transmitted in response to the transition judgment request. The communication device is applicable to a communication system in the wireless LAN.

---

**Inventors:** AIO; Kosuke (Tokyo, JP)

**Applicant:** Sony Group Corporation (Tokyo, JP)

**Family ID:** 1000008560551

**Assignee:** Sony Group Corporation (Tokyo, JP)

**Appl. No.:** 19/192975

**Filed:** April 29, 2025

#### **Foreign Application Priority Data**

JP 2019-004039

Jan. 15, 2019

#### **Related U.S. Application Data**

parent US continuation 18628811 20240408 parent-grant-document US 12302186 child US 19192975

parent US continuation 17419293 20210629 parent-grant-document US 12082066 WO continuation PCT/JP2019/051423 20191227 child US 18628811

---

## Publication Classification

**Int. Cl.:** **H04W36/30** (20090101); **H04W48/10** (20090101); **H04W48/20** (20090101); **H04W76/10** (20180101); **H04W84/12** (20090101); **H04W88/12** (20090101)

**U.S. Cl.:**

**CPC** **H04W36/30** (20130101); **H04W36/302** (20230501); **H04W48/10** (20130101); **H04W48/20** (20130101); **H04W76/10** (20180201); **H04W88/12** (20130101); **H04W84/12** (20130101)

---

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] The present application is a continuation of U.S. application Ser. No. 18/628,811, filed Apr. 8, 2024, which is a continuation of U.S. application Ser. No. 17/419,293, filed Jun. 29, 2021 (now U.S. Pat. No. 12,082,066), which is based on PCT filing PCT/JP2019/051423, filed Dec. 27, 2019, which claims priority to JP 2019-004039, filed Jan. 15, 2019, the entire contents of each are incorporated herein by reference.

### TECHNICAL FIELD

[0002] The present disclosure relates to a wireless device, and a wireless communication method of the wireless device, a wireless terminal, and a wireless communication method of the wireless terminal, and a wireless base station, and a wireless communication method of the wireless base station, and, in particular, relates to a wireless device, and a wireless communication method of the wireless device, a wireless terminal, and a wireless communication method of the wireless terminal, and a wireless base station, and a wireless communication method of the wireless base station, which are capable of achieving stable communication in response to a change in a communication environment of a wireless local area network (LAN).

### BACKGROUND ART

[0003] These years, in order to expand wireless local area network (LAN) services, use cases of installing a plurality of wireless base stations in buildings such as offices and homes are increasing.

[0004] Therefore, a wireless terminal that starts a wireless LAN service has to select an optimum wireless base station from a plurality of existing wireless base stations.

[0005] Furthermore, in a similar manner for wireless terminals such as laptop computers and smartphones that are considered to use wireless LAN services while moving, it is desirable to switch the connection to the optimum wireless base station in every situation so as not to disconnect the communication, and to make a transition to another basic service set (BSS).

[0006] For this purpose, a technique for the BSS transition while maintaining a stable communication state has been proposed (see Patent Document 1).

### CITATION LIST

Patent Document

[0007] Patent Document 1: Japanese Patent Application Laid-Open No. 2007-158765

### SUMMARY OF THE INVENTION

Problems to be Solved by the Invention

[0008] Generally, it is not until the communication quality (signal to interference plus noise ratio (SINR), a packet success rate, a delay, or the like) of a wireless terminal itself degrades that the wireless terminal starts a process of deciding whether or not to make the BSS transition.

[0009] However, in an environment in which a plurality of wireless base stations is installed close to each other, it is desirable to actively perform a transition process in a case where another base station is capable of ensuring a better communication quality.

[0010] However, in the current situation, what the wireless terminal is capable of directly acquiring from a neighboring wireless base station is only information included in a Beacon signal that has been transmitted by such a wireless base station, and what type of information is to be placed in the Beacon signal depends on the wireless base station.

[0011] For this reason, in a case where the wireless terminal judges the BSS transition using information other than a received electric power (RSSI), unless the Beacon signal that has been transmitted from the wireless base station includes the necessary information, the wireless terminal is not capable of judging the BSS transition.

[0012] For example, Patent Document 1 introduces an example of comparing the number of connected terminals placed in the Beacon signal of a neighboring access point (AP) to judge whether or not to make the BSS transition. However, in a case where the neighboring wireless base station does not place the information regarding the number of connected terminals in the Beacon signal, the BSS transition cannot be judged.

[0013] As an example of making the BSS transition using a judgment criterion other than the received electric power, conceivable is an active scan method in which a wireless terminal issues a Probe Request or a method of entrusting the judgment to a centralized control station capable of collecting information regarding all wireless base stations and controlling them.

[0014] However, in these processes, it takes time to exchange information and the like on the wireless communication, and therefore takes time for the BSS transition.

[0015] For such a reason, the wireless terminal is not capable of judging which wireless base station is desirable to be connected with, by acquiring only the Beacon signal that has been transmitted from the neighboring wireless base station.

[0016] The present disclosure has been made in view of the above circumstances, and in particular, selects an optimum wireless base station with which a communication connection should be established on the basis of information included in a Beacon signal that has been transmitted from a neighboring wireless base station, and achieves stable communication in response to a change in a communication environment.

#### Solutions to Problems

[0017] A wireless device in a first aspect of the present disclosure is a wireless device including a control unit configured to control inclusion information included in a Beacon signal in a wireless base station that is to establish a communication connection for communication with a wireless terminal.

[0018] A wireless communication method in the first aspect of the present disclosure corresponds to a first wireless device.

[0019] In the first aspect of the present disclosure, the inclusion information included in the Beacon signal in the wireless base station that is to establish the communication connection for communication with the wireless terminal is controlled.

[0020] A wireless terminal in a second aspect of the present disclosure is a wireless terminal including a control unit configured to select a new wireless base station with which the wireless terminal is to establish a communication connection on the basis of inclusion information included in a Beacon signal transmitted from a neighboring wireless base station.

[0021] A wireless communication method in the second aspect of the present disclosure corresponds to a second receiving device.

[0022] In the second aspect of the present disclosure, the new wireless base station that is to

establish the communication connection is selected on the basis of the inclusion information included in the Beacon signal transmitted from the neighboring wireless base station.

[0023] A wireless base station in a third aspect of the present disclosure is a wireless base station including a control unit configured to receive a control notification for providing notification of inclusion information to be included in a Beacon signal, and configured to transmit the Beacon signal including the inclusion information on the basis of the control notification.

[0024] A wireless communication method in the third aspect of the present disclosure corresponds to a third wireless base station.

[0025] In the third aspect of the present disclosure, the control notification for providing notification of the inclusion information to be included in the Beacon signal is received, and the Beacon signal including the inclusion information is transmitted on the basis of the control notification.

---

## Description

### BRIEF DESCRIPTION OF DRAWINGS

[0026] FIG. 1 is a diagram illustrating a general communication system.

[0027] FIG. 2 is a diagram illustrating a configuration example of a communication system in the present disclosure.

[0028] FIG. 3 is a diagram illustrating a communication system in a first embodiment in the present disclosure.

[0029] FIG. 4 is a diagram illustrating a configuration example of a controller in the communication system of FIG. 3.

[0030] FIG. 5 is a diagram illustrating a configuration example of a base station in the communication system of FIG. 3.

[0031] FIG. 6 is a diagram illustrating a configuration example of the controller in the communication device in FIG. 3.

[0032] FIG. 7 is a flowchart illustrating a communication control process by the communication system of FIG. 3.

[0033] FIG. 8 is a diagram illustrating a configuration of a BSS transition config setting frame transmitted from a controller to a base station.

[0034] FIG. 9 is a diagram illustrating a configuration of a BSS transition config setting frame transmitted from the base station to the communication device.

[0035] FIG. 10 is a flowchart illustrating a communication quality degradation determination process by the communication device in FIG. 3.

[0036] FIG. 11 is a flowchart illustrating a BSS transition query process by the communication system of FIG. 3.

[0037] FIG. 12 is a flowchart illustrating a BSS transition judgment information request process by the communication system of FIG. 3.

[0038] FIG. 13 is a diagram illustrating a configuration of a BSS transition judgment information request frame transmitted from the communication device to the base station.

[0039] FIG. 14 is a diagram illustrating a configuration of a BSS transition judgment information request frame.

[0040] FIG. 15 is a diagram illustrating a configuration of a Beacon Element control notification frame transmitted from the controller to the base station.

[0041] FIG. 16 is a diagram illustrating a configuration of a Beacon Element decision table.

[0042] FIG. 17 is a diagram illustrating a configuration of a Beacon frame.

[0043] FIG. 18 is a flowchart illustrating a communication quality comparison process by the communication device in FIG. 3.

[0044] FIG. 19 is a flowchart illustrating a communication control process in a case where a signal quality determination process is performed by the base station by the communication device in FIG. 3.

[0045] FIG. 20 is a diagram illustrating an example in which a Mandatory Element ID in the Required Beacon Element ID included in a Beacon Element control notification is set beforehand according to a service in the communication device.

[0046] FIG. 21 is a diagram illustrating a display example of a process result of a signal quality determination process performed by the communication device in FIG. 3.

[0047] FIG. 22 is a flowchart illustrating the communication quality comparison process in a case where a process result of the signal quality determination process is displayed.

[0048] FIG. 23 is a diagram illustrating a communication system in a second embodiment of the present disclosure.

[0049] FIG. 24 is a flowchart illustrating a communication control process by the communication system of FIG. 23.

[0050] FIG. 25 is a diagram illustrating a configuration of a Beacon Element control notification frame in the communication system of FIG. 23.

[0051] FIG. 26 is a diagram illustrating a configuration example of a general-purpose personal computer.

## MODE FOR CARRYING OUT THE INVENTION

[0052] Preferred embodiments of the present disclosure will be described in detail below with reference to the accompanying drawings. It is to be noted that in the present specification and the drawings, components having substantially the same functional configuration are designated by the same reference numerals, so that duplicate description will be omitted.

[0053] Hereinafter, modes for carrying out the present technology will be described. The description will be given in the following order. [0054] 1. Outline of the present disclosure [0055] 2. First embodiment [0056] 3. First application example of first embodiment [0057] 4. Second application example of first embodiment [0058] 5. Third application example of first embodiment [0059] 6. Second embodiment [0060] 7. Example performed by software

### 1. Outline of the Present Disclosure

[0061] The present disclosure is a communication system for achieving stable communication in response to a change in a signal reception environment in a wireless local area network (LAN) or a wave local area network standardized by IEEE 802.11.

[0062] The outline of the present disclosure will be described.

[0063] A communication system standardized by IEEE 802.11 generally includes a controller C1, base stations (access points) AP1 and AP2, and a communication device STA1. It is to be noted that FIG. 1 shows an example of two base stations AP1 and AP2. However, the number of the base stations may be larger than that.

[0064] The communication device STA1 is, for example, a smartphone, a personal computer (PC), or the like used by a user, establishes a communication connection with the base station AP1 or AP2, and is connected in communication with a basic service set (BSS) managed by the base station AP1 or AP2, and transmits and receives data and programs.

[0065] In addition, the communication device STA1 monitors RSSI (the received electric power) indicating a communication state related to the communication with the base station AP1 or AP2, with which a communication connection is currently established. In a case where the RSSI is lower than a predetermined threshold value, the communication device STA1 transmits a BSS transition query to the controller C1 via the base station AP1 or AP2 with which the communication connection is established.

[0066] The controller C1 selects a base station with which the communication device STA1 should be connected on the basis of the BSS query from the communication device STA1, and supplies the information regarding the communication device STA with the information regarding the base

station that has been selected, as a BSS transition request.

[0067] Upon reception of the BSS transition request, the communication device STA1 transmits a BSS transition response to the controller C1, also makes a connection application to the base station that has been designated by the BSS transition request, and establishes a communication connection.

[0068] More specifically, for example, as shown in FIG. 1, it is assumed that the connection between the communication device STA1 and the base station AP1 is established. That is, in FIG. 1, as indicated by a solid arrow, the communication connection between the communication device STA1 and the base station AP1 is established. It is assumed that the communication device STA1 is in a state of being capable of transmitting and receiving various data and programs via the base station AP1.

[0069] In this situation, the communication device STA1 measures the RSSI (the received signal strength), which is a signal quality of a download signal (hereinafter, also referred to as a DL signal), while transmitting and receiving data via the base station AP1, and monitors whether or not the RSSI becomes lower than a predetermined threshold value.

[0070] As shown in FIG. 1, for example, the communication device STA1 is apart from the base station AP1 by a predetermined distance, and therefore when the RSSI becomes lower than a predetermined threshold value  $th$ , the communication device STA1 transmits a BSS transition query to the controller C1 via the base station AP1 with which the connection is established, so as to inquire about a base station AP that manages a BSS with a better communication environment.

[0071] It is to be noted that the solid line of the threshold value  $th$  in FIG. 1 indicates a distance between the communication device STA1 and the base station AP1, when the degradation in the signal quality that occurs as the communication device STA1 moves away from the base station AP1 becomes the threshold value  $th$  that necessitates the BSS transition.

[0072] In response to the BSS transition query, it is assumed that the controller C1 selects the base station AP2 in FIG. 1, as the base station that manages the BSS with a better communication environment. In this situation, the controller C1 transmits a BSS transition request for requesting the communication device STA to make a transition of the communication connection to the base station AP2 via the base station AP1 with which the connection is currently being established.

[0073] Upon reception of the BSS transition request, the communication device STA1 transmits a BSS transition response to the base station AP1 with which the connection is being established, and also applies a communication connection to the base station AP2 on the basis of the BSS transition request, so that since then, the communication continues in the BSS managed by the base station AP2.

[0074] By repeating the above process, the communication device STA1 switches the base station according to the RSSI state, and makes a BSS transition, so as to maintain the communication state and continue the communication via the base station with which the communication connection has been established.

[0075] However, in the case of FIG. 1, when the RSSI becomes lower than the predetermined threshold value  $th$ , even though the communication state has degraded, the communication device STA1 cannot make a BSS transition, unless the communication device STA1 once makes a BSS transition query to the controller C1 via the base station AP1, a BSS transition destination is decided by the controller C1, and the communication device STA1 receives the BSS transition request that has been decided. That is, in a case where the communication state further degrades and the BSS transition query cannot be transmitted or the BSS transition request cannot be received, the BSS transition cannot be made, and the communication may not be capable of continuing.

[0076] Therefore, in the communication system in the present disclosure, at a stage before the communication quality degrades to an extent that the base station has to be switched immediately, a communication device STA11 (FIG. 2) acquires managing information and Link information of

other base stations, and judges whether or not to make a BSS transition, or in a case of making the BSS transition, uniquely judges which BSS the transition should be made to, so as to be capable of making the BSS transition on the basis of the unique judgment.

[0077] More specifically, as shown in FIG. 2, by setting two types of threshold values for the BSS transition including a first threshold value  $th1$  and a second threshold value  $th2$ , the communication device STA11 itself judges whether or not to make a BSS transition or uniquely judges which BSS a transition should be made to in a case of making the BSS transition.

[0078] Here, the first threshold value is a similar threshold value to the threshold value  $th$  of FIG. 1 described above, and it is necessary to immediately make a transition to another BSS, and which BSS the transition should be made to is entrusted to the controller C1.

[0079] On the other hand, the second threshold value  $th2$  is a threshold value for the communication device STA11 to start selecting a BSS transition destination, and is set as a second threshold value  $th2$  (greater than the first threshold value  $th1$ ) of a state where the signal quality does not degrade as compared with that of the first threshold value  $th1$ . That is, the second threshold value  $th2$  is set to a level at which the communication quality between the communication device STA11 and the base station AP11 does not become lower than the first threshold value  $th1$ .

[0080] In addition, when the signal quality becomes lower than the second threshold value  $th2$ , the communication device STA11 starts collecting information regarding the neighboring base stations to select a BSS transition destination, causes the neighboring base stations to respectively transmit Beacon signals placing information regarding the neighboring base stations so as to select the BSS transition destination of itself, and selects a new connection destination on the basis of the information regarding the neighboring base stations.

[0081] Then, the communication device STA11 acquires the Beacon signals transmitted from the neighboring base stations. When a base station with a better communication quality than the current one is found, the communication device STA11 make a transition of the communication connection to the base station AP2, which has the better communication quality than the current one, without transmitting a BSS transition query to the base station AP11 with which the communication connection is being established.

[0082] It is to be noted that a boundary line indicated by the first threshold value represents locations, which are distances from the base station AP11 and at which the communication quality degrades to an extent that the service related to the communication is affected. In addition, a boundary line indicated by the second threshold value represents locations, which are distances from the base station AP11, and at which the communication quality does not degrade to the extent that the service related to communication is affected, but there is a possibility that the communication quality is improved by making a transition to another base station.

[0083] By the series of actions as described above, at a stage before the degradation of the communication quality progresses to the extent that the service related to the communication is affected, a base station with a better communication quality is searched for. When such a base station is found, the BSS transition is made to the base station with a better communication quality. This configuration enables the achievement of stable communication in response to a change in the wireless LAN communication environment. It is to be noted that a controller C11, base stations AP11 and AP12, and a communication device STA11 in FIG. 2 respectively have configurations to correspond to the controller C1, the base stations AP1 and AP2, and the communication device STA1 in FIG. 1.

## 2. First Embodiment

### Configuration Example of Communication System in the Present Disclosure

[0084] Next, a configuration example of a communication system in the present disclosure will be described with reference to FIG. 3.

[0085] A communication system 1 in the present disclosure includes a controller 11, base stations

**12-1** and **12-2**, and a communication device **13**. It is to be noted that in the following description, in a case where it is not necessary to distinguish between the base stations **12-1** and **12-2**, they will be simply referred to as the base station **12**, and other configurations will also be referred to in a similar manner. Further, in FIG. 3, a configuration example in which only two base stations **12-1** and **12-2** are included is shown. However, except for the base station **12-1**, which has established the communication connection with the communication device **13**, any number of the base stations **12** may be included.

[0086] The controller **11**, the base stations **12-1** and **12-2**, and the communication device **13** in the communication system **1** in FIG. 3 respectively have configurations to basically correspond to the controllers **C1**, the base stations **AP1** and **AP2**, and the communication device **STA** in FIG. 2.

[0087] It is to be noted that in FIG. 3, the communication connection between the communication device **13** and the base station **12-1** is established. The communication device **13** detects a communication quality from a DL signal from the base station **12-1**, compares the communication quality with the first threshold value **th1** and the second threshold value **th2**, which have been described with reference to FIG. 2, and determines the degree of degradation in the communication quality.

[0088] In a case where the communication quality degrades as compared with the first threshold value **th1**, the communication device **13** transmits to the controller **11** via the base station **12-1**, a BSS transition query for requesting the information regarding the base station **12**, to which the transition of the communication connection should be made.

[0089] The controller **11** decides the information regarding the base station **12**, to which the transition of the communication connection should be made from among the neighboring base stations **12** of the communication device **13**, on the basis of the BSS transition query, and transmits a BSS connection transition request including the information regarding the base station **12**, which has been decided that the transition of the communication connection should be made to, to the communication device **13** via the base station **12-1**.

[0090] The communication device **13** receives the BSS connection transition request, makes a connection application on the basis of the information, regarding the base station **12** to which the transition of the communication connection should be made and included in the BSS connection transition request, and makes a transition of the communication connection.

[0091] Further, in a case where the communication quality of the communication device **13** does not degrade as much as the first threshold value **th1**, but degrades as compared with the second threshold value **th2**, the communication device **13** transmits to the controller **11** via the base station **12-1**, a BSS transition judgment information request for requesting BSS transition judgment information, which is a judgment criterion used for comparing the communication qualities so as to select the base station **12** to which the transition of the communication connection should be made, to be included in the Beacon signals from the neighboring base stations **12**.

[0092] The controller **11** decides the BSS transition judgment information to become a judgment criterion and to be included in the Beacon signal and transmitted, on the basis of the BSS transition judgment information request, generates a Beacon Element control notification that includes the BSS transition judgment information to become a decided judgment criterion in the Beacon signal for transmission, and transmits the Beacon Element control notification to all the base stations **12** (here, the base stations **12-1** and **12-2**).

[0093] Upon reception of the Beacon Element control notification, the base station **12** generates a Beacon signal including the BSS transition judgment information to become a judgment criterion used for comparing the communication qualities in the communication device **13**, on the basis of the Beacon Element control notification, and transmits the Beacon signal to the communication device **13**.

[0094] Upon reception of the Beacon signals transmitted from the neighboring base stations **12**, the communication device **13** compares the signal quality of the base station **12-1** with which the



communication connection has already been established with the signal quality of the other base station **12-2**, on the basis of the BSS transition judgment information to become a judgment criterion, included in the Beacon signals.

[0095] Then, in a case where the base station **12** that is higher in the signal quality than the base station **12-1**, with which the communication connection has already been established, is found on the basis of a comparison result, the communication device **13** makes a connection application for the base station **12** that has been newly found (the base station **12-2** in FIG. **3**), establishes a communication connection, and makes a BSS transition.

[0096] By a series of processes, in the communication system **1** of FIG. **3**, before the communication quality with the base station **12-1**, with which the communication connection has been established, degrades to the first threshold value for making the BSS transition query to the controller **11**, at a timing when the threshold value degrades to the second threshold value, the communication device **13** is capable of selecting the base station **12** on the basis of the BSS transition judgment information and is capable of achieving the BSS transition.

[0097] That is, at a stage before the communication quality with the base station **12-1**, with which the communication connection has been established, significantly degrades, the communication device **13** makes a comparison with the BSS transition judgment information included in the Beacon signals transmitted from the neighboring base stations **12** used as the judgment criterion, and is capable of selecting the base station **12-2** with which the optimum communication quality is obtainable for itself, so as to enable the achievement of the BSS transition.

[0098] As a result, before the degradation in the communication quality that makes the communication impossible occurs, the process of making the BSS transition to the base station **12** with a good communication quality is repeated, so that the connection with the optimum base station **12** always continues, and the achievement of the stable communication is enabled.

#### Configuration Example of Controller

[0099] Next, a configuration example of the controller **11** will be described with reference to FIG. **4**.

[0100] The controller **11** includes a control unit **31**, a data processing unit **32**, a wireless communication unit **33**, a wired communication unit **34**, and a network control unit **35**.

[0101] The control unit **31** includes a processor, a memory, and the like, and controls the entire action of the controller **11**.

[0102] The data processing unit **32** processes a data signal used for communication. Specifically, the data processing unit **32** performs a process of generating a data signal to be placed and transmitted in a packet, and a process of extracting a data signal from a received signal that has been demodulated. The data signal described here includes both communication data exchanged with the base station **12** and control data including a control content that has been decided by the control unit **31**.

[0103] The wireless communication unit **33** includes an antenna **33a**, performs an analog conversion process and a radio frequency (RF) process on the data signal that has been generated by the data processing unit **32**, and generates a transmission signal to be output from the antenna **33a**.

[0104] Further, the wireless communication unit **33** performs an RF process and a digital conversion process on the received signal that has been received via the antenna **33a** to extract a data signal.

[0105] The wireless communication unit **33** is used for communicating with the base station **12**, which constitutes a network.

[0106] The wireless communication unit **33** controls the antenna unit **33a** to emit a wireless packet that has been generated, as an electromagnetic wave. Further, the wireless communication unit **33** controls the antenna **33a** to extract the received electromagnetic wave as a wireless packet.

[0107] The wired communication unit **34** generates a transmission signal, which is to be output to a

wired cable, from the data signal that has been generated by the data processing unit **32**. Further, the wired communication unit **34** extracts a data signal from the received signal that has been acquired via the wired cable.

[0108] The wired communication unit **34** is mainly used for communicating with a backhaul line and communicating with the base station **12**, which constitutes the network.

[0109] It is to be noted that a plurality of wired communication units **34** and a plurality of wireless communication units **33** may be provided. For example, by providing the plurality of wired communication units **34**, the connection with the backhaul and the connection with the base station **12** can be used separately. Further, the wireless communication unit **33** may have a plurality of blocks respectively corresponding to different frequencies (2.4 Ghz band/5 GHz band).

[0110] The network control unit **35** collects information such as Link information from another base station **12**, which constitutes the same network, and controls the frequency and the like.

[0111] More specifically, the network control unit **35** decides a content of a BSS transition config setting and information to be placed by the base station **12** in the Beacon signal and to be transmitted to the communication device **13**.

[0112] It is to be noted that the controller **11** may have any configuration, as long as it includes the network control unit **35** described above. With the provision of either the wireless communication unit **33** or the wired communication unit **34**, the provision of both may not necessarily be essential. Further, in a case where the controller **11** includes the wireless communication unit **33**, the controller **11** is also capable of acting as a conventional base station (an access point).

#### Configuration Example of Base Station

[0113] Next, a configuration example of the base station **12** will be described with reference to FIG. 5.

[0114] The base station **12** includes a control unit **51**, a data processing unit **52**, a wireless communication unit **53**, a wired communication unit **54**, a display unit **55**, and an operation unit **56**.

[0115] The control unit **51** includes a processor and a memory, and controls the entire action of the base station **12**.

[0116] The control unit **51** controls the wireless communication unit **53** and the wired communication unit **54** via the data processing unit **52**, and performs various processes on the basis of the signal notification of which is provided from the controller **11**. Further, the control unit **51** decides a control content notification of which is provided to the controller **11** and the communication device **13**.

[0117] The data processing unit **52** processes the data signal used for communication. More specifically, the data processing unit **52** generates a data signal to be placed and transmitted in a packet, and extracts a data signal from the received signal that has been demodulated.

[0118] The wireless communication unit **53** controls the antenna **53a** to perform an analog conversion process and an RF process on the data signal that has been generated by the data processing unit **52**, and generates and transmits a transmission signal. Further, the wireless communication unit **53** performs an RF process and a digital conversion process on the received signal that has been received via the antenna **53a**, extracts the data signal, and outputs the data signal to the data processing unit **52**.

[0119] The wireless communication unit **53** is used not only for communicating with the communication device **13**, which is put under the control and with which the communication connection is established, but also for communicating with the controller **11**, which constitutes a network.

[0120] The wireless communication unit **53** controls the antenna unit **53a** to emit a wireless packet that has been generated, as an electromagnetic wave. Further, the wireless communication unit **53** acquires the electromagnetic wave that has been received via the antenna **53a**, as the wireless packet.

[0121] The wired communication unit **54** generates a transmission signal to be output to the wired

cable from the data signal that has been generated by the data processing unit **52**, and outputs the transmission signal. Further, the wired communication unit **54** extracts a data signal from the received signal that has been acquired via the wired cable.

[0122] The wired communication unit **54** is mainly used for communicating with a backhaul line and communicating with the controller **11**, which constitutes the network.

[0123] It is to be noted that a plurality of wired communication units **54** and a plurality of wireless communication units **53** may be provided. For example, a plurality of wired communication units **54** may be provided, so that the connection with the backhaul and the connection with the controller **11** may be used separately. Further, the wireless communication unit **53** may also have a plurality of blocks respectively corresponding to different frequencies (2.4 Ghz band/5 GHz band).

#### Configuration Example of Communication Device

[0124] Next, a configuration example of the communication device **13** will be described with reference to FIG. **6**.

[0125] The communication device **13** includes a control unit **71**, a data processing unit **72**, a wireless communication unit **73**, and a display unit **74**.

[0126] The control unit **71** includes a processor and a memory, and controls the entire action of the communication device **13**.

[0127] The control unit **71** controls the wireless communication unit **73** to detect the signal quality in communication with the base station **12-1** with which the communication connection is established, makes a comparison with the first threshold value or the second threshold value, and decides whether or not there is a BSS query or a BSS transition judgment information request.

[0128] The data processing unit **72** processes the data signal for communication. More specifically, the data processing unit **72** generates a data signal to be placed and transmitted in a packet, and extracts a data signal from the received signal that has been demodulated.

[0129] The wireless communication unit **73** controls the antenna **73a** to perform an analog conversion process and an RF process on the data signal that has been generated by the data processing unit **72**, and generates and transmits a transmission signal. Further, the wireless communication unit **73** performs an RF process and a digital conversion process on the received signal that has been received via the antenna **73a** to extract a data signal.

[0130] The wireless communication unit **73** communicates with the base station **12**, which puts under the control and with which a communication connection has been established.

[0131] The wireless communication unit **73** controls the antenna unit **73a** to emit a wireless packet that has been generated, as an electromagnetic wave. Further, the wireless communication unit **73** acquires the electromagnetic wave that has been received via the antenna **73a**, as a wireless packet.

[0132] The display unit **74** includes a liquid crystal display (LCD), an organic electro luminescence (EL), or the like, and is controlled by the control unit **71** to display the process results of the data processing unit **72** and various data. Further, the display unit **74** includes a touch panel, and functions as an operation unit. That is, the display unit **74** generates an operation signal according to an operation content on a keyboard, operation buttons, and the like to be displayed, and outputs an operation signal to the control unit **71**.

#### Communication Control Process

[0133] Next, a first communication control process by the communication system **1** of FIG. **3** will be described with reference to the flowchart of FIG. **7**. It is to be noted that in the communication control process in the flowchart of FIG. **7**, it is assumed as a precondition that the communication connection between the base station **12-1** and the communication device **13** in FIG. **3** is in an established state.

[0134] In step **S11**, the control unit **31** of the controller **11** controls the network control unit **35** to decide a content of the BSS transition config setting, and also causes the data processing unit **32** to generate the BSS transition config setting, and uses either the wireless communication unit **33** or the wired communication units **34** to transmit the BSS transition config setting to the base stations

## 12-1 and 12-2.

BSS Transition Config Setting Frame to be Transmitted from Controller to Base Station

[0135] A BSS transition config setting frame to be transmitted from the controller **11** to the base stations **12-1** and **12-2** has, for example, a configuration shown in FIG. **8**.

[0136] In the BSS transition config setting frame of FIG. **8**, from the left in the upper level in the figure, tlvType of one Octet, tlvLength of two Octets, Num. of AP of one Octet, and AP #1 Steering Info., to AP #N Steering Info each being nine Octets are stored.

[0137] tlvType is information of a TLV format type, and tlvLength is information has a data length in a TLV format. In addition, Num. of AP is information regarding the number of the base stations **12** (the number of the access points (APs)). Furthermore, in AP #N Steering Info., information regarding each base station is recorded, and MAC Address, Policy, Threshold **1**, and Threshold **2** are stored as indicated in the lower level of FIG. **8**.

[0138] MAC Address is a physical address of the base station **12** to be identified by AP #N from among the base stations **12**. Policy is information used for designating a device capable of starting a BSS transition process and a type of information to become a judgment criterion (a judgment parameter).

[0139] Policy is, for example, in existing specifications, information regarding whether or not the communication device **13** is capable of judging the BSS transition with the RSSI (the received electric power) used as the judgment criterion, whether or not the base station **12** is capable of judging the BSS transition with the RSSI (the received electric power) used as the judgment criterion, and the like is represented as either ON or OFF each being 1-bit information.

[0140] In addition, Policy is not limited to the existing specifications, and information for specifying the type of information to become a judgment criterion (the judgment parameter) of the signal quality may be added. In addition to the RSSI (the received electric power), which is a conventional judgment criterion, for example, a packet success rate, a standby period, and the like may be added as the type of information to become the judgment criterion.

[0141] Further, Policy may be extended to indicate ON or OFF of the determinations using the first threshold value and the second threshold value. Further, regarding Policy, information indicating any one method may be stored, instead of ON or OFF each being 1-bit information.

[0142] Threshold **1** and Threshold **2** respectively store information corresponding to the first threshold value th1 and the second threshold value th2, which have been described with reference to FIG. **2**.

[0143] It is to be noted that the example in which the two threshold values are set has been described in FIG. **2**. However, the number of the threshold values may be three or more. For example, in a case of three, Threshold **1** to Threshold **3** will be set.

[0144] It is to be noted that the size of each field in the BSS transition config setting frame shown in FIG. **8** is the unit of Octet represented below each field in the figure. Hereinafter, a similar configuration will be applicable, unless otherwise specified. Further, the size of each field may be not only the size shown in FIG. **8** but also another size.

[0145] Here, the description returns to the flowchart of FIG. **7**.

[0146] In steps S31 and S71, the control units **51** of the base stations **12-1** and **12-2** each control the data processing unit **52** to receive the BSS transition config setting, which includes the BSS transition config setting frame that has been described with reference to FIG. **8**, and which is transmitted by the wireless communication unit **53** or the wired communication unit **54**.

[0147] Then, the control unit **51** sets the type of information to become a judgment criterion for the signal quality for judging whether or not the BSS transition query or the BSS transition judgment information request is necessary in the communication device **13** on the basis of the BSS transition config setting that has been received, a threshold value for making the BSS transition query (corresponding to the first threshold value in FIG. **2**), and a threshold value for making the BSS transition judgment information request (corresponding to the second threshold value in FIG. **2**).

[0148] In step S32, the control unit **51** of the base station **12-1** controls the data processing unit **52** to generate a BSS transition config setting for the communication device **13** on the basis of the BSS transition config setting that has been received, and causes the wireless communication unit **53** to transmit the BSS transition config setting to the communication device **13**.

#### BSS Transition Config Setting Frame to be Transmitted from Base Station to Communication Device

[0149] A BSS transition config setting frame transmitted from the base station **12-1** to the communication device **13** has a configuration as shown in FIG. **9**, for example.

[0150] In the BSS transition config setting frame in FIG. **9**, from the left in the upper level in the figure, Element ID of one Octet, Length of one Octet, Element ID Extension of one Octet, and Steering Info. of three Octets are stored.

[0151] Element ID is identifier information for identifying the BSS transition config setting frame, and Length is information regarding a data length.

[0152] Element ID Extension is an extension of an identifier for identifying the BSS transition config setting frame.

[0153] In Steering Info., as indicated at the lower level of FIG. **9**, information similar to Policy, Threshold **1**, and Threshold **2**, which are MAC Address and subsequent information in AP #N Steering Info. in the BSS transition config setting frame that has been described with reference to FIG. **8**, are stored.

[0154] In step S51, the control unit **71** of the communication device **13** controls the data processing unit **72** so that the wireless communication unit **73** receives the BSS transition config setting transmitted from the base station **12-1**.

[0155] Here, the control unit **71** sets information or a threshold value to become a judgment criterion for judging the communication quality of the base station **12-1**, with which the communication connection has been established, on the basis of the BSS transition config setting that has been received.

[0156] In step S33, the control unit **51** of the base station **12-1** controls the data processing unit **52** to transmit a download (DL) signal from the wireless communication unit **53** to the communication device **13**.

[0157] In step S52, the control unit **71** of the communication device **13** receives the DL signal that has been transmitted from the base station **12-1** on the basis of the BSS transition config setting, performs a communication quality degradation determination process, and determines a degradation in the communication quality.

#### Communication Quality Degradation Determination Process

[0158] Here, a communication quality degradation determination process will be described with reference to the flowchart of FIG. **10**.

[0159] In step S91, the control unit **71** of the communication device **13** controls the data processing unit **72** so that the wireless communication unit **73** receives the DL signal transmitted from the base station **12-1**.

[0160] In step S92, when receiving the DL signal, the control unit **71** confirms the signal quality of, for example, the RSSI on the basis of the BSS transition config setting.

[0161] In step S93, the control unit **71** determines whether or not the signal quality is lower than the first threshold value on the basis of the BSS transition config setting, that is, whether or not it is necessary to transmit the BSS transition query immediately.

[0162] In a case where the communication quality is considered to be lower than the first threshold value in step S93, the process proceeds to step S94.

[0163] In step S94, the control unit **71** determines that it is necessary to transmit the BSS transition query.

[0164] Further, in a case where it is considered in step S93 that the signal quality is not lower than the first threshold value, the process proceeds to step S95.

[0165] In step **S95**, the control unit **71** determines whether or not the signal quality is lower than the second threshold value. That is, it is not necessary to make the BSS transition query immediately, but the control unit **71** determines whether or not it is necessary to request the BSS transition judgment information for judging a BSS transition in a case where there is a BSS with a high signal quality.

[0166] In a case where the communication quality is considered to be lower than the second threshold value in step **S95**, the process proceeds to step **S96**.

[0167] In step **S96**, the control unit **71** determines that it is necessary to transmit the BSS transition judgment information request.

[0168] That is, in the communication quality degradation determination process, in response to the communication quality, it is determined whether the BSS transition query, which is a query for immediately making a BSS transition, is transmitted, or whether the BSS transition judgment information request for judging the BSS transition is transmitted, in a case where there is a BSS with a high signal quality.

[0169] Here, the description returns to the flowchart of FIG. 7.

[0170] In step **S53**, the control unit **71** determines whether or not it is determined that it is necessary to transmit the BSS transition query, in the communication quality degradation determination process.

[0171] In a case where it is determined in step **S53** that it is necessary to transmit the BSS transition query, the process proceeds to step **S54**.

[0172] In step **S54**, the control unit **71** performs a BSS transition query process, transmits the BSS transition query to the controller **11** via the base station **12-1**, acquires the information regarding the BSS to become a transition destination, and performs the BSS transition.

[0173] It is to be noted that the BSS transition query process will be described in detail later with reference to the flowchart of FIG. 11.

[0174] Further, in step **S53**, in a case where the communication device **13** determines that it is necessary to transmit the BSS transition query, the BSS transition query is transmitted to the controller **11** via the base station **12-1** in the process of step **S54**, and the information regarding the BSS (the base station **12**) to become a transition destination is transmitted from the controller **11** via the base station **12-1**.

[0175] Therefore, in subsequent processes, both in the process of step **S34** by the base station **12-1** and in the process of step **S12** by the controller **11**, it is considered that there is a BSS transition query. The processes respectively proceed to steps **S35** and **S13**, and the controller **11** and the base station **12-1** respectively perform the BSS transition query processes.

[0176] Therefore, regarding the BSS transition query process, the details of the respective processes of the controller **11**, the base stations **12-1** and **12-2**, and the communication device **13** will be described later with reference to the flowchart of FIG. 11.

[0177] On the other hand, in a case where it is determined in step **S53** that it is not necessary to transmit the BSS transition query, the process proceeds to step **S55**.

[0178] In step **S55**, the control unit **71** determines whether or not it has been determined that it is necessary to transmit the BSS transition judgment information request, in the communication quality degradation determination process.

[0179] In a case where it is determined in step **S55** that it is necessary to transmit the BSS transition judgment information request, the process proceeds to step **S56**.

[0180] In step **S56**, the control unit **71** performs a BSS transition judgment information request process, transmits the BSS transition judgment information request to the controller **11** via the base station **12-1**, and compares the communication quality of the neighboring base station **12** with the communication quality of the base station **12-1** with which the communication connection is currently established, on the basis of the BSS transition judgment information included in the Beacon signal transmitted from the neighboring base station **12**, and makes a BSS transition as

necessary.

[0181] It is to be noted that the details of the BSS transition judgment information request process will be described later with reference to the flowchart of FIG. 12.

[0182] Further, in step S55, in a case where the communication device 13 determines that it is necessary to transmit the BSS transition judgment information request, the BSS transition judgment information request is transmitted to the controller 11 via the base station 12-1 in the process of step S56.

[0183] Therefore, in subsequent processes, also in steps S34 and S12, the processes are performed after the BSS transition judgment information request have been supplied. Therefore, the processes respectively proceed to steps S36 and S14. Further, the BSS transition judgment information request process is performed, so that the BSS transition judgment information request processes are also performed respectively by the controller 11 and the base station 12-1 in the processes of steps S37 and S15.

[0184] Therefore, regarding the BSS transition judgment information request process, the details of the respective processes of the controller 11, the base stations 12-1 and 12-2, and the communication device 13 will be described later with reference to the flowchart of FIG. 12.

[0185] It is to be noted that regarding the process of step S72 and subsequent processes by the base station 12-2 in FIG. 7, similar flowcharts are respectively included in the flowcharts of FIGS. 11 and 12, and the description will be given to correspond to one another.

[0186] Then, in step S55, in a case where it is considered that the BSS transition judgment information request is not necessary, the process ends.

[0187] Therefore, similar processes are respectively performed by the controller 11 and the base station 12-1, and it is considered in each step S14 or S36 that neither the BSS query nor the BSS transition judgment information request is present, and the processes end.

[0188] By the above-described series of processes, when the signal quality becomes lower than the first threshold value as described with reference to FIG. 2, the BSS query is transmitted, and the BSS transition is made in response to the BSS transition request that has been decided by the controller 11. In addition, when the signal quality becomes lower than the second threshold value, which is lower in the degradation degree than the first threshold value, the BSS transition judgment information request is transmitted. The signal quality of the base station 12-1 with which the communication connection is established and the signal quality of the neighboring base station 12-2 are compared with each other, on the basis of the BSS transition judgment information included in the Beacon signal, and the BSS transition according to the comparison result is made.

[0189] Consequently, in a state in which the communication quality does not degrade as compared with a case of making the BSS transition query after the situation in which the BSS transition is immediately necessary occurs, the BSS transition is enabled on the basis of the BSS transition judgment information at a stage of having found a base station 12 with a better communication quality, from among the neighboring base stations 12, than the communication quality of the current base station 12.

[0190] As a result, in a case where the communication quality degrades to the extent that the BSS transition is immediately necessary, and then the BSS transition is performed by the BSS transition query, it is possible to prevent a situation in which the BSS transition query becomes impossible, and an appropriate BSS transition becomes impossible. The achievement of the stable communication is enabled in response to a change in the wireless LAN communication environment.

#### BSS Transition Query Process

[0191] Next, the BSS transition query process will be described with reference to the flowchart of FIG. 11.

[0192] In step S121, the control unit 71 of the communication device 13 controls the data processing unit 72 so that the wireless communication unit 73 transmits a BSS transition query to

the base station **12-1**.

[0193] In step **S111**, the control unit **51** of the base station **12-1** controls the data processing unit **52** so that the wireless communication unit **53** receives the BSS transition query from the communication device **13**.

[0194] More specifically, the control unit **51** of the base station **12-1** recognizes that there is the BSS transition query in step **S34** (FIG. 7) from the BSS transition query to be received here. The process proceeds to step **S35** (FIG. 7), and the BSS transition query process is started.

[0195] In step **S112**, the control unit **51** of the base station **12-1** controls the data processing unit **52** so that either the wireless communication unit **53** or the wired communication unit **54** transmits the BSS transition query from the communication device **13** to the controller **11**.

[0196] In step **S101**, the control unit **31** of the controller **11** controls the data processing unit **32** so that either the wireless communication unit **33** or the wired communication unit **34** receives the BSS transition query from the communication device **13** via the base station **12-1**.

[0197] More specifically, the control unit **31** of the controller **11** recognizes that there is the BSS transition query in step **S12** (FIG. 7) from the BSS transition query to be received here. The process proceeds to step **S13** (FIG. 7), and the BSS transition query process is started.

[0198] In step **S102**, the control unit **31** controls the network control unit **35** to decide that the base station **12** is a transition destination, to which the communication device **13** that has transmitted the BSS transition query should make a transition to establish the communication connection.

[0199] In step **S103**, the control unit **31** controls the data processing unit **32** so that either the wireless communication unit **33** or the wired communication unit **34** transmits information regarding the transition destination that is the information regarding the base station **12**, with which the communication device **13** should make a transition to establish the communication connection, to the base station **12-1**, with which the communication device **13** is currently establishing the communication connection.

[0200] In step **S113**, the control unit **51** of the base station **12-1** controls the data processing unit **52** so that either the wireless communication unit **53** or the wired communication unit **54** receives the information regarding the transition destination that is transmitted from the controller **11** and that is the information regarding the base station **12**, with which the communication device **13** should make a transition to establish the communication connection.

[0201] In step **S114**, the control unit **51** of the base station **12-1** controls the data processing unit **52** to generate a BSS transition destination request including the information regarding the base station **12**, with which the communication device **13** should make a transition to establish communication, and causes the wireless communication unit **53** to transmit the BSS transition request to the communication device **13**.

[0202] In step **S122**, the control unit **71** of the communication device **13** controls the data processing unit **72** so that the wireless communication unit **73** receives the BSS transition request transmitted from the base station **12-1**.

[0203] In step **S123**, the control unit **71** of the communication device **13** controls the data processing unit **72** to generate a BSS transition response corresponding to the BSS transition request transmitted from the base station **12-1**, and causes the wireless communication unit **73** to transmit the BSS transition response to the base station **12-1**.

[0204] In step **S115**, the control unit **51** of the base station **12-1** controls the data processing unit **52** so that the wireless communication unit **53** receives the BSS transition response transmitted from the communication device **13**.

[0205] In step **S124**, the control unit **71** of the communication device **13** controls the data processing unit **72** so that the wireless communication unit **73** transmits, to the corresponding base station **12-2**, a connection application on the basis of the information regarding the base station **12**, to become a transition destination, included in the BSS transition request.

[0206] In step **S75**, the control unit **51** of the base station **12-2** controls the data processing unit **52**



to determine whether or not the connection application that had been transmitted from the communication device **13** has been received by the wireless communication unit **53**. In a case where the connection application is received, the process proceeds to step **S76**.

[0207] In step **S76**, the control unit **51** of the base station **12-2** controls the data processing unit **52** to receive the connection application on the basis of the connection application that has been received by the wireless communication unit **53**, and to establish connection communication with the communication device **13**.

[0208] By the above process, in a case where the communication quality is lower than the first threshold value and it is necessary that the communication device **13** make a transition of the base station **12** immediately, the BSS transition query is transmitted to controller **11** via the base station **12-1** with which the connection communication is established. The controller **11** decides the transition destination, generates BSS transition request information on the basis of the transition destination, and transmits the BSS transition request information to the communication device **13**. Then, the communication device **13** receives the BSS transition request information, and the BSS transition to a new base station **12-2** with a high communication quality included in the BSS transition request information is achieved.

[0209] It is to be noted that the process of steps **S72** to **S74** will be described in detail later with reference to the flowchart of FIG. **12**.

#### BSS Transition Judgment Information Request Process

[0210] Next, the BSS transition judgment information request process will be described with reference to the flowchart of FIG. **12**.

[0211] In step **S151**, the control unit **71** of the communication device **13** controls the data processing unit **72** to generate a BSS transition judgment information request, and causes the wireless communication unit **73** to transmit the BSS transition judgment information request to the base station **12-1** to the communication device **13**.

#### BSS Transition Judgment Information Request Frame to be Transmitted from Communication Device to Base Station

[0212] A BSS transition judgment information request frame transmitted from the communication device **13** to the base station **12-1** has a configuration as shown in FIG. **13**, for example.

[0213] In the BSS transition judgment information request frame in FIG. **13**, from the left in the upper level in the figure, Element ID of one Octet, Length of one Octet, Element ID Extension of one Octet, and the BSS Transition Criteria of N Octets are stored.

[0214] Element ID is information of an identifier for identifying the BSS transition judgment information request frame, and Length is information regarding a data length.

[0215] Element ID Extension is an extension of the identifier of the BSS transition judgment information request frame, and stores information indicating whether or not BSS Transition Criteria is stored.

[0216] As shown in the lower level of FIG. **13**, in BSS Transition Criteria, identifiers for designating information necessary for transmission by being placed (included) in a Beacon signal transmitted from the base station **12** are stored in the order of priority, as criteria used for selecting the base station **12** to become a BSS transition destination. In FIG. **13**, the priority is higher on the left, and Criteria ID is stored in association with a Criteria ID (Priority **1**), Criteria ID (Priority **2**), . . . each having one Octet as an identifier of information to become a judgment criterion. In FIG. **13**, the criteria corresponding to N pieces are stored.

[0217] That is, the BSS transition judgment information request frame includes the judgment criteria, which are necessary for the communication device **13** to make a BSS transition judgment and which are requested to be placed in the Beacon signal, and the information for specifying the priorities. It is to be noted that the judgment criteria which are requested to be placed in the Beacon signal, and the priorities may be optionally set by a user who uses the transmission device **13**.

[0218] In step **S141**, the control unit **51** of the base station **12-1** controls the data processing unit **52**

so that the wireless communication unit **53** receives the BSS transition judgment information request from the communication device **13**.

[0219] More specifically, the control unit **51** of the base station **12-1** recognizes that there is the BSS transition judgment information request in step **S36** (FIG. 7) from the BSS transition judgment information request to be received here. The process proceeds to step **S37** (FIG. 7), and the BSS transition judgment information request process is started.

[0220] In step **S142**, the control unit **51** of the base station **12-1** controls the data processing unit **52** to generate a BSS transition judgment information request for the controller **11** on the basis of the BSS transition judgment information request from the communication device **13**, and causes either the wireless communication unit **53** or the wired communication unit **54** to transmit the BSS transition judgment information request to the controller **11**.

BSS Transition Judgment Information Request Frame to be Transmitted from Base Station to Controller

[0221] The BSS transition judgment information request frame to be transmitted from the base station **12-1** to the controller **11** has, for example, a configuration example as shown in FIG. **14**.

[0222] In the BSS transition judgment information request frame in FIG. **14**, from the left in the upper level in the figure, tlvType of one Octet, tlvLength of two Octets, and BSS Transition Criteria of N Octets are stored.

[0223] tlvType is information of a TLV format type, and tlvLength is information has a data length in a TLV format. It is to be noted that BSS Transition Criteria of N Octets is similar to BSS Transition Criteria in the BSS transition judgment information request frame transmitted from the communication device **13** in FIG. **13** to the base station **12-1**. Therefore, the description thereof will be omitted.

[0224] In step **S131**, the control unit **31** of the controller **11** controls the data processing unit **32** so that either the wireless communication unit **33** or the wired communication unit **34** receives the BSS transition judgment information request from the base station **12-1**.

[0225] More specifically, the control unit **31** of the controller **11** recognizes that there is a BSS transition judgment information request in step **S14** (FIG. 7) from the BSS transition judgment information request to be received here. The process proceeds to **S15** (FIG. 7), and the BSS transition judgment information request process is started.

[0226] In step **S132**, the control unit **31** controls the network control unit **35** to decide the BSS transition judgment information that should be placed in a Beacon on the basis of the BSS transition judgment information request and transmitted to the communication device **13**, that is, the judgment criteria for judging the BSS transition.

[0227] In step **S133**, the control unit **31** controls the data processing unit **32** to generate a Beacon Element control notification on the basis of the BSS transition judgment information that has been decided, and causes either the wireless communication units **33** or the wired communication unit **34** to transmit the Beacon Element control notification to all the base stations **12-1** and **12-2**.

Beacon Element Control Notification Frame

[0228] A Beacon Element control notification frame transmitted from the controller **11** to the base stations **12-1** and **12-2** has, for example, a configuration example as shown in FIG. **15**.

[0229] In the Beacon Element control notification frame in FIG. **15**, from the left in the upper level in the figure, tlvType of one Octet, tlvLength of two Octets, and Required Beacon Element ID of N Octets are stored.

[0230] In Required Beacon Element ID, an identifier for specifying the judgment criteria to become the BSS transition judgment information. From the left in the lower level in the figure of FIG. **15**, Policy, Mandatory Element ID #1, Mandatory Element ID #2, . . . are stored.

[0231] In Policy, information regarding a control policy is stored. As a control policy, a timing or a period including Required Beacon Element ID in a Beacon signal are set. The timing or the period is set such that, for example, "Required Beacon Element ID is always included continuously",

“Required Beacon Element ID is included only during a given period”, “Required Beacon Element ID is included only at a given interval”, and the like.

[0232] Mandatory Element ID #N is information regarding an identifier in the Beacon signal corresponding to Criteria ID in BSS Transition Criteria in the BSS transition judgment information request.

[0233] That is, in the BSS transition judgment information request, Criteria ID is set as an identifier for identifying the judgment criteria that is the BSS transition judgment information. On the other hand, Element ID (Required Beacon Element ID) is set for an identifier regarding the information to be included in the Beacon signal.

[0234] Therefore, for example, the network control unit **35** stores, for example, a Beacon Element decision table in which a Criteria ID and an Element ID (Required Beacon Element ID) are associated with each other as shown in FIG. **16**, and in generating a Beacon Element control notification frame, refers to the Beacon Element decision table, reads a Required Beacon Element ID corresponding to Criteria ID of the BSS transition judgment information request, and stores as Mandatory Element ID #N.

[0235] That is, in the Beacon Element decision table of FIG. **16**, Criteria ID=1 indicates that a judgment criterion (Criteria) is the RSSI (the received electric power), but indicates that there is no identifier (Required Beacon Element ID) in particular for identifying the information regarding the judgment criterion stored in the corresponding Beacon signal. That is, in the Beacon signal, the RSSI (the received electric power) is measured by default at the time of signal reception, no identifier is set in particular.

[0236] In addition, Criteria ID=2 indicates that information to become a judgment criterion (Criteria) is BSS Load (BSS load), but 28 is an identifier (Required Beacon Element ID) as the judgment criterion stored in the corresponding Beacon signal. It is indicated that the information to become the judgment criterion is BSS Load.

[0237] Furthermore, Criteria ID=3 indicates that a judgment criterion (Criteria) is Access Delay, but 39 is an identifier (Required Beacon Element ID) as the judgment criterion stored in the corresponding Beacon signal. It is indicated that the information to become the judgment criterion is BSS Average Access Delay.

[0238] In addition, Criteria ID=4 indicates that a judgment criterion (Criteria) is a quality of signal (QoS), but 35 is an identifier (Required Beacon Element ID) as the judgment criterion stored in the corresponding Beacon signal. It is indicated that the information to become the judgment criterion is QoS Capability.

[0239] In addition, in the Mandatory Element ID #1, Mandatory Element ID #2, . . . , identifiers (Required Beacon Element ID) for identifying the information regarding the judgment criteria are arranged in the order according to the priority in a similar manner to Criteria ID (Priority 1), Criteria ID (Priority 2), . . . in the BSS transition judgment information request frame transmitted from the communication device **13** to the base station **12-2** that has been described with reference to FIG. **13**. As a result, for example, in FIG. **15**, the information to become the judgment criterion specified by Mandatory Element ID #1 has the first highest priority, and the information to become the judgment criterion specified by Mandatory Element ID #2 has the second highest priority. That is, the information regarding Mandatory Element ID #N has a higher priority, as the degree of N is smaller, and has a lower priority as the degree of N is larger.

[0240] That is, the base station **12**, which has received the Beacon Element control notification, confirms Mandatory Element ID #N included in Required Beacon Element ID, recognizes which of the BSS transition judgment information at what priority is included for transmission.

[0241] In step **S143**, the control unit **51** of the base station **12-1** controls the data processing unit **52** so that either the wireless communication unit **53** or the wired communication unit **54** receives the Beacon Element control notification transmitted from the controller **11**.

[0242] In step **S144**, the control unit **51** of the base station **12-1** controls the data processing unit **52**

to generate a Beacon frame on the basis of the Beacon Element control notification, and causes the wireless communication unit **53** to transmit the Beacon frame as a Beacon signal to the communication device **13**.

#### Beacon Frame

[0243] The Beacon frame transmitted from the base station **12** to the communication device **13** has a configuration as shown in FIG. **17**, for example.

[0244] In the Beacon frame of FIG. **17**, from the left in the upper level in the figure, MAC header of three Octets, Frame Body of a variable length (V), and FCS of four Octets are stored.

[0245] In MAC header, information such as a frame type, a transmission timing, a reception destination address, a transmission destination address, and the like are stored.

[0246] Frame Body includes actual data to be transmitted, and includes from the left in the lower level in the figure, Timestamp of eight bits, Beacon Interval of two bits, Capability Information of two bits, SSID of a variable length, Supported Rates and BSS Membership Selectors of a variable length, and Element #1, . . . Element #n.

[0247] In Timestamp, time information used for synchronizing the communication being conducted between the base station **12** and the communication device **13** is stored.

[0248] Further, in Beacon Interval, a time interval in which the Beacon signal is transmitted is stored.

[0249] In Capability Information, basic Capability information regarding the base station **12** is stored. In SSID, information for identifying the base station **12** is stored.

[0250] In Supported Rates and BSS Membership Selectors, information regarding supported communication rates is stored.

[0251] In Element #n, information corresponding to Mandatory Element ID #N in Required Beacon Element ID in the Beacon Element control notification is stored, and as N is smaller, the priority is set to be higher.

[0252] In frame check sequence (FCS), an error correction code is stored.

[0253] It is to be noted that in the base station **12-2** with which the communication connection is not currently established, in step **S72**, the control unit **51** controls the data processing unit **52** so that either the wireless communication unit **53** or the wired communication unit **54** determines whether or not the Beacon Element control notification has been transmitted from the controller **11**. In a case where it is considered in step **S72** that the Beacon Element control notification has been transmitted, the process proceeds to step **S73**.

[0254] In step **S73**, the control unit **51** of the base station **12-2** controls the data processing unit **52** so that either the wireless communication unit **53** or the wired communication unit **54** receives the Beacon Element control notification transmitted from the controller **11**.

[0255] In step **S74**, the control unit **51** of the base station **12-2** controls the data processing unit **52** to generate a Beacon frame on the basis of the Beacon Element control notification, and causes the wireless communication unit **53** to transmit the Beacon frame as a Beacon signal to the communication device **13**.

[0256] That is, by the process heretofore, the Beacon signals each including the information to become the judgment criterion to become BSS transition judgment information that has been specified by Criteria ID requested from the communication device **13** on the basis of the BSS transition judgment information request from the communication device **13** are transmitted from the neighboring base stations **12-1** and **12-2** to the communication device **13**.

[0257] In step **S152**, the control unit **71** of the communication device **13** controls the data processing unit **72** so that the wireless communication unit **73** receives the Beacon signals respectively transmitted from the base stations **12-1** and **12-2**, and a communication quality comparison process is performed on the basis of the Beacon signal that has been received.

#### Communication Quality Comparison Process

[0258] Here, the communication quality comparison process will be described with reference to the

flowchart of FIG. 18.

[0259] In step **S201**, the control unit **71** of the communication device **13** controls the data processing unit **72** so that the wireless communication unit **73** receives the Beacon signals transmitted from the neighboring base stations **12**.

[0260] In step **S202**, the control unit **71** controls the data processing unit **72** to determine whether or not the Beacon signals have been received from two or more base stations **12**. That is, unless the Beacon signals are received from at least another one or more base stations **12** including the base station **12-1**, with which the communication is currently established, no comparison can be performed. Therefore, whether or not the comparison is possible is determined.

[0261] In a case where it is considered in step **S202** that the Beacon signal has not been received from two or more base stations **12**, the process ends. The state in which the communication connection with the current base station **12** has been established continues.

[0262] On the other hand, in a case where it is considered in step **S202** that the Beacon signals has been received from two or more base stations **12**, the process proceeds to step **S203**.

[0263] In step **S203**, the control unit **71** controls the data processing unit **72** to initialize a counter **P** of priority to 1.

[0264] In step **S204**, the control unit **71** controls the data processing unit **72** to compare the communication quality between the neighboring base station **12** and the base station **12** with which the communication connection is currently established, with regard to the judgment criterion of a **P**-th priority.

[0265] In step **S205**, the control unit **71** controls the data processing unit **72** to determine whether or not the communication quality of the base station **12** with which the communication connection is currently established and the communication quality of the neighboring base station **12** are substantially the same with regard to the judgment criteria of the **P**-th priority.

[0266] In step **S205**, in a case where it is determined that the communication quality of the base station **12** with which the communication connection is currently established and the communication quality of the neighboring base stations **12** are not substantially the same with regard to the judgment criterion of the **P**-th priority, the process proceeds to step **S206**.

[0267] In step **S206**, the control unit **71** controls the data processing unit **72** to determine whether or not the communication quality of any of the neighboring base stations **12-1** is higher than the communication quality of the base station **12** with which the communication is currently established, with regard to the judgment criterion of the **P**-th priority.

[0268] In step **S206**, in a case where it is determined that the communication quality of any of the neighboring base stations **12** is higher than the communication quality of the base station **12** with which the communication connection is currently established, with regard to the judgment criterion of the **P**-th priority, the process proceeds to step **S207**.

[0269] In step **S207**, the control unit **71** judges that it is necessary to make a transition to establish the communication with the base station **12** having a higher communication quality, from among the neighboring base stations **12**, than the communication quality of the base station **12**, with which the communication connection is currently established, with regard to the judgment criterion of the **P**-th priority, and the process ends.

[0270] Further, in a case where it is determined in step **S206** that the communication quality of any of the neighboring base stations **12**, from among the neighboring base stations **12**, is not higher than the communication quality of the base station **12** with which the communication connection is currently established, with regard to the judgment criterion of the **P**-th priority **P**, the process of step **S207** is skipped, and the process ends.

[0271] On the other hand, in a case where it is determined in step **S205** that the communication quality of the base station **12** with which the communication is currently established and the communication quality of the neighboring base station **12** are substantially the same with regard to the judgment criterion of the **P**-th priority, the process proceeds to step **S208**.

[0272] In step **S208**, the control unit **71** determines whether or not the counter **P** is the maximum value, that is, the priority **P** has the lowest value, and determines whether or not the counter **P** is not the maximum value, that is, does not have the lowest value.

[0273] In a case where the counter **P** is not the maximum value in step **S208**, the process proceeds to step **S209**.

[0274] In step **S209**, the control unit **71** controls the data processing unit **72** to increment the counter **P** by 1, and the process returns to step **S204**.

[0275] That is, with regard to the judgment criterion to become the **P**-th priority, the comparison between the communication qualities is repeated while gradually lowering the priority of the judgment criteria, until it is determined that the communication quality of the base station **12** with which the communication connection is currently established and the communication quality of the neighboring base station **12** are not substantially the same, or until the priority of the judgment criteria becomes the lowest.

[0276] Then, in step **S208**, in a case where the communication qualities are compared until the counter **P** becomes the maximum value and the priority of the judgment criterion becomes the lowest, and both are substantially the same, the process ends.

[0277] That is, the communication quality is compared from the one with a higher priority as a judgment criterion. In a case where any of the base stations **12** is superior, and such a base station **12** is the base station **12** with which the communication connection is not currently established, it is determined that a communication connection should be applied for. In other cases, it is determined that the communication with the base station **12** with which the communication connection is currently established should be continued.

[0278] Here, the description returns to the flowchart of FIG. **12**.

[0279] In step **S153**, the control unit **71** of the communication device **13** controls the data processing unit **72** to determine whether or not it is necessary to make a transition of the base station **12** and newly apply for a communication connection. That is, in the present case, in the communication quality comparison process, with regard to the judgment criterion with a high priority, it is determined whether or not the communication quality of the base station **12-2** is higher than that of the base station **12-1** with which the communication connection is currently established, and it is determined whether or not the transition and the communication connection should be applied for.

[0280] Then, in step **S153**, in a case where it is determined that it is necessary to make a transition of the base station **12** and to newly apply for a communication connection, the process proceeds to step **S154**.

[0281] In step **S154**, the control unit **71** of the communication device **13** controls the data processing unit **72** so that the wireless communication unit **73** transmits a communication connection application to the base station **12-2**, which is considered to be higher in the communication quality than the current base station **12** in the communication quality comparison process, and which becomes a transition destination.

[0282] In step **S75**, the control unit **51** of the base station **12-2** controls the data processing unit **52** to determine whether or not the communication connection application that had been transmitted from the communication device **13** has been received by the wireless communication unit **53**. In a case where the communication connection application is received, the process proceeds to step **S76**.

[0283] In step **S76**, the control unit **51** of the base station **12-2** controls the data processing unit **52** to receive the communication connection application on the basis of the communication connection application that has been received by the wireless communication unit **53**, and establishes a communication connection with the communication device **13**.

[0284] Further, in step **S153**, in a case where it is not determined that it is necessary to make a transition of the base station **12** or newly apply for the communication connection, the process of

step S154 is skipped.

[0285] Correspondingly, in step S75, since it is considered that there is no connection application, the process of step S76 is skipped.

[0286] By the above process, when the communication quality is lower than the second threshold value, the communication device 13 requests the neighboring base stations 12 to respectively transmit information to become the judgment criteria placed in the Beacon signals. Upon reception of the Beacon signals, the judgment criteria are sequentially compared in a descending order of priority. In a case where the neighboring base station 12 is considered to be superior, a transition to a new base station 12-2 with a higher communication quality is achieved.

[0287] Accordingly, without issuing a query about the optimum transition destination to the controller 11 or the base station 12, the communication device 13 obtains information necessary for the BSS transition judgment from the Beacon signals from the neighboring base stations 12, and is capable of deciding the optimum transition destination by itself. The achievements of advancements and shortening of the BSS transition are enabled.

[0288] As a result, the base station 12 with which the communication connection should be established is selected on the basis of the judgment criterion with a high priority. Therefore, the achievement in the stable communication is enabled in response to a change in the wireless LAN communication environment.

[0289] It is to be noted that in the above description, the description has been given with regard to the method for controlling, by the controller 11 or the base station 12, the information included in the Beacon signal, when the communication device 13 in the communication system 1 in FIG. 3 makes a BSS transition from the base station 12-1, with which the communication connection has been established, to the base station 12-2 with a higher communication quality. However, also in other processes, the information included in the Beacon signal may be controlled.

[0290] For example, when the base station 12 switches a channel, the base station 12 transmits a Beacon signal for controlling Channel Switch Announcement to be included in the Beacon signal, so that the communication device 13 is capable of learning beforehand that a channel is to be switched. Therefore, the communication device 13 is capable of switching the channel in synchronization with a timing when the base station 12 switches the channel on the basis of Channel Switch Announcement, so as to enable the continuation of communication even when the channel is switched.

[0291] Further, even in a case where a newly connected communication device 13 necessitates information that is not included in the Beacon signal due to the implementation dependence of the base station 12, Criteria ID used for designating the information to be placed in the Beacon signal for transmission is enabled, in a similar manner to the case of transmitting the BSS transition judgment information request.

### 3. First Application Example of First Embodiment

[0292] In the above description, an example in which the communication device 13 performs the communication quality determination process when receiving the DL signal from the base station 12-1 has been described. However, the base station 12-1 may perform a signal quality determination process on the basis of an upload (UL) signal from the communication device 13, and may transmit a BSS transition query or a BSS transition judgment information request.

[0293] Such a configuration eliminates the need for transmitting the determination result by the signal quality determination process from the communication device 13. Therefore, a reduction in the amount of communication data of the entire communication system 1 is enabled.

#### Communication Control Process in a Case where Base Station Performs Signal Quality Determination Process

[0294] Next, a communication control process of a case where the signal quality determination process is performed by the base station 12-1 will be described with reference to the flowchart of FIG. 19.

[0295] It is to be noted that a process of steps **S211** to **S215**, a process of steps **S231** to **S232**, and **S234** to **S237**, a process of steps **S251**, and **S253** to **S256**, and a process of steps **S271** to **S276** in the flowchart of FIG. **19** are similar to the process of steps **S11** to **S15**, the process of steps **S31** to **S32**, and **S34** to **S37**, the process of steps **S51**, and **S53** to **S56**, and the process of steps **S71** to **S76** in the flowchart of FIG. **7**, and the description thereof will be omitted.

[0296] That is, in the flowchart of FIG. **19**, the difference from the flowchart of FIG. **7** is the process of steps **S233** and **S252**.

[0297] That is, in step **S252**, the control unit **71** of the communication device **13** controls the data processing unit **72** on the basis of the BSS transition config setting, and transmits the UL signal from the wireless communication unit **73** to the base station **12-1**.

[0298] In response to this, in step **S233**, the control unit **51** of the base station **12-1** receives the UL signal that has been transmitted from the communication device **13** on the basis of the BSS transition config setting, performs the communication quality degradation determination process, and determines a degradation of the communication quality.

[0299] For the subsequent processes, any of the BSS transition query process, the BSS transition judgment information request process, and none of the process is performed, on the basis of the determination result of the communication quality degradation determination process.

[0300] In the communication control process of FIG. **19**, the communication quality degradation determination process is performed by the base station **12-1**. This eliminates the need for a process of transmitting the determination result of the communication quality degradation determination process from the communication device **13** to the base station **12-1**. A reduction in the amount of the communication data in the entire communication system **1** is enabled.

#### 4. Second Application Example of First Embodiment

[0301] In the above description, Mandatory Element ID in Required Beacon Element ID included in the Beacon Element control notification has been decided on the basis of the BSS Transition Criteria included in the BSS transition judgment information request transmitted from the communication device **13**, but may be set beforehand according to a service content in the communication device **13**.

[0302] That is, for example, as shown in FIG. **20**, the priority (Priority) and the judgment criterion (Criteria) are set according to the service content. The communication device **13** may transmit information regarding the content of the service, instead of the BSS Transition Criteria, when transmitting the BSS transition judgment information request.

[0303] In FIG. **20**, the priority (Priority) is set to 0, 1, 2 . . . from the top, as indicated in the leftmost part in the figure, and File DownLoad, Video Call, and Real-Time Gaming are shown as the service contents.

[0304] In FIG. **20**, the priority becomes 0, and the RSSI (the received electric power) is set as a judgment criterion (Criteria) for the lowest File DownLoad. It is indicated that no setting is made as Required Beacon Element ID, which is an identifier in the corresponding Beacon signal. That is, the RSSI is measured by default.

[0305] In addition, regarding Video Call with a priority of 1, the RSSI (the received electric power) and a BSS Load (BSS load) are set as judgment criteria (Criteria), and it is indicated that 28 corresponding to the BSS Load (BSS Load) is set as the Required Beacon Element ID, which is an identifier in the Beacon signal.

[0306] Furthermore, regarding Real-Time Gaming with a priority of 2, Accesses Delay (an access delay), RSSI (the received electric power), and BSS Load (BSS load) are set as judgment criteria (Criteria). It is indicated that 28 corresponding to the BSS Load and 39 corresponding to the BSS Average Access Delay are respectively set as the Required Beacon Element IDs, which are the identifiers in the Beacon signal.

[0307] The network control unit **35** of the controller **11** stores a table as shown in FIG. **20**, reads a Required Beacon Element ID in the table of FIG. **20** according to the information of the service



content included in the BSS transition judgment information request from the communication device **13**, generates a Beacon Element control notification frame, and transmits the Beacon Element control notification frame to all the base stations **12**.

[0308] Further, only the Required Beacon Element ID corresponding to a service may be set beforehand, and the priority of each service may be included in the BSS transition judgment information request from the communication device **13**. In this case, information regarding the priority may be judged from information such as a priority code point (PCP) and, an access category (AC), or the like.

[0309] Further, regarding the table showing the correspondence between the service content and the Required Beacon Element ID as shown in FIG. **20**, for example, by the process of step **S76** in the flowchart of FIG. **7**, as a part of the procedure when the communication connection is newly established between the base station **12** and the communication device **13**, the table may be supplied to the controller **11** via the base station **12** with which the communication connection has been newly established from the communication device **13**, so as to be the information that has been designated by the communication device **13**.

[0310] It is to be noted that regarding the process, in step **S132** of FIG. **12**, the difference is only the process of deciding the content of the BSS transition judgment information with reference to FIG. **20**. Therefore, the description thereof will be omitted.

### 5. Third Application Example of First Embodiment

[0311] In the above description, an example in which the transition of the base station **12** is judged on the basis of the determination result of the communication quality degradation determination process regardless of the user's intention has been described. However, the determination result of the communication quality degradation determination process may be presented to the user, and the transition of the base station **12** may be made by a user's judgment.

[0312] That is, for example, in a case where the communication quality of a neighboring base station **12** is higher by the comparison result in the communication quality comparison process, and can be considered to be a candidate for the transition destination, the control unit **71** controls the display unit **74** to display, for example, a pop-up **101** representing that “AP switch candidate has been found” on a normal screen, as indicated in the left part of FIG. **21**. The user is able to recognize that the back of the transition destination has been found by the pop-up **101** being displayed.

[0313] The pop-up **101** is operated by the user for confirming the information regarding the base station **12** to become a candidate for the transition destination and considering the transition of the base station **12**, that is, the BSS transition, and by being tapped, for example, the display of the display unit **74** is switched so that, for example, a comparison result **102** as indicated in the right part of FIG. **21** is displayed.

[0314] In the comparison result **102** on the right side of FIG. **21**, “Please select one for connection” is represented at the top, and below the top, a display field **111** is displayed for presenting a comparison result for every judgment criterion in the base station **12** currently being connected with. Further, below the display field **111**, a display field **112** for presenting a comparison result for every judgment criterion in the base station **12**, which becomes a candidate for the transition destination, that is, a candidate for a switch destination.

[0315] In FIG. **21**, in the display field **111**, “currently connected AP” is represented at the uppermost level, indicating that the information regarding the base station **12** with which the connection is currently established is displayed. Then, in the display field **111**, from the top, the SSID of the base station **12** with which the connection is currently established is XXX. The RSSI is represented by a double circle, and is in a good condition. The BSS load is represented by a triangle mark, and is in a slightly bad state. The average delay is represented by a triangle mark to indicate that it is in a slightly bad state.

[0316] On the other hand, in the display field **112**, from the top, “switch candidate AP” is

represented, and the information regarding the base station **12** to become a candidate for the transition destination is displayed. Then, in the display field **112**, from the top, the SSID of the base station **12** to become a switch candidate is **YYY**. The RSSI is represented by a circle, and is in an ordinary state. The BSS load is represented by a triangle mark, and is in a slightly bad state. The average delay is represented by a triangle mark, and is in a slightly bad state.

[0317] It is to be noted that in a case where the comparison result **102** of FIG. **21** is displayed, it is assumed as a precondition that the BSS load and the average delay are higher in the priority order than the RSSI, in the judgment criteria. That is, in the comparison result **102** of FIG. **21**, as indicated by the display fields **111** and **112**, regarding the BSS load and the average delay, the base station **12** of a transition destination to become a switch candidate is better in the communication quality than the base station **12** with which the connection is currently established. As a result, it is considered that the switch candidate has been found.

[0318] The user is able to judge which base station **12** the connection is to be established with, on the basis of the information regarding the judgment criteria in the display fields **111** and **112**, and to select a connection destination by tapping either the display field **111** or **112**.

[0319] That is, in the case of FIG. **21**, when the display field **111** is tapped, the connection with the base station **12** currently connected with is continued. When the display field **112** is tapped, the connection with the base station **12** to become a candidate for the transition destination is applied for and the connection is switched.

Communication Quality Comparison Process in Third Application Example of First Embodiment

[0320] Next, a communication quality comparison process in a third application example of the first embodiment will be described with reference to the flowchart of FIG. **22**. It is to be noted that the process of steps **S281** to **S286** and **S291** to **S293** in the flowchart of FIG. **22** is similar to the process of steps **S201** to **S209** in the flowchart of FIG. **18**. Therefore, the description thereof will be omitted as appropriate.

[0321] That is, in step **S286**, in a case where it is determined that the communication quality of any of the neighboring base stations **12** is higher than the communication quality of the base station **12** with which the communication is currently established, with regard to the judgment criterion of the P-th priority, the process proceeds to step **S287**.

[0322] In step **S287**, the control unit **71** displays, on an ordinary screen displayed by the display unit **74**, a pop-up **101** shown in, for example, FIG. **21**, indicating that there is a base station **12** to become a switch candidate with a higher communication quality, from among the neighboring base stations **12**, than the communication quality of the base station **12** with which communication is currently established, with regard to the judgment criterion of the P-th priority.

[0323] In step **S288**, the control unit **71** determines whether or not the display unit **74** is operated as a touch panel and the pop-up **101** is tapped. In a case of being tapped, the process proceeds to step **S289**.

[0324] In step **S289**, the control unit **71** generates the display fields **111** and **112** respectively including the information regarding the communication qualities of the base station **12** with a higher priority, from among the neighboring base stations **12**, than the communication quality of the base station **12** with which the communication is currently established, and the base station **12** with which the connection is currently established, with regard to the judgment criterion of the P-th priority, and controls the display unit **74** to display as the comparison result **102**.

[0325] In step **S290**, the control unit **71** determines whether or not the display unit **74** is operated as a touch panel and the display field **112** is tapped to give an instruction for switching. In a case where the instruction is given for switching, the process proceeds to step **S291**.

[0326] In step **S291**, the control unit **71** judges that it is necessary to make a transition to the base station **12** with a higher communication quality, from among the neighboring base stations **12**, than the communication quality of the base station **12** with which the communication connection is currently established, and to establish the communication, with regard to the judgment criterion of

the P-th priority.

[0327] It is to be noted that in a case where the pop-up **101** is not tapped in step **S288**, or in a case where the display field **111** is tapped and an instruction on the transition of the base station **12** is not given in step **S290**, the process ends and the switching of the base station **12** is not conducted.

[0328] By the above process, the determination result of the communication quality degradation determination process is presented to the user, and the transition of the base station **12** according to a user's judgment is enabled.

[0329] Accordingly, for example, in a case where a base station **12** to become a switch candidate is found by moving from a predetermined location to another one, but the base station **12** returns to the original predetermined location within a short period of time, a user tries not to select the transition of the base station **12** so that an occurrence of a delay associated with the transition of the base station **12** can be avoided.

## 6. Second Embodiment

[0330] In the above description, the case where the communication system **1** including the controller **11**, the base stations **12-1** and **12-2**, and the communication device **13** has been described. However, the communication system **1** may have a configuration including base stations **12-1** and **12-2** and the communication device **13**.

[0331] That is, as shown in FIG. **23**, the communication system **1** may have a configuration including the base stations **12-1** and **12-2** and the communication device **13**.

[0332] It is to be noted that also in the communication system **1** of FIG. **23**, the description will be given as a precondition that the communication device **13** has established the connection for communication via the base station **12-1**.

[0333] That is, in such a case, the base station **12-1** with which the communication with the communication device **13** has been established also functions as the controller **11** and the base station **12-1** in FIG. **1**.

[0334] That is, the communication device **13** performs the communication quality degradation determination process, and transmits a determination result to the base station **12-1**. In response to this, the base station **12-1** performs either the BSS transition query process or the BSS transition judgment information request process by the controller **11** and the base station **12-1** in FIG. **1**, on the basis of a determination result of the communication quality degradation determination process.

### Communication Control Process in Communication System Including Base Station and Communication Device

[0335] Next, a communication control process in the communication system including the base stations **12-1** and **12-2** and the communication device **13** will be described with reference to the flowchart of FIG. **24**.

[0336] It is to be noted that, regarding a process of steps **S331** to **S334** and **S336**, and a process of steps **S351** to **S356**, **S371** to **S373**, and **S375** to **S377** in the flowchart of FIG. **24** are similar to the process of steps **S11**, **S32** to **S34**, and **S36**, and the process of steps **S51** to **S56**, and the process of steps **S71** to **S76** in FIG. **7**. Therefore, the description thereof will be omitted.

[0337] That is, in the process of step **S335**, the base station **12-1** performs the process of steps **S111**, **S102**, and **S114** in FIG. **11**, receives the BSS transition query, decides the transition destination, generates the BSS transition request, and transmits the BSS transition request to the communication device **13**.

[0338] Further, in the process of step **S337**, the base station **12-1** performs the process of steps **S141**, **S132**, **S133** (only the Beacon Element control notification is generated) and **S144** in FIG. **12**, receives the BSS transition judgment information request, determines the BSS transition judgment information, generates the Beacon Element control notification, and transmits the Beacon Element control notification to all the base stations **12**.

[0339] In this situation, upon reception of the Beacon Element control notification, in the base station **12-2**, in step **S374**, the control unit **51** of the base station **12-2** controls the data processing

unit **52** to generate a response signal to the Beacon Element control notification, and causes the wireless communication unit **53** to transmit the response signal to the base station **12-1**, from which the Beacon Element control notification has been transmitted.

[0340] In response to this, in step **S338**, the control unit **51** of the base station **12-2** controls the data processing unit **52** so that the wireless communication unit **53** receives the response signal to the Beacon Element control notification.

[0341] Then, in step **S339**, the control unit **51** of the base station **12-2** controls the data processing unit **52** to generate a Beacon in response to the Beacon Element control notification, and causes the wireless communication unit **53** to transmit the Beacon to the communication device **13**.

Beacon Element Control Notification Frame in Communication System Shown in FIG. **23**

[0342] A Beacon Element control notification frame to be transmitted from the base station **12-1** to the base station **12-2** in the communication system of FIG. **23** has, for example, a configuration example as shown in FIG. **25**.

[0343] In the Beacon Element control notification frame in FIG. **25**, from the left in the upper level in the figure, Element ID of one Octet, Length of one Octet, Element ID Extension of one Octet, and Required Beacon Element ID of N Octets are stored.

[0344] Element ID is information of an identifier of the Beacon Element control notification, and Length is information regarding a data length.

[0345] In addition, Element ID Extension is an extension of the identifier of the Beacon Element control notification, and stores information indicating whether or not Steering Info is stored.

[0346] It is to be noted that Required Beacon Element ID is similar to the Beacon Element control notification frame that has been described with reference to FIG. **16**. Therefore, the description thereof will be omitted.

[0347] That is, the Beacon Element control notification frame shown in FIG. **25** has a tlv format.

[0348] Also in the above configuration, in a similar manner to the communication system **1** in FIG. **3**, the achievement of the stable communication in response to a change in the communication environment of a wireless local area network (LAN) is enabled.

## 7. Example Performed by Software

[0349] The above-described series of processes, by the way, can be performed by hardware, but can also be performed by software. In a case where the series of processes is performed by software, a program that constitutes the software is installed from a recording medium into a computer embedded in dedicated hardware or into, for example, a general-purpose computer capable of conducting various functions by installing various programs.

[0350] FIG. **26** shows a configuration example of the general-purpose computer. Such a personal computer includes a built-in central processing unit (CPU) **1001**. An input and output interface **1005** is connected with the CPU **1001** via a bus **1004**. A read only memory (ROM) **1002** and a random access memory (RAM) **1003** are connected with the bus **1004**.

[0351] The input and output interface **1005** includes an input unit **1006** including input devices such as a keyboard and a mouse for a user to input operation commands, an output unit **1007** for outputting a process operation screen and an image of a process result to a display device, a storage unit **1008** including a hard disk drive for storing programs and various data, a local area network (LAN) adapter, and the like, and is connected with a communication unit **1009** for performing a communication process via a network represented by the Internet. In addition, a drive **1010** is connected for reading and writing data to and from a removable storage medium **1011**, such as a magnetic disk (including a flexible disk), an optical disk (including a compact disc-read only memory (CD-ROM), a digital versatile disc (DVD)), a magneto-optical disk (including mini disc (MD)), or a semiconductor memory.

[0352] The CPU **1001** performs various processes according to a program stored in the ROM **1002** or a program installed from the removable storage medium **1011** such as the magnetic disk, the optical disk, the magneto-optical disk, or the semiconductor memory, into the storage unit **1008**,

and loaded from the storage unit **1008** onto the RAM **1003**. The RAM **1003** also appropriately stores data necessary for the CPU **1001** to perform the various processes.

[0353] In the computer configured as described above, the CPU **1001** loads the program stored in the storage unit **1008** onto the RAM **1003** via the input and output interface **1005** and the bus **1004**, and performs the above-described series of processes, for example.

[0354] The program conducted by the computer (the CPU **1001**) can be recorded and supplied on the removable storage medium **1011** as a package medium or the like, for example. In addition, the program can be also supplied via a wired or wireless transmission medium such as a local area network, the Internet, and digital satellite broadcasting.

[0355] In the computer, the program can be installed into the storage unit **1008** via the input and output interface **1005** by attaching the removable storage medium **1011** to the drive **1010**. Further, the program can be received by the communication unit **1009** and installed in the storage unit **1008** via a wired or wireless transmission medium. In addition, the program can be installed beforehand in the ROM **1002** or the storage unit **1008**.

[0356] It is to be noted that the program performed by the computer may be a program that is processed in a time-series order according to the order described in the present specification, or may be a program that is processed in parallel or at a necessary timing such as when a call is made, or the like.

[0357] It is to be noted that the CPU **1001** in FIG. **26** achieves the functions of the control unit **31** in FIG. **4**, the control unit **51** in FIG. **5**, and the control unit **71** in FIG. **6**.

[0358] Further, in the present specification, the system means a group of a plurality of component elements (devices, modules (parts), and the like), and does not matter whether or not all the component elements are included in the same housing. Therefore, a plurality of devices accommodated in separate housings and connected via networks, and a single device in which a plurality of modules is accommodated in a single housing are both systems.

[0359] It is to be noted that the embodiments of the present disclosure are not limited to the above-described embodiments, and various changes can be made without departing from the gist of the present disclosure.

[0360] For example, the present disclosure can be configured as cloud computing in which a single function is shared by a plurality of devices via networks, and is processed in cooperation.

[0361] Further, each step that has been described in the above-described flowcharts can be performed by a single device, or can be shared and performed by a plurality of devices.

[0362] Further, in a case where a single step includes a plurality of processes, the plurality of processes included in such a single step can be performed by a single device or shared by a plurality of devices.

[0363] It is to be noted that the present disclosure can also have the following configuration.

<1> A wireless device including: [0364] a control unit configured to control inclusion information included in a Beacon signal in a wireless base station that is to establish a communication connection for communication with a wireless terminal.

<2> The wireless device described in <1>, [0365] in which in a case where the wireless terminal selects a wireless base station with which the wireless terminal is to establish the communication connection for the communication on the basis of a communication quality of the wireless base station, the control unit controls the inclusion information included in the Beacon signal in the wireless base station.

<3> The wireless device described in <2>, [0366] in which the control unit transmits, to the wireless terminal, information for setting to determine whether or not the wireless terminal selects a new wireless base station with which the wireless terminal is to establish the communication connection for the communication on the basis of the communication quality with the wireless base station with which the communication connection is currently established.

<4> The wireless device described in <3>, [0367] in which the control unit transmits, to the

wireless terminal, the information for setting to determine whether or not the wireless terminal selects the new wireless base station with which the wireless terminal is to establish the communication connection for the communication on the basis of at least any of a received electric power, a packet success rate, or a standby period of the communication quality with the wireless base station with which the communication connection is currently established.

<5> The wireless device described in <4>, [0368] in which the control unit transmits, to the wireless terminal, the information for setting to determine whether or not the wireless terminal selects the new wireless base station with which the wireless terminal is to establish the communication connection for the communication on the basis of a comparison between a predetermined threshold value and the at least any of the received electric power, the packet success rate, or the standby period of the communication quality with the wireless base station with which the communication connection is currently established.

<6> The wireless device described in <5>, [0369] in which the predetermined threshold value includes a threshold value higher than a level at which the wireless base station is caused to make a transition immediately, [0370] in a case where the at least any of the received electric power, the packet success rate, or the standby period of the communication quality with the wireless base station with which the communication connection is currently established is lower than the predetermined threshold value, the control unit transmits, to the wireless terminal, the information for setting to determine whether or not the wireless terminal selects the new wireless base station with which the wireless terminal is to establish the communication connection for the communication.

<7> The wireless device described in <1>, [0371] in which the control unit controls the inclusion information included in the Beacon signal on the basis of information designated in the wireless terminal.

<8> The wireless device described in <7>, [0372] in which notification of the information designated in the wireless terminal is provided by the wireless terminal.

<9> The wireless device described in <7>, [0373] in which the information designated in the wireless terminal is specified by a service type of the wireless terminal.

<10> The wireless device described in any of <1> to <9>, [0374] in which the control unit transmits, to the wireless base station, a control notification for designating the inclusion information included in the Beacon signal as an Element ID, and [0375] the wireless base station controls the inclusion information included in the Beacon signal on the basis of the Element ID in the control notification, and transmits the Beacon signal.

<11> The wireless device described in <10>, [0376] in which the wireless base station further includes information for specifying a period or a timing at which the inclusion information included in the Beacon signal is included.

<12> A wireless communication method by a wireless device, the wireless communication method including: [0377] a control process for controlling inclusion information included in a Beacon signal in a wireless base station that is to establish a communication connection for communication with a wireless terminal.

<13> A wireless terminal including: [0378] a control unit configured to select a new wireless base station with which the wireless terminal is to establish a communication connection on the basis of inclusion information included in a Beacon signal transmitted from a neighboring wireless base station.

<14> The wireless terminal described in <13>, [0379] in which the control unit transmits a judgment criterion information for selecting a wireless base station with which the wireless terminal is to establish the communication connection, to a wireless device that controls the inclusion information included in the Beacon signal.

<15> The wireless terminal described in <14>, [0380] in which the judgment criterion information includes information indicating a plurality of priorities of the judgment criterion information.

<16> The wireless terminal described in <14>, [0381] in which the judgment criterion information includes a received electric power, a BSS load, an access delay, and a signal quality.

<17> The wireless terminal described in <13>, [0382] in which the control unit presents a candidate for a new wireless base station with which the wireless terminal is to establish the communication connection on the basis of the inclusion information included in the Beacon signal transmitted from the neighboring wireless base station, and in a case where an operation for giving an instruction on an establishment of the communication connection with the candidate that has been presented, the control unit selects the candidate that has been operated as the new wireless base station with which the wireless terminal is to establish the communication connection.

<18> A wireless communication method by a wireless terminal, the wireless communication method including: [0383] a control process for selecting a new wireless base station with which the wireless terminal is to establish a communication connection on the basis of inclusion information included in a Beacon signal transmitted from a neighboring wireless base station.

<19> A wireless base station including: [0384] a control unit configured to receive a control notification for providing notification of inclusion information to be included in a Beacon signal, and configured to transmit the Beacon signal including the inclusion information on the basis of the control notification.

<20> A wireless communication method by a wireless base station, the wireless communication method including: [0385] a control process for receiving a control notification for providing notification of inclusion information to be included in a Beacon signal, and transmitting the Beacon signal including the inclusion information on the basis of the control notification.

#### REFERENCE SIGNS LIST

[0386] **11** Controller [0387] **12, 12-1, 12-2** Base station [0388] **13** Communication device [0389] **31** Control unit [0390] **32** Data processing unit [0391] **33** Wireless communication unit [0392] **34** Wired communication unit [0393] **35** Network control unit [0394] **51** Control unit [0395] **52** Data processing unit [0396] **53** Wireless communication unit [0397] **54** Wired communication unit [0398] **55** Display unit [0399] **56** Operation unit [0400] **71** Control unit [0401] **72** Data processing unit [0402] **73** Wireless communication unit [0403] **74** Display unit

## Claims

**1.** A wireless device comprising: a control unit configured to control inclusion information included in a Beacon signal in a wireless base station that is to establish a communication connection for communication with a wireless terminal.

---