

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250257791

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Folkesson; Johan et al.

---

### TRANSMISSION ARRANGEMENT FOR AN ELECTRICALLY PROPELLED VEHICLE

---

#### Abstract

The present disclosure relates to a transmission arrangement including an input shaft, and an output shaft, a first gear stage including a first gear wheel and a second gear wheel drivingly connected to each other, a first planetary gear set including a first sun gear, a first ring gear and a first planet carrier, wherein the first planet carrier is rotationally connected to the output shaft, and a crawler unit being drivingly connectable between the first planetary gear set and the output shaft by a first clutch, wherein the first clutch is configured to rotationally connect one of the plurality of gear members of the crawler unit to one of the first ring gear, the first planet carrier or a stationary member of the transmission arrangement, to cause the first ring gear to rotate in an opposite direction compared to a rotational direction of the first planet carrier.

---

**Inventors:** Folkesson; Johan (SKENE, SE), Norberg; Sven (Hisings Backa, SE), Hedman; Anders (MARSTRAND, SE)

**Applicant:** Volvo Truck Corporation (GÖTEBORG, SE)

**Family ID:** 1000008591539

**Appl. No.:** 19/046937

**Filed:** February 06, 2025

#### Foreign Application Priority Data

EP 24157498.7

Feb. 14, 2024

---

#### Publication Classification

**Int. Cl.:** F16H3/66 (20060101)

**U.S. Cl.:**

## Background/Summary

### CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to European Patent Application No. 24157498.7, filed on Feb. 14, 2024, the disclosure and content of which is incorporated by reference herein in its entirety.

### TECHNICAL FIELD

[0002] The disclosure relates generally to vehicle transmissions. In particular aspects, the disclosure relates to a transmission arrangement for an electrically propelled vehicle. The disclosure can be applied to heavy-duty vehicles, such as trucks, buses, and construction equipment, among other vehicle types. Although the disclosure may be described with respect to a particular vehicle, the disclosure is not restricted to any particular vehicle.

### BACKGROUND

[0003] Propulsion systems for vehicles are continuously developed to meet the demands from the market. A particular aspect relates to the emission of environmentally harmful exhaust gases. Therefore, vehicles propelled by electric traction motors have been increasingly popular, both for cars as well as for heavy duty vehicles.

[0004] For cars, a transmission may conventionally comprise a fixed ratio between an input shaft and an output shaft to provide a desired output torque and a desired cruise speed. However, for heavy duty vehicles, the demands for startability and a suitable rotational speed of the electric machine requires a transmission that enables for a plurality of gear states due to e.g., the relatively large weight of this type of vehicle. The omission of a transmission arrangement for a heavy duty vehicle would, for example, require the use of powerful and expensive electric traction motors.

[0005] Conventional transmission arrangements for heavy duty vehicle are either bulky or are not providing for the desired functionalities, such as enabling for a sufficiently large speed reduction during crawling. There is thus a desire to provide a compact transmission arrangement that can enable for desired speed ranges as well as providing a sufficiently high torque to the wheels during start-up.

### SUMMARY

[0006] According to a first aspect of the disclosure, there is provided a transmission arrangement for a vehicle, the transmission arrangement comprising an input shaft drivingly connectable to an electric traction motor, and an output shaft drivingly connectable to a pair of wheels of the vehicle, a first gear stage comprising a first gear wheel and a second gear wheel drivingly connected to each other, the first gear wheel being rotationally connected to the input shaft, a first planetary gear set comprising a first sun gear, a first ring gear and a first planet carrier carrying a first set of planet gears, the first set of planet gears being in meshing engagement with the first ring gear and the first sun gear, wherein the first sun gear and the first ring gear are rotationally connectable to the second gear wheel of the first gear stage, and wherein the first planet carrier is rotationally connected to the output shaft, and a crawler unit comprising a plurality of gear members, the crawler unit being drivingly connectable between the first planetary gear set and the output shaft by a first clutch, wherein the first clutch is configured to rotationally connect one of the plurality of gear members of the crawler unit to one of the first ring gear, the first planet carrier or a stationary member of the transmission arrangement, to cause the first ring gear to rotate in an opposite direction compared to a rotational direction of the first planet carrier.

[0007] The first aspect of the disclosure may seek to at least partly mitigate the problem of

transmission arrangements being bulky to enable for the desired functionalities associated with heavy duty vehicle implementations. A technical benefit may thus include that a compact transmission arrangement is provided, which compact transmission arrangement enables for a desirable number of selectable speed ratios as well as being provided with a crawler unit with a large speed reduction between the input shaft and the output shaft. The large speed reduction enables for large weight vehicles to start from standstill in a desirable manner. The inventors of the present disclosure have realized that by providing a crawler unit with a first clutch that causes the first ring gear to rotate in an opposite direction compared to a rotational direction of the first planet carrier when the first clutch is engaged further increases the speed reduction between the input shaft and the output shaft. A technical benefit is thus that the wheels of the vehicle can be provided with a high torque during crawling when the first clutch is engaged.

[0008] In the following and throughout the description, the wording “rotationally connected to” and “rotationally connect” should be interpreted such that a component of the transmission arrangement is connected to another component of the transmission arrangement in such a way that the components rotate in the same direction and with the same rotational speed. The components thus rotate in the same direction and with the same rotational speed when being rotationally connected to each other. The wording “connectable” should thus be construed as connectable by a clutch, the components are hence selectively connectable. In the above, when one of the plurality of gear members of the crawler unit is rotationally connected to the stationary member, the gear member of the crawler unit is also stationary which should be construed as falling within the scope of the definition “rotationally connected to”.

[0009] Further, the wording “drivingly connected to” and “drivingly connectable to” should be interpreted as two components being either directly connected to each other, i.e. the components rotate in the same direction and with the same rotational speed, or connected to each other with one or more gear wheels therebetween. In the latter example, when a first component rotates, then a second component also rotates with a ratio to the first component. The first and second components may not necessarily rotate in the same direction and with the same rotational speed.

[0010] In some embodiments, the first gear stage is a reduction gear stage in which, during operation of the transmission arrangement, the first gear wheel rotates at a higher rotational speed compared to a rotational speed of the second gear wheel. A technical benefit may include that the electric machine can be allowed to rotate faster. The size of an electric machine is dependent on the maximum torque it is able to produce. High rotational speed can thus compensate for lower torque levels and the electric machine can hereby be made smaller which in turn reduces the cost for such electric machine.

[0011] The first and second gear wheels may be arranged in meshing engagement with each other. Alternatively, one or more additional gear wheels may be provided between the first and second gear wheels.

[0012] In some embodiments, the first sun gear of the first planetary gear set is rotationally connectable to the second gear wheel of the first gear stage by a second clutch of the transmission arrangement. A technical benefit may include that the first sun gear is rotationally connected to the second gear wheel for some gear states but not for others.

[0013] In a similar vein as described above in relation to the interpretation of the definition “rotationally connected to”, the wording “rotationally connectable to” should be construed such that the components of the transmission arrangement rotate in the same direction and with the same rotational speed when being connected to each other by a clutch, which clutch in the specific example is the second clutch.

[0014] In some embodiments, the first ring gear of the first planetary gear set is rotationally connectable to the second gear wheel of the first gear stage by a third clutch of the transmission arrangement. A technical benefit may include that the first ring gear is rotationally connected to the second gear wheel for some gear states but not for others.

[0015] In some embodiments, the first ring gear of first planetary gear set is rotationally connectable to the stationary member via the third clutch.

[0016] The third clutch should also be construed as being able to assume a neutral position in which the third clutch is not connected to any one of the second gear wheel of the first gear stage or the stationary member. In such case, the ring gear rotates without direct interaction with the second gear wheel or the stationary member.

[0017] With the implementation of the second clutch and the third clutch, three gear ratios are obtainable for the transmission arrangement. By means of the first clutch of the crawler unit, a fourth gear ratio is provided.

[0018] In some embodiments, the crawler unit comprises a second planetary gear set, the plurality of gear members of the crawler unit comprising a second sun gear, a second ring gear and a second planet carrier carrying a second set of planet gears, the second set of planet gears being in meshing engagement with the second ring gear and the second sun gear.

[0019] In some embodiments, the second sun gear is rotationally connected to the first planet carrier.

[0020] In some embodiments, the second ring gear is rotationally connectable to the first ring gear via the first clutch of the crawler unit. A technical benefit may include that the opposite rotational direction of the ring gear provides a sufficiently large ratio between the second gear wheel and the first planet carrier. Further, the crawler gear state may hereby be engaged at a large diameter which will generate low load on gear teeth.

[0021] In some embodiments, the second planet carrier is rotationally connected to the stationary member of the transmission arrangement. A technical benefit may include that the planet carrier and its planet wheels are not exposed to centrifugal loads.

[0022] In some embodiments, the second ring gear is rotationally connected to the first ring gear.

[0023] In some embodiments, the second planet carrier is rotationally connectable to the stationary member via the first clutch of the crawler unit.

[0024] In some embodiments, the second ring gear is rotationally connected to the first ring gear.

[0025] In some embodiments, the second planet carrier is rotationally connected to the stationary member.

[0026] In some embodiments, the second sun gear is rotationally connectable to the first planet carrier via the first clutch of the crawler unit.

[0027] A technical benefit may include that the crawler gear state can be engaged via the second sun gear. The second sun gear can hereby be provided with a small diameter since it will not be exposed to high torque loads.

[0028] In some embodiments, the second ring gear is rotationally connected to the first planet carrier.

[0029] In some embodiments, the second planet carrier is rotationally connected to the stationary member.

[0030] In some embodiments, the second sun gear is rotationally connectable to the first ring gear via the first clutch of the crawler unit.

[0031] A technical benefit may include that a large rotation in the opposite direction is provided for the first ring gear, which in turn generates a large ratio between the second gear wheel and the output shaft. In addition, the second sun gear can be provided with a small diameter since it will not be exposed to high torque loads.

[0032] In some embodiments, the second sun gear is rotationally connected to the first ring gear.

[0033] In some embodiments, the second ring gear is rotationally connected to the first planet carrier.

[0034] In some embodiments, the second planet carrier is rotationally connectable to the stationary member via the first clutch of the crawler unit.

[0035] A technical benefit may include that a large rotation in the opposite direction is provided for

the first ring gear, which in turn generates a large ratio between the second gear wheel and the output shaft. In addition, the second sun gear can be provided with a small diameter since it will not be exposed to high torque loads.

[0036] In some embodiments, the second sun gear is rotationally connected to the first ring gear.

[0037] In some embodiments, the second planet carrier is rotationally connected to the stationary member.

[0038] In some embodiments, the second ring gear is rotationally connectable to the first planet carrier via the first clutch of the crawler unit.

[0039] A technical benefit may include that the crawler gear state can be engaged at a large diameter which will provide low loads on the gear teeth. Also, since the second planet carrier is rotationally connected to the stationary member, the second planet carrier and its planet wheels will not be exposed to centrifugal forces.

[0040] In some embodiments, the crawler unit comprises a crawler gear stage, the crawler gear stage comprising a set of crawler gear wheels drivingly connectable between the first planet carrier and the first ring gear via the first clutch of the crawler unit. The first clutch of the crawler unit may be positioned to rotationally connect a first gear wheel of the set of gear wheels to the first planet carrier. Optionally, the first clutch of the crawler unit may be positioned to rotationally connect a second gear wheel and a third gear wheel of the set of gear wheels to each other, wherein the second gear wheel is arranged in meshing engagement with the first gear wheel, and the third gear wheel is rotationally connected to the first ring gear. As another option, the first clutch of the crawler unit may be positioned to rotationally connect the third gear wheel of the set of gear wheels to the first ring gear.

[0041] A technical benefit may include that there is an increased freedom to choose ratio between the first ring gear and the output shaft, thereby simplifying the adaption to specific purposes for the transmission arrangement.

[0042] Furthermore, the above described first clutch may advantageously be a first dog clutch. A technical benefit may include that a dog clutch has low power losses when being disengaged. The second and third clutches may also be a respective second and third dog clutch.

[0043] According to a second aspect, there is provided a powertrain for an electrically propelled vehicle, the powertrain comprising: an electric traction motor, and a transmission arrangement according to any one of the examples described above in relation to the first aspect, wherein the input shaft of the transmission arrangement is drivingly connected to the electric traction motor.

[0044] Effects and features of the second aspect are largely analogous to those described above in relation to the first aspect.

[0045] According to a third aspect, there is provided a vehicle comprising the transmission arrangement according to any one of the examples described above in relation to the first aspect, or the powertrain according to the above described second aspect.

[0046] Effects and features of the third aspect are largely analogous to those described above in relation to the first aspect.

[0047] The disclosed aspects, examples, and/or accompanying claims may be suitably combined with each other as would be apparent to anyone of ordinary skill in the art. Additional features and advantages are disclosed in the following description, claims, and drawings, and in part will be readily apparent therefrom to those skilled in the art or recognized by practicing the disclosure as described herein.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0048] Examples are described in more detail below with reference to the appended drawings.

[0049] FIG. **1** is an exemplary vehicle according to an example,  
[0050] FIGS. **2-8** are schematic illustrations of exemplary transmission arrangements, and  
[0051] FIG. **9** is a schematic illustration of an exemplary powertrain comprising a transmission arrangement.

#### DETAILED DESCRIPTION

[0052] The detailed description set forth below provides information and examples of the disclosed technology with sufficient detail to enable those skilled in the art to practice the disclosure.

[0053] The following disclosure aims at providing a compact and efficient transmission arrangement that can enable for a desirable number of speed ratios as well as to provide a crawler unit with a large speed reduction between the input shaft and the output shaft.

[0054] With initial reference to FIG. **1**, in which an exemplary vehicle **10** is depicted. The exemplified vehicle **10** is configured to be at least partly propelled by an electric traction motor **110**. As will be evident from the below description, and as can be seen in FIGS. **2-9**, the electric traction motor **110** is drivingly connected to a transmission arrangement **120**, **220**, **320**, **420**, **520**, **620**, **720**.

[0055] In order to describe the transmission arrangement, reference is now made to FIG. **2** in which a first example of the transmission arrangement **120** is depicted. The transmission arrangement **120** comprises an input shaft **115**. The input shaft **115** is drivingly connected to the electric traction motor **110**. In the example depicted in FIG. **2**, as well as in FIGS. **3-9**, the input shaft **115** is directly connected to the electric traction motor **110**. It should however be readily understood that a transmission component, such as e.g., a clutch and/or a gear stage may be present between the input shaft **115** and the electric traction motor **110**.

[0056] Further, the transmission arrangement **120** comprises a first gear stage **130**. The first gear stage **130** comprises a first gear wheel **131** and a second gear wheel **132** drivingly connected to each other. In some embodiments, the first gear stage **130** is a reduction gear stage in which, during operation of the transmission arrangement, the first gear wheel **131** rotates at a higher rotational speed compared to a rotational speed of the second gear wheel **132**. The first **131** and second **132** gear wheels are in the example illustrated in FIG. **2** arranged in meshing engagement with each other. In such implementation, the first gear wheel **131** comprises a lower number of gear teeth compared to a number of gear teeth of the second gear wheel **132**. It should however be readily understood that one or more gear wheels may be positioned between the first **131** and second **132** gear wheels. The first gear wheel **131** is rotationally connected to the input shaft **115**, while the second gear wheel is rotationally connected to a transmission shaft **121**, also referred to as an inter-gearset shaft. In some embodiments, the transmission shaft **121** is hollow to accommodate an additional shaft **122**.

[0057] The transmission arrangement **120** further comprises a first planetary gear set **140**, which first planetary gear set **140** comprises a first sun gear **141**, a first ring gear **144**, and a first planet carrier **142** carrying a first set of planet gears **143**. The first set of planet gears **143** are in meshing engagement with the first ring gear **144** and the first sun gear **141**.

[0058] Moreover, the transmission arrangement **120** also comprises a crawler unit **150**. The crawler unit **150** comprises a plurality of gear members **151**, **153**, **154**. In the example depicted in FIG. **2**, the plurality of gear members are arranged as gear members of a second planetary gear set **160**. The second planetary gear set **160** comprises a second sun gear **151**, a second ring gear **154** and a second planet carrier **152** carrying a second set of planet gears **153**, wherein the second set of planet gears **153** is in meshing engagement with the second ring gear **154** and the second sun gear **151**.

[0059] Further, the second sun gear **151** is rotationally connected to the first planet carrier **142**. The second sun gear **151** is also rotationally connected to an output shaft **190** of the transmission arrangement **120**, which output shaft **190** is drivingly connectable to a pair of wheels of the vehicle, as can be seen in FIG. **9**. Since the second sun gear **151** is rotationally connected to the first planet

carrier **142** as well as to the output shaft **190**, the first planet carrier **142** is also rotationally connected to the output shaft **190**. Moreover, the second planet carrier **152** is rotationally connected to a stationary member **159** of the transmission arrangement **120**. The stationary member **159** may be a transmission housing (not shown) accommodating the transmission arrangement **120**. By rotationally connecting the planet carrier **152** to the stationary member **159**, the planet carrier **152** is maintained stationary for each of the gear states described below. Finally, the second ring gear **154** is rotationally connectable to the first ring gear **144** by a first clutch **155** of the crawler unit **150**. The first clutch **155** is thus configured to assume a crawler engagement mode in which the crawler unit **150** is drivably connected to the first planetary gear set **140** by rotationally connecting the second ring gear **154** to the first ring gear **144**. The first clutch **155** is also configured to a crawler disengagement mode in which the crawler unit **150** is disconnected from the first planetary gear set **140** by arranging the first clutch **155** in a neutral position.

[0060] Turning again to the first planetary gear set **140**. The first sun gear **141** of the first planetary gear set **140** is rotationally connected to the above described additional shaft **122**. The additional shaft **122** is rotationally connectable to the second gear wheel **132** of the first gear stage **130** by a second clutch **146**. As such, the first sun gear **141** is rotationally connectable to the second gear wheel **132** via the second clutch **146**. The second clutch **146** is further configured to rotationally connect the first sun gear **141** to the stationary member **149a**. Moreover, the first ring gear **144** of the first planetary gear set **140** is rotationally connectable to the transmission shaft **121** by a third clutch **145**. As such, the third clutch **145** is configured to rotationally connect the first ring gear **144** to the second gear wheel **132** of the first gear stage **130**. The third clutch **145** is further configured to rotationally connect the first ring gear **144** to the stationary member **149b**. In addition, the third clutch **145** is also configured to assume a neutral position in which the first ring gear **144** is not rotationally connected to any one of the second gear wheel **132** and the stationary member **149**, i.e. the first ring gear **144** rotates freely.

[0061] The above describe stationary member **149a** to which the second clutch **146** is connectable, the stationary member **149b** to which the third clutch **145** is connectable and the stationary member rotationally connected to the second planet carrier **152** may be one and the same stationary member, such as e.g., the above indicated transmission housing. The stationary members may however be formed by different transmission components as long as being stationary relative to the rotational components to which they are connected or connectable.

[0062] The transmission arrangement **120** described above in relation to the example depicted in FIG. 2 is configured to assume three gear states, i.e. three different speed ratios, as well as to assume a crawler gear. A first gear state is assumed by positioning the first clutch **155** in neutral position, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the second gear wheel **132**, and positioning the third clutch **145** to rotationally connect the first ring gear **144** to the stationary member **149b**. Hereby, the first ring gear **144** is stationary and the first sun gear **141** is driven, whereby a first speed reduction is obtained between the input shaft and the output shaft. The second gear wheel **132**, the first sun gear **141**, the first planet carrier **142**, and the output shaft **190** all rotate in the same direction.

[0063] A second gear state is assumed by positioning the first clutch **155** in neutral position, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the stationary member **149a**, and positioning the third clutch **145** to rotationally connect the first ring gear **144** to the second gear wheel **132**. Hereby, the first sun gear **141** is stationary and the first ring gear **144** is driven, whereby a second speed reduction is obtained between the input shaft and the output shaft. The second speed reduction is lower/smaller compared to the first speed reduction. The second gear wheel **132**, the first ring gear **144**, the first planet carrier **142**, and the output shaft **190** all rotate in the same direction.

[0064] A third gear state is assumed by positioning the first clutch **155** in neutral position, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the second gear

wheel **132**, and positioning the third clutch **145** to rotationally connect the first ring gear **144** to the second gear wheel **132**. Hereby, a direct gear is obtained where the second gear wheel **132**, the first sun gear **141**, the first ring gear **144**, the first planet carrier **142**, and the output shaft **190** all rotate with the same rotational speed in the same direction.

[0065] The crawler gear is assumed by positioning the first clutch **155** to rotationally connect the second ring gear **154** to the first ring gear **144**, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the second gear wheel **132**, and positioning the third clutch **145** to assume the neutral position. Hereby, a third speed reduction is obtained between the input shaft and the output shaft in which the first ring gear **144** and the first planet carrier **142** rotates in opposite directions. The third speed reduction is higher/larger than the first speed reduction. In other words, the output shaft rotates at a lower rotational speed relative to the input shaft for the third speed reduction compared to the relative rotation speed of the input and output shafts for the first speed reduction. The second gear wheel **132**, the first sun gear **141**, the first planet carrier **142**, the second sun gear **151** and the output shaft **190** all rotate in the same direction, while the first **144** and second **154** ring gears rotate in the opposite direction.

[0066] In order to describe the transmission arrangement **220** according to another example, reference is made to FIG. **3**. The difference between the example depicted in FIG. **2** and the example depicted in FIG. **3** is the crawler unit and how it is connected to the first planetary gear set **140** and the stationary member. The following will only describe the differences between the examples in FIGS. **2** and **3**.

[0067] In the example illustrated in FIG. **3**, the second ring gear **154** is rotationally connected to the first ring gear **144**. The second planet carrier **152** is rotationally connectable to the stationary member **159** via the first clutch **155** of the crawler unit **150**.

[0068] The transmission arrangement **220** in the example depicted in FIG. **3** is configured to assume three gear states, i.e. three different speed ratios, as well as to assume a crawler gear. A first gear state is assumed by positioning the first clutch **155** in neutral position, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the second gear wheel **132**, and positioning the third clutch **145** to rotationally connect the first ring gear **144** to the stationary member **149b**. Hereby, the first ring gear **144** is stationary and the first sun gear **141** is driven, whereby a first speed reduction is obtained between the input shaft and the output shaft.

[0069] A second gear state is assumed by positioning the first clutch **155** in neutral position, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the stationary member **149a**, and positioning the third clutch **145** to rotationally connect the first ring gear **144** to the second gear wheel **132**. Hereby, the first sun gear **141** is stationary and the first ring gear **144** is driven, whereby a second speed reduction is obtained between the input shaft and the output shaft. The second speed reduction is lower/smaller compared to the first speed reduction.

[0070] A third gear state is assumed by positioning the first clutch **155** in neutral position, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the second gear wheel **132**, and positioning the third clutch **145** to rotationally connect the first ring gear **144** to the second gear wheel **132**. Hereby, a direct gear is obtained where the second gear wheel **132**, the first sun gear **141**, the first ring gear **144**, the first planet carrier **142**, and the output shaft **190** all rotate with the same rotational speed in the same direction. In the direct gear of the example illustrated in FIG. **3**, there is no relative rotation between the second sun gear **151**, the second planet carrier **152**, the second set of planet gears **153** and the second ring gear **154**, which may reduce power losses.

[0071] The crawler gear is assumed by positioning the first clutch **155** to rotationally connect the second planet carrier gear **152** to the stationary member **159**, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the second gear wheel **132**, and positioning the third clutch **145** to assume the neutral position. Hereby, a third speed reduction is obtained between the input shaft and the output shaft in which the first ring gear **144** and the first planet carrier **142** rotates in opposite directions. The third speed reduction is higher/larger than the first speed



reduction. In other words, the output shaft rotates at a lower rotational speed relative to the input shaft for the third speed reduction compared to the relative rotation speed of the input and output shafts for the first speed reduction.

[0072] In order to describe the transmission arrangement **320** according to another example, reference is made to FIG. **4**. The difference between the examples depicted in FIGS. **2-3** and the example depicted in FIG. **4** is the crawler unit and how it is connected to the first planetary gear set **140** and the stationary member. The following will mainly describe the differences between the examples in FIGS. **2-3** and the example in FIG. **4**.

[0073] In the example illustrated in FIG. **4**, the second ring gear **154** is rotationally connected to the first ring gear **144**. The second planet carrier **152** is rotationally connected to the stationary member **159**, while the second sun gear **151** is rotationally connectable to the first planet carrier **142** via the first clutch **155** of the crawler unit **150**.

[0074] The transmission arrangement **320** in the example depicted in FIG. **4** is configured to assume three gear states, i.e. three different speed ratios, as well as to assume a crawler gear. A first gear state is assumed by positioning the first clutch **155** in neutral position, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the second gear wheel **132**, and positioning the third clutch **145** to rotationally connect the first ring gear **144** to the stationary member **149b**. Hereby, the first ring gear **144** is stationary and the first sun gear **141** is driven, whereby a first speed reduction is obtained between the input shaft and the output shaft.

[0075] A second gear state is assumed by positioning the first clutch **155** in neutral position, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the stationary member **149a**, and positioning the third clutch **145** to rotationally connect the first ring gear **144** to the second gear wheel **132**. Hereby, the first sun gear **141** is stationary and the first ring gear **144** is driven, whereby a second speed reduction is obtained between the input shaft and the output shaft. The second speed reduction is lower/smaller compared to the first speed reduction.

[0076] A third gear state is assumed by positioning the first clutch **155** in neutral position, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the second gear wheel **132**, and positioning the third clutch **145** to rotationally connect the first ring gear **144** to the second gear wheel **132**. Hereby, a direct gear is obtained where the second gear wheel **132**, the first ring gear **144**, the first planet carrier **142**, and the output shaft **190** all rotate in the same direction.

[0077] The crawler gear is assumed by positioning the first clutch **155** to rotationally connect the second sun gear **151** to the first planet carrier **142**, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the second gear wheel **132**, and positioning the third clutch **145** to assume the neutral position. Hereby, a third speed reduction is obtained between the input shaft and the output shaft in which the first ring gear **144** and the first planet carrier **142** rotates in opposite directions. The third speed reduction is higher/larger than the first speed reduction. In other words, the output shaft rotates at a lower rotational speed relative to the input shaft for the third speed reduction compared to the relative rotation speed of the input and output shafts for the first speed reduction.

[0078] In order to describe the transmission arrangement **420** according to another example, reference is made to FIG. **5**. The difference between the example depicted in FIGS. **2-4** and the example depicted in FIG. **5** is the crawler unit and how it is connected to the first planetary gear set **140** and the stationary member. The following will mainly describe the differences between the examples in FIGS. **2-4** and the example in FIG. **5**.

[0079] In the example illustrated in FIG. **5**, the second sun gear **151** is rotationally connectable to the first ring gear **144** via the first clutch **155**. The second planet carrier **152** is rotationally connected to the stationary member **159**. The second ring gear **154** is rotationally connected to the first planet carrier **142**. Since, as described above in relation to the description of FIG. **2**, the first planet carrier **142** is rotationally connected to the output shaft **190**, the second ring gear **154** is also rotationally connected to the output shaft **190**.

[0080] The transmission arrangement **420** in the example depicted in FIG. 5 is configured to assume three gear states, i.e. three different speed ratios, as well as to assume a crawler gear. A first gear state is assumed by positioning the first clutch **155** in neutral position, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the second gear wheel **132**, and positioning the third clutch **145** to rotationally connect the first ring gear **144** to the stationary member **149b**. Hereby, the first ring gear **144** is stationary and the first sun gear **141** is driven, whereby a first speed reduction is obtained between the input shaft and the output shaft.

[0081] A second gear state is assumed by positioning the first clutch **155** in neutral position, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the stationary member **149a**, and positioning the third clutch **145** to rotationally connect the first ring gear **144** to the second gear wheel **132**. Hereby, the first sun gear **141** is stationary and the first ring gear **144** is driven, whereby a second speed reduction is obtained between the input shaft and the output shaft. The second speed reduction is lower/smaller compared to the first speed reduction.

[0082] A third gear state is assumed by positioning the first clutch **155** in neutral position, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the second gear wheel **132**, and positioning the third clutch **145** to rotationally connect the first ring gear **144** to the second gear wheel **132**. Hereby, a direct gear is obtained where the second gear wheel **132**, the first ring gear **144**, the first planet carrier **142**, and the output shaft **190** all rotate in the same direction.

[0083] The crawler gear is assumed by positioning the first clutch **155** to rotationally connect the second sun gear **151** to the first ring gear **144**, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the second gear wheel **132**, and positioning the third clutch **145** to assume the neutral position. Hereby, a third speed reduction is obtained between the input shaft and the output shaft in which the first ring gear **144** and the first planet carrier **142** rotates in opposite directions. The third speed reduction is higher/larger than the first speed reduction. In other words, the output shaft rotates at a lower rotational speed relative to the input shaft for the third speed reduction compared to the relative rotation speed of the input and output shafts for the first speed reduction.

[0084] In order to describe the transmission arrangement **520** according to another example, reference is made to FIG. 6. The difference between the examples depicted in FIGS. 2-5 and the example depicted in FIG. 6 is the crawler unit and how it is connected to the first planetary gear set **140** and the stationary member. The following will mainly describe the differences between the examples in FIGS. 2-5 and the example in FIG. 6.

[0085] In the example illustrated in FIG. 6, the second sun gear **151** is rotationally connected to the first ring gear **144**. The second planet carrier **152** is rotationally connectable to the stationary member **159** via the first clutch **155** of the crawler unit **150**. The second ring gear **154** is rotationally connected to the first planet carrier **142**. Since, as described above in relation to the description of FIG. 2, the first planet carrier **142** is rotationally connected to the output shaft **190**, the second ring gear **154** is also rotationally connected to the output shaft **190**.

[0086] The transmission arrangement **520** in the example depicted in FIG. 6 is configured to assume three gear states, i.e. three different speed ratios, as well as to assume a crawler gear. A first gear state is assumed by positioning the first clutch **155** in neutral position, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the second gear wheel **132**, and positioning the third clutch **145** to rotationally connect the first ring gear **144** to the stationary member **149b**. Hereby, the first ring gear **144** is stationary and the first sun gear **141** is driven, whereby a first speed reduction is obtained between the input shaft and the output shaft.

[0087] A second gear state is assumed by positioning the first clutch **155** in neutral position, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the stationary member **149a**, and positioning the third clutch **145** to rotationally connect the first ring gear **144** to the second gear wheel **132**. Hereby, the first sun gear **141** is stationary and the first ring gear **144** is driven, whereby a second speed reduction is obtained between the input shaft and the output shaft.

The second speed reduction is lower/smaller compared to the first speed reduction.

[0088] A third gear state is assumed by positioning the first clutch **155** in neutral position, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the second gear wheel **132**, and positioning the third clutch **145** to rotationally connect the first ring gear **144** to the second gear wheel **132**. Hereby, a direct gear is obtained where the second gear wheel **132**, the first ring gear **144**, the first planet carrier **142**, and the output shaft **190** all rotate in the same direction.

[0089] The crawler gear is assumed by positioning the first clutch **155** to rotationally connect the second planet carrier **152** to the stationary member **159**, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the second gear wheel **132**, and positioning the third clutch **145** to assume the neutral position. Hereby, a third speed reduction is obtained between the input shaft and the output shaft in which the first ring gear **144** and the first planet carrier **142** rotates in opposite directions. The third speed reduction is higher/larger than the first speed reduction. In other words, the output shaft rotates at a lower rotational speed relative to the input shaft for the third speed reduction compared to the relative rotation speed of the input and output shafts for the first speed reduction.

[0090] In order to describe the transmission arrangement **620** according to another example, reference is made to FIG. 7. The difference between the examples depicted in FIGS. 2-6 and the example depicted in FIG. 7 is the crawler unit and how it is connected to the first planetary gear set **140** and the stationary member. The following will mainly describe the differences between the examples in FIGS. 2-6 and the example in FIG. 7.

[0091] In the example illustrated in FIG. 7, the second sun gear **151** is rotationally connected to the first ring gear **144**. The second planet carrier **152** is rotationally connected to the stationary member **159**. The second ring gear **154** is rotationally connectable to the first planet carrier **142** via the first clutch **155** of the crawler unit **150**. Since, as described above in relation to the description of FIG. 2, the first planet carrier **142** is rotationally connected to the output shaft **190**, the second ring gear **154** is also rotationally connectable to the output shaft **190** via the first clutch **155**.

[0092] The transmission arrangement **620** in the example depicted in FIG. 7 is configured to assume three gear states, i.e. three different speed ratios, as well as to assume a crawler gear. A first gear state is assumed by positioning the first clutch **155** in neutral position, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the second gear wheel **132**, and positioning the third clutch **145** to rotationally connect the first ring gear **144** to the stationary member **149b**. Hereby, the first ring gear **144** is stationary and the first sun gear **141** is driven, whereby a first speed reduction is obtained between the input shaft and the output shaft.

[0093] A second gear state is assumed by positioning the first clutch **155** in neutral position, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the stationary member **149a**, and positioning the third clutch **145** to rotationally connect the first ring gear **144** to the second gear wheel **132**. Hereby, the first sun gear **141** is stationary and the first ring gear **144** is driven, whereby a second speed reduction is obtained between the input shaft and the output shaft. The second speed reduction is lower/smaller compared to the first speed reduction.

[0094] A third gear state is assumed by positioning the first clutch **155** in neutral position, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the second gear wheel **132**, and positioning the third clutch **145** to rotationally connect the first ring gear **144** to the second gear wheel **132**. Hereby, a direct gear is obtained where the second gear wheel **132**, the first ring gear **144**, the first planet carrier **142**, and the output shaft **190** all rotate in the same direction.

[0095] The crawler gear is assumed by positioning the first clutch **155** to rotationally connect the second ring gear **154** to the first planet carrier **142**, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the second gear wheel **132**, and positioning the third clutch **145** to assume the neutral position. Hereby, a third speed reduction is obtained between the input shaft and the output shaft in which the first ring gear **144** and the first planet carrier **142** rotates in opposite directions. The third speed reduction is higher/larger than the first speed reduction. In other words,

the output shaft rotates at a lower rotational speed relative to the input shaft for the third speed reduction compared to the relative rotation speed of the input and output shafts for the first speed reduction.

[0096] In order to describe the transmission arrangement **720** according to another example, reference is made to FIG. **8**. Contrary to the examples described in relation to FIGS. **2-7**, the crawler unit comprises a crawler gear stage **760** instead of the above second planetary gear stage **160**. The crawler gear stage **760** comprises a set of crawler gear wheels **751**, **753a**, **753b** which are drivingly connectable between the first planet carrier **142** and the first ring gear **144** via the first clutch **155** of the crawler unit **150**. In particular, the crawler unit **150** comprises a first crawler gear wheel **751** rotationally connectable to the first planet carrier **142** via the first clutch **155** of the crawler unit **150**, a second crawler gear wheel **753a** arranged in meshing engagement with the first crawler gear wheel **751**. The crawler unit **150** further comprises a third crawler gear wheel **753b** rotationally connected to the second crawler gear wheel **753a** via a crawler countershaft **752**. The third crawler gear wheel **753b** is in turn in meshing engagement with the first ring gear **144** of the first planetary gear set **140**. As an alternative, the crawler unit **150** may comprise a plurality of parallel crawler countershafts to drivingly connect the first crawler gear wheel **751** to the first ring gear **144**. Also, the first clutch **155** may be arranged at a different position compared to the illustration in FIG. **8**, such as between the second **753a** and third **753b** crawler gear wheels.

[0097] The transmission arrangement **720** in the example depicted in FIG. **8** is configured to assume three gear states, i.e. three different speed ratios, as well as to assume a crawler gear. A first gear state is assumed by positioning the first clutch **155** in neutral position, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the second gear wheel **132**, and positioning the third clutch **145** to rotationally connect the first ring gear **144** to the stationary member **149b**. Hereby, the first ring gear **144** is stationary and the first sun gear **141** is driven, whereby a first speed reduction is obtained between the input shaft and the output shaft.

[0098] A second gear state is assumed by positioning the first clutch **155** in neutral position, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the stationary member **149a**, and positioning the third clutch **145** to rotationally connect the first ring gear **144** to the second gear wheel **132**. Hereby, the first sun gear **141** is stationary and the first ring gear **144** is driven, whereby a second speed reduction is obtained between the input shaft and the output shaft. The second speed reduction is lower/smaller compared to the first speed reduction.

[0099] A third gear state is assumed by positioning the first clutch **155** in neutral position, positioning the second clutch **146** to rotationally connect the first sun gear **141** to the second gear wheel **132**, and positioning the third clutch **145** to rotationally connect the first ring gear **144** to the second gear wheel **132**. Hereby, a direct gear is obtained where the second gear wheel **132**, the first ring gear **144**, the first planet carrier **142**, and the output shaft **190** all rotate in the same direction.

[0100] The crawler gear is assumed by positioning the first clutch **155** to rotationally connect the first crawler gear wheel **751** to the first planet carrier **142**. Since the first planet carrier **142** is rotationally connected to the output shaft **190**, the first crawler gear wheel **751** is thus also rotationally connected to the output shaft **190**. The second clutch **146** is positioned to rotationally connect the first sun gear **141** to the second gear wheel **132**, and positioning the third clutch **145** to assume the neutral position. Hereby, a third speed reduction is obtained between the input shaft and the output shaft in which the first ring gear **144** and the first planet carrier **142** rotates in opposite directions. The third speed reduction is higher/larger than the first speed reduction. In other words, the output shaft rotates at a lower rotational speed relative to the input shaft for the third speed reduction compared to the relative rotation speed of the input and output shafts for the first speed reduction.

[0101] Reference is finally made to FIG. **9** which is a schematic illustration of an exemplary powertrain comprising a transmission arrangement. In FIG. **9**, the powertrain **901** comprises the transmission arrangement **120** described above in relation to FIG. **2**. It should however be readily

understood that each of the exemplified transmission arrangements described in relation to FIGS. 3-8 are equally implementable for the powertrain 901.

[0102] The powertrain 901 comprises the electric traction motor 110 drivingly connected to the input shaft 115. In addition, the powertrain 901 comprises a final drive 904, such as e.g., a bevel gear, drivingly connected to the output shaft 190. The final drive 904 is drivingly connected to a differential 902 which in turn is connected to the wheels 906 of the vehicle. It should however be readily understood that the output shaft 190 may equally as well be directly connected to the differential 902 without the use of a final drive 904.

#### EXAMPLE LIST

[0103] Example 1: A transmission arrangement for a vehicle, the transmission arrangement comprising an input shaft drivingly connectable to an electric traction motor, and an output shaft drivingly connectable to a pair of wheels of the vehicle, a first gear stage comprising a first gear wheel and a second gear wheel drivingly connected to each other, the first gear wheel being rotationally connected to the input shaft, a first planetary gear set comprising a first sun gear, a first ring gear and a first planet carrier carrying a first set of planet gears, the first set of planet gears being in meshing engagement with the first ring gear and the first sun gear, wherein the first sun gear and the first ring gear are rotationally connectable to the second gear wheel of the first gear stage, and wherein the first planet carrier is rotationally connected to the output shaft, and a crawler unit comprising a plurality of gear members, the crawler unit being drivingly connectable between the first planetary gear set and the output shaft by a first clutch, wherein the first clutch is configured to rotationally connect one of the plurality of gear members of the crawler unit to one of the first ring gear, the first planet carrier or a stationary member of the transmission arrangement, to cause the first ring gear to rotate in an opposite direction compared to a rotational direction of the first planet carrier.

[0104] Example 2. The transmission arrangement of example 1, wherein the first gear stage is a reduction gear stage in which, during operation of the transmission arrangement, the first gear wheel rotates at a higher rotational speed compared to a rotational speed of the second gear wheel.

[0105] Example 3. The transmission arrangement of any one of examples 1 or 2, wherein the first sun gear of the first planetary gear set is rotationally connectable to the second gear wheel of the first gear stage by a second clutch of the transmission arrangement.

[0106] Example 4. The transmission arrangement of any one of the preceding examples, wherein the first ring gear of the first planetary gear set is rotationally connectable to the second gear wheel of the first gear stage by a third clutch of the transmission arrangement.

[0107] Example 5. The transmission arrangement of example 4, wherein the first ring gear of first planetary gear set is rotationally connectable to the stationary member via the third clutch.

[0108] Example 6. The transmission arrangement of any one of the preceding examples, wherein the crawler unit comprises a second planetary gear set, the plurality of gear members of the crawler unit comprising a second sun gear, a second ring gear and a second planet carrier carrying a second set of planet gears, the second set of planet gears being in meshing engagement with the second ring gear and the second sun gear.

[0109] Example 7. The transmission arrangement of example 6, wherein the second sun gear is rotationally connected to the first planet carrier.

[0110] Example 8. The transmission arrangement of example 7, wherein the second ring gear is rotationally connectable to the first ring gear via the first clutch of the crawler unit.

[0111] Example 9. The transmission arrangement of any one of examples 7 or 8, wherein the second planet carrier is rotationally connected to the stationary member of the transmission arrangement.

[0112] Example 10. The transmission arrangement of example 7, wherein the second ring gear is rotationally connected to the first ring gear.

[0113] Example 11. The transmission arrangement of examples 7 or 10, wherein the second planet

carrier is rotationally connectable to the stationary member via the first clutch of the crawler unit.

[0114] Example 12. The transmission arrangement of example 6, wherein the second ring gear is rotationally connected to the first ring gear.

[0115] Example 13. The transmission arrangement of examples 6 or 12, wherein the second planet carrier is rotationally connected to the stationary member.

[0116] Example 14. The transmission arrangement of any one of example 6 or 12-13, wherein the second sun gear is rotationally connectable to the first planet carrier via the first clutch of the crawler unit.

[0117] Example 15. The transmission arrangement of example 6, wherein the second ring gear is rotationally connected to the first planet carrier.

[0118] Example 16. The transmission arrangement of examples 6 or 15, wherein the second planet carrier is rotationally connected to the stationary member.

[0119] Example 17. The transmission arrangement of any one of example 6 or 15-16, wherein the second sun gear is rotationally connectable to the first ring gear via the first clutch of the crawler unit.

[0120] Example 18. The transmission arrangement of example 6, wherein the second sun gear is rotationally connected to the first ring gear.

[0121] Example 19. The transmission arrangement of examples 6 or 18, wherein the second ring gear is rotationally connected to the first planet carrier.

[0122] Example 20. The transmission arrangement of any one of examples 6 or 18-19, wherein the second planet carrier is rotationally connectable to the stationary member via the first clutch of the crawler unit.

[0123] Example 21. The transmission arrangement of example 6, wherein the second sun gear is rotationally connected to the first ring gear.

[0124] Example 22. The transmission arrangement of examples 6 or 21, wherein the second planet carrier is rotationally connected to the stationary member.

[0125] Example 23. The transmission arrangement of example 6 or 21-22, wherein the second ring gear is rotationally connectable to the first planet carrier via the first clutch of the crawler unit.

[0126] Example 24. The transmission arrangement of any one of examples 1-5, wherein the crawler unit comprises a crawler gear stage, the crawler gear stage comprising a set of crawler gear wheels drivingly connectable between the first planet carrier and the first ring gear via the first clutch of the crawler unit.

[0127] Example 25. A powertrain for an electrically propelled vehicle, the powertrain comprising: an electric traction motor, and a transmission arrangement according to any one of the preceding examples, wherein the input shaft of the transmission arrangement is drivingly connected to the electric traction motor.

[0128] Example 26. A vehicle comprising the transmission arrangement of any one of examples 1-24, or the powertrain according to example 25.

[0129] The terminology used herein is for the purpose of describing particular aspects only and is not intended to be limiting of the disclosure. As used herein, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items. It will be further understood that the terms “comprises,” “comprising,” “includes,” and/or “including” when used herein specify the presence of stated features, integers, actions, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, actions, steps, operations, elements, components, and/or groups thereof.

[0130] It will be understood that, although the terms first, second, etc., may be used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. For example, a first element could be termed a

second element, and, similarly, a second element could be termed a first element without departing from the scope of the present disclosure.

[0131] Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this disclosure belongs. It will be further understood that terms used herein should be interpreted as having a meaning consistent with their meaning in the context of this specification and the relevant art and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

[0132] It is to be understood that the present disclosure is not limited to the aspects described above and illustrated in the drawings; rather, the skilled person will recognize that many changes and modifications may be made within the scope of the present disclosure and appended claims. In the drawings and specification, there have been disclosed aspects for purposes of illustration only and not for purposes of limitation, the scope of the disclosure being set forth in the following claims.

## Claims

1. A transmission arrangement for a vehicle, the transmission arrangement comprising: an input shaft drivingly connectable to an electric traction motor, and an output shaft drivingly connectable to a pair of wheels of the vehicle, a first gear stage comprising a first gear wheel and a second gear wheel drivingly connected to each other, the first gear wheel being rotationally connected to the input shaft, a first planetary gear set comprising a first sun gear, a first ring gear and a first planet carrier carrying a first set of planet gears, the first set of planet gears being in meshing engagement with the first ring gear and the first sun gear, wherein the first sun gear and the first ring gear are rotationally connectable to the second gear wheel of the first gear stage, and wherein the first planet carrier is rotationally connected to the output shaft, and a crawler unit comprising a plurality of gear members, the crawler unit being drivingly connectable between the first planetary gear set and the output shaft by a first clutch, wherein the first clutch is configured to rotationally connect one of the plurality of gear members of the crawler unit to one of the first ring gear, the first planet carrier or a stationary member of the transmission arrangement, to cause the first ring gear to rotate in an opposite direction compared to a rotational direction of the first planet carrier.
2. The transmission arrangement of claim 1, wherein the first gear stage is a reduction gear stage in which, during operation of the transmission arrangement, the first gear wheel rotates at a higher rotational speed compared to a rotational speed of the second gear wheel.
3. The transmission arrangement of claim 1, wherein the first sun gear of the first planetary gear set is rotationally connectable to the second gear wheel of the first gear stage by a second clutch of the transmission arrangement.
4. The transmission arrangement of claim 1, wherein the first ring gear of the first planetary gear set is rotationally connectable to the second gear wheel of the first gear stage by a third clutch of the transmission arrangement.
5. The transmission arrangement of claim 4, wherein the first ring gear of first planetary gear set is rotationally connectable to the stationary member via the third clutch.
6. The transmission arrangement of claim 1, wherein the crawler unit comprises a second planetary gear set, the plurality of gear members of the crawler unit comprising a second sun gear, a second ring gear and a second planet carrier carrying a second set of planet gears, the second set of planet gears being in meshing engagement with the second ring gear and the second sun gear.
7. The transmission arrangement of claim 6, wherein the second sun gear is rotationally connected to the first planet carrier.
8. The transmission arrangement of claim 7, wherein the second ring gear is rotationally connectable to the first ring gear via the first clutch of the crawler unit.
9. The transmission arrangement of claim 7, wherein the second planet carrier is rotationally

connected to the stationary member of the transmission arrangement.

**10.** The transmission arrangement of claim 7, wherein the second ring gear is rotationally connected to the first ring gear.

**11.** The transmission arrangement of claim 7, wherein the second planet carrier is rotationally connectable to the stationary member via the first clutch of the crawler unit.

**12.** The transmission arrangement of claim 6, wherein the second ring gear is rotationally connected to the first ring gear.

**13.** The transmission arrangement of claim 6, wherein the second planet carrier is rotationally connected to the stationary member.

**14.** The transmission arrangement of claim 6, wherein the second sun gear is rotationally connectable to the first planet carrier via the first clutch of the crawler unit.

**15.** The transmission arrangement of claim 6, wherein the second ring gear is rotationally connected to the first planet carrier.

**16.** The transmission arrangement of claim 6, wherein the second planet carrier is rotationally connected to the stationary member.

**17.** The transmission arrangement of claim 6, wherein the second sun gear is rotationally connectable to the first ring gear via the first clutch of the crawler unit.

**18.** The transmission arrangement of claim 1, wherein the crawler unit comprises a crawler gear stage, the crawler gear stage comprising a set of crawler gear wheels drivingly connectable between the first planet carrier and the first ring gear via the first clutch of the crawler unit.

**19.** A powertrain for an electrically propelled vehicle, the powertrain comprising: an electric traction motor, and a transmission arrangement according to claim 1, wherein the input shaft of the transmission arrangement is drivingly connected to the electric traction motor.

**20.** A vehicle comprising the transmission arrangement of the powertrain according to claim 19.

---