

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12389211
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Hundert; Harel et al.

Communication resource management

Abstract

A UE includes: at least one transceiver; a memory; one or more sensors configured to provide one or more sensor indications; and at least one processor. The sensor(s) includes at least one of: one or more first sensors configured to sense one or more environmental conditions; or one or more second sensors configured to sense one or more UE conditions. The processor(s) is configured to control operation, for communication with an entity external to the UE, of at least one of the processor(s) or the transceiver(s) based on the sensor indication(s) provided by the sensor(s) to affect at least one of: a communication directionality of the UE; or a transmit power of the transceiver(s); or a transmit frequency of the transceiver(s); or a processing effort of the processor(s) for processing communication signals.

Inventors:	Hundert; Harel (Rosh Ha-Ayin, IL), Baruch; Doron (Hod Hasharon, IL)
Applicant:	QUALCOMM Incorporated (San Diego, CA)
Family ID:	1000008750555
Assignee:	QUALCOMM Incorporated (San Diego, CA)
Appl. No.:	17/908120
Filed (or PCT Filed):	April 17, 2021
PCT No.:	PCT/US2021/027849
PCT Pub. No.:	WO2021/221935
PCT Pub. Date:	November 04, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230101555 A1	Mar. 30, 2023

Foreign Application Priority Data

IL 274235 Apr. 26, 2020

Publication Classification

Int. Cl.: H04W4/40 (20180101); H04B7/06 (20060101); H04W4/38 (20180101); H04W24/02 (20090101)

U.S. Cl.:

CPC H04W4/38 (20180201); H04B7/0617 (20130101); H04W4/40 (20180201); H04W24/02 (20130101);

Field of Classification Search

CPC: H04W (4/38); H04W (4/30)

USPC: 455/414.1

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2016/0242229	12/2015	Balachandran	N/A	H04W 72/20
2017/0123428	12/2016	Levinson et al.	N/A	N/A
2018/0139593	12/2017	Chun	N/A	H04W 4/46
2018/0322784	12/2017	Schild	N/A	N/A
2019/0245592	12/2018	Chae	N/A	H04B 7/0413

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103339796	12/2012	CN	N/A
103906129	12/2013	CN	N/A
105409298	12/2015	CN	N/A
110875765	12/2019	CN	N/A
2008049873	12/2007	JP	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion—PCT/US2021/027849—ISA/EPO—Jul. 5, 2021.
cited by applicant

Primary Examiner: Ghulamali; Qutbuddin

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is the National Stage of International Application No. PCT/US2021/027849, filed Apr. 17, 2021, entitled “COMMUNICATION RESOURCE MANAGEMENT,” which claims the benefit of Israel Patent Application No. 274235, filed Apr. 26, 2020, entitled “COMMUNICATION RESOURCE MANAGEMENT,” both of which are assigned to the assignee hereof, and the entire contents of which are hereby incorporated herein by reference for all purposes.

BACKGROUND

(2) The connected-vehicle radio-frequency environment is a spectrum-limited, bandwidth-limited resource. For example, the available spectrum may be about 20 MHz at just under 6 GHz. This spectrum may be increasingly used as more radio-frequency-based connected-vehicle (e.g., vehicle to everything (V2X)) message exchanges occur. V2X may utilize several wireless technologies such as cellular, dedicated short range communications (DSRC), and other vehicular communication systems to exchange information between vehicles and other entities, to include roadside units (RSUs) and edge servers. Applications running on mobile devices are increasingly dependent on high-data rate services. For example, users may be able to view media data such as television and movies, as well as participate in video conference calls and networked based gaming. Often, mobile users may be concentrated in an area such as in a public transportation carrier (e.g., bus, train), or in an area of traffic congestion. Requests for high-data rate services from multiple mobile devices in a congested area can place large demands on a cellular network. The increased data demands may cause a degradation in the user experience in high-data rate application due to latency issues, reduced resolution video, and failed connections.

SUMMARY

(3) An example user equipment (UE) includes: at least one transceiver configured to send and receive wireless signals, the at least one transceiver comprising one or more antennas; a memory; one or more sensors configured to provide one or more sensor indications, the one or more sensors comprising at least one of: one or more first sensors configured to sense one or more environmental conditions; or one or more second sensors configured to sense one or more UE conditions; and at least one processor communicatively coupled to the at least one transceiver, the memory, and the one or more sensors and configured to control operation, for communication with an entity external to the UE, of at least one of the at least one processor or the at least one transceiver based on the one or more sensor indications provided by the one or more sensors to affect at least one of: a communication directionality of the UE; or a transmit power of the at least one transceiver; or a transmit frequency of the at least one transceiver; or a processing effort of the at least one processor for processing communication signals.

(4) Another example UE includes: sensing means for obtaining one or more sensor indications by sensing at least one of: one or more environmental conditions; or one or more UE conditions; and communication means for affecting communication between the UE and an external entity based on the one or more sensor indications by affecting at least one of: a communication directionality of the UE; or a transmit power of the UE; or a transmit frequency of the UE; or a processing effort of the UE for processing communication signals.

(5) An example method of managing communication resources of a UE includes: obtaining one or more sensor indications by sensing, at the UE, at least one of: one or more environmental conditions; or one or more UE conditions; and affecting communication between the UE and an external entity, disposed externally to the UE, based on the one or more sensor indications by affecting at least one of: a communication directionality of the UE; or a transmit power of the UE; or a transmit frequency of the UE; or a processing effort of the UE for processing communication signals.

(6) A non-transitory, processor-readable storage medium includes processor-readable instructions

configured to cause one or more processors of a UE to: obtain one or more sensor indications of at least one of: one or more environmental conditions; or one or more UE conditions; and affect communication between the UE and an external entity, disposed externally to the UE, based on the one or more sensor indications by affecting at least one of: a communication directionality of the UE; or a transmit power of the UE; or a transmit frequency of the UE; or a processing effort of the UE for processing communication signals.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic diagram of a connected-vehicle communication system.
- (2) FIG. 2 is a block diagram of components of an example of a user equipment shown in FIG. 1.
- (3) FIG. 3 is a block diagram of components of an example transmission/reception point shown in FIG. 1.
- (4) FIG. 4 is a block diagram of components of an example of a server shown in FIG. 1.
- (5) FIG. 5 is a block diagram of components of an example user equipment.
- (6) FIG. 6 is a top view of an example environment with multiple UEs.
- (7) FIG. 7 is an example table of sensor information.
- (8) FIG. 8 is a block flow diagram of a method for managing communication resources.

DETAILED DESCRIPTION

(9) Techniques are discussed herein for managing communication resources. For example, a UE (user equipment), such as a vehicle, may use information sensed by one or more sensors to control one or more resources for use in communication, e.g., vehicle-to-everything (V2X) communication. For example, the UE may use information from one sensor, a combination of information from multiple sensors, and/or a change in sensed information from one or more sensors over time to determine how to allocate communication resources. The allocation of resources may be done for any of a variety of reasons or combinations of reasons, e.g., to reduce wasted effort, increase likelihood of successful communication, and/or reduce redundancy. For example, the UE may allocate more resources to communication in a direction of travel, fewer resources to communication in a direction away from a direction of travel, and/or fewer resources in a direction obstructed by an obstacle. As another example, the UE may allocate fewer resources for communication if the UE is part of a group of UEs and the information to be provided by the UE would be redundant with information provided by another of the UEs in the group. These are examples, and other examples may be implemented. For example, one or more decisions regarding resource allocation may be made outside of a UE and conveyed to the UE for implementation. Still other examples may be implemented.

(10) Items and/or techniques described herein may provide one or more of the following capabilities, as well as other capabilities not mentioned. Processing efficiency may be improved or maintained, e.g., by avoiding redundant processing, processing transmit signals that are likely to reach a desired destination, preventing processing of transmit signals with significant impediments to reaching a desired destination successfully, and/or processing received signals that are more significant than other received signals. Processing power may be conserved or improved, e.g., by limiting unnecessary and/or unproductive processing and thus reducing heat production by a processor. Safety may be improved, e.g., by reducing interference with communications to and/or from an emergency vehicle. One or more UE resources may be better utilized, e.g., optimized, based on one or more sensor measurements indicative of an environment of the UE and/or a situation of the UE. Other capabilities may be provided and not every implementation according to the disclosure must provide any, let alone all, of the capabilities discussed. It may be possible for an effect noted above to be achieved by means other than that noted, and a noted item/technique may

not necessarily yield the noted effect.

(11) Referring to FIG. 1, an example wireless communications system **110** includes a user equipment (UE) **112**, a UE **113**, a UE **114**, base transceiver stations (BTSs) **120**, **121**, **122**, **123**, a network **130**, a core network **140**, an external client **150**, and a roadside unit (RSU) **160**. The core network **140** (e.g., a 5G core network (5GC)) may include back-end devices including, among other things, an Access and Mobility Management Function (AMF) **141**, a Session Management Function (SMF) **142**, a server **143**, and a Gateway Mobile Location Center (GMLC) **144**. The AMF **141**, the SMF **142**, the server **143**, and the GMLC **144** are communicatively coupled to each other. The server **143** may be, for example, a Location Management Function (LMF) that supports positioning of the UEs **112-114** (e.g., using techniques such as Assisted Global Navigation Satellite System (A-GNSS), OTDOA (Observed Time Difference of Arrival, e.g., Downlink (DL) OTDOA and/or Uplink (UL) OTDOA), Round Trip Time (RTT), Multi-Cell RTT, RTK (Real Time Kinematic), PPP (Precise Point Positioning), DGNSS (Differential GNSS), E-CID (Enhanced Cell ID), AoA (Angle of Arrival), AoD (Angle of Departure), etc.). The RSU **160** may be configured for communication (e.g., bi-directional or uni-directional communication) with the UEs **112-114**. For example, the RSU **160** may be configured with similar communication capabilities to any of the BTSs **120-123**, but perhaps with different functionality(ies) (e.g., different programming). Also, while one RSU **160** is shown in FIG. 1, the system **100** may include more than one RSU, or may not include any RSUs. The communication system **110** may include additional or alternative components.

(12) The communication system **110** may utilize information from a constellation **180** of satellite vehicles (SVs) **181**, **182**, **183**. The constellation **180** may correspond to a respective Global Navigation Satellite System (GNSS) (i.e., Satellite Positioning System (SPS)) such as the Global Positioning System (GPS), the GLObal NAVigation Satellite System (GLONASS), Galileo, Beidou, or some other local or regional SPS such as the Indian Regional Navigational Satellite System (IRNSS), the European Geostationary Navigation Overlay Service (EGNOS), or the Wide Area Augmentation System (WAAS). Only three SVs are shown for the constellation **180**, but constellations of GNSS SVs will include more than three SVs.

(13) An LMF may also be referred to as a Location Manager (LM), a Location Function (LF), a commercial LMF (CLMF), or a value-added LMF (VLMF). The server **143** (e.g., an LMF) and/or one or more other devices of the system **110** (e.g., one or more of the UEs **112-114**) may be configured to determine locations of the UEs **112-114**. The server **143** may communicate directly with the BTS **121** (e.g., a gNB) and/or one or more other BTSs, and may be integrated with the BTS **121** and/or one or more other BTSs. The SMF **142** may serve as an initial contact point of a Service Control Function (SCF) (not shown) to create, control, and delete media sessions. The server **143** (e.g., an LMF) may be co-located or integrated with a gNB or a TRP (Transmission/Reception Point), or may be disposed remote from the gNB and/or TRP and configured to communicate directly or indirectly with the gNB and/or the TRP.

(14) The AMF **141** may serve as a control node that processes signaling between the UEs **112-114** and the core network **140**, and provides QoS (Quality of Service) flow and session management. The AMF **141** may support mobility of the UEs **112-114** including cell change and handover and may participate in supporting signaling connection to the UEs **112-114**.

(15) The system **110** is capable of wireless communication in that components of the system **110** can communicate with one another (at least some times using wireless connections) directly or indirectly, e.g., via the BTSs **120-123** and/or the network **130** (and/or one or more other devices not shown, such as one or more other base transceiver stations). While the BTSs **120-123** are shown separately from the network **130**, the network **130** may include one or more of the BTSs **120-123** and may constitute a Radio Access Network (RAN), e.g., a New Radio (NR) RAN which may also be called a Fifth Generation (5G) Next Generation (NG) RAN (NG-RAN). For indirect communications, the communications may be altered during transmission from one entity to

another, e.g., to alter header information of data packets, to change format, etc. The UEs **112-114** may communicate with the BTSs **120-123** via Uu interfaces, e.g., in RRC-encapsulated LPP messages (Radio Resource Control encapsulated LTE Positioning Protocol messages) over Uu interfaces. The UEs **112-114** shown are a smartphone, a tablet computer, and a vehicle-based device, but these are examples only as the UEs **112-114** are not required to be any of these configurations, and other configurations of UEs may be used. The UEs **112, 113** shown are mobile wireless communication devices (although they may communicate wirelessly and via wired connections) including mobile phones (including smartphones) and a tablet computer. The UE **114** shown is a vehicle-based mobile wireless communication device (although the UE **114** may communicate wirelessly and via wired connections). Other UEs may include wearable devices (e.g., smart watches, smart jewelry, smart glasses or headsets, etc.). Still other UEs may be used, whether currently existing or developed in the future. Further, other wireless devices (whether mobile or not) may be implemented within the system **110** and may communicate with each other and/or with the UEs **112-114**, the BTSs **120-123**, the network **130**, the core network **140**, and/or the external client **150**. For example, such other devices may include internet of thing (IoT) devices, medical devices, home entertainment and/or automation devices, etc. The core network **140** may communicate with the external client **150** (e.g., a computer system), e.g., to allow the external client **150** to request and/or receive location information regarding the UEs **112-114** (e.g., via the GMLC **144**).

(16) The UEs **112-114** or other devices may be configured to communicate in various networks and/or for various purposes and/or using various technologies (e.g., 5G, Wi-Fi communication, multiple frequencies of Wi-Fi communication, satellite positioning, one or more types of communications (e.g., GSM (Global System for Mobiles), CDMA (Code Division Multiple Access), LTE (Long-Term Evolution), V2X (e.g., V2P (Vehicle-to-Pedestrian), V2I (Vehicle-to-Infrastructure), V2V (Vehicle-to-Vehicle), etc.), IEEE 802.11p, etc.). V2X communications may be cellular (Cellular-V2X (C-V2X)) and/or WiFi (e.g., DSRC (Dedicated Short-Range Connection)). The system **110** may support operation on multiple carriers (waveform signals of different frequencies). Multi-carrier transmitters can transmit modulated signals simultaneously on the multiple carriers. Each modulated signal may be a Code Division Multiple Access (CDMA) signal, a Time Division Multiple Access (TDMA) signal, an Orthogonal Frequency Division Multiple Access (OFDMA) signal, a Single-Carrier Frequency Division Multiple Access (SC-FDMA) signal, etc. Each modulated signal may be sent on a different carrier and may carry pilot, overhead information, data, etc.

(17) The BTSs **120-123** may wirelessly communicate with the UEs **112-114** in the system **110** via one or more antennas. A BTS may also be referred to as a base station, an access point, a gNode B (gNB), an access node (AN), a Node B, an evolved Node B (eNB), etc. For example, each of the BTSs **120, 121** may be a gNB or a transmission point gNB, the BTS **122** may be a macro cell (e.g., a high-power cellular base station) and/or a small cell (e.g., a low-power cellular base station), and the BTS **123** may be an access point (e.g., a short-range base station configured to communicate with short-range technology such as WiFi, WiFi-Direct (WiFi-D), Bluetooth®, Bluetooth®-low energy (BLE), Zigbee, etc. One or more of the BTSs **120-123** may be configured to communicate with the UEs **112-114** via multiple carriers. Each of the BTSs **120, 121** may provide communication coverage for a respective geographic region, e.g. a cell. Each cell may be partitioned into multiple sectors as a function of the base station antennas.

(18) The BTSs **120-123** each comprise one or more Transmission/Reception Points (TRPs). For example, each sector within a cell of a BTS may comprise a TRP, although multiple TRPs may share one or more components (e.g., share a processor but have separate antennas). The system **110** may include only macro TRPs or the system **110** may have TRPs of different types, e.g., macro, pico, and/or femto TRPs, etc. A macro TRP may cover a relatively large geographic area (e.g., several kilometers in radius) and may allow unrestricted access by terminals with service

subscription. A pico TRP may cover a relatively small geographic area (e.g., a pico cell) and may allow unrestricted access by terminals with service subscription. A femto or home TRP may cover a relatively small geographic area (e.g., a femto cell) and may allow restricted access by terminals having association with the femto cell (e.g., terminals for users in a home).

(19) The UEs **112-114** may be referred to as terminals, access terminals (ATs), mobile stations, mobile devices, subscriber units, etc. The UEs **112-114** may include various devices as listed above and/or other devices. The UEs **112-114** may be configured to connect indirectly to one or more communication networks via one or more device-to-device (D2D) peer-to-peer (P2P) links. The D2D P2P links may be supported with any appropriate D2D radio access technology (RAT), such as LTE Direct (LTE-D), WiFi Direct (WiFi-D), Bluetooth®, and so on. One or more of a group of the UEs **112-114** utilizing D2D communications may be within a geographic coverage area of a TRP such as one or more of the BTSs **120-123**. Other UEs in such a group may be outside such geographic coverage areas, or be otherwise unable to receive transmissions from a base station. Groups of the UEs **112-114** communicating via D2D communications may utilize a one-to-many (1:M) system in which each UE may transmit to other UEs in the group. A TRP of the BTSs **120-123** may facilitate scheduling of resources for D2D communications. In other cases, D2D communications may be carried out between UEs without the involvement of a TRP.

(20) Referring also to FIG. 2, a UE **200** is an example of any of the UEs **112, 113, 114** and comprises a computing platform including a processor **210**, memory **211** including software (SW) **212**, one or more sensors **213**, a transceiver interface **214** for a transceiver **215** (that includes a wireless transceiver **240** and a wired transceiver **250**), and a user interface **216**. The processor **210**, the memory **211**, the sensor(s) **213**, the transceiver interface **214**, and the user interface **216** may be communicatively coupled to each other by a bus **220** (which may be configured, e.g., for optical and/or electrical communication). One or more of the components shown (e.g., one or more of the sensors **213**, etc.) may be omitted from the UE **200**.

(21) The processor **210** may include one or more intelligent hardware devices, e.g., a central processing unit (CPU), a microcontroller, an application specific integrated circuit (ASIC), etc. The processor **210** may comprise multiple processors including a general-purpose/application processor **230**, a Digital Signal Processor (DSP) **231**, a modem processor **232**, a video processor **233**, and/or a sensor processor **234**. One or more of the processors **230-234** may comprise multiple devices (e.g., multiple processors). For example, the sensor processor **234** may comprise, e.g., processors for radar, ultrasound, and/or lidar, etc. The modem processor **232** may support dual SIM/dual connectivity (or even more SIMs). For example, a SIM (Subscriber Identity Module or Subscriber Identification Module) may be used by an Original Equipment Manufacturer (OEM), and another SIM may be used by an end user of the UE **200** for connectivity. The memory **211** is a non-transitory storage medium that may include random access memory (RAM), flash memory, disc memory, and/or read-only memory (ROM), etc. The memory **211** stores the software **212** which may be processor-readable, processor-executable software code containing instructions that are configured to, when executed, cause the processor **210** to perform various functions described herein. Alternatively, the software **212** may not be directly executable by the processor **210** but may be configured to cause the processor **210**, e.g., when compiled and executed, to perform the functions. The description may refer only to the processor **210** performing a function, but this includes other implementations such as where the processor **210** executes software and/or firmware. The description may refer to the processor **210** performing a function as shorthand for one or more of the processors **230-234** performing the function. The description may refer to the UE **200** performing a function as shorthand for one or more appropriate components of the UE **200** performing the function. The processor **210** may include a memory with stored instructions in addition to and/or instead of the memory **211**. Functionality of the processor **210** is discussed more fully below.

(22) The configuration of the UE **200** shown in FIG. 2 is an example and not limiting of the aspects

and features of the disclosure, including the claims, and other configurations may be used. For example, an example configuration of the UE includes one or more of the processors **230-234** of the processor **210**, the memory **211**, and the wireless transceiver **240**. Other example configurations include one or more of the processors **230-234** of the processor **210**, the memory **211**, the wireless transceiver **240**, and one or more of the sensors **213**, the user interface **216**, and/or the wired transceiver **250**.

(23) The UE **200** may comprise the modem processor **232** that may be capable of performing baseband processing of signals received and down-converted by the transceiver **215** and/or the SPS receiver **281** (discussed below). The modem processor **232** may perform baseband processing of signals to be upconverted for transmission by the transceiver **215**. Also or alternatively, baseband processing may be performed by the processor **230** and/or the DSP **231**. Other configurations, however, may be used to perform baseband processing.

(24) The UE **200** includes the sensors **213** that may include one or more of various types of sensors, for example, an environmental sensor **260**, a status sensor **270**, and a position/motion/orientation (PMO) sensor **280**. The PMO sensor **280** may include one or more sensors from which position and/or motion and/or orientation of the UE **200** may be determined. While each of the sensors **260**, **270**, **280** may be referred to in the singular, each of the sensors **260**, **270**, **280** may include more than one sensor, examples of some of which are discussed explicitly herein. The sensors **213** may generate analog and/or digital signals indications of which may be stored in the memory **211** and processed by the processor **210** (e.g., the processor **230**, the DSP **231**, the video processor **233**, and/or the sensor processor **234** as appropriate) in support of one or more applications such as, for example, applications directed to positioning, navigation, and/or resource management. The description herein may refer to the processor **210** generally as performing one or more functions that one or more of the processors **230-234** perform.

(25) The sensor(s) **213** may be used in resource management, relative location measurements, relative location determination, motion determination, etc. Information detected by the sensor(s) **213** may be used to determine how to allocate resources of the UE **200**, e.g., transmission power, processing power for transmission and/or reception of communication signals, transmission and/or reception directionality, etc. The plural term “resources” is often used throughout the discussion herein, but this term includes the singular as well, i.e., a single resource, e.g., being allocated. Also or alternatively, information detected by the sensor(s) may be used for motion detection, relative displacement, dead reckoning, sensor-based location determination, and/or sensor-assisted location determination. The sensor(s) **213** may be useful to determine whether the UE **200** is fixed (stationary) or mobile and/or whether to report certain useful information to the server **143** regarding the mobility of the UE **200**. For example, based on the information obtained/measured by the sensor(s) **213**, the UE **200** may notify/report to the server **143** that the UE **200** has detected movements or that the UE **200** has moved, and report the relative displacement/distance (e.g., via dead reckoning, or sensor-based location determination, or sensor-assisted location determination enabled by the sensor(s) **213**). In another example, for relative positioning information, the sensors/IMU can be used to determine the angle, size (e.g., width and/or height), and/or orientation of another device with respect to the UE **200**, etc. The position and/or motion of the UE **200** may be used in determining resource allocation for communication, e.g., between vehicles. The UE **200** may, for example, be disposed in or integrated with a vehicle. For example, the UE **200** may be the UE **114** that is a vehicle, in the example shown in FIG. 1, a car, although other forms of vehicles may be used, e.g., trucks, aerial UEs such as drones, etc. As such, the UE **200** may be configured for various forms of communication, e.g., V2V (vehicle-to-vehicle), V2X (vehicle-to-everything), CV2X (cellular V2X), CV2V (cellular V2V), etc.

(26) The environmental sensor **260** may include one or more sensors for measuring one or more internal and/or external environmental conditions. In this example, the environmental sensor **260** includes a camera **261**, a microphone **262**, an air-flow sensor **263**, a temperature sensor **264**, a

motion sensor **265**, and a LIDAR (Light Detection and Ranging) sensor **266**. While each of the sensors **261-266** may be referred to in the singular, each of the sensors **261-266** may include more than one sensor, examples of some of which are discussed explicitly herein. For example, the camera **261** may include at least one camera configured (e.g., designed, made, disposed, and directed) to capture images external to the UE **200** and/or may include one or more cameras configured to capture images internal to the UE **200** (e.g., in a passenger compartment of a vehicle). As other examples, the microphone **262**, the temperature sensor **264**, and/or the motion sensor **265** may include multiple microphones, multiple thermometers, and/or multiple motion detectors configured to detect sound, temperature, and/or motion (respectively) outside and/or inside of the UE **200**, e.g., a vehicle. Indeed, any of the sensors **261-265** may include multiple respective sensors outside the vehicle and/or multiple respective sensors inside the vehicle for making respective measurements at multiple locations about the vehicle and/or in different directions relative to the vehicle. While this discussion assumes the UE **200** is a vehicle, the UE **200** may be a different device (i.e., other than a vehicle). The sensors **261-265** are examples and one or more of the sensors **261-265** may be omitted from the UE **200** and/or one or more other sensors may be included in the UE **200**. For example, the environmental sensor **260** may include one or more barometric pressure sensors and/or one or more ambient light sensors and/or one or more other sensors.

(27) The camera **261** may be configured for capturing still and/or moving imagery. For example, each camera of the camera **261** may comprise, for example, one or more imaging sensors (e.g., a charge coupled device (CCD) or a CMOS imager), one or more lenses, analog-to-digital circuitry, frame buffers, etc. Additional processing, conditioning, encoding, and/or compression of signals representing captured images may be performed by the general-purpose processor **230** and/or the DSP **231**. Also or alternatively, the video processor **233** may perform conditioning, encoding, compression, and/or manipulation of signals representing captured images. The video processor **233** may decode/decompress stored image data for presentation on a display device (not shown), e.g., of the user interface **216**.

(28) The motion detector **265** is configured to detect motion. For example, the motion detector **265** may send and receive sound waves (e.g., ultrasound signals) and analyze the received signals for Doppler effects indicative of motion. Use of multiple motion detectors may help identify the relative location (e.g., direction relative to the UE **200**) of an object.

(29) The LIDAR sensor **266** is configured to determine range to an object, which may be used by the processor **210** to detect the presence of an object. Use of multiple LIDAR sensors may help identify the relative location (e.g., direction relative to the UE **200**) of an object. The LIDAR sensor **266** may be called a LADAR (laser radar) sensor, as is common when using a LIDAR sensor for detecting relatively small objects such as vehicles or other artificial (human-made) objects.

(30) The status sensor **270** is configured to provide one or more indications of one or more UE conditions of the UE **200** indicative of UE status. For example, UE conditions where the UE **200** is a vehicle (with UE conditions thus being vehicle conditions) may include a gear status of the vehicle (e.g., whether the vehicle is in park, drive, or neutral, or in which gear the vehicle is presently (e.g., reverse, first, second, third, fourth, etc.)). Another vehicle condition may be whether an emergency brake is engaged. Another vehicle condition may be whether a main brake is presently engaged and possibly engaged to what degree. Another vehicle condition may be whether an accelerator is presently engaged and possibly to what degree. Another vehicle condition may be the status of the steering wheel (e.g., turned which way and how much) and/or wheel(s) directing the vehicle (e.g., direction of front wheels). Other example vehicle conditions may include whether a right-turn indicator is actuated, whether a left-turn indicator is actuated, and/or whether hazard lights (also called “four ways” or emergency flashers, etc.) are actuated. Another example vehicle condition may include tire status (e.g., tire pressure, rate of tire pressure change (e.g., to indicate a flat or blowout)). Another example vehicle condition is speed, e.g., as registered by a speedometer

of the vehicle and/or determined by other means (e.g., using the PMO sensor **280**). These vehicle conditions are examples, and one or more other sensors may be provided to sense one or more other vehicle conditions. Further, numerous other UE conditions may be sensed and indicated where the UE **200** is not a vehicle or is not associated with a vehicle.

(31) The PMO sensor **280** may include one or more sensors for providing one or more UE conditions such as, for example, vehicle conditions. For example, the PMO sensor **280** may include one or more sensors for measuring information from which position and/or motion and/or orientation of the UE **200** may be determined and possibly determining position and/or motion (e.g., speed and/or direction of motion) and/or orientation of the UE **200**. In this example, the PMO sensor **280** includes a Satellite Positioning System (SPS) receiver **281**, a position device (PD) **282**, an Inertial Measurement Unit (IMU) **283**, and a magnetometer **284**. The components of the PMO sensor **280** shown are examples, and one or more of these components may be omitted and/or one or more other components included in the PMO sensor **280**. Also, while each of the components **281-284** of the PMO sensor **280** may be referred to in the singular, each of the components **281-284** may include more than one such component, examples of some of which are discussed explicitly herein. Also, the PD **282** may be part of the SPS receiver **281** and/or the IMU **283** and/or part of the processor **210**, and may not be a sensor itself (e.g., may not take measurements), but may process information from one or more of the sensors **281**, **283**, **284** and/or one or more other sensors. The PMO **280** may be used to determine UE speed and/or direction of motion, e.g., by determining UE location over time (e.g., determined using SPS, one or more ranging sensors, etc.).

(32) The IMU **283** may comprise one or more inertial sensors, for example, an accelerometer **287** (e.g., responding to acceleration of the UE **200** in three dimensions) and/or a gyroscope **288**. While each of the sensors **287**, **288** may be referred to in the singular, each of the sensors **287**, **288** may include more than one sensor. The accelerometer may include one or more three-dimensional accelerometers and the gyroscope may include one or more three-dimensional gyroscopes. The IMU **283** may be configured to provide measurements about a direction of motion and/or a speed of motion of the UE **200**, which may be used, for example, in relative location determination. For example, the accelerometer **287** and/or the gyroscope **288** of the IMU **283** may detect, respectively, a linear acceleration and a speed of rotation of the UE **200**. The linear acceleration and speed of rotation measurements of the UE **200** may be integrated over time (e.g., by the IMU **283** and/or the PD **282**) to determine an instantaneous direction of motion as well as a displacement of the UE **200**. The instantaneous direction of motion and the displacement may be integrated to track a location of the UE **200**. For example, a reference location of the UE **200** may be determined, e.g., using the SPS receiver **281** (and/or by some other means) for a moment in time and measurements from the accelerometer **287** and the gyroscope **288** taken after this moment in time may be used in dead reckoning to determine a present location of the UE **200** based on movement (direction and distance) of the UE **200** relative to the reference location.

(33) The magnetometer **284** may determine magnetic field strengths in different directions which may be used to determine orientation of the UE **200**, which may be used, for example, to provide a digital compass for the UE **200**. The magnetometer **284** may include a two-dimensional magnetometer configured to detect and provide indications of magnetic field strength in two orthogonal dimensions. Also or alternatively, the magnetometer **284** may include a three-dimensional magnetometer configured to detect and provide indications of magnetic field strength in three orthogonal dimensions. The magnetometer **284** may provide means for sensing a magnetic field and providing indications of the magnetic field, e.g., to the processor **210**. The magnetometer **284** may provide measurements to determine orientation (e.g., relative to magnetic north and/or true north) that may be used for any of a variety of purposes, e.g., to support one or more compass applications. While referred to in the singular, the magnetometer **284** may include multiple magnetometers.

(34) The SPS receiver **281** (e.g., a Global Positioning System (GPS) receiver or other Global

Navigation Satellite System (GNSS) receiver) may be capable of receiving and acquiring SPS signals **285** via an SPS antenna **286**. The antenna **286** is configured to transduce the wireless SPS signals **285** to wired signals, e.g., electrical or optical signals, and may be integrated with the antenna **246**. The SPS receiver **281** may be configured to process, in whole or in part, the acquired SPS signals **285** for estimating a location of the UE **200**. For example, the SPS receiver **281** may be configured to determine location of the UE **200** by trilateration using the SPS signals **285**. The general-purpose processor **230**, the memory **211**, the DSP **231** and/or one or more specialized processors (not shown) may be utilized to process acquired SPS signals, in whole or in part, and/or to calculate an estimated location of the UE **200**, in conjunction with the SPS receiver **281**. The memory **211** may store indications (e.g., measurements) of the SPS signals **285** and/or other signals (e.g., signals acquired from the wireless transceiver **240**) for use in performing positioning operations. The general-purpose processor **230**, the DSP **231**, and/or one or more specialized processors, and/or the memory **211** may provide or support a location engine for use in processing measurements to estimate a location of the UE **200**. Also or alternatively, some or all of the position determination signal processing may be performed by the PD **282**.

(35) The position device (PD) **282** may be configured to determine a position of the UE **200** (including absolute and/or relative position of the UE **200**), motion of the UE **200**, and/or time. For example, the PD **282** may communicate with, and/or include some or all of, the SPS receiver **281**. The PD **282** may use measurements from the SPS receiver **281** and/or the IMU **283** and/or the magnetometer **284** to determine position and/or motion of the UE **200**, e.g., using trilateration and/or dead reckoning. The PD **282** may work in conjunction with the processor **210** and the memory **211** as appropriate to perform at least a portion of one or more positioning methods (to determine location of the UE **200**), although the description herein may refer only to the PD **282** being configured to perform, or performing, one or more operations in accordance with the positioning method(s). The PD **282** may also or alternatively be configured to determine location of the UE **200** using terrestrial-based signals (e.g., at least some of signals **248** discussed below) for trilateration, for assistance with obtaining and using the SPS signals **285**, or both. The PD **282** may be configured to use one or more other techniques (e.g., relying on the UE's self-reported location (e.g., part of the UE's position beacon)) for determining the location of the UE **200**, and may use a combination of techniques (e.g., SPS and terrestrial positioning signals) to determine the location of the UE **200**. The PD **282** may be configured to provide indications of uncertainty and/or error in the determined position and/or motion. Functionality of the PD **282** may be provided in a variety of manners and/or configurations, e.g., by the general purpose/application processor **230**, the transceiver **215**, the SPS receiver **281**, and/or another component of the UE **200**, and may be provided by hardware, software, firmware, or various combinations thereof.

(36) The transceiver **215** may include a wireless transceiver **240** and/or a wired transceiver **250** configured to communicate with other devices through wireless connections and wired connections, respectively. For example, the wireless transceiver **240** may include a wireless transmitter **242** and a wireless receiver **244** coupled to one or more antennas **246** for transmitting (e.g., on one or more uplink channels and/or one or more sidelink channels) and/or receiving (e.g., on one or more downlink channels and/or one or more sidelink channels) wireless signals **248** and transducing signals from the wireless signals **248** to wired (e.g., electrical and/or optical) signals and from wired signals to the wireless signals **248**. The wireless transceiver **240** may be configured for wireless communication to send communications to, and receive communications from, a variety of entities such as other UEs, base stations, etc. Thus, the wireless transmitter **242** may include multiple transmitters that may be discrete components or combined/integrated components, and/or the wireless receiver **244** may include multiple receivers that may be discrete components or combined/integrated components. The wireless transceiver **240** may be configured to communicate signals (e.g., with TRPs and/or one or more other devices) according to a variety of radio access technologies (RATs) such as 5G New Radio (NR), GSM (Global System for Mobiles), UMTS

(Universal Mobile Telecommunications System), AMPS (Advanced Mobile Phone System), CDMA (Code Division Multiple Access), WCDMA (Wideband CDMA), LTE (Long-Term Evolution), LTE Direct (LTE-D), 3GPP LTE-V2X (PC5), IEEE 802.11 (including IEEE 802.11p), WiFi, WiFi Direct (WiFi-D), Bluetooth®, Zigbee etc. New Radio may use mm-wave frequencies and/or sub-6 GHz frequencies. The wired transceiver **250** may include a wired transmitter **252** and a wired receiver **254** configured for wired communication, e.g., a network interface that may communicate with the network **130**, e.g., to send communications to, and receive communications from, a gNB, for example. The wired transmitter **252** may include multiple transmitters that may be discrete components or combined/integrated components, and/or the wired receiver **254** may include multiple receivers that may be discrete components or combined/integrated components. The wired transceiver **250** may be configured, e.g., for optical communication and/or electrical communication. The transceiver **215** may be communicatively coupled to the transceiver interface **214**, e.g., by optical and/or electrical connection. The transceiver interface **214** may be at least partially integrated with the transceiver **215**.

(37) The wireless transceiver **240** may be configured for beam management to affect directionality of the wireless transceiver **240**, e.g., of the antenna **246**. For example, the wireless transceiver **240** may be configured to implement beam forming for transmission and/or reception of the signals **248**. The antenna **246** may include multiple antennas that are configured, e.g., designed, made, disposed, and directed to point in different directions relative to a body of the UE **200**. One or more of such antennas may be capable of electronic beam steering (e.g., using appropriate phase shifts of elements of the antenna) and/or mechanical beam steering. Also or alternatively, the transceiver **240** may be configured to selectively (e.g., under direction/control of the processor **210**) transmit from one or more antennas and/or to selectively process signals (e.g., to pass from the transceiver **215** to the processor **210** or to process by the processor **210**) received from one or more antennas.

(38) The user interface **216** may comprise one or more of several devices such as, for example, a speaker, microphone, display device, vibration device, keyboard, touch screen, etc. The user interface **216** may include more than one of any of these devices. The user interface **216** may be configured to enable a user to interact with one or more applications hosted by the UE **200**. For example, the user interface **216** may store indications of analog and/or digital signals in the memory **211** to be processed by DSP **231** and/or the general-purpose processor **230** in response to action from a user. Similarly, applications hosted on the UE **200** may store indications of analog and/or digital signals in the memory **211** to present an output signal to a user. The user interface **216** may include an audio input/output (I/O) device comprising, for example, a speaker, a microphone, digital-to-analog circuitry, analog-to-digital circuitry, an amplifier and/or gain control circuitry (including more than one of any of these devices). Other configurations of an audio I/O device may be used. Also or alternatively, the user interface **216** may comprise one or more touch sensors responsive to touching and/or pressure, e.g., on a keyboard and/or touch screen of the user interface **216**.

(39) Referring also to FIG. 3, an example of a TRP **300** of the BTSs **120-123** and/or the RSU **160** comprises a computing platform including a processor **310**, memory **311** including software (SW) **312**, and a transceiver **315**. The processor **310**, the memory **311**, and the transceiver **315** may be communicatively coupled to each other by a bus **320** (which may be configured, e.g., for optical and/or electrical communication). One or more of the shown apparatus (e.g., a wireless interface) may be omitted from the TRP **300**. The processor **310** may include one or more intelligent hardware devices, e.g., a central processing unit (CPU), a microcontroller, an application specific integrated circuit (ASIC), etc. The processor **310** may comprise multiple processors (e.g., including a general-purpose/application processor, a DSP, a modem processor, a video processor, and/or a sensor processor as shown in FIG. 2). The memory **311** is a non-transitory storage medium that may include random access memory (RAM)), flash memory, disc memory, and/or read-only memory (ROM), etc. The memory **311** stores the software **312** which may be processor-readable,

processor-executable software code containing instructions that are configured to, when executed, cause the processor **310** to perform various functions described herein. Alternatively, the software **312** may not be directly executable by the processor **310** but may be configured to cause the processor **310**, e.g., when compiled and executed, to perform the functions. The description may refer only to the processor **310** performing a function, but this includes other implementations such as where the processor **310** executes software and/or firmware. The description may refer to the processor **310** performing a function as shorthand for one or more of the processors contained in the processor **310** performing the function. The description may refer to the TRP **300** performing a function as shorthand for one or more appropriate components of the TRP **300** (and thus of one of the BTSs **120-123** or the RSU **160**) performing the function. The processor **310** may include a memory with stored instructions in addition to and/or instead of the memory **311**. Functionality of the processor **310** is discussed more fully below.

(40) The transceiver **315** may include a wireless transceiver **340** and/or a wired transceiver **350** configured to communicate with other devices through wireless connections and wired connections, respectively. For example, the wireless transceiver **340** may include a wireless transmitter **342** and a wireless receiver **344** coupled to one or more antennas **346** for transmitting (e.g., on one or more uplink channels and/or one or more downlink channels) and/or receiving (e.g., on one or more downlink channels and/or one or more uplink channels) wireless signals **348** and transducing signals from the wireless signals **348** to wired (e.g., electrical and/or optical) signals and from wired (e.g., electrical and/or optical) signals to the wireless signals **348**. Thus, the wireless transmitter **342** may include multiple transmitters that may be discrete components or combined/integrated components, and/or the wireless receiver **344** may include multiple receivers that may be discrete components or combined/integrated components. The wireless transceiver **340** may be configured to communicate signals (e.g., with the UE **200**, one or more other UEs, and/or one or more other devices) according to a variety of radio access technologies (RATs) such as 5G New Radio (NR), GSM (Global System for Mobiles), UMTS (Universal Mobile Telecommunications System), AMPS (Advanced Mobile Phone System), CDMA (Code Division Multiple Access), WCDMA (Wideband CDMA), LTE (Long-Term Evolution), LTE Direct (LTE-D), 3GPP LTE-V2X (PC5), IEEE 802.11 (including IEEE 802.11p), WiFi, WiFi Direct (WiFi-D), Bluetooth®, Zigbee etc. The wired transceiver **350** may include a wired transmitter **352** and a wired receiver **354** configured for wired communication, e.g., a network interface that may communicate with the network **130**, e.g., to send communications to, and receive communications from, the server **143**, for example. The wired transmitter **352** may include multiple transmitters that may be discrete components or combined/integrated components, and/or the wired receiver **354** may include multiple receivers that may be discrete components or combined/integrated components. The wired transceiver **350** may be configured, e.g., for optical communication and/or electrical communication.

(41) The configuration of the TRP **300** shown in FIG. 3 is an example and not limiting of the aspects and features of the disclosure, including the claims, and other configurations may be used. For example, the description herein discusses that the TRP **300** is configured to perform or performs several functions, but one or more of these functions may be performed by the server **143** and/or the UE **200** (i.e., the server **143** and/or the UE **200** may be configured to perform one or more of these functions).

(42) Referring also to FIG. 4, a server **400**, which is an example of the server **143**, comprises a computing platform including a processor **410**, memory **411** including software (SW) **412**, and a transceiver **415**. The processor **410**, the memory **411**, and the transceiver **415** may be communicatively coupled to each other by a bus **420** (which may be configured, e.g., for optical and/or electrical communication). One or more of the shown apparatus (e.g., a wireless interface) may be omitted from the server **400**. The processor **410** may include one or more intelligent hardware devices, e.g., a central processing unit (CPU), a microcontroller, an application specific

integrated circuit (ASIC), etc. The processor **410** may comprise multiple processors (e.g., including a general-purpose/application processor, a DSP, a modem processor, a video processor, and/or a sensor processor as shown in FIG. 2). The memory **411** is a non-transitory storage medium that may include random access memory (RAM)), flash memory, disc memory, and/or read-only memory (ROM), etc. The memory **411** stores the software **412** which may be processor-readable, processor-executable software code containing instructions that are configured to, when executed, cause the processor **410** to perform various functions described herein. Alternatively, the software **412** may not be directly executable by the processor **410** but may be configured to cause the processor **410**, e.g., when compiled and executed, to perform the functions. The description may refer only to the processor **410** performing a function, but this includes other implementations such as where the processor **410** executes software and/or firmware. The description may refer to the processor **410** performing a function as shorthand for one or more of the processors contained in the processor **410** performing the function. The description may refer to the server **400** performing a function as shorthand for one or more appropriate components of the server **400** performing the function. The processor **410** may include a memory with stored instructions in addition to and/or instead of the memory **411**. Functionality of the processor **410** is discussed more fully below.

(43) The transceiver **415** may include a wireless transceiver **440** and/or a wired transceiver **450** configured to communicate with other devices through wireless connections and wired connections, respectively. For example, the wireless transceiver **440** may include a wireless transmitter **442** and a wireless receiver **444** coupled to one or more antennas **446** for transmitting (e.g., on one or more downlink channels) and/or receiving (e.g., on one or more uplink channels) wireless signals **448** and transducing signals from the wireless signals **448** to wired (e.g., electrical and/or optical) signals and from wired (e.g., electrical and/or optical) signals to the wireless signals **448**. Thus, the wireless transmitter **442** may include multiple transmitters that may be discrete components or combined/integrated components, and/or the wireless receiver **444** may include multiple receivers that may be discrete components or combined/integrated components. The wireless transceiver **440** may be configured to communicate signals (e.g., with the UE **200**, one or more other UEs, and/or one or more other devices) according to a variety of radio access technologies (RATs) such as 5G New Radio (NR), GSM (Global System for Mobiles), UMTS (Universal Mobile Telecommunications System), AMPS (Advanced Mobile Phone System), CDMA (Code Division Multiple Access), WCDMA (Wideband CDMA), LTE (Long-Term Evolution), LTE Direct (LTE-D), 3GPP LTE-V2X (PC5), IEEE 802.11 (including IEEE 802.11p), WiFi, WiFi Direct (WiFi-D), Bluetooth®, Zigbee etc. The wired transceiver **450** may include a wired transmitter **452** and a wired receiver **454** configured for wired communication, e.g., a network interface that may communicate with the network **130** to send communications to, and receive communications from, the TRP **300**, for example. The wired transmitter **452** may include multiple transmitters that may be discrete components or combined/integrated components, and/or the wired receiver **454** may include multiple receivers that may be discrete components or combined/integrated components. The wired transceiver **450** may be configured, e.g., for optical communication and/or electrical communication.

(44) The configuration of the server **400** shown in FIG. 4 is an example and not limiting of the aspects and features of the disclosure, including the claims, and other configurations may be used. For example, the wireless transceiver **440** may be omitted. Also or alternatively, the description herein discusses that the server **400** is configured to perform or performs several functions, but one or more of these functions may be performed by the TRP **300** and/or the UE **200** (i.e., the TRP **300** and/or the UE **200** may be configured to perform one or more of these functions).

(45) Referring to FIG. 5, with further reference to FIGS. 1-4, a UE **500** includes a processor **510**, an interface **520**, a memory **530**, and one or more sensors **540** communicatively coupled to each other by a bus **550**. The UE **500** may include the components shown in FIG. 5, and may include one or more other components such as any of those shown in FIG. 2 such that the UE **200** may be

an example of the UE **500**. The interface **520** may include one or more of the components of the transceiver **215**, e.g., the wireless transmitter **242** and the antenna **246**, or the wireless receiver **244** and the antenna **246**, or the wireless transmitter **242**, the wireless receiver **244**, and the antenna **246**. The memory **530** may be configured similarly to the memory **211**, e.g., including software with processor-readable instructions configured to cause the processor **510** to perform functions. The sensor(s) **540** may include one or more of the sensors in the sensor(s) **213**. For example, the sensor(s) **540** may include one or more environmental sensors and/or one or more sensors (e.g., the status sensor **270** and/or the PMO sensor **280**, or one or more portions thereof) for providing one or more indications of one or more UE conditions. The processor **510** may be configured similarly to the processor **210** or may include a subset of the components of the processor **210** and/or one or more components in addition to the components of the processor **210**. The description may refer only to the processor **510** performing a function, but this includes other implementations such as where the processor **510** executes software (stored in the memory **530**) and/or firmware. The description may refer to the UE **500** performing a function as shorthand for one or more appropriate components (e.g., the processor **510** and the memory **530**) of the UE **500** performing the function. The processor **510** (possibly in conjunction with the memory **530** and, as appropriate, the interface **520**) includes a communication resource allocation unit **560** configured to allocate resources of the UE **200** for communication as discussed herein. The functional unit **560** is discussed further below, and the description may refer to the processor **510** generally, or the UE **500** generally, as performing any of the functions of the functional unit **560**.

(46) The communication resource allocation unit **560** is configured to determine and control which resources to use for communication. The unit **560** may be configured to use information from the sensor(s) **540**, the location(s) of the sensor(s) in the UE **500**, coverage area(s) of the sensor(s) **540** (e.g., a field of view of a camera), etc. to draw conclusions from the information provided by the sensor(s) **540** that may affect how the unit **560** allocates one or more resources (e.g., (usage of) one or more components of the UE **500**, energy used by the UE **500**, etc.) for communication. The unit **560** may, for example, determine directionality and/or power to use for communication transmission and/or reception, and/or may determine a quantity of antenna beams and/or a quantity of antennas to use for transmission and/or reception, and/or may determine processing effort (also referred to herein as processing level) (e.g., processing power, bandwidth, and/or time) for communication transmission and/or reception. The unit **560** may, for example, save power by selectively transmitting and/or receiving with less than full bandwidth and/or by selectively reducing a message repetition (i.e., how many times that a message is repeatedly transmitted). The unit **560** may use power and/or beam management to allocate communication resources, e.g., as discussed herein.

(47) Referring also to FIG. **6**, an environment **600** includes a base station **610**, UEs **620**, **621**, **622**, **623**, **624**, **625**, **626**, an emergency vehicle **627** (here a fire engine), and a building **628**. In this example, the UEs **620-626** are vehicles, e.g., integrated into the vehicles, although one or more UEs may be associated with, but not integrated into, one or more respective vehicles, or not associated with a vehicle. In this example, each of the UEs **620-626** is an example of the UE **500**. The UEs **620-626** may be configured to use CV2X to communicate with each other, being configured to send and receive signals to and from each other. The UEs **620-626** may also be configured to send and receive various types of messages to and from the base station **610**, here a roadside equipment (RSE) base station. The description may refer to the UE **500** (and/or one or more components of the UE **500**) with respect to any of the UEs **620-626** (because the UEs **620-626** are examples of the UE **500**) and may refer to specific ones of the UEs **620-626** as examples of the UE **500** as appropriate.

(48) The UE **500** may be configured to broadcast messages, via the interface **520**, for receipt by any device within communication range (based on the RAT (Radio Access Technology) used to transmit the messages and other conditions, e.g., environment, weather, etc.) of the UE **500**. For

example, the UE **500** may be configured to produce and send position messages, standalone transaction messages (STMs), and/or embedded transaction messages (ETMs) that are transaction messages embedded in position messages. The STMs may include private information, e.g., a token, that is associated with and identifies the UE **500**. The position messages and the ETMs may include position information (e.g., UE location (position) and possibly including uncertainty and/or error) for the UE **500**. The position information may include motion information (i.e., changing-position information) for the UE **500**. For example, the position messages and the ETMs may include a position of the UE **500** relative to a reference point (e.g., center of the Earth, or a point on a surface of the Earth, etc.) and may include information indicative of kinematic state of the UE **500**, e.g., a velocity vector and/or an acceleration vector. The position messages may comprise Basic Safety Messages (BSMs) and/or other messages. The position messages may be conveyed, e.g., using V2X technology such as C-V2X and/or DSRC. The ETMs may include the position information (possibly including motion information) as well as private information identifying the UE **500** as found in STMs. The position and/or motion information of the position messages and/or the ETMs may be used by any of the other UEs for various purposes such as collision avoidance (e.g., blind-zone object detection), other safety-related purposes, and/or other purposes, whether safety related or not.

(49) The UE **500** may be configured to use one or more indications from one or more of the sensor(s) **540** to determine whether and how to affect communication operation of the UE **500**, e.g., communication transmission, communication reception, and/or communication signal processing, and to control the communication operation accordingly. The processor **510** (e.g., the communication resource allocation unit **560**) may analyze various sensor indications and/or various combinations of sensor indications and/or one or more sensor indications over time (e.g., one or more differences in one or more sensor indications at different times) to affect communication operation of the UE **500**. The processor **510** may determine whether communication may be compromised, e.g., in a certain direction due to, for example, an object and may determine to reduce communication resource(s) in that direction. As another example, the processor **510** may determine to reduce communication generally, e.g., processing power and/or transmission power, for one or more reasons such as lack of recipients of information, communication priority of another entity (e.g., another UE such as an emergency vehicle). Numerous reasons for affecting communication and numerous ways of affecting communication are possible, some of which are discussed herein as examples. Communication may be affected temporarily, e.g., while a transient condition exists, and communication processing returned to a previous condition once the condition no longer exists.

(50) The processor **510** may be configured to affect communication directionality. For example, the processor **510** may be configured to implement beam management of the interface **520**. For example, the processor **510** may be configured to control the interface **520** to select one or more beams (e.g., one or more beams **671**, **672**, **673**, **674**, **675**, **676** of the UE **623**) corresponding to one or more desired directions for transmitting and/or receiving signals. Also or alternatively, the processor **510** may be configured to cause the interface **520** to affect an antenna pattern of one or more beams (e.g., to focus or broaden a mainbeam). Also or alternatively, the processor **510** may be configured to cause the interface **520** to implement beam steering to direct one or more beams as desired. Also or alternatively, the processor **510** may be configured to cause the interface **520** to provide more or less transmit power for one or more beams, respectively, and/or for one or more transmission signals, respectively (e.g., different beams and/or different signals may be transmitted with different powers). Also or alternatively, the processor **510** may be configured to cause the interface **520** to increase or reduce a transmit frequency or periodicity for one or more beams, respectively, and/or for one or more transmission signals, respectively (e.g., different beams and/or different signals may be transmitted with different frequencies or periodicities). For example, the processor **510** may increase transmission frequency (reduce periodicity) in one or more desired

directions and/or reduce frequency (increase periodicity) of transmissions in one or more undesired directions. Also or alternatively, the processor **510** may be configured to process signals from selected beams in order to process signals received from one or more desired directions. Also or alternatively, the processor **510** may be configured not to process signals from one or more beams (e.g., not from one or more entire antennas of the interface **520**) in order not to process signals received from one or more undesired directions. Also or alternatively, the processor **510** may be configured to control the interface **520** not to provide one or more particular signals to the processor **510** and/or not to provide signals from one or more beams (e.g., not from one or more entire antennas of the interface **520**) to the processor **510** in order to inhibit or prevent processing of signals received from one or more undesired directions. Affecting the directionality may affect multiple directions, e.g., increasing transmit power in one direction and reducing (e.g., eliminating) transmit power in another direction.

(51) Also or alternatively, the processor **510** may be configured to affect communication operation by affecting one or more transmission parameters. For example, the processor **510** may be configured to control a transmission power of one or more beams and/or one or more signals transmitted by the interface **520**. Also or alternatively, the processor **510** may be configured to control a transmission frequency (periodicity) for one or more signals and/or one or more beams. Also or alternatively, the processor **510** may be configured to increase or reduce a quantity of signals transmitted.

(52) Also or alternatively, the processor **510** may be configured to affect communication operation by affecting processing effort or processing level of the processor **510**. For example, the processor **510** may be configured to control which signals (for transmission and/or that are received) are processed by the processor **510**, how much processing resources (e.g., power and/or memory) are made available or used to process (e.g., transmit or measure) one or more particular signals, and/or how much time is made available or allocated for processing one or more particular signals.

(53) Also or alternatively, the processor **510** may affect sensor integration priority, e.g., change pre-defined terms and/or data used in an artificial intelligence (AI) algorithm or neural network. The sensor information obtained by the processor **510** may be used by the processor **510** to guide one or more AI algorithms run by the processor **510** for using the sensor information. For example, the sensor information may affect the AI algorithm(s) which may result in the processor **510** directing operation of the UE **500** differently when the UE **500** is at rest and parked (e.g., the vehicle is in park) compared to when the UE **500** is at rest at a traffic light (e.g., the vehicle is in drive but the brake is applied).

Example Scenarios

(54) Referring also to FIG. 7, a table **700** of sensor values includes values at different times corresponding to various sensor information. In this example, the sensor information includes fields of video **711**, audio **712**, speed **713**, acceleration **714**, LIDAR **715**, temperature **716**, air flow **717**, and SPS location **718**. The table **700** is a very simple example, with each field showing a variable indicative of a sensor value, and with the table **700** including only one sensor indication for each type of information, and with far fewer types of sensor information included than may be used. The table **700** is thus a simplified example only, provided to give a relatively uncomplicated example of such information and from which a few examples of determined resource allocation are discussed. In the table **700**, four sensor value sets (SVS) **731**, **732**, **733**, **734** comprise respective values of each of the sensor information fields **711-718** measured (or determined from measurements taken) at different times $t_{sub.1}$, $t_{sub.2}$, $t_{sub.3}$, $t_{sub.1}$, respectively. Differences between the times are arbitrary and may be any number of amounts of times (e.g., one second, 10 seconds, 500 ms, etc.), and may be different between different pairs of the sensor value sets **731-734**. The examples below are based on values in the table **700** and are examples only and not limiting of the aspects and features of the disclosure or the claims. The examples are for a UE at rest, a UE in forward motion, and a UE slowing forward motion. Clearly, numerous other examples

are possible, e.g., rearward motion, slowing rearward motion, increasing forward motion, increasing rearward motion, etc. Further, the discussion regarding the examples is not limited to these examples, and thus the discussion (e.g., capabilities of the UE **500**) has applicability beyond these examples, e.g., to the UE **500** generally.

(55) The processor **510** (e.g., the communication resource allocation unit **560**) may analyze the sensor values of the table **700** to determine allow to allocate one or more communication resources, and implement the determined allocation. For example, the processor **510** may analyze one or more individual sensor values in the table **700**, one or more of the sensor value sets **731-734**, two or more of the values within one or more of the sensor value sets **731-734**, and/or combinations of two or more of the sensor value sets **731-734**. For example, the processor **510** may determine and analyze one or more differences between sensor value sets (one or more changes from one sensor value set to another sensor value set) such as a first difference between the sensor value sets **731**, **732**, a second difference between the sensor value sets **732**, **733**, and/or a third difference between the sensor value sets **733**, **734**. The processor **510** may be configured to allocate one or more resources based on one or more values of one or more sensor value sets and/or based on one or more sensor value changes (differences) between sensor value sets. For example, the processor may be configured to allocate one or more resources based on one or more sensor values changing and/or based on the value(s) (e.g., magnitude(s)) of the change(s).

UE at Rest

(56) The processor **510** may determine from the sensor value set **731**, the sensor value set **732**, and/or from a difference between sensor value sets **731** and **732** that the UE **500** is at rest. For example, the processor **510** may conclude from the sensor value set **731** that the UE **500** is at rest, e.g., in response to the value C of the speed field **713** and the value D of the acceleration field **714** both being zero. As another example, the processor **510** may conclude from the sensor value sets **731**, **732** that the UE **500** is at rest, e.g., in response to the values of the speed field **713**, the acceleration field **714**, and the SPS location field **718** being the same in both of the sensor value sets **731**, **732** (a difference being zero) and the value C of the speed field **713** and the value D of the acceleration field **714** both being zero. For example, the UE **500** may be the UE **626** shown in FIG. **6** that is at rest, being parked next to a road **640** and the building **628**.

(57) The processor **510** may be configured to determine an amount of other UEs nearby (e.g., within communication range). For example, the processor **510** may analyze information from the video field **711** (e.g., one or more captured images), information from the audio field **712**, and/or information from the LIDAR field **715** to determine whether there are any other UEs nearby, and if so how many (e.g., a quantity, a density) other UEs, e.g., vehicles, nearby. Also or alternatively, one or more other types of information (e.g., from a motion sensor) may be used to determine presence of other UEs.

(58) The processor **510** may be configured to allocate one or more communication resources based on the UE **500** being at rest and/or with little UE traffic nearby (e.g., below a threshold quantity of UEs). For example, the UE **500** may respond to determining that the UE **500** is at rest (e.g., the parked UE **626**) with less than a threshold amount of nearby UEs by setting a transmit power value or transmit power limit or a receive signal processing power value or receive signal processing limit, reducing transmit and/or receive signal processing power if the present transmit and/or receive power is higher than the respective power value or limit that is set. The processor **510** may adjust the processing power to be more efficient. The processor **510** may set (e.g., alter) one or more transmit and/or receive processing parameters such as periodicity, number of transmissions, which resource blocks (RBs) are transmitted and/or processed if received, a modulation and coding scheme (MCS) implemented by the UE **500**, etc. This may help reduce cost, e.g., reduce processing power (e.g., CPU power, edge power) and thus save (conserve) battery power, reduce temperature of the processor **510** (and/or a chip containing the processor **510**), and/or increase a life expectancy of the processor **510** (and/or a chip containing the processor **510**). The processor **510** may not

change operation of the sensor(s) **530** so that the sensor(s) may remain active even after the processor **510** determines that the UE **500** is at rest and there is little nearby traffic so that the processor **510** can determine a change in motion of the UE **500**, a change in nearby traffic, and/or another change.

UE in Forward Motion

(59) The processor **510** may determine from the sensor value set **733** and/or from a difference between sensor value sets **732** and **733** that the UE **500** is in forward motion. For example, the processor **510** may conclude from the sensor value set **733** that the UE **500** is in forward motion in response to the value C1 of the speed field **713** and the value D1 of the acceleration field **714** both being positive, non-zero values, or in response to the value C1 being positive regardless of the value D1 (with positive speed values being associated with forward motion and negative values being associated with reverse motion). As another example, the processor **510** may conclude from the sensor value sets **732**, **733** that the UE **500** is in forward motion, e.g., in response to the values H, H1 of the SPS location field **718** being different in the two sensor value sets, the values of the video field **711** being different in the two sensor value sets, and the value of the speed field C1 in the sensor value set **733** being positive, and possibly in response to an orientation of the UE **500** being directed from the earlier location toward the later location, e.g., from the location H toward the location H1 (where t.sub.3 is after t.sub.2).

(60) The processor **510** may be configured to allocate one or more communication resources based on the UE **500** being in forward motion. For example, the processor **510** may affect communication directionality, e.g., including affecting beam management, to allocate more communication resources to a front of the UE **500** and/or in a forward direction. For example, the processor **510** may cause the interface **520** to transmit and/or receive more communication signals and/or with more power to and/or from forward directions (e.g., a sector **660** away from a front of the UE **500**, in this example, the UE **623**). Also or alternatively, the processor **510** may allocate fewer resources to a rear of the UE **500** and/or in a rearward direction. For example, the processor **510** may cause the interface **520** to transmit and/or receive fewer communication signals and/or with less power to and/or from rearward directions (i.e., directions away from a rear of the UE **500**, e.g., a sector **662** of directions away from the rear of the UE **500**). The processor **510** may cause the interface **520** to increase transmit power (e.g., to provide more coverage (more area in communication range)) and/or transmit frequency and/or transmit signal quantity in the sector **660**. The processor **510** may cause the interface **520** to reduce or prevent forwarding of signals from the sector **662** to the processor **510** for processing. The processor **510** may reduce or stop processing of signals received from the sector **662**. The processor **510** may affect processing effort, e.g., increasing processing effort for signals sent to the sector **660** and/or signals received from the sector **660** and/or decreasing processing effort for signals received from the sector **662** and/or signals transmitted in the sector **662**. Any of these measures may improve safety, e.g., by providing improved communication with one or more UEs in a direction in which the UE **500**, e.g., the UE **623**, is moving. The UE **500** may use the allocated resources in a variety of ways, e.g., to notify one or more other UEs of the motion of the UE **500** (e.g., for use in collision avoidance, traffic planning, etc.).

(61) The processor **510** may be configured to allocate one or more communication resources based on the UE **500** being in rearward motion. For example, the processor **510** may be configured to allocate resources in a similar manner as for forward motion, but reversed, e.g., to direct more communication resources toward a rear of the UE **500** and less resources toward a front of the UE **500**.

UE in Slowing Forward Motion

(62) The processor **510** may determine from the sensor value set **734** and/or from a difference between sensor value sets **733** and **734** that the UE **500** is in slowing forward motion. For example, the processor **510** may conclude from the sensor value set **734** that the UE **500** is in slowing

forward motion in response to the value C2 of the speed field **713** being positive and the value D2 of the acceleration field **714** being negative. As another example, the processor **510** may conclude from the sensor value sets **733**, **734** that the UE **500** is in slowing forward motion, e.g., in response to the values C1, C2 of the speed field **713** both being positive and the value C2 being of a lower magnitude than the value C1 (with the time t.sub.4 being after the time t.sub.3).

(63) The processor **510** may be configured to allocate one or more communication resources based on the UE **500** being in slowing forward motion. For example, the processor **510** may affect communication directionality, e.g., including affecting beam management, to allocate more communication resources to a rear of the UE **500** and/or in a rearward direction (e.g., more than allocated to a front of the UE **500** and/or more than previously allocated to the rear of the UE **500**) and to allocate fewer communication resources to a front of the UE **500** and/or in a forward direction (e.g., fewer than allocated to the rear of the UE **500** and/or fewer than previously allocated to the front of the UE **500**). The processor **510** may be configured to allocate more resources in one or more directions at least partially toward a direction of motion (travel) and fewer resources in one or more directions at least partially away from a direction of motion.

Object Presence

(64) The processor **510** may be configured to allocate one or more communication resources based on object detection. For example, the processor **510** may be able to analyze one or more measurements in the LIDAR field **715** and/or the air flow field **717** to determine presence of an object, and possibly determine direction of the object relative to the UE **500** and/or size (e.g., width and/or height) of the object. For example, the value E of the LIDAR field **715**, e.g., a range value, may indicate that an object is close on the starboard side of the UE **500**. Also or alternatively, the processor **510** may use a low air flow and/or a decrease in air flow as at least part of an analysis to determine whether an object is present. Also or alternatively, the processor **510** may use location, e.g., from the SPS location field **718**, orientation of the UE **500**, and information regarding topography near the location as at least part of an analysis for determining the presence (and direction) of an object. For example, the orientation may be used in conjunction with a location of the UE **500** to determine a direction relative to the UE **500** of an object that may impede communication between the UE **500** and another device such as another UE or a network entity (e.g., a base station or a server). For example, with the UE **500** being the UE **626**, the processor **510** may analyze one or more sensor measurements and determine that an object, here the building **628**, is on the starboard side of the UE **500** and that the object is a significant impediment to communication. The processor **510** may be configured to determine a size of an object. For example, the processor **510** may use image information from the video field **711** and/or multiple LIDAR measurements (providing distance to an object at different directions) and/or other information to determine the size of the object.

(65) The processor **510** may respond to a determination of object presence (and possibly orientation and/or object size) by affecting one or more characteristics, e.g., the directionality, of communication of the UE. The processor **510** may reduce or even eliminate communication transmission in the direction of the building **628**, e.g., a direction **650** (or directions near the direction **650**, e.g., in a sector including the direction **650**). Also or alternatively, the processor **510** may affect communication transmission and/or reception to be directed away from the detected object, here in a sector **652**, especially if the processor **510** knows that a base station, here the base station **610**, is in the direction of the sector **652**. For example, the processor **510** may select (only) the beam(s) directed in the sector **652** for transmission and/or reception, may process (only) signals from such beam(s), or may direct the interface **520** to use more power when transmitting signals in the sector **652** (e.g., to increase transmit power to the sector **652**) (e.g., more than for other sectors and/or more than previously used in the sector **652**). Also or alternatively, the processor **510** may reduce communication transmission and/or reception toward the object, e.g., reducing processing power of received signals from that direction, not processing signals received from that direction,

reducing transmit power toward the object, preventing transmission of signals toward the object, etc. The UE **500** may use the allocated communication resource(s) for one or more of a variety of reasons, e.g., to complete cellular calls, to notify one or more other UEs of the presence of and/or location of an object, etc. The allocation of resources (e.g., allocation of beams, allocation of transmission power, etc.) may be affected by the size of an object. For example, presence of a small object may not warrant reduction, or significant reduction, in resources in a direction of the object. As another example, transmission power may be increased toward a small object to overcome loss introduced by the object while transmission power may be reduced (possibly eliminated) toward a large object (e.g., that might block transmissions or introduce so much loss that transmission power used in the direction of the object would be inefficient, e.g., possibly completely wasted). Allocating resources may have one or more beneficial effects, e.g., reduction in heat generated by and/or temperature of the processor **510** and/or a chip containing the processor **510** in response to reduction of resources (e.g., processing power).

(66) The processor **510** may be configured to determine a change from absence to presence of an object. For example, the processor **510** may conclude from the sensor value set **734** that an object is present near the UE **500**, e.g., using techniques discussed above. As another example, the processor **510** may determine that an object is currently present, e.g., as discussed above, but was not previously, e.g., by analyzing the sensor value sets **733**, **734**. For example, the processor **510** may conclude from one or more of the differences between the sensor value sets **733**, **734** (one or more changes from the SVS **733** to the SVS **734**) that an object is now present (e.g., due to motion of the UE **500** and/or the object (e.g., a large vehicle)) in response to the value of the air flow field **716** decreasing between the sensor value sets **733**, **734** and/or the value of the LIDAR field **714** changing between the sensor value sets **733**, **734** and/or a value of the video field **711** (e.g., an image) containing an object that was previously absent. The processor **510** may allocate resources accordingly, e.g., to reduce resources in a direction of an object impeding communication and/or to increase allocated resources in one or more directions away from the object. For example, the vehicle **624** may detect the presence of the vehicle **627** and reduce (e.g., stop) transmission in the direction of the vehicle **627**.

Specific Object Presence

(67) The UE **500** may be configured to detect presence of one or more particular types of objects, e.g., an emergency vehicle, and allocate communication resources accordingly. For example, the processor **510** may analyze audio input from a microphone, e.g., one or more values of the audio field **712**, to detect a siren and/or may analyze one or more values of the video field **711** (e.g., one or more images) and/or other sensor information (e.g., LIDAR output, radar output) to determine that an emergency vehicle such as the fire engine **627** or another emergency vehicle (e.g., a police car, an ambulance) is present. The processor **510** may respond to determination of presence of an emergency vehicle by, for example, reducing or stopping communication transmissions, and/or reducing transmit power, at least temporarily and/or using beam management to help avoid interference between communications from the UE **500** and communications to and/or from the emergency vehicle. This may help improve emergency vehicle communication coverage, e.g., CV2X coverage, and/or reliability. Alternatively, the UE **500** may allocate more resources directed toward the emergency vehicle, e.g., increasing transmit power and/or transmit frequency toward the emergency vehicle and/or to increase signal processing of signals received from the emergency vehicle. Such action(s) may help increase information exchange with the emergency vehicle, e.g., to help with collision avoidance and/or to help clear a path for the emergency vehicle to move (e.g., to expedite arrival of the emergency vehicle to a desired location).

Lack of Object Presence

(68) The UE **500** may be configured to detect the lack of presence of objects, e.g., fewer than a threshold quantity of objects especially within a threshold distance of the UE **500**, and allocate communication resources accordingly. For example, the processor **510** may analyze video, lidar,

and/or radar input to determine that there are few or no objects nearby (e.g., if the UE 500 is on a desert road). The processor 510 may respond to determination of lack of presence of (at least a threshold quantity of) objects by, for example, reducing or stopping communication transmissions, and/or reducing transmit power, and/or applying beam forming to focus transmission and/or reception (e.g., to the road and not to the sides of the UE 500 and/or toward a base station).

Group Mode Operation

(69) The processor 510 may be configured to affect communication resources based on the UE 500 being part of a group of UEs, e.g., a fleet of associated vehicles, a dense set of vehicles (e.g., a traffic jam or traffic congestion), etc. For example, the UEs 620, 621, 623 may be part of a group 670 of associated UEs (e.g., owned by a single entity) and/or that has a density of at least a threshold density (e.g., a threshold quantity of vehicles per distance or area such as three vehicles per 30 m, or a threshold quantity of vehicles within a threshold range of the UE (e.g., five other vehicles each within 10 m of the UE 500)). The processor 510 may require that the group have a threshold quantity of vehicles (e.g., three vehicles) to operate in a group mode. The processor 510 may be configured to reduce transmission of redundant information, e.g., transmitted by one or more other UEs in the group of UEs. For example, the processor 510 may not transmit information that was or will be transmitted by another UE in the group 670. The processor 510 may be configured to set a power value (e.g., reduce power if the set power value is higher than a presently-used power) and/or otherwise allocate one or more other communication resources for communicating with one or more other UEs in the group 670, which may conserve power, reduce interference, and/or reduce network loading. Also or alternatively, the processor 510 may relay received information to other UEs in the group 670, which may help reduce processing power for receiving information. Also or alternatively, the processor 510 may be configured to cause the interface 520 not to communicate with base stations, e.g., the base station 610, which may also conserve power, reduce interference, and/or reduce network loading. Group mode operation may be particularly useful with respect to autonomous driving vehicles.

Interior Region Conditions

(70) The processor 510 may be configured to affect communication resources based on one or more conditions inside a region, e.g., vehicle interior conditions inside a passenger compartment of a vehicle UE. For example, if the UE 500 is a vehicle, the processor 510 may determine whether one or more passengers in the passenger compartment show signs of needing assistance. For example, the processor 510 may determine that motion of the driver (e.g., repeated head bobbing) indicates that the driver is falling asleep. The processor 510 may respond to determining that the driver is falling asleep, combined with the UE 500 being in motion, to affect communication, e.g., by providing or increasing transmission power for communication (especially for an emergency communication) to increase coverage area, initiating an emergency call, causing the vehicle to slow, and/or sounding an alarm and/or providing another alert to help prevent the driver from falling asleep. Such action(s) may save lives both of a user of the UE 500 and of other persons, e.g., other passengers of the UE 500 and/or persons that may otherwise be hit by the UE 500. The processor 510 may be configured to use one or more pieces of sensor information in addition to or instead of motion to determine that a passenger, especially the driver, is falling asleep. For example, the processor 510 may analyze audio, e.g., for snoring or other sleep-related sounds, to determine whether a passenger is asleep, and may be able to determine a source of the sounds to determine whether a sleeping passenger is the driver.

Emergency Conditions

(71) The processor 510 may be configured to affect communication resources based on one or more emergency conditions being detected. For example, the processor 510 may detect sudden acceleration from the acceleration field 714, which may be indicative of the UE 500 hitting or being hit by an object. As another example, the processor 510 may analyze the audio field 712 for verbal indications of an emergency, e.g., screams, yells, verbal commands to place an emergency

call, etc. As another example, the processor **510** may analyze one or more UE status sensors for indications of UE integrity, e.g., collapsing of one or more vehicle body parts of a vehicle UE, such as a door or a bumper, to determine that a crash has occurred. As another example, the processor **510** may analyze accelerometer and/or gyroscope information to determine that a vehicle UE is rolling, and thus indicative of a crash. The processor **510** may be configured to respond to determination of an emergency condition by, for example, providing or increasing transmission power for communication (especially for an emergency communication), initiating an emergency call, causing a speaker of the vehicle to play an inquiry for information (e.g., “Do you need emergency assistance?”) from the passenger(s), and/or sounding an alarm. Such action(s) may save lives, e.g., by getting medical aid to passengers faster than without such action(s).

Operation

(72) Referring to FIG. **8**, with further reference to FIGS. **1-7**, a method **800** of managing communication resources includes the stages shown. The method **800** is, however, an example only and not limiting. The method **800** may be altered, e.g., by having stages added, removed, rearranged, combined, performed concurrently, and/or having single stages split into multiple stages.

(73) At stage **810**, the method **800** includes obtaining one or more sensor indications by sensing, at a UE, at least one of: one or more environmental conditions; or one or more UE conditions. The UE **500** may, for example, be a vehicle or otherwise associated with a vehicle, e.g., disposed on or in a vehicle, or integrated with a vehicle, etc., or may be independent of a vehicle. The environmental condition(s) may be associated with the UE by, for example, being in or near the UE (e.g., within a distance such that the environment may be considered regarding communication to and/or from the UE). The processor **510** may monitor the sensor(s) **540** for one or more conditions outside and/or inside the UE **500** and distinct from the UE **500** (e.g., distinct from a vehicle). For example, the processor **510** may monitor one or more camera images (e.g., still and/or video images of one or more regions visible from the UE **500**), audio, temperature, air flow, ranging information (e.g., from radar, LIDAR, etc.), motion, etc. Also or alternatively, the processor **510** may monitor the sensor(s) **540** for one or more conditions of the UE **500** such as location, orientation, movement, UE status (e.g., vehicle status such as gear, brake on/off, accelerator position, steering wheel position, turn indicator(s) on/off, etc.). The processor **510**, the memory **530**, and one or more of the sensor(s) **540** may comprise means for obtaining one or more sensor indications.

(74) At stage **820**, the method **800** includes affecting communication between the UE and an external entity, disposed externally to the UE, based on the one or more sensor indications by affecting at least one of: a communication directionality of the UE; or a transmit power of the UE; or a transmit frequency of the UE; or a processing effort of the UE for processing communication signals. For example, the processor **510** may affect a transmit direction of communication signals using beam management, e.g., selecting one or more antennas to use for signal transmission (e.g., controlling which antenna(s) receive power or which antenna(s) receive signals to be transmitted), controlling beam steering by one or more antennas, etc. As another example, the processor **510** may affect received signal processing, e.g., by controlling which antennas provide received signals to the processor **510**, which received signals are processed by the processor **510**, by controlling beam steering to affect quality of received signals, etc. Also or alternatively, the processor **510** may determine and control how much power to use to process signals to be transmitted and/or received signals (e.g., bandwidth allocated, processing time allocated). The processor **510**, the interface **520**, the memory **530**, and one or more of the sensor(s) **540** may comprise means for affecting communication between the UE and the external entity.

(75) Implementations of the method **800** may include one or more of the following features. In an example implementation, the method **800** may include determining that an object is present at an object direction relative to the UE, where affecting communication between the UE and the

external entity comprises at least one of: reducing a communication transmit directionality of the UE in the object direction; or reducing a communication receive directionality of the UE in the object direction. For example, to reduce communication transmit directionality, the processor **510** may reduce frequency and/or reduce power for transmissions in the direction of the object. As other examples, the processor **510** may perform beam management, e.g., by affecting beam forming by at least one transceiver of the UE **500** and/or affecting beam selection by the at least one transceiver. The UE **500** may, e.g., focus one or more beams away from the object and/or select one or more beams directed toward the object for non-transmission, or change the direction of one or more beams to point away from the object, etc., to reduce the transmission directionality toward the object. To reduce receive directionality, the processor **510** may, for example, reduce processing power and/or time dedicated to reception of signals from the direction of the object. As other examples, the processor **510** may reduce or eliminate processing of from the direction of the object, e.g., by sending only signals not from the object direction to the processor **510** for processing. The processor **510**, the memory **530**, and one or more of the sensor(s) **540** may comprise means for determining that an object is present at the object direction, and the processor, the interface **520**, and the memory **530** may comprise means for affecting the communication directionality.

(76) Also or alternatively, implementations of the method **800** may include one or more of the following features. In an example implementation, affecting the communication may include responding to acceleration of the UE in a first direction by increasing communication transmission in the first direction and/or increasing communication reception in the first direction and/or reducing communication transmission in a second direction that is opposite the first direction and/or reducing communication reception in the second direction. For example, the processor **510** may increase transmit power, frequency, and/or quantity of communication in or near a direction of travel and/or may increase processing power and/or processing time for received signals, and/or directionality for receiving signals in or near the direction or travel. Also or alternatively, the processor **510** may reduce one or more of these features in or near a direction opposite that of the direction of travel. In another example implementation, affecting communication between the UE and the external entity may include reducing communication transmission in response to determination of presence of an emergency vehicle by the UE. For example, the processor **510** may sense the presence of an emergency vehicle (e.g., by analyzing information from one or more of the sensor(s) **540**) and/or may be informed of the presence of the emergency vehicle (e.g., by receiving an indication of the emergency vehicle, e.g., from a base station or from the emergency vehicle itself)). For example, the processor **510** may analyze one or more images captured by a camera of the sensor(s) **540** and/or one or more indications of sound output by a microphone of the sensor(s) **540** to determine the presence of the emergency vehicle (e.g., by identifying an emergency vehicle shape and/or sound (e.g., siren)). The processor **510** may reduce communication in response to determination of the presence of the emergency vehicle, e.g., to reduce interference with the emergency vehicle communication. The processor **510**, the memory **530**, and possibly one or more of the sensor(s) **540** and/or the interface **520** may comprise means for determining presence of an emergency vehicle and the processor, the memory **530**, and possibly the interface **520** may comprise means for reducing communication transmission.

(77) Also or alternatively, implementations of the method **800** may include one or more of the following features. In an example implementation, affecting communication between the UE and the external entity may include affecting communication transmission by the UE based on UE status (e.g., vehicle status) indicated by the one or more sensor indications and/or increasing communication transmission by the UE based on passenger status indicated by the one or more sensor indications and/or reducing communication transmission by the UE in response to determining that the UE is a member of a group of associated UEs and/or reducing communication transmission by the UE based on an environment proximate to the UE. For example, regarding vehicle status, the processor **510** may use a gear selection, a brake status, an accelerator status,

whether a turn signal is active, whether emergency/hazard flashers are active, whether a stopped vehicle is in park or drive, status of vehicle condition sensors (e.g., airbag(s) deployed, bumper moved, car panel(s) and/or frame damaged), etc. to determine whether and how to affect communication appropriately, e.g., by increasing transmit communication. As another example, the processor **510** may increase communication based on passenger status (e.g., a driver being asleep or otherwise impaired), e.g., to help with collision avoidance, notify an emergency service, etc. As another example, the processor **510** may determine to reduce communication transmission in response to determining that the UE **500** is part of a group of UEs, e.g., a group of vehicles with similar characteristics (e.g., similar status (e.g., location, speed, direction)), and at least one of the other UEs is providing communication transmission similar to (e.g., identical to) what the UE **500** would provide (e.g., such that the communication from the UE **500** may be redundant). As another example, the processor **510** may determine to reduce communication transmission based on an environment proximate to the UE (e.g., within sensing range of one or more environmental sensors of the UE **500** and/or within a threshold distance of the UE **500**). For example, the UE **500** may determine whether the UE is in heavy traffic (e.g., in a region with a vehicle density above a threshold) or in an area of high object density (e.g., a density of communication-affecting objects being above a threshold density) or in an area of low object density. The UE **500** may determine such information from one or more sensor measurements and/or one or more received communications.

(78) Also or alternatively, implementations of the method **800** may include one or more of the following features. In an example implementation, the method **800** may include allocating one or more communication resources of the UE based on one or more changes in one or more of the sensor indications. For example, the processor **510** may analyze multiple sensor indications, e.g., multiple sensor value sets, to determine a change in value output by a sensor, or changes in outputs of multiple sensors. The processor **510** may use the change(s) to allocate one or more resources, e.g., to beam steer away from a direction that becomes blocked, to increase transmit power in a direction of increased movement, or to reduce or eliminate transmit power in a direction away from increased movement. These are examples only, and numerous sensor value changes may be used alone or in various combinations to determine various resources allocations. The processor **510** and the memory, and possibly one or more of the sensor(s) **540** and/or the interface **520**, may comprise means for allocating one or more communication resources of the UE.

IMPLEMENTATION EXAMPLES

(79) Non-exhaustive implementation examples are provided in the following numbered clauses.

(80) 1. A user equipment (UE) comprising: at least one transceiver configured to send and receive wireless signals, the at least one transceiver comprising one or more antennas; a memory; one or more sensors configured to provide one or more sensor indications, the one or more sensors comprising at least one of: one or more first sensors configured to sense one or more environmental conditions; or one or more second sensors configured to sense one or more UE conditions; and at least one processor communicatively coupled to the at least one transceiver, the memory, and the one or more sensors and configured to control operation, for communication with an entity external to the UE, of at least one of the at least one processor or the at least one transceiver based on the one or more sensor indications provided by the one or more sensors to affect at least one of: a communication directionality of the UE; or a transmit power of the at least one transceiver; or a transmit frequency of the at least one transceiver; or a processing effort of the at least one processor for processing communication signals.

(81) 2. The UE of clause 1, wherein the at least one processor is configured to determine an object direction of an object relative to the UE and to affect the communication directionality of the UE, and wherein to affect the communication directionality of the UE the at least one processor is configured to at least one of: reduce a communication transmit directionality of the UE in the object direction; or reduce a communication receive directionality of the UE in the object direction.

(82) 3. The UE of clause 2, wherein to affect the communication directionality of the UE the at least one processor is configured to at least one of: affect beam forming by the at least one transceiver; or affect beam selection by the at least one transceiver.

(83) 4. The UE of clause 1, wherein the at least one processor is configured to affect the communication directionality of the UE, and wherein to affect the communication directionality of the UE the at least one processor is configured to at least one of: respond to acceleration of the UE in a first direction by increasing communication transmission in the first direction; or respond to acceleration of the UE in the first direction by increasing communication reception in the first direction; or respond to acceleration of the UE in the first direction by reducing communication transmission in a second direction that is opposite the first direction; or respond to acceleration of the UE in the first direction by reducing communication reception in the second direction.

(84) 5. The UE of clause 1, wherein the at least one processor is configured to reduce communication transmission in response to determination of presence of an emergency vehicle by the UE.

(85) 6. The UE of clause 5, wherein the one or more first sensors include at least one of a camera or a microphone, and wherein the at least one processor is configured to at least one of: detect the presence of the emergency vehicle by analyzing one or more images captured by the camera; or detect the presence of the emergency vehicle by analyzing output of the microphone.

(86) 7. The UE of clause 1, wherein the at least one processor is configured to at least one of: affect communication transmission by the UE based on UE status as indicated by the one or more second sensors; or increase communication transmission by the UE based on status of a vehicle passenger as indicated by the one or more second sensors; or reduce communication transmission in response to the at least one processor determining that the UE is a member of a group of associated UEs; or reduce communication transmission by the UE based on an environment proximate to the UE.

(87) 8. The UE of clause 1, wherein the at least one processor is configured to allocate one or more communication resources of the UE based on one or more changes in one or more of the one or more sensor indications.

(88) 9. The UE of clause 1, wherein the UE comprises a vehicle.

(89) 10. A user equipment (UE) comprising: sensing means for obtaining one or more sensor indications by sensing at least one of: one or more environmental conditions; or one or more UE conditions; and communication means for affecting communication between the UE and an external entity based on the one or more sensor indications by affecting at least one of: a communication directionality of the UE; or a transmit power of the UE; or a transmit frequency of the UE; or a processing effort of the UE for processing communication signals.

(90) 11. The UE of clause 10, further comprising means for determining that an object is present at an object direction relative to the UE, wherein the communication means include at least one of: means for reducing a communication transmit directionality of the UE in the object direction; or means for reducing a communication receive directionality of the UE in the object direction.

(91) 12. The UE of clause 11, wherein the communication means include at least one of: means for affecting beam forming by at least one transceiver of the UE; or means for affecting beam selection by the at least one transceiver.

(92) 13. The UE of clause 10, wherein the communication means include responding means for responding to acceleration of the UE in a first direction, the responding means including at least one of: means for increasing communication transmission in the first direction; or means for increasing communication reception in the first direction; or means for reducing communication transmission in a second direction that is opposite the first direction; or means for reducing communication reception in the second direction.

(93) 14. The UE of clause 10, wherein the communication means are for affecting communication between the UE and the external entity by reducing communication transmission in response to determination of presence of an emergency vehicle by the UE.

(94) 15. The UE of clause 14, further comprising means for determining the presence of the emergency vehicle by at least one of: analyzing one or more images captured by a camera of the UE; or analyzing output of a microphone, of the UE, indicative of sound received by the UE.

(95) 16. The UE of clause 10, wherein the communication means include at least one of: means for affecting communication transmission by the UE based on UE status determined by the sensing means; or means for increasing communication transmission by the UE based on status of a vehicle passenger determined by the sensing means; or means for reducing communication transmission by the UE in response to determining that the UE is a member of a group of associated UEs; or means for reducing communication transmission by the UE based on an environment proximate to the UE.

(96) 17. The UE of clause 10, wherein the communication means are for allocating one or more communication resources of the UE based on one or more changes in one or more of the one or more sensor indications.

(97) 18. The UE of clause 10, wherein the UE comprises a vehicle.

(98) 19. A method of managing communication resources of a user equipment (UE), the method comprising: obtaining one or more sensor indications by sensing, at the UE, at least one of: one or more environmental conditions; or one or more UE conditions; and affecting communication between the UE and an external entity, disposed externally to the UE, based on the one or more sensor indications by affecting at least one of: a communication directionality of the UE; or a transmit power of the UE; or a transmit frequency of the UE; or a processing effort of the UE for processing communication signals.

(99) 20. The method of clause 19, further comprising determining that an object is present at an object direction relative to the UE, wherein affecting communication between the UE and the external entity comprises at least one of: reducing a communication transmit directionality of the UE in the object direction; or reducing a communication receive directionality of the UE in the object direction.

(100) 21. The method of clause 20, wherein affecting communication between the UE and the external entity comprises at least one of: affecting beam forming by at least one transceiver of the UE; or affecting beam selection by the at least one transceiver.

(101) 22. The method of clause 19, wherein affecting communication between the UE and the external entity comprises responding to acceleration of the UE in a first direction by at least one of: increasing communication transmission in the first direction; or increasing communication reception in the first direction; or reducing communication transmission in a second direction that is opposite the first direction; or reducing communication reception in the second direction.

(102) 23. The method of clause 19, wherein affecting communication between the UE and the external entity comprises reducing communication transmission in response to determination of presence of an emergency vehicle by the UE.

(103) 24. The method of clause 19, wherein affecting communication between the UE and the external entity comprises at least one of: affecting communication transmission by the UE based on UE status indicated by the one or more sensor indications; or increasing communication transmission by the UE based on passenger status indicated by the one or more sensor indications; or reducing communication transmission by the UE in response to determining that the UE is a member of a group of associated UEs; or reducing communication transmission by the UE based on an environment proximate to the UE.

(104) 25. A non-transitory, processor-readable storage medium comprising processor-readable instructions configured to cause one or more processors of a user equipment (UE) to: obtain one or more sensor indications of at least one of: one or more environmental conditions; or one or more UE conditions; and affect communication between the UE and an external entity, disposed externally to the UE, based on the one or more sensor indications by affecting at least one of: a communication directionality of the UE; or a transmit power of the UE; or a transmit frequency of the UE; or a processing effort of the UE for processing communication signals.

(105) 26. The storage medium of clause 25, further comprising instructions configured to cause the one or more processors to determine that an object is present at an object direction relative to the UE, wherein to affect communication between the UE and the external entity the instructions are configured to cause the one or more processors to at least one of: reduce a communication transmit directionality of the UE in the object direction; or reduce a communication receive directionality of the UE in the object direction.

(106) 27. The storage medium of clause 25, wherein to affect communication between the UE and the external entity the instructions are configured to cause the one or more processors to at least one of: affect beam forming by at least one transceiver of the UE; or affect beam selection by the at least one transceiver.

(107) 28. The storage medium of clause 25, wherein to affect communication between the UE and the external entity the instructions are configured to cause the one or more processors to at least one of: respond to acceleration of the UE in a first direction by increasing communication transmission in the first direction; or respond to acceleration of the UE in the first direction by increasing communication reception in the first direction; or respond to acceleration of the UE in the first direction by reducing communication transmission in a second direction that is opposite the first direction; or respond to acceleration of the UE in the first direction by reducing communication reception in the second direction.

(108) 29. The storage medium of clause 25, wherein the instructions configured to cause the one or more processors to affect communication between the UE and the external entity comprise instructions configured to cause the one or more processors to reduce communication transmission in response to presence of an emergency vehicle.

(109) 30. The storage medium of clause 25, wherein to affect communication between the UE and the external entity the instructions are configured to cause the one or more processors to at least one of: affect communication transmission by the UE based on UE status; or increase communication transmission by the UE based on status of a vehicle passenger; or reduce communication transmission by the UE in response to determining that the UE is a member of a group of associated UEs; or reduce communication transmission by the UE based on an environment proximate to the UE.

OTHER CONSIDERATIONS

(110) Other examples and implementations are within the scope of the disclosure and appended claims. For example, due to the nature of software and computers, functions described above can be implemented using software executed by a processor, hardware, firmware, hardwiring, or a combination of any of these. Features implementing functions may also be physically located at various positions, including being distributed such that portions of functions are implemented at different physical locations.

(111) As used herein, the singular forms “a,” “an,” and “the” include the plural forms as well, unless the context clearly indicates otherwise. The terms “comprises,” “comprising,” “includes,” and/or “including,” as used herein, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

(112) As used herein, unless otherwise stated, a statement that a function or operation is “based on” an item or condition means that the function or operation is based on the stated item or condition and may be based on one or more items and/or conditions in addition to the stated item or condition.

(113) Also, as used herein, “or” as used in a list of items (possibly prefaced by “at least one of” or prefaced by “one or more of”) indicates a disjunctive list such that, for example, a list of “at least one of A, B, or C,” or a list of “one or more of A, B, or C” or a list of “A or B or C” means A, or B, or C, or AB (A and B), or AC (A and C), or BC (B and C), or ABC (i.e., A and B and C), or combinations with more than one feature (e.g., AA, AAB, ABBC, etc.). Thus, a recitation that an

item, e.g., a processor, is configured to perform a function regarding at least one of A or B, or a recitation that an item is configured to perform a function A or a function B, means that the item may be configured to perform the function regarding A, or may be configured to perform the function regarding B, or may be configured to perform the function regarding A and B. For example, a phrase of “a processor configured to measure at least one of A or B” or “a processor configured to measure A or measure B” means that the processor may be configured to measure A (and may or may not be configured to measure B), or may be configured to measure B (and may or may not be configured to measure A), or may be configured to measure A and measure B (and may be configured to select which, or both, of A and B to measure). Similarly, a recitation of a means for measuring at least one of A or B includes means for measuring A (which may or may not be able to measure B), or means for measuring B (and may or may not be configured to measure A), or means for measuring A and B (which may be able to select which, or both, of A and B to measure). As another example, a recitation that an item, e.g., a processor, is configured to at least one of perform function X or perform function Y means that the item may be configured to perform the function X, or may be configured to perform the function Y, or may be configured to perform the function X and to perform the function Y. For example, a phrase of “a processor configured to at least one of measure X or measure Y” means that the processor may be configured to measure X (and may or may not be configured to measure Y), or may be configured to measure Y (and may or may not be configured to measure X), or may be configured to measure X and to measure Y (and may be configured to select which, or both, of X and Y to measure).

(114) Substantial variations may be made in accordance with specific requirements. For example, customized hardware might also be used, and/or particular elements might be implemented in hardware, software (including portable software, such as applets, etc.) executed by a processor, or both. Further, connection to other computing devices such as network input/output devices may be employed. Components, functional or otherwise, shown in the figures and/or discussed herein as being connected or communicating with each other are communicatively coupled unless otherwise noted. That is, they may be directly or indirectly connected to enable communication between them.

(115) The systems and devices discussed above are examples. Various configurations may omit, substitute, or add various procedures or components as appropriate. For instance, features described with respect to certain configurations may be combined in various other configurations. Different aspects and elements of the configurations may be combined in a similar manner. Also, technology evolves and, thus, many of the elements are examples and do not limit the scope of the disclosure or claims.

(116) A wireless communication system is one in which communications are conveyed wirelessly, i.e., by electromagnetic and/or acoustic waves propagating through atmospheric space rather than through a wire or other physical connection. A wireless communication network may not have all communications transmitted wirelessly, but is configured to have at least some communications transmitted wirelessly. Further, the term “wireless communication device,” or similar term, does not require that the functionality of the device is exclusively, or even primarily, for communication, or that the device be a mobile device, but indicates that the device includes wireless communication capability (one-way or two-way), e.g., includes at least one radio (each radio being part of a transmitter, receiver, or transceiver) for wireless communication.

(117) Specific details are given in the description to provide a thorough understanding of example configurations (including implementations). However, configurations may be practiced without these specific details. For example, well-known circuits, processes, algorithms, structures, and techniques have been shown without unnecessary detail in order to avoid obscuring the configurations. This description provides example configurations only, and does not limit the scope, applicability, or configurations of the claims. Rather, the preceding description of the configurations provides a description for implementing described techniques. Various changes may

be made in the function and arrangement of elements.

(118) The terms “processor-readable medium,” “machine-readable medium,” and “computer-readable medium,” as used herein, refer to any medium that participates in providing data that causes a machine to operate in a specific fashion. Using a computing platform, various processor-readable media might be involved in providing instructions/code to processor(s) for execution and/or might be used to store and/or carry such instructions/code (e.g., as signals). In many implementations, a processor-readable medium is a physical and/or tangible storage medium. Such a medium may take many forms, including but not limited to, non-volatile media and volatile media. Non-volatile media include, for example, optical and/or magnetic disks. Volatile media include, without limitation, dynamic memory.

(119) Having described several example configurations, various modifications, alternative constructions, and equivalents may be used. For example, the above elements may be components of a larger system, wherein other rules may take precedence over or otherwise modify the application of the disclosure. Also, a number of operations may be undertaken before, during, or after the above elements are considered. Accordingly, the above description does not bound the scope of the claims.

(120) A statement that a value exceeds (or is more than or above) a first threshold value is equivalent to a statement that the value meets or exceeds a second threshold value that is slightly greater than the first threshold value, e.g., the second threshold value being one value higher than the first threshold value in the resolution of a computing system. A statement that a value is less than (or is within or below) a first threshold value is equivalent to a statement that the value is less than or equal to a second threshold value that is slightly lower than the first threshold value, e.g., the second threshold value being one value lower than the first threshold value in the resolution of a computing system.

Claims

1. A user equipment (UE) comprising: at least one transceiver configured to send and receive wireless signals, the at least one transceiver comprising one or more antennas; a memory; one or more sensors configured to provide one or more sensor indications, the one or more sensors comprising at least one of: one or more first sensors configured to sense one or more environmental conditions; or one or more second sensors configured to sense one or more UE conditions; and at least one processor communicatively coupled to the at least one transceiver, the memory, and the one or more sensors and configured to control operation, for communication with an entity external to the UE, of at least one of the at least one processor or the at least one transceiver based on the one or more sensor indications provided by the one or more sensors to affect at least one of: a communication directionality of the UE; or a transmit power of the at least one transceiver; or a transmit frequency of the at least one transceiver; or a processing effort of the at least one processor for processing communication signals, and wherein the at least one processor is configured to at least one of: affect communication transmission by the UE based on UE status as indicated by the one or more second sensors; or increase communication transmission by the UE based on status of a vehicle passenger as indicated by the one or more second sensors; or reduce communication transmission in response to the at least one processor determining that the UE is a member of a group of associated UEs; or reduce communication transmission by the UE based on an environment proximate to the UE.

2. The UE of claim 1, wherein the at least one processor is configured to determine an object direction of an object relative to the UE and to affect the communication directionality of the UE, and wherein to affect the communication directionality of the UE the at least one processor is configured to at least one of: reduce a communication transmit directionality of the UE in the object direction; or reduce a communication receive directionality of the UE in the object direction.

3. The UE of claim 2, wherein to affect the communication directionality of the UE the at least one processor is configured to at least one of: affect beam forming by the at least one transceiver; or affect beam selection by the at least one transceiver.
4. The UE of claim 1, wherein the at least one processor is configured to affect the communication directionality of the UE, and wherein to affect the communication directionality of the UE the at least one processor is configured to at least one of: respond to acceleration of the UE in a first direction by increasing communication transmission in the first direction; or respond to acceleration of the UE in the first direction by increasing communication reception in the first direction; or respond to acceleration of the UE in the first direction by reducing communication transmission in a second direction that is opposite the first direction; or respond to acceleration of the UE in the first direction by reducing communication reception in the second direction.
5. The UE of claim 1, wherein the at least one processor is configured to reduce communication transmission in response to determination of presence of an emergency vehicle by the UE.
6. The UE of claim 5, wherein the one or more first sensors include at least one of a camera or a microphone, and wherein the at least one processor is configured to at least one of: detect the presence of the emergency vehicle by analyzing one or more images captured by the camera; or detect the presence of the emergency vehicle by analyzing output of the microphone.
7. The UE of claim 1, wherein the at least one processor is configured to allocate one or more communication resources of the UE based on one or more changes in one or more of the one or more sensor indications.
8. The UE of claim 1, wherein the UE comprises a vehicle.
9. A user equipment (UE) comprising: sensing means for obtaining one or more sensor indications by sensing at least one of: one or more environmental conditions; or one or more UE conditions; and communication means for affecting communication between the UE and an external entity based on the one or more sensor indications by affecting at least one of: a communication directionality of the UE; or a transmit power of the UE; or a transmit frequency of the UE; or a processing effort of the UE for processing communication signals, and wherein the communication means include at least one of: means for affecting communication transmission by the UE based on UE status determined by the sensing means; or means for increasing communication transmission by the UE based on status of a vehicle passenger determined by the sensing means; or means for reducing communication transmission by the UE in response to determining that the UE is a member of a group of associated UEs; or means for reducing communication transmission by the UE based on an environment proximate to the UE.
10. The UE of claim 9, further comprising means for determining that an object is present at an object direction relative to the UE, wherein the communication means include at least one of: means for reducing a communication transmit directionality of the UE in the object direction; or means for reducing a communication receive directionality of the UE in the object direction.
11. The UE of claim 10, wherein the communication means include at least one of: means for affecting beam forming by at least one transceiver of the UE; or means for affecting beam selection by the at least one transceiver.
12. The UE of claim 9, wherein the communication means include responding means for responding to acceleration of the UE in a first direction, the responding means including at least one of: means for increasing communication transmission in the first direction; or means for increasing communication reception in the first direction; or means for reducing communication transmission in a second direction that is opposite the first direction; or means for reducing communication reception in the second direction.
13. The UE of claim 9, wherein the communication means are for affecting communication between the UE and the external entity by reducing communication transmission in response to determination of presence of an emergency vehicle by the UE.
14. The UE of claim 13, further comprising means for determining the presence of the emergency

vehicle by at least one of: analyzing one or more images captured by a camera of the UE; or analyzing output of a microphone, of the UE, indicative of sound received by the UE.

15. The UE of claim 9, wherein the communication means are for allocating one or more communication resources of the UE based on one or more changes in one or more of the one or more sensor indications.

16. The UE of claim 9, wherein the UE comprises a vehicle.

17. A method of managing communication resources of a user equipment (UE), the method comprising: obtaining one or more sensor indications by sensing, at the UE, at least one of: one or more environmental conditions; or one or more UE conditions; and affecting communication between the UE and an external entity, disposed externally to the UE, based on the one or more sensor indications by affecting at least one of: a communication directionality of the UE; or a transmit power of the UE; or a transmit frequency of the UE; or a processing effort of the UE for processing communication signals, and wherein affecting communication between the UE and the external entity comprises at least one of: affecting communication transmission by the UE based on UE status indicated by the one or more sensor indications; or increasing communication transmission by the UE based on passenger status indicated by the one or more sensor indications; or reducing communication transmission by the UE in response to determining that the UE is a member of a group of associated UEs; or reducing communication transmission by the UE based on an environment proximate to the UE.

18. The method of claim 17, further comprising determining that an object is present at an object direction relative to the UE, wherein affecting communication between the UE and the external entity comprises at least one of: reducing a communication transmit directionality of the UE in the object direction; or reducing a communication receive directionality of the UE in the object direction.

19. The method of claim 18, wherein affecting communication between the UE and the external entity comprises at least one of: affecting beam forming by at least one transceiver of the UE; or affecting beam selection by the at least one transceiver.

20. The method of claim 17, wherein affecting communication between the UE and the external entity comprises responding to acceleration of the UE in a first direction by at least one of: increasing communication transmission in the first direction; or increasing communication reception in the first direction; or reducing communication transmission in a second direction that is opposite the first direction; or reducing communication reception in the second direction.

21. The method of claim 17, wherein affecting communication between the UE and the external entity comprises reducing communication transmission in response to determination of presence of an emergency vehicle by the UE.

22. A non-transitory, processor-readable storage medium comprising processor-readable instructions configured to cause one or more processors of a user equipment (UE) to: obtain one or more sensor indications of at least one of: one or more environmental conditions; or one or more UE conditions; and affect communication between the UE and an external entity, disposed externally to the UE, based on the one or more sensor indications by affecting at least one of: a communication directionality of the UE; or a transmit power of the UE; or a transmit frequency of the UE; or a processing effort of the UE for processing communication signals, and wherein to affect communication between the UE and the external entity the instructions are configured to cause the one or more processors to at least one of: affect communication transmission by the UE based on UE status; or increase communication transmission by the UE based on status of a vehicle passenger; or reduce communication transmission by the UE in response to determining that the UE is a member of a group of associated UEs; or reduce communication transmission by the UE based on an environment proximate to the UE.

23. The storage medium of claim 22, further comprising instructions configured to cause the one or more processors to determine that an object is present at an object direction relative to the UE,

wherein to affect communication between the UE and the external entity the instructions are configured to cause the one or more processors to at least one of: reduce a communication transmit directionality of the UE in the object direction; or reduce a communication receive directionality of the UE in the object direction.

24. The storage medium of claim 22, wherein to affect communication between the UE and the external entity the instructions are configured to cause the one or more processors to at least one of: affect beam forming by at least one transceiver of the UE; or affect beam selection by the at least one transceiver.

25. The storage medium of claim 22, wherein to affect communication between the UE and the external entity the instructions are configured to cause the one or more processors to at least one of: respond to acceleration of the UE in a first direction by increasing communication transmission in the first direction; or respond to acceleration of the UE in the first direction by increasing communication reception in the first direction; or respond to acceleration of the UE in the first direction by reducing communication transmission in a second direction that is opposite the first direction; or respond to acceleration of the UE in the first direction by reducing communication reception in the second direction.

26. The storage medium of claim 22, wherein the instructions configured to cause the one or more processors to affect communication between the UE and the external entity comprise instructions configured to cause the one or more processors to reduce communication transmission in response to presence of an emergency vehicle.
