

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250260217

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Ash; Jon et al.

---

### Wire Clamp

---

#### Abstract

A wire clamp may include a bottom piece having: a first base portion defining a first aperture, an at least partially elliptical barrier extending from the first base portion about the first aperture, and a plurality of legs extending from sides of the first base portion; a top piece having: a second base portion, a protrusion extending from the second base portion, the protrusion defining a second aperture, and a plurality of legs extending from sides of the second base portion; and a fastener. The first aperture and the second aperture may be configured to align and receive the fastener therethrough. A first side of the partially elliptical barrier and a first portion of the plurality of legs may define a first wire channel, and a second side of the partially elliptical barrier and a second portion of the plurality of legs may define a second wire channel.

---

**Inventors:** Ash; Jon (Walnut Creek, CA), Hudson; John (Atlanta, GA), Pedlar; Roger (Phoenix, AZ), Ray; Taylor (Doraville, GA)

**Applicant:** EcoFasten Solar, LLC (Phoenix, AZ)

**Family ID:** 1000008561319

**Appl. No.:** 19/191572

**Filed:** April 28, 2025

#### Related U.S. Application Data

parent US continuation 18603488 20240313 parent-grant-document US 12300985 child US 19191572

parent US division 17948058 20220919 parent-grant-document US 11949217 child US 18603488

---

#### Publication Classification

**Int. Cl.:** H02G3/04 (20060101); F16B2/06 (20060101)

## Background/Summary

### BACKGROUND OF THE INVENTION

#### Field of the Invention

[0001] This disclosure relates generally to a wire clamp and, more particularly, to a wire clamp capable of being applied to a rail in a solar panel system to organize and arrange the wires running through the solar panel array.

#### Description of Related Art

[0002] Various wire conduits, clips and clamps have been developed to route and protect wires throughout industrial spaces. However these apparatuses tend to bunch and clamp wires together in such a way that affects their lifespan. They also fail to provide easy access to individuals trying to move the wires for one purpose or another. Thus, there exists a need to provide a mountable wire clamp that can organize wires in such a way that prolongs their lifespan and makes them easier to access or move when organized.

[0003] Common methods for managing wires include using zip ties that are commonly made of plastic and have a lifespan that is shorter than the service life of the wires and equipment they are used to support. This can lead to failure of the wire management causing sagging wires that can contact surfaces that can damage the wires and wire insulation such as sharp edges and high heat surfaces. Another common wire management device is wire clips that are typically made of stainless steel and while these do commonly have sufficient lifespan they have other limitations which make them less desirable. They often require the use of many clips which can be expensive and the clips can only manage the wires in a single direction most commonly parallel to the rail or member the clip is attached to. Wires are sometimes managed in such a way that the wire contacts the sharp edges of rails or other cut edges of various materials and structures. The limitations of current wire management solutions creates situations where installers are unable to maintain the minimum required bend radiuses for wires. Thus, there exists a need to provide an affordable, durable, simple and easy to install clamp that can manage single or multiple wires in unlimited direction relative to the structural members the wires are connected to.

### SUMMARY OF THE INVENTION

[0004] One non-limiting embodiment of the present disclosure may be a wire clamp including a bottom piece having: a first base portion defining a first aperture, an at least partially elliptical barrier extending from the first base portion about the first aperture, and a plurality of legs extending from sides of the first base portion; a top piece having: a second base portion, a protrusion extending from the second base portion, the protrusion defining a second aperture, and a plurality of flanges extending from sides of the second base portion; and a fastener. The first aperture and the second aperture may be configured to align and receive the fastener therethrough. A first side of the at least partially elliptical barrier and a first portion of the plurality of legs may define a first wire channel, and a second side of the at least partially elliptical barrier and a second portion of the plurality of legs may define a second wire channel.

[0005] The first wire channel and the second wire channel may be further defined by the second base portion. The protrusion may be at least partially received within the at least partially elliptical barrier. The protrusion may define a third aperture and a fourth aperture. The bottom piece may further include a first post and a second post extending from the first base portion. The first post and the second post may be configured to be received within the third aperture and the fourth

aperture.

[0006] The first post and the second post may be disposed symmetrically about the first aperture. The segments of the first base portion extending between the at least partially elliptical barrier and the plurality of legs may be ridged. The top piece may be at least partially arched about the bottom piece. The plurality of legs may be sloped in a direction away from the top piece and extend in a direction away from the first base portion. The flanges may include a first portion that is sloped downward in a direction extending away from the second base portion and a second portion that is sloped upward relative to the first portion. The plurality of flanges may correspond to and extend at least partially over the plurality of legs. The wire clamp may include four flanges and four legs, a pair of each corresponding to each corner of the wire clamp.

[0007] Another non-limiting embodiment of the present disclosure may be a wire routing system that may include: a rail; and a wire clamp having a bottom piece having: a first base portion defining a first aperture, an at least partially elliptical barrier extending from the first base portion, and a plurality of legs extending from sides of the first base portion; a top piece having: a second base portion and a protrusion extending from the second base portion, the protrusion defining a second aperture; and a self-tapping fastener configured to define a third aperture in the rail. The first aperture, the second aperture, and the third aperture may be configured to align and receive the fastener therethrough, thereby mounting the wire clamp to the rail. A first side of the at least partially elliptical barrier, a first portion of the plurality of legs, and at least a portion of the second base portion of the top piece may define a first wire channel, and a second side of the at least partially elliptical barrier, a second portion of the plurality of legs, and at least a portion of the second base portion of the top piece may define a second wire channel.

[0008] The protrusion may be at least partially received within the at least partially elliptical barrier. The protrusion may define a fourth aperture and a fifth aperture. The bottom piece may include a first post and a second post extending from the first base portion, and the first post and the second post may be configured to be received within the fourth aperture and the fifth aperture. The segments of the first base portion extending between the at least partially elliptical barrier and the plurality of legs may be ridged. The top piece may be at least partially arched about the bottom piece. The plurality of legs may be sloped in a direction away from the top piece and extend away from the first base portion.

[0009] Another non-limiting embodiment of the present disclosure may be a method of clamping wires, the method having the steps of: placing wires within a first wire channel of a bottom piece, the bottom piece having a first aperture, the first wire channel being defined by a first side of an at least partially elliptical barrier and a first plurality of legs, the at least partially elliptical barrier and the first plurality of legs extending from the bottom piece; placing within a second wire channel of a bottom piece the second wire channel being defined by a second side of the at least partially elliptical barrier and a second plurality of legs, the second plurality of legs extending from the bottom piece; aligning a second aperture defined by a top piece over the first aperture; and extending a fastener through the second aperture and the first aperture, thereby clamping the top piece to the bottom piece. The first aperture is located centrally within the at least partially elliptical barrier.

[0010] The top piece may include a protrusion configured to be received at least partially in the at least partially elliptical barrier of the bottom piece, the second aperture being defined in the protrusion. The method may have the additional step of inserting the fastener into a third aperture defined in the rail, thereby securing the top and bottom pieces to the rail.

[0011] In some embodiments or aspects, the present disclosure may be characterized by one or more of the following numbered clauses:

[0012] Clause 1. A wire clamp comprising: a bottom piece comprising: a first base portion defining a first aperture; an at least partially elliptical barrier extending from the first base portion about the first aperture; and a plurality of legs extending from sides of the first base portion; a top piece

comprising: a second base portion; a protrusion extending from the second base portion, the protrusion defining a second aperture; and a plurality of flanges extending from sides of the second base portion; and a fastener, wherein the first aperture and the second aperture are configured to align and receive the fastener therethrough, and wherein a first side of the at least partially elliptical barrier and a first portion of the plurality of legs define a first wire channel.

[0013] Clause 2A. The wire clamp of clause 1, wherein the second side of the at least partially elliptical barrier and a second portion of the plurality of legs may define a second wire channel.

[0014] Clause 2B. The wire clamp of clause 1 or 2A, wherein the first wire channel and the second wire channel are further defined by the second base portion.

[0015] Clause 3. The wire clamp of any of clauses 1-2B, wherein the protrusion is at least partially received within the at least partially elliptical barrier.

[0016] Clause 4. The wire clamp of any of clauses 1-3, wherein the protrusion defines a third aperture and a fourth aperture, wherein the bottom piece further comprises a first post and a second post extending from the first base portion, and wherein the first post and the second post are configured to be received within the third aperture and the fourth aperture.

[0017] Clause 5. The wire clamp of any of clauses 1-4, wherein the first post and the second post are disposed symmetrically about the first aperture.

[0018] Clause 6. The wire clamp of any of clauses 1-5, wherein the segments of the first base portion extending between the at least partially elliptical barrier and the plurality of legs are ridged.

[0019] Clause 7. The wire clamp of any of clauses 1-6, wherein the top piece is at least partially arched about the bottom piece.

[0020] Clause 8. The wire clamp of any of clauses 1-7, wherein the plurality of legs are sloped in a direction away from the top piece and extend in a direction away from the first base portion.

[0021] Clause 9. The wire clamp of any of clauses 1-8, wherein the flanges comprise a first portion that is sloped downward in a direction extending away from the second base portion and a second portion that is sloped upward relative to the first portion.

[0022] Clause 10. The wire clamp of any of clauses 1-9, wherein the plurality of flanges correspond to and extend at least partially over the plurality of legs.

[0023] Clause 11. The wire clamp of any of clauses 1-10, further comprising four flanges and four legs, a pair of each corresponding to each corner of the wire clamp.

[0024] Clause 12. A wire routing system comprising: a rail; and a wire clamp comprising: a bottom piece comprising: a first base portion defining a first aperture; an at least partially elliptical barrier extending from the first base portion about the first aperture; and a plurality of legs extending from sides of the first base portion; a top piece comprising: a second base portion; and a protrusion extending from the second base portion, the protrusion defining a second aperture; and a self-tapping fastener configured to define a third aperture in the rail, wherein the first aperture, the second aperture, and the third aperture are configured to align and receive the fastener therethrough, thereby mounting the wire clamp to the rail, and wherein a first side of the at least partially elliptical barrier, a first portion of the plurality of legs, and at least a portion of the second base portion define a first wire channel, and a second side of the at least partially elliptical barrier, a second portion of the plurality of legs, and at least a portion of the second base portion define a second wire channel.

[0025] Clause 13. The wire routing system of clause 12, wherein the protrusion is at least partially received within the at least partially elliptical barrier.

[0026] Clause 14. The wire routing system of clause 12 or 13, wherein the protrusion defines a fourth aperture and a fifth aperture, wherein the bottom piece further comprises a first post and a second post extending from the first base portion, and wherein the first post and the second post are configured to be received within the fourth aperture and the fifth aperture.

[0027] Clause 15. The wire routing system of any of clauses 12-14, wherein the segments of the first base portion extending between the at least partially elliptical barrier and the plurality of legs

are ridged.

[0028] Clause 16. The wire routing system of any of clauses 12-15, wherein the top piece is at least partially arched about the bottom piece.

[0029] Clause 17. The wire routing system of any of clauses 12-16, wherein the plurality of legs are sloped in a direction away from the top piece and extend away from the first base portion.

[0030] Clause 18. A method of clamping wires comprising the steps of: placing wires within a first wire channel of a bottom piece, the bottom piece comprising a first aperture, the first wire channel being defined by a first side of an at least partially elliptical barrier and a first plurality of legs, the at least partially elliptical barrier and the first plurality of legs extending from the bottom piece; placing wires within a second wire channel of a bottom piece, the second wire channel being defined by a second side of the at least partially elliptical barrier and a second plurality of legs, the second plurality of legs extending from the bottom piece; aligning a second aperture defined by a top piece over the first aperture; and extending a fastener through the second aperture and the first aperture, thereby clamping the top piece to the bottom piece, wherein the first aperture is located centrally within the at least partially elliptical barrier.

[0031] Clause 19. The method of clause 18, wherein the top piece comprises a protrusion configured to be received at least partially in the at least partially elliptical barrier of the bottom piece, the second aperture being defined in the protrusion.

[0032] Clause 20. The method of clause 18 or 19, further comprising the step of: inserting the fastener into a third aperture defined in the rail, thereby securing the top and bottom pieces to the rail

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0033] FIG. 1 is a perspective view of a wire clamp according to one non-limiting embodiment of the present disclosure;

[0034] FIG. 2 is an exploded view of the wire clamp of FIG. 1;

[0035] FIG. 3 is a perspective view of a bottom piece of the wire clamp of FIG. 1;

[0036] FIG. 4 is a perspective view of a top piece of the wire clamp of FIG. 1;

[0037] FIG. 5 is a side view of the wire clamp of FIG. 1;

[0038] FIG. 6 is another side view of the wire clamp of FIG. 1;

[0039] FIG. 7 is a top view of the wire clamp of FIG. 1;

[0040] FIG. 8A is a side view of a wire clamp showing the process of placing a wire therein according to one non-limiting embodiment of the present disclosure;

[0041] FIG. 8B is a side view of the wire clamp of FIG. 8A showing the process of placing a wire therein;

[0042] FIG. 8C is another side view of the wire clamp of FIG. 8A showing the process of placing a wire therein; and

[0043] FIG. 9 is a perspective view of the wire clamp of FIG. 1 mounted to a rail.

### DETAILED DESCRIPTION OF THE INVENTION

[0044] As used herein, the singular forms of “a”, “an”, and “the” include plural referents unless the context clearly dictates otherwise.

[0045] Spatial or directional terms, such as “left”, “right”, “inner”, “outer”, “above”, “below”, and the like, relate to the disclosure as shown in the drawing figures and are not to be considered as limiting as the disclosure can assume various alternative orientations.

[0046] For purposes of the description hereinafter, the terms “upper”, “lower”, “right”, “left”, “vertical”, “horizontal”, “top”, “bottom”, “lateral”, “longitudinal”, and derivatives thereof shall relate to the disclosure as it is oriented in the figures. However, it is to be understood that the

disclosure may assume alternative variations and step sequences, except where expressly specified to the contrary. It is also to be understood that the specific devices and processes illustrated in the attached drawings and described in the following specification are simply exemplary aspects of the disclosure. Hence, specific dimensions and other physical characteristics related to the aspects disclosed herein are not to be considered as limiting.

[0047] The terms “first”, “second”, and the like are not intended to refer to any particular order or chronology, but refer to different conditions, properties, or elements.

[0048] The term “at least” is synonymous with “greater than or equal to”.

[0049] The term “includes” is synonymous with “comprises”.

[0050] The present disclosure is directed, in general, to a wire clamp **10** designed to be mounted to a rail **R** (shown in FIG. **8**) and used to organize and arrange wires in various industrial environments, such as in a solar panel array. Certain aspects of the wire clamp **10** are shown in FIGS. **1-8**.

[0051] With reference to FIGS. **1** and **2**, the wire clamp **10** includes a bottom piece **12** and a top piece **14**. The bottom piece **12** and top piece **14** are joined together via a screw **16**. While a screw **16** is shown, other fastening means known to those having skill in the art may be used. Both the bottom piece **12** and the top piece **14** are generally rectangular and complementary in shape so that the pieces **12**, **14**, when connected via the screw **16**, define channels **32A**, **32B** (shown in FIGS. **2**, **3**, **5**, **6**, and **8**) for routing and clamping wires **W** (shown in FIGS. **5-8**) therethrough. It is understood that the bottom piece **12** and the top piece **14** may take other shapes, so long as they fit together to define a channel or channels for the wires **W**.

[0052] With reference to FIGS. **1-3**, the bottom piece **12** will now be described. The bottom piece **12** includes a first base **20**. The first base **20** is divided into a first side **20A** and a second side **20B**, which are separated by a barrier **22**. As shown, the barrier **22** is partially elliptical, having two sidewalls **22A**, **22B** curving about an aperture **24**. The sidewalls **22A**, **22B** define a shape that is similar to that of a football. Such a shape allows a user to maximize the bend radius of the wires that run through the clamp **10**. The first sidewall **22A** extends along and serves as a demarcation line of the first side **20A**. The second sidewall **22B** extends along and serves as a demarcation line of the second side **20B**. The sidewalls **22A**, **22B** are curved to prevent the wires **W** from being pinched together when the top piece **14** is connected to the bottom piece **12**. The curved sidewalls **22A**, **22B** also cause the wires **W** to curve when placed in the bottom piece **12**, which may allow for more efficient and organized routing of the wires **W** in the system to which the wire clamp **10** is applied. The curvature also prevents pinching or unnecessary bunching of the wires **W**, which can lead to entanglements. While shown as an elliptical or football-like shape, the sidewalls **22A**, **22B** may take different rounded shapes, such as an ovular or circular shape, in order to properly orient the wires **W** within the wire clamp **10**.

[0053] Located centrally relative to the two sidewalls **22A**, **22B** of the barrier **22** is the aperture **24** that receives the screw **16** therein. The aperture **24** may have threads **25** that correspond to threads **62** on the screw **16** to facilitate the connection therebetween. The space between the sidewalls **22A**, **22B** and around the aperture **24** may be smooth and includes two posts **26A**, **26B** extending upward from the first base **20**. The posts **26A**, **26B** are received within corresponding holes **46A**, **46B** in the top piece **14** (shown in FIG. **4**). The posts **26A**, **26B** serve to help orient the bottom piece **12** and the top piece **14** during their connection. The posts **26A**, **26B** also add additional points of engagement between the bottom piece **12** and the top piece **14**, which helps ensure the pieces **12**, **14** remain together and in the correct relative orientation when in use.

[0054] The bottom piece **12** also includes legs **28A**, **28B**, **28C**, **28D** extending proximate the corners of the first base **20**. The legs **28A**, **28B**, **28C**, **28D** extend outward from the corners, with two legs **28A**, **28D**, extending in one direction from the first base **20**, and the other two legs **28B**, **28C**, extending in an opposing direction. The legs **28A**, **28B**, **28C**, **28D** are generally wedge shaped and include sloped outer surfaces **30A**, **30B**, **30C**, **30D**. The slopes of these surfaces **30A**, **30B**,

30C, 30D extend in the same direction as the legs 28A, 28B, 28C, 28D extend away from the first base 20. While the sidewalls 22A, 22B demarcate one side of the base's 20 sides 20A, 20B, the legs 28A, 28B, 28C, 28D demarcate the opposing side. In particular, legs 28A, 28D oppose sidewall 22A, and legs 28B, 28C oppose sidewall 22B. The opposing nature of these elements at least partially defines wire channels 32A, 32B, with sidewall 22A and legs 28A, 28D defining a first wire channel 32A therebetween and sidewall 22B and legs 28B, 28C defining a second wire channel 32B there between. The sloped nature of the legs 28A, 28B, 28C, 28D ensures that the portions of the legs 28A, 28B, 28C, 28D facing their respective sidewalls 22A, 22B are high enough to retain the wires W in their respective channels 32A, 32B. As a result of these features, the shapes of the legs 28A, 28B, 28C, 28D can be anything that is large enough to retain the wires W in the channels 32A, 32B. Within the channels 32A, 32B, the sides 20A, 20B include ridges 34 (not all labeled for clarity). The ridges 34 provide a corrugated surface on the sides 20A 20B that can help align the wires W within the channels 32A, 32B. The corrugation of the ridges 34 also creates some friction that helps retain the wires W in their specific location within the channels 32A, 32B.

[0055] With reference to FIGS. 1, 2, and 4, the top piece 14 will now be described. The top piece 14 also includes a base 40 with a first side 40A and a second side 40B. The sides 40A, 40B are divided by a central portion 40C that includes a protrusion 42 extending therefrom. As the protrusion 42 extends in the direction of the bottom piece 12, it defines a cavity 43 in the top surface 19 of the top piece 14. The protrusion 42 is rounded and shaped so as to at least partially complement the curved sidewalls 22A, 22B of the bottom piece 12. The protrusion 42 includes an aperture 44 and holes 46A, 46B that respectively align with aperture 24 and posts 26A, 26B of the bottom piece 12. The aperture 44 may include threads 45 that correspond to threads 62 on the screw 16 and, along with the alignment of the holes 46A, 46B and posts 26A, 26B, serve to orient and connect the top piece 14 to the bottom piece 12. Based on these alignments, the protrusion 42 is shaped to fit within the space defined within the curved sidewalls 22A, 22B. As shown, the protrusion 42 is rounded, having three different partial circles extending downward, one circle defines the aperture 44 and the two other circles define the holes 46A, 46B. It is understood that different shapes can be used, so long as the protrusion 42 allows for the alignments discussed herein. It is also to be understood that the arrangement of the features associated with the protrusion 42 and the features associated with the partially elliptical barrier 22 can be reversed. In this instance, the top piece 14 may include the curved sidewalls 22A, 22B and posts 26A, 26B, and the bottom piece 12 may include the protrusion 42 and holes 46A, 46B.

[0056] The top piece 14 also includes flanges 48A, 48B, 48C, 48D extending proximate the corners of the second base 40. The flanges 48A, 48B, 48C, 48D correspond with and are aligned over the legs 28A, 28B, 28C, 28D of the bottom piece 12 when the wire clamp 10 is assembled. The flanges 48A, 48B, 48C, 48D are angled both downward and upward relative to the second base 40. This means that the flanges 48A, 48B, 48C, 48D include downward extending portions 50A, 50B, 50C, 50D, that, when the wire clamp 10 is assembled, contact at least a portion of the sloped surfaces 30A, 30B, 30C, 30D, of the legs 28A, 28B, 28C, 28D. Extending from the downward extending portions 50A, 50B, 50C, 50D are upward extending portions 52A, 52B, 52C, 52D extending away from the sloped surfaces 30A, 30B, 30C, 30D of the legs 28A, 28B, 28C, 28D. The upward extending portions 52A, 52B, 52C, 52D provide areas of the top piece 14 that can be easily gripped to remove the top piece 14 from the bottom piece 12.

[0057] The lower surface of upwardly extending portions 52A, 52B, 52C, 52D slope upward and away from the sloped outer surfaces 30A, 30B, 30C, 30D of the legs 28A, 28B, 28C, 28D of the bottom piece 12. Thus the sloping surfaces of the upper and lower pieces extend outward and away from each other, such that they may touch or almost touch at the portions closest to the center of the wire clamp 10 where the legs define the outermost border of the wire channels 32A and 32B and as the legs 28A, 28B, 28C, 28D, and the upwardly extending portions 52A, 52B, 52C, 52D

extend outward from the center of the wire clamp **10** the sloping surfaces open away from each other creating a mouth or opening. This mouth or opening can assist in guiding wires **W** into the channels **32A**, **32B** and in separating the bottom piece **12** and the upper piece **14** to allow the wires **W** to enter into the channels **32A**, **32B**. Such an action is shown in FIGS. **8A-8C** and discussed in greater detail below

[0058] The sides **40A**, **40B** of the top piece **14** also serve as channel walls **54A**, **54B**. The channel walls **54A** **54B** further define the wire channels **32A**, **32B** along with the sidewalls **22A**, **22B** and legs **28A**, **28B**, **28C**, **28D** of the bottom piece **12**. The channel walls **54A**, **54B** may contact the tops of the wires **W** upon the assembly of the wire clamp **10**, or the sizing of the top piece **14** and the bottom piece **12** may be such that a small space may be provided between the channel walls **54A**, **54B** and the wires **W** when the clamp **10** is assembled. The channel walls **54A**, **54B** may also include ridges **56** to provide similar corrugation benefits as the ridges **34** of the bottom piece. The shape and sizing of both sets of ridges **34**, **56** allows for a variety of wires **W** to be gripped and secured within the wire channels **32A**, **32B**. The arrangement shown also allows for wires **W** of different sizes to be received and secured within the wire channels **32A** **32B**. Finally, the top piece **14** is arched over the bottom piece **12**, having a curved sidewall **58** that arches over the first base **20** of the bottom piece **12**. This shape allows for the wires to fit snugly and safely within the channels **32A**, **32B** when the top piece **14** is mated with and connected to the bottom piece **12**.

[0059] With reference to FIGS. **1**, **2**, and **5-8**, the screw **16** includes an extension **60** having threads **62** thereon to mate with the threads **25**, **45** of the bottom piece **12** and the top piece **14**. A head **64** of the screw **16** is sized and shaped to rest within the indentation **43** when applied to the top piece **14**. Fully assembled wire clamps are shown in FIGS. **5-8**. To assemble these wire clamps **10**, wires **W** are placed in the wire channels **32A**, **32B** as defined by only the curved sidewalls **22A**, **22B** and legs **28A**, **28B**, **28C**, **28D** of the bottom piece **12** and aligned in the desired manner. Then, the top piece **14** is placed above and aligned with the bottom piece **12**, meaning that the protrusion **42** is aligned within the curved sidewalls **22A**, **22B** and the holes **46A**, **46B** are aligned with the posts **26A**, **26B**. Then the top piece **14** is connected to the bottom piece **12** by having the protrusion **42** received within the barrier **22** and the posts **26A**, **26B** received within the holes **46A**, **46B**. Then the screw **16** can be placed through and engaged with the apertures **24**, **44** of the bottom and top pieces **12**, **14**.

[0060] As shown in FIGS. **8A-9**, the wire clamp **10** can be applied to a rail **R** used in an industrial environment, such as a solar panel array. To apply the wire clamp **10** to the rail **R**, or to whatever element the wire clamp **10** is being applied, the rail **R** may include an aperture to receive the screw **16** therein. The screw **16** may also be self-tapping, as discussed below. In such an embodiment the rail **R** may not initially include an aperture. The aperture in the rail **R** may be formed by a drill tip **63** on the screw. This aperture may also include threads that correspond to the threads **62** on the screw **16**. To apply the wire clamp **10** to the rail, the wire clamp **10** can be assembled as previously described and then the threads **62** of the screw **16** can engage with and connect to the aperture of the rail **R**. In another method of assembly, the aperture **24** of the bottom piece **12** is aligned with the aperture of the rail **R**. Then the wires **W** can be placed within the wire channels **32A**, **32B**, and the top piece **14** can be applied to the bottom piece **12** as previously described. Then the screw **16** can be applied through each aperture to secure the wire clamp **10** and attach it to the rail **R**.

[0061] In a preferred embodiment the screw **16** includes the drill tip **63** at the distal end of the extension **60** and screw **16** is effectively a self-drilling self-tapping screw. This enables the wire clamp **10** to be located, placed, and installed at any appropriate location along the rail or other installation surface. Another method of assembly is that the top piece **14** and the bottom piece **12** can be assembled loosely with the posts **26A**, **26B** extending into the holes **46A**, **46B** and the protrusion **42** extending between the sidewalls **22A**, **22B**. The wires **W** can be inserted into channels **32A**, **32B**. The screw **16** can be inserted through aperture **24**, **44**. then the assembly can be placed on an installation surface such as a rail top surface and the self-drilling, self-tapping screw



**16** can be driven into the installation surface until the entire wire clamp **10** assembly is tightened and fixed onto the installation surface.

[0062] The orientation of the top piece **14** and the bottom piece **12** relative to each other is fixed by the interlocking relationship of the posts **26A**, **26B** and the holes **46A**, **46B** and well as the interlocking relationship between the protrusion **42** and the recessed area between the sidewalls **22A**, **22B**. The assembled wire clamp **10** allows for the top and bottom pieces **14**, **12** to freely rotate around the screw **16**. The wire clamp can be installed in any orientation on an installation surface. For instance the wire clip **10** can be installed on top of a rail **R** such that the wires extend perpendicular to the longitudinal axis of the rail, parallel to the longitudinal axis of the rail or at any angle in between. This provides maximum flexibility to an installer who is running wires in a solar array and must get the wires across a distance on a roof or other installation environment while preventing the wires from sagging and touching the roof or other surface.

[0063] The apertures **24**, **44** may be clearance holes without including threads. The wire clamp **10** can be assembled and installed on an installation surface without fully tightening the screw **16**. Then the wires can be inserted through the mouth or opening between the upward extending portions **52A**, **52B**, **52C**, **52D** of the top piece **14** and the legs **28A**, **28B**, **28C**, **28D** of the bottom piece **12** as is shown in FIGS. **8A-8C**. In such an arrangement, the flanges **48A**, **48B**, **48C**, **48D** located at one end of the top piece **14** (i.e., flanges **48A**, **48D** or flanges **48B**, **48C**) can be pulled upward to create a space between the respective flanges **48A**, **48B**, **48C**, **48D** and their corresponding legs **28A**, **28B**, **28C**, **28D** so that a wire **W** can fit between that space to be placed in the desired wire channel **32A**, **32B**.

[0064] The channels **32A**, **32B** are curved as a result of the elliptical shape of barrier **22**. The peripheral edges of the first base **20** and the inside vertical portions of the legs **28A**, **28B**, **28C**, **28D** are radiused. These features allow the wires **W** to enter and exit the channels **32A**, **32B** at an angle or bending in a non-orthogonal direction without risk of damage to the wires **W** or wire insulation.

[0065] While various aspects of the wire clamp **10** were provided in the foregoing description, those skilled in the art may make modifications and alterations to these aspects without departing from the scope and spirit of the invention. For example, it is to be understood that this disclosure contemplates that, to the extent possible, one or more features of any aspect can be combined with one or more features of any other aspect. Accordingly, the foregoing description is intended to be illustrative rather than restrictive. The invention described hereinabove is defined by the appended claims, and all changes to the invention that fall within the meaning and the range of equivalency of the claims are to be embraced within their scope.

## Claims

**1.-20.** (canceled)

**21.** A wire clamp comprising: a bottom piece comprising: a first base portion defining a first aperture; a first barrier extending from the first base portion, the first barrier being curved around and spaced from the first aperture; and at least one first leg extending from a first side of the base portion; a top piece comprising a second base portion, the top piece defining a second aperture; and a fastener, wherein the first aperture and the second aperture are configured to align and receive the fastener therethrough, thereby securing the top piece to the bottom piece, and wherein the first barrier and the at least one first leg define a first wire channel.

**22.** The wire clamp of claim 21, wherein the first wire channel is further defined by the second base portion.

**23.** The wire clamp of claim 21, wherein the bottom piece further comprises: a second barrier extending from the first base portion, the second barrier being curved around and spaced from the first aperture; and at least one second leg extending from a second side of the base portion, wherein the second side of the base portion opposes the first side of the base portion, and wherein the

second barrier and the at least one second leg define a second wire channel.

**24.** The wire clamp of claim 23, wherein the first barrier and the second barrier are symmetrical about the first aperture, thereby defining an at least partially elliptical barrier.

**25.** The wire clamp of claim 23, wherein the second wire channel is further defined by the second base portion.

**26.** The wire clamp of claim 21, wherein the top piece further comprises a protrusion extending from the second base portion, wherein the protrusion defines the second aperture, and wherein the protrusion is configured to be at least partially received between the first barrier and the second barrier.

**27.** The wire clamp of claim 26, wherein the protrusion defines at least one hole, wherein the bottom piece further comprises at least one post, and wherein the at least one post is configured to be received within the at least one hole.

**28.** The wire clamp of claim 21, wherein the top piece further comprises at least one first flange extending from a first side of the second base portion.

**29.** The wire clamp of claim 28, wherein the top piece is configured, such that, when the top piece is secured to the bottom piece, a force applied to the at least one first flange displaces the first side of the second base portion to allow a wire to be placed within the first wire channel.

**30.** The wire clamp of claim 23, wherein the top piece further comprises: at least one first flange extending from a first side of the second base portion; and at least one second flange extending from a second side of the second base portion, and wherein the second side of the second base portion opposes the first side of the second base portion.

**31.** The wire clamp of claim 30, wherein the top piece is configured, such that, when the top piece is secured to the bottom piece, a force applied to the at least one first flange displaces the first side of the second base portion to allow a wire to be placed within the first wire channel, and wherein the top piece is configured, such that, when the top piece is secured to the bottom piece, a force applied to the at least one second flange displaces the second side of the second base portion to allow a wire to be placed within the second wire channel.

**32.** A wire clamp comprising: a bottom piece comprising: a first base portion defining a first aperture; a first barrier extending from the first base portion, the first barrier being curved around and spaced from the first aperture; a second barrier extending from the first base portion, the second barrier being curved around and spaced from the first aperture; and a plurality of legs extending from sides of the first base portion; a top piece defining a second aperture, the top piece comprising: a second base portion; and a plurality of flanges extending from sides of second base portion; and a fastener, wherein the first aperture and the second aperture are configured to align and receive the fastener therethrough, thereby securing the top piece to the bottom piece, wherein the each of the plurality of legs correspond to one of the plurality of flanges, wherein the first barrier and a first portion of the plurality of legs define a first wire channel, and wherein the second barrier and a second portion of the plurality of legs define a second wire channel.

**33.** The wire clamp of claim 32, wherein the first wire channel and the second wire channel are further defined by the second base portion.

**34.** The wire clamp of claim 32, wherein the top piece is configured, such that, when the top piece is secured to the bottom piece, a force applied to at least one of the plurality of flanges displaces the second base portion to allow a wire to be placed within the first wire channel or the second wire channel.

**35.** The wire clamp of claim 34, wherein a portion of each of the plurality of flanges extends away from the corresponding leg of the plurality of legs.

**36.** The wire clamp of claim 35, wherein the first portion of the plurality of legs comprise a first leg and a second leg, wherein the second portion of the plurality of legs comprise a first leg and a second leg, wherein the first portion of the plurality of legs extend from a first side of the first base portion, wherein the second portion of the plurality of legs extend from a second side of the first

base portion, wherein the second side of the first base portion is opposite the first side of the first base portion, and wherein the plurality of flanges comprises four flanges, each corresponding to one leg of the plurality of legs.

**37.** A wire routing system comprising: a wire clamp comprising: a bottom piece comprising: a first base portion defining a first aperture; a first barrier extending from the first base portion, the first barrier being curved around and spaced from the first aperture; a second barrier extending from the first base portion, the second barrier being curved around and spaced from the first aperture; and at least two legs, a first leg extending from a first side of the first base portion, and a second leg extending from a second side of the first base portion; a top piece defining a second aperture, the top piece comprising: a second base portion; and at least two flanges, a first flange extending from a first side of the second base portion, and a second flange extending from a second side of the second base portion; a rail configured to define a third aperture; and a fastener, wherein the first aperture, the second aperture, and the third aperture are configured to be aligned and to receive the fastener therethrough, thereby securing the top piece to the bottom piece and mounting the wire clamp to the rail, wherein the first barrier and a first portion of the plurality of legs define a first wire channel, and wherein the second barrier and a second portion of the plurality of legs define a second wire channel.

**38.** The wire routing system of claim 37, wherein the fastener is a self-tapping fastener that is configured to define the third aperture in the rail.

**39.** The wire routing system of claim 37, wherein the top piece is configured, such that, when the top piece is secured to the bottom piece, a force applied to the at least one flange displaces the second base portion to allow a wire to be placed within the first wire channel or the second wire channel.

**40.** The wire routing system of claim 39, wherein the at least two legs comprise four legs, two legs extending from the first side of the first base portion and two legs extending from the second side of the first base portion, and wherein the at least two flanges comprise four flanges, each flange corresponding to and extending over at least a portion of one of the four legs.

---