

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12386474
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Lee; Dong-Ki et al.

---

### Touch sensible organic light emitting device

---

#### Abstract

An organic light emitting device includes: a substrate; a thin film transistor disposed on the substrate; an organic light emitting element connected to the thin film transistor and receiving a data voltage; a plurality of encapsulation thin films disposed on the organic light emitting element, and encapsulating the thin film transistor and the organic light emitting element; a planarization layer disposed on the encapsulation thin film; and a touch sensor disposed on the planarization layer.

---

<b>Inventors:</b>	Lee; Dong-Ki (Seongnam-si, KR), Min; Hoon-Kee (Seoul, KR)
<b>Applicant:</b>	Samsung Display Co., Ltd. (Yongin-si, KR)
<b>Family ID:</b>	1000008747497
<b>Assignee:</b>	Samsung Display Co., Ltd. (Yongin-si, KR)
<b>Appl. No.:</b>	18/222475
<b>Filed:</b>	July 16, 2023

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20230363236 A1	Nov. 09, 2023

#### Foreign Application Priority Data

KR	10-2008-0120015	Nov. 28, 2008
----	-----------------	---------------

#### Related U.S. Application Data

continuation parent-doc US 17986754 20221114 US 11737339 child-doc US 18222475  
continuation parent-doc US 17699195 20220321 US 11522022 20221206 child-doc US 17986754  
continuation parent-doc US 16278425 20190218 US 11282902 20220322 child-doc US 17699195

continuation parent-doc US 15869024 20180111 US 10211267 20190219 child-doc US 16278425  
continuation parent-doc US 15651903 20170717 US 10103209 20181016 child-doc US 15869024  
continuation parent-doc US 15479090 20170404 US 9711570 20170718 child-doc US 15651903  
continuation parent-doc US 15071137 20160315 US 9690423 20170627 child-doc US 15479090  
continuation parent-doc US 12421641 20090410 US 9292118 20160322 child-doc US 15071137

---

**Publication Classification**

**Int. Cl.:** **G06F3/044** (20060101); **G06F3/041** (20060101); **G06F3/045** (20060101); **G09G3/3225** (20160101); **G09G3/3258** (20160101); **G09G3/3266** (20160101); **G09G3/3275** (20160101); **H10K50/844** (20230101); **H10K59/123** (20230101); **H10K59/131** (20230101); **H10K59/40** (20230101); **H10K59/80** (20230101); H10K59/12 (20230101)

**U.S. Cl.:**

CPC **H10K59/40** (20230201); **G06F3/0412** (20130101); **G06F3/04166** (20190501); **G06F3/0444** (20190501); **G06F3/045** (20130101); **G09G3/3225** (20130101); **G09G3/3258** (20130101); **G09G3/3266** (20130101); **G09G3/3275** (20130101); **H10K50/844** (20230201); **H10K59/123** (20230201); **H10K59/131** (20230201); **H10K59/873** (20230201); H10K59/12 (20230201)

**Field of Classification Search**

**CPC:** G06F (3/044); H01L (51/5253); H01L (51/5256); H01L (27/323); H05B (33/04)

---

**References Cited**

**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6879319	12/2004	Cok	N/A	N/A
6985275	12/2005	Miyazawa	N/A	N/A
7187006	12/2006	Hayashi	N/A	N/A
7612498	12/2008	Sano et al.	N/A	N/A
7700385	12/2009	Hayashi	N/A	N/A
7737637	12/2009	Koshihara et al.	N/A	N/A
7928646	12/2010	Ryuji et al.	N/A	N/A
8063853	12/2010	Jung et al.	N/A	N/A
8259070	12/2011	Kim et al.	N/A	N/A
8823653	12/2013	Matsuo et al.	N/A	N/A
2003/0071569	12/2002	Chung et al.	N/A	N/A
2005/0224820	12/2004	Yamazaki et al.	N/A	N/A
2006/0158108	12/2005	Hayashi	313/506	H10K 50/844
2006/0158111	12/2005	Hayashi	428/917	H10K 50/8426
2006/0187213	12/2005	Su	N/A	N/A
2007/0030221	12/2006	Pak et al.	N/A	N/A
2007/0063991	12/2006	Lee et al.	N/A	N/A
2007/0242055	12/2006	Lai	N/A	N/A
2007/0267973	12/2006	Suh	N/A	N/A

2008/0042562	12/2007	Hayashi	N/A	N/A
2008/0252612	12/2007	Yu	N/A	N/A
2008/0278070	12/2007	Kim	N/A	N/A
2009/0051672	12/2008	Chen et al.	N/A	N/A
2009/0102774	12/2008	Hattori	N/A	N/A
2009/0153521	12/2008	Jiang et al.	N/A	N/A
2009/0268131	12/2008	Tsai et al.	N/A	N/A

#### **FOREIGN PATENT DOCUMENTS**

<b>Patent No.</b>	<b>Application Date</b>	<b>Country</b>	<b>CPC</b>
2005-011572	12/2004	JP	N/A
2005-252693	12/2004	JP	N/A
2007-140796	12/2006	JP	N/A
2007-299385	12/2006	JP	N/A
2007-300087	12/2006	JP	N/A
2008-087258	12/2007	JP	N/A
10-2003-0036089	12/2002	KR	N/A
10-2004-0030345	12/2003	KR	N/A
10-2004-0086556	12/2003	KR	N/A
10-2005-0020436	12/2004	KR	N/A
10-0548686	12/2005	KR	N/A
10-0654680	12/2005	KR	N/A
10-2007-0020431	12/2006	KR	N/A
10-2007-0033533	12/2006	KR	N/A
10-0688366	12/2006	KR	N/A
10-2007-0052889	12/2006	KR	N/A
10-2007-0068890	12/2006	KR	N/A
10-2008-0016194	12/2007	KR	N/A
10-2008-0094243	12/2007	KR	N/A
10-2008-0099684	12/2007	KR	N/A

#### **OTHER PUBLICATIONS**

Office Action dated Sep. 12, 2017, in Korean Patent Application No. 10-2017-0094178. cited by applicant

Notice of Allowance dated May 9, 2017, in U.S. Appl. No. 15/479,090. cited by applicant

Notice of Allowance dated Apr. 25, 2017, in U.S. Appl. No. 15/071,137. cited by applicant

Final Office Action dated Feb. 3, 2017, in U.S. Appl. No. 15/071,137. cited by applicant

Non-Final Office Action dated Oct. 27, 2016, in U.S. Appl. No. 15/071,137. cited by applicant

Notice of Allowance dated Nov. 6, 2015, in U.S. Appl. No. 12/421,641. cited by applicant

Non-Final Office Action dated Jun. 25, 2015, in U.S. Appl. No. 12/421,641. cited by applicant

Final Office Action dated Mar. 13, 2015, in U.S. Appl. No. 12/421,641. cited by applicant

Non-Final Office Action dated Dec. 5, 2014, in U.S. Appl. No. 12/421,641. cited by applicant

Final Office Action dated Apr. 25, 2014, in U.S. Appl. No. 12/421,641. cited by applicant

Non-Final Office Action dated Mar. 12, 2014, in U.S. Appl. No. 12/421,641. cited by applicant

Final Office Action dated Aug. 2, 2012, in U.S. Appl. No. 12/421,641. cited by applicant

Non-Final Office Action dated May 10, 2012, in U.S. Appl. No. 12/421,641. cited by applicant

Notice of Allowance dated Mar. 27, 2018, in Korean Patent Application No. 10-2017-0094178. cited by applicant

Notice of Allowance dated Jun. 15, 2018, in U.S. Appl. No. 15/651,903. cited by applicant

Office Action dated Jul. 13, 2018, in Korean Patent Application No. 10-2018-0074176. cited by

applicant  
Office Action dated Mar. 24, 2015, in Korean Patent Application No. 10-2008-0120015. cited by applicant  
Office Action dated Sep. 14, 2015, in Korean Patent Application No. 10-2008-0120015. cited by applicant  
Notice of Allowance dated Mar. 28, 2016, in Korean Patent Application No. 10-2008-0120015. cited by applicant  
Notice of Allowance dated Sep. 5, 2016, in Korean Patent Application No. 10-2016-0078875. cited by applicant  
Office Action dated Dec. 22, 2016, in Korean Patent Application No. 10-2016-0154273. cited by applicant  
Final Office Action dated Jun. 26, 2017, in Korean Patent Application No. 10-2016-0154273. cited by applicant  
Notice of Result of Reexamination dated Sep. 22, 2017, in Korean Patent Application No. 10-2016-0154273. cited by applicant  
Notice of Allowance dated Oct. 5, 2018, in U.S. Appl. No. 15/869,024. cited by applicant  
Office Action dated Jan. 21, 2019, in Korean Patent Application No. 10-2018-0074176. cited by applicant  
Non-Final Office Action dated Aug. 15, 2019, issued to U.S. Appl. No. 16/278,425. cited by applicant  
Final Office Action dated Nov. 19, 2019, issued to U.S. Appl. No. 16/278,425. cited by applicant  
Non-Final Office Action dated Apr. 7, 2020, issued to U.S. Appl. No. 16/278,425. cited by applicant  
Final Office Action dated Jul. 13, 2020, issued to U.S. Appl. No. 16/278,425. cited by applicant  
Non-Final Office Action dated Feb. 19, 2021, issued to U.S. Appl. No. 16/278,425. cited by applicant  
Notice of Allowance dated Nov. 23, 2021, issued to U.S. Appl. No. 16/278,425. cited by applicant  
Notice of Allowance dated Aug. 5, 2022, issued to U.S. Appl. No. 17/699,195. cited by applicant  
Notice of Allowance dated Apr. 6, 2023, issued to U.S. Appl. No. 17/986,754. cited by applicant  
Notice of Allowance dated Jun. 30, 2023, issued to U.S. Appl. No. 17/986,754. cited by applicant

---

*Primary Examiner:* Joseph; Dennis P

*Attorney, Agent or Firm:* Womble Bond Dickinson (US) LLP

---

## **Background/Summary**

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/986,754, filed on Nov. 14, 2022, which is a continuation of U.S. patent application Ser. No. 17/699,195, filed on Mar. 21, 2022, now issued as U.S. Pat. No. 11,522,022, which is a continuation of U.S. patent application Ser. No. 16/278,425, filed on Feb. 18, 2019, now issued as U.S. Pat. No. 11,282,902, which is a continuation of U.S. patent application Ser. No. 15/869,024, filed Jan. 11, 2018, now issued as U.S. Pat. No. 10,211,267, which is a continuation of U.S. patent application Ser. No. 15/651,903, filed Jul. 17, 2017, now issued as U.S. Pat. No. 10,103,209, which is a continuation of U.S. patent application Ser. No. 15/479,090, filed Apr. 4, 2017, now issued as U.S. Pat. No. 9,711,570, which is a continuation of U.S. patent application Ser. No. 15/071,137, filed Mar. 15, 2016, now issued as U.S. Pat. No. 9,690,423, which is a continuation application of U.S. patent application Ser. No. 12/421,641, filed Apr. 10, 2009,

now issued as U.S. Pat. No. 9,292,118, and which claims priority from and the benefit of Korean Patent Application No. 10-2008-0120015, filed Nov. 28, 2008, each of which is hereby incorporated by reference for all purposes as if fully set forth herein.

## BACKGROUND

### (a) Technical Field

(1) Embodiments of the present invention generally relate to a touch sensible organic light emitting device.

### (b) Description of the Related Art

(2) An organic light emitting device includes two electrodes and an organic light emitting layer interposed between the two electrodes. One of the two electrodes injects holes and the other injects electrons into the light emitting layer. The injected electrons and holes combine to form excitons and the excitons emit light as discharging energy.

(3) An organic light emitting device includes an organic light emitting element and a plurality of thin film transistors for driving it. The thin film transistors comprise a plurality of thin films and are generally disposed at the lower side of the organic light emitting device, the organic light emitting element is disposed at the upper side thereof, and an anode of the organic light emitting element is disposed at the lower side and a cathode thereof is disposed at the upper side.

(4) An organic light emitting element includes an anode and a cathode as two electrodes, and an organic light emitting member as the emission layer disposed therebetween. An organic light emitting member emits light of three primary colors such as red, green, and blue, or white. Materials for the organic light emitting member vary according to the colors that the organic light emitting member emits. When an organic light emitting member emits white light, light emitting materials that emit red, green, and blue are stacked so that the synthesized light becomes white. Moreover, in the case where the organic light emitting member emits the white light, color filters may be added to obtain light of a desired color.

(5) Meanwhile, thin film transistors include a switching transistor for switching a voltage applied to each pixel, and a driving transistor for driving the organic light emitting element.

(6) An organic light emitting device may be classified into a top emission type that emits light in the upper direction and a bottom emission type that emits light in the lower direction.

(7) On the other hand, a touch screen panel is a device for allowing a machine such as a computer to perform a desired command by writing a character, drawing a picture, or executing an icon through touching a finger or a touch pen (or a stylus) on a screen. A display device to which a touch screen panel is attached can determine whether a user finger or a touch pen, etc., touches a screen and touch position information. The cost of such a display device, however, increases due to the touch screen panel. Because of additional processes for adhering or coupling the touch screen panel to the display panel, the yield of the organic light emitting device is reduced, the luminance and the viewing angle of the display panel are deteriorated, and the overall thickness of the product increases.

(8) The above information disclosed in this Background section is only for enhancement of understanding of the background of the disclosure and therefore it may contain information that does not form the prior art that is already known in this country to a person of ordinary skill in the art.

## SUMMARY

(9) An organic light emitting device according to an exemplary embodiment of the present invention comprises: a substrate; a thin film transistor disposed on the substrate; an organic light emitting element connected to the thin film transistor and receiving a data voltage; a plurality of encapsulation thin films disposed on the organic light emitting element, and encapsulating the thin film transistor and the organic light emitting element; a planarization layer disposed on the encapsulation thin film; and a touch sensor disposed on the planarization layer.

- (10) The plurality of encapsulation thin films may comprise an organic insulator or an inorganic insulator.
- (11) The inorganic insulator may comprise silicon oxide or silicon nitride.
- (12) The planarization layer may comprise an organic material, and has a flat surface.
- (13) The touch sensor may comprise a variable capacitor connected to a sensing signal line transmitting a sensing signal, and a reference capacitor connected between the sensing signal line and a reference voltage terminal.
- (14) A capacitance of the variable capacitor may be changed according to an external touch comprising a pressure applied to one terminal of the variable capacitor.
- (15) The touch sensor may comprise a first transparent conductive layer.
- (16) The first transparent conductive layer may comprise indium tin oxide (ITO) or indium zinc oxide (IZO).
- (17) A plurality of electrode island portions each disposed on a corner of the substrate and transmitting a voltage to the first transparent conductive layer may be further comprised.
- (18) A signal line pattern connecting the plurality of electrode island portions; and a sensing signal processor connected to the signal line pattern and receiving the changed voltage according to a touch on the first transparent conductive layer and generating a digital sensing signal may be further comprised.
- (19) A plurality of electrode island portions each disposed on a corner of the substrate and transmitting a high-frequency signal to the first transparent conductive layer, a signal line pattern connecting the plurality of electrode island portions, and a sensing signal processor connected to the signal line pattern and receiving a changed high-frequency signal according to a touch on the first transparent conductive layer and generating a sensing signal may be further comprised.
- (20) The touch sensor may further comprise a first insulating layer disposed on the first transparent conductive layer; and a second transparent conductive layer disposed on the first insulating layer.
- (21) A plurality of electrode island portions each disposed on a corner of the substrate and transmitting a voltage to the first and second transparent conductive layers, a signal line pattern connecting the plurality of electrode island portions, and a sensing signal processor connected to the signal line pattern and receiving a changed voltage according to a touch on the second transparent conductive layer and generating a sensing signal may be further comprised.
- (22) A plurality of electrode island portions each disposed on a corner of the substrate and transmitting a high-frequency signal to the first and second transparent conductive layers, a signal line pattern connecting the plurality of electrode island portions, and a sensing signal processor connected to the signal line pattern and receiving a changed high-frequency signal according to a touch on the second transparent conductive layer and generating a sensing signal may be further comprised.
- (23) A second insulating layer disposed on the second transparent conductive layer may be further comprised.
- (24) The first transparent conductive layer may be connected to the reference voltage terminal, and the second transparent conductive layer is connected to a sensing signal line disposed on the substrate.
- (25) A sensing signal processor receiving a changed voltage of the second transparent conductive layer according to a touch on the second insulating layer and generating a sensing signal may be further comprised.
- (26) The organic light emitting element may comprise a pixel electrode connected to the thin film transistor and receiving a data voltage through the thin film transistor, an organic light emitting member disposed on the pixel electrode, and a common electrode disposed on the organic light emitting member.
- (27) The thin film transistor may comprise a switching transistor controlled by a scanning signal;

and a driving transistor connected to the switching transistor and transmitting an output current to the organic light emitting element.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a block diagram of a touch sensible organic light emitting device according to an exemplary embodiment of the present invention.
- (2) FIG. 2 is an equivalent circuit diagram of a touch sensible organic light emitting device according to an exemplary embodiment of the present invention.
- (3) FIG. 3 is a cross-sectional view of one pixel of a touch sensible organic light emitting device according to an exemplary embodiment of the present invention.
- (4) FIG. 4 is an equivalent circuit diagram of a touch sensor of a touch sensible organic light emitting device according to an exemplary embodiment of the present invention.
- (5) FIG. 5 and FIG. 6 are cross-sectional views of one pixel of a touch sensible organic light emitting device according to an exemplary embodiment of the present invention.
- (6) FIG. 7 is a view showing a connection relationship of a high-frequency sensor in a touch sensible organic light emitting device according to an exemplary embodiment of the present invention.

### DETAILED DESCRIPTION

- (7) Embodiments of the present invention will be described more fully hereinafter with reference to the accompanying drawings, in which exemplary embodiments of the invention are shown. As those skilled in the art would realize, the described embodiments may be modified in various different ways, all without departing from the spirit or scope of the present disclosure.
- (8) In the drawings, the thickness of layers, films, panels, regions, etc., are exaggerated for clarity. Like reference numerals designate like elements throughout the specification. It will be understood that when an element such as a layer, film, region, or substrate is referred to as being “on” another element, it may be directly on the other element, or intervening elements may also be present. In contrast, when an element is referred to as being “directly on” another element, there are no intervening elements present.
- (9) A touch sensible organic light emitting device according to an exemplary embodiment of the present invention will now be described with reference to FIGS. 1 and 2.
- (10) FIG. 1 is a block diagram of a touch sensible organic light emitting device according to an exemplary embodiment of the present invention, and FIG. 2 is an equivalent circuit diagram of a touch sensible organic light emitting device according to an exemplary embodiment of the present invention.
- (11) Referring to FIG. 1, an organic light emitting device according to an exemplary embodiment of the present invention includes a display panel **300** including a touch sensor (not shown), a scan driver **400**, a data driver **500** and a sensing signal processor **800** that are connected to the display panel **300**, and a touch determining unit **900** connected to the sensing signal processor **800**.
- (12) Referring to FIG. 1 and FIG. 2, an organic light emitting device according to the present exemplary embodiment includes a plurality of signal lines **121**, **171**, and **172**, and a plurality of pixels PX connected thereto and arranged substantially in a matrix.
- (13) The signal lines include a plurality of scanning signal lines **121** for transmitting gate signals (or scanning signals), a plurality of data lines **171** for transmitting data signals, and a plurality of driving voltage lines **172** for transmitting a driving voltage. The scanning signal lines **121** extend substantially in a row direction and are substantially parallel to each other, and the data lines **171** extend substantially in a column direction and are substantially parallel to each other. Although the driving voltage lines **172** are shown as extending substantially in a column direction, the driving

voltage lines **172** may extend in a row direction or in a column direction, or may be formed in a matrix. Also, the signal lines may further comprise a sensing signal line (not shown) for transmitting a sensing signal of the touch sensor.

(14) As shown in FIG. 2, each pixel PX includes a switching transistor Qs, a driving transistor Qd, a storage capacitor Cst, and an organic light emitting element LD.

(15) The switching transistor Qs includes a control terminal, an input terminal, and an output terminal, in which the control terminal is connected to the scanning signal line **121**, the input terminal is connected to the data line **171**, and the output terminal is connected to the driving transistor Qd. The switching transistor Qs transmits a data signal received from the data line **171** to the driving transistor Qd in response to the scanning signal received from the scanning signal line **121**.

(16) The driving transistor Qd also includes a control terminal, an input terminal, and an output terminal, in which the control terminal is connected to the switching transistor Qs, the input terminal is connected to the driving voltage line **172**, and the output terminal is connected to the organic light emitting element LD. The driving transistor Qd transmits an output current  $I_{sub,LD}$  of which the magnitude varies according to the voltage applied between the control terminal and the output terminal of the driving transistor Qd.

(17) The capacitor Cst is connected between the control terminal and the input terminal of the driving transistor Qd. The capacitor Cst stores the data signal applied to the control terminal of the driving transistor Qd and maintains the stored data signal even after the switching transistor Qs is turned off.

(18) The organic light emitting element LD may be an organic light emitting diode (OLED), for example having an anode connected to the output terminal of the driving transistor Qd and a cathode connected to a common voltage Vss. The organic light emitting element LD emits light of which the intensity is varied according to the output current  $I_{sub,LD}$  of the driving transistor Qd, to display an image. The organic light emitting element LD may include an organic material uniquely emitting at least one of the primary colors such as red, green, or blue, or a white color, and the organic light emitting device emits desired images by a spatial sum thereof.

(19) The switching transistor Qs and the driving transistor Qd may be n-channel field effect transistors (FET); however, at least one of the switching transistor Qs and the driving transistor Qd may be a p-channel FET. Moreover, the connection relationship among the transistors Qs and Qd, the storage capacitor Cst, and the organic light emitting element LD may be changed.

(20) Referring again to FIG. 1 and FIG. 2, the scan driver **400** is connected to the scanning lines **121**, and applies scanning signals that are a combination of a high voltage Von for turning on the switching transistors Qs and a low voltage Voff for turning off the switching transistors Qs to the scanning lines **121**.

(21) The data driver **500** is connected to the data lines **171** in the display panel **300** and applies data voltages to the data lines **171**.

(22) The sensing signal processor **800** receives a sensing signal from the touch sensor (not shown) of the display panel **300**, performs a signal process such as amplifying and filtering, and converts the processed signal to a digital sensing signal DS through an analog-digital conversion.

(23) The touch determining unit **900** receives the digital sensing signal DS from the sensing signal processor **800**, performs a predetermined calculation process, and determines whether the display panel **300** is touched or not as well as a touch position to generate a touch information INF, and then, outputs the touch information INF to an external device. An external device may transmit the image signal based on the touch information INF to the organic light emitting device. Alternatively, when the external device directly receives the digital sensing signal DS and performs the function of the touch determining unit **900** such as determining the touch position, the touch determining unit **900** may be omitted.

(24) Next, a display operation of the organic light emitting device will be described according to



one or more embodiments.

(25) The data driver **500** receives digital output image signals for a row of pixels PX, and converts the digital output image signals into analog data voltages to apply to the data lines **171**.

(26) The scan driver **400** applies the high voltage Von to the gate lines **121** to turn on the switching element Qs coupled to the gate lines **121**. Thereby, the data voltage applied to the data lines **171** is applied to the corresponding pixel PX through the turned on switching element Qs.

(27) The driving transistor Qd receives the data voltages through the turned on switching element Qs thereby generating a corresponding output current I.sub.LD. The organic light emitting element LD emits light having an intensity corresponding to the output current I.sub.LD of the driving transistor Qd.

(28) By repeating the above procedure by a unit of one horizontal period, which is denoted by "1H", the scanning signal is sequentially applied for all scanning signal lines **121** and the data voltage is applied to all pixels PX to display an image of one frame.

(29) Next, the display panel of the organic light emitting device shown in FIGS. **1** and FIG. **2** will be described in detail according to one or more embodiments with reference to FIG. **3** and FIG. **4** as well as FIG. **1** and FIG. **2**.

(30) FIG. **3** is a cross-sectional view of one pixel of a touch sensible organic light emitting device according to an exemplary embodiment of the present invention, and FIG. **4** is an equivalent circuit diagram of a touch sensor of a touch sensible organic light emitting device according to an exemplary embodiment of the present invention,

(31) Referring to FIG. **4**, a touch sensor of a touch sensible organic light emitting device according to an exemplary embodiment of the present invention includes a variable capacitor Cv connected to the sensing signal line SL, and a reference capacitor Cr connected between the sensing signal line SL and the reference voltage Vr terminal.

(32) The capacitance of the variable capacitor Cv may be varied according to an external touch applied to the upper terminal of the variable capacitor Cv such as a contact (touch) of a finger Fn of a user. For example, the external touch may be a pressure. If the capacitance of the variable capacitor Cv is changed, the node voltage Vn between of the reference capacitor Cr and the variable capacitor Cv depending on the capacitance changes. The node voltage Vn is transmitted through the sensing signal line SL as a sensing signal, and either the existence or lack of a touch as well as a touch position may be determined based on the sensing signal. Here, the reference capacitor Cr has a fixed capacitance and the reference voltage Vr applied to the reference capacitor Cr has a uniform voltage, such that the node voltage Vn is changed within a predetermined range. Accordingly, the sensing signal may always have a voltage level within a predetermined range such that the existence or lack of a touch as well as touch position may be easily determined.

(33) Next, a cross-sectional structure of the driving transistor Qd, the organic light emitting element LD, and the touch sensor of a touch sensible organic light emitting device according to an exemplary embodiment of the present invention will be described with reference to FIG. **3**, FIG. **1**, FIG. **2**, and FIG. **4**.

(34) A plurality of gate conductors including control electrodes **124** are formed on an insulation substrate **110** made of transparent glass or plastic.

(35) A gate insulating layer **140** that may be made of silicon nitride (SiNx) or silicon oxide (SiOx) is formed on the gate conductor.

(36) A plurality of semiconductors **154** are formed on the gate insulating layer **140**. The semiconductors **154** overlap the control electrodes **124**.

(37) A plurality of pairs of ohmic contacts **163** and **165** are formed on the semiconductors **154**.

(38) A plurality of data conductors including a plurality of driving voltage lines **172** and a plurality of output electrodes **175** are formed on the ohmic contacts **163** and the gate insulating layer **140**.

(39) The driving voltage lines **172** transmit a driving voltage, and include input electrodes **173** extending toward the control electrodes **124**.

(40) The output electrodes **175** are separated from the driving voltage lines **172**.

(41) The input electrodes **173** and the output electrodes **175** oppose each other on the semiconductors **154**.

(42) A control electrode **124**, an input electrode **173**, and an output electrode **175** form a driving transistor Qd along with a semiconductor **154**, and a channel of the driving transistor Qd is formed in the semiconductor **154** between the input electrode **173** and the output electrode **175**.

(43) The ohmic contacts **163** and **165** are only disposed between the underlying semiconductor **154** and the overlying data conductor, thereby reducing the contact resistance therebetween. The semiconductor **154** has a portion that is exposed without being covered with the input electrode **173** and the output electrode **175**, and a portion between the source electrodes **173** and the drain electrodes.

(44) A lower passivation layer **180p** made of an inorganic insulator such as silicon nitride or silicon oxide is formed on the gate insulating layer **140**, the data conductor, and the exposed semiconductor **154**.

(45) An upper passivation layer **180q** is formed on the lower passivation layer **180p**. The upper passivation layer **180q** may be made of an organic material, and may have a flat surface.

(46) The lower passivation layer **180p** and the upper passivation layer **180q** have contact holes **185** exposing the output electrodes **175**.

(47) A plurality of pixel electrodes **191** are formed on the upper passivation layer **180q**. The pixel electrodes **191** may be made of a reflective metal such as Al, Ag, Au, Pt, Ni, Cu, W, or alloys thereof. The pixel electrodes **191** may further include a transparent electrode that is disposed on or under the reflective metal and made of a conductive metal oxide such as indium tin oxide (ITO) or indium zinc oxide (IZO). The transparent electrode may improve the cohesion between the layer made of a reflective metal and another layer, and may prevent corrosion thereof.

(48) The pixel electrodes **191** are physically-electrically connected to the output electrodes **175** through the contact holes **185**.

(49) Partitions **360** are formed on the upper passivation layer **180**. The partitions **360** define a plurality of openings enclosing edges of the pixel electrodes **191** like a bank, and may be made of an organic insulator or an inorganic insulator. Alternatively, the partitions **360** may be made of a photoresist including black pigments, and in this case, the partitions **360** may function as a light blocking member, thereby simplifying the manufacturing process.

(50) An organic light emitting member **370** is formed in openings defined by the partitions **360** on the pixel electrodes **191**. The organic light emitting member **370** may be made of an organic material uniquely emitting light of one primary color such as red, green, or blue. The organic light emitting device displays a desired image by spatially combining primary colors of the organic light emitting members **370**.

(51) The organic light emitting member **370** may have a multi-layer structure including auxiliary layers for improving light emitting efficiency of an emission layer (not shown) in addition to the emission layer. An auxiliary layer may include an electron transport layer (not shown) and a hole transport layer (not shown) that achieve a balance of electrons and holes, and an electron injection layer (not shown) and a hole injection layer (not shown) that reinforce the injection of the electrons and the holes.

(52) A common electrode **270** is formed on the organic light emitting member **370**. The common electrode **270** receives a common voltage Vss, and may be made of a transparent conductive material such as ITO or IZO, etc., or of a thin metal layer through which light may be transmitted.

(53) In the organic light emitting device, a pixel electrode **191**, an organic light emitting member **370**, and the common electrode **270** form an organic light emitting element LD having the pixel electrode **191** as an anode and the common electrode **270** as a cathode, or vice versa. The organic light emitting device display emits light in the upper direction with respect to the substrate **110** to display images.

(54) An encapsulation thin film layer **260** including a first encapsulation thin film **261**, a second encapsulation thin film **262**, and a third encapsulation thin film **263** is formed on the common electrode **270**. The first, second, and third encapsulation thin films **261**, **262**, and **263** may be made of an inorganic material such as silicon oxide or silicon nitride, or of an organic insulator. The encapsulation layer encapsulates the organic light emitting member **370** and the common electrode **270** such that moisture and/or oxygen from the exterior may be prevented from flowing into them and oxidation of the organic light emitting member **370** and the common electrode **270** may be prevented. The third encapsulation thin film **263** that is disposed uppermost may completely encapsulate the organic light emitting member **370** and the common electrode **270** by covering the upper surface of the substrate **110** at the edges of the display panel **300**. Accordingly, the thin films are used to encapsulate and protect the organic light emitting member **370** and so forth such that the thickness of the organic light emitting device may be further reduced and the display characteristics such as transmittance and viewing angle may be improved.

(55) According to another exemplary embodiment of the present invention, the encapsulation thin film layer **260** may be made of a single layer, double layers, or a plurality of layers of more than two layers including inorganic insulators or organic insulators.

(56) A planarization layer **240** is formed on the encapsulation thin film layer **260**. The planarization layer **240** may be made of an organic material, and flatten the surface on the encapsulation thin film layer **260**.

(57) A lower transparent conductive layer **232**, an insulating layer **220**, and an upper transparent conductive layer **231** may be sequentially formed on the whole surface of the planarization layer **240**.

(58) The lower and upper transparent conductive layers **232** and **231** may be made of a transparent conductive material such as ITO, ATO (antimony tin oxide), or IZO. The lower transparent conductive layer **232** may receive a predetermined voltage such as the reference voltage  $V_r$ , and the upper transparent conductive layer **231** may be connected to the sensing signal line SL.

(59) The insulating layer **220** may be made of an inorganic material such as silicon oxide or silicon nitride, or of an organic insulator through, for example, spin coating or printing.

(60) The lower transparent conductive layer **232** and the upper transparent conductive layer **231** form a reference capacitor  $C_r$  along with the insulating layer **220**.

(61) A surface insulating layer **210** that may be made of an inorganic material such as silicon oxide or silicon nitride, or an organic insulator, is coated on the whole surface of the upper transparent conductive layer **231**. The upper surface of the surface insulating layer **210** or an external touch object form the variable capacitor  $C_v$  along with the upper transparent conductive layer **231**, wherein the surface insulating layer **210** between the upper surface of the surface insulating layer **210** or the external touch object, and the upper transparent conductive layer **231** functions as a dielectric material of the variable capacitor  $C_v$ .

(62) Referring to FIG. 3 and FIG. 4, when an external touch by a finger  $F_n$  is applied to any portion on the surface insulating layer **210**, the voltage of the upper transparent conductive layer **231**, that is, the node voltage  $V_n$  between the reference capacitor  $C_r$  and the variable capacitor  $C_v$  is changed. Alternatively, the capacitance of the variable capacitor  $C_v$  changes at the touch portion such that the node voltage  $V_n$  of the upper transparent conductive layer **231** may be changed. For example, if a pressure by a touch is applied to the surface insulating layer **210**, the thickness of the surface insulating layer **210** is changed so that the capacitance of the variable capacitor  $C_v$  may be changed. Thus, the node voltage  $V_n$  of the upper transparent conductive layer **231** depending on the capacitance of the variable capacitor  $C_v$  is changed. The changed node voltage  $V_n$  of the upper transparent conductive layer **231** is transmitted through the sensing signal line SL as a sensing signal, and either a touch or a lack of touch may be determined based on the sensing signal. Such sensing operation is separately executed from the above-described display operation, and may not be influenced by the display operation or vice versa.

(63) According to another embodiment, a conductive layer (not shown) may be further formed on the surface insulating layer **210**. Also, a coating layer (not shown) for protection of the upper transparent conductive layer **231** and reduction of noises may be further formed on the surface insulating layer **210**.

(64) Next, a touch sensible organic light emitting device according to another exemplary embodiment of the present invention will be described with reference to FIG. 5 to FIG. 7 as well as FIG. 1 and FIG. 2.

(65) FIG. 5 and FIG. 6 are cross-sectional views of one pixel of a touch sensible organic light emitting device according to an exemplary embodiment of the present invention, and FIG. 7 is a view showing a connection relationship of a high-frequency sensor in a touch sensible organic light emitting device according to an exemplary embodiment of the present invention.

(66) Referring to FIG. 5 and FIG. 6, a touch sensible organic light emitting device according to an exemplary embodiment of the present invention has almost the same cross-sectional structure as the organic light emitting device shown in the embodiment of FIG. 3. In the present exemplary embodiment, descriptions of the same elements will be omitted, and the same constituent elements as in the above-described exemplary embodiment are indicated by the same reference numerals.

(67) Referring to FIG. 5, a gate conductor including a control electrode **124**, a gate insulating layer **140**, a plurality of semiconductors **154**, a plurality of pairs of ohmic contacts **163** and **165**, a plurality of data conductors including a driving voltage line **172** and an output electrode **175**, a lower passivation layer **180p** and an upper passivation layer **180q**, a plurality of pixel electrodes **191**, a partition **360**, an organic light emitting member **370**, a common electrode **270**, an encapsulation thin film layer **260** including a first encapsulation thin film **261**, a second encapsulation thin film **262**, and a third encapsulation thin film **263**, a planarization layer **240**, and a transparent conductive layer **232a** are sequentially formed on the insulation substrate **110**.

(68) Referring to FIG. 1 and FIG. 7, a plurality of electrode island portions **233** are formed at the four corners of the display panel **300** in the organic light emitting device according to the present exemplary embodiment. The electrode island portions **233** are connected to the four corners of the transparent conductive layer **232a**. The electrode may include electrode islands (not shown) for transmitting a high-frequency signal or a predetermined voltage to the transparent conductive layer **232a** and a signal receiver (not shown) for sensing a changed high-frequency signal or voltage.

(69) A signal line pattern **80** that may have a stripe shape and that may be made of a metal such as silver or aluminum is formed near the edge of the display panel **300**. The signal line pattern **80** connects four electrode island portions **233**, and the end portion thereof is connected to the sensing signal processor **800**. The signal line pattern **80** may be formed on the transparent conductive layer **232a**.

(70) In such an organic light emitting device, a high-frequency signal or a voltage is applied to the transparent conductive layer **232a** through the electrode islands (not shown) of the electrode island portions **233**. If an external object such as a finger **Fn** touches the transparent conductive layer **232a**, the high-frequency signal is changed or the voltage is changed, and the changed signal such as the changed high-frequency signal is detected by the signal receiver (not shown) of the electrode island portions **233**. The detected signal is input to the sensing signal processor **800** and the touch determining unit **900** through the signal line pattern **80**, thereby determining the touch position.

(71) Also, referring to FIG. 6, in a touch sensible organic light emitting device according to another exemplary embodiment of the present invention, a lower transparent conductive layer **232** may be formed in replacement of the transparent conductive layer **232a** of the organic light emitting device shown in the embodiment of FIG. 5. Also, an insulating layer **220**, an upper transparent conductive layer **231** and a coating layer **215** may be further formed on the lower transparent conductive layer **232**. The coating layer **215** may protect the upper transparent conductive layer **231** from contamination and external influence.

(72) Referring to FIG. 6 and FIG. 7, the lower transparent conductive layer **232** and the upper

transparent conductive layer 231 are connected to the electrode islands (not shown) of the electrode island portions 233, thereby receiving the high-frequency signal or the predetermined voltage. A changed high-frequency signal or a changed voltage by a touch is detected by the signal receiver (not shown) of the electrode island portions 233. Also, many characteristics of the organic light emitting device shown in the embodiments of FIG. 5 and FIG. 7 may be applied to the organic light emitting display device shown in the embodiments of FIG. 6 and FIG. 7.

(73) Numerous characteristics of the touch sensible organic light emitting device shown in the embodiment of FIG. 3 may be applied identically to the organic light emitting device shown in the embodiments of FIG. 5 to FIG. 6.

(74) The sensing method of an organic light emitting device according to an exemplary embodiment of the present invention is an example of a touch sensing method. A touch sensor operating by various sensing methods such as the capacitance type sensing method may be included.

(75) According to an exemplary embodiment of the present invention, organic light emitting elements and thin film transistors of an organic light emitting device may be encapsulated by several encapsulation thin films, and a touch sensor of the capacitance type sensing method that is thin may be formed. Accordingly, the thickness of the touch sensible organic light emitting device may be reduced, and the display characteristics such as transmittance and viewing angles may be improved.

(76) Embodiments of the present invention may be applied to an organic light emitting device having various structures.

(77) While this disclosure has been described in connection with what is presently considered to be practical exemplary embodiments, it is to be understood that the disclosure is not limited to the disclosed embodiments, but, on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims.

## Claims

1. A light emitting device comprising: a substrate; a thin film transistor on a surface of the substrate; a pixel electrode electrically connected to the thin film transistor; a first insulating layer defining an opening on the pixel electrode; a light emitting layer comprising a portion disposed in the opening; a common electrode on the light emitting layer and the first insulating layer; a first thin film layer formed on the common electrode; a second thin film layer formed on the first thin film layer; an organic layer formed on the second thin film layer; and a touch sensor formed on the organic layer without any adhesive layer for adhering between the touch sensor and the organic layer, wherein the second thin film layer comprising a first portion overlapping the opening and a second portion overlapping the first insulating layer outside the opening and adjacent to the first portion in a plan view, and wherein a first distance between an upper surface of the first portion and the surface of the substrate is less than a second distance between an upper surface of the second portion and the surface of the substrate.
2. The light emitting device of claim 1, wherein at least one of the first thin film layer and the second thin film layer comprises an inorganic material.
3. The light emitting device of claim 2, wherein at least one of the first thin film layer and the second thin film layer comprises silicon nitride or silicon oxide.
4. The light emitting device of claim 1, wherein the first insulating layer comprises an organic material and a black pigment.
5. The light emitting device of claim 1, further comprising a third thin film layer formed on the second thin film layer.
6. The light emitting device of claim 1, wherein the common electrode comprises a transparent conductive material.

7. The light emitting device of claim 1, wherein a light emitted from the light emitting layer is configured to go toward the touch sensor.
8. The light emitting device of claim 7, wherein the touch sensor comprises a first touch conductor on the organic layer.
9. The light emitting device of claim 8, wherein the touch sensor further comprises a second touch conductor on the organic layer.
10. The light emitting device of claim 9, further comprising a second insulating layer on the organic layer.
11. The light emitting device of claim 9, wherein the first touch conductor and the second touch conductor form a capacitor.
12. The light emitting device of claim 8, wherein the substrate comprises a pixel area where a plurality of pixels capable of displaying an image are disposed, and wherein the light emitting device further comprises a first sensing signal line and a second sensing signal line formed on the organic layer in a sectional view and outside the pixel area in the plan view.
13. The light emitting device of claim 12, wherein each of the first sensing signal line and the second sensing signal line comprises: a first portion extending in a first direction along an edge of the substrate; a second portion curved from the first portion and extending in a second direction perpendicular to the first direction; and a third portion curved from the second portion and extending in the first direction.
14. The light emitting device of claim 13, wherein the first sensing signal line or the second sensing signal line is configured to transmit a frequency signal to the first touch conductor.
15. The light emitting device of claim 14, wherein the first and second sensing signal lines comprise aluminum.
16. The light emitting device of claim 12, further comprising a processor electrically connected to the first and second sensing signal lines.
17. The light emitting device of claim 12, wherein the first and second sensing signal lines directly contact a first surface of the organic layer.
18. An electronic device comprising: a display panel; a driver connected to the display panel; a sensing signal processor connected to the display panel; and a touch determining unit connected to the sensing signal processor, wherein the display panel comprises: a substrate; a thin film transistor on a surface of the substrate; a pixel electrode electrically connected to the thin film transistor; a first insulating layer defining an opening on the pixel electrode; a light emitting layer comprising a portion disposed in the opening; a common electrode on the light emitting layer and the first insulating layer; a first thin film layer formed on the common electrode; a second thin film layer formed on the first thin film layer; an organic layer formed on the second thin film layer; and a touch sensor formed on the organic layer without any adhesive layer for adhering between the touch sensor and the organic layer, wherein the second thin film layer comprises a first portion overlapping the opening and a second portion overlapping the first insulating layer outside the opening and adjacent to the first portion in a plan view, and wherein a first distance between an upper surface of the first portion and the surface of the substrate is less than a second distance between an upper surface of the second portion and the surface of the substrate.
19. The electronic device of claim 18, wherein a light emitted from the light emitting layer is configured to go toward the touch sensor.
20. The electronic device of claim 19, wherein the touch sensor comprises a first touch conductor on the organic layer.
21. The electronic device of claim 20, wherein the substrate comprises a pixel area where a plurality of pixels capable of displaying an image are disposed, and wherein the display panel further comprises a first sensing signal line and a second sensing signal line formed on the organic layer in a sectional view and outside the pixel area in the plan view.

22. The electronic device of claim 21, wherein the sensing signal processor is electrically connected to the first sensing signal line and the second sensing signal line.

---